



(12) **United States Patent**
Zhang et al.

(10) **Patent No.:** **US 11,112,651 B1**
(45) **Date of Patent:** **Sep. 7, 2021**

(54) **LIQUID CRYSTAL DISPLAY DEVICE**

(71) Applicant: **SHENZHEN CHINA STAR OPTOELECTRONICS SEMICONDUCTOR DISPLAY TECHNOLOGY CO., LTD.**, Shenzhen (CN)

(72) Inventors: **Xin Zhang**, Shenzhen (CN); **Hu Dou**, Shenzhen (CN); **Chunchi Chen**, Shenzhen (CN)

(73) Assignee: **SHENZHEN CHINA STAR OPTOELECTRONICS SEMICONDUCTOR DISPLAY TECHNOLOGY CO., LTD.**, Shenzhen (CN)

(*) Notice: Subject to any disclaimer, the term of this patent is extended or adjusted under 35 U.S.C. 154(b) by 0 days.

(21) Appl. No.: **16/976,438**

(22) PCT Filed: **May 11, 2020**

(86) PCT No.: **PCT/CN2020/089636**

§ 371 (c)(1),

(2) Date: **Aug. 27, 2020**

(30) **Foreign Application Priority Data**

Apr. 14, 2020 (CN) 202010288846.5

(51) **Int. Cl.**
G02F 1/1335 (2006.01)
G02F 1/13357 (2006.01)

(52) **U.S. Cl.**
CPC .. **G02F 1/133606** (2013.01); **G02F 1/133607** (2021.01)

(58) **Field of Classification Search**

None

See application file for complete search history.

(56) **References Cited**

U.S. PATENT DOCUMENTS

2008/0284715 A1* 11/2008 Kawata G02F 1/1336 345/102

2019/0331945 A1* 10/2019 Fang G02F 1/1336

FOREIGN PATENT DOCUMENTS

CN	1748179 A	3/2006
CN	101430455 A	5/2009
CN	103185982 A	7/2013
CN	105116586 A	12/2015
CN	107636517 A	1/2018
JP	H0815677 A	1/1996

* cited by examiner


Primary Examiner — James A Dudek

(74) *Attorney, Agent, or Firm* — PV IP PC; Wei Te Chung; Ude Lu

(57) **ABSTRACT**

A liquid crystal display device provided by the present invention includes a backlight source, a light path modulation box and a liquid crystal display panel. The light path modulation box is disposed on the backlight source. The light path modulation box is configured to modulate light emitted out from the backlight source such that backlight is emitted out along a direction perpendicular to the light path modulation box. The liquid crystal display panel is disposed on the light path modulation box. The backlight emitted by the backlight source passes through the light path modulation box and enters the liquid crystal display panel.

6 Claims, 3 Drawing Sheets






FIG. 1




FIG. 2




FIG. 3




FIG. 4




FIG. 5




FIG. 6

LIQUID CRYSTAL DISPLAY DEVICE**RELATED APPLICATIONS**

This application is a National Phase of PCT Patent Application No. PCT/CN2020/089636 having international filing date of May 11, 2020, which claims the benefit of priority of Chinese Patent Application No. 202010288846.5 filed on Apr. 14, 2020. The contents of the above applications are all incorporated by reference as if fully set forth herein in their entirety.

FIELD OF INVENTION

The present invention relates to a field of displays, specifically relates to a liquid crystal display device.

BACKGROUND OF INVENTION

A liquid crystal display device is an active matrix liquid crystal display driven by thin film transistors, and it generates points, lines, and surfaces with a back lamp to form images mainly by using current to excite liquid crystal molecules. Therefore, the conventional liquid crystal display device is generally a passive light emitting device, and has no self-luminescence characteristics and must acquire a display capability depending on light emission of a light source in the backlight module. Thus, a brightness of the LCD is determined by the backlight module thereof.

However, when the liquid crystal display device uses the backlight module to acquire a display performance, because light of the liquid crystal display panel emitted from the backlight module into the liquid crystal display device is not fully perpendicularly incident, a certain brightness crosstalk phenomenon occurs.

Therefore, solving an issue of a brightness crosstalk phenomenon existing in the conventional liquid crystal display device is a hardship that the display panel manufacturers in the world are trying hard to overcome.

SUMMARY OF INVENTION**Technical Issue**

The present invention provides a liquid crystal display device that can solve a technical issue of a brightness crosstalk phenomenon existing in the conventional liquid crystal display device.

Technical Solution

The present invention provides a liquid crystal display device, comprising:

a backlight source;

a light path modulation box, disposed on the backlight source, wherein the light path modulation box is configured to modulate backlight emitted by the backlight source such that the backlight is emitted out along a direction perpendicular to the light path modulation box, the light path modulation box comprises a first substrate, a second substrate, and a liquid crystal layer disposed between the first substrate and the second substrate, wherein the first substrate comprises a first base, a pixel electrode layer disposed on the first base, and a dielectric layer disposed on the pixel electrode layer, and the second substrate comprises a second base and a common electrode layer disposed on the second base; and

a liquid crystal display panel, disposed on the light path modulation box, wherein the backlight emitted by the backlight source enters the liquid crystal display panel through the light path modulation box, and two polarizers are disposed respectively on a surface of the light path modulation box near the liquid crystal display panel and a surface of the light path modulation box near the backlight source.

In the liquid crystal display device provided by the present invention, the liquid crystal layer comprises a plurality of liquid crystal molecules, and the liquid crystal molecules are arranged in an array.

In the liquid crystal display device provided by the present invention, a refractive index of the dielectric layer is greater than a normal refractive index of the liquid crystal molecules, and the refractive index of the dielectric layer is equal to an abnormal refractive index of the liquid crystal molecules.

In the liquid crystal display device provided by the present invention, a thickness of the liquid crystal layer is greater than or equal to a thickness of the dielectric layer.

In the liquid crystal display device provided by the present invention, the pixel electrode layer comprises a plurality of pixel electrodes disposed at intervals, a gap is defined between adjacent two of the pixel electrodes, and the dielectric layer forms a curved structure in the gap.

In the liquid crystal display device provided by the present invention, the dielectric layer comprises a plurality of dielectric blocks, the pixel electrodes correspond to the dielectric blocks, and each of the pixel electrodes is disposed one of the dielectric blocks; and

in adjacent two of the dielectric blocks, both the two dielectric blocks extend into the gap to form the curved structures.

In the liquid crystal display device provided by the present invention, the curved structure comprises a first portion and a second portion disposed opposite to each other, and both the first portion and the second portion are curved.

In the liquid crystal display device provided by the present invention, the liquid crystal display device comprises a normal display status and a abnormal modulation status;

when the liquid crystal display device is in the normal display status, a longitudinal axis of the liquid crystal molecules is parallel to a first direction, and the first direction is a direction parallel to a boundary line between the liquid crystal layer and the second substrate; and

when the liquid crystal display device is in the abnormal modulation status, the longitudinal axis of the liquid crystal molecules is parallel to a second direction, the second direction is a direction perpendicular to the boundary line between the liquid crystal layer and the second substrate.

The present invention provides a liquid crystal display device, comprising:

a backlight source;

a light path modulation box, disposed on the backlight source, wherein the light path modulation box is configured to modulate backlight emitted by the backlight source such that the backlight is emitted out along a direction perpendicular to the light path modulation box; and

a liquid crystal display panel, disposed on the light path modulation box, wherein the backlight emitted by the backlight source enters the liquid crystal display panel through the light path modulation box.

In the liquid crystal display device provided by the present invention, the light path modulation box comprises

3

a first substrate, a second substrate, and a liquid crystal layer disposed between the first substrate and the second substrate; and

the first substrate comprises a first base, a pixel electrode layer disposed on the first base, and a dielectric layer disposed on the pixel electrode layer, and the second substrate comprises a second base and a common electrode layer disposed on the second base.

In the liquid crystal display device provided by the present invention, the liquid crystal layer comprises a plurality of liquid crystal molecules, and the liquid crystal molecules are arranged in an array.

In the liquid crystal display device provided by the present invention, a refractive index of the dielectric layer is greater than a normal refractive index of the liquid crystal molecules, and the refractive index of the dielectric layer is equal to an abnormal refractive index of the liquid crystal molecules.

In the liquid crystal display device provided by the present invention, a thickness of the liquid crystal layer is greater than or equal to a thickness of the dielectric layer.

In the liquid crystal display device provided by the present invention, the pixel electrode layer comprises a plurality of pixel electrodes disposed at intervals, a gap is defined between adjacent two of the pixel electrodes, and the dielectric layer forms a curved structure in the gap.

In the liquid crystal display device provided by the present invention, the dielectric layer comprises a plurality of dielectric blocks, the pixel electrodes correspond to the dielectric blocks, and each of the pixel electrodes is disposed one of the dielectric blocks; and

in adjacent two of the dielectric blocks, both the two dielectric blocks extend into the gap to form the curved structures.

In the liquid crystal display device provided by the present invention, the curved structure comprises a first portion and a second portion disposed opposite to each other, and both the first portion and the second portion are curved.

In the liquid crystal display device provided by the present invention, the liquid crystal display device comprises a normal display status and an abnormal modulation status;

when the liquid crystal display device is in the normal display status, a longitudinal axis of the liquid crystal molecules is parallel to a first direction, and the first direction is a direction parallel to a boundary line between the liquid crystal layer and the second substrate; and

when the liquid crystal display device is in the abnormal modulation status, the longitudinal axis of the liquid crystal molecules is parallel to a second direction, the second direction is a direction perpendicular to the boundary line between the liquid crystal layer and the second substrate.

In the liquid crystal display device provided by the present invention, two polarizers are disposed respectively on a surface of the light path modulation box near the liquid crystal display panel and a surface of the light path modulation box near the backlight source.

Advantages

In the liquid crystal display device provided by the present invention, by disposing the light path modulation box between the backlight source and the liquid crystal display panel to modulate light emitted from the backlight source to the liquid crystal display panel so that the obliquely emitted light from the backlight source enters the liquid crystal display panel along a direction perpendicular

4

to the liquid crystal display panel, solves the technical issue of the brightness crosstalk phenomenon existing in the conventional liquid crystal display device.

DESCRIPTION OF DRAWINGS

To more clearly elaborate on the technical solutions of embodiments of the present invention or prior art, appended figures necessary for describing the embodiments of the present invention or prior art will be briefly introduced as follows. Apparently, the following appended figures are merely some embodiments of the present invention. A person of ordinary skill in the art may acquire other figures according to the appended figures without any creative effort.

FIG. 1 is a schematic structural view of a liquid crystal display device provided by an embodiment of the present invention.

FIG. 2 is a schematic structural view of a light path modulation box provided by the embodiment of the present invention.

FIG. 3 is a schematic structural view of a first substrate provided by the embodiment of the present invention.

FIG. 4 is another schematic structural view of the first substrate provided by the embodiment of the present invention.

FIG. 5 is another schematic structural view of a light path modulation box provided by the embodiment of the present invention.

FIG. 6 is another schematic structural view of a liquid crystal display device provided by the embodiment of the present invention.

DETAILED DESCRIPTION OF PREFERRED EMBODIMENTS

The technical solution in the embodiment of the present invention will be clearly and completely described below with reference to the accompanying drawings in the embodiments of the present invention. Apparently, the described embodiments are merely some embodiments of the present invention instead of all embodiments. According to the embodiments in the present invention, all other embodiments obtained by those skilled in the art without making any creative effort shall fall within the protection scope of the present invention.

With reference to FIG. 1, FIG. 1 is a schematic structural view of a liquid crystal display device provided by the embodiment of the present invention. As shown in FIG. 1, the liquid crystal display device provided by the embodiment of the present invention comprises: a backlight source **101**, a light path modulation box **102**, and a liquid crystal display panel **103**. The light path modulation box **102** is disposed on the backlight source **101**. The liquid crystal display panel **103** is disposed on the light path modulation box **102**. The light path modulation box **102** is configured to modulate backlight emitted from the backlight source **101** such that the backlight is emitted out from a direction perpendicular to the light path modulation box **102**. Furthermore, the backlight emitted out from the backlight source **101** enters the liquid crystal display panel **103** through the light path modulation box **102**.

It can be understood that light emitted from the backlight source **101** has not only light emitted along a direction perpendicular to the light path modulation box **102** but also light emitted along an oblique direction. Such obliquely emitted light would be entirely blocked by a polarizer, and

5

therefore a brightness crosstalk phenomenon occurs on the liquid crystal display panel **103**. After addition of the light path modulation box **102**, the light emitted from the backlight source **101** is modulated by the light path modulation box **102** before entering the liquid crystal display panel **103** such that the light emitted from the backlight source **101** is emitted out along the direction perpendicular to the light path modulation box **102**. As such the polarizer can block the light not required to enter the liquid crystal display panel **103**, which reduces occurrence of the brightness crosstalk phenomenon and improves the display effect of the liquid crystal display panel **103**.

Specifically, with reference to FIG. 2, FIG. 2 is a schematic structural view of a light path modulation box provided by the embodiment of the present invention. The light path modulation box **102** provided by the present invention comprises: a first substrate **1021**, a second substrate **1022**, and a liquid crystal layer **1023** disposed on the first substrate **1021** and the second substrate **1022**. The first substrate **1021** comprises a first base **1024**, a pixel electrode layer **1025** disposed on the first base **1024**, and a dielectric layer **1026** disposed on the pixel electrode layer **1025**. The second substrate **1022** comprises a second base **1027** and a common electrode layer **1028** disposed on the second base **1027**.

In an embodiment, the liquid crystal layer **1023** comprises a plurality of liquid crystal molecules, and the liquid crystal molecules are arranged in an array. The liquid crystal molecules optionally employs nematic liquid crystal or blue-phase liquid crystal. When the nematic liquid crystal is selected, positive or negative liquid crystal is used.

In an embodiment, a refractive index of the dielectric layer **1026** is greater than a normal refractive index of the liquid crystal molecules, and the refractive index of the dielectric layer **1026** is equal to an abnormal refractive index of the liquid crystal molecules. The liquid crystal molecules have two refractive indexes, which is the so-called anisotropy of dielectric medium in the electric field. However, in the optical field, it is so-called birefringence. The two refractive indexes owned by the liquid crystal molecules are the normal refractive index and abnormal refractive index respectively. The normal refractive index refers to a refractive index along a short direction of the liquid crystal molecules, and the abnormal refractive index refers to a refractive index along a longitudinal axis direction of the liquid crystal molecules. The abnormal refractive index of the liquid crystal molecules is greater the normal refractive index of the liquid crystal molecules.

In an embodiment, a thickness of the liquid crystal layer **1023** is greater than or equal to a thickness of the dielectric layer **1026**. Because the liquid crystal layer **1023** is required to flatten the dielectric layer **1026**, the thickness of the liquid crystal layer **1023** is required to greater than the thickness of the dielectric layer **1026**.

Specifically, with reference to FIG. 3, FIG. 3 is a schematic structural view of a first substrate provided by the embodiment of the present invention, wherein the pixel electrode layer **1025** comprises a plurality of pixel electrodes **10251** disposed at intervals, and a gap is defined adjacent two of the pixel electrodes **10251**. The dielectric layer **1026** forms a curved structure **1029** in the gap. The curved structure **1029** comprises a first portion **10291** and a second portion **10292** disposed opposite to each other, and both the first portion **10291** and the second portion **10292** are curved.

In an embodiment, the dielectric layer **1026** is coated and formed on an entire surface of the pixel electrode layer **1025**

6

after formation of the pixel electrode layer **1025**, and forms the curved structure **1029** in the gap.

It can be understood that the curved structure **1029** formed by the dielectric layer **1026** is determined by the light emitted out from the backlight source **101**. An oblique angle of light emitted out from the backlight source **101** becomes greater from an inside to an outside, and therefore the oblique angle of the light emitted out from the dielectric layer **1026** is curved such that, all light emitted out from the backlight source **101** at the oblique angle is modulated as possible to be emitted out along the direction perpendicular to the light path modulation box **102**.

Furthermore, with references to FIGS. 3 and 4, FIG. 4 is another schematic structural view of the first substrate provided by the embodiment of the present invention. A difference between the first substrate shown in FIG. 4 from the first substrate shown in FIG. 3 is that the dielectric layer **1026** comprises a plurality of dielectric blocks **10261**, the pixel electrodes **10251** correspond to the dielectric blocks **10261**, and the dielectric blocks **10261** are disposed on the pixel electrodes **10251** respectively.

It can be understood that the dielectric blocks **10261** are arranged regularly, and the dielectric blocks **10261** are coated respectively on the pixel electrodes **10251** after the formation of the pixel electrodes **10251**. One of the dielectric blocks **10261** is disposed on each of the pixel electrodes **10251**. In adjacent two of the dielectric blocks **10261**, both the two dielectric blocks **10261** extend into the gap to form the curved structures to modulate the light emitted out from the backlight source **101** at the oblique angle as possible to be emitted out the direction perpendicular to the light path modulation box **102**.

Furthermore, with reference to FIGS. 2 and 5, FIG. 5 is another schematic structural view of a light path modulation box provided by the embodiment of the present invention. A difference of the light path modulation box shown in FIG. 5 from the light path modulation box shown in FIG. 2 is the different directions of the longitudinal axes of the liquid crystal molecules in the liquid crystal layers **1023**. In FIG. 2, the longitudinal axis of the liquid crystal molecules is parallel to a first direction, and the first direction is a direction parallel to a boundary line between the liquid crystal layer **1023** and the second substrate **1022**. In FIG. 5, the longitudinal axis of the liquid crystal molecules is parallel to a second direction, and the second direction is a direction perpendicular to the boundary line between the liquid crystal layer **1023** and the second substrate **1022**.

It can be understood that the liquid crystal display device has an abnormal modulation status and a normal display status. When the liquid crystal display device light path modulation box is in the normal display status, the longitudinal axis of the liquid crystal molecules is parallel to the first direction, the first direction is a direction parallel to the boundary line between the liquid crystal layer **1023** and the dielectric layer **1025**, and the refractive index of the dielectric layer **1025** is equal to the abnormal refractive index of the liquid crystal molecules. Therefore, when the light emitted out from the backlight source **101** enters the liquid crystal layer **1023** the through the dielectric layer **1025**, the light is transmitted like transmission in the same medium. Thus, the light emitted out from the backlight source **101** has no change to the light path after passing through the light path modulation box **102**. When the liquid crystal display device is in the abnormal modulation status, the light path of the light emitted out from the backlight source **101** requires modulation. In the meantime the longitudinal axis of the liquid crystal molecules is parallel to the second direction,

the second direction is a direction perpendicular to the boundary line between the liquid crystal layer **1023** and the dielectric layer **1025**, and the refractive index of the dielectric layer **1025** is greater than the normal refractive index of the liquid crystal molecules. Therefore, when the light emitted out from the backlight source **101** enters the liquid crystal layer **1023** through the dielectric layer **1025**, the light is transmitted from an optically dense medium to an optically sparse medium, and the light obliquely emitted out from the backlight source **101** is emitted outward along the direction perpendicular to the light path modulation box **102**, which achieves reduction of light crosstalk phenomenon.

Specific steps for mitigating brightness crosstalk provided by the liquid crystal display device provided by the embodiment of the present invention are that the liquid crystal display device provides vertical alternating current to the pixel electrode layer **1025** and the common electrode layer **1028** such that a constant voltage difference exists between the pixel electrodes in the pixel electrode layer **1025** and the common electrodes in the common electrode layer **1028** to generate an electrical field. The liquid crystal molecules in the liquid crystal layer **1023** deflect under the effect of the electrical field, the direction of the longitudinal axis of the liquid crystal molecules deflects from the first direction to the second direction, the first direction is a direction parallel to the boundary line between the liquid crystal layer **1023** and the second substrate **1022**; in the meantime, the light obliquely emitted out from the backlight source **101** passes through the light path modulation box **102**, and is emitted out toward the liquid crystal display panel **103** along a direction perpendicular to the light path modulation box **102** to solve the brightness crosstalk phenomenon of the liquid crystal display device.

Furthermore, with reference to FIGS. **1** and **6**, FIG. **6** is another schematic structural view of a liquid crystal display device provided by the embodiment of the present invention. A difference of the liquid crystal display device shown in FIG. **6** from the liquid crystal display device shown in FIG. **1** is that two polarizers **104** are disposed respectively on a surface of a side of the light path modulation box **102** near the liquid crystal display panel **103** and a surface of a side of the light path modulation box **102** near the backlight source **101**.

It can be understood that the polarizer **104** is configured to block light emitted from the backlight source **101** when the liquid crystal display device is in a status of dark display effect.

In the liquid crystal display device provided by the present invention, by disposing the light path modulation box between the backlight source and the liquid crystal display panel to modulate light emitted from the backlight source to the liquid crystal display panel so that the obliquely emitted light from the backlight source enters the liquid crystal display panel along a direction perpendicular to the liquid crystal display panel, solves the technical issue of the brightness crosstalk phenomenon existing in the conventional liquid crystal display device.

The embodiments of the present invention are described above. In the specification, the specific examples are used to explain the principle and embodiment of the present invention. The above description of the embodiments is only used to help understand the method of the present invention and its spiritual idea. Meanwhile, for those skilled in the art, according to the present the idea of invention, changes will

be made in specific embodiment and application. In summary, the contents of this specification should not be construed as limiting the present invention.

What is claimed is:

1. A liquid crystal display device, comprising:
a backlight source;

a light path modulation box, disposed on the backlight source, wherein the light path modulation box is configured to modulate backlight emitted by the backlight source such that the backlight is emitted out along a direction perpendicular to the light path modulation box, the light path modulation box comprises a first substrate, a second substrate, and a liquid crystal layer disposed between the first substrate and the second substrate, wherein the first substrate comprises a first base, a pixel electrode layer disposed on the first base, and a dielectric layer disposed on the pixel electrode layer, and the second substrate comprises a second base and a common electrode layer disposed on the second base; and

a liquid crystal display panel, disposed on the light path modulation box, wherein the backlight emitted by the backlight source enters the liquid crystal display panel through the light path modulation box, and two polarizers are disposed respectively on a surface of the light path modulation box near the liquid crystal display panel and a surface of the light path modulation box near the backlight source;

wherein the pixel electrode layer comprises a plurality of pixel electrodes disposed at intervals, a gap is defined between adjacent two of the pixel electrodes, and the dielectric layer forms a curved structure in the gap;

wherein the curved structure comprises a first portion and a second portion disposed symmetrically opposite to each other in the gap, and both the first portion and the second portion are curved and are substantially quarter-circular in shape.

2. The liquid crystal display device as claimed in claim 1, wherein the liquid crystal layer comprises a plurality of liquid crystal molecules, and the liquid crystal molecules are arranged in an array.

3. The liquid crystal display device as claimed in claim 2, wherein a refractive index of the dielectric layer is greater than a normal refractive index of the liquid crystal molecules, and the refractive index of the dielectric layer is equal to an abnormal refractive index of the liquid crystal molecules.

4. The liquid crystal display device as claimed in claim 1, wherein a thickness of the liquid crystal layer is greater than or equal to a thickness of the dielectric layer.

5. The liquid crystal display device as claimed in claim 1, wherein

the dielectric layer comprises a plurality of dielectric blocks, the pixel electrodes correspond to the dielectric blocks, and each of the pixel electrodes is disposed in one of the dielectric blocks; and

in adjacent two of the dielectric blocks, both the two dielectric blocks extend into the gap to form the curved structures.

6. The liquid crystal display device as claimed in claim 2, wherein

the liquid crystal display device comprises a normal display status and an abnormal modulation status;

when the liquid crystal display device is in the normal display status, a longitudinal axis of the liquid crystal molecules is parallel to a first direction, and the first

direction is a direction parallel to a boundary line between the liquid crystal layer and the second substrate; and

when the liquid crystal display device is in the abnormal modulation status, the longitudinal axis of the liquid crystal molecules is parallel to a second direction, the second direction is a direction perpendicular to the boundary line between the liquid crystal layer and the second substrate.

* * * * *