



US00RE48690E

(19) **United States**
(12) **Reissued Patent**
Park et al.

(10) **Patent Number:** **US RE48,690 E**
(45) **Date of Reissued Patent:** **Aug. 17, 2021**

(54) **LIGHT UNIT AND A LCD LIQUID CRYSTAL DISPLAY COMPRISING THE LIGHT UNIT**

(56) **References Cited**

U.S. PATENT DOCUMENTS

(71) Applicant: **LG INNOTEK CO., LTD.**, Seoul (KR)

4,989,933 A * 2/1991 Duguay G02B 5/0242
359/599

(72) Inventors: **Kwang Ho Park**, Seoul (KR); **Woo Young Chang**, Seoul (KR); **Chul Hong Kim**, Seoul (KR); **Byoung Eon Lee**, Seoul (KR)

5,956,107 A 9/1999 Hashimoto et al.
(Continued)

FOREIGN PATENT DOCUMENTS

(73) Assignee: **LG INNOTEK CO., LTD.**, Seoul (KR)

JP H05-341131 A 12/1993
JP 2004-311353 A 11/2004

(21) Appl. No.: **16/440,343**

(Continued)

(22) Filed: **Jun. 13, 2019**

OTHER PUBLICATIONS

Related U.S. Patent Documents

Reissue of:

(64) Patent No.: **9,678,382**
Issued: **Jun. 13, 2017**
Appl. No.: **14/343,721**
PCT Filed: **Sep. 9, 2011**
PCT No.: **PCT/KR2011/006739**
§ 371 (c)(1),
(2) Date: **Mar. 7, 2014**
PCT Pub. No.: **WO2013/035909**
PCT Pub. Date: **Mar. 14, 2013**

European Search Report dated Nov. 19, 2019 in European Application No. 19190305.3.

(Continued)

Primary Examiner — James A Menefee

(74) *Attorney, Agent, or Firm* — Saliwanchik, Lloyd & Eisenschenk

(51) **Int. Cl.**
G02F 1/1335 (2006.01)
F21V 8/00 (2006.01)
G02F 1/13357 (2006.01)

(52) **U.S. Cl.**
CPC **G02F 1/133603** (2013.01); **G02B 6/0021** (2013.01); **G02B 6/0041** (2013.01); **G02B 6/0051** (2013.01); **G02B 6/0055** (2013.01)


(58) **Field of Classification Search**
CPC G02F 1/1336; G02F 1/133603; G02F 1/133606; G02F 1/133611;

(57) **ABSTRACT**

Provided is a light unit including a plurality of LED light sources formed on a PCB, a resin layer stacked on the PCB to diffuse and guide emitted light forwards, and a diffusion plate having an optical pattern printed thereon to shield light emitted from the LED light sources. The optical pattern is composed of a diffusion pattern implemented as at least one layer, or a combination of the diffusion pattern layer and a light shielding pattern. The light unit forms an optical pattern for shielding or diffusing light on a surface of a light diffusion plate of the back-light unit, and combines a diffusion pattern and a metal pattern to attain uniformity of light and realize a yellow-light shielding effect, thus leading to a reliable light quality.

(Continued)

20 Claims, 5 Drawing Sheets



(58) **Field of Classification Search**

CPC G02F 1/133615; G02B 6/0001; G02B
6/0055; G02B 6/0051; G02B 6/0021

See application file for complete search history.

(56) **References Cited**

U.S. PATENT DOCUMENTS

8,355,093	B2	1/2013	Shin et al.	
8,675,149	B2	3/2014	Jung et al.	
8,858,025	B2 *	10/2014	Park	F21V 7/22 362/248
9,303,844	B2 *	4/2016	Kim	F21V 5/008
9,482,889	B2 *	11/2016	Choe	G02F 1/133603
9,627,595	B2 *	4/2017	Park	H01L 25/0753
9,664,844	B2 *	5/2017	Park	F21S 43/195
9,939,677	B2 *	4/2018	Hur	G02F 1/133605
9,970,604	B2 *	5/2018	Yang	G02B 6/0016
2006/0181901	A1 *	8/2006	Sakai	G02B 6/0096 362/613
2009/0066878	A1 *	3/2009	Ogiro	G02F 1/133611 349/62
2009/0079908	A1	3/2009	Miyazaki et al.	
2009/0231264	A1	9/2009	Hatakeyama et al.	
2010/0046202	A1 *	2/2010	Joo	G02B 5/0215 362/97.1
2011/0051411	A1 *	3/2011	Kim	G02F 1/133603 362/235
2011/0051412	A1 *	3/2011	Jeong	G02F 1/133603 362/235
2011/0205758	A1	8/2011	Kim et al.	
2011/0228193	A1 *	9/2011	Shin	F21V 11/00 349/61
2011/0242796	A1 *	10/2011	Yang	C09J 11/02 362/97.1
2011/0249215	A1 *	10/2011	Jung	G02F 1/133611 349/61
2011/0261290	A1 *	10/2011	Kim	G02B 6/0021 349/64
2012/0014092	A1 *	1/2012	Lee	G02B 6/0021 362/97.1
2012/0250350	A1 *	10/2012	Kim	G02F 1/133606 362/606
2014/0048779	A1 *	2/2014	Lee	H01L 51/52 257/40

FOREIGN PATENT DOCUMENTS

JP	2007-141546	A	6/2007
JP	2008-053069	A	3/2008
JP	2008-268707	A	11/2008
JP	2009-244861	A	10/2009
JP	2010-040236	A	2/2010
JP	4461197	B1	5/2010
KR	10-2003-0081975	A	10/2003
KR	10-2006-0031518	A	4/2006
KR	10-2007-0109555	A	11/2007
KR	10-2009-0001104	A	1/2009
KR	10-2011-0032476	A	3/2011
KR	10-2011-0068833		6/2011
KR	10-2011-0104398		9/2011
KR	10-2011-0104401		9/2011
WO	WO-2011/025174	A2	3/2011
WO	WO-2011/025175	A2	3/2011
WO	WO-2011/033901	A1	3/2011
WO	WO-2011/056026	A2	5/2011
WO	WO-2011/115343	A1	9/2011
WO	WO-2011/129561	A2	10/2011

OTHER PUBLICATIONS

Office Action dated May 30, 2011 in Korean Application No. 10-2010-0023518.
Office Action dated Jul. 18, 2011 in Korean Application No. 10-2010-0023520.
Office Action dated Mar. 12, 2014 in Japanese Application No. 2014-529597.
Supplementary European Search Report dated May 27, 2015 in European Application No. 11872142.2.
Office Action dated Jan. 4, 2016 issued in U.S. Appl. No. 14/343,721.
Final Office Action dated Oct. 3, 2016 issued in U.S. Appl. No. 14/343,721.
Notice of Allowance dated Feb. 10, 2017 issued in U.S. Appl. No. 14/343,721.
Office Action dated May 22, 2014 in Taiwanese Application No. 100132837.
Office Action dated Dec. 9, 2014 in Japanese Application No. 2014-529597.
Extended European Search Report dated May 27, 2015 in European Application No. 11872142.2.
International Search Report in International Application No. PCT/KR2011/006739, filed Sep. 9, 2011.

* cited by examiner




FIG. 1

PRIOR ART




FIG. 2




FIG. 3




FIG. 4




FIG. 5




FIG. 6




FIG. 7




FIG. 8




FIG. 9

1

LIGHT UNIT AND A LCD LIQUID CRYSTAL DISPLAY COMPRISING THE LIGHT UNIT

Matter enclosed in heavy brackets [] appears in the original patent but forms no part of this reissue specification; matter printed in italics indicates the additions made by reissue; a claim printed with strikethrough indicates that the claim was canceled, disclaimed, or held invalid by a prior post-patent action or proceeding.

CROSS-REFERENCE TO RELATED APPLICATIONS

[This application is the U.S. national stage application of International Patent Application No. PCT/KR2011/006739, filed Sep. 9, 2011, the disclosure of which is incorporated herein by reference in its entirety.] *The present application is a reissue application of U.S. patent application Ser. No. 14/343,721, filed Mar. 7, 2014, now U.S. Pat. No. 9,678,382, issued Jun. 13, 2017, which is the U.S. national stage application of International Patent Application No. PCT/KR2011/006739, filed Sep. 9, 2011, the disclosure of each of which is hereby incorporated herein by reference in its entirety.*

TECHNICAL FIELD

The present invention relates to a light unit eliminating a light guide plate and having a diffusion plate on which an optical pattern for increasing light shielding and haze effects is formed.

BACKGROUND ART

In general, a liquid crystal display (LCD) is a device that individually supplies a data signal based on image information to pixels arranged in a matrix array and adjusts optical transmittance of the pixels to form a desired image. Since LCD cannot emit light by itself, a light unit is mounted to a rear of the LCD to produce an image.

Referring to FIG. 1, such a light unit 1 is configured so that a flat light guide plate 30 is placed on a substrate 20 and a plurality of side view LEDs 10 (only one of them is shown) is placed at a side of a light guide plate 30 in an array form.

Light L transmitted from the LED 10 to the light guide plate 30 is reflected upwards by a fine reflection pattern or a reflection sheet 40 formed on a lower surface of the light guide plate 30, exits from the light guide plate 30, and thereafter supplies back light to a LCD panel 50 located above the light guide plate 30.

As shown in the conceptual view of FIG. 2, the light unit may further include a plurality of optical sheets, including a diffusion sheet 31, prism sheets 32 and 33, and a protection sheet 34, between the light guide plate 30 and the LCD panel 50.

Such a light unit functions to uniformly illuminate the LCD, which cannot emit light by itself, from the back thereof to allow a display image to be seen. The light guide plate functions to provide uniform luminance and illumination to the light unit and is a kind of plastic molded lens uniformly delivering light from a light source (LED) to an entire surface of the LCD. Thus, such a light guide plate is basically used as an essential part of the back-light unit. However, the conventional light unit is problematic in that it is difficult to achieve thinness of an entire product because

2

of the thickness of the light guide plate, and an image quality may be deteriorated in the case of a large-area back-light unit.

Further, the light diffusion plate or the diffusion sheet 31 of the conventional light unit for diffusing light has a shielding pattern to prevent light from being concentrated. Such a shielding pattern implements a light shielding effect using Ag. However, the optical pattern using Ag for obtaining the light shielding effect has a drawback in that a portion having the pattern is completely optically shielded, so that it is difficult to attain uniformity of light through an entire portion, and reliability of the light unit emitting white light is lowered because of yellow light emitted from the light source, the LED.

DISCLOSURE OF INVENTION

Technical Problem

An aspect of the present invention is directed to a light unit which forms an optical pattern for shielding or diffusing light on a surface of a light diffusion plate of the back-light unit, and combines a diffusion pattern and a metal pattern to attain uniformity of light and realize a yellow-light shielding effect, thus leading to a reliable light quality.

Another aspect of the present invention is directed to a light unit which eliminates a light guide plate essential for a general light unit and forms a light-source guide structure using a film-type resin layer, thus reducing the number of light sources, achieving thinness of the entire back-light unit, and enhancing the degree of freedom when designing a product.

Solution to Problem

According to an embodiment of the present invention, there is provided a light unit including a plurality of LED light sources formed on a PCB formed by stacking reflection films; a resin layer stacked on the PCB to diffuse and guide emitted light forwards; and a diffusion plate having an optical pattern printed thereon to shield light emitted from the LED light sources. The light unit may further include a surface treatment layer formed to receive the optical pattern between the resin layer and the light diffusion plate.

According to another embodiment of the present invention, the optical pattern may be formed on a surface of the diffusion plate, and may comprise a diffusion pattern implemented as at least one layer, or a combination of the diffusion pattern layer and a light shielding pattern.

Advantageous Effects of Invention

The present invention is advantageous in that an optical pattern is formed on a surface of a light diffusion plate of a light unit to shield or diffuse light, and combines a diffusion pattern and a metal pattern to attain uniformity of light and shield yellow light, thus resulting in a reliable light quality.

Particularly, the present invention is advantageous in that a light guide plate essential for a general light unit is eliminated, and a light-source guide structure is formed using a film-type resin layer, thus reducing the number of light sources, achieving thinness of the back-light unit, and enhancing the degree of freedom when designing a product.

Further, a side view LED is installed in a direct type to remarkably reduce the number of light sources and attain optical characteristics, and a light guide plate is eliminated to allow the light unit to be applied to a flexible display

structure, and a resin layer is provided with a reflection film having a reflection pattern and a light diffusion plate having a shielding pattern to achieve stable emission properties.

BRIEF DESCRIPTION OF DRAWINGS

The above and other aspects, features and advantages of certain exemplary embodiments of the present invention will be more apparent from the following description taken in conjunction with the accompanying drawings, in which:

FIGS. 1 and 2 are conceptual views showing a configuration of a conventional back-light unit;

FIGS. 3 and 4 are conceptual views showing important parts of light unit in accordance with the present invention;

FIG. 5 is a plan view showing an arrangement of LEDs and optical patterns of a diffusion plate in accordance with the present invention;

FIG. 6 is a view illustrating optical patterns in accordance with the present invention;

FIGS. 7a to 7c are views illustrating an embodiment of manufacturing optical patterns in accordance with the present invention;

FIG. 8 is a view illustrating a reflection pattern in accordance with the present invention; and

FIG. 9 is a view illustrating a configuration and operation of the light unit in accordance with the present invention.

REFERENCE NUMERALS

- 110: PCB
- 111: LED light source
- 120: reflection film
- 130: reflection pattern
- 140: resin layer
- 150: diffusion plate
- 151: optical pattern
- 151a: diffusion pattern
- 151b: shielding pattern
- 152: surface treatment layer
- 160: prism sheet

BEST MODE FOR CARRYING OUT THE INVENTION

Exemplary embodiments of the present invention will be described below in detail with reference to the accompanying drawings. Wherever possible, the same reference numerals will be used to refer to the same elements throughout the specification, and a duplicated description thereof will be omitted. It will be understood that although the terms "first", "second", etc. are used herein to describe various elements, these elements should not be limited by these terms. These terms are only used to distinguish one element from another element.

The present invention is directed to a back-light unit, which forms a diffusion plate having an optical pattern layer for efficiently shielding or diffusing light, thus enhancing optical efficiency, and eliminates a light guide plate from a conventional light unit and forms a resin layer in place of the light guide plate, thus remarkably reducing an entire thickness of the back-light unit, and can reduce the number of light sources. Particularly, the present invention is directed to a light unit having a surface treatment layer, which is capable of removing an air layer due to a step of an optical pattern when a diffusion plate and a resin layer are coupled to each other.

Mode for the Invention

FIGS. 3 and 4 show a configuration of a light unit according to the present invention. The light unit of the present invention includes a plurality of LED light sources 111 that are formed on a PCB 110, and a resin layer 140 that is stacked on the LED light sources 111 to diffuse and guide emitted light forwards. Of course, in this case, a reflection film 120 is stacked on an upper surface of the PCB, a diffusion plate 150 is provided above the resin layer 140, and a prism sheet 160 and a protection sheet 170 are additionally provided above the diffusion plate 150.

Particularly, in the above-mentioned configuration, a surface treatment layer 152 is preferably provided between the resin layer 140 and an optical pattern 151 formed on a surface of the diffusion plate 150 to flatten unevenness of the optical pattern.

Preferably, the surface treatment layer 152 is formed as a flattened layer for covering an entire step of the optical pattern 151 so as to eliminate a difference between a dark space and a bright space due to an air layer caused by the step when the optical pattern 151 of the diffusion plate adheres to the resin layer 140 disposed thereunder. Thus, as shown in the drawings, it is preferable that a height of the surface treatment layer be equal to or higher than that of the optical pattern. It is more preferable that the surface treatment layer 152 be basically made of the same material as the resin layer 140 so as to improve adhesive properties.

As shown in the drawings, at least one LED light source 111 is placed on the PCB 110 to emit light. According to a preferred embodiment of the present invention, a side view LED may be used. That is, it is possible to use a light source that is configured so that light emitted from the LED light source 111 does not travel straight upwards but travels towards a side surface. Further, the LED light source may be disposed in a direct type using the side view LED. Thereby, the entire thickness of the light unit can be remarkably reduced while reducing the number of light sources using the resin layer for diffusing and reflecting light.

The resin layer 140 is stacked to surround the LED light source 111, thus dispersing light emitted laterally from the light source. That is, the resin layer 140 may perform the function of the conventional light guide plate. Any material may be applied to the resin layer, as long as the material is resin capable of diffusing light. The resin layer according to an embodiment of the present invention may comprise resin that uses urethane acrylate oligomer as a main material. For example, a mixture of urethane acrylate oligomer that is synthetic oligomer and polyacryl that is a polymer type may be used. Of course, this mixture may further contain a reactive dilution monomer with a low boiling point, such as isobornyl acrylate (IBOA) and Hydroxypropyl acrylate (HPA), 2-hydroxyethyl acrylate (2-HEA), and may contain a photo initiator (e.g. 1-hydroxycyclohexyl phenyl-ketone) or antioxidant as an additive.

In this case, as shown in FIG. 3, the resin layer 140 includes beads 141 to increase the diffusion and reflection of light. It is preferable that the beads be 0.01 to 0.3 wt % of the total composition of the resin layer. That is, light emitted laterally from the LED is diffused and reflected by the resin layer 140 and the beads 141 so as to travel upwards. Further, the reflection film 120 and a reflection pattern 130, which will be described below in detail, can promote a reflecting function. The resin layer remarkably reduces a thickness occupied by the conventional light guide plate, thus achieving the thinness of an entire product, and includes a flexible

5

material, thus having universality to allow the light unit to be applied to a flexible display.

More preferably, the reflection film **120** is made of a reflective material to disperse light emitted from the light source, and is provided with the reflection pattern **130** through white printing so as to promote the dispersion of light. The reflection pattern may be printed using reflective ink containing any one of TiO_2 and Al_2O_3 .

The diffusion plate **150** functions to diffuse light that is emitted through the resin layer **140**, and preferably has an optical pattern **151** to partially shield light, thus preventing yellow light from being emitted or preventing optical characteristics from being deteriorated when the intensity of light is excessively strong. That is, a shielding pattern may be printed using light shielding ink so as to prevent light from being concentrated.

Further, the optical pattern **151** formed a lower surface of the diffusion plate is treated by the surface treatment layer **152** to prevent a dark space from occurring due to the air layer when the optical pattern is printed and to improve adhesive strength between the diffusion plate **150** and the resin layer **140**. Particularly, to this end, the surface treatment layer **152** may be made of the same material as the resin layer.

FIG. **5** is a conceptual view showing a configuration wherein the diffusion plate **150** covers an upper portion of each LED light source **111**, and particularly shows a positional relation between the light source and the optical pattern **151**. The optical pattern **151** may be basically printed on the lower or upper surface of the diffusion plate **150**. More preferably, the optical pattern is located in a direction (front direction) where light is emitted from the LED light source **111** placed under the diffusion plate. That is, the optical pattern may be formed on the diffusion plate at a position corresponding to a light emitting direction or a vertical upper surface of the LED light source.

The optical pattern **151** according to the present invention may be formed on the lower surface of the diffusion plate in a light emitting direction by overlapping printing a diffusion pattern and a shielding pattern as a single layer or a multiple layer. Here, the diffusion pattern is formed using light shielding ink that contains at least one substance selected from a group consisting of TiO_2 , CaCO_3 , BaSO_4 , Al_2O_3 , and Silicon. The shielding pattern is formed using light shielding ink that contains Al or a mixture of Al and TiO_2 .

FIG. **6** illustrates an example of forming an optical pattern according to the present invention.

The example of forming the optical pattern will be described with reference to the drawing. The optical pattern **151** may be implemented on the lower surface of the diffusion plate in the light emitting direction by overlapping printing a diffusion pattern **151a** and a shielding pattern **151b**. The diffusion pattern **151a** is formed using light shielding ink containing at least one substance selected from a group consisting of TiO_2 , CaCO_3 , BaSO_4 , Al_2O_3 , and Silicon. The shielding pattern **151b** is formed using light shielding ink containing Al or a mixture of Al and TiO_2 . That is, after the diffusion pattern **151a** is formed on the surface of the diffusion plate by white printing, the shielding pattern **151b** is formed on the diffusion pattern **151a**. Alternatively, such a double structure may be formed in a reverse order. It is obvious that a design having such a pattern may be variously changed in consideration of efficiency and intensity of light and a light shielding ratio.

Further, as a subsequent stacked structure, the shielding pattern **151b** that is a metal pattern may be formed as an intermediate layer, and the diffusion patterns **151a** may be

6

formed, respectively, on upper and lower portions of the shielding pattern **151b** to provide a triple structure. Such a triple structure may be implemented using the above substances. As a preferred embodiment, one of the diffusion patterns may be formed using TiO_2 having a high refractive index, the other diffusion pattern may be formed using both CaCO_3 and TiO_2 having good light stability and color sense, and the shielding pattern may be formed using Al having a high shielding ability, thus providing a triple structure. Such a structure can provide efficiency and uniformity of light. Particularly, CaCO_3 reduces the exposure of yellow light to finally implement white light, thus achieving more stable light efficiency. In addition to CaCO_3 , it is possible to use inorganic material, such as BaSO_4 , Al_2O_3 , or Silicon bead, having a large particle size and a similar structure. The optical pattern is preferably formed so that a pattern density is reduced as a distance from the emitting direction of the LED light source increases, which is advantageous in terms of light efficiency.

A process of forming the optical pattern will be described below with reference to FIGS. **7a** to **7c**.

As shown in the drawings, the optical pattern according to the present invention may be printed on the upper or lower surface of the diffusion plate **150**. As shown in FIG. **7a**, the optical pattern may be implemented by single tone printing to form one pattern layer (first pattern; **151a**). As shown in FIG. **7b**, the optical pattern may be implemented by overlapping printing a second pattern **151b** on the first pattern **151a**. Further, as shown in FIG. **7c**, the optical pattern may be implemented as a triple structure by printing the first and second patterns and subsequently overlapping printing a third pattern on the printed first and second patterns. The overlapping printing structure means a structure obtained by forming one pattern and printing another pattern on the previously formed pattern.

As shown in FIG. **7a**, when the optical pattern is formed on a surface of the diffusion plate **150** by single tone printing, the printing is preferably performed using light shielding ink containing TiO_2 to achieve excellent light shielding effect and diffusion effect. In this case, the light shielding ink may use a resin substance, for example, a mixture of resin such as acryl polyol, hydrocarbon- or ester-based solvent, and inorganic pigment such as TiO_2 . Particularly, an additive such as a silicone-type wetting and dispersing agent or a defoamer/levelling agent may be added to the above substance.

Further, the inorganic pigment may use TiO_2 or TiO_2 and one or more substances selected from a group consisting of CaCO_3 , BaSO_4 , Al_2O_3 and Silicon.

The inorganic pigment may use a particle size of 500 to 550 nm. According to one experimental example, the light shielding ink may contain 20 to 25% acryl polyol resin, 20 to 29% solvent, 50 to 55% inorganic pigment, and 1 to 2% additive.

Next, at the step shown in FIG. **7b**, another optical pattern according to the present invention may be formed in a double structure by overlapping printing the diffusion pattern (first pattern) that achieves light diffusing or shielding effect and the shielding pattern (second pattern) that achieves light shielding effect. That is, after the first pattern is printed as shown in FIG. **7a**, the second pattern may be formed on the first pattern by the light shielding ink containing a metal-based substance. The second pattern may be printed using light shielding ink containing Al or a mixture of Al and TiO_2 . Of course, in this case, the first and second patterns may be stacked in a different order.

7

The second pattern is characterized in that it contains metal-based pigment. For example, light shielding ink containing the metal-based pigment may use a substance produced by mixing resin such as acryl polyol, hydrocarbon- or ester-based solvent, metal-based pigment, and an additive such as a wetting and dispersing agent, a defoamer or a levelling agent. The substance may have the following composition, for example, 36 to 40% acryl polyol resin, 33 to 40% solvent, 20 to 25% inorganic pigment, and 1 to 2% additive. Further, the solvent may be produced by mixing 10 to 15% hydrocarbon-based solvent that has a low boiling point and 23 to 25% ester-based solvent. The second pattern that is the metal pattern can basically achieve light shielding effect.

In the case of forming the stacked structure having two patterns, the diffusion pattern and the shielding pattern as in this embodiment, the first pattern, namely, the diffusion pattern may be formed using light shielding ink containing one or more substances selected from a group consisting of CaCO_3 , BaSO_4 , Al_2O_3 and Silicon.

Further, at the step shown in FIG. 7c, the optical pattern according to the present invention may be formed in a triple structure by overlapping printing.

That is, the intermediate layer of the optical pattern may be implemented as the shielding pattern layer having the metal pattern, and the diffusion patterns may be formed on upper and lower surfaces of the intermediate layer.

As described above, the shielding pattern (second pattern) that is the metal pattern is formed using light shielding ink containing Al or a mixture of Al and TiO_2 , and the diffusion pattern described at the step of FIG. 7a or 7b is formed on the upper or lower portion of the shielding pattern.

For example, the first and third patterns that are the outermost pattern comprises diffusion patterns, and are formed as the light shielding ink layer containing TiO_2 or one or more substances selected from a group consisting of CaCO_3 , BaSO_4 , Al_2O_3 , and Silicon, or formed as the light shielding ink layer containing a mixture of TiO_2 and any one of CaCO_3 , BaSO_4 , Al_2O_3 , and Silicon. Further, each of the patterns (first, second, and third patterns) forming the optical pattern may have a thickness from 4 to 100 μm .

FIG. 8 is a plan view showing a configuration of the reflection film and the reflection pattern in accordance with the present invention.

Referring to FIG. 8, the reflection film 120 according to the present invention is stacked on the PCB, and the LED light source 111 protrudes to an outside through a hole formed on the reflection film 120. When the LED light source is implemented as the side view LED structure, the number of light sources may be considerably reduced as described above. In order to cope with the reduction, the reflection pattern 130 is preferably formed to considerably improve reflectivity of light.

As in the example shown in the drawing, the reflection pattern is preferably formed in a light emitting direction of the LED light source. Particularly, the optical pattern is formed so that a pattern density is increased as a distance from the emitting direction of the LED light source increases. In a detailed description, a second area 132 distant from the light emitting direction has a higher pattern density in comparison with a first area 131 near to the light emitting direction so as to increase reflectivity. Of course, the pattern may be implemented in various shapes according to design intention. Further, the reflection pattern may be formed by a printing method using reflective ink containing any one of TiO_2 and Al_2O_3 .

8

FIG. 9 is a view showing an operation of the light unit according to the present invention. The operation of the light unit will be described with reference to FIG. 3 illustrating the basic configuration and FIG. 9 illustrating the operation.

As shown in the drawings, the light unit according to the present invention is operated so that light is laterally emitted from the side view LED 111 and the emitted light is reflected and diffused by the resin layer 140 formed in place of the conventional light guide plate. Here, the reflection efficiency of the light is further enhanced by the reflection film 120 and the reflection pattern 130 to allow light to be guided forwards.

The light passing through the resin layer 140 as such is diffused or shielded by the optical pattern 151 formed on the diffusion plate 150. The light L purified as such passes through an optical sheet such as the prism sheet 160, and is incident into an LCD panel as white light. More preferably, the surface treatment layer 152 is provided on the optical pattern 151 to improve adhesiveness between the optical pattern 151 and the resin layer 140 and eliminate the air layer during adhesion, thus eliminating a dark space and improving reliability.

As such, the light unit according to the present invention eliminates the light guide plate, applies the side view LED to a light supply source, and guides light by diffusing and reflecting light through the resin layer, thus achieving thinness and reducing the number of light sources. Further, reduction in luminance and uniformity due to reduction of the number of light sources may be compensated for by the optical pattern such as the reflection pattern, the shielding pattern, or the diffusion pattern, thus realizing a uniform image quality.

Further, a step of the optical pattern occurring when the resin layer is attached to the diffusion plate may reduce adhesive strength and form the air layer, thus producing a dark space. In this case, in order to eliminate the dark space, the surface treatment layer is added. Thereby, a reliable light unit is obtained, which can be applied to an LCD.

While the invention has been shown and described with reference to exemplary embodiments thereof, it will be understood by those skilled in the art that various changes in form and details may be made therein without departing from the spirit and scope of the invention as defined by the appended claims. Therefore, the scope of the invention is defined not by the detailed description of the invention but by the appended claims, and all differences within the scope will be construed as being included in the present invention.

The invention claimed is:

1. A light unit, comprising:

- a printed circuit board (PCB) which extends in a horizontal direction;
 - a plurality of LED light sources formed on the PCB;
 - a resin layer on the PCB and surrounding the LED light sources, the resin layer being configured to diffuse and guide light emitted from the LED light sources;
 - a diffusion plate on the resin layer; and
 - an optical pattern disposed between the diffusion plate and the resin layer,
- wherein the optical pattern is disposed on a lower surface of the diffusion plate and comprises a first pattern on a lower surface of the diffusion plate, a second pattern on a lower surface of the first pattern, and a third pattern on a lower surface of the second pattern,
- [wherein the first pattern is a diffusion pattern, wherein the second pattern is a shielding pattern.]

wherein [the shielding pattern] *at least one of the first pattern, the second pattern, and the third pattern* is configured to shield light emitted from the LED light sources, [and

wherein the optical pattern is implemented by overlapping printing the shielding pattern onto the diffusion pattern in a vertical direction]

wherein a vertical direction is perpendicular to the lower surface of the diffusion plate,

wherein an imaginary plane, taken in the vertical direction and including an outer lateral surface of the second pattern, also includes a portion of the first pattern and a portion of the third pattern,

wherein an area of the first pattern is larger than an area of the second pattern,

wherein the optical pattern includes a first region, a second region, and a third region from the imaginary plane toward a light emitting direction of each of the LED light sources,

wherein the first region is closest to the imaginary plane, the third region is farthest from the imaginary plane, and the second region is disposed between the first region and the third region, and

wherein the first region is formed of three layers, the second region is formed of two layers, and the third region is formed of one layer in the optical pattern.

2. The light unit of claim 1, wherein the optical pattern is [disposed on a] *in direct physical contact with the lower surface of the diffusion plate.*

[3. The light unit of claim 1, wherein the diffusion pattern comprises at least one substance selected from the group consisting of TiO_2 , CaCO_3 , BaSO_4 , Al_2O_3 , and silicon.]

4. The light unit of claim 1, wherein the second pattern is [disposed on a portion of] *in direct physical contact with the first pattern. [and]*

wherein the first pattern is [disposed on] *in direct physical contact with the lower surface of the diffusion plate.*

5. The light unit of claim 1, wherein the [a] second pattern is [formed by overlapping printing on an upper or lower portion of] *in direct physical contact with the first pattern, [thereby shielding or reflecting the emitted light; and]*

wherein the [optical pattern further comprises a] third pattern [comprising a diffusion] *is in direct physical contact with the second pattern, and*

wherein the [third] first pattern is [disposed between the first pattern and the second pattern] *in direct physical contact with the lower surface of the diffusion plate.*

[6. The light unit of claim 1, wherein the diffusion pattern comprises a substance containing TiO_2 or a substance containing TiO_2 and CaCO_3 .]

7. The light unit of claim 1, wherein the first pattern has a thickness *in a range of* from $4\text{ }\mu\text{m}$ to $100\text{ }\mu\text{m}$.

8. The light unit of claim 1, wherein the [shielding] optical pattern comprises light shielding ink containing Al or a mixture of Al and TiO_2 .

9. The light unit of claim 1, wherein *at least one of the first [or] pattern and the second pattern [further] comprises beads.*

10. The light unit of claim 1, wherein the second pattern has a thickness *in a range of* from $4\text{ }\mu\text{m}$ to $100\text{ }\mu\text{m}$.

[11. The light unit of claim 5, wherein the third pattern comprises a substance containing TiO_2 or a substance containing TiO_2 and CaCO_3 .]

12. The light unit of [claim 5] *claim 1*, wherein the third pattern has a thickness *in a range of* from $4\text{ }\mu\text{m}$ to $100\text{ }\mu\text{m}$.

13. The light unit of claim 1, [further] comprising a surface treatment layer [formed] *disposed* between the resin layer and the diffusion plate and configured to receive the optical pattern, wherein a thickness of the surface treatment layer is equal to or greater than a thickness of the optical pattern.

[14. The light unit of claim 13, wherein the surface treatment layer comprises the same material as the resin layer.]

15. The light unit of claim 1, [further] comprising: a reflection film on the PCB and having at least one reflection pattern formed thereon.

[16. The light unit of claim 15, wherein the reflection pattern comprises reflective ink containing TiO_2 or Al_2O_3 .]

17. The light unit of claim 1, wherein the resin layer [further] comprises beads.

[18. A liquid crystal display comprising a light unit according to claim 1.]

19. The light unit of claim 13, wherein the optical pattern is buried in the surface treatment layer.

20. *The light unit of claim 1, wherein the optical pattern is spaced apart from the resin layer.*

21. *The light unit of claim 20, comprising a surface treatment layer disposed between the resin layer and the diffusion plate and configured to receive the optical pattern, wherein a thickness of the surface treatment layer is equal to or greater than a thickness of the optical pattern, and wherein the optical pattern is buried in the surface treatment layer.*

22. *The light unit of claim 1, wherein each of the LED light sources comprises a front surface from which light is emitted and a rear surface opposite to the front surface.*

23. *The light unit of claim 22, wherein at least one of the first pattern, the second pattern, and the third pattern is disposed so as not to overlap in the vertical direction with the rear surface of each of the LED light sources.*

24. *The light unit of claim 22, wherein the area of the first pattern, the area of the second pattern, and an area of the third pattern are all different from each other, and wherein the second pattern is disposed so as not to overlap in the vertical direction with the rear surface of each of the LED light sources.*

25. *The light unit of claim 1, wherein an area of the lower surface of the first pattern is larger than an area of the lower surface of the second pattern,*

wherein an entire upper surface of the second pattern is disposed within a region of the lower surface of the first pattern,

wherein an entire lower surface of the second pattern is positioned lower than the entire lower surface of the first pattern, and

wherein an entire lower surface of the third pattern is positioned lower than the entire lower surface of the second pattern.

26. *The light unit of claim 25, wherein the first pattern, the second pattern, and the third pattern of the optical pattern are formed of a material that is non-metallic, inorganic, or both.*