



(11)

EP 2 320 264 A1

(12)

EUROPEAN PATENT APPLICATION

(43) Date of publication:
11.05.2011 Bulletin 2011/19

(51) Int Cl.:
G02F 1/13 (2006.01)

(21) Application number: **10181718.7**

(22) Date of filing: **23.05.2000**

(84) Designated Contracting States:
DE FR GB

(30) Priority: **01.10.1999 KR 19990042216**

(62) Document number(s) of the earlier application(s) in
accordance with Art. 76 EPC:
00110292.0 / 1 091 238

(71) Applicant: **SAMSUNG ELECTRONICS CO., LTD.**
Suwon-si,
Gyeonggi-do (KR)

(72) Inventors:
• **Song, Jang-Kun**
Seoul (KR)

• **Ryu, Jae-Jin**
Kyungki-do (KR)

(74) Representative: **Modiano, Micaela Nadia**
Modiano & Partners
Thierschstrasse 11
80538 München (DE)


Remarks:

This application was filed on 29-09-2010 as a
divisional application to the application mentioned
under INID code 62.

(54) **Liquid crystal display**

(57) A liquid crystal display includes a first insulating substrate having a top surface and a bottom surface. A pixel electrode is formed on the top surface of the first insulating substrate, the pixel electrode having a first opening pattern. A second insulating substrate has a top surface and a bottom surface. A common electrode is formed on the bottom surface of the second insulating substrate, the common electrode having a second opening pattern. A liquid crystal layer is sandwiched between the first substrate and the second substrate. The first opening pattern and the second opening pattern each have a middle, first and second opening, the openings being alternately arranged except where a trunk opening of the middle opening of the second opening pattern overlaps the middle opening of the first opening pattern. The trunk opening is a portion of the middle opening and of the second opening pattern.

FIG. 19



Description

BACKGROUND OF THE INVENTION

(a) Field of the Invention

[0001] The present invention relates to a liquid crystal display and, more particularly, to a liquid crystal display in which a predetermined opening pattern is formed at pixel and common electrodes such that a wide viewing angle is obtained.

(b) Description of the Related Art

[0002] Generally, liquid crystal displays have a structure in which liquid crystal material is sandwiched between two substrates, and an electric field is applied to the liquid crystal material to control the alignment of molecules of the liquid crystal material, ultimately controlling the transmittance of incident light. In VA liquid crystal displays, the liquid crystal molecules are aligned normal to the substrates when an electric field is not applied. In case two polarizer films are arranged with their lines (a plurality of which is formed in parallel on each polarizer film) perpendicular to each other, the linearly polarized light passed through the first polarizer film is completely blocked by the second polarizer film in the absence of an electric field. As such a liquid crystal display exhibits a very low brightness in an "off" state of the normally black mode, a relatively higher contrast ratio than that of the conventional TN liquid crystal display can be obtained.

[0003] However, the liquid crystal molecules are irregularly inclined with respect to the substrate in the presence of an electric field such that one or more areas develop where the direction of the long axis of some of the liquid crystal molecules conforms to the polarizing direction of the first or second polarizer film. In such areas, the liquid crystal molecules cannot induce the rotation of the polarizing direction, i.e., polarization, and the light is completely blocked by the polarizer film. Such areas appear as black portions on the screen which cause a reduction in picture quality. These areas are referred to as areas of "texture".

[0004] In order to solve the above problem, several electrode-patterning techniques have been suggested. However, the problem of a slow response speed remains in the resulting LCD.

[0005] Fig. 1 illustrates a schematic view of opening patterns formed at pixel and common electrodes in a prior art liquid crystal display. As shown in Fig. 1, the pixel and common electrodes are formed with opening patterns 1 and 2, respectively. Each of the opening patterns 1 and 2 is formed in a V-shape and is arranged with ends of the V-shapes in proximity to one another so that roughly a diamond shape is formed by the opening patterns 1 and 2. Liquid crystal material is injected between the pixel and common electrodes, and liquid crystal molecules 3

are aligned perpendicular to the electrodes.

[0006] When an electric field is applied to the liquid crystal material, the liquid crystal molecules 3 come to be arranged parallel to the electrodes. However, the response speed of the liquid crystal molecules 3 with respect to the applied electric field is very slow with the formation of the opening patterns 1 and 2 at the pixel and common electrodes. That is, as a result of a fringe field formed due to the opening patterns 1 and 2, the liquid crystal molecules 3 are first arranged perpendicular to the opening patterns 1 and 2 (A state), then aligned to be parallel thereto (B state) due to the inherent tendency of long axes of liquid crystal molecules to align themselves roughly parallel. Because of these two alignment steps, a slow response speed results.

[0007] The slow response speed of liquid crystal molecules causes afterimages when displaying moving pictures on the screen. There is therefore a need to increase the response speed of liquid crystal molecules.

SUMMARY OF THE INVENTION

[0008] It is an object of the present invention to provide a liquid crystal display which has an improved response speed and a wide viewing angle.

[0009] It is another object of the present invention to provide a liquid crystal display which produces improved picture images. These and other objects may be achieved by a liquid crystal display having a first insulating substrate with top and bottom surfaces. A pixel electrode is formed on the top surface of the first insulating substrate. The pixel electrode has a first opening pattern at each pixel area. The pixel electrode with the first opening pattern is substantially rectangular in shape and having first and second long sides, and first and second short sides. The pixel electrode is divided into an upper region defined by the first and second long sides and the first short side, and a lower region defined by the first and second long sides and the second short side. A second insulating substrate with top and bottom surfaces is arranged parallel to the first insulating substrate at a predetermined distance from the same such that the bottom surface of the second insulating substrate faces the top surface of the first insulating substrate. A common electrode is formed on the bottom surface of the second insulating substrate. The common electrode has a second opening pattern at each pixel area, which correspond to each pixel area of the pixel electrode. A liquid crystal layer is sandwiched between the first and second substrates while contacting the pixel and common electrodes.

[0010] The first and second opening patterns each have a plurality of openings, the openings of the first and second opening patterns being alternately arranged parallel to each other.

[0011] The first and second opening patterns each have a middle linear portion. The linear portions of the first and second opening patterns are alternately ar-

ranged parallel to each other. The first opening pattern includes a first opening formed in the upper region of the pixel electrode in a first direction. A second opening portion is formed in the lower region of the pixel electrode in a second direction normal to the first direction. The second opening pattern includes a first trunk opening formed in the upper region of the common electrode in the first direction, and a second trunk opening formed in the lower region of the common electrode in the second direction. The first direction is slanted at a predetermined angle with respect to the long or short sides of the pixel electrode. The second opening pattern further includes first branch openings overlapping the first and second short sides of the pixel electrode, and second branch openings overlapping the first and second long sides of the pixel electrode. The first opening pattern further includes a third opening formed where the upper and lower regions of the pixel electrode meet while proceeding parallel to the first and second short sides of the pixel electrode. The second branch openings each have a width greater than that of the trunk opening portion. The first direction is parallel to one of the long and short sides of the pixel electrode. The first and second trunk openings each have opposite ends each with a gradually enlarged width. One of the second trunk openings overlaps the second short side of the pixel electrode. The first opening has opposite ends each with a gradually reduced width.

[0012] The pixel and common electrodes are overlapped with each other such that the first and second opening patterns partition the pixel electrode into several micro-regions. The micro-regions of the pixel electrode are in the shape of polygons where the longest sides are parallel to each other. The micro-regions of the pixel electrode are classified into a first type where the longest sides are arranged in a first direction, and a second type where the longest sides are arranged in a second direction normal to the first direction. The first direction is slanted at a predetermined angle with respect to the long or short sides of the pixel electrode. Alternatively, the first direction may be parallel to one of the long and short sides of the pixel electrode.

[0013] The first and second opening patterns form fringe fields when voltage is applied between the pixel and common electrodes. The orienting direction of the liquid crystal molecules due to the fringe fields corresponds to that of the liquid crystal molecules as a result of a force exerted by the molecules. It is preferable that the liquid crystal molecules are oriented in four directions. The opening width of the first and second opening patterns is preferably in the range of 10-16 μm .

[0014] The pixel electrode may have protrusions at the sides adjacent to the ends of the first and second openings.

BRIEF DESCRIPTION OF THE DRAWINGS

[0015] A more complete appreciation of the invention, and many of the attendant advantages thereof, will be

readily apparent as the same becomes better understood by reference to the following detailed description when considered in conjunction with the accompanying drawings in which like reference symbols indicate the same or the similar components, wherein:

Fig. 1 is a schematic view of opening pattern units formed at common and pixel electrodes in a prior art liquid crystal display;

Fig. 2 is a schematic cross sectional view of a liquid crystal display according to a preferred embodiment of the present invention;

Fig. 3A is a schematic view of opening pattern units formed at common and pixel electrodes according to a first preferred embodiment of the present invention;

Fig. 3B is a schematic view of opening pattern units formed at common and pixel electrodes according to a second preferred embodiment of the present invention;

Fig. 4A is a schematic view of an opening pattern of a pixel electrode according to a third preferred embodiment of the present invention;

Fig. 4B is a schematic view of an opening pattern of a common electrode according to a third preferred embodiment of the present invention;

Fig. 4C is a schematic view of the opening patterns of the pixel and common electrodes shown respectively in Figs. 4A and 4B in an overlapped state;

Fig. 5A is a schematic view of an opening pattern of a pixel electrode according to a fourth preferred embodiment of the present invention;

Fig. 5B is a schematic view of an opening pattern of a common electrode according to a fourth preferred embodiment of the present invention;

Fig. 5C is a schematic view of the opening patterns of the pixel and common electrodes shown respectively in Figs. 5A and 5B in an overlapped state;

Fig. 6A is a schematic view of an opening pattern of a pixel electrode according to a fifth preferred embodiment of the present invention;

Fig. 6B is a schematic view of an opening pattern of a common electrode according to a fifth preferred embodiment of the present invention;

Fig. 6C is a schematic view of the opening patterns of the pixel and common electrodes shown respectively in Figs. 6A and 6B in an overlapped state;

Fig. 7A is a schematic view of an opening pattern of a pixel electrode according to a sixth preferred embodiment of the present invention;

Fig. 7B is a schematic view of an opening pattern of a common electrode according to a sixth preferred embodiment of the present invention;

Fig. 7C is a schematic view of the opening patterns of the pixel and common electrodes shown respectively in Figs. 7A and 7B in an overlapped state;

Fig. 8A is a schematic view of an opening pattern of a pixel electrode according to a seventh preferred

embodiment of the present invention;
 Fig. 8B is a schematic view of an opening pattern of a common electrode according to a seventh preferred embodiment of the present invention; ;
 Fig. 8C is a schematic view of the opening patterns of the pixel and common electrodes shown respectively in Figs. 8A and 8B in an overlapped state;
 Fig. 9A is a schematic view of an opening pattern of a pixel electrode according to an eighth preferred embodiment of the present invention;
 Fig. 9B is a schematic view of an opening pattern of a common electrode according to an eighth preferred embodiment of the present invention;
 Fig. 9C is a schematic view of the opening patterns of the pixel and common electrodes shown respectively in Figs. 9A and 9B in an overlapped state;
 Fig. 10A is a schematic view of an opening pattern of a pixel electrode according to a ninth preferred embodiment of the present invention;
 Fig. 10B is a schematic view of an opening pattern of a common electrode according to a ninth preferred embodiment of the present invention;
 Fig. 10C is a schematic view of the opening patterns of the pixel and common electrodes shown respectively in Figs. 10A and 10B in an overlapped state;
 Fig. 11 are schematic views of various types of opening patterns for demonstrating the affect of opening pattern width and spacing on response speed and brightness; Fig. 12A is a graph illustrating light transmissivity levels of test cells applying the opening patterns shown in Fig. 11;
 Fig. 12B is a graph comparing the light transmissivity level of a test cell applying a specific opening pattern shown in Fig. 11 to the light transmissivity levels of test cells applying the other opening patterns shown in Fig. 11;
 Fig. 13 is a graph illustrating response times as a function of gray scale of test cells applying the opening patterns shown in Fig. 11;
 Fig. 14 is a graph illustrating response times as a function of gray scale of actual panels applying specific opening patterns shown in Fig. 11;
 Figs. 15A to 15C are photographs of specific opening patterns shown in Fig. 11 at white gray scales;
 Figs. 16A and 16B are photographs of specific opening patterns shown in Fig. 11 used to illustrate a change in partitioned regions according to a level of an applied voltage; Figs. 17A and 17B are schematic views used to illustrate the change in intensity of a fringe field according to variations in opening pattern width;
 Figs. 18A to 18D are schematic views illustrating orientation states of liquid crystal molecules at a peripheral portion of opening patterns;
 Figs. 19 and 20 are schematic views of areas where texture occurs in specific opening patterns shown in Fig. 11; and Figs. 21A to 21C are schematic views of opening patterns where texture improvement

techniques have been applied.

DETAILED DESCRIPTION OF THE PREFERRED EMBODIMENTS

[0016] Preferred embodiments of this invention will be explained with reference to the accompanying drawings.

[0017] Fig. 2 is a schematic cross sectional view of a liquid crystal display according to a preferred embodiment of the present invention. As shown in Fig. 2, the liquid crystal display includes lower and upper substrates 10 and 20 arranged substantially in parallel with a predetermined gap therebetween. Liquid crystal material is injected between the lower and upper substrates 10 and 20 to form a liquid crystal layer, the liquid crystal material being comprised of liquid crystal molecules 30. A long axis of liquid crystal molecules 30 is oriented normal to the lower and upper substrates 10 and 20. Both the lower and upper substrates 10 and 20 are formed from a transparent material such as glass.

[0018] The lower substrate 10 is overlaid with a pixel electrode 12 that is connected to a switching element 11 to receive display signals. The pixel electrode 12 is formed from a transparent material such as indium tin oxide (ITO) or indium zinc oxide (IZO), and has an opening pattern (not shown). The switching element 11 is, for example, a thin film transistor, and is connected to a gate line (not shown), which transmits scanning signals, and a data line (not shown), which transmits picture signals. The switching element 11 turns the pixel electrode 12 on and off. A lower polarizer film 14 is adhered to an outer surface of the lower substrate 10. If the pixel electrode 12 is formed from non-transparent material as in the reflection-type liquid crystal display, the lower polarizer film 14 is not needed.

[0019] An inner surface of the upper substrate 20 is sequentially overlaid with a black matrix 21 for preventing the leakage of light, a color filter 22, and a common electrode 23. The common electrode 23 is formed of a transparent material such as ITO or IZO, and has an opening pattern (not shown). A polarizer film 24 is adhered to an outer surface of the upper substrate 20. Alternatively, the black matrix 21 or the color filter 22 may be formed on the lower substrate 10.

[0020] The LCD can be structured to operate in a normally black mode by arranging the lower and upper polarizer films 14 and 24 so that lines formed on the lower polarizer film 14 are perpendicular to lines formed on the upper polarizer film 24, or can be structured to operate in a normally white mode by arranging the lower and upper polarizer films 14 and 24 with their lines parallel to each other. In the following description, only the arrangement producing a normally black mode will be described. Fig. 3A shows a schematic view of opening patterns of the pixel and common electrodes 12 and 23 according to a first preferred embodiment of the present invention. As shown in Fig. 3A, opening patterns 101 and 102 respectively of the pixel and common electrodes 12 and

23 are each formed in a straight line, the opening pattern 101 being substantially parallel to the opening pattern 102. With this structure, the liquid crystal molecules 30 are arranged in parallel as a result of a fringe field generated by the opening patterns 101 and 102. Furthermore, the movement of the liquid crystal molecules 30 into the parallel arrangement is performed in a single step, thereby enabling a rapid response speed.

[0021] However, with the use of the above structure, texture develops over a wide area of the screen. It is also possible for white afterimages to be generated on the screen. The term "white afterimage" refers to a phenomenon in which a portion of the screen, where a dark color has been displayed on a bright background then returned to the color of the bright background, momentarily becomes brighter than the the bright background.

[0022] Fig. 3B shows a schematic view of opening patterns of the pixel and common electrodes 12 and 23 according to a second preferred embodiment of the present invention. As shown in Fig. 3B, opening patterns 111 and 112 respectively of the pixel and common electrodes 12 and 23 are each formed in a curved shape, with ends of the opening patterns 111 and 112 positioned in close proximity and centers bulging in opposite directions. However, with this structure, the movement of the liquid crystal molecules 30 cannot be completed in a single step, resulting in a slow response speed. In the following preferred embodiments, opening patterns of the pixel and common electrodes 12 and 23 will be described with reference to one pixel area. In a single pixel area, the pixel electrode 12 is substantially rectangular in shape having first and second long sides, respectively corresponding to left and right sides (in the drawings) of the pixel electrode 12; first and second short sides, respectively corresponding to top and bottom sides (in the drawings) of the pixel electrode 12; a first corner formed by ends of the first long side and the first short side; a second corner formed by ends of the first short side and the second long side; a third corner formed by ends of the second long side and the second short side; and a fourth corner formed by ends of the first long side and the second short side. Further, the pixel electrode 12 includes an upper region and a lower region, the upper region corresponding to an upper half (in the drawings) of the pixel electrode 12 and defined by the first long side, the second long side and the first short side, and the lower region corresponding to a lower half (in the drawings) of the pixel electrode 12 and defined by the first long side, the second long side and the second short side.

[0023] As the common electrode 23 is present over the entire surface of the upper substrate 20, a portion of the common electrode 23 roughly corresponding to the pixel electrode 12 in one pixel area will be described. Here, such portions of the common electrode 23 will be indicated by a dotted line and the identifying markers (i.e., upper region and lower region; first long side and second long side; first short side and second short side; and first, second, third and fourth corners) used for ease

of explanation of the pixel electrode 12 will also apply to these portions of the common electrode 23 defined by the dotted lines. Fig. 4A shows a schematic view of an opening pattern of the pixel electrode 12 according to a third preferred embodiment of the present invention. As shown in Fig. 4A, a middle opening 121 is formed inwardly from the first long side where the upper and lower regions of the pixel electrode 12 meet. The middle opening 121 extends a predetermined distance toward the second long side while being tapered. The first long side is cut at a predetermined angle on both sides of the middle opening 121 such that a wide inlet area of the middle opening 121 is formed. Upper and lower openings 122 and 123 are formed in the upper and lower regions of the pixel electrode 12, respectively, proceeding from the second long side at a predetermined angle respectively toward the first and fourth corners of the pixel electrode 12 in a symmetrical manner.

[0024] Fig. 4B shows a schematic view of an opening pattern of the common electrode 23 according to a third preferred embodiment of the present invention. As shown in Fig. 4B, the opening pattern of the common electrode 23 includes middle, upper and lower openings 210, 220 and 230 spaced apart from each at predetermined distances. The middle opening 210 includes a trunk 211 positioned where the upper and lower regions of the common electrode 23 meet and proceeding from the second long side a predetermined distance toward the first long side. First and second branches 212 and 214 are extended at a predetermined angle from the trunk 211 toward the first long side, and first and second sub-branches 213 and 215 extend along the first long side from the first and second branches 212 and 214, respectively, toward the first and second short sides, respectively. The upper opening 220, which is formed in the upper region of the common electrode 23, includes a first body 221 that is formed extended from the second long side to the first short side at a predetermined distance from the second corner and parallel to the first branch 212. A first upper limb 222 extends from an end of the first body 221 along the first short side and until reaching the first long side, and a first lower limb 223 extends from an opposite end of the first body 221 along the second long side toward the second short side. The lower opening 230 includes a second body 231, a second lower limb 232, and a second upper limb 233. The lower opening 230 is arranged in the lower region and is symmetrical to the upper opening 220.

[0025] Fig. 4C shows a schematic view of the opening patterns of the pixel and common electrodes 12 and 23 shown respectively in Figs. 4A and 4B in an overlapped state. As shown in Fig. 4C, the opening patterns of the pixel and common electrodes 12 and 23 divide the pixel electrode 12 into several regions. The openings 121, 122 and 123 of the pixel electrode 12 and the openings 210, 220 and 230 of the common electrode 23 are alternately arranged except where the trunk 211 of the middle opening 210 of the common electrode partially overlaps the

middle opening 121 of the pixel electrode 12.

[0026] In this preferred embodiment, the lower and upper polarizer films 14 and 24 are arranged such that their polarizing directions are respectively 0° and 90° (or vice versa) with respect to the first and second short sides of the pixel electrode 12. With such an arrangement, when the liquid crystal molecules 30 are rearranged under the application of an electric field, they are prevented from orienting in the polarizing direction of the polarizer films 14 and 24 so that the problem of texture does not occur. Furthermore, as the liquid crystal molecules 30 are fully oriented in parallel under the influence of the fringe field, the movement of the liquid crystal molecules 30 is completed in one step, resulting in a rapid response speed.

[0027] In addition, the opening portions of the pixel and common electrodes 12 and 23 are arranged generally in two directions normal to each other. Since the opening portions of the pixel and common electrodes 12 and 23 are alternately arranged, the fringe field is applied in four directions at one pixel area. Therefore, wide viewing angles can be obtained in all directions.

[0028] Fig. 5A shows a schematic view of an opening pattern of the pixel electrode 12 according to a fourth preferred embodiment of the present invention. As shown in Fig. 5A, the opening pattern of the pixel electrode 12 is a V-shaped opening 130. The V-shaped opening 130 has a vertex in proximity to the second long side and positioned where the upper region meets the lower region of the pixel electrode 12, and opens toward the first long side of the pixel electrode 12. That is, an upper half 131 of the opening 130 extends at a predetermined angle from the vertex of the opening 130 toward the first long side of the pixel electrode 12 such that the upper half 131 is positioned wholly in the upper region of the pixel electrode 12, and a lower half 132 of the opening 130 extends at a predetermined angle from the vertex of the opening 130 toward the first long side of the pixel electrode 12 such that the lower half 132 is positioned wholly in the lower region of the pixel electrode 12. Further, the second and third corners of the pixel electrode 12 are cut away to form a curved shape. Fig. 5B shows a schematic view of an opening pattern of the common electrode 23 according to a fourth preferred embodiment of the present invention. As shown in Fig. 5B, the opening pattern of the common electrode 23 includes a right opening 240 and a left opening 250. The right opening 240 includes a base 241 formed along and extending past the first long side of the common electrode 23, and which tapers from a middle portion along the first long side toward the first and second short sides. The base 241 of the right opening 240 also includes a projection 242 extending a predetermined distance from the base 241 toward the second long side and tapered in the same direction. A portion of the projection 242 adjacent to the base 241 is formed at a predetermined slant. The left opening 250 includes a body 251 formed along the second long side of the common electrode 23, an upper limb 252 extended at a predetermined angle from one end of the body 251 toward

and continuing past the first corner of the common electrode 23, and a lower limb 253 extended at a predetermined angle from the other end of the body 251 toward and continuing past the fourth corner of the common electrode 23. Centers of both the right and left openings 240 and 250 are positioned where the upper and lower regions of the common electrode 23 meet.

[0029] Fig. 5C shows a schematic view of the opening patterns of the pixel and common electrodes 12 and 23 shown respectively in Figs. 5A and 5B in an overlapped state. As shown in Fig. 5C, the opening patterns of the pixel and common electrodes 12 and 23 divide the pixel electrode 12 into several regions. The V-shaped opening 130 of the pixel electrode 12 is placed between the right and left openings 240 and 250 of the common electrode 23. The upper and lower parts 131 and 132 of the V-shaped opening 130 proceed in parallel to the lower and upper limbs 252 and 253 of the left opening 250, respectively, as well as to the portion of the projection 242 adjacent to the base 241 of the right opening portion 240. An end of the projection 242 overlaps the vertex of the V-shaped opening portion 130. With the configuration of the fourth preferred embodiment of the present invention as described above, the lower and upper polarizer films 14 and 24 are arranged such that their polarizing directions are the same as in the third preferred embodiment.

[0030] Fig. 6A shows a schematic view of an opening pattern of the pixel electrode 12 according to a fifth preferred embodiment of the present invention. As shown in Fig. 6A, the opening pattern of the pixel electrode 12 includes an upper opening 141 formed in the upper region of the pixel electrode 12, and a lower opening 142 formed in the lower region of the pixel electrode. If the pixel electrode 12 is divided into three areas of equal length, that is, first to third areas, with the first area having as its one side the first short side, the third area having as its one side the second short side, and the second area being formed between the first and third areas, the upper opening 141 is positioned where the first and second areas meet, and the lower opening 142 is positioned where the second and third areas meet. The upper opening 141 extends from the first long side to the second long side of the pixel electrode 12 in the horizontal direction, and areas of the pixel electrode 12 corresponding to where the upper opening 141 is positioned along the first long side are cut away to form a curved shape. Similarly, the lower opening 142 extends from the second long side to the first long side of the pixel electrode 12 in the horizontal direction, and areas of the pixel electrode 12 corresponding to where the lower opening 142 is positioned along the second long side are cut away to form a curved shape. In addition, second and third corners of the pixel electrode 12 are cut such that they are rounded. Fig. 6B shows a schematic view of an opening pattern of the common electrode 23 according to a fifth preferred embodiment of the present invention. As shown in Fig. 6B, the opening pattern of the common electrode 23 is a zigzag-shaped opening 260. The zigzag-shaped opening 260 includes

an upper part 261 proceeding from the first corner of the common electrode 23 at a predetermined slant toward and meeting the second long side of the common electrode 23, a middle part 262 extended at a predetermined slant from an end of the upper part 261 where the same meets the second long side toward and meeting the first long side of the common electrode 23, and a lower part 263 extended at a predetermined slant from an end of the middle part 262 where the same meets the first long side toward and meeting the third corner of the common electrode 23. If the common electrode 23 is divided into three areas of equal length, that is, first to third areas, with the first area having as its one side the first short side, the third area having as its one side the second short side, and the second area being formed between the first and third areas, the upper and middle parts 261 and 262 converge where the first and second areas meet, and the middle and lower parts 262 and 263 converge where the second and third areas meet.

[0032] Fig. 6C shows a schematic view of the opening patterns of the pixel and common electrodes 12 and 23 shown respectively in Figs. 6A and 6B in an overlapped state. As shown in Fig. 6C, the opening patterns of the pixel and common electrodes 12 and 23 divide the pixel electrode 12 into several regions. The portion where the upper and middle parts 261 and 262 of the opening 260 of the common electrode 23 meet overlaps an end of the upper opening portion 141 of the pixel electrode 12 adjacent to the second long side, and the portion where the middle and lower parts 262 and 263 of the opening 260 of the common electrode 23 meet overlaps an end of the lower opening portion 142 of the pixel electrode 12 adjacent to the first long side.

[0033] With the configuration of the fifth preferred embodiment of the present invention as described above, the lower and upper polarizer films 14 and 24 are arranged such that their polarizing directions are the same as in the third preferred embodiment. Fig. 7A shows a schematic view of an opening pattern of the pixel electrode 12 according to a sixth preferred embodiment of the present invention. As shown in Fig. 7A, the opening pattern of the pixel electrode 12 includes an upper opening 151 formed parallel to the first and second short sides in the upper region of the pixel electrode 12, and a lower opening 152 also formed parallel to the first and second short sides in the lower region of the pixel electrode 12. If the pixel electrode 12 is divided into three areas of equal length, that is, first to third areas, with the first area having as its one side the first short side, the third area having as its one side the second short side, and the second area being formed between the first and third areas, the upper opening 151 is positioned where the first and second areas meet, and the lower opening portion 152 positioned where the second and third areas meet. The upper and lower openings 151 and 152 extend from a position in proximity to the first long side to a position in proximity to the second long side. Fig. 7B shows a schematic view of an opening pattern of the common

electrode 23 according to a sixth preferred embodiment of the present invention. As shown in Fig. 7B, the opening pattern of the common electrode 23 includes first, second and third X-shaped openings 270, 280 and 290 spaced apart from each other at a predetermined distance along the length of the common electrode 23. A center area of each of the X-shaped openings 270, 280 or 290 is cut away to form an enlarged area approximately rectangular in shape. One line forming the "X" of the first X-shaped opening 270 extends from the first corner to the second long side of the common electrode 23 and its other line extends from the second corner to the first long side of the common electrode 23; one line forming the "X" of the second X-shaped opening 280 extends from the first long side to the second long side of the common electrode 23 and its other line extends from the second long side to the first long side of the common electrode 23; and one line forming the "X" of the third X-shaped opening 290 extends from the second long side to the fourth corner of the common electrode 23 and its other line extends from the first long side to the third corner of the common electrode 23.

[0034] Fig. 7C shows a schematic view of the opening patterns of the pixel and common electrodes 12 and 23 shown respectively in Figs. 7A and 7B in an overlapped state. As shown in Fig. 7C, the opening patterns of the pixel and common electrodes 12 and 23 are alternately arranged, and divide the pixel electrode 12 into several regions.

[0035] With the configuration of the sixth preferred embodiment of the present invention as described above, the lower and upper polarizer films 14 and 24 are arranged such that their polarizing directions are respectively 45° and 135° (or vice versa) with respect to the first and second short sides of the pixel electrode 12. Fig. 8A shows a schematic view of an opening pattern of the pixel electrode 12 according to a seventh preferred embodiment of the present invention. As shown in Fig. 8A, the opening pattern of the pixel electrode 12 includes an upper opening 160 formed in the upper region of the pixel electrode 12, and a lower opening 170 formed in the lower region of the pixel electrode 12. The upper opening 160 is T-shaped. That is, the upper opening 160 has a base 161 (the top of the "T") formed at a predetermined distance from where the upper and lower regions of the pixel electrode 12 meet, the base 161 extending from approximately the first long side to the second long side of the pixel electrode 12. The upper opening 160 also has a protrusion 162 extending substantially from a center of the base 161 in a direction toward the first short side of the pixel electrode 12, thereby bisecting the upper region of the pixel electrode 12 into left and right sub-areas. The lower opening 170 is formed parallel to the base 161 of the upper opening 160 and extends across the pixel electrode 12 approximately and at predetermined distances from the first long side to the second long side of the pixel electrode 12 such that the lower opening 170 bisects the lower region of the pixel electrode 12 into upper and lower

sub-areas. Fig. 8B shows a schematic view of an opening pattern of the common electrode 23 according to a seventh preferred embodiment of the present invention. As shown in Fig. 8B, the opening pattern of the common electrode 23 includes two upper openings 310 and 320, a middle opening 330, and a lower opening 340. The two upper openings 310 and 320 are spaced apart from each other at a predetermined distance in the upper region of the common electrode 23, and are parallel to each other and to the first and second long sides of the common electrode 23. The middle and lower openings 330 and 340 are spaced apart from each other at a predetermined distance in the lower region of the common electrode 23, and are parallel to each other and to the first and second short sides of the common electrode 23. Both end portions of the middle and lower openings 330 and 340 are enlarged in roughly a triangular shape, and the triangle-shaped end portions of the middle and lower opening portions 330 and 340 proceed over the first and second long sides of the common electrode 23.

[0036] Fig. 8C shows a schematic view of the opening patterns of the pixel and common electrodes 12 and 23 shown respectively in Figs. 8A and 8B in an overlapped state. As shown in Fig. 8C, the opening patterns of the pixel and common electrodes 12 and 23 divide the pixel electrode 12 into several regions. That is, ends of the upper opening portions 310 and 320 of the common electrode 23 farthest from the first short side of the common electrode 23 overlap the base 161 of the T-shaped opening 160 of the pixel electrode 12. Accordingly, the upper openings 310 and 320 of the common electrode 23, and the protrusion 162 of the T-shaped opening 160 of the pixel electrode 12 divide an area of the pixel electrode 12 defined by the base 161 of the T-shaped opening 160, the first and second long sides of the pixel electrode 12, and the first short side of the pixel electrode 12 into four sub-areas. The middle and lower openings 330 and 340 of the common electrode 23, and the lower opening 170 of the pixel electrode 12 divide an area of the pixel electrode 12 defined by the base 161 of the T-shaped opening 160, the first and second long sides of the pixel electrode 12, and the second short side of the pixel electrode 12 into four sub-areas.

[0037] With the configuration of the seventh preferred embodiment of the present invention as described above, the lower and upper polarizer films 14 and 24 are arranged such that their polarizing directions are the same as in the sixth preferred embodiment. Accordingly, the orienting direction of the liquid crystal molecules 30 becomes 45° with respect to the polarizing direction of the polarizer films 14 and 24 so that the response speed is rapid and the occurrence of texture is decreased, resulting in enhanced picture quality. The opening portions of the pixel and common electrodes 12 and 23 proceed generally in two directions normal to each other. Furthermore, as the opening portions of the pixel and common electrodes 12 and 23 are alternately arranged, the fringe field in one pixel area is applied in all directions. Fig. 9A

shows a schematic view of an opening pattern of the pixel electrode 12 according to an eighth preferred embodiment of the present invention. As shown in Fig. 9A, the opening pattern of the pixel electrode 12 is a single linear opening 180 parallel to the first and second short sides of the pixel electrode 12. If the pixel electrode 12 is divided into three areas of equal length, that is, first to third areas, with the first area having as its one side the first short side, the third area having as its one side the second short side, and the second area being formed between the first and third areas, the linear opening 180 is positioned where the second and third areas meet.

[0038] Fig. 9B shows a schematic view of an opening pattern of the common electrode 23 according to an eighth preferred embodiment of the present invention. As shown in Fig. 9B, the opening pattern of the common electrode 23 includes an upper opening 350 formed in the upper region of the common electrode 23 and a lower opening 360 formed in the lower region of the common electrode. The upper opening 350 includes a base 351, a trunk 352, and two branches 353 and 354. The base 351 of the upper opening 350 is formed roughly in a triangular shape and positioned extending over and past the first short side of the common electrode 23. The trunk 352 is linearly extended from an apex of the base 351 in a direction toward the second short side of the common electrode 23. The branches 353 and 354 are branched from a distal end of the trunk 352 toward and extending over the first and second long sides of the common electrode 23, each of the branches 353 and 354 forming an obtuse angle with respect to the trunk 352. The lower opening 360 linearly proceeds in a direction parallel to the first and short sides of the common electrode 23. Both ends of the lower opening 360 are enlarged in roughly a triangular shape and extend over the first and second long sides of the common electrode 23.

[0039] Fig. 9C shows a schematic view of the pixel and common electrodes 12 and 23 shown respectively in Figs. 9A and 9B in an overlapped state. As shown in Fig. 9C, the branches 353 and 354 of the upper opening 350 of the common electrode 23 roughly divide the pixel electrode 12 into upper and lower areas. The trunk 352 of the upper opening 350 of the common electrode 23 bisects the upper area of the pixel electrode 12 into two sub-areas, one sub-area having as its one side the second long side of the pixel electrode 12 and the other sub-area having as its one side the first long side of the pixel electrode 12. The lower opening 360 of the common electrode 23, and the linear opening 180 of the pixel electrode 12 trisect the lower area of the pixel electrode 12 into upper, middle and lower sub-areas.

[0040] With the configuration of the eighth preferred embodiment of the present invention as described above, the lower and upper polarizer films 14 and 24 are arranged such that their polarizing directions are the same as in the sixth preferred embodiment. With this structure, effects similar to those obtained in the seventh preferred embodiment are realized.

[0041] Fig. 10A shows a schematic view of an opening pattern of the pixel electrode 12 according to a ninth preferred embodiment of the present invention. As shown in Fig. 10A, the pixel electrode 12 is formed of four oval-shaped portions sequentially interconnected in the longitudinal direction.

[0042] Fig. 10B shows a schematic view of an opening pattern of the common electrode 23 according to a ninth preferred embodiment of the present invention. As shown in Fig. 10B, the opening pattern of the common electrode 23 includes four diamond-shaped openings 370, and left and right openings 380 and 390 surrounding the diamond-shaped openings 370. The diamond-shaped openings 370 are arranged over a longitudinal center of the common electrode 23 and are spaced apart from each other at a predetermined distance. Inner sides of the left and right openings 380 and 390 facing the diamond-shaped openings 370 substantially form cycloids such that four partial ovals result, each oval surrounding one of the diamond-shaped openings 370.

[0043] Fig. 10C shows a schematic view of the pixel electrode 12 and the common electrode 23 shown respectively in Figs. 10A and 10B in an overlapped state. As shown in Fig. 10C, each diamond-shaped opening 370 of the common electrode 23 is placed at the center of the corresponding oval-shaped portion of the pixel electrode 12. Also, the left and right openings 380 and 390 of the common electrode 23 surround the pixel electrode 12 at a predetermined distance.

[0044] With the configuration of the ninth preferred embodiment of the present invention as described above, the lower and upper polarizer films 14 and 24 are arranged such that their polarizing directions are the same as in the third preferred embodiment. The opening patterns of the pixel and common electrodes 12 and 23 according to the third to ninth preferred embodiments were designed with the intent of maximally satisfying the following conditions, the conditions being particular to opening patterns of the type for obtaining the partitioned orientation of the liquid crystal molecules 30.

[0045] First, in order to obtain a maximum viewing angle, it is preferable that four partitioned regions for orienting the liquid crystal molecules 30 are present within one pixel area.

[0046] Second, to obtain a stable partitioned orientation, disclination or texture should not be generated outside of the partitioned regions. Disclination occurs when the long axes of liquid crystal molecules are oriented in various directions in a confined area, particularly when the long axes are inclined toward one another. Therefore, it is preferable that the opening patterns of the pixel and common electrodes 12 and 23 are alternately arranged, and the end portions of the opening patterns are adjacent to each other. That is, when viewed from above, the opening patterns of the pixel and common electrodes 12 and 23 are preferably structured in the form of closed polygons. Furthermore, since disinclination is prone to occur when the opening patterns are structured having acute

angles, it is preferable that the opening patterns are formed including only obtuse angles. A stable partitioned orientation of liquid crystal molecules also enhances brightness. At areas where the orientation of the liquid crystal molecules 30 is dispersed, the leakage of light occurs in an off state, and dark portions are generated in an on state. Also, this dispersion of the orientation of liquid crystal molecules causes the generation of after-images when the liquid crystal molecules are rearranged.

[0047] Third, in order to obtain a high level of brightness, the following conditions should be satisfied. The angle made by the two directors of the liquid crystal molecules 30 at adjacent partitioned regions is preferably about 90° . When the angle of the director is established in this manner, disclination occurs only at the narrowest areas. The brightness is highest when the angle between the light transmission axis of the polarizer film and the director for liquid crystal molecules is 45° . It is preferable that twisting or bending of the opening patterns of the pixel and common electrodes 12 and 23 is minimized as much as possible.

[0048] Finally, in order to obtain a rapid response speed of the liquid crystal molecules 30, it is preferable again that the opening patterns of the pixel and common electrodes 12 and 23 are not twisted or bent too much. That is, it is preferable that the opening patterns of the pixel and common electrodes 12 and 23 linearly face each other. The affect of an opening width of the opening patterns and a spacing interval between the openings on light transmission and response speed will now be described.

[0049] In order to investigate such an interrelation, nine panels, each with different opening patterns were made and tested. Fig. 11 shows schematic views of nine different opening patterns A - J for demonstrating the affect of opening pattern width and spacing on response speed and brightness. In the drawing, the opening patterns of the common electrode are indicated by diagonal lines, and the opening patterns of the pixel electrode are indicated by solid lines.

[0050] As shown in Fig. 11, the B, C and D opening patterns are identical and the E, F and G opening patterns are identical. However, these opening patterns differ in opening width and spacing. The I and J opening patterns differ in the number of openings used, effectively having different opening spacings. The A opening pattern has a shape similar to that of the B, C and D opening patterns except for the formation at a center area of the A opening pattern. As a result, the A opening pattern is different in opening spacing from the B, C and D opening patterns. The opening width and the opening spacing of each opening pattern are listed in Table 1. Fig. 12A is a graph illustrating light transmissivity levels of test cells applying the A through J opening patterns, and Fig. 12B is a graph comparing the light transmissivity level of a test cell applying the B opening pattern to the light transmissivity levels of test cells applying the A through J opening patterns. As shown in the graphs, the light transmissivity

level of the test cell applying the G opening pattern is the highest, exceeding 13%. If the light transmissivity levels of the test cells are ranked from highest to lowest according to which opening pattern is used, the following ranking results: G, E, I, B, D, A, C, F, and J. Fig. 13 is a graph illustrating response times as a function of gray scale of test cells applying the A through J opening patterns. Although only sixty-nine (69) gray scales are used in actual application, the experiment was performed with one hundred and ten (110) gray scales. As shown in the graph, response times of the test cells applying the B, C, D, and J opening patterns were relatively fast over the whole range of gray scales. For the test cells applying the other opening patterns, the response times were relatively slow. In the case of the test cells applying the A and I opening patterns, the slow response times were due to the movement of texture, and in the case of the test cells applying the E, F, and G opening patterns, the slow response times can be attributed to the two-step movement of liquid crystal molecules.

[0051] The A through J opening patterns shown in Fig. 11 were applied to actual panels and the panels were tested. Testing was performed on a total of four panels for each opening pattern. The results are listed in Table 2.

[0052] The results of the experiment performed with the actual panels were similar to the results when using the test cells. However, there were some differences as follows. First, the actual panel in which the I opening pattern was applied exhibited a higher response speed than the test cell applying the same opening pattern. Also, better results with regard to brightness were obtained with the actual panel applying the J opening pattern than when the test cell was used. Specifically, the brightness of the test cell applying the J opening pattern was 75% of the cell applying the B opening pattern, whereas this was increased to 90% when the J opening pattern was applied to the actual panel.

[0053] When the actual panels were used, white afterimages were generated with the application of the C, I, and J opening patterns. The degree of white-afterimage generation was so high with the application of the C opening pattern that picture quality was impaired beyond a level that could be corrected. However, the generation of white afterimages was low enough when the I and J opening patterns were applied so that with some improvement, the panels could be used.

[0054] On the basis of the above results, the opening patterns to select depending on what the intended area of improvement is are as follows. If the improvement of brightness and the minimization of white afterimages are what are desired, it is preferable to use the B, D, E, and I opening patterns. However, if an improvement in response speed while keeping the brightness at a normal level is desired, the B, D, and I opening patterns are preferred. Finally, if what is needed is solely an improvement in response speed (without concerning brightness), the D and J opening patterns are preferred.

[0055] In order to further examine the interrelation be-

tween the response speed and the opening width of the opening patterns, the differences in the optical characteristics of panels applying the B, C, and D opening patterns, which have the same shape but different opening widths, will now be described.

[0056] Fig. 14 is a graph illustrating response times as a function of gray scale of actual panels applying the B, C, and D opening patterns. As shown in the graph, the response times of the panels applying the opening patterns exhibited the following relation (based on the type of opening pattern) when 20 to 40 gray scales were used: $D < B < C$. It is evident, therefore, that the larger the width of the opening pattern the faster the response time.

[0057] Roughly between 40 and 45 gray scales, the response time of the panel applying the C opening pattern is shorter than that of the panel applying B opening pattern, and after 45 gray scales, the response time of the panel applying the C opening pattern is shorter than that of the panel applying the D opening pattern. However, such a change in the response time of the panel applying the C opening pattern is not actually taking place, but instead is given the appearance of change as a result of the generation of white afterimages. That is, the response waveform is distorted due to the white afterimages so that the response time seems to be shorter than it actually is. Accordingly, the conclusion originally reached that the larger the width of the opening pattern the faster the response speed remains valid.

[0058] With the use 60 gray scales or more, the response speed slows considerably due to the occurrence of texture. In conclusion, the panel applying the D opening pattern, which has the greatest width, exhibits the most stable characteristics. Figs. 15A to 15C are photographs of the C, B and D opening patterns, respectively, at white gray scales. As seen from the photographs, the C opening pattern with poor texture stability displays the lowest level of brightness, with the B and D opening patterns exhibiting similarly higher levels of brightness. The D opening pattern exhibits a low opening ratio due to its significant width, but displays good texture stability such that panels applying this opening pattern have a high brightness. Texture stability is determined by the intensity of the fringe field and the width of the opening pattern.

[0059] The boundary areas between adjacent partitioned regions in the C, B and D opening patterns are formed differently. That is, two clearly distinguishable textures are present in most of the boundary areas of the C opening pattern, and with the B opening pattern, the boundary areas are again distinguishable but not as clearly as with the C opening pattern. The boundary areas of the D opening pattern, on the other hand, are not clearly formed and are faint in many portions.

[0060] Figs. 16A and 16B are photographs of the C and D opening patterns applied to test cells in which a change in the partitioned regions according to a level of an applied voltage is shown.

[0061] In the C opening pattern, two clearly distinguishable textures are present in the boundary areas when

the applied voltage reaches 3.5V, and becomes clearer with further increases in the applied voltage. However, in the D opening pattern, the boundary areas are somewhat clearly distinguishable only when the applied voltage reaches 5V. Such distinguishable boundary areas are a result of the non-uniform orientation of the liquid crystal molecules. To better describe such a phenomenon, the intensity of the fringe field as a function of the widths of the opening patterns will be examined.

[0062] Figs. 17A and 17B are schematic views used to illustrate the change in intensity of a fringe field according to variations in opening pattern width.

[0063] As the width of the opening pattern becomes larger, the horizontal component of the fringe field experiences corresponding increases. The horizontal component of the fringe field plays an important role in determining the orienting direction of liquid crystal molecules. Therefore, opening patterns with a large width are preferred in forming partitioned regions. In contrast, the larger the width of the opening pattern the weaker the intensity of the vertical component of the electric field working at the center of the opening pattern.

[0064] Figs. 18A to 18D are schematic views illustrating orienting states of liquid crystal molecules at a peripheral portion of the opening patterns. When the width of the opening pattern is relatively small, the liquid crystal molecules are horizontally oriented to some degree even at the center area of the opening pattern. That is, they are slightly inclined when the applied voltage is low, but completely oriented in the horizontal direction when the applied voltage is high. This is due to the vertical component of the electric field being strong even at the center area of the opening pattern. As a result, the leakage of light occurs and the boundary area between the partitioned regions is formed by two separate lines. Furthermore, in case the orienting direction of the liquid crystal molecules is changed by 180°, elasticity becomes greater due to the small width of the opening pattern. In contrast, as the horizontal component of the fringe field is weak, the fringe field is not strong enough to overcome the elasticity, thereby resulting in the orienting direction of the liquid crystal molecules at the boundary areas becoming non-uniform between the partitioned regions. Such a non-uniform orientation of the liquid crystal molecules occurs even in micro regions of the pixel.

[0065] When the width of the opening pattern is relatively large, the long axes of the liquid crystal molecules are perpendicular to the electrodes at the center area of the opening pattern. As the applied voltage is increased, the liquid crystal molecules are slightly inclined, but the degree of inclination is less than when the opening pattern has a small width. Therefore, only a minimal amount of light leakage occurs and the boundary area between adjacent partitioned regions is shaped with a dark line.

[0066] As described previously, the greater the width of the opening pattern the more rapid the response speed, and as stated above, a greater width of the opening pattern leads to more uniform micro regions of the

pixel. When the width of the opening pattern is great, although the opening ratio is low, the orientation of the liquid crystal molecules is uniform such that a satisfactory degree of brightness is obtained. According to the above experimental results, it is preferable that the opening width of the opening pattern is in the range of $13 \pm 3 \mu\text{m}$, and the cell gap is in the range of about 4-6 μm .

[0067] The affect of opening spacing on the optical characteristics of the opening patterns will now be described. The I and J opening patterns have the same total widths but effectively different spacings. According to the experimental results with respect to the test cells, the optical characteristics of the I and J opening patterns are significantly different. However, when actual panels apply these opening patterns, the resulting optical characteristics of the I and J opening patterns do not vary by such a degree. It is viewed that this is a result of the such factors as the difference in the type of alignment layer used, whether a protective insulating layer is used, the difference in the waveforms of the applied voltage, etc. However, when the speeds of moving picture images are compared in the actual panels, they are more rapid with the J opening pattern than with the I opening pattern. This can be easily demonstrated by observing the motion of a dark rectangle on a gray background. The only difference in response speed occurs by variations in the gray scales.

[0068] As with the opening width of the opening pattern, when the spacing between the opening portions of the opening pattern becomes smaller, the opening ratio is significantly reduced but the brightness does not undergo much change. This is due to texture. That is, when the distance between the opening portions is increased, the control of texture becomes difficult, whereas such control is easily performed when the opening spacing is small. Therefore, when the distance between the opening portions is small, the opening ratio is reduced but the control of texture is easy, thereby enabling the compensation of brightness. The exception is with the I opening pattern in which even though the distance between the opening portions is large, a high brightness results because texture control is easily performed. In brief, a smaller distance between the opening portions results in an improvement of the response speed at various gray scales. Even though the brightness is prone to deteriorate due to the decrease in the opening ratio, this can be compensated for to some degree by controlling texture.

[0069] There exists a direct correlation between texture and response speed. Moving texture reduces response speed. When a high voltage is applied, the response speed is reduced in most of the opening patterns. This is due to the generation of texture. Therefore, if texture can be suitably controlled, picture quality as well as response speed can be improved. Techniques of inhibiting the occurrence of texture will now be described.

[0070] Figs. 19 and 20 show schematic views of portions where texture occurs in the B and J opening patterns, respectively. The opening pattern shown in Fig. 19

is nearly identical to that shown in Fig. 4C. However, in the opening pattern of Fig. 19, second and third openings 122 and 123 of the pixel electrode 12 begin from the first long side of the pixel electrode 12 and extend toward the second long side of the pixel electrode 12 nearly reaching the same, whereas in the opening pattern of Fig. 4C, the second and third openings 122 and 123 are structured in the opposite manner. Furthermore, portions of the second long side of the pixel electrode 12 adjacent to ends of the second and third openings 122 and 123 of the opening pattern of Fig. 19 are protruded externally to prevent the interconnection of the partitioned regions of the pixel electrode 12 from deteriorating due to the opening portions 122 and 123.

[0071] Portions where texture occurs mainly correspond to areas where ends of the opening portions of the common electrode 23 and ends of the opening portions of the pixel electrode 12 meet. When the upper and lower substrates are appropriately arranged, the occurrence of texture is low, whereas when the substrates are inappropriately arranged, half moon-shaped textures, which do not cause the generation of white afterimages, occur. In order to inhibit such texture occurrence, the width of the ends of the opening portions of the common electrode 23 may be enlarged. Through such enlargement, the allowable range of error in arrangement can be increased. The opening pattern shown in Fig. 20 is similar to that shown in Fig. 8C, but differs in the number of openings extending across the pixel electrode from the first long side to the second long side. Furthermore, the openings of the pixel electrode 12 are such that they are open where they begin at the first long side of the pixel electrode 12 and extend across toward, but not reaching, the second long side of the pixel electrode 12. Portions of the second long side of the pixel electrode 12 adjacent to ends of these openings are protruded externally.

[0072] The occurrence of texture is concentrated at areas "a" corresponding to ends of openings of the common electrode 23 proceeding across from the first long side to the second long side of the common electrode 23. Furthermore, texture occurs also along the second short side of the pixel electrode 12, or area "b", which is deformed outwardly to enable a connection with the source electrode, as well as at area "c" at an end of an opening of the pixel electrode 12.

[0073] Such texture can be inhibited in the following way. In the case of area a, a width of the ends of the openings of the common electrode 23 are increased. In the case of area b, the openings of the common electrode 23 are structured to overlap part of area b. For this purpose, it is necessary to control the width and spacing of the opening portions. When the spacing is decreased, the opening ratio is reduced but the response speed is enhanced. In the case of area c, the end of the opening of the pixel electrode 12 extended from the first short side is formed having sharp edges.

[0074] Figs. 21A to 21C illustrate opening patterns

where the above-described texture improving techniques have been applied.

[0075] In the above description, a structure in which the opening patterns are formed at both the pixel and common electrodes 12 and 23 is disclosed. However, it is also possible to form the opening patterns, together with the protrusions, only at the pixel electrode 12. In this case, the protrusions are formed using a gate insulating layer or a protective layer. In the formation of the protrusions, care should be taken to avoid the formation of parasitic capacitance between electrical lines. The openings and the protrusions can be arranged as illustrated in Fig. 21.

[0076] Alternatively, the opening patterns may be formed only in the pixel electrode 12 while forming the protrusions in the common electrode 23. In this case, the openings and the protrusions can be arranged also as illustrated in Fig. 21.

[0077] As described above, the inventive liquid crystal display obtains a wide viewing angle, and exhibits stable orientation of the liquid crystal molecules and a rapid response speed.

[0078] While the present invention has been described in detail with reference to the preferred embodiments, those skilled in the art will appreciate that various modifications and substitutions can be made thereto without departing from the spirit and scope of the present invention as set forth in the appended claims.

[0079] Where technical features mentioned in any claim are followed by reference signs, those reference signs have been included for the sole purpose of increasing the intelligibility of the claims and accordingly, such reference signs do not have any limiting effect on the scope of each element identified by way of example by such reference signs.

[0080] The present disclosure concerns:

1. A liquid crystal display comprising:

- a first insulating substrate having top and bottom surfaces;
- a pixel electrode formed on the top surface of the first insulating substrate, the pixel electrode having a first opening pattern at each pixel area, the pixel electrode with the first opening pattern being substantially rectangular in shape in each pixel area and having (a) first and second long sides, (b) first and second short sides, (c) an upper region corresponding to roughly half of the pixel electrode defined by the first and second long sides and the first short side, and (d) a lower region corresponding to roughly half of the pixel electrode defined by the first and second long sides and the second short side;
- a second insulating substrate having top and bottom surfaces, the second insulating substrate being arranged parallel to the first insulating substrate at a predetermined distance from

the same such that the bottom surface of the second insulating substrate faces the top surface of the first insulating substrate;
 a common electrode formed on the bottom surface of the second insulating substrate, the common electrode having a second opening pattern at each pixel area, the common electrode with the second opening pattern being substantially rectangular in shape in each pixel area and having (a) first and second long sides, (b) first and second short sides, (c) an upper region corresponding to roughly half of the common electrode defined by the first and second long sides and the first short side, and (d) a lower region corresponding to roughly half of the pixel electrode defined by the first and second long sides and the second short side; and
 a liquid crystal layer sandwiched between the first and second substrates while contacting the pixel and common electrodes,

wherein the first and second opening patterns each have a middle linear portion, the linear portions being alternately arranged parallel to each other.

2. The liquid crystal display of Point 1 wherein the first opening pattern comprises a first opening formed in the upper region of the pixel electrode in a first direction and a second opening formed in the lower region of the pixel electrode in a second direction normal to the first direction, and the second opening pattern comprises a first trunk opening formed in the upper region of the common electrode in the first direction and a second trunk opening formed in the lower region of the common electrode in the second direction.

3. The liquid crystal display of Point 2 wherein the first direction is at a slant with respect to the long or short sides of the pixel electrode.

4. The liquid crystal display of Point 3 wherein the second opening pattern further comprises first branch openings overlapping the first and second short sides of the pixel electrode and second branch openings overlapping the first and second long sides of the pixel electrode, and the first opening pattern further comprises a third opening formed where the upper and lower regions of the pixel electrode meet while proceeding parallel to the first and second short sides of the pixel electrode, the first and second opening patterns partitioning the pixel electrode into a plurality of micro-regions each shaped as a closed polygon.

5. The liquid crystal display of Point 4 wherein the second branch openings each has a width greater than a width of the trunk opening portion.

6. The liquid crystal display of Point 2 wherein the first direction is parallel to one of the long and short sides of the pixel electrode.

7. The liquid crystal display of Point 6 wherein the

first and second trunk openings each has opposite ends, each end having a gradually enlarged width.

8. The liquid crystal display of Point 6 wherein one of the second trunk opening portions overlaps the second short side of the pixel electrode.

9. The liquid crystal display of Point 6 wherein the first opening portion has opposite ends, each end having a gradually reduced width.

10. The liquid crystal display of Point 2 further comprising a first polarizer film formed on the bottom surface of the first substrate, and a second polarizer film formed on the top surface of the second substrate, the first and second polarizer films being polarized by 45° with respect to the first and second directions, respectively.

11. The liquid crystal display of Point 2 wherein the pixel electrode has protrusions at portions adjacent to the ends of the first and second openings.

12. The liquid crystal display of Point 1 wherein the opening width of the first and second opening patterns is in the range of 10-16μm.

[0081] The present disclosure also concerns:

13. A liquid crystal display comprising:

a first insulating substrate having top and bottom surfaces;

a pixel electrode formed on the top surface of the first insulating substrate, the pixel electrode having a first opening pattern at each pixel area, the pixel electrode with the first opening pattern being substantially rectangular in shape in each pixel area and having (a) first and second long sides, (b) first and second short side, (c) an upper region corresponding to roughly half of the pixel electrode defined by the first and second long sides and the first short side, and (d) a lower region corresponding to roughly half of the pixel electrode defined by the first and second long sides and the second short side;

a second insulating substrate having top and bottom surfaces, the second insulating substrate being arranged parallel to the first insulating substrate at a predetermined distance from the same such that the bottom surface of the second insulating substrate faces the top surface of the first insulating substrate;

a common electrode formed on the bottom surface of the second insulating substrate, the common electrode having a second opening pattern at each pixel area, the common electrode with the second opening pattern being substantially rectangular in

shape in each pixel area and having (a) first and second long sides, (b) first and second short sides, (c) an upper region corresponding to roughly half of the common electrode defined by the first and

5

second long sides and the first short side, and (d) a lower region corresponding to roughly half of the pixel electrode defined by the first and second long sides and the second short side; and

10

a liquid crystal layer sandwiched between the first and second substrates while contacting the pixel and common electrodes,

15

wherein the first and second opening patterns are overlap each other to thereby partition the pixel electrode into a plurality of micro-regions, each micro-region being polygonal in shape with two longest sides proceeding parallel to each other.

20

14. The liquid crystal display of Point 13 wherein the micro-regions of the pixel electrode are classified into a first type where the longest sides are arranged in a first direction, and a second type where the longest sides are arranged in a second direction normal to the first direction.

25

15. The liquid crystal display of Point 14 wherein the first direction is at a slant with respect to the long or short sides of the pixel electrode.

30

16. The liquid crystal display of Point 14 wherein the first direction is parallel to one of the long and short sides of the pixel electrode.

17. The liquid crystal display of Point 13 wherein the opening width of the first and second opening patterns is in the range of 10-16 μ m.

35

[0082] The present disclosure also concerns:

18. A liquid crystal display comprising:

40

a first insulating substrate having top and bottom surfaces;

a pixel electrode formed on the top surface of the first insulating substrate, the pixel electrode having a first opening pattern at each pixel area, the pixel electrode with the first opening pattern being substantially rectangular in shape in each pixel area and having (a) first and second long sides, (b) first and second short sides, (c) an upper region corresponding to roughly half of the pixel electrode defined by the first and second long sides and the first short side, and (d) a lower region corresponding to roughly half of the pixel electrode defined by the first and second long sides and the second short

45

50

55

side;

a second insulating substrate having top and bottom surfaces, the second insulating substrate being arranged parallel to the first insulating substrate at a predetermined distance from the same such that the bottom surface of the second insulating substrate faces the top surface of the first insulating substrate;

a common electrode formed on the bottom surface of the second insulating substrate, the common electrode having a second opening pattern at each pixel area, the common electrode with the second opening pattern being substantially rectangular in shape in each pixel area and having (a) first and second long sides, (b) first and second short sides, (c) an upper region corresponding to roughly half of the common electrode defined by the first and second long sides and the first short side, and (d) a lower region corresponding to roughly half of the pixel electrode defined by the first and second long sides and the second short side; and a liquid crystal layer sandwiched between the first and second substrates while contacting the pixel and common electrodes,

wherein the first and second opening patterns generate fringe fields when voltage is applied between the pixel and common electrodes, the orienting direction of the liquid crystal molecules due to the fringe fields corresponding to the orienting direction of the liquid crystal molecules resulting from a force exerted by molecules.

19. The liquid crystal display of Point 18 wherein the orientation of the liquid crystal molecules due to the fringe fields occurs in four directions.

20. The liquid crystal display of Point 18 wherein the opening width of the first and second opening patterns is in the range of 10-16 μ m.

[0083] The present disclosure also concerns:

21. A liquid crystal display comprising:

a first insulating substrate having top and bottom surfaces;

a pixel electrode formed on the top surface of the first insulating substrate, the pixel electrode having a first opening pattern at each pixel area, the pixel electrode with the first opening pattern being substantially rectangular in shape in each pixel area and having (a) first and second long sides, (b) first and second short sides, (c) an upper region corresponding to roughly half of the

pixel electrode defined by the first and second long sides and the first short side, and (d) a lower region corresponding to roughly half of the pixel electrode defined by the first and second long sides and the second short side;

a second insulating substrate having top and bottom surfaces, the second insulating substrate being arranged parallel to the first insulating substrate at a predetermined distance from the same such that the bottom surface of the second insulating substrate faces the top surface of the first insulating substrate;

a common electrode formed on the bottom surface of the second insulating substrate, the common electrode having a second opening pattern at each pixel area, the common electrode with the second opening pattern being substantially rectangular in shape in each pixel area and having (a) first and second long sides, (b) first and second short sides, (c) an upper region corresponding to roughly half of the common electrode defined by the first and second long sides and the first short side, and (d) a lower region corresponding to roughly half of the pixel electrode defined by the first and second long sides and the second short side; and a liquid crystal layer sandwiched between the first and second substrates while contacting the pixel and common electrodes,

wherein the first opening pattern comprises a first opening proceeding from the first long side in a direction toward the second long side, second and third openings proceeding from the second long side at a predetermined incline toward the first long side, the second and third openings being symmetrical with respect to the first opening, wherein the second opening pattern comprises fourth to sixth openings, the fourth opening comprising a trunk proceeding in a direction horizontal to the first and second short sides, first and second branches branched from the trunk toward the first long side slightly up and downwards, and first and second sub-branches respectively extended from the first and second branches opposite each other in a direction parallel to the first and second long sides, the fifth opening portion comprising a body parallel to the first branch, and first and second limbs extended from top and bottom ends of the body respectively in directions parallel and perpendicular to the first and second short sides, the sixth opening portion being symmetrical to the fifth opening portion with respect to the fourth opening portion,

and wherein the first and second opening patterns are alternately arranged when viewed from above.

22. The liquid crystal display of Point 21 wherein the first and second sub-branches, and the second limbs have a width greater than a width of other portions of the second opening pattern.

23. The liquid crystal display of Point 21 or 22 further comprising a first polarizer film formed on the bottom surface of the first substrate, and a second polarizer film formed on the top surface of the second substrate, the first and second polarizer films being polarized either in the horizontal and vertical directions or in the vertical and horizontal directions.

24. The liquid crystal display of Point 21 or 22 wherein the width of the first to sixth openings is in the range of 10-16 μ m.

[0084] The present disclosure also concerns:

25. A liquid crystal display comprising:

a first insulating substrate having top and bottom surfaces;

a pixel electrode formed on the top surface of the first insulating substrate, the pixel electrode having a first opening pattern at each pixel area, the pixel electrode with the first opening pattern being substantially rectangular in shape in each pixel area and having (a) first and second long sides, (b) first and second short sides, (c) first and fourth corners formed respectively by ends of the first short side and the first long side and by the second short side and the first long side, (d) second and third corners respectively formed by the first short side and the second long side and by the second short side and the second long side, (e) an upper region corresponding to roughly half of the pixel electrode defined by the first and second long sides and the first short side, and (f) a lower region corresponding to roughly half of the pixel electrode defined by the first and second long sides and the second short side;

a second insulating substrate having top and bottom surfaces, the second insulating substrate being arranged parallel to the first insulating substrate at a predetermined distance from the same such that the bottom surface of the second insulating substrate faces the top surface of the first insulating substrate;

a common electrode formed on the bottom surface of the second insulating substrate, the common electrode having a second opening pattern at each pixel area, the common electrode with the second opening pattern being substantially rectangular in shape in each pixel area and having (a) first and second long sides, (b) first and second short sides, (c) an upper region corresponding to roughly half of the common electrode defined by the first and second long sides

and the first short side, and (d) a lower region corresponding to roughly half of the pixel electrode defined by the first and second long sides and the second short side; and
a liquid crystal layer sandwiched between the first and second substrates while contacting the pixel and common electrodes,

wherein the first opening pattern comprises a first opening, the first opening comprising a first inclined line proceeding from the first long side toward the second long side, and a second inclined line extended from the first inclined line toward the first long side, wherein the second opening pattern comprises second and third openings, the second opening comprising a base proceeding in a direction parallel to the first and second long sides, and a projection extended from the base in a direction parallel to the first and second short sides, the third opening comprising a body proceeding in a direction parallel to the first and second short sides, and first and second limbs extended from top and bottom ends of the body at a predetermined incline while being symmetrical to each other with respect to the second opening; and wherein the first and second opening patterns are alternately arranged when viewed from above.

26. The liquid crystal display of Point 25 further comprising a first polarizer film formed on the bottom surface of the first substrate, and a second polarizer film formed on the top surface of the second substrate, the first and second polarizer films being polarized either in the horizontal and vertical directions or in the vertical and horizontal directions.

27. The liquid crystal display of Point 25 or 26 wherein the width of the first to third openings is in the range of 10-16 μ m.

28. The liquid crystal display of Point 25 or 26 wherein the second top and bottom edges of the pixel electrode, and edges of the pixel electrode at where the base and the projection meet are cut away.

[0085] The present disclosure also concerns:

29. A liquid crystal display comprising:

a first insulating substrate having top and bottom surfaces;

a pixel electrode formed on the top surface of the first insulating substrate, the pixel electrode having a first opening pattern at each pixel area, the pixel electrode with the first opening pattern being substantially rectangular in shape and having (a) first and second long sides, (b) first and second short sides, (c) first and fourth corners formed respectively by ends of the first and short side and the first long side and by the second

short side and the first long side, (d) second and third corners formed respectively by the first short side and the second long side and by the second short side and the second long side, (e) an upper region corresponding to roughly half of the pixel electrode defined by the first and second long sides and the first short side, and (f) a lower region corresponding to roughly half of the pixel electrode defined by the first and second long sides and the second short side;
a second insulating substrate having top and bottom surfaces, the second insulating substrate being arranged parallel to the first insulating substrate at a predetermined distance from the same such that the bottom surface of the second insulating substrate faces the top surface of the first insulating substrate;

a common electrode formed on the bottom surface of the second insulating substrate, the common electrode having a second opening pattern at each pixel area, the common electrode with the second opening pattern being substantially rectangular in shape in each pixel area and having (a) first and second long sides, (b) first and second short sides, (c) an upper region corresponding to roughly half of the common electrode defined by the first and second long sides and the first short side, and (d) a lower region corresponding to roughly half of the pixel electrode defined by the first and second long sides and the second short side; and
a liquid crystal layer sandwiched between the first and second substrates while contacting the pixel and common electrodes,

wherein the first opening pattern comprises a first opening hollowed from the first long side and extending toward the second long side in a direction parallel to the first and second short sides, and a second opening hollowed from the second long side and extending toward the first long side parallel to the first opening,

wherein the second opening pattern comprises a third opening, the third opening comprising a first inclined line proceeding in a first direction, a second inclined line extended from the first inclined line in a second direction opposite the first direction, and a third inclined line extended from the second inclined line parallel to the first inclined line, and wherein the first and second openings partition the pixel electrode into three separate regions, and the third opening partitions each region of the pixel electrode into two sub-regions.

30. The liquid crystal display of Point 29 further comprising a first polarizer film formed on the bottom sur-

face of the first substrate, and a second polarizer film formed on the top surface of the second substrate, the first and second polarizer films being polarized either by 45° and 135° or by 135° and 45°.

31. The liquid crystal display of Point 29 or 30 wherein the width of the first to third openings is in the range of 10-16μm.

32. The liquid crystal display of Point 29 or 30 wherein edges of the pixel electrode at inlet areas of the first and second openings as well as the second and third corners of the pixel electrode are cut away.

[0086] The present disclosure also concerns:

33. A liquid crystal display comprising:

a first insulating substrate having top and bottom surfaces;

a pixel electrode formed on the top surface of the first insulating substrate, the pixel electrode having a first opening pattern at each pixel area, the pixel electrode with the first opening pattern being substantially rectangular in shape and having long sides and short sides;

a second insulating substrate having top and bottom surfaces, the second insulating substrate being arranged parallel to the first insulating substrate at a predetermined distance from the same such that the bottom surface of the second insulating substrate faces the top surface of the first insulating substrate;

a common electrode formed on the bottom surface of the second insulating substrate, the common electrode having a second opening pattern at each pixel area, which correspond to each pixel area of the pixel electrode; and

a liquid crystal layer sandwiched between the first and second substrates while contacting the pixel and common electrodes,

wherein the first opening pattern comprises a plurality of linear openings spaced apart at a predetermined distance and arranged in parallel in a direction parallel to the long sides,

wherein the second opening pattern comprises a plurality of X-shaped openings spaced apart from each other at a predetermined distance and arranged in parallel in a direction parallel to the long sides, and wherein the first opening pattern partitions the pixel electrode into a plurality of regions, and the second opening pattern partitions each region of the pixel electrode into four sub-regions.

34. The liquid crystal display of Point 33 further comprising a first polarizer film formed on the bottom surface of the first substrate, a second polarizer film formed on the top surface of the second substrate, the first and second polarizer films being polarized either by 45° and 135° or by 135° and 45°.

35. The liquid crystal display of Point 33 or 34 wherein the width of the openings of the first and second opening patterns is in the range of 10 to 16μm.

[0087] The present disclosure also concerns:

36. A liquid crystal display comprising:

a first insulating substrate having top and bottom surfaces;

a pixel electrode formed on the top surface of the first insulating substrate, the pixel electrode having a first opening pattern at each pixel area, the pixel electrode with the first opening pattern being substantially rectangular in shape in each pixel area and having first and second long sides, first and second short sides, an upper region corresponding to roughly half of the pixel electrode defined by the first and second long sides and the first short side, and a lower region corresponding to roughly half of the pixel electrode defined by the first and second long sides and the second short side;

a second insulating substrate having top and bottom surfaces, the second insulating substrate being arranged parallel to the first insulating substrate at a predetermined distance from the same such that the bottom surface of the second insulating substrate faces the top surface of the first insulating substrate;

a common electrode formed on the bottom surface of the second insulating substrate, the common electrode having a second opening pattern at each pixel area, which correspond to each pixel area of the pixel electrode; and

a liquid crystal layer sandwiched between the first and second substrates while contacting the pixel and common electrodes,

wherein the first opening pattern comprises a first opening proceeding in a direction parallel to the first and second long sides, and second openings positioned under the first opening portion while proceeding in a direction parallel to the first and second short sides, the second opening partitioning the pixel electrode into upper and lower regions,

wherein the second opening pattern comprises third openings proceeding in a direction parallel to the first and second long sides, and fourth openings positioned below the third opening while proceeding in a direction parallel to the first and second short sides,

and wherein the first and third openings are al-

ternately arranged while partitioning the upper region of the pixel electrode into a plurality of sub-regions in a direction parallel to the first and second long sides, and the second and fourth openings are alternately arranged while partitioning the lower region of the pixel electrode into a plurality of sub-regions in a direction parallel to the first and second short sides.

37. The liquid crystal display of Point 36 wherein the fourth opening closest to the second short side overlap the second short side of the pixel electrode.

38. The liquid crystal display of Point 36 wherein both ends of the fourth openings have a gradually enlarged width.

39. The liquid crystal display of Point 36 wherein a bottom end of the first opening has a gradually reduced width.

40. The liquid crystal display of Point 36 further comprising a first polarizer film formed on the bottom surface of the first substrate, and a second polarizer film formed on the top surface of the second substrate, the first and second polarizer films being polarized either by 45° and 135° or by 135° and 45°.

41. The liquid crystal display of Point 36 wherein the width of the first to fourth openings is in the range of 10 to 16μm.

[0088] The present disclosure also concerns:

42. A liquid crystal display comprising:

a first insulating substrate having top and bottom surfaces;

a pixel electrode formed on the top surface of the first insulating substrate, the pixel electrode having a first opening pattern at each pixel area, the pixel electrode with the first opening pattern being substantially rectangular in shape in each pixel area and having (a) first and second long sides, (b) first and second short sides, (c) an upper region corresponding to roughly half of the pixel electrode defined by the first and second long sides and the first short side, and (d) a lower region corresponding to roughly half of the pixel electrode defined by the first and second long sides and the second short side;

a second insulating substrate having top and bottom surfaces, the second insulating substrate being arranged parallel to the first insulating substrate at a predetermined distance from the same such that the bottom surface of the second insulating substrate faces the top surface of the first insulating substrate;

a common electrode formed on the bottom surface of the second insulating substrate, the common electrode having a second opening pattern at each pixel area, the common electrode with the second opening pattern being substantially rectangular in shape in each pixel area and having (a) first and second long sides, (b) first and second short sides, (c) an upper region corresponding to roughly half of the common electrode defined by the first and second long sides and the first short side, and (d) a lower region corresponding to roughly half of the pixel electrode defined by the first and second long sides and the second short side; and a liquid crystal layer sandwiched between the first and second substrates while contacting the pixel and common electrodes,

wherein the first opening pattern comprises a first linear opening proceeding in a direction parallel to the first and second short sides, wherein the second opening pattern comprises a second opening proceeding in a direction parallel to the first and second long sides, and a third opening positioned away from the second opening toward the second short side and proceeding in a direction parallel to the first and second short sides, and wherein the second opening bisects the upper region of the pixel electrode into left and right sub-regions, and the first and third openings partition the lower region of the pixel electrode into a plurality of sub-regions.

43. The liquid crystal display of Point 42 wherein a top end of the second opening portion, and both ends of the third opening portion have a gradually enlarged width.

44. The liquid crystal display of Point 42 wherein the third opening overlaps the second short side of the pixel electrode.

45. The liquid crystal display of Point 42 further comprising a first polarizer film formed on the bottom surface of the first substrate, and a second polarizer film formed on the top surface of the second substrate, the first and second polarizer films being polarized either by 45° and 135° or by 135° and 45°

46. The liquid crystal display of Point 42 wherein the width of the first to third openings is in the range of 10 to 16μm.

[0089] The present disclosure also concerns:

47. A liquid crystal display comprising:

a first insulating substrate having top and bottom surfaces;

a pixel electrode formed on the top surface of the first insulating substrate, the pixel electrode at each pixel area being shaped with a plurality of ovals continuously interconnected in the vertical direction;
 a second insulating substrate having top and bottom surfaces, the second insulating substrate being arranged parallel to the first insulating substrate at a predetermined distance from the same such that the bottom surface of the second insulating substrate faces the top surface of the first insulating substrate;
 a common electrode formed on the bottom surface of the second insulating substrate, the common electrode having an opening pattern at each pixel area, which correspond to each pixel area of the pixel electrode; and
 a liquid crystal layer sandwiched between the first and second substrates while contacting the pixel and common electrodes,

wherein the opening pattern comprises first diamond-shaped openings spaced apart from each other at a predetermined distance in a longitudinal direction, and second and third openings externally surrounding the first diamond-shaped openings,
 wherein the region of the common electrode defined by inner sides of the second and third openings facing the diamond-shaped opening portion being formed with oval-shaped portions, each oval-shaped portion surrounding one of the diamond-shaped openings,
 and wherein each of the first diamond-shaped openings is positioned at each oval-shaped portion of the pixel electrode when viewed from above, and the second and third openings surround the pixel electrode.

48. The liquid crystal display of Point 47 further comprising a first polarizer film formed on the bottom surface of the first substrate, and a second polarizer film formed on the top surface of the second substrate, the first and second polarizer films being polarized either in the longitudinal direction and perpendicular to the longitudinal direction or vice versa.

49. The liquid crystal display of Point 47 wherein a distance of the second and third openings to an outer side of the pixel electrode is uniformly in the range of 10-16 μ m.

Claims

1. A liquid crystal display, comprising:

a first insulating substrate having a top surface and a bottom surface;
 a pixel electrode formed on the top surface of the first insulating substrate, the pixel electrode having a first opening pattern;
 a second insulating substrate having a top surface and a bottom surface;
 a common electrode formed on the bottom surface of the second insulating substrate, the common electrode having a second opening pattern; and
 a liquid crystal layer sandwiched between the first substrate and the second substrate, wherein the first opening pattern and the second opening pattern each have a middle, first and second opening, the openings being alternately arranged except where a trunk opening of the middle opening of the second opening pattern overlaps the middle opening of the first opening pattern, wherein the trunk opening is a portion of the middle opening and of the second opening pattern.

2. The liquid crystal display of claim 1, wherein the first opening of the first opening pattern is formed in an upper region of the pixel electrode in a first direction and the second opening of the first opening pattern is formed in a lower region of the pixel electrode in a second direction normal to the first direction, and the middle opening of the second opening pattern comprises a first branch opening extending from the trunk opening formed in a first region of the common electrode in the first direction and a second branch opening extending from the trunk opening formed in the second region of the common electrode in the second direction wherein the first region and the second region of the common electrode respectively correspond to the upper region and the lower region of the pixel electrode.

3. The liquid crystal display of claim 2, wherein the first direction is at a slant with respect to long sides or short sides of the pixel electrode.

4. The liquid crystal display of claim 3, wherein the middle opening of the second opening pattern further comprises first and second sub-branch openings overlapping a second long side of the pixel electrode and the first and second openings of the second opening pattern each comprise first and second branch openings overlapping a first long side and a first or second short side of the pixel electrode, respectively, the first opening pattern and the second opening pattern partition the pixel electrode into a plurality of sub-regions.

5. The liquid crystal display of claim 4, wherein each of the first and second sub-branch openings has a

width greater than a width of the first and second branch openings.

6. The liquid crystal display of claim 2, wherein the first direction is parallel to one of the long side and the short side of the pixel electrode. 5
7. The liquid crystal display of claim 6, wherein the first sub-branch opening and the second sub-branch opening each have first ends, each first end having a gradually enlarged width and second ends, each second end having a gradually reduced width. 10
8. The liquid crystal display of claim 6, wherein the trunk opening of the middle opening of the second opening pattern overlaps the first long side of the pixel electrode. 15
9. The liquid crystal display of claim 6, wherein the first branch openings of the first and second openings of the second opening pattern have first ends, each first end having a gradually enlarged width and second ends, each second end having a gradually reduced width. 20
10. The liquid crystal display of claim 2, further comprising a first polarizer film formed on the bottom surface of the first substrate, and a second polarizer film formed on the top surface of the second substrate, the first polarizer film and the second polarizer film being arranged to have polarizing directions of about 45.degree. with respect to the first direction and the second direction, respectively. 25 30
11. The liquid crystal display of claim 2, wherein the pixel electrode has protrusions at portions adjacent to ends of the first opening and the second opening of the first opening pattern. 35
12. The liquid crystal display of claim 1, wherein an opening width of the first opening pattern and the second opening pattern is in the range of about 10 μm to about 16 μm . 40
13. The liquid crystal display of claim 1, wherein a width of the trunk opening varies along a length of the trunk opening. 45
14. The liquid crystal display of claim 1, wherein the first and second openings of the second opening pattern include first and second branches respectively extending from the first and second openings along respective first and second sides of the pixel electrode substantially parallel to the trunk portion and at obtuse angles with respect to the first and second openings of the second opening pattern. 50 55

15. A liquid crystal display, comprising:

a first insulating substrate having a top surface and a bottom surface;
 a pixel electrode formed on the top surface of the first insulating substrate, the pixel electrode having an opening pattern;
 a second insulating substrate having a top surface and a bottom surface;
 a common electrode formed on the bottom surface of the second insulating substrate, the common electrode having a plurality of protrusions; and
 a liquid crystal layer sandwiched between the first substrate and the second substrate, wherein the opening pattern has a middle, first and second opening and the plurality of protrusions include a middle, first and second protrusion, the openings and protrusions being alternately arranged except where a trunk protrusion of the middle protrusion of the plurality of protrusions overlaps the middle opening of the opening pattern, wherein the trunk protrusion is a portion of the middle protrusion and of the plurality of protrusions.

16. The liquid crystal display of claim 15, wherein a width of the trunk protrusion varies along a length of the trunk protrusion. 25
17. The liquid crystal display of claim 15, wherein the first and second protrusions of the plurality of protrusions include first and second branches respectively extending from the first and second protrusions along respective first and second sides of the pixel electrode substantially parallel to the trunk protrusion and at obtuse angles with respect to the first and second protrusions 30

FIG. 1




FIG. 2




FIG. 3A




FIG. 3B




FIG. 4A




FIG. 4B




FIG. 4C




FIG. 5A




FIG. 5B




FIG. 5C




FIG. 6A




FIG. 6B




FIG. 6C




FIG. 7A




FIG. 7B




FIG. 7C




FIG. 8A




FIG. 8B




FIG. 8C




FIG. 9A




FIG. 9B




FIG. 9C




FIG. 10A




FIG.10B




FIG.10C




FIG. 11




FIG. 12A




FIG. 12B




FIG. 13




FIG. 14




FIG. 15






FIG. 16



(A) C Pattern: 3V $\rightarrow$ 3.5V $\rightarrow$ 4V $\rightarrow$ 5V



(B) D Pattern: 3V $\rightarrow$ 3.5V $\rightarrow$ 4V $\rightarrow$ 5V

FIG. 17A




FIG. 17B






FIG.18



(A) Small Width, Low Voltage



(A) Small Width, High Voltage



(C) Large Width, Low Voltage



(D) Large Width, High Voltage

FIG. 19




FIG. 20




FIG. 21A




FIG. 21B





FIG. 21C





EUROPEAN SEARCH REPORT

Application Number
EP 10 18 1718

DOCUMENTS CONSIDERED TO BE RELEVANT			
Category	Citation of document with indication, where appropriate, of relevant passages	Relevant to claim	CLASSIFICATION OF THE APPLICATION (IPC)
X	EP 0 884 626 A2 (FUJITSU LTD [JP] SHARP KK [JP]) 16 December 1998 (1998-12-16) * page 21, line 30 - page 22, line 16; figures 44-46 * * page 23, line 1 - page 23, line 12; figure 54 * * page 28, line 9 - page 28, line 10; figures 79A, 79B * -----	1-14	INV. G02F1/13
			TECHNICAL FIELDS SEARCHED (IPC)
			G02F
The present search report has been drawn up for all claims			
Place of search Munich		Date of completion of the search 18 March 2011	Examiner Lerbinger, Klaus
CATEGORY OF CITED DOCUMENTS X : particularly relevant if taken alone Y : particularly relevant if combined with another document of the same category A : technological background O : non-written disclosure P : intermediate document T : theory or principle underlying the invention E : earlier patent document, but published on, or after the filing date D : document cited in the application L : document cited for other reasons & : member of the same patent family, corresponding document			

2
EPO FORM 1503 03.82 (P04C01)

**ANNEX TO THE EUROPEAN SEARCH REPORT
ON EUROPEAN PATENT APPLICATION NO.**

EP 10 18 1718

This annex lists the patent family members relating to the patent documents cited in the above-mentioned European search report.
The members are as contained in the European Patent Office EDP file on
The European Patent Office is in no way liable for these particulars which are merely given for the purpose of information.

18-03-2011

Patent document cited in search report	Publication date	Patent family member(s)	Publication date
EP 0884626 A2	16-12-1998	CN 1211745 A	24-03-1999
		CN 1550832 A	01-12-2004
		CN 1550833 A	01-12-2004
		CN 1550852 A	01-12-2004
		CN 1550834 A	01-12-2004
		DE 69838927 T2	26-02-2009
		EP 1103840 A2	30-05-2001
		EP 1113311 A2	04-07-2001
		EP 1111441 A2	27-06-2001
		EP 1113312 A2	04-07-2001
		EP 1413915 A2	28-04-2004
		EP 1411385 A2	21-04-2004
		EP 1621923 A1	01-02-2006
		EP 1870767 A1	26-12-2007
		EP 1930767 A2	11-06-2008
		EP 1930768 A1	11-06-2008
		EP 2068196 A2	10-06-2009
		EP 2085815 A1	05-08-2009
		JP 11258605 A	24-09-1999
		JP 11258606 A	24-09-1999
		JP 2947350 B2	13-09-1999
		JP 11242225 A	07-09-1999
		JP 3565771 B2	15-09-2004
		JP 2001100211 A	13-04-2001
		JP 3556159 B2	18-08-2004
		JP 2001083523 A	30-03-2001
		JP 3556160 B2	18-08-2004
		JP 2001108823 A	20-04-2001
		JP 4007846 B2	14-11-2007
		JP 2002365636 A	18-12-2002
		JP 3795048 B2	12-07-2006
		JP 2004157569 A	03-06-2004
		JP 3770893 B2	26-04-2006
		JP 2004213036 A	29-07-2004
		JP 3872797 B2	24-01-2007
		JP 2004252479 A	09-09-2004
		JP 3872798 B2	24-01-2007
		JP 2004252480 A	09-09-2004
		JP 3872799 B2	24-01-2007
		JP 2004220050 A	05-08-2004
		JP 4166250 B2	15-10-2008
		JP 2006209143 A	10-08-2006
		JP 4030569 B2	09-01-2008
		JP 2006301670 A	02-11-2006
		JP 4197537 B2	17-12-2008
		JP 2007256987 A	04-10-2007

EPO FORM P0459

For more details about this annex : see Official Journal of the European Patent Office, No. 12/82

**ANNEX TO THE EUROPEAN SEARCH REPORT
ON EUROPEAN PATENT APPLICATION NO.**

EP 10 18 1718

This annex lists the patent family members relating to the patent documents cited in the above-mentioned European search report.
The members are as contained in the European Patent Office EDP file on
The European Patent Office is in no way liable for these particulars which are merely given for the purpose of information.

18-03-2011

Patent document cited in search report	Publication date	Patent family member(s)	Publication date
EP 0884626	A2	JP 4255509 B2	15-04-2009
		JP 2008310358 A	25-12-2008
		JP 2009086683 A	23-04-2009

EPO FORM P0459

For more details about this annex : see Official Journal of the European Patent Office, No. 12/82

专利名称(译)	液晶显示器		
公开(公告)号	EP2320264A1	公开(公告)日	2011-05-11
申请号	EP2010181718	申请日	2000-05-23
[标]申请(专利权)人(译)	三星电子株式会社		
申请(专利权)人(译)	SAMSUNG ELECTRONICS CO. , LTD.		
当前申请(专利权)人(译)	三星DISPLAY CO. , LTD.		
[标]发明人	SONG JANG KUN RYU JAE JIN		
发明人	SONG, JANG-KUN RYU, JAE-JIN		
IPC分类号	G02F1/13 G02F1/1337 G02F1/1333 G02F1/1335 G02F1/1343 G02F1/136 G02F1/139		
CPC分类号	G02F1/134309 G02F1/133707 G02F1/134336 G02F1/1393 G02F2001/13373 G02F2001/133742 G02F2001/134318 G02F2001/134345 G02F2001/134372 G02F2201/123		
优先权	1019990042216 1999-10-01 KR		
其他公开文献	EP2320264B1		
外部链接	Espacenet		

摘要(译)

液晶显示器包括具有顶表面和底表面的第一绝缘基板。像素电极形成在第一绝缘基板的顶表面上，像素电极具有第一开口图案。第二绝缘基板具有顶表面和底表面。公共电极形成在第二绝缘基板的底表面上，公共电极具有第二开口图案。液晶层夹在第一基板和第二基板之间。第一开口图案和第二开口图案均具有中间，第一和第二开口，开口交替地布置，除了第二开口图案的中间开口的主干开口与第一开口图案的中间开口重叠之外。后备箱开口是中间开口和第二开口图案的一部分。

