

(19)



(11)

EP 2 423 911 A2

(12)

EUROPEAN PATENT APPLICATION

(43) Date of publication:

29.02.2012 Bulletin 2012/09

(51) Int Cl.:

G09G 3/36 ^(2006.01)(21) Application number: **11190094.0**(22) Date of filing: **13.12.2004**


(84) Designated Contracting States:

**AT BE BG CH CY CZ DE DK EE ES FI FR GB GR
HU IE IS IT LI LT LU MC NL PL PT RO SE SI SK TR**• **Ben-chorin, Moshe****76262 Rehovot (IL)**• **Malka, Doron****67458 Tel Aviv (IL)**(30) Priority: **15.12.2003 US 529101 P****26.08.2004 US 604461 P**(62) Document number(s) of the earlier application(s) in
accordance with Art. 76 EPC:**04801607.5 / 1 704 555**(74) Representative: **Dr. Graf & Partner AG****Intellectual Property****Herrenacker 15****Postfach 518****8201 Schaffhausen (CH)**(71) Applicant: **Genoa Color Technologies Ltd.****Herzliya 46733 (IL)**

Remarks:

This application was filed on 22-11-2011 as a
divisional application to the application mentioned
under INID code 62.

(72) Inventors:

• **Roth, Shmuel****49550 Petach Tikva (IL)**(54) **Multi-primary liquid crystal display**(57) A display device comprising a plurality of pixels,
wherein at least some of said pixels comprise a red sub-
pixel, a green sub-pixel, a blue sub-pixel, and a yellowsub-pixel, wherein an area of the blue sub-pixel is greater
than an area of the yellow sub-pixel or the green sub-
pixel.

200

FIG. 2**EP 2 423 911 A2**

DescriptionField Of The Invention

5 **[0001]** The invention relates generally to multi-primary color displays and, more particularly, to multi-primary Liquid Crystal Displays (LCDs).

Background

10 **[0002]** A Liquid Crystal Display device includes an array of Liquid Crystal (LC) elements, which may be driven, for example, by one or more Thin Film Transistor (TFT) elements. In some LCD devices, the LC array may include a plurality of column line drivers and a plurality of row line drivers to allow controlling each element of the LC array.

[0003] The TFTs, the row line drivers and the column line drivers may block part of the light provided to the LC array, and consequently reduce the level of brightness of the display. Thus, it may be desired to reduce the amount of light
15 blocked by the TFTs, the row line drivers and the column line drivers. Furthermore, it may be desired to reduce the number of the TFTs, the row line drivers and/or the column line drivers in order to reduce the cost of the display.

Summary Of Embodiments of The Invention

20 **[0004]** Embodiments of the invention include a method, device and/or system for displaying a color image having a plurality of more-than-three primary color pixels.

[0005] According to some exemplary embodiments of the invention, the device may include, for example, an array of sub-pixel elements of at least four different primary colors, wherein the total number of sub-pixel elements in the array may be significantly smaller than a multiplication product of the number of more-than-three-primary color pixels in the
25 image multiplied by the number of the at least four different primary colors.

[0006] According to some exemplary embodiments of the invention, the color display device may include an array of sub-pixel elements of at least four different primary colors arranged in at least first and second repeatable color sequences of sub-pixel elements of at least three primary colors, wherein the first color sequence may include at least one sub-pixel element of a primary color not included in the second sequence, and/or the second color sequence may include
30 at least one sub-pixel element of a primary color not included in the first sequence.

[0007] According to some exemplary embodiments of the invention, the sub-pixel elements of the array are may be arranged in a repeatable pattern including sub-pixel elements of each of the at least four primary colors. The pattern may include, for example, less sub-pixel elements of a first primary color than sub-pixel elements of a second primary color.

[0008] According to some exemplary embodiments of the invention, the color display device may include a controller
35 able to selectively activate at least some sub-pixel elements of the array to produce one or more attenuation patterns based on sub-pixel data representing pixels of the color image.

[0009] According to some exemplary embodiments of the invention, sub-pixel elements of the first and second color sequences may be activated based on sub-pixel data corresponding to at least first and second pixels of the color image. For example, at least one sub-pixel element of at least one of the first and second sequences may be activated, based
40 on a value determined by a combination of sub-pixel data of the at least first and second pixels.

[0010] According to some exemplary embodiments, the at least one sub-pixel element to be activated may include, for example, the sub-pixel element of the primary color not included in the second sequence, and the sub-pixel data may include sub-pixel data of the at least first and second pixels corresponding to the primary color not included in the second sequence.

45 **[0011]** According to some exemplary embodiments, a sub-pixel element of the second sequence may be activated, for example, based on a value determined by a combination of sub-pixel data of the sub-pixel element to be activated and the primary color not included in the second sequence.

[0012] According to some exemplary embodiments of the invention, a first sub-pixel element of the second sequence may be activated based on a value determined by a combination of sub-pixel data of the second pixel corresponding
50 to the primary color of the first sub-pixel element, and a first correction component; a second sub-pixel element of the second sequence may be activated based on a value determined by a combination of sub-pixel data of the second pixel corresponding to the primary color of the second sub-pixel element, and a second correction component; and/or the sub-pixel element of the primary color not included in the second sequence may be activated based on a value determined by a combination of sub-pixel data of the first pixel corresponding to the primary color not included in the second
55 sequence, and a third correction component.

Brief Description Of The Drawings

[0013] The invention will be understood and appreciated more fully from the following detailed description of embodiments of the invention, taken in conjunction with the accompanying drawings of which:

Fig. 1 is a schematic illustration of a more-than-three primary color display system in accordance with exemplary embodiments of the invention;

Fig. 2 is a schematic illustration of a sub-pixel configuration including a repeatable pattern of sub-pixel elements, in accordance with one exemplary embodiment of the invention;

Figs. 3A and 3B are schematic illustrations of a first 5-primary pattern of sub-pixel elements and a second 5-primary pattern of sub-pixel elements, respectively, which may be implemented to form sub-pixel configurations in accordance with other exemplary embodiments of the invention;

Fig. 4 is a schematic illustration of a sub-pixel configuration including a repeatable pattern of sub-pixel elements, in accordance with yet another exemplary embodiment of the invention; and

Fig. 5 is a schematic illustration of a pattern of sub-pixel elements, which may be implemented to form a sub-pixel configuration in accordance with additional exemplary embodiments of the invention.

[0014] It will be appreciated that for simplicity and clarity of illustration, elements shown in the figures have not necessarily been drawn accurately or to scale. For example, the dimensions of some of the elements may be exaggerated relative to other elements for clarity or several physical components included in one element. Further, where considered appropriate, reference numerals may be repeated among the figures to indicate corresponding or analogous elements. It will be appreciated that these figures present examples of embodiments of the present invention and are not intended to limit the scope of the invention.

Detailed Description Of Embodiments Of The Invention

[0015] In the following description, various aspects of the present invention will be described. For purposes of explanation, specific configurations and details are set forth in order to provide a thorough understanding of the present invention. However, it will be apparent to one skilled in the art that the present invention may be practiced without the specific details presented herein. Furthermore, some features of the invention relying on principles and implementations known in the art may be omitted or simplified to avoid obscuring the present invention.

[0016] Embodiments of monitors and display devices with more than three primaries, in accordance with exemplary embodiments of the invention, are described in International Application PCT/IL02/00452, filed June 11, 2002, entitled "DEVICE, SYSTEM AND METHOD FOR COLOR DISPLAY" and published 19 December 2002 as PCT Publication WO 02/101644, the disclosure of which is incorporated herein by reference.

[0017] Reference is made to Fig. 1, which schematically illustrates a more-than-three primary color display system 100 in accordance with exemplary embodiments of the invention.

[0018] According to exemplary embodiments of the invention, system 100 may include a light source 112, and an array of sub-pixel elements. For example, system 100 may include an array 113 of liquid crystal (LC) elements (cells) 114, for example, an LC array using Thin Film Transistor (TFT) active-matrix technology, as is known in the art; and an n-primary-color filter array 116, wherein n is greater than three, which may be, for example, juxtaposed to array 113. System 100 may include any other suitable configuration of sub-pixel elements. System 100 may further include electronic circuits 120 ("drivers") for driving the cells of array 114, e.g., by active-matrix addressing, as is known in the art. According to some exemplary embodiments of the invention, a pixel of a color image may be reproduced by sub-pixel elements of more than three primary colors, wherein each sub-pixel element corresponds to one of the n primary colors. Back-illumination source 112 provides the light needed to produce the color images. The transmittance of each of the sub-pixel elements may be controlled, for example, by the voltage applied to a corresponding LC cell of array 113, based on image data input for one or more corresponding pixels, as described below. An n-primaries controller 118 may be able to receive the image data including sub-pixel data representing pixels of the color image, and to selectively activate at least some of the sub-pixel elements of array 113 to produce an attenuation pattern based on the sub-pixel data. For example, controller 118 may receive the input data, e.g., in Red (R), Green (G), and Blue (B) or YCbCr format, optionally scale the data to a desired size and resolution, and adjust the magnitude of the signal delivered to the different drivers based on the input data. Controller 118 may be able to convert input image data, e.g., data including RGB image components or YCbCr data of a pixel, into sub-pixel data of more than three primary colors, e.g., R, G, B, Yellow (Y), and Cyan (C). The intensity of white light provided by back-illumination source 112 may be spatially modulated by elements of the LC array, selectively controlling the illumination of each sub-pixel element according to the image data for one or more pixels, as described below. The selectively attenuated light of each sub-pixel passes through a corresponding color filter of color filter array 116, thereby producing desired color sub-pixel combinations. The human vision

system spatially integrates the light filtered through the different color sub-pixel elements to perceive a color image.

[0019] An aperture ratio of a LCD display may be defined as the ratio between the net area of the display and the overall area of the display, wherein the net area of the display is defined as the overall area of the display excluding a total area of blocking, e.g., a total of areas of the display "blocked" by TFTs and the column and row driver lines, as is known in the art. For example, the total area of blocking of a display including l rows of m sub-pixel elements, wherein each sub-pixel element includes one TFT, wherein each row includes one row driver line, and wherein each column includes one column driver, may be calculated as follows:

$$m * L_{column} * t_{column} + l * L_{row} * t_{row} + l * m * S_{tft} \quad (1)$$

wherein S_{tft} denotes the blocking area of each TFT, L_{row} and t_{row} denote the length and width of each row driver line, respectively, and L_{column} and t_{column} denote the length and width of each column driver line, respectively. Accordingly, the overall area of the display may be approximately $L_{column} * L_{row}$, and the aperture ratio of the display may be calculated assuming an aspect ratio $AR = L_{row} / L_{column}$.

[0020] It will be appreciated by those skilled in the art that a higher total area of blocking may correspond to a lower brightness level of the display, since a larger amount of the light provided to the display is blocked by the TFTs and/or driver lines.

[0021] According to some exemplary embodiments of the invention, system 100 may be implemented for reproducing a color image having a plurality of more-than-three primary color pixels, using an array of sub-pixel elements of at least four different primary colors, wherein the total number, denoted S_T , of sub-pixel elements in the array is significantly smaller than a product $P = s * n$, wherein s denotes the number of more-than-three-primary color pixels in the image, and wherein n denotes the number of the at least four different primary colors, as described in detail below. For example, the number of sub-pixel elements in the array as a fraction of the product P may be related to the number of the four or more primary colors. The array may include, for example, sub-pixel elements arranged in at least one repeatable color sequence of sub-pixel elements of at least three primary colors, and the total number of sub-pixel elements in the array as a fraction of the product P may be equal to approximately the number of sub-pixel elements in the color sequence divided by the number of the four or more primary colors, as described below.

[0022] The human vision system may perceive different primary colors in different levels of spatial resolution. For example, the human vision may perceive some primary colors, e.g., blue and cyan, in a substantially lower level of spatial resolution in comparison to the perceived spatial resolution level of other primary colors, e.g., green, yellow and red. Thus, according to embodiments of the invention, some of the primary colors, e.g., blue and/or cyan, may be displayed in a lower spatial resolution, e.g., using a smaller number of sub-pixel elements, as compared to other primary colors, e.g., red, green and/or yellow, without significantly affecting the over-all resolution of the color image perceived by the human vision system, as described below.

[0023] According to exemplary embodiments of the invention, the sub-pixel elements of array 113 may be arranged in a predetermined configuration including a predetermined repeatable pattern including a predetermined, fixed, number of sub-pixel elements, each corresponding to one of the n primary colors. For example, array 113 may include sub-pixel elements of at least four different primary colors arranged in at least first and second repeatable color sequences of sub-pixel elements of at least three primary colors, wherein the first color sequence includes at least one sub-pixel element of a primary color not included in the second sequence, as described below. Accordingly, the pattern may include a smaller number of sub-pixel elements corresponding to one or more predetermined primary colors compared to the number of sub-pixel elements corresponding to other primary colors. According to some of these exemplary embodiments, drivers 120 of some of the sub-pixel elements, e.g., the drivers of sub-pixel elements corresponding to the one or more predetermined primary colors, may be provided with a value corresponding to a combination of sub-pixel data of more than one pixel, as described below. This manipulation of image data may be performed, for example, by controller 118.

[0024] Reference is made to Fig. 2, which schematically illustrates a configuration 200 of sub-pixel elements in a five-primary display device including a repeatable pattern 201, in accordance with one exemplary embodiment of the invention.

[0025] Pattern 201 may include sub-pixel elements corresponding to five primary colors, e.g., red, yellow, green, cyan and blue, arranged in a row including eight sub-pixel elements.

[0026] According to an exemplary embodiment, pattern 201 may include a smaller number of sub-pixel elements corresponding to each of the blue and cyan primary colors in comparison to the number of sub-pixel elements corresponding to each of the red, green and yellow primary colors, as described below.

[0027] Pattern 201 may include two sub-pixel elements, e.g., sub-pixel elements 211 and 215, corresponding to the red primary color, two sub-pixel elements, e.g., sub-pixel elements 212 and 216, corresponding to the yellow primary color, two sub-pixel elements, e.g., sub-pixel elements 213 and 217, corresponding to the green primary color, one sub-

pixel element, e.g., sub-pixel element 214 corresponding to the cyan primary color, and one sub-pixel element, e.g., sub-pixel element 218, corresponding to the blue primary color.

[0028] According to this exemplary embodiment, configuration 200 may include sub-pixel elements arranged in at least first and second repeatable color sequences, e.g., color sequences 230 and 232. Sequence 230 may include at least one sub-pixel element, e.g., element 214, of a primary color, e.g., cyan, not included in sequence 232. Sequence 232 may include at least one sub-pixel element, e.g., element 218, of a primary color, e.g., blue, not included in sequence 230.

[0029] According to this exemplary embodiment, sequences 230 and 232 may each include sub-pixel elements of a predetermined sub-sequence of some of the primary colors, for example, a red-yellow-green sub-sequence. According to other embodiments of the invention one or more of the repeatable color sequences may include any other predetermined sub-color sequence.

[0030] According to some exemplary embodiments of the invention, each pixel of the color image may be reproduced by one or more sub-pixel elements of configuration 200. For example, a first pixel of the color image may be reproduced by sub-pixel elements 214, 215, 216, 217, and/or 218; and a second pixel, e.g., adjacent to the first pixel, may be reproduced by sub-pixel elements 218, 233, 234, 235 and/or 236. According to some embodiments of the invention, one or more sub-pixel elements of configuration 200, for example, sub-pixel elements corresponding to the blue and/or cyan primary colors, e.g., sub-pixel elements 214 and/or 218, may be activated based on a value determined by a combination of sub-pixel data corresponding to two or more pixels of the color image. Other sub-pixel elements of configuration 200, for example, sub-pixel elements corresponding to the green, red and/or yellow primary colors, e.g., sub-pixel elements 211, 212, 213, 215, 216, 217, 233, 234 and/or 235, may be activated based on sub-pixel data corresponding to one or more pixels. For example, one or more drivers, e.g. of drivers 120 (Fig. 1), of a sub-pixel element corresponding to one or more of the red, green or yellow primary colors, respectively, may be provided with a value corresponding to red, green and yellow sub-pixel data, respectively, of one or more pixels. This data arrangement may be provided by controller 118 (Fig. 1). A driver, e.g. of drivers 120 (Fig. 1), of a sub-pixel element corresponding to a primary color not included in one of sequences 230 and 232 may be provided with a value determined by a combination of sub-pixel data of two or more pixels. For example, a driver of a sub-pixel element corresponding to the cyan primary color may be provided with a value determined by a combination, e.g., an arithmetic average, a weighted average and/or any other suitable combination, of cyan sub-pixel data of two or more pixels. A driver, e.g. of drivers 120 (Fig. 1), of a sub-pixel element corresponding to a blue sub-pixel may be provided, for example, with a value determined by a combination, e.g., an arithmetic average, a weighted average and/or any other suitable combination, of blue sub-pixel data of two or more pixels. The two or more pixels may include, for example, two or more neighboring pixels, e.g., two or more vertically, horizontally and/or diagonally adjacent pixels, or any other two or more pixels of the color image. Thus, it will be appreciated by those skilled in the art that since the sub-pixel elements of pattern 201 may be activated to reproduce two pixels, the size of an effective pixel corresponding to configuration 200 ("the effective pixel size") may be equal to half the sum of the areas of the sub-pixel elements of pattern 201. Controller 118 (Fig. 1) may rearrange the sub-pixel data to provide the desired sequences of values to drivers 120.

[0031] According to exemplary embodiments of the invention, the size of some of the sub-pixel elements may be different than the size of other sub-pixel elements in order to achieve a desired white balance of the display. For example, the area covered by each sub-pixel element corresponding to the blue and/or the cyan primaries may be larger than the area covered by each sub-pixel element corresponding to the red, yellow and/or green primaries.

[0032] It will be appreciated by those skilled in the art that a display system, e.g., system 100 (Fig. 1), implementing configuration 200 for reproducing a color image including l rows of s 5-primary pixels, may include $4*s$ column driver lines and l row driver lines. Such a display may also include $4*s/l$ TFTs, e.g., one TFT located on each sub-pixel element. Accordingly, a total blocking area of such a display may be equal to:

$$4*s*L_{column}*t_{column}+l*L_{row}*t_{row}+4*l*s*S_{tft} \quad (2)$$

[0033] It will be appreciated by those skilled in the art that a display according to the exemplary embodiments described above, may include a smaller number of column driver lines and a smaller number of TFTs compared to the number of column driver lines, e.g., $5*s$, and the number of TFTs, e.g., $5*s/l$, of other 5-primary display systems, e.g., wherein sub-pixel elements of five primary colors are used for reproducing each pixel. Consequently, a display according to the exemplary embodiments described above, may also have a relatively smaller total blocking area resulting in a higher brightness level, compared to the total blocking area, e.g., $5*s*L_{column}*t_{column}+l*L_{row}*t_{row}+5*s*S_{tft}$, and the resulting brightness level of other 5-primary display systems. For example, a 1280X720 display having a 16:9 aspect ratio, i.e., $s=1280$, $l=720$ and $L_{row}=16/9*L_{column}$, may have an aperture ratio of approximately 70%, i.e., a total area of blocking of approximately 30%, if sub-pixel elements of five primary colors are used for reproducing each pixel. Assuming the total

area of blocking includes 6% TFT blocking, and 24% driver lines blocking, and assuming $t_{row}=t_{column}$, it will be appreciated by those skilled in the art that implementing sub-pixel arrangement 200 may reduce the TFT blocking to approximately 5%, and the driver line blocking to approximately 20%. Accordingly, the aperture ratio of such a display implementing arrangement 200 may be increased by approximately 5%, e.g. to an approximate value of 75%. Furthermore, implementing sub-pixel arrangement 200 may reduce the number of column drivers by approximately 20%, which may result in a reduction in a data rate required for activating the sub-pixel elements of pattern 200

[0034] It will be appreciated by those skilled in the art that according to other embodiments of the invention, any other suitable pattern of sub-pixel elements, e.g., including any suitable two or more repeatable color sequences, may be implemented by display system 100 (Fig. 1) to form a sub-pixel configuration similar to configuration 200, e.g., as described below.

[0035] Reference is also made to Figs. 3A and 3B which schematically illustrate a first 5-primary pattern 300 of sub-pixel elements and a second 5-primary pattern 310 of sub-pixel elements, respectively, which may be implemented to form configuration 200 according to other exemplary embodiments of the invention.

[0036] Pattern 300 may include two different rows, e.g., row 302 and row 304. Row 302 may include sub-pixel elements arranged, for example, in the order "yellow-green-red-cyan-yellow-green-red-blue". Row 304 may include sub-pixel elements arranged, for example, in the order "yellow-green-red-blue-yellow-green-red-cyan". Accordingly, pattern 300 may include a first color sequence 303, e.g., including sub-pixels elements of the primary colors "yellow-green-red-cyan", and a second color sequence 305, e.g., including sub-pixels elements of the primary colors "yellow-green-red-blue".

[0037] Pattern 310 may include two different rows, e.g., row 312 and row 314. Row 312 may include sub-pixel elements arranged, for example, in the order "red-yellow-green-cyan-red-yellow-green-blue". Row 314 may include sub-pixel elements arranged, for example, in the order "red-yellow-green-blue-red-yellow-green-cyan". Accordingly, pattern 310 may include a first color sequence 313, e.g., including sub-pixels elements of the primary colors "red-yellow-green-cyan", and a second color sequence 315, e.g., including sub-pixels elements of the primary colors "red-yellow-green-blue". According to other embodiments of the invention pattern 300 and/or pattern 310 may include any other suitable configuration of sub-pixel elements.

[0038] It will be appreciated by those skilled in the art that a pattern, e.g., pattern 300 or pattern 310, wherein the location of the cyan and blue primary colors is interchanged along the columns, may be implemented to achieve a more uniform color distribution across the display.

[0039] According to some embodiments of the invention, an effective pixel of the color image may be reproduced by sub-pixel elements of more than one row, as described below.

[0040] Reference is made to Fig. 4, which schematically illustrates a configuration 400 of sub-pixel elements in a five-primary display device including a repeatable pattern 401, in accordance with another exemplary embodiment of the invention.

[0041] Pattern 401 may include sub-pixel elements corresponding to five primary colors, e.g., red, yellow, green, cyan and blue, arranged in two adjacent rows, e.g., rows 410 and 420.

[0042] According to an exemplary embodiment, pattern 401 may include a smaller number of sub-pixel elements corresponding to each of the blue and cyan primary colors in comparison to the number of sub-pixel elements corresponding to each of the red, green and yellow primary colors, as described below.

[0043] Row 420 may include four sub-pixel elements 412, 416, 415, and 434 corresponding to the primary colors red, yellow, red and yellow, respectively. Row 410 may include four sub-pixel elements 413, 414, 417, and 418 corresponding to the primary colors green, cyan, green and blue, respectively.

[0044] According to this exemplary embodiment, the sub-pixel elements of pattern 401 may be arranged in at least first and second repeatable color sequences, e.g., color sequences 460 and 462. Sequence 460 may include at least one sub-pixel element, e.g., element 414, of a primary color, e.g., cyan, not included in sequence 462. Sequence 462 may include at least one sub-pixel element, e.g., element 418, of a primary color, e.g., blue, not included in sequence 460.

[0045] According to this exemplary embodiment, sequences 460 and/or 462 may include sub-pixel elements of a predetermined sub-sequence of some of the primary colors, for example, a red-yellow-green sub-sequence.

[0046] According to some exemplary embodiments of the invention, each pixel of the color image may be reproduced by one or more sub-pixel elements of configuration 400. For example, a first pixel of the color image may be reproduced by sub-pixel elements 416, 415, 414, 417 and/or 418; and a second pixel, e.g., adjacent to the first pixel, may be reproduced by sub-pixel elements 434, 418, 433, 435 and/or 436. According to some embodiments of the invention, one or more sub-pixel elements of configuration 400, for example, sub-pixel elements corresponding to the blue and/or cyan primary colors, e.g., sub-pixel elements 414 and/or 418, may be activated based on a value determined by a combination of sub-pixel data corresponding to two or more pixels of the color image. Other sub-pixel elements of configuration 400, for example, sub-pixel elements corresponding to the green, red and/or yellow primary colors, e.g., sub-pixel elements 416, 415, 417, 434, 435 and/or 433, may be activated based on sub-pixel data corresponding to one or more pixels. For example, one or more drivers, e.g. of drivers 120 (Fig. 1), of a sub-pixel element corresponding to

one or more of the red, green and/or yellow primary colors, respectively, may be provided a value corresponding to red, green and/or yellow sub-pixel data, respectively, of one or more pixels. This data arrangement may be provided by controller 118 (Fig. 1). A driver, e.g. of drivers 120 (Fig. 1), of a sub-pixel element corresponding to the cyan primary color may be provided with a value determined by a combination, e.g., an arithmetic average, a weighted average and/or any other suitable combination, of cyan sub-pixel data corresponding to two or more pixels. A driver, e.g. of drivers 120 (Fig. 1), of a sub-pixel element corresponding to a blue sub-pixel may be provided with a value determined by a combination, e.g., an arithmetic average a weighted average and/or any other suitable combination, of blue sub-pixel data corresponding to two or more pixels. The two or more pixels may include, for example, two or more neighboring pixels, e.g., two or more vertically, horizontally and/or diagonally adjacent pixels, or any other two or more pixels of the color image. Thus, it will be appreciated by those skilled in the art that since the sub-pixel elements of pattern 401 may be activated to reproduce two pixels, the effective pixel size corresponding to configuration 400 may be equal to half the sum of the areas of the sub-pixel elements of pattern 401. Controller 118 (Fig. 1) may rearrange the sub-pixel data to provide the desired sequences of values to drivers 120.

[0047] According to exemplary embodiments of the invention, the size of some of the sub-pixel elements may be different from the size of other sub-pixel elements in order to achieve a desired white balance of the displayed image. For example, the area of each sub-pixel element corresponding to the blue and/or the cyan primaries may be larger than the area of each sub-pixel element corresponding to the red, yellow and/or green primaries.

[0048] It will be appreciated by those skilled in the art, that a display system, e.g., system 100 (Fig. 1), implementing configuration 400 for reproducing a color image including l rows of s 5-primary pixels, may include $2*s$ column driver lines and $2*l$ row driver lines. Such a display may also include $4*s*l$ TFTs, e.g., one TFT located on each sub-pixel element. Accordingly, a total blocking area of such a display may be equal to:

$$2*s*L_{column}*t_{column} + 2*l*L_{row}*t_{row} + 4*l*s*S_{tft} \quad (3)$$

[0049] It will be appreciated by those skilled in the art that the over-all cost of driver lines of a 5-primary display implementing configuration 400 may be lower compared to the cost of driver lines of a conventional 3-primary LCD display, e.g., a display including $3*s$ column driver lines and l row driver lines, because the cost of a column driver line is generally higher than the cost of a row driver line. It will also be appreciated by those skilled in the art, that the over-all cost of a 5-primary display implementing configuration 400 may be lower compared to the over-all cost of some four-primary displays, wherein sub-pixel elements of four or five primaries are used for reproducing each pixel, and of some five-primary displays, wherein sub-pixel elements of five primary colors are used for reproducing each pixel.

[0050] It will further be appreciated by those skilled in the art that a display according to the exemplary embodiments described above may have a total blocking area of $2*s*L_{column}*t_{column} + 2*l*L_{row}*t_{row} + 4*l*s*S_{tft}$, compared to the total blocking area of a conventional 3-primary LCD display, e.g., $3s*L_{column}*t_{column} + l*L_{row}*t_{row} + 3*l*s*S_{tft}$. Furthermore, if $L_{row} = 16/9*L_{column}$, $s = 1280$, and $l = 720$, an aperture ratio of approximately 78% may be achieved if configuration 400 is implemented, which is higher than the achievable aperture ratio, e.g., 75%, corresponding to configuration 200, which in turn is higher than the achievable aperture ratio, e.g., 70%, corresponding to a five-primary display wherein sub-pixel elements of five primary colors are used for reproducing each pixel.

[0051] It will be appreciated by those skilled in the art that according to other embodiments of the invention, any other suitable pattern of sub-pixel elements, e.g., including any suitable two or more repeatable color sequences, may be implemented by display system 100 (Fig. 1) to form a configuration similar to configuration 400, e.g., as described below.

[0052] Reference is also made to Fig. 5, which schematically illustrates a 5-primary pattern 500 of sub-pixel elements, which may be implemented to form a sub-pixel configuration according to other exemplary embodiments of the invention.

[0053] Pattern 500 may include four rows, e.g., row 502, row 504, row 506, and row 508. Row 504 and row 508 may be identical and may each include a 2-primary sequence, for example, a sequence "red-yellow-red-yellow". Row 506 and row 508 may include a 3-primary sequence, e.g., "green-cyan-green-blue" and a 3-primary sequence, e.g., "green-blue-green-cyan", respectively. It will be appreciated by those skilled in the art that a pattern, e.g., pattern 500, wherein the location of the cyan and blue primary colors is interchanged along the columns, may be implemented to achieve a more uniform color distribution across the display.

[0054] Some exemplary embodiments of the invention, e.g., as are described above, may relate to a controller, e.g., controller 118 (Fig. 1) able to provide a driver of a sub-pixel element corresponding to the cyan primary color with a value determined based on a combination of sub-pixel data corresponding to the cyan primary color of two or more pixels, and/or to provide a driver of a sub-pixel element corresponding to the blue primary color with a value determined based on a combination of sub-pixel data corresponding to the blue primary color of two or more pixels. However, other exemplary embodiments of the invention may include a controller, e.g., controller 118 (Fig. 1) able to provide the drivers of one or more sub-pixel elements with a value determined based on any other desired combination of sub-pixel data

of one or more pixels, e.g., as described below.

[0055] According to some embodiments of the invention, controller 118 (Fig. 1) may be able to provide drivers, e.g., drivers 120 (Fig. 1), corresponding to sub-pixel elements of at least first and second color sequences, e.g., as are described above, based on sub-pixel data corresponding to at least first and second pixels of the color image. Controller 118 (Fig. 1) may be able, for example, to activate at least one sub-pixel element of at least one of the first and second sequences, based on a value determined by a combination of sub-pixel data of at least the first and second pixels, as described below.

[0056] According to some exemplary embodiments of the invention, controller 118 (Fig. 1) may be able to activate a sub-pixel element of the first/second sequence based on a value determined by a combination of sub-pixel data of the sub-pixel element to be activated and the primary color not included in the first/second sequence. For example, controller 118 (Fig. 1) may be able to provide the drivers of green sub-pixel elements with a value determined based on a combination of green sub-pixel data and cyan sub-pixel data of a pixel; and/or to provide the drivers of blue sub-pixel elements with a value determined based on a combination of blue sub-pixel data and cyan sub-pixel data of a pixel. Alternatively or additionally controller 118 may be able to provide the drivers of cyan sub-pixel elements with a value determined based on a combination of blue sub-pixel data and cyan sub-pixel data of a pixel; and/or to provide the drivers of red sub-pixel elements with a value determined based on a combination of blue sub-pixel data and red sub-pixel data of a pixel.

[0057] In some embodiments, the green, blue and cyan primaries of a display, e.g., display 100 (Fig. 1) may be represented by predetermined green, blue and cyan primary color vectors in the XYZ color space, denoted $\vec{P}_G$, $\vec{P}_B$ and $\vec{P}_C$ respectively.

[0058] According to some exemplary embodiments of the invention, a combination, e.g., a linear combination, of the green and blue primary color vectors, may be implemented to produce a color approximately equivalent or comparable to the cyan primary color. A desired linear combination may be determined, for example, using the following equation:

$$\vec{P}_C \cong \beta \vec{P}_B + \gamma \vec{P}_G \quad (4)$$

wherein β and γ denote parameters relating to the linear contributions of the blue and green primary colors, respectively. It will be appreciated that the linear combination according to Equation 4 may be used to reproduce a color equivalent to the cyan primary color, e.g., if the chromaticity value of the cyan primary color is located on a line connecting the chromaticity values of the green and blue primary colors, or comparable to the cyan primary color, e.g., if the chromaticity value of the cyan primary color is located off but relatively proximal to the line connecting the chromaticity values of the green and blue primary colors.

[0059] As described above, some pixels of display 100 may be reproduced by a plurality of sub-pixel elements not including a blue sub-pixel element ("non-blue sub-pixel elements"), and/or some pixels may be reproduced by a plurality of sub-pixel elements not including a cyan sub-pixel ("non-cyan sub-pixel elements"). According to exemplary embodiments of the invention, controller 118 (Fig. 1) may be able to provide the drivers of one or more non-cyan sub-pixel elements with a value determined based on cyan sub-pixel data. For example, controller 118 (Fig. 1) may provide the drivers of blue and/or green sub-pixel elements for reproducing a pixel with signals B' and G', respectively, e.g., according to the following equation set:

$$\begin{aligned} B' &= B + C \cdot \beta \\ G' &= G + C \cdot \gamma \end{aligned} \quad (5)$$

wherein B, G, and C denote the blue, green and cyan image components of the pixel to be reproduced. According to some exemplary embodiments of the invention, the values of one or both of B' and/or G' may be "clipped", i.e., set to a maximal producible value of the blue and green primary colors, respectively, e.g., if the values of B' and/or G' calculated according to Equation 5 exceed the maximal producible value of the blue and/or green primary colors, respectively.

[0060] It will be appreciated by those skilled in the art, that activating blue and/or green sub-pixel elements based on cyan sub-pixel data may improve the perceived spatial resolution of the cyan primary color and/or reduce a perceived luminance variation between a pixel reproduced by non-blue sub-pixel elements and a pixel reproduced by non-cyan sub-pixel elements.

[0061] According to some exemplary embodiments of the invention, it may be desired to reduce a color shift, e.g., a cyan color shift, which may result, for example, from activating one or more non-cyan sub-pixel elements based on a value determined by cyan sub-pixel data. Such a color shift may be reduced, according to some exemplary embodiments of the invention, by activating a blue sub-pixel element, e.g., of a first color sequence, based on a corrected value

determined by a combination, e.g., a sum, of blue sub-pixel data of a first pixel and a blue correction component, ΔB ; activating a green sub-pixel element, e.g., of the first color sequence, based on a corrected value determined by a combination, e.g., a sum, of green sub-pixel data of the first pixel and a green correction component, ΔG ; and activating a cyan sub-pixel element, for example, of a second color sequence, e.g., adjacent to the first color sequence, based on a corrected value determined by a combination of, e.g., a difference between, cyan sub-pixel data of a second pixel and a cyan correction component, ΔC , as described below.

[0062] According to some exemplary embodiments of the invention, the correction components ΔC , ΔB , and ΔG may be determined such that the luminance of the cyan primary color reproduced by the cyan sub-pixel element is substantially equal to the sum of the luminance of the blue primary color reproduced by the blue sub-pixel element and the luminance of the green primary color resulting from the green correction component ΔG . Additionally, it may be desired that the amount of the cyan color resulting from the cyan correction component ΔC , will be substantially equal to the amount of a cyan-equivalent color reproduced by the green and blue sub-pixel elements, e.g., the sum of the amount of blue color resulting from the blue correction component, ΔB , and the amount of the green color resulting from the green correction component, ΔG . For example, the correction components may be determined using the following equations:

$$(C - \Delta C) \cdot Y_C = (B + \Delta B) \cdot Y_B + \Delta G \cdot Y_G \quad (6)$$

$$\Delta C \cdot \bar{P}_C = \Delta B \cdot \bar{P}_B + \Delta G \cdot \bar{P}_G \quad (7)$$

wherein Y_C , Y_B , and Y_G denote the luminance of the cyan, blue and green primary colors.

[0063] Substituting Equation 4 in Equation 7 and re-arranging terms may yield the following equations:

$$\Delta B = \beta \Delta C \quad (8)$$

$$\Delta G = \gamma \Delta C \quad (9)$$

[0064] Substituting Equations 8 and 9 in Equation 6 and rearranging terms may yield the following equation:

$$\Delta C = \frac{C \cdot Y_C - B \cdot Y_B}{Y_C + \beta \cdot Y_B + \gamma \cdot Y_G} \quad (10)$$

[0065] According to exemplary embodiments of the invention, controller 118 (Fig. 1) may determine a value for the cyan correction component ΔC , e.g., by substituting in Equation 10 the primary color luminance values Y_C , Y_B , and Y_G , predefined parameters β and γ , and the cyan and a value corresponding to the blue sub-pixel data of the first pixel. Controller 118 may additionally determine a value for the blue correction component ΔB and/or a value for the green correction component ΔG , e.g., using Equations 8 and 9. Controller 118 may provide the blue, green and cyan sub-pixel elements with corrected values, e.g., based on the correction components ΔB , ΔG , and ΔC , e.g., as described above.

[0066] According to some exemplary embodiments of the invention, the corrected value provided to the blue sub-pixel and/or the corrected value provided to the green sub-pixel may be clipped, e.g., if the corrected value provided to the blue sub-pixel element and/or the corrected value provided to the green sub-pixel element exceed the maximal producible value of the blue and/or green primary colors, respectively.

[0067] Some exemplar embodiments of the invention, e.g., as are described above, relate to activating green and/or blue sub-pixel elements based on cyan sub-pixel data; and/or activating green, blue and/or cyan sub-pixel elements based on corrected values. However, other embodiments of the invention may analogously be implemented for activating one or more other sub-pixel elements, e.g., a cyan sub-pixel element or cyan and red sub-pixel elements, based on other sub-pixel data, e.g., blue sub-pixel data; and/or activating other sub-pixel elements, e.g., cyan red and blue sub-pixel elements, based on corrected values. For example, in other embodiments, one or more sub-pixel elements may be activated based on any suitable combination of sub-pixel data of one or more pixels, e.g., a combination corresponding

to a spatial function of one or more pixels.

[0068] Although some of the exemplary devices, systems and/or methods described above are described in the context of devices for reproducing five primary colors, it will be appreciated by those skilled in the art, that similar devices, systems and/or methods may be implemented, with appropriate changes, in conjunction with devices for reproducing more or less than five primary colors.

[0069] While certain features of the invention have been illustrated and described herein, many modifications, substitutions, changes, and equivalents will now occur to those of ordinary skill in the art. It is, therefore, to be understood that the appended claims are intended to cover all such modifications and changes as fall within the true spirit of the invention.

Claims

1. A display device comprising a plurality of pixels, wherein at least some of said pixels comprise a red sub-pixel, a green sub-pixel, a blue sub-pixel, and a yellow sub-pixel, wherein an area of the blue sub-pixel is greater than an area of the yellow sub-pixel or the green sub-pixel.
2. The display device according to claim 1, wherein the area of the green sub-pixel is substantially the same as the area of the yellow sub-pixel.
3. The display device according to claim 1, wherein the area of the blue sub-pixel is greater than an area of the red sub-pixel.
4. The display device according to claim 3, wherein the area of the green sub-pixel is substantially the same as the area of the red sub-pixel.
5. The display device according to claim 3, wherein the area of the yellow sub-pixel is substantially the same as the area of the red sub-pixel.
6. The display device according to claim 1, wherein at least some of said pixels comprise a cyan sub-pixel.
7. The display device according to claim 6, wherein an area of the cyan sub-pixel is greater than the area of the green sub-pixel.
8. The display device according to claim 7, wherein the area of the blue sub-pixel is substantially the same as the area of the cyan sub-pixel.




FIG.1




FIG. 2




FIG. 3B





FIG. 3A






FIG. 5

REFERENCES CITED IN THE DESCRIPTION

This list of references cited by the applicant is for the reader's convenience only. It does not form part of the European patent document. Even though great care has been taken in compiling the references, errors or omissions cannot be excluded and the EPO disclaims all liability in this regard.


Patent documents cited in the description

- IL 0200452 W [0016]
- WO 02101644 A [0016]

专利名称(译)	多原色液晶显示器		
公开(公告)号	EP2423911A2	公开(公告)日	2012-02-29
申请号	EP2011190094	申请日	2004-12-13
[标]申请(专利权)人(译)	格诺色彩技术有限公司		
申请(专利权)人(译)	热那亚色彩技术有限公司.		
当前申请(专利权)人(译)	三星DISPLAY CO. , LTD.		
[标]发明人	ROTH SHMUEL BEN CHORIN MOSHE MALKA DORON		
发明人	ROTH, SHMUEL BEN-CHORIN, MOSHE MALKA, DORON		
IPC分类号	G09G3/36 G02F1/1335 G02F1/1343 G09G		
CPC分类号	G09G3/3611 G02F2201/52 G09G3/2003 G09G3/3607 G09G2300/0452 G09G2300/0465 G09G2340/0407 G09G2340/0457		
优先权	60/529101 2003-12-15 US 60/604461 2004-08-26 US		
其他公开文献	EP2423911A3		
外部链接	Espacenet		

摘要(译)

一种显示装置，包括多个像素，其中至少一些所述像素包括红色子像素，绿色子像素，蓝色子像素和黄色子像素，其中蓝色子像素的区域像素大于黄色子像素或绿色子像素的面积。



200

FIG. 2