



US008891044B2

(12) **United States Patent**  
**Hirota et al.**

(10) **Patent No.:** **US 8,891,044 B2**  
(45) **Date of Patent:** **Nov. 18, 2014**

(54) **COLOR DISPLAY, LIQUID CRYSTAL DISPLAY, AND SEMI-TRANSMISSIVE LIQUID CRYSTAL DISPLAY**

(58) **Field of Classification Search**  
USPC ..... 349/106-111, 139  
See application file for complete search history.

(75) Inventors: **Shoichi Hirota**, Hitachi (JP); **Shinichi Komura**, Mobara (JP); **Yoshifumi Sekiguchi**, Hitachiota (JP); **Tsunenori Yamamoto**, Hitachi (JP); **Masaya Adachi**, Hitachi (JP)

(56) **References Cited**

U.S. PATENT DOCUMENTS

2005/0128413 A1 \* 6/2005 Son et al. .... 349/143  
2005/0225574 A1 10/2005 Brown et al.  
2005/0225575 A1 10/2005 Brown Elliott et al.  
2005/0270444 A1 \* 12/2005 Miller et al. .... 349/108

(Continued)

FOREIGN PATENT DOCUMENTS

CN 1588197 3/2005  
JP H 10-319924 12/1998

(Continued)

OTHER PUBLICATIONS

Partial Translation of Office Action issued in Japanese Patent Application No. 2013-101198 dated Jan. 14, 2014.

*Primary Examiner* — Jessica M Merlin

(74) *Attorney, Agent, or Firm* — Antonelli, Terry, Stout & Kraus, LLP.

(73) Assignees: **Japan Display Inc.**, Tokyo (JP); **Panasonic Liquid Display Co., Ltd.**, Hyogo-ken (JP)

(\* ) Notice: Subject to any disclaimer, the term of this patent is extended or adjusted under 35 U.S.C. 154(b) by 987 days.

(21) Appl. No.: **11/869,770**

(22) Filed: **Oct. 10, 2007**

(65) **Prior Publication Data**

US 2008/0084376 A1 Apr. 10, 2008

(30) **Foreign Application Priority Data**

Oct. 10, 2006 (JP) ..... 2006-275967


(51) **Int. Cl.**  
**G02F 1/1333** (2006.01)  
**G02F 1/1335** (2006.01)  
**G09G 3/36** (2006.01)  
**G09G 3/20** (2006.01)

(52) **U.S. Cl.**  
CPC ..... **G09G 3/3607** (2013.01); **G09G 2320/0276** (2013.01); **G09G 2320/0219** (2013.01); **G09G 3/2074** (2013.01); **G09G 2300/0452** (2013.01); **G09G 3/3648** (2013.01); **G09G 2320/0233** (2013.01); **G09G 2300/0456** (2013.01)  
USPC ..... **349/106**; **349/110**

(57) **ABSTRACT**

In a color display device, when using white (W) sub-pixels in addition to subpixels of red (R) and green (G) plus blue (B) without increasing a wiring line number, the per-color pixel number in a unit area decreases so that the image resolution is deteriorated. The area and number of subpixels are adjusted in accordance with the visual sensitivity or luminosity required. Practically, the area of red (R) and blue (B) subpixels which are relatively low in luminosity is set to be about two times greater than the area of green (G) and white (W) subpixels that are relatively high in luminosity while letting the number of green (G) and white (W) subpixels be twice the number of red (R) and blue (B) subpixels. A larger subpixel is configured from a plurality of unit subpixels. A smaller subpixel is formed of a one unit subpixel.

**11 Claims, 10 Drawing Sheets**



(56)

**References Cited**

U.S. PATENT DOCUMENTS

2005/0270445 A1\* 12/2005 Lee et al. .... 349/108  
2005/0275769 A1\* 12/2005 Roh et al. .... 349/109  
2006/0139517 A1\* 6/2006 Ahn et al. .... 349/110

FOREIGN PATENT DOCUMENTS

JP 11-295717 10/1999

JP 2003-84719 3/2003  
JP 2003-157051 5/2003  
JP 2003-308048 10/2003  
JP 2004-53715 2/2004  
JP 2004-325716 11/2004  
JP 2005-284037 10/2005  
JP 2005-338783 12/2005  
WO WO 2005/122122 12/2005

\* cited by examiner

FIG. 1




FIG. 2




FIG. 3




FIG. 4




FIG. 5  
PRIOR ART




FIG. 6A




FIG. 6B




FIG. 7




FIG. 8




FIG. 9




FIG. 10




FIG. 11





FIG. 12



**COLOR DISPLAY, LIQUID CRYSTAL  
DISPLAY, AND SEMI-TRANSMISSIVE  
LIQUID CRYSTAL DISPLAY**

**BACKGROUND OF THE INVENTION**

The present invention relates to a color display device for displaying images, a liquid crystal display (LCD) device, and a semi-transmissive LCD device.

Currently available color display devices for use in practical applications include devices based on various kinds of display technologies, such as cathode ray tube (CRT) monitors, liquid crystal display (LCD) devices, plasma display panels (PDPs), organic light-emitting diode (LED) panels, field emission display (FED) panels, and electrophoresis or electrochrominance-based electronic paper ("e-paper") display panels. A major approach to achieving color image displaying in non-emissive LCDs is to use a technique for arranging a picture element or "pixel" by a parallel layout of sub-pixels having color filters of the three primary colors, i.e., red (R), green (G) and blue (B), and for adjusting the brightness of each subpixel independently of one another to thereby represent any given color by additive color mixture methods. Another approach for use with emissive displays is to arrange a pixel by parallel layout of subpixels having fluorescent materials of the three primary colors, i.e., red (R), green (G) and blue (B), and for adjusting the brightness on a per-subpixel basis in a similar way to LCDs to thereby represent any given color by additive color mixture methods in a similar way to LCDs.

In the case of the technique for performing color displaying by additive color mixture with the use of three-primary-color subpixels, it is possible to display on-screen images in vivid colors with high fidelity; on the contrary, as the area of each primary color-allocated subpixel is one third ( $\frac{1}{3}$ ) the total area of a pixel, the resulting efficiency stays less, posing a problem as to deficiency of light amount.

One solution to this problem is to employ an arrangement with addition of subpixels of white (W) color, as proposed and disclosed in JP-A-11-295717. In the white (W) subpixels used in non-emissive LCDs, there is no light absorption at color filters so that it is possible to enhance the use efficiency of a light source. As the white (W) subpixels in emissive ones is high in brightness per unit area, it is easy to increase the brightness of display device.

In the case of adding the white (W) subpixels, if these subpixels are simply added, there exists a penalty as to unwanted increase in number of signal transmission lines and/or scanning lines. A pixel configuration with the white (W) subpixels being added thereto without having to increase the number of such lines is disclosed, for example, in U.S. Patent Application Publication No. 2005/0225575 A1.

Another problem of the additive color mixture-based color display scheme with the parallel layout of three-primary-color subpixels is that the color reproduction range is limited to within the zone of a triangle determined by chromaticity coordinate points of the three primary colors, resulting in a region being left widely, which is incapable of reproducing most of the real colors in the natural world. To solve this problem, an attempt is made to lay out subpixels of four primary colors to thereby expand the color reproduction range from the triangle to a rectangle.

An example of such four-primary-color display device is found in JP-A-2005-338783.

**SUMMARY OF THE INVENTION**

Although the addition of white (W) subpixels for reducing the color absorption loss due to color filters is effective,

merely adding white (W) subpixels to red (R), green (G) and blue (B) subpixels causes a total number of subpixels to increase, resulting in an increase in number of electrical wiring lines associated therewith. When fixing this problem by use of the technique as taught by the above-cited US 2005/0225575A1, another problem arises as to a decrease in image resolution because of the fact that a per-color pixel number in the lateral direction is set to one-half of that of the parallel layout of extra-fine red (R), green (G) and blue (B) subpixels. In the case of ultrahigh-definition display devices with resolutions of more than 300 pixels per inch (ppi), this penalty is not so appreciable. However, in middle or high definition display devices with the resolution being set at 200 ppi, or more or less, the penalty appreciably degrades the viewability and visibility of on-screen color images. It is therefore an object of this invention to provide a display device capable of reducing the color filter-caused absorption loss while at the same time preventing reduction of image resolution.

Especially in the case of LCD devices, these are also required to reduce the loss occurring due to a black matrix which shields peripheral portions of subpixels in addition to the above-noted color filter-caused loss. Alternatively, in the case of LCD devices of the type employing a technique for driving a layer of liquid crystal (LC) material by use of a common electrode and comb-like signal electrode formed on the same substrate, a need is felt to provide a sufficiently long distance between an end portion of the comb-like signal electrode and a signal line in order to prevent occurrence of unwanted color mixture between neighboring subpixels, and thus these LCDs are under requirement for reduction of the loss occurable due to the presence of such increased distance.

To attain the foregoing object, in accordance with one aspect of this invention, there is provided a color display device of the type having a matrix array of unit subpixel layouts which are comprised of a plurality of red (R), green (G), blue (B) and white (W) subpixels and performing color image display operations, characterized in that the subpixels are made different in area and number on a per-color basis while letting a total area of respective colors be kept unchanged and substantially equal.

More specifically, the red (R) and blue (B) subpixels are arranged to be about two times greater in area than the green (G) and white (W) subpixels. The green (G) and white (W) subpixels are two times greater in number than the red (R) and blue (B) subpixels. Those subpixels which are included in a pixel unit configuration that is a recurring unit are made up of an ensemble of twelve (12) subpixels in total, i.e., two red (R) subpixels, two blue (B) subpixels, four green (G) subpixels, and four white (W) subpixels.

Also importantly, each subpixel is constituted from one or a plurality of continuously disposed unit subpixels of the same area. Regarding the red (R) and blue (B) subpixels, each of these subpixels consists essentially of two unit subpixels. As for the green (G) and white (W) subpixels, each of them is formed of a single unit subpixel.

In accordance with another aspect of the invention, a color LCD device which is also capable of attaining the above-stated object is provided, which includes a color display device provided between two substrates to have a matrix array of rows and columns of unit subpixel layouts each being configured from a plurality of red (R), green (G), blue (B) and white (W) subpixels for performing color image displaying and a layer of LC material filled in a space gap between the substrates, characterized in that a black matrix is formed between the red (R) subpixels and green (G) subpixels and also between the blue (B) subpixels and green (G) subpixels

whereas the black matrix is not formed between the red (R) subpixels and white (W) subpixels and between the blue (B) subpixels and white (W) subpixels.

Preferably in the color LCD device, specific layout design is employable for disposing a boundary of red and blue color filters between any one of the red (R) and blue (B) subpixels and a white (W) subpixel in such a manner that the boundary is closer to the white (W) subpixel side than a signal line between the red (R) and blue (B) subpixels on one hand and the white (W) subpixel on the other hand.

Alternatively, in order to attain the above-noted object in a color LCD device which has an LC layer filled in a gap space between two separate substrates with a color display device being provided therein, wherein this color display device has a matrix array of unit pixel layouts each being made up of a plurality of subpixels of red (R), green (G), blue (B) and white (W) for performing color display operations, this invention provides a color liquid crystal display device which is arranged so that in each subpixel the liquid crystal is driven by a comb-shaped signal electrode and common electrode provided on one substrate and which is characterized in that the distance between signal line and signal electrode end portion is changed in a color-dependent manner.

Further, in the color liquid crystal display device, it is recommendable to change the number of teeth of the comb-like signal electrode in a color-dependent way.

According to this invention, by adding white (W) pixels without having to increase the wiring line number, the loss occurring due to the presence of a color filter(s) is lessened to thereby make it possible to provide a display device with suppressibility of the image resolution reduction and also provide information terminal equipment using such the device.

Other objects, features and advantages of the invention will become apparent from the following description of the embodiments of the invention taken in conjunction with the accompanying drawings.

#### BRIEF DESCRIPTION OF THE DRAWINGS

FIG. 1 is a diagram showing an enlarged partial plan view of a display device of an embodiment 1 of the present invention.

FIG. 2 is an explanation diagram of a pixel unit configuration of the embodiment 1 of this invention.

FIG. 3 is an explanation diagram of another example of the pixel unit configuration of the embodiment 1 of the invention.

FIG. 4 is an explanation diagram of an application example of a black matrix layout method of the invention.

FIG. 5 is an explanation diagram of a layout of pixels which are equivalent in area to the embodiment 1 in prior known RGB parallel layout design.

FIGS. 6A and 6B are diagrams for explanation of a gradation voltage generator and a gradation voltage selector in signal line drive circuitry.

FIG. 7 is an explanation diagram of a cellular phone system.

FIG. 8 is an explanation diagram of a pixel unit arrangement of an embodiment 3 of the invention.

FIG. 9 is an explanation diagram of another example of the unit pixel arrangement of the embodiment 3 of the invention.

FIG. 10 is an explanation diagram of a pixel unit configuration of an embodiment 4 of the invention.

FIG. 11 is an explanation diagram of another example of the unit pixel configuration of the embodiment 4 of the invention.

FIG. 12 is an explanation diagram of still another example of the unit pixel configuration of the embodiment 4 of the invention.

#### DETAILED DESCRIPTION OF THE INVENTION

An explanation will be given of respective embodiments with reference to the accompanying figures of the drawing below.

#### Embodiment 1

A configuration of this embodiment will be described by use of FIG. 1. FIG. 1 is an enlarged plan view of part of a display device of this embodiment, including a plurality of picture elements or "pixels" in a display area with a matrix array of pixels each made up of sub-pixels being provided in units of colors. The display device of this embodiment is a liquid crystal display (LCD) device, which is arranged so that a liquid crystal (LC) layer is filled between a first substrate on which a plurality of thin-film transistors (TFTs) provided on a per-subpixel basis and wiring lines are disposed in a matrix form and a second substrate with color filters and a black matrix being disposed thereon. The LCD device is of the type using the so-called active matrix drive technique. Optical films, such as polarization plates, are bonded onto specified surfaces of the first and second substrates, which surfaces are on the opposite side to the LC layer. The display device of this embodiment is able to perform displaying with any given brightness or luminance by using a backlight module (not shown) as its light source and by electrically controlling the LC layer to modulate the polarization state of polarized light that has passed through the polarizer plate while also modulating the transmissivity of the other polarizer plate.

FIG. 1 shows an ensemble of unit arrangements 120 of pixels which are periodically disposed at substantially equal intervals, wherein each unit includes twelve subpixels in total—i.e., two red (R) subpixels 121R, two blue (B) subpixels 121B, four green (G) subpixels 121G and four white (W) subpixels 121W. Regarding the red (R) subpixels 121R and blue (B) subpixels 121B, each is further dividable into unit subpixels 109: the red (R) subpixels 121R and blue (B) subpixels 121B are each constituted from two unit subpixels. The longitudinal-to-lateral or "aspect" ratio of the red (R) subpixels 121R and blue (B) subpixels 121B is such that the longitudinal length is set to approximately two (2) with respect to the lateral length of one (1). On the contrary, the aspect ratio of the green (G) subpixels 121G and white (W) subpixels 121W is set at about 1:1. The green (G) subpixels 121G and white (W) subpixels 121W are such that each is formed of a single unit subpixel 109.

The red (R) subpixels 121R and blue (B) subpixels 121B are different in area from the green (G) subpixels 121G and white (W) subpixels 121W. The area of the former is approximately twice the area of the latter.

The reason for changing the number and area between the red (R) subpixels 121R and blue (B) subpixels 121B on one hand and the green (G) subpixels 121G and white (W) subpixels 121W on the other hand in this way is based on the relation of the visual sensitivity or luminosity and the image resolution. It is known that the human eyes are relatively higher in resolution of colors of high luminosity than other colors low in luminosity. In this embodiment, among the red (R), green (G), blue (B) and white (W) colors, the number of the G and W subpixels that are relatively high in luminosity is specifically set to about twice the number of the R and B subpixels that are relatively low in luminosity.

See FIG. 2, which is a pictorial representation of the layout of respective subpixels in unit pixels. FIG. 5 is a pictorial representation of one prior art RGB parallel layout design having subpixel layouts which are equivalent in area to the pixel unit arrangements 120 of this embodiment shown in FIG. 2. In the prior art RGB parallel layout design, one pixel consists of three subpixels. FIG. 5 shows a total of twelve subpixels in a group of two rows and two columns of pixels. As apparent by comparison between FIG. 2 and FIG. 5, this embodiment is with addition of the white (W) subpixels 121W and, nevertheless, is kept identical in subpixel number in the same area—i.e., 12 subpixels. Whereas the number of the green (G) subpixels 121G and white (W) subpixels 121W is the same, the number of the green (G) subpixels 121G and blue (B) subpixels 121B is set at the half.

A modified example of the subpixel layout scheme of FIG. 2 is shown in FIG. 3, wherein each pair of green (G) subpixel 121G and white (W) subpixel 121W is modifiable so that these are interchanged in position with each other.

A pixel is arranged to at least include a scan line 101, first signal line 102B, second signal line 102G, third signal line 102W, TFTs 103R, 103G, 103B and 103W, common electrode 104 (symbols in FIG. 1 indicate contact holes), amorphous silicon layer 105, and signal electrodes 106 and 113, which are formed on or above the first substrate, and also include a black matrix 110, red (R) color filter 111R, green (G) color filter 111G, blue (B) color filter 111B and white (W) color filter 111W, which are formed on the second substrate, and further includes an LC layer that is filled in the gap space provided between the first substrate and the second substrate. The black matrix 110 is for light shield purposes so it is opaque. In the drawing, this part is indicated by contour lines to avoid concealment of its background configurations. The red (R) color filter 111R, green (G) color filter 111G and blue (B) color filter 111B are each made of currently available color resist material. As for the white (W) color filter 111W, this filter may be formed by burying with a transparent resist material a step-like difference that was formed either by pre-removal of a color resist or by removing the color resist. The scan line 101, signal lines 102B, 102G and 102W, signal electrode 106 are each made of a metallic material of low electrical resistance. The common electrode 104 and signal electrode 113 are each formed of a transparent electrode. The signal electrode 106 and signal electrode 113 are connected via contact hole 107, 108. The LC layer is driven by an electric field being applied between the common electrode 104 and signal electrode 113. Although this embodiment uses amorphous silicon TFTs using amorphous silicon layer 105 in the TFTs 103, other types of transistors may alternatively be used, such as for example low-temperature polycrystalline silicon transistors, organic transistors, etc.

(Description as to Other Displays)

It would readily occur to those skilled in the art that the subpixel layout of this invention is applicable to display devices other than the LCD device stated in this embodiment. Examples of such devices include, but not limited to, organic LED panels, electrophoresis or electrochrominance-based electronic paper (“e-paper”) display panels, PDPs, FED panels, and CRT monitors.

It is readily understandable that in display devices of the self-luminous type, such as organic LED panels and PDPs, the function of the color filter in the LCD device is achieved by per-color fluorescent material.

In the self-luminous display devices also, a technique is known for using white fluorescent material and color filters in a combined form to thereby perform color image displaying.

In this case, it is possible to attain required designs by an approach similar to the LCD device of this embodiment. (Details of Unit Subpixel)

The red (R) subpixels 121R and the blue (B) subpixels 121B are each formed of two unit subpixels 109 with TFTs 103 being connected to the same signal line for the reason which follows. Although the subpixels of this embodiment are different in size on a per-color basis, if each of the red (R) subpixels 121R and blue (B) subpixels 121B, which are relatively large-size subpixels, is not subdivided into unit subpixels 109, the area of an LC layer portion to be driven by the TFTs 103R and 103B is unintentionally different from that of each of the green (G) subpixels 121G and white (W) subpixels 121W. Accordingly, the significance of the so-called LC capacitance with the TFT 103’s bearing LC layer portion as dielectric substance becomes different per color. Alternatively, if the subpixels are different in size on a per-color basis, the significance of parasitic capacitance between the signal electrode 113 and the signal line 102 becomes different on a per-color basis. In active matrix driving, the presence of the capacitance of TFT 103 per se and/or the parasitic capacitance thereof would result in a feed-through voltage being derived as an error of drive voltage. The feed-through voltage is variable in potential in a way depending upon the magnitude of the LC capacitance and/or parasitic capacitance. Consequently, if the LC capacitance and/or parasitic capacitance becomes different on a per-subpixel basis, the feed-through voltage also becomes different. If the feed-through voltage of each subpixel is kept constant, it is possible to alleviate the influence of feed-through voltage by amending a relative relation between common voltage potential and signal potential; however, such amendment is no longer executable in case the feed-through voltage is different per subpixel. For this reason, in this embodiment, larger subpixels are specifically arranged to be divided into unit subpixels, each of which is the same in size as smaller subpixels, to thereby ensure that each TFT 103’s LC capacitance and parasitic capacitance become almost equal. With this arrangement, it is possible to sufficiently suppress the subpixel dependency of the feed-through voltage. This makes it possible to employ prior known feed-through voltage strategies with no changes even in arrangements with subpixels being different in area on a per-color basis.

(Explanation of Other Display Methods)

So far, this embodiment was described by mainly exemplifying LCD devices of the type using the active matrix (AM) drive technique, i.e., AM-LCDs, it is needless to say that the arrangement of this invention for dividing each of the larger subpixels into unit subpixels is applicable to other AM-driven display devices—for example, organic LED display devices, or electrophoresis/electrochrominance-based electronic paper (e-paper) display devices. This can be said because of the fact which follows. In the case of AM drive designs, the display image brightness deviation phenomenon per se is common—more precisely, when the capacitance of TFT 103 of each subpixel is varied, the feed-through voltage acting as noises varies accordingly, resulting in a display image being deviated from its intended level of brightness.

(Regarding Black Matrix)

Some major functions of the black matrix 110 are as follows: (1) preventing invasion of the outside light into TFTs 103, (2) shielding a region which can experience light leakage during black displaying due to a failure of prespecified movement of an LCD layer portion associated therewith, and (3) avoiding exposure of a color filter to its neighboring subpixel when misalignment occurs in the process of bonding together the first and second substrates. To attain the third goal, the

black matrix is provided between R and G subpixels, between G and B subpixels and between R and B subpixels. An example is that in the case of displaying red (R) color that is high in chromaticity, only the red (R) subpixels **121R** are driven to turn on while causing their adjacent green (G) subpixels **121G** and blue (B) subpixels **121B** to be kept deactivated and nonoperative. If the first and second substrates are misaligned in position, when any one of the green (G) subpixels **121G** and blue (B) subpixels **121B** partly overlaps its associated red (R) subpixel **121R**, unwanted color mixture takes place. To avoid this risk, the black matrix is formed between the neighboring subpixels to ensure that such color mixture does not occur as far as the possible misalignment between the first and second substrates falls within a prespecified range. Unfortunately, this advantage of the black matrix layout does not come without accompanying a penalty: the black matrix partly shields the effective display area also, resulting in a likewise decrease in efficiency.

As a consequence, no black matrixes are provided between the W and B subpixels and between W and R subpixels. In view of the fact that it is low-chromaticity color that turns on the white (W) subpixels **121W**, the blue (B) subpixels **121B** and red (R) subpixels **121R** are forced to turn on simultaneously. Accordingly, even when the red (R) subpixels **121R** and blue (B) subpixels **121B** slightly overlap white (W) subpixels **121W**, the influence thereof is negligible. From this viewpoint, any black matrix is not provided at portions between W and B subpixels and between W and R subpixels. Note here that the boundary **112R** of red (R) color filter in a region between W-R with no black matrix being provided therein is provided on the white (W) subpixel **121W** side. Similarly, the boundary **112B** of blue (B) color filter in a region between W-R with no black matrix being provided therein is provided on the white (W) subpixel **121W** side. This is in order to prevent the invasion of white (W) color filter to the neighboring blue (B) subpixel **121B** and red (R) subpixel **121R** even when misalignment occurs in the process of bonding the first and second substrates together. With the black matrix layout unique to this embodiment, it is possible to recover and improve the efficiency, which was lowered due to the black-matrix shielding of effective display pixel areas.

In prior art color display devices of the type driving LC by similar principles to this embodiment, it is necessary to retain a predetermined distance between terminate ends of signal electrodes **113** of neighboring subpixels in order to avoid unwanted color mixture occurring due to the leakage of an electric field into such neighboring subpixels. From a viewpoint of efficiency improvement, this distance is too long slightly. The reason of this is that if the distance between the terminate ends of signal line **102** and signal electrode **113** is long excessively then it becomes difficult to efficiently drive a region therebetween. In this embodiment, there is a portion between subpixels in which two signal lines **102B** and **102W** are disposed: at this portion, a sufficient length of distance is acquirable between neighboring subpixels at the end of signal electrode **113**. Accordingly, the distance between the end of signal electrode **113** of a subpixel neighboring upon two signal lines **102B** and **102W** and the signal line **102B**, **102W** is specifically designed to be shorter than the distance between the signal electrode **113**'s end of a subpixel adjacent to one signal line **102G** and this signal line **102G**.

The black matrix layout of this arrangement may also be applied to other color filter layout designs.

See FIG. 4, which is an explanation diagram in the case of the black matrix layout of this embodiment being applied to a color filter layout which is disclosed in US 2005/0225575. A black matrix **110** is provided between green (G) and red (R)

subpixels and between green (G) and blue (B) subpixels in order to prevent color mixture otherwise occurring due to the presence of substrate-bonding misalignment whereas the black matrix **110** is not provided on the right and left sides of each white (W) subpixel.

In addition, the color filter boundary **112B** of a blue (B) subpixel is provided at a position nearer to its associated white (W) subpixel than signal line **102**; similarly, the color filter boundary **112R** of a red (R) subpixel is provided at a position nearer to the white (W) subpixel than signal line **102**. This is in order to prevent invasion of the color filter of white (W) subpixel into blue (B) and red (R) subpixels even upon occurrence of substrate bond misalignment. Comb teeth of signal electrode **113** of white (W) subpixel **121W** are arranged to be greater in number than comb teeth of signal electrode **113** of those subpixels of the other colors. It is needed to retain a prespecified length of distance between the terminate ends of signal electrodes **113** of neighboring subpixels in order to prevent color mixture occurring due to leakage of an electric field to such neighboring subpixels.

However, from the viewpoint of efficiency, this distance is too long by little. In the case of an arrangement with white (W) subpixels being provided in addition to those subpixels of the three primary colors, the white (W) subpixels are sometimes turned off during turn-on driving of red (R) subpixels and blue (B) subpixels; adversely, in the case of the white (W) subpixels being turned on, the red (R) subpixels and blue (B) subpixels are driven to turn on simultaneously so that there is no need to worry about the occurrence of color mixture due to leakage of an electric field of at the end of signal electrode **113W** of white (W) subpixel to its neighboring subpixels. Accordingly, unlike the subpixels of the three primary colors, the white (W) subpixels are arranged to increase in number of comb teeth of signal electrode **113W** to thereby make the distance between the end of signal electrode **113** and signal line **102** shorter than the distance between end of signal electrode **113** and signal line **102** in the subpixels of three primary colors.

#### Embodiment 2

Regarding peripheral circuit design in a case where the unit subpixel configuration is not employed, this embodiment provides a solution to problems occurrable in the pixel layouts shown in FIGS. 2 and 3 when failing to use the unit subpixel arrangement and thus resulting in the subpixels being different in size on a per-color basis, which solution is different from that of the embodiment 1. One problem occurring in case the subpixels are different in size on a per-color basis is that the optimum common voltage becomes different in its potential value due to a difference of feed-through voltage on a per-subpixel basis, which can occur due to differences of each subpixel's electrical characteristics (e.g., retained capacitance, parasitic capacitance or else). Size-different subpixels will be referred to as a first kind of subpixel and second kind of subpixel, respectively. A method for supplying color-tone or gradation voltages which are optimized to the first kind of subpixel and second kind of subpixel, which are different in size from each other, will be explained with reference to FIGS. 6A and 6B. In this embodiment, an explanation will be given of a case where green (G) subpixels and white (W) subpixels are each regarded as the first kind of subpixel whereas red (R) subpixels and blue (B) subpixels are each assumed to be the second kind of subpixel.

FIG. 6A is a schematic diagram of a circuit arrangement embodying the invention. A gradation voltage generation unit **305** supplies 256 gradation voltages  $V_0$  to  $V_{255}$  to a gradation

voltage selector **302**. This gradation voltage selector selects from among the 256 gradation voltages a gradation voltage corresponding to image data and then outputs it to an image data output terminal **4001**. A selector switch **4002** is responsive to receipt of a signal SEL for connecting the image data output terminal **4001** to either a signal transfer line **4003** that is connected to green (G) and white (W) subpixels or a signal line **4004** that is connected to red (R) and blue (B) subpixels. In FIG. 6A, the case is shown where the selector switch **4002** is fabricated on an LCD panel: in this case, a number of image data output terminals **4001** is one-half of the number of signal lines. For example, it is also conceivable that as shown in FIG. 6B, the selector switch **4002** is formed within a signal line drive circuit with the image data output terminals **4001** being equal in number to the signal lines.

The gradation voltage generator **305** includes an output stage **3080** which consists essentially of operation amplifiers **3052** that perform current amplification and string resistors **3083** for increasing the number of color tones, a first ladder resistor **3081** which generates a reference voltage of first gradation voltage, a second ladder resistor **3082** that generates a reference voltage of second gradation voltage, and a reference voltage changeover switch module **3084** for performing, in sync with the signal SEL, switching between voltages to be output from the first ladder resistor and the second ladder resistor and for outputting a switched voltage to more than one of the op-amps **3052**. In this embodiment, there is also provided a switch module for controlling each ladder resistor in response to receipt of a polarity-inverted signal M that is in sync with a polarity inversion period of liquid crystal (LC). With this switch, the ladder(s) is/are varied in resistance value in a way synchronized with the polarity inversion also. This configuration is the one that supplies a signal line(s) with the first gradation voltage and second gradation voltage by causing the two types of ladder resistors to produce at least two different kinds of reference voltages and then performing switching of these voltages in response to the signal SEL to thereby input it to the opamp(s) **3052**.

Other employable arrangements include an arrangement with the two ladder resistors being replaced by a single ladder resistor capable of changing its resistance value in a time-division manner, thereby enabling the first gradation voltage and second gradation voltage to be supplied to signal lines in a time-division way, and an arrangement with the string resistor being modified to be controlled in a time division fashion.

FIG. 7 shows a circuit configuration of a cellular or "mobile" phone incorporating the principles of this invention. This mobile phone is designated by numeral **1000** in FIG. 7, which is wirelessly communicable over-the-air with a host station **1004**. Mobile phone **1000** is generally made up of an input means **1001**, main memory **1002**, transmission/reception (Tx/Rx) unit **1003**, central processor unit (CPU), and LCD device **1**. This LCD device includes as its major components an LCD panel **2**, signal line drive circuit **3**, scan line drive circuit **4**, power supply (PS) circuit **5**, and backlight unit **6**. The signal line drive circuit **3** includes a timing control circuit **300**, memory **301**, gradation voltage selector **302**, interface (IF) **303**, control register **304**, and gradation voltage generator **305**.

The CPU of mobile phone **1000** performs various kinds of control operations of the phone. Concerning the control of the LCD device **1**, it outputs a display sync signal and image data **306** to the timing controller **300**, thereby enabling visual displaying of information received from the host station **1004** and/or the data stored in the main memory **1002**. In addition, it issues operation-defining data **307** (in this embodiment, this data will be called the instruction). The IF **303** performs

transmission and reception of data containing therein the instruction to and from the CPU. In addition, the control register **304** also performs such data receive/transmit operations. The instruction will be stored in the control register **304**.

The signal line drive circuit **3** drives signal lines **101** whereas the scan line drive circuit **4** drives scan lines **102**. The PS circuit **5** produces from a voltage fed from the mobile phone an appropriate potential level of power supply voltage, which is supplied to the signal line drive circuit **3** and scan line drive circuit **4**. PS circuit **105** also has a built-in circuit for driving an opposing electrode, also known as "counter" electrode.

The timing controller **300** reads image data out of the memory **301** and then sequentially outputs the image data to the gradation voltage selector **302** in a way of one row of image data in unison at a time. The gradation voltage selector **302** selects one from among the gradation voltages generated by the gradation voltage generator **305** and then applies it to each signal line. The gradation voltage generator **305** functions to generate all possible gradation voltages, which correspond in number to all the color tone levels required—for example, 64 different voltages in case the number of gradation levels required is 64.

#### Embodiment 3

##### RGBC Layout

In this embodiment, a description will be given of another configuration of color filters in the subpixel layouts shown in FIGS. 2 and 3. While the embodiments shown in FIGS. 2-3 are each arranged to have white (W) subpixels in addition to the subpixels of three primary colors, i.e., red (R), green (G) and blue (B), this arrangement may be modified so that the green (G) and white (W) subpixels which are higher in visual sensitivity than red (R) and blue (B) subpixels are replaced by subpixels of blue-blended green (CG) and yellow-blended green (YG) which are similarly high in visual sensitivity to thereby provide a configuration of four primary colors as shown in FIGS. 8 and 9. An advantage of this arrangement lies in its ability to widen the range of color reproduction when compared to the case of using only three primary colors, i.e., red (R), green (G) and blue (B). Very importantly, the advantage as to expandability of the color reproduction range is obtainable without having to increase the signal lines and scan lines in number when compared to prior art pixel configurations using only the three primary colors of red (R), green (G) and blue (B). Thus it is possible to appreciably increase aperture ratios when compared to an arrangement with parallel layout of size-equal subpixels of four primary colors. This makes it possible to achieve a display device capable of offering increased efficiency and enhanced color reproducibility.

#### Embodiment 4

##### Case of Semi-Transmissive Display

This embodiment is drawn to a semi-transmissive LCD device, also known as transreflective LCD, which has subpixels each of which is constituted from a transmissive part and a reflective part. Prior art transreflective LCD devices using subpixels of only three primary colors, i.e., red (R), green (G) and blue (B), are usually arranged to partly remove a color filter at the reflective part and provide a white-colored area within a subpixel. In cases where it is acceptable to perform

image displaying in a black-and-white mode, another configuration is employable in a way such that reflective part **121W(R)** is provided only in white (W) subpixels as shown in FIGS. **10** and **11**. Still alternatively, as shown in FIG. **12**, every subpixel may be designed to have reflective parts **121B** (R), **121G(R)**, **121R(R)** and **121W(R)** to thereby provide the transfective display specification, thus causing the reflective part's area ratio to change so that it is different between for white (W) subpixels and for the other subpixels.

An expected advantage obtainable in any one of these cases is as follows: the reflective part is higher in the ratio of white (W) area than the transmissive part, resulting in a decrease in the color reproduction range even at the reflective part, thereby enabling enhancement of the reflectivity thereof. When viewed from another standpoint, it can be said that this arrangement is such that only the white (W) subpixels are arranged to be low in area ratio of transmissive part. Adding the white (W) subpixels contributes to improvements in brightness. However, this merit does not come without accompanying risks: a relative decrease in area ratio of primary colors, and an increase in brightness ratio of primary colors to white. By lessening the aperture ratio of transmissive part of white (W) subpixels less when compared to aperture ratios of three primary colors, it becomes possible to make smaller or "alleviate" the ratio of the brightness during displaying the white color versus the brightness during displaying the three primary colors.

This invention provides a successful solution for improvement of the viewability of LCD devices adaptable for use in information terminal equipment—typically, cellular phones.

It should be further understood by those skilled in the art that although the foregoing description has been made on embodiments of the invention, the invention is not limited thereto and various changes and modifications may be made without departing from the spirit of the invention and the scope of the appended claims.

The invention claimed is:

**1.** A color display device having a matrix array of unit pixel layouts each comprised of four colors of sub-pixels for performing color displaying, wherein each color is made substantially equal in total area while causing an area of sub-pixel and a number thereof to be different on a per-color basis,

wherein

each sub-pixel includes a single unit sub-pixel or a plurality of unit sub-pixels which are placed adjacent to each other;

size of each of the unit sub-pixels is substantially equal each other;

said four colors include two colors red (R) and blue (B) with lower visual sensitivity and two colors with higher visual sensitivity;

the two colors of sub-pixels with higher visual sensitivity among said four colors of sub-pixels are each constituted from two unit sub-pixels which are not directly adjacent to each other;

each of the red (R) sub-pixel and the blue (B) sub-pixel comprises two unit sub-pixels, which are directly adjacent to each other;

each of the single unit sub-pixels consists of one color of sub-pixels;

each of the two unit sub-pixels included in the red (R) and blue (B) sub-pixels includes a thin-film transistor;

two thin-film transistors of the two unit sub-pixels included in the red (R) sub-pixel are connected to a same signal line; and

two thin-film transistors of the two unit sub-pixels included in the blue (B) sub-pixel are connected to a same signal line,

each of the single unit sub-pixels of the two colors of sub-pixels with higher visual sensitivity among said four colors of sub-pixels includes one thin-film transistor.

**2.** The color display device according to claim **1**, wherein an area of two colors of sub-pixels with higher visual sensitivity among said four colors of sub-pixels is set at approximately one-half of an area of remaining two colors of sub-pixels with lower visual sensitivity among said four colors of sub-pixels and wherein the two colors of sub-pixels with higher visual sensitivity among said four colors of sub-pixels are two times greater in number than the two colors of sub-pixels with lower visual sensitivity among said four colors of sub-pixels.

**3.** The color display device according to claim **2**, wherein colors of the two colors of sub-pixels with higher visual sensitivity among said four colors of sub-pixels are green (G) and white (W) whereas colors of the two colors of sub-pixels with lower visual sensitivity among said four colors of sub-pixels are red (R) and blue (B).

**4.** The color display device according to claim **2**, wherein colors of the two colors of sub-pixels with higher visual sensitivity among said four colors of sub-pixels are blue-blended green (CG) and yellow-blended green (YG) whereas colors of the two colors of sub-pixels with lower visual sensitivity among said four colors of sub-pixels are red (R) and blue (B).

**5.** The color display device according to claim **1**, wherein sub-pixels included in a pixel unit arrangement for use as a repeat unit is made up, in total, of twelve (12) sub-pixels consisting essentially of a total of eight (8) ones each corresponding to any one of two colors of sub-pixels with higher visual sensitivity among said four colors of sub-pixels and a total of four ones each corresponding to any one of two colors of sub-pixels with lower visual sensitivity among said four colors of sub-pixels.

**6.** The color display device according to claim **1**, wherein at each of intersections of signal lines and scan lines which are disposed to cross together in a matrix form, an intersection of a signal line and a scan line with a plurality of thin-film transistors being disposed for connection to the signal line and the scan line and an intersection of a signal line and a scan line with a one thin-film transistor being disposed are arranged to coexist.

**7.** The color display device according to claim **1**,

wherein said color display device having a layer of liquid crystal material as filled in a gap space between two substrates with a color display device being provided for performing color displaying while letting unit pixel layouts be disposed in a matrix form, each said unit pixel layout being configured from a plurality of subpixels of red (R), green (G), blue (B) and white (W), wherein each said subpixel an arrangement is employed to drive the liquid crystal by a comb-shaped signal electrode and a common electrode provided on one substrate, and wherein a distance between the signal line and the signal electrode end portion is changed on a per-color basis, wherein a red or blue color filter is formed on a signal line, and wherein a red or blue color filter is disposed nearer to a white (W) subpixel than the signal line, wherein a number of teeth of the comb-shaped signal electrode is changed on a per-color basis,

13

wherein comb teeth of signal electrode of white (W) subpixel are arranged to be greater in number than comb teeth of signal electrode of those subpixels of the other colors,

wherein the distance between the signal line and signal electrode end portion is designed to be shorter than a distance between a signal line and a signal electrode end portion in at least one of the subpixel from three primary colors.

8. A color liquid crystal display device having a layer of liquid crystal material as filled in a gap space between two substrates with a color display device being provided for performing color displaying while letting unit pixel layouts be disposed in a matrix form, each said unit pixel layout being configured from a plurality of subpixels of red (R), green (G), blue (B) and white (W), which form a plurality of unit subpixels which are placed adjacent to each other with a size of each of the unit sub-pixels being substantially equal each other,

wherein a black matrix is formed between directly adjacent subpixels of red (R) and green (G) and also between directly adjacent subpixels of blue (B) and green (G);

wherein the black matrix is prevented from being formed between directly adjacent subpixels of red (R) and white (W) and between directly adjacent subpixels of blue (B) and white (W) and wherein a red or blue color filter is formed on a signal line;

14

wherein each of the red (R) subpixel and the blue (B) subpixel includes two unit sub-pixels which are directly adjacent to each other;

wherein each of the green (G) subpixel and the white (W) subpixel includes a single unit sub-pixel;

each of the single unit sub-pixels consists of one color of sub-pixels;

wherein the unit subpixel of the subpixel included in the subpixel of one of red (R), green (G), blue (B) and white (W) has a thin film transistor placed different position from the other unit subpixel.

9. The color liquid crystal display device according to claim 8, wherein a boundary of red and blue color filters between red (R) and blue (B) subpixels and white (W) subpixel is disposed to be more adjacent to the white (W) subpixel side than a signal line between the red (R) and blue (B) subpixels and the white (W) subpixel.

10. The color liquid crystal display device according to claim 8, wherein in each said subpixel an arrangement is employed to drive the liquid crystal by a comb-shaped signal electrode and a common electrode provided on one substrate, and wherein a distance of a signal line and a signal electrode end portion is changed on a per-color basis.

11. The color liquid crystal display device according to claim 8, wherein a number of teeth of the comb-shaped signal electrode is changed on a per-color basis.

\* \* \* \* \*

专利名称(译)	彩色显示器，液晶显示器和半透射液晶显示器		
公开(公告)号	<a href="#">US8891044</a>	公开(公告)日	2014-11-18
申请号	US11/869770	申请日	2007-10-10
[标]申请(专利权)人(译)	广田川昭一 高村正彦SHINICHI 关口义文 恒则YAMAMOTO 安达MASAYA		
申请(专利权)人(译)	广田川昭一 高村正彦SHINICHI 关口义文 恒则YAMAMOTO 安达MASAYA		
当前申请(专利权)人(译)	日本展示INC. 松下液晶显示CO., LTD.		
[标]发明人	HIROTA SHOICHI KOMURA SHINICHI SEKIGUCHI YOSHIFUMI YAMAMOTO TSUNENORI ADACHI MASAYA		
发明人	HIROTA, SHOICHI KOMURA, SHINICHI SEKIGUCHI, YOSHIFUMI YAMAMOTO, TSUNENORI ADACHI, MASAYA		
IPC分类号	G09G3/20 G09G3/36 G02F1/1333 G02F1/1335		
CPC分类号	G09G2300/0456 G09G3/3648 G09G3/3607 G09G2320/0219 G09G2300/0452 G09G2320/0233 G09G3/2074 G09G2320/0276 G02F1/133514 G02F1/134309 G02F1/136286 G09G3/2003 H01L27/3213 H01L27/3218		
优先权	2006275967 2006-10-10 JP		
其他公开文献	US20080084376A1		
外部链接	<a href="#">Espacenet</a> <a href="#">USPTO</a>		

#### 摘要(译)

在彩色显示装置中，当使用白色（W）子像素以及红色（R）和绿色（G）加蓝色（B）的子像素而不增加布线数时，单位像素数以单位为面积减小，使图像分辨率降低。根据所需的视觉灵敏度或亮度调整子像素的面积和数量。实际上，发光度相对较低的红色（R）和蓝色（B）子像素的面积设定为发光度相对较高的绿色（G）和白色（W）子像素的面积的两倍。使绿色（G）和白色（W）子像素的数量是红色（R）和蓝色（B）子像素的数量的两倍。较大的子像素由多个单位子像素构成。较小的子像素由一个单位子像素形成。

