



US007768615B2

(12) **United States Patent**  
**Lyu et al.**

(10) **Patent No.:** **US 7,768,615 B2**  
(45) **Date of Patent:** **Aug. 3, 2010**

(54) **LIQUID CRYSTAL DISPLAY HAVING WIDE VIEWING ANGLE**

(75) Inventors: **Jae-Jin Lyu**, Kyungki-do (KR);  
**Kyeong-Hyeon Kim**, Seongnam (KR);  
**Hea-Ri Lee**, Seoul (KR); **Jian-Min Chen**, Suwon (KR)

(73) Assignee: **Samsung Electronics Co., Ltd.** (KR)

(\*) Notice: Subject to any disclaimer, the term of this patent is extended or adjusted under 35 U.S.C. 154(b) by 0 days.

(21) Appl. No.: **11/334,025**

(22) Filed: **Jan. 18, 2006**

(65) **Prior Publication Data**

US 2006/0114402 A1 Jun. 1, 2006

**Related U.S. Application Data**

(60) Continuation of application No. 10/903,480, filed on Aug. 2, 2004, now Pat. No. 7,016,004, which is a continuation of application No. 09/877,481, filed on Jun. 8, 2001, now Pat. No. 6,771,344, which is a division of application No. 09/087,408, filed on May 29, 1998, now Pat. No. 6,285,431.

(30) **Foreign Application Priority Data**

May 29, 1997 (KR) ..... 97-21708  
Aug. 25, 1997 (KR) ..... 97-40665

(51) **Int. Cl.**  
**G02F 1/1343** (2006.01)

(52) **U.S. Cl.** ..... **349/143**

(58) **Field of Classification Search** ..... None  
See application file for complete search history.

(56) **References Cited**

**U.S. PATENT DOCUMENTS**

3,914,022 A 10/1975 Kashnow

4,385,806 A 5/1983 Fergason

4,639,087 A 1/1987 Cannella

4,701,028 A 10/1987 Clerc et al.

4,786,147 A 11/1988 Clerc et al.

4,869,576 A 9/1989 Aoki et al. .... 350/336

4,889,412 A 12/1989 Clerc et al.

(Continued)

**FOREIGN PATENT DOCUMENTS**

EP 0445777 A2 9/1991

(Continued)

**OTHER PUBLICATIONS**

Full-Cone Wide-Viewing-Angle Multicolor CSH-LCD;  
Author: Tsuyoshi Yamamoto, et al.; SID 91 Digest, 1991, pp. 762-765.


(Continued)

*Primary Examiner*—Timothy Rude  
(74) *Attorney, Agent, or Firm*—Cantor Colburn LLP

(57) **ABSTRACT**

Apertures are formed in the common electrode or in the pixel electrode of a liquid crystal display to form a fringe field. Storage capacitor electrodes are formed at the position corresponding to the apertures to prevent the light leakage due to the disclination caused by the fringe field. The apertures extend horizontally, vertically or obliquely. The apertures in adjacent pixel regions may have different directions to widen the viewing angle.

**13 Claims, 18 Drawing Sheets**



# US 7,768,615 B2

Page 2

## U.S. PATENT DOCUMENTS

5,032,883 A 7/1991 Wakai et al.  
 5,136,407 A 8/1992 Clerc ..... 359/55  
 5,166,086 A 11/1992 Takeda et al.  
 5,229,873 A 7/1993 Hirose et al. .... 359/55  
 5,298,199 A 3/1994 Hirose et al.  
 5,309,264 A 5/1994 Lien et al. .... 359/87  
 5,434,690 A 7/1995 Hisatake et al.  
 5,473,455 A 12/1995 Koike et al.  
 5,579,140 A 11/1996 Yamahara et al.  
 5,583,679 A 12/1996 Ito et al.  
 5,592,199 A 1/1997 Kawaguchi et al.  
 5,608,556 A 3/1997 Koma ..... 349/143  
 5,615,028 A 3/1997 Ishiguro et al.  
 5,641,974 A 6/1997 Den Boer et al. .... 257/59  
 5,666,179 A \* 9/1997 Koma ..... 349/143  
 5,670,994 A 9/1997 Kawaguchi et al.  
 5,673,092 A 9/1997 Horie et al.  
 5,689,322 A 11/1997 Hirata et al.  
 5,710,611 A 1/1998 Suzuki et al.  
 5,724,107 A 3/1998 Nishikawa et al. .... 349/38  
 5,726,077 A 3/1998 Kawahata et al.  
 5,731,855 A 3/1998 Koyama et al.  
 5,745,206 A 4/1998 Koike et al.  
 5,748,275 A \* 5/1998 Sato et al. .... 349/144  
 5,757,451 A 5/1998 Miyazaki et al.  
 5,767,926 A 6/1998 Kim et al. .... 349/38  
 5,771,083 A 6/1998 Fujihara et al.  
 5,777,700 A 7/1998 Kaneko et al.  
 5,781,262 A 7/1998 Suzuki et al.  
 5,796,456 A 8/1998 Takatori et al.  
 5,805,250 A 9/1998 Hatano et al.  
 5,831,704 A 11/1998 Yamada et al. .... 349/124  
 5,831,708 A 11/1998 Hiraishi et al.  
 5,846,452 A 12/1998 Gibbons et al.  
 5,859,683 A 1/1999 Tagusa et al.  
 5,877,830 A 3/1999 Shimada et al.  
 5,880,797 A 3/1999 Yamada et al.  
 5,907,380 A 5/1999 Lien  
 5,917,572 A 6/1999 Kurauchi et al.  
 5,923,310 A 7/1999 Kim  
 5,946,065 A 8/1999 Tagusa et al.  
 5,953,093 A 9/1999 Hirata et al. .... 349/143  
 5,953,148 A 9/1999 Moseley et al. .... 359/237  
 5,963,285 A 10/1999 Kim  
 5,976,639 A 11/1999 Iwata  
 5,986,732 A 11/1999 Ozeki et al.  
 5,986,738 A 11/1999 Tagusa et al.  
 5,995,176 A 11/1999 Sibahara ..... 349/44  
 5,995,190 A 11/1999 Nagae et al.  
 6,034,747 A 3/2000 Tanaka et al.  
 6,040,882 A 3/2000 Jun et al.  
 6,052,162 A 4/2000 Shimada et al.  
 6,061,116 A 5/2000 Nishida et al.  
 6,061,117 A 5/2000 Horie et al.  
 6,100,953 A 8/2000 Kim et al. .... 349/129  
 6,115,093 A 9/2000 Murai et al. .... 349/129  
 6,147,729 A 11/2000 Kurachi et al.  
 6,157,428 A 12/2000 Koma  
 6,175,393 B1 \* 1/2001 Ban et al. .... 349/39  
 6,191,836 B1 2/2001 Woo et al.  
 6,266,116 B1 \* 7/2001 Ohta et al. .... 349/141  
 6,266,166 B1 7/2001 Katsumata et al.  
 6,288,762 B1 9/2001 Sasaki et al.  
 6,327,014 B1 12/2001 Mulatier et al.  
 6,597,415 B2 7/2003 Rho et al.  
 6,661,488 B1 12/2003 Takeda et al.  
 6,724,452 B1 4/2004 Takeda et al.  
 6,771,342 B1 8/2004 Hirakata et al.  
 6,819,384 B2 11/2004 Nakanishi et al.  
 7,304,703 B1 12/2007 Takeda et al.  
 7,573,554 B2 \* 8/2009 Song et al. .... 349/129

2001/0052949 A1 12/2001 Yamaguchi et al.  
 2005/0140887 A1 \* 6/2005 Song et al. .... 349/129

## FOREIGN PATENT DOCUMENTS

EP 0636917 2/1995  
 EP 0676661 A2 10/1995  
 EP 0854377 A2 7/1998  
 GB 1462978 1/1977  
 JP 60-256121 12/1985  
 JP 62-131578 A 6/1987  
 JP S63-300224 A 12/1988  
 JP 01189629 7/1989  
 JP 01196020 8/1989  
 JP 02035416 2/1990  
 JP 02063020 3/1990  
 JP 02151830 6/1990  
 JP 02190825 7/1990  
 JP 03-002731 A 1/1991  
 JP 03043701 2/1991  
 JP 03209220 9/1991  
 JP 03261914 11/1991  
 JP 03-274029 A 12/1991  
 JP 04-157494 A 5/1992  
 JP 04251285 9/1992  
 JP 04-331922 A 11/1992  
 JP 05-019298 A 1/1993  
 JP 05-040252 A 2/1993  
 JP 11-065472 A 3/1993  
 JP 05-088150 4/1993  
 JP 05173142 7/1993  
 JP 05203933 8/1993  
 JP 05-243333 A 9/1993  
 JP 05-303109 A 11/1993  
 JP 05-323373 A 12/1993  
 JP H05-333358 A 12/1993  
 JP 06018923 1/1994  
 JP 06082777 3/1994  
 JP 11-109356 A 4/1994  
 JP 06-140296 A 5/1994  
 JP 06-194656 A 7/1994  
 JP 06-202132 7/1994  
 JP 06-202153 A 7/1994  
 JP 06194656 7/1994  
 JP 06-230414 A 8/1994  
 JP 06-230428 A 8/1994  
 JP 06-273798 A 9/1994  
 JP 06258649 9/1994  
 JP 06301036 10/1994  
 JP 6-308533 11/1994  
 JP 07-013191 A 1/1995  
 JP 07-028091 A 1/1995  
 JP 07013164 1/1995  
 JP 07028063 1/1995  
 JP 07-049657 2/1995  
 JP 07043719 2/1995  
 JP 07-064089 3/1995  
 JP 07104450 4/1995  
 JP 07-120772 A 5/1995  
 JP 07-134301 A 5/1995  
 JP 07120767 5/1995  
 JP 07147426 6/1995  
 JP 07199193 8/1995  
 JP 07199205 8/1995  
 JP 07225389 8/1995  
 JP 07-245405 A 9/1995  
 JP 07234414 9/1995  
 JP 07-261199 A 10/1995  
 JP 07-263700 A 10/1995  
 JP 07-273346 A 10/1995  
 JP 07281195 10/1995  
 JP 07-311390 A 11/1995  
 JP 07311383 11/1995

JP	07318950	12/1995
JP	07333617	12/1995
JP	08-015714 A	1/1996
JP	08006052	1/1996
JP	08022023	1/1996
JP	08029790	2/1996
JP	08029812	2/1996
JP	08043825	2/1996
JP	08-76125	3/1996
JP	2507122	4/1996
JP	08095054	4/1996
JP	08101396	4/1996
JP	08-122822 A	5/1996
JP	08-129180 A	5/1996
JP	08-146464 A	6/1996
JP	08-146465 A	6/1996
JP	08-179341 A	7/1996
JP	08-179343 A	7/1996
JP	08-179372 A	7/1996
JP	08179381	7/1996
JP	08220511 A	8/1996
JP	08220524 A	8/1996
JP	8-313923	11/1996
JP	08292423	11/1996
JP	08-338995 A	12/1996
JP	09-043610 A	2/1997
JP	09-054323 A	2/1997
JP	09033882	2/1997
JP	09043592	2/1997
JP	09105908	4/1997
JP	09120072	5/1997
JP	09120075	5/1997
JP	09160061	6/1997
JP	09-179141 A	7/1997
JP	9-258266	10/1997
JP	09-292624 A	11/1997
JP	09-325373	12/1997
JP	H10-10564 A	1/1998
JP	10048634	2/1998
JP	10-090708 A	4/1998
JP	10-197894 A	7/1998
JP	H10-198285 A	7/1998
JP	10-214858	8/1998
JP	10-221707 A	8/1998
JP	10-222097 A	8/1998
JP	10-268349 A	10/1998

JP	H10-307301	11/1998
JP	10333170 A	12/1998
JP	2000-235371 A	8/2000
JP	2001-109018 A	4/2001
JP	2002-63020	2/2002
JP	2002040400 A	2/2002
JP	2006-18923	1/2006
JP	H127540 A	5/2007
JP	2007-193347 A	8/2007
WO	9712275	4/1997

## OTHER PUBLICATIONS

EURODISPLAY '93; Author: Takahashi; pp. 158-159.

The above references were cited in a Japanese OA, dated Oct. 30, 2007.

Optimum Film Compensation Modes for TN and VA LCDs; J. Chen, K.-H. Kim, J.-J. Jyu, J. H. Souk; 21.2/Chen; SID 98 Digest.315.

XP-000722823; 33.3: Development of Super-High-Image-Quality Vertical-Alignment-Mode LCD; K. Ohmuro, S. Kataoka, T. Sasaki, Y. Kolke; Fujitsu Ltd., Atsugi, Japan; SID 97 Digests.845; May 13, 1997; pp. 845-848.

A Super-High-Image-Quality Multi-Domain Vertical Alignment LCD by New Rubbing-Less Technology; A. Takeda, S. Kataoka, T. Sasaki, H. Chida, H. Tsuda, K. Ohmuro, Y. Koike, SID 98 Digest-1077-1080.

'311 Patent Invalidity; Improper Inventorship; Sharp RDX 002 - RDX 228.

2 Separate substrates CDX 1095; '311 CDX; Samsung Memo of Nov. 5, 1997.

'311 Validity CDX 270-CDX 283; Samsung.

Complaint of Samsung Electronics Co., Ltd. Under Section 337 of the Tariff Act of 1930, As Amended; Dec. 21, 2007; Samsung; Investigatin No. 337-TA.

Denying Respondents' Motion for Summary Determination That Claims 7 and 8 of the '344 Patent Are Invalid; Order 17; Oct. 10, 2008' Investigation No. 337-TA-631.

Final Initial and Recommended Determination; Mar. 3, 2009; Investigation No. 337-TA-631.

'344 Claim Construction; RDX230-RDX246.


Complaint for Patent Infringement; Aug. 6, 2007; Demand for Jury Trial Case No. 2-07CV-330; Sharp.



'344 Validity - CDX250-CDX269 Samsung.


'344 Claim Construction; RDX254-RDX294 Sharp.


Commission Opinion; Investigation No. 337-TA-631; Jul. 14, 2009.


\* cited by examiner

**FIG. 1A**


**FIG. 1B****FIG. 2**


**FIG. 3**


**FIG. 4**

**FIG. 5**





**FIG. 6**


**FIG. 7**

**FIG. 8**

**FIG. 9**



**FIG. 10**

**FIG. 11**


**FIG. 12**

FIG. 13A





FIG. 13B












**FIG. 14**

FIG. 15



**FIG. 16****FIG. 17**

**FIG. 18****FIG. 19**

**FIG. 20**

# LIQUID CRYSTAL DISPLAY HAVING WIDE VIEWING ANGLE

## CROSS REFERENCE

The present application is a continuation of U.S. patent application Ser. No. 10/903,480 filed on Aug. 2, 2004 now U.S. Pat. No. 7,016,004 which is a continuation of U.S. patent application Ser. No. 09/877,481 filed on Jun. 8, 2001 issued as U.S. Pat. No. 6,771,344 which is a divisional of U.S. patent application Ser. No. 09/087,408 filed on May 29, 1998 issued as U.S. Pat. No. 6,285,431 all of which are incorporated herein in their entirety.

## BACKGROUND OF THE INVENTION

### (a) Field of the Invention

The present invention relates to a liquid crystal display having wide viewing angle.

### (b) Description of the Related Art

A liquid crystal display (LCD) includes two substrates and a liquid crystal layer interposed therebetween. The transmittance of the light is controlled by the strength of the electric field applied to the liquid crystal layer.

A conventional twisted nematic (TN) liquid crystal display, which is one of the most widely used LCD, has a couple of transparent substrates which have transparent electrodes respectively on their inner surfaces, a liquid crystal layer between two substrates, and a couple of polarizers which are attached to the outer surfaces of the substrates respectively. In off state of the LCD, i.e., in the state that the electric field is not applied to the electrodes, the long axes of the liquid crystal molecules are parallel to the substrates and twisted spirally with a constant pitch from the inner surface of one substrate to that of the other substrate, and thus the orientation of the long axes of the liquid crystal molecules vary continuously.

However, the contrast ratio of the conventional TN LCD in a normally black mode may not be so high because the incident light is not fully blocked in its off state, i.e., in absence of the electric field.

To solve this problem, a vertically aligned twisted nematic (VATN) mode LCD is proposed in the U.S. Pat. No. 3,914,022 and in "Eurodisplay '93", pp. 158-159 by Takahashi.

The VATN in normally black mode may have an off state which is sufficiently dark, because the liquid crystal molecules are aligned perpendicular to the substrates in off state. However, the viewing angle of the VATN LCD may not be so wide.

On the other hand, T. Yamamoto et al. disclosed a VATN simple matrix LCD using fringe fields in "SID '91, pp. 762-765", and Lien proposed a structure having an aperture in the pixel electrode to solve the problem of low transmittance in on state of a simple matrix multi domain VATN.

However, the structure that Lien proposed may have light leakage generated near the aperture.

## SUMMARY OF THE INVENTION

It is therefore an object of the present invention to widen the viewing angle of LCD.

It is another object of the present invention to prevent the disclination of LCD.

These and other objects, features and advantages are provided, according to the present invention, by a liquid crystal display comprising a first substrate having a common electrode, a second substrate having a pixel electrode and a stor-

age capacitor electrode. One of the electrodes has an aperture and the storage capacitor electrode is located at the position corresponding to the aperture.

The storage capacitor electrode prevents the light leakage due to a fringe field generated from the aperture.

Between the first and the second substrates, a liquid crystal layer having negative dielectric anisotropy may be interposed. The liquid crystal layer may include chiral nematic liquid crystal or nematic liquid crystal having chiral dopant of 0.01-3.0 wt %.

Two substrates may have alignment layers respectively, to align the molecular axes of the liquid crystal molecules perpendicular to the substrates. The alignment layers may be rubbed or not.

The storage capacitor electrode may be connected to a gate line and the number of the storage capacitor electrode may be more than one.

It is preferable that the width of the aperture is 3-15  $\mu\text{m}$  and the distance between the apertures is 8-50  $\mu\text{m}$ .

To obtain the wide viewing angle, the linear apertures in adjacent pixel regions extend in the different directions. For example, if the direction of the aperture of one pixel is parallel to the gate line, the aperture of the adjacent pixel is preferably perpendicular to the gate line. As a result, the liquid crystal molecules rotate in 4 directions.

## BRIEF DESCRIPTION OF THE DRAWINGS

FIGS. 1A and 1B are schematic diagrams of the alignment of liquid crystal molecules of a VATN LCD respectively in black state and white state according to an embodiment of the present invention.

FIG. 2 shows the structure of the electrodes and the alignment of the liquid crystal molecules of a VATN LCD according to an embodiment of the present invention.

FIG. 3 is a layout view of a common substrate according to the first embodiment of the present invention.

FIG. 4 is a layout view of a TFT (thin film transistor) substrate according to the first embodiment of the present invention.

FIG. 5 is a sectional view of a TFT substrate shown in FIG. 4 taken along the line V-V'.

FIG. 6 is a layout view of a common substrate according to the second embodiment of the present invention.

FIG. 7 is a layout view of a TFT substrate according to the second embodiment of the present invention.

FIG. 8 is a layout view of a common substrate according to the third embodiment of the present invention.

FIG. 9 is a layout view of a TFT substrate according to the third embodiment of the present invention.

FIG. 10 is a layout view of a common substrate according to the fourth embodiment of the present invention.

FIG. 11 is a layout view of a TFT substrate according to the fourth embodiment of the present invention.

FIG. 12 is a layout view of a substrate according to an embodiment of the present invention.

FIGS. 13A and 13B show rotated directions of the liquid crystal molecules near the apertures.

FIG. 14 is a layout view of a common substrate according to the fifth embodiment of the present invention.

FIG. 15 is a layout view of a TFT substrate according to the fifth embodiment of the present invention.

FIG. 16-19 are layout views of substrates according to the sixth to the ninth embodiments of the present invention.

FIG. 20 is a sectional view of LCD according to an embodiment of the present invention.

#### DETAILED DESCRIPTION OF THE PREFERRED EMBODIMENTS

The present invention will now be described more fully hereinafter with reference to the accompanying drawings, in which preferred embodiments of the present invention are shown. This invention may, however, be embodied in different forms and should not be construed as limited to the embodiments set forth herein. Rather, these embodiments are provided so that this disclosure will be thorough and complete, and will fully convey the scope of the invention to those skilled in the art. In the drawings, the thickness of layers and regions are exaggerated for clarity.

FIGS. 1A and 1B are schematic diagrams of the alignment of liquid crystal molecules of a VATN LCD respectively in black state and white state according to an embodiment of the present invention. FIG. 2 shows the structure of the electrodes and the alignment of the liquid crystal molecules of a VATN LCD according to an embodiment of the present invention.

As shown in FIGS. 1A and 1B, two glass substrates **1** and **2** are spaced apart from each other. On the inner surfaces of the substrates **1** and **2**, transparent electrodes **12** and **120** made of a transparent conductive material such as ITO (indium tin oxide) or the like are formed respectively, and alignment layers **14** and **140** are formed thereon respectively. Between the substrates **1** and **2**, a liquid crystal layer **100** including a chiral nematic liquid crystal having negative dielectric anisotropy or a nematic liquid crystal doped with chiral dopant of 0.01-0.3 wt % is disposed. On the outer surfaces of the substrates **1** and **2**, polarizers **13** and **130** are attached. The polarizers **13** and **130** polarize the rays incident on the liquid crystal layer **100** and the rays out of the liquid crystal layer **100** respectively. The polarizing directions of the polarizers **13** and **130** are perpendicular to each other. The alignment layers **14** and **140** may be rubbed or not.

FIG. 1A shows the off state that the electric field is not applied, where the long molecular axes of the liquid crystal molecules **3** in the liquid crystal layer **100** are aligned perpendicular to the surface of the substrates **1** and **2** by the aligning force of the alignment layers **14** and **140**.

The polarized light by the polarizer **13** attached to the lower substrate **1** passes through the liquid crystal layer **100** without changing its polarization. Then, the light is blocked by the analyzer **130** attached to the upper substrate **2** to make a black state.

FIG. 1B shows the on state that the sufficient electric field is applied to the liquid crystal layer **100** by the electrode **4** and **5**, where the liquid crystal molecules **3** in the liquid crystal layer **100** are twisted spirally by 90° from the lower substrate **1** to the upper substrate **2**, and the director of the liquid crystal layer **100** varies continuously. However, near the inner surfaces of two substrates **1**, **2**, the aligning force of the alignment layers **14**, **140** is larger than the force due to the applied electric field, and the liquid crystal molecules stay vertically aligned.

The polarized light by the polarizer **13** passes through the liquid crystal layer **100** and its polarization is rotated by 90° according to the variation of the director of the liquid crystal layer **100**. Therefore, the light passes through the analyzer **130** to make a white state.

FIG. 2 shows the structure of the electrodes and the alignment of the liquid crystal molecules of a VATN LCD according to an embodiment of the present invention. An ITO electrode **4** formed on the upper substrate **2** has an aperture **6**. In

absence of electric field as shown in FIG. 1A, the liquid crystal molecules **3** stay in its vertically aligned state to show the black state. If the electric field applied to the liquid crystal layer by the electrodes **4** and **5**, in most regions between the electrodes **4** and **5**, the field direction is perpendicular to the substrates **1** and **2**. However, near the aperture of the ITO electrode **4**, the electric field is not completely perpendicular to the substrate **2**. The electric field near the aperture is called the fringe field. The long axes of the liquid crystal molecules tend to be perpendicular to the field direction since the liquid crystal layer have negative dielectric anisotropy. Therefore, the directions of the long axes of the liquid crystal molecules are tilted and twisted near the fringe field.

An LCD according to embodiments of the present invention includes a TFT (thin film transistor) substrate and a common substrate. On the TFT substrate, a plurality of gate lines and data lines crossing each other are formed, and the gate lines and the data lines define pixel regions. On the common substrate, a common electrode having apertures and a black matrix which defines pixel regions are formed.

According to the first to the fourth embodiments of the present invention, a storage capacitor electrode is formed at the position corresponding to the aperture to shield the light leakage.

Now, the first embodiment of the present invention will be described with reference to FIGS. 3-5.

FIG. 3 is a layout view of a common substrate of a liquid crystal display according to the first embodiment of the present invention. FIG. 3 shows a pixel region, where a common electrode has apertures.

As shown in FIG. 3, a black matrix pattern **7** is formed along the boundary of a pixel region **P**, and a common electrode **6** is formed to cover the entire surface of the common substrate. The common electrode **6** has two longitudinally long linear apertures **15** which are spaced apart from and parallel to each other in a pixel region.

It is preferable that the width of the apertures **15** may be 3-15  $\mu\text{m}$ , and the distance between the apertures **15** may be 8-50  $\mu\text{m}$ . The width of 3-12  $\mu\text{m}$  and the distance of 10-30  $\mu\text{m}$  would be better.

FIG. 4 is a layout view of a TFT substrate according to the first embodiment of the present invention, and FIG. 5 is a sectional view of the TFT substrate taken along the line V-V' of FIG. 4.

As shown in FIGS. 4 and 5, a first and a second gate lines **81** and **82** spaced apart from each other are formed on a transparent glass substrate **20**, and extend in the horizontal or transverse direction. Two storage capacitor electrodes **11** which are separated from and parallel to each other connected to both the gate lines **81** and **82** are formed on the substrate **20**. The storage capacitor electrodes **11** are longitudinally lay, and they are located at the positions corresponding to the apertures **15** in the common electrode **6** on the common substrate.

A gate insulating layer **30** covers the storage capacitor electrodes **11** and the first and the second gate lines **81** and **82**. A data line **9** perpendicular to the gate lines **81** and **82** is formed on the gate insulating layer **30**. A TFT having a gate electrode which is a portion of the first gate line **81** is formed at a portion near the intersection of the first gate line **81** line and the data line **9**. A planarized passivation layer **40** is formed thereon, and a pixel electrode **10** overlapping the first and the second gate lines **81** and **82** and the data line **9** is formed on the passivation layer **40**. An alignment layer **50** is formed thereon, and the alignment layer **50** may be rubbed or may not.

Although the linear apertures in the common electrode extend longitudinally in this embodiment, they may extend horizontally or obliquely.

FIGS. 6 and 7 are the respective layout views of the common and TFT substrates having horizontal apertures according to the second embodiment.

As shown in FIG. 6, a black matrix pattern 7 is formed along the boundary of a pixel region P, and a common electrode 6 is formed to cover the entire surface of the common substrate. The common electrode 6 has a plurality of horizontally long linear apertures 15 which are spaced apart from and parallel to each other in a pixel region.

The width and the distance of the apertures 15 may be the same as those of the first embodiment.

On the other hand, as shown in FIG. 7, a first and a second gate lines 81 and 82 which are separated from each other and extend horizontally and a branch 12 connecting the gate lines 81 and 82 extending in a vertical direction are formed on a transparent glass substrate 20. A plurality of storage capacitor electrodes 11 which are parallel to each other and to the gate lines 81 and 82 are formed on the substrate and connected to the branch 12. The storage capacitor electrodes 11 are transversely lay, and they are located at the positions corresponding to the apertures 15 in the common electrode 6 on the common substrate.

FIGS. 8-11 are layout views of common and TFT substrates having oblique apertures according to the third and the fourth embodiments. In the third and the fourth embodiment, the apertures make an angle of 0°-90° to the data line and the gate line.

As shown in FIGS. 8 and 10, a black matrix pattern 7 is formed along the boundary of a pixel region P, and a common electrode 6 is formed to cover the entire surface of the common substrate. The common electrode 6 has two obliquely long linear apertures 15 which are spaced apart from each other in a pixel region.

In the third embodiment shown in FIG. 8, each pixel has an aperture extending in the down left direction from the up right edge and an aperture extending in the up left direction from the bottom right edge, and the end of apertures 15 reach the left central edge of the pixel. On the other hand, in the fourth embodiment illustrated in FIG. 10, each pixel has two parallel apertures extending in the up right or the down left direction.

The width and the distance of the apertures 15 may be the same as those of the first embodiment.

FIGS. 9 and 11 are the layout views of TFT substrates according to the third and the fourth embodiments of the present invention.

As shown in FIG. 9, a first and a second gate lines 81 and 82 which are separated from each other and extend horizontally and a branch 12 connecting the gate lines 81 and 82 extending in a vertical direction are formed on a transparent glass substrate 20. Two storage capacitor electrodes 11 on the substrate extend obliquely from the gate lines 81 and 82 to the left center of the pixel region P, and are connected to the branch 12.

A TFT substrate illustrated in FIG. 11 has a first and a second gate lines 81 and 82, a branch 12 and a data line 9 having the same shapes as those in the third embodiment shown in FIG. 9. Two storage capacitor electrodes 11 parallel to each other extend obliquely in the up right or the bottom left direction and are connected to the branch 12.

In the third and the fourth embodiments, as in the first embodiment, the position of the storage capacitor electrodes 11 are corresponding to the apertures 15 in the common electrode 6 on the common substrate to shield the light leakage due to a fringe field.

In the third and the fourth embodiments of the present invention, the alignment layers formed on the pixel electrode may be rubbed or may not. When the alignment layers are rubbed, the rubbing direction may make an angle of 0°-135° with respect to the direction of the linear aperture.

Next, the fifth embodiment of the present invention will be described. In the fifth embodiment, adjacent pixels have apertures extending different directions to widen the viewing angle.

FIG. 12 is a layout view of a common substrate according to the fifth embodiment.

As shown in FIG. 12, a black matrix pattern 7 is formed and defines a plurality of pixel regions corresponding to the red, green and blue color filters R, G and B. An ITO electrode 4 having a plurality of linear apertures 15 is formed thereon. The extending directions of the linear apertures of adjacent pixel regions are different from each other, i.e., horizontal apertures and vertical apertures are arranged alternately by pixel. For example, a red pixel region has vertical apertures and an green pixel region adjacent to the red pixel region has horizontal apertures.

It is assumed to display red color using this LCD. Then, the blue and the green pixels remain in their OFF state, and only the red pixels turn on. If the extending direction of the apertures of a first red pixel is horizontal, and the extending direction of the aperture of a second red pixel adjacent to the first red pixel is vertical.

Now, the behaviors of the liquid crystal molecules are described with reference to FIGS. 13A and 13B in this case.

The linear apertures 15 of the ITO electrode 4 extends vertically in FIG. 13A, while the linear apertures 15 of the ITO electrode 4 extends horizontally in FIG. 13B.

Here, the liquid crystal molecules are left-handed when viewed from the bottom of the drawing sheet.

When the voltage is applied to the electrodes 4 and 5, the liquid crystal molecules tilt in the directions perpendicular to the direction of the electric field due to the voltage difference between the electrodes 4 and 5, as shown in FIG. 2. In addition, as shown in FIGS. 13A and 13B, the liquid crystal molecules rotate clockwise in xy plane.

The tilt directions of the liquid crystal molecules vary according to the extending directions of the apertures. Since the tilt directions of the molecules opposite each other with respect to an aperture are opposite, and there are two extending directions of the apertures, the number of the tilt direction is about four on the Y axis in upper part twist to the right to the X axis, and those on the Y axis in lower part twist to the left to X axis due to the linear aperture formed along the Y axis.

Since the liquid crystal molecules tilt and rotate in four different directions, the viewing angles of up, down, left and right directions are equal and the gray inversion does not occur.

Now, the structures of the color filter and the TFT substrate according to the fifth embodiment are described more fully.

FIG. 14 is a layout view of a common substrate showing two adjacent pixels.

As shown in FIG. 14, a black matrix pattern 7 which defines pixel regions P1, P2 is formed on the substrate, and a common electrode 6 formed thereon.

The common electrode 6 has two vertical linear apertures 15 parallel to each other in the first pixel region P1, and has a plurality of horizontal linear apertures 15 parallel to each other in the second pixel region P2 adjacent to the first pixel region P1.

The width and the distance of the apertures may be the same as those of the first embodiment.



FIG. 15 is a layout view of a TFT substrate according to the fifth embodiment of the present invention. In a pixel region P1 corresponding to the pixel region P1 on the common substrate in FIG. 14, a first and a second gate lines 81 and 82 and two vertical storage capacitor electrodes 11 parallel to each other and connecting the gate lines 81 and 82 are formed as those in FIG. 4. In a pixel region P2, a branch 12 connecting two gate lines 81 and 82 extends parallel to a data line 9, and a plurality of storage capacitor electrodes 11 extend parallel to the gate lines 81 and 82 from the branch 12.

As all the above-described embodiments, the storage capacitor electrodes 11 are located at the positions corresponding to the apertures 15 in the common electrode 6.

The storage capacitor electrodes 11 overlaps a pixel electrode 10 to form storage capacitors, and play a role of a black matrix to prevent the light leakage caused by the disclination due to the apertures 15 in common electrode 6.

The apertures in adjacent pixel regions may have various shapes. FIGS. 16-19 are layout views of the sixth to the ninth embodiments having variously shaped apertures in adjacent pixel regions.

An LCD according to the sixth embodiment shown in FIG. 16 has first pixels having apertures shown in FIG. 10 and second pixels having apertures of shapes which is the same as the apertures in the first pixels rotated by 180° with respect to the central point of the pixel. In horizontal direction, two kinds of pixels are arranged alternately, and in vertical direction, pixels in a column are the same kind. As a whole, the apertures form a chevron shape in the sixth embodiment. An LCD according to the seventh embodiment shown in FIG. 17 has the same arrangement in the horizontal direction, however, in the vertical direction, two kinds of pixels are arranged alternately as in the horizontal direction. In the seventh embodiment, the apertures form a chevron shape in a row, but when viewing adjacent rows, the apertures form X or diamond shapes.

An LCD according to the eighth embodiment shown in FIG. 18 has first pixels having apertures shown in FIG. 8 and the second pixels having apertures of shapes which is the same as the apertures in the first pixels rotated by 180° with respect to the central point of the pixel. In horizontal direction, two kinds of pixels are arranged alternately, and in vertical direction, pixels in a column are the same kind. As a whole, the apertures form an X or diamond shape. An LCD according to the ninth embodiment shown in FIG. 19 has the same arrangement in the horizontal direction, however, in the vertical direction, two kinds of pixels are arranged alternately as in the horizontal direction. In the ninth embodiment, the apertures form an X or diamond shape in a row.

According to the embodiments of the present invention, column shaped spacers made of metal or organic material may be used instead of ball shaped spacers since the ball shaped spacers may cause light leakage due to the disturbance of the liquid crystal molecules near the spacers.

FIG. 20 shows a sectional view of an LCD having spacers according to an embodiment of the present invention. A liquid crystal layer 40 is interposed between a substrate 10 having a TFT 30 and a substrate 20 having a color filter (not shown). The TFT 30 formed on the lower substrate 10 includes a gate electrode 31, a gate insulating layer 32 formed thereon, a semiconductor layer 33 formed on a portion of the gate insulating layer 32 over the gate electrode 31, source/drain electrodes 341, 342 formed on the semiconductor layer 33. A passivation layer 50 covers the entire surface of the substrate 10 having the TFT 30. A pixel electrode 60 is formed in the pixel region and electrically connected to the drain electrode

342 through a contact hole in the passivation layer 50. A spacer 100 made of a metal or an organic material is formed on the TFT.

In the embodiments of the present invention, the apertures are formed in the common electrode 6, however, the apertures can be formed in the pixel electrode 10. When the apertures are formed in the pixel electrode 10, the fringe field generated between the pixel electrode 10 and the common electrode 6 may be affected by the voltages applied to the data line 9, the gate lines 81 and 82 and the storage capacitor electrode 11. To remove the influence due to the voltage applied to those signal lines, it is preferable that the thickness of the passivation layer 50 is equal to or more than 3 μm by using organic insulating material.

In the embodiments of the present invention, although the storage capacitor electrodes 11 are connected to the gate lines 81 and 82, the storage capacitor electrodes 11 may be connected to another signal sources.

According to the embodiments of the present invention, the liquid crystal molecules are tilted in the various directions due to the fringe field to have a wide viewing angle, and the storage capacitor electrodes prevents the light leakage near the fringe field.

In the drawings and specification, there have been disclosed typical preferred embodiments of the invention and, although specific terms are employed, they are used in a generic and descriptive sense only and not for purposes of limitation, the scope of the invention being set forth in the following claims.

What is claimed is:

1. A liquid crystal display comprising:

a first substrate;

a gate line formed on the first substrate;

a data line formed on the first substrate;

a first field-generating electrode formed on the first substrate, the first field-generating electrode comprising a first aperture as a domain divider in an upper portion and a second aperture as a domain divider in a lower portion;

a second substrate, spaced apart from the first substrate, and  
a liquid crystal layer comprising liquid crystal molecules having negative dielectric anisotropy and aligned substantially in a vertical direction to the first substrate when no electric field is applied to the liquid crystal layer, the liquid crystal layer being interposed between the first substrate and the second substrate and divided into a plurality of domain areas by the first aperture and the second aperture when an electric field is applied to the liquid crystal layer,

wherein the first aperture and the second aperture are linear apertures respectively, and are substantially arranged in a chevron and are slantingly extended with respect to the gate line or the data line,

wherein no other linear aperture as a domain divider crosses over or meets the first aperture or the second aperture, and the first and second apertures are spaced apart from each other in a pixel region, and

wherein widths of the first aperture and the second aperture are about 3 μm to about 15 μm, respectively.

2. A liquid crystal display of claim 1, further comprises an organic insulating layer formed on the data line and the gate line, wherein the first field-generating electrode is formed on the organic insulating layer.

3. A liquid crystal display of claim 2, wherein the organic insulating layer is equal or more than 3 μm.

9

4. A liquid crystal display of claim 2, further comprises an organic spacer disposed between the first substrate and the second substrate.

5. A liquid crystal display of claim 1, further comprises a first storage electrode overlapped with one of edge portions of the first field-generating electrode, wherein the first storage electrode extends in parallel with the gate line and one portion of outer edge lines of the first field-generating electrode is disposed inside the first storage electrode and along the first storage electrode.

6. A liquid crystal display of claim 5, further comprises a second storage electrode overlapped with the first field-generating electrode and electrically connected to the first storage electrode, wherein the second storage electrode extends in parallel with the data line.

7. A liquid crystal display of claim 5, further comprises a third storage electrode overlapped with the first field-generating electrode and electrically connected to the first storage electrode, wherein the third storage electrode slantingly extends with respect to the gate line or the data line.

8. A liquid crystal display of claim 1, wherein the liquid crystal layer is divided into four different domain areas by the first aperture and the second aperture.

10

9. A liquid crystal display of claim 8, further comprises a first storage electrode overlapped with one of edge portions of the first field-generating electrode, wherein the first storage electrode extends in parallel with the gate line and one portion of outer edge lines of the first field-generating electrode is disposed inside the first storage electrode and along the first storage electrode.

10. A liquid crystal display of claim 9, further comprises a second storage electrode overlapped with the first field-generating electrode and electrically connected to the first storage electrode, wherein the second storage electrode extends in parallel with the data line.

11. A liquid crystal display of claim 9, further comprises a third storage electrode overlapped with the first field-generating electrode and electrically connected to the first storage electrode, wherein the third storage electrode slantingly extends with respect to the gate line or the data line.

12. A liquid crystal display of claim 1, wherein the first field-generating electrode overlaps adjacent data lines.

13. A liquid crystal display of claim 12, wherein the first field-generating electrode overlaps the gate line.

\* \* \* \* \*

专利名称(译)	具有宽视角的液晶显示器		
公开(公告)号	<a href="#">US7768615</a>	公开(公告)日	2010-08-03
申请号	US11/334025	申请日	2006-01-18
[标]申请(专利权)人(译)	LYU JAE 金 KIM KYEONG ^ h LEE HEA RI 陈健MIN		
申请(专利权)人(译)	LYU JAE-JIN KIM KYEONG ^ h 李HEA-RI 陈建民		
当前申请(专利权)人(译)	三星DISPLAY CO. , LTD.		
[标]发明人	LYU JAE JIN KIM KYEONG HYEON LEE HEA RI CHEN JIAN MIN		
发明人	LYU, JAE-JIN KIM, KYEONG-HYEON LEE, HEA-RI CHEN, JIAN-MIN		
IPC分类号	G02F1/1343 G02F1/1337 G02F1/13 G02F1/1333 G02F1/1335 G02F1/1362 G02F1/139		
CPC分类号	G02F1/133707 G02F1/134336 G02F1/1393 G02F1/137 G02F1/136213 G02F1/133512 G02F1/1337 G02F1/134309 G02F2001/13712 G02F2001/134372 G02F2201/121 G02F2201/128		
代理机构(译)	康托科尔伯恩LLP		
审查员(译)	粗鲁 , TIMOTHY		
优先权	1019970021708 1997-05-29 KR 1019970040665 1997-08-25 KR		
其他公开文献	US20060114402A1		
外部链接	<a href="#">Espacenet</a> <a href="#">USPTO</a>		

#### 摘要(译)

孔径形成在液晶显示器的公共电极或像素电极中以形成边缘场。存储电容器电极形成在与孔对应的位置处，以防止由于边缘场引起的向错导致的漏光。孔径水平，垂直或倾斜地延伸。相邻像素区域中的孔可以具有不同的方向以加宽视角。

