



US008144094B2

(12) **United States Patent**
Brown Elliott et al.

(10) **Patent No.:** **US 8,144,094 B2**
(45) **Date of Patent:** ***Mar. 27, 2012**

(54) **LIQUID CRYSTAL DISPLAY BACKPLANE LAYOUTS AND ADDRESSING FOR NON-STANDARD SUBPIXEL ARRANGEMENTS**

(75) Inventors: **Candice Hellen Brown Elliott**, Santa Rosa, CA (US); **Thomas Lloyd Credelle**, Morgan Hill, CA (US); **Matthew Osborne Schlegel**, Palo Alto, CA (US); **Seok Jin Han**, Cupertino, CA (US)

(73) Assignee: **Samsung Electronics Co., Ltd.** (KR)

(*) Notice: Subject to any disclaimer, the term of this patent is extended or adjusted under 35 U.S.C. 154(b) by 823 days.

This patent is subject to a terminal disclaimer.

(21) Appl. No.: **12/147,286**

(22) Filed: **Jun. 26, 2008**

(65) **Prior Publication Data**

US 2008/0252581 A1 Oct. 16, 2008

Related U.S. Application Data

(63) Continuation of application No. 10/456,838, filed on Jun. 6, 2003, now Pat. No. 7,397,455.

(51) **Int. Cl.**
G09G 3/36 (2006.01)

(52) **U.S. Cl.** **345/88**; 345/694

(58) **Field of Classification Search** 345/88, 345/89, 96, 694; 349/88, 139
See application file for complete search history.

(56) **References Cited**

U.S. PATENT DOCUMENTS

3,971,065 A 7/1976 Bayer
4,353,062 A 10/1982 Lortetje et al.

4,642,619 A 2/1987 Togashi
4,651,148 A 3/1987 Takeda et al.
4,773,737 A 9/1988 Yokono et al.
4,781,438 A 11/1988 Noguchi
4,792,728 A 12/1988 Chang et al.
4,800,375 A 1/1989 Silverstein et al.
4,822,142 A 4/1989 Yasui
4,853,592 A 8/1989 Stratham
4,874,986 A 10/1989 Menn et al.

(Continued)

FOREIGN PATENT DOCUMENTS

DE 197 46 329 A1 3/1999

(Continued)

OTHER PUBLICATIONS

Brown Elliott, C., "Active Matrix Display . . .", IDMC 2000, 185-189, Aug. 2000.

(Continued)

Primary Examiner — Quan-Zhen Wang


Assistant Examiner — Yuk Chow

(74) *Attorney, Agent, or Firm* — Innovation Counsel LLP

(57) **ABSTRACT**

Liquid crystal display backplane layouts and addressing for non-standard subpixel arrangements are disclosed. A liquid crystal display comprises a panel and a plurality of transistors. The panel substantially comprises a subpixel repeating group having an even number of subpixels in a first direction. Each thin film transistor connects one subpixel to a row and a column line at an intersection in one of a group of quadrants. The group comprises a first quadrant, a second quadrant, a third quadrant and a fourth quadrant, wherein the thin film transistors are formed in a backplane structure adjacent to intersections of the row and column lines. The thin film transistors are also substantially formed in more than one quadrant in the backplane structure.

20 Claims, 21 Drawing Sheets



U.S. PATENT DOCUMENTS

4,886,343 A	12/1989	Johnson	6,396,505 B1	5/2002	Lui et al.
4,908,609 A	3/1990	Stroomer	6,469,756 B1	10/2002	Booth, Jr.
4,920,409 A	4/1990	Yamagishi	6,469,766 B2	10/2002	Waterman et al.
4,965,565 A	10/1990	Noguchi	6,545,653 B1	4/2003	Takahara et al.
5,006,840 A	4/1991	Hamada et al.	6,552,706 B1	4/2003	Ikeda et al.
5,052,785 A	10/1991	Takimoto et al.	6,570,584 B1	5/2003	Cok et al.
5,083,853 A	1/1992	Ueki et al.	6,590,555 B2	7/2003	Su et al.
5,097,297 A	3/1992	Nakazawa	6,624,828 B1	9/2003	Dresevic et al.
5,113,274 A	5/1992	Takahashi et al.	6,661,429 B1	12/2003	Phan
5,124,695 A	6/1992	Green	6,674,430 B1	1/2004	Kaufman et al.
5,142,392 A	8/1992	Ueki et al.	6,674,436 B1	1/2004	Dresevic et al.
5,144,288 A	9/1992	Hamada et al.	6,680,761 B1	1/2004	Greene et al.
5,184,114 A	2/1993	Brown	6,714,206 B1	3/2004	Martin et al.
5,191,451 A	3/1993	Katayama et al.	6,714,212 B1	3/2004	Tsuboyama et al.
5,311,205 A	5/1994	Hamada et al.	6,714,243 B1	3/2004	Mathur et al.
5,311,337 A	5/1994	McCartney, Jr.	6,727,878 B2	4/2004	Okuzono et al.
5,315,418 A	5/1994	Sprague et al.	6,738,204 B1	5/2004	Chuang et al.
5,334,996 A	8/1994	Tanigaki et al.	6,750,875 B1	6/2004	Keely, Jr. et al.
5,341,153 A	8/1994	Benzschawel et al.	6,771,028 B1	8/2004	Winters
5,384,266 A	1/1995	Chapman	6,804,407 B2	10/2004	Weldy
5,398,066 A	3/1995	Martinez-Uriegas et al.	6,833,890 B2	12/2004	Hong et al.
5,436,747 A	7/1995	Suzuki	6,836,300 B2	12/2004	Choo et al.
5,459,595 A	10/1995	Ishiguro	6,850,294 B2	2/2005	Roh et al.
5,461,503 A	10/1995	Defontaine et al.	6,867,549 B2	3/2005	Cok et al.
5,485,293 A	1/1996	Robinder	6,885,380 B1	4/2005	Primerano et al.
5,535,028 A	7/1996	Bae et al.	6,888,604 B2	5/2005	Rho et al.
5,563,621 A	10/1996	Silsby	6,897,876 B2	5/2005	Murdoch et al.
5,579,027 A	11/1996	Sakurai et al.	6,903,378 B2	6/2005	Cok
5,646,702 A	7/1997	Akinwande et al.	6,927,754 B2	8/2005	Lai
5,648,793 A	7/1997	Chen	6,930,676 B2	8/2005	De Haan et al.
5,739,802 A	4/1998	Mosier	6,937,217 B2	8/2005	Klompenshouwer et al.
5,754,163 A	5/1998	Kwon	6,989,876 B2	1/2006	Song et al.
5,754,226 A	5/1998	Yamada et al.	6,995,346 B2	2/2006	Johannesson et al.
5,767,829 A	6/1998	Verhulst	7,110,012 B2	9/2006	Messing et al.
5,808,594 A	9/1998	Tsubyama et al.	7,129,955 B2	10/2006	Motomura
5,818,405 A	10/1998	Eglit et al.	7,151,518 B2	12/2006	Fukumoto
5,818,968 A	10/1998	Yoshimoto	7,187,353 B2	3/2007	Credelle et al.
5,877,512 A	3/1999	Kim	7,209,105 B2 *	4/2007	Elliott 345/89
5,899,550 A	5/1999	Masaki	7,218,301 B2 *	5/2007	Credelle 345/96
5,949,396 A	9/1999	Lee	7,230,667 B2	6/2007	Shin et al.
5,971,546 A	10/1999	Park	2001/0015716 A1	8/2001	Kim
6,002,446 A	12/1999	Eglit	2001/0017607 A1	8/2001	Kwon et al.
6,005,692 A	12/1999	Stahl	2001/0048764 A1	12/2001	Betrissey et al.
6,008,868 A	12/1999	Silverbrook	2001/0052897 A1	12/2001	Nakano et al.
6,023,315 A	2/2000	Harrold et al.	2002/0015110 A1	2/2002	Brown Elliott
6,037,719 A	3/2000	Yap et al.	2002/0030780 A1	3/2002	Nishida et al.
6,064,363 A	5/2000	Kwon	2002/0093476 A1	7/2002	Hill et al.
6,069,670 A	5/2000	Borer	2002/0149598 A1	10/2002	Greier et al.
6,088,050 A	7/2000	Ng	2002/0158997 A1	10/2002	Fukami et al.
6,097,367 A	8/2000	Kuriwaki et al.	2003/0006978 A1	1/2003	Fujiyoshi
6,108,122 A	8/2000	Ulrich et al.	2003/0011603 A1	1/2003	Koyama et al.
6,115,092 A	9/2000	Greene et al.	2003/0016310 A1	1/2003	Lee et al.
6,144,352 A	11/2000	Matsuda et al.	2003/0034992 A1	2/2003	Brown Elliott et al.
6,147,664 A	11/2000	Hansen	2003/0071943 A1	4/2003	Choo et al.
6,151,001 A	11/2000	Anderson et al.	2003/0077000 A1	4/2003	Blinn et al.
6,160,535 A	12/2000	Park	2003/0090581 A1	5/2003	Credelle et al.
6,188,385 B1	2/2001	Hill et al.	2003/0117423 A1	6/2003	Brown Elliott
6,198,507 B1	3/2001	Ishigami	2003/0128179 A1	7/2003	Credelle
6,219,019 B1	4/2001	Hasegawa	2003/0128225 A1	7/2003	Credelle et al.
6,219,025 B1	4/2001	Hill et al.	2003/0146893 A1	8/2003	Sawabe
6,225,967 B1	5/2001	Hebiguchi	2003/0189537 A1	10/2003	Yun
6,225,973 B1	5/2001	Hill et al.	2003/0214499 A1	11/2003	Ohsawa et al.
6,236,390 B1	5/2001	Hitchcock	2003/0218618 A1	11/2003	Phan
6,239,783 B1	5/2001	Hill et al.	2004/0008208 A1	1/2004	Dresevic et al.
6,243,055 B1	6/2001	Ferguson	2004/0021804 A1	2/2004	Hong et al.
6,243,070 B1	6/2001	Hill et al.	2004/0046714 A1	3/2004	Brown Elliott
6,278,434 B1	8/2001	Hill et al.	2004/0061710 A1	4/2004	Messing et al.
6,326,981 B1	12/2001	Mori et al.	2004/0075764 A1	4/2004	Law et al.
6,327,008 B1	12/2001	Fujiyoshi	2004/0085495 A1	5/2004	Roh et al.
6,332,030 B1	12/2001	Manjunath et al.	2004/0094766 A1	5/2004	Lee et al.
6,335,719 B1	1/2002	An et al.	2004/0095521 A1	5/2004	Song et al.
6,340,998 B1	1/2002	Kim et al.	2004/0104873 A1	6/2004	Kang et al.
6,342,876 B1	1/2002	Kim	2004/0108818 A1	6/2004	Cok et al.
6,348,929 B1	2/2002	Acharya et al.	2004/0114046 A1	6/2004	Lee et al.
6,377,262 B1	4/2002	Hitchcock et al.	2004/0140983 A1	7/2004	Credelle
6,388,644 B1	5/2002	De Zwart et al.	2004/0150651 A1	8/2004	Phan
6,392,717 B1	5/2002	Kunzman	2004/0155895 A1	8/2004	Lai
6,393,145 B2	5/2002	Betrissey et al.	2004/0169807 A1	9/2004	Rho et al.
			2004/0174389 A1	9/2004	Ben-David et al.

2004/0179160	A1	9/2004	Rhee et al.	
2004/0189662	A1	9/2004	Friskén et al.	
2004/0189664	A1	9/2004	Friskén et al.	
2004/0213449	A1	10/2004	Safee-Rad et al.	
2004/0223005	A1	11/2004	Lee	
2004/0239813	A1	12/2004	Klompénhouwer	
2004/0239837	A1	12/2004	Hong et al.	
2004/0246213	A1	12/2004	Credelle et al.	
2004/0246278	A1	12/2004	Elliott	
2004/0246279	A1	12/2004	Credelle et al.	
2004/0246280	A1	12/2004	Credelle et al.	
2004/0246381	A1	12/2004	Credelle	
2004/0246404	A1 *	12/2004	Elliott et al.	349/88
2004/0247070	A1	12/2004	Ali et al.	
2004/0263528	A1	12/2004	Murdoch et al.	
2005/0007539	A1	1/2005	Taguchi et al.	
2005/0024380	A1	2/2005	Lin et al.	
2005/0040760	A1	2/2005	Taguchi et al.	
2005/0068477	A1	3/2005	Shin et al.	
2005/0083277	A1	4/2005	Credelle	
2005/0083356	A1	4/2005	Roh et al.	
2005/0099426	A1	5/2005	Primerano et al.	
2005/0140634	A1	6/2005	Takatori	
2005/0151752	A1	7/2005	Phan	
2005/0162600	A1 *	7/2005	Rho et al.	349/139
2005/0219274	A1	10/2005	Yang et al.	
2007/0229430	A1 *	10/2007	Wang et al.	345/96
2009/0051638	A1 *	2/2009	Horiuchi et al.	345/88
2009/0102769	A1 *	4/2009	Kouno et al.	345/88

FOREIGN PATENT DOCUMENTS

DE	299 09 537	U1	10/1999
DE	199 23 527		11/2000
DE	201 09 354	U1	9/2001
EP	0 158 366	A2	10/1985
EP	0 203 005	A1	11/1986
EP	0 322 106	A2	6/1989
EP	0 671 650	A2	9/1995
EP	0 812 114	A1	12/1997
EP	0 878 969	A3	11/1998
EP	0 899 604	A2	3/1999
EP	1 261 014	A2	11/2002
EP	1 381 020	A2	1/2004
GB	2 133 912	A	8/1984
GB	2 146 478	A	4/1985
JP	60-107022		6/1985
JP	02-000826	A	1/1990
JP	02-983027	B2	4/1991
JP	03-78390		4/1991
JP	06-102503		4/1994
JP	06-324649		11/1994
JP	08-202317		8/1996
JP	2004-004822		1/2004
JP	2004 078218		3/2004
TW	499664		8/2002
WO	WO 00/21067		4/2000
WO	WO 00/42762		7/2000
WO	WO 00/45365		8/2000
WO	WO 00/65432		11/2000
WO	WO 01/10112	A2	2/2001
WO	WO 01/52546	A2	7/2001
WO	WO 02/059685	A2	8/2002
WO	WO 02/099557	A2	12/2002
WO	WO 02/101644	A2	12/2002
WO	WO 03/014819	A1	2/2003

WO	WO 03/050605	A1	2/2003
WO	WO 03/034380	A2	4/2003
WO	WO 03/056383	A1	7/2003
WO	WO 2004/017129	A1	2/2004
WO	WO 2004/021323	A2	3/2004
WO	WO 2004/027503	A1	4/2004
WO	WO 2004/086128	A1	10/2004
WO	WO 2005/050296	A1	6/2005

OTHER PUBLICATIONS

Brown Elliott, C., "Color Subpixel Rendering Projectors and Flat Panel Displays," SMPTE, Feb. 27-Mar. 1, 2003, Seattle, WA pp. 1-4.

Brown Elliott, C., "Co-Optimization of Color AMLCD Subpixel Architecture and Rendering Algorithms," SID 2002 Proceedings Paper, May 30, 2002 pp. 172-175.

Brown Elliott, C., "Development of the PenTile Matrix™ Color AMLCD Subpixel Architecture and Rendering Algorithms", SID 2003, Journal Article.

Brown Elliott, C., "New Pixel Layout for PenTile Matrix™ Architecture", IDMC 2002, pp. 115-117.

Brown Elliott, C., "Pentile Matrix™ Displays and Drivers" ADEAC Proceedings Paper, Portland OR., Oct. 2005.

Brown Elliott, C., "Reducing Pixel Count Without Reducing Image Quality", Information Display Dec. 1999, vol. 1, pp. 22-25.

Credelle, Thomas, "P-00: MTF of High-Resolution PenTile Matrix Displays", Eurodisplay 02 Digest, 2002 pp. 1-4.

Daly, Scott, "Analysis of Subtriad Addressing Algorithms by Visual System Models", SID Symp. Digest, Jun. 2001 pp. 1200-1203.

Klompénhouwer, Michiel, Subpixel Image Scaling for Color Matrix Displays, SID Symp. Digest, May 2002, pp. 176-179.

Michiel A. Klompénhouwer, Gerard de Haan, Subpixel image scaling for color matrix displays, Journal of the Society for Information Display, vol. 11, Issue 1, Mar. 2003, pp. 99-108.

Krantz, John et al., Color Matrix Display Image Quality: The Effects of Luminance . . . SID 90 Digest, pp. 29-32.

Lee, Baek-woon et al., 40.5L: Late-News Paper: TFT-LCD with RGBW Color system, SID 03 Digest, 2003, pp. 1212-1215.

Messing, Dean et al., Improved Display Resolution of Subsampled Colour Images Using Subpixel Addressing, IEEE ICIP 2002, vol. 1, pp. 625-628.

Messing, Dean et al., Subpixel Rendering on Non-Striped Colour Matrix Displays, 2003 International Conf on Image Processing, Sep. 2003, Barcelona, Spain, 4 pages.

Okumura et al., "A New Flicker-Reduction Drive Method for High Resolution LCTVs", SID Digest, pp. 551-554, 2001.

PCT International Search Report dated Dec. 9, 2005 for PCT/US04/18034 (U.S. Appl. No. 10/455,925).

PCT International Search Report dated Feb. 1, 2006 for PCT/US04/18038 (U.S. Appl. No. 10/455,931).

PCT International Search Report dated Mar. 15, 2006 for PCT/US04/18033 (U.S. Appl. No. 10/455,927).

PCT International Search Report dated Jan. 10, 2006 for PCT/US04/18035 (U.S. Appl. No. 10/456,806).

PCT International Search Report dated Sep. 24, 2004 for PCT/US04/17796 (U.S. Appl. No. 10/456,838).

PCT International Search Report dated Feb. 24, 2005 for PCT/US04/18037 (U.S. Appl. No. 10/456,794).

PCT International Search Report dated Nov. 3, 2004 for PCT/US04/18036 (U.S. Appl. No. 10/696,236).

* cited by examiner




FIG. 1A
(PRIOR ART)





FIG. 1B
(PRIOR ART)



200

FIG. 2




FIG. 3

300




FIG. 4




FIG. 5




FIG. 6





FIG. 7

**FIG. 9**




FIG. 10

<u>OPTION</u>	<u>R</u>	<u>G</u>
1	+	+
2	+	-
3	-	+
4	-	-

EXAMPLE - OPTION 1






FIG. 11



		+	-	+	-	+	-	+	-	+	
0											
		+	R+	B-	G+	B-	R	B+	G	B+	R
0											
		+		-		+		-		+	
E			G	B-	R	B-	G	B+	R	B+	G
		-		+		-		+		-	
E											
			R	B+	G	B+	R	B-	G	B-	R
		-		+		-		+		-	
E											
			G	B+	R	B+	G	B-	R	B-	G
0			+	-		+	-		+	-	
			R	B-	G	B-	R	B+	G	B+	R

...

•
•
•

FIG. 14



		+	-	+	-	+	-	+	-	+	
0											
		+	R+	B-	G+	B-	R-	B+	G-	B+	R+
0											
		+		-		+		-		+	
E			G-	B-	R-	B-	G+	B+	R+	B+	G-
		-		+		-		+		-	
E											
			R-	B+	G-	B+	R+	B-	G+	B-	R-
		-		+		-		+		-	
E											
			G+	B+	R+	B+	G-	B-	R-	B-	G+
0			+	-		+	-		+	-	
			R+	B-	G+	B-	R-	B+	G-	B+	R+

...

1502

•
•
•

FIG. 15






FIG. 16C




FIG. 17A
(PRIOR ART)

FIG. 17B

FIG. 17C

FIG. 18
(PRIOR ART)





FIG. 19B

FIG. 19A






FIG. 21B

FIG. 21A

LIQUID CRYSTAL DISPLAY BACKPLANE LAYOUTS AND ADDRESSING FOR NON-STANDARD SUBPIXEL ARRANGEMENTS

This application is a continuation of U.S. patent application Ser. No. 10/456,838, filed on Jun. 6, 2003, and claims the benefit of priority thereof and is now issued as U.S. Pat. No. 7,397,455 which is hereby incorporated by reference.

RELATED APPLICATIONS

The present application is related to commonly owned (and filed on even date) United States Patent Applications: (1) United States Patent Publication No. 2004/0246213 ("the '213 application") U.S. patent application Ser. No. 10/455,925 entitled "DISPLAY PANEL HAVING CROSSOVER CONNECTIONS EFFECTING DOT INVERSION"; (2) U.S. Pat. No. 7,218,301 ("the '301 patent") U.S. patent application Ser. No. 10/455,931 entitled "SYSTEM AND METHOD OF PERFORMING DOT INVERSION WITH STANDARD DRIVERS AND BACKPLANE ON NOVEL DISPLAY PANEL LAYOUTS"; (3) U.S. Pat. No. 7,209,105 ("the '105 patent") U.S. patent application Ser. No. 10/455,927 entitled "SYSTEM AND METHOD FOR COMPENSATING FOR VISUAL EFFECTS UPON PANELS HAVING FIXED PATTERN NOISE WITH REDUCED QUANTIZATION ERROR"; (4) U.S. Pat. No. 7,187,353 ("the '353 patent") U.S. patent application Ser. No. 10/456,806 entitled "DOT INVERSION ON NOVEL DISPLAY PANEL LAYOUTS WITH EXTRA DRIVERS"; and (5) United States Patent Publication No. 2004/0246280 ("the '280 application") U.S. patent application Ser. No. 10/456,839 entitled "IMAGE DEGRADATION CORRECTION IN NOVEL LIQUID CRYSTAL DISPLAYS," which are hereby incorporated herein by reference.

BACKGROUND

In commonly owned United States Patent Applications: (1) U.S. Pat. No. 6,903,754 ("the '754 patent") U.S. patent application Ser. No. 09/916,232 entitled "ARRANGEMENT OF COLOR PIXELS FOR FULL COLOR IMAGING DEVICES WITH SIMPLIFIED ADDRESSING," filed Jul. 25, 2001; (2) United States Patent Publication No. 2003/0128225 ("the '225 application") U.S. patent application Ser. No. 10/278,353 entitled "IMPROVEMENTS TO COLOR FLAT PANEL DISPLAY SUB-PIXEL ARRANGEMENTS AND LAYOUTS FOR SUB-PIXEL RENDERING WITH INCREASED MODULATION TRANSFER FUNCTION RESPONSE," filed Oct. 22, 2002; (3) United States Patent Publication No. 2003/0128179 ("the '179 application") U.S. patent application Ser. No. 10/278,352, entitled "IMPROVEMENTS TO COLOR FLAT PANEL DISPLAY SUB-PIXEL ARRANGEMENTS AND LAYOUTS FOR SUB-PIXEL RENDERING WITH SPLIT BLUE SUB-PIXELS," filed Oct. 22, 2002; (4) United States Patent Publication No. 2004/0051724 ("the '724 application") U.S. patent application Ser. No. 10/243,094, entitled "IMPROVED FOUR COLOR ARRANGEMENTS AND EMITTERS FOR SUB-PIXEL RENDERING," filed Sep. 13, 2002; (5) United States Patent Publication No. 2003/0117423 ("the '423 application") U.S. patent application Ser. No. 10/278,328, entitled "IMPROVEMENTS TO COLOR FLAT PANEL DISPLAY SUB-PIXEL ARRANGEMENTS AND LAYOUTS WITH REDUCED BLUE LUMINANCE WELL VISIBILITY," filed Oct. 22, 2002; (6) U.S. Pat. No. 7,283,142 ("the '142 patent") U.S.

patent application Ser. No. 10/278,393, entitled "COLOR DISPLAY HAVING HORIZONTAL SUB-PIXEL ARRANGEMENTS AND LAYOUTS," filed Oct. 22, 2002; (7) United States Patent Publication No. 2004/0080479 ("the '479 application") U.S. patent application Ser. No. 10/347,001 entitled "IMPROVED SUB-PIXEL ARRANGEMENTS FOR STRIPED DISPLAYS AND METHODS AND SYSTEMS FOR SUB-PIXEL RENDERING SAME," filed Jan. 16, 2003, novel sub-pixel arrangements are therein disclosed for improving the cost/performance curves for image display devices and herein incorporated by reference.

These improvements are particularly pronounced when coupled with sub-pixel rendering (SPR) systems and methods further disclosed in those applications and in commonly owned United States Patent Applications: (1) U.S. Pat. No. 7,123,277 ("the '277 patent") U.S. patent application Ser. No. 10/051,612, entitled "CONVERSION OF A SUB-PIXEL FORMAT DATA TO ANOTHER SUB-PIXEL DATA FORMAT," filed Jan. 16, 2002; (2) U.S. Pat. No. 7,221,381 ("the '381 patent") U.S. patent application Ser. No. 10/150,355, entitled "METHODS AND SYSTEMS FOR SUB-PIXEL RENDERING WITH GAMMA ADJUSTMENT," filed May 17, 2002; (3) U.S. Pat. No. 7,184,066 ("the '066 patent") U.S. patent application Ser. No. 10/215,843, entitled "METHODS AND SYSTEMS FOR SUB-PIXEL RENDERING WITH ADAPTIVE FILTERING," filed Aug. 8, 2002; (4) United States Patent Publication No. 2004/0196302 ("the '302 application") U.S. patent application Ser. No. 10/379,767, entitled "SYSTEMS AND METHODS FOR TEMPORAL SUB-PIXEL RENDERING OF IMAGE DATA" filed Mar. 4, 2003; (5) U.S. Pat. No. 7,167,186 ("the '186 patent") U.S. patent application Ser. No. 10/379,765, entitled "SYSTEMS AND METHODS FOR MOTION ADAPTIVE FILTERING," filed Mar. 4, 2003; (6) U.S. Pat. No. 6,917,368 ("the '368 patent") U.S. patent application Ser. No. 10/379,766 entitled "SUB-PIXEL RENDERING SYSTEM AND METHOD FOR IMPROVED DISPLAY VIEWING ANGLES" filed Mar. 4, 2003; (7) U.S. Pat. No. 7,352,374 ("the '374 patent") U.S. patent application Ser. No. 10/409,413 entitled "IMAGE DATA SET WITH EMBEDDED PRE-SUBPIXEL RENDERED IMAGE" filed Apr. 7, 2003, which are hereby incorporated herein by reference.

BRIEF DESCRIPTION OF THE DRAWINGS

The accompanying drawings, which are incorporated in, and constitute a part of this specification illustrate exemplary implementations and embodiments of the invention and, together with the description, serve to explain principles of the invention.

FIG. 1A shows a conventional RGB stripe panel with 1x1 dot inversion.

FIG. 1B shows a conventional RGB stripe panel with 1x2 dot inversion.

FIG. 2 shows a panel having a novel subpixel repeating group of even number of subpixels in a first (row) direction with a conventional 1x1 dot inversion scheme.

FIG. 3 shows the panel of FIG. 2 with a novel TFT backplane layout.

FIG. 4 depicts the operation of the panel of FIG. 3 during two row-writes.

FIG. 5 depicts another embodiment of a TFT backplane layout with a 1x1 dot inversion scheme.

FIG. 6 depicts the panel of FIG. 5 with a 1x2 dot inversion scheme.

FIG. 7 depicts a panel wherein at least two regions are defined with TFTs constructed in the a first region of a pixel and TFTs constructed in a second region of a pixel.

FIGS. 8 through 15 depict a general technique for remapping TFT to a backplane layout so as to effect a desired dot inversion scheme on a panel having a novel subpixel repeating group.

FIGS. 16A and 16B show a particular embodiment of a TFT backplane layout on a panel having a novel subpixel repeating group with a 1x2 dot inversion scheme.

FIG. 16C shows yet another embodiment of a TFT backplane layout with a novel subpixel repeating group affecting a 1x2 dot inversion scheme.

FIGS. 17A, 17B, and 17C show particular TFTs having a double source/drain structure.

FIG. 18 shows a TFT with a double gate structure.

FIGS. 19A and 19B show TFT structures in a normal orientation and a reverse orientation respectively.

FIGS. 20A and 20B show TFT structures in a normal orientation and a reverse orientation with an added gate crossover in the normal orientation to balance any parasitic capacitance found in the reverse orientation.

FIGS. 21A and 21B show TFT structures in a normal orientation and a reverse orientation with one fewer gate crossover in the reverse orientation to match any parasitic capacitance in the normal orientation.

FIG. 22 shows one novel pixel element design having a corner removed from the pixel to balance parasitic capacitances.

FIG. 23 shows yet another novel pixel element design having multiple corners removed to balance parasitic capacitances.

FIG. 24 shows yet another novel pixel structure in which at least one extra line is added to shield the pixel element from parasitic effects.

DETAILED DESCRIPTION

Reference will now be made in detail to implementations and embodiments, examples of which are illustrated in the accompanying drawings. Wherever possible, the same reference numbers will be used throughout the drawings to refer to the same or like parts.

FIG. 1A shows a conventional RGB stripe structure on panel 100 for an Active Matrix Liquid Crystal Display (AM-LCD) having thin film transistors (TFTs) 116 to activate individual colored subpixels—red 104, green 106 and blue 108 subpixels respectively. As may be seen, a red, a green and a blue subpixel form a repeating group of subpixels 102 that comprise the panel.

As also shown, each subpixel is connected to a column line (each driven by a column driver 110) and a row line (e.g. 112 and 114). In the field of AMLCD panels, it is known to drive the panel with a dot inversion scheme to reduce crosstalk and flicker. FIG. 1A depicts one particular dot inversion scheme—i.e. 1x1 dot inversion—that is indicated by a “+” and a “-” polarity given in the center of each subpixel. Each row line is typically connected to a gate (not shown in FIG. 1A) of TFT 116. Image data—delivered via the column lines—are typically connected to the source of each TFT. Image data is written to the panel a row at a time and is given a polarity bias scheme as indicated herein as either ODD (“O”) or EVEN (“E”) schemes. As shown, row 112 is being written with ODD polarity scheme at a given time while row 114 is being written with EVEN polarity scheme at a next time. The polarities alternate ODD and EVEN schemes a row at a time in this 1x1 dot inversion scheme.

FIG. 1B depicts another conventional RGB stripe panel having another dot inversion scheme—i.e. 1x2 dot inversion. Here, the polarity scheme changes over the course of two rows—as opposed to every row, as in 1x1 dot inversion. In both dot inversion schemes, a few observations are noted: (1) in 1x1 dot inversion, every two physically adjacent subpixels (in both the horizontal and vertical direction) are of different polarity; (2) in 1x2 dot inversion, every two physically adjacent subpixels in the horizontal direction are of different polarity; (3) across any given row, each successive colored subpixel has an opposite polarity to its neighbor. Thus, for example, two successive red subpixels along a row will be either (+,-) or (-,+). Of course, in 1x1 dot inversion, two successive red subpixels along a column will have opposite polarity; whereas in 1x2 dot inversion, each group of two successive red subpixels will have opposite polarity. This changing of polarity decreases noticeable visual defects that occur with particular images rendered upon an AMLCD panel.

FIG. 2 shows a panel comprising a repeat subpixel grouping 202, as further described in the '353 application. As may be seen, repeat subpixel grouping 202 is an eight subpixel repeat group, comprising a checkerboard of red and blue subpixels with two columns of reduced-area green subpixels in between. If the standard 1x1 dot inversion scheme is applied to a panel comprising such a repeat grouping (as shown in FIG. 2), then it becomes apparent that the property described above for RGB striped panels (namely, that successive colored pixels in a row and/or column have different polarities) is now violated. This condition may cause a number of visual defects noticed on the panel—particularly when certain image patterns are displayed. This observation also occurs with other novel subpixel repeat grouping—for example, the subpixel repeat grouping in FIG. 1 of the '352 application—and other repeat groupings that are not an odd number of repeating subpixels across a row. Thus, as the traditional RGB striped panels have three such repeating subpixels in its repeat group (namely, R, G and B), these traditional panels do not necessarily violate the above noted conditions. However, the repeat grouping of FIG. 2 in the present application has four (i.e. an even number) of subpixels in its repeat group across a row (e.g. R, G, B, and G). It will be appreciated that the embodiments described herein are equally applicable to all such even modulus repeat groupings.

In order to affect improved performance, several embodiments are herein described. A first embodiment of an AMLCD panel 300 is shown in FIG. 3. Box 302 encloses four TFTs 116 that drive their associated four colored subpixels. As may be seen, the gates of each TFT 116 are connected to a row line in such a manner as to have same colored subpixels—successively staggered—across each row affect opposite polarity. This effect is shown in FIG. 4, for example, with red subpixels 408, 410, and 412, etc. receiving (-, +, -, . . .) polarities during a row write to line 404. The same effect is shown for blue subpixels across line 404. One possible benefit of this condition is that any parasitic capacitances (for example, as between the gate and the drain of the TFT, CGD, and as between the pixel and the gate line, CG-Pixel.) that occur across a row/gate line with are minimized by having the same number of “+” and “-” polarities connected to the row/gate line.

It is further seen in FIG. 3 that the TFTs 116 in repeating group 302 are formed at the intersection of a pair of row and column lines at a given quadrant of the subpixel. For example, the upper red subpixel in group 302 has its TFT formed in the first quadrant; while the upper green subpixel has its TFT formed in the third quadrant. To affect a dot inversion scheme

on a subpixel repeating group of an even number of subpixels in a row or column direction, one embodiment is to find a suitable remapping of the TFT backplane from their usual placement in one quadrant, so that the remapping may use any number of quadrants greater than one.

FIG. 4 depicts how panel 300 operates over the course of two successive row-writes. During the first row-write (panel 300 on the left hand side), row 402 sends an active gate signal down to the connected TFTs and their associated subpixels (shown in BOLD hatching) on an EVEN cycle. In this case, all of the green subpixels in two rows are activated. However, as may be seen, the TFTs have been advantageously replaced so that two bordering green subpixels in the vertical direction have opposite polarities. So, for example, green subpixel 406 has a "+" polarity; while green subpixel 408 has a "-" polarity. Additionally, as may be seen, the polarities of all of the green subpixels connected to row line 402 are balanced—i.e. the number of "+" polarity green subpixels equals the number of "-" polarity green subpixels.

During the next row-write (as shown in panel 300 on the right hand side), row line 404 sends an active gate signal to its connected TFTs and their associated subpixels (also shown in BOLD hatching) on an ODD cycle. Again, given the replacement of the TFTs, each two adjacent subpixels in the vertical direction have opposite polarity. Additionally, as described above, same colored subpixels that are successively staggered along a row line are of opposite polarity.

Yet another embodiment comprising a TFT replacement (i.e. off from the traditional manner of consistently placing TFTs in a single position relative to the subpixels—such as the upper left hand corner) is shown in FIG. 5. The repeat grouping of TFTs in this arrangement are shown as block 502. With this arrangement, similar corrective polarity conditions as noted for FIGS. 3 and 4 are found with the TFT placement of FIG. 5. For example, along row/gate line 504, every two red subpixels alternate polarity—e.g. red subpixels 510 and 512 have "+" polarity; while red subpixels 514 and 516 have "-" polarity. As will be discussed in greater detail below, there are a number of different TFT placements that will achieve the same effects. Each such TFT placement (or TFT "remapping") is contemplated within the scope of the present invention and, as such, the present invention should not be limited to any particular TFT placement or remapping.

FIG. 6 is yet another embodiment of TFT remapping on panel 600 that may take into account additional parasitic capacitance effects between pixel and the CS electrode 602. In this case, two successive row/gate lines are driven by a given polarity scheme (O or E). The polarity of each subpixel is shown in its center. It will be noted that along any given row (and hence along a given CS line), successive same colored subpixels alternate polarity.

Another TFT remapping that may produce similar beneficial effects is shown in FIG. 7. In this case, the panel 700 is partitioned into sections (e.g. 702, 704) that place the TFTs of their associated subpixels in corners such that the polarity at the two columns at the partition line repeats. Thus, for example, column 710 and 712 have the same polarities of subpixels going down the respective columns. If the number of subpixels across a row defining a given partition is small enough, the accumulated parasitic capacitances in that partition may be sufficiently below a visually detectable (or at least manageable) level. This partitioning across a panel might occur a number of times in order to keep those parasitics at a low enough level. As an alternative embodiment, this panel could have a 1x2 dot inversion scheme—thereby effectively solving vertical crosstalk (i.e. whereby same colored subpixels have same polarity in a given column).

FIGS. 8 through 15 outline a general procedure for developing many different embodiments of TFT remappings that may effect reduced parasitic capacitance in an panel having even modulus for a subpixel repeating group. Starting with a basic grid 800 of FIG. 8, a repeating subpixel grouping 902 is placed upon the grid in FIG. 9. It will be appreciated that, as noted above, any repeating group would suffice here; but preferably one with an even number of subpixels across a row. A dot inversion scheme is selected in FIG. 10—in this case, a 1x2 dot inversion scheme is selected with two polarity schemes or "phases"—O and E. Additionally, these two phases are repeated for every two row/gate lines—O, O, E, E, etc. If 1x1 dot inversion were desired, then the phases would alternate every row/gate line.

Any symmetries in the repeat grouping are now to be considered. For example, in FIG. 11, it is noted that every other column is a line of blue subpixels. Thus, a possible symmetry to consider is in the other columns of alternating red and green subpixels. Now, consider all possible combinations of polarities for the first two subpixels in the columns of interest. In FIG. 11 for example, the first two red and green subpixels could assume a set of four possible polarity values. In general, if the first N subpixels in relevant rows or columns are considered, then 2N combinations of polarities may or should be considered.

Other symmetries may also be taken into consideration. In FIG. 12, the polarities in one of the columns of same colored subpixels are considered. A listing of possible polarities are shown in list 1202 for the second column of blue subpixels—and the first four such blue subpixels in the column are considered. The list could be exhaustive of the possibilities of polarities and certainly another number other than four may be considered. As it may be advantageous to balance the polarities down a given column—all of those possibilities with a balanced number of polarities are noted as "OK". One OK combination 1204 is selected, solely for exemplary purposes, for grid 1206.

FIG. 13 shows an initial selection of TFT placements on the grid. Initially, for optional visual aiding, the polarities accorded to each intersection of a row/gate line and a column/data line are placed on the grid—as either a "+" or a "-". It is noted that any TFT placed in any quadrant around an intersection point will effect the same polarity on its associated subpixel. As for the subpixels in FIG. 12 that have been assigned a polarity, there is a degree of freedom in selecting which intersection to place the TFT. For example, red subpixel 1302 has been assigned a "+" polarity and there are two possible intersections 1304 and 1306 at which to place its associated TFT. For exemplary purposes, the TFT is selected to be placed at intersection 1304. Of course, the placement of TFTs could be affected by many possible factors—for example, the desire to minimally impact design rules, to minimize ill effect (e.g. parasitic capacitances), etc. As may be seen, the other TFTs for the polarity-assigned subpixels in FIG. 13 have also been placed—as one possible embodiment and selection thereof. Of course, other embodiments/selections are also possible.

FIG. 14 extends this process of TFT placement to the remaining blue subpixels on the grid. Although there are other selections possible, this particular selection was made with the idea of balancing the polarities across any given row. As may be seen, the blue subpixels polarities balance out across any given row/gate line. FIG. 15 fills in the remaining red and green subpixel TFT placements. One possible goal is to assign the remaining TFTs in a grouping that may be repeated across the entire panel to form the backplane. One such repeat grouping is 1502 in FIG. 15. Grouping 1502 is an 8x4 sub-

pixel grouping that seeks to balance polarities across all subpixels in the row and column directions, as well as balancing polarities within each single color subpixel sub-grid in the row and column directions. It will be appreciated that by following the general procedure outlined above and exploiting the various degrees of freedom in design choice, many possible TFT placements or remappings are possible to develop a suitable TFT grid.

FIG. 16A shows one possible TFT remapping grid effecting a 1x2 dot inversion scheme. FIG. 16B shows how the remapping grid might be implemented on a panel with a little greater detail. TFT 1602 and 1604—with TFT 1602 implemented at the bottom of a pixel area and TFT 1604 at the top of a pixel area—are possibly susceptible to some uneven effects that might be introduced during the manufacturing process. For example, if the gate metal or pixel electrode masks are translated upwards during manufacturing, then it may be possible for reduced parasitic capacitance for TFT 1602 and its associated pixel and for increased parasitic capacitance for TFT 1604 and its associated pixel. If the errors in parasitics are out of tolerance bounds, then the yield of manufacturing such panels with unconventional TFT remappings might decrease. Thus, it may be desirable to redesign the TFT structure as described below in order to abate any uneven effects as noted above.

FIG. 16C shows another embodiment of a panel having a novel subpixel repeating group 1650. In this group, the pattern looks like:

R G B G
R G B G
B G R G
B G R G

When a 1x1 dot inversion scheme is applied to this repeat grouping, vertical crosstalk problems are solved. Additionally, all the TFTs may be placed on the same side of the pixel structure—which may reduce some parasitic effects or imbalances.

One known attempt to correct for TFT misalignments and any associated increase in parasitic capacitance is found in U.S. Pat. No. 5,191,451 to Katayama et al. FIG. 17A depicts the “double TFT” arrangement 1700 of the ‘451 patent. Source line 1704 connects to the TFT via source electrode 1706. Two gate electrodes 1708 are connected to gate line 1702. Two drain electrodes 1710 connect to the pixel and are formed such that the two gate electrodes 1708 affect conduction from the source electrode to the drain electrodes when activated. It is noted that there are two crossover regions 1712 that are connected to TFT may produce additional parasitic capacitance between the gate and the source. As discussed in the ‘451 patent, any vertical misalignment of the TFT placement is somewhat corrected by this double TFT arrangement as is discussed therein. FIGS. 17B and 17C provide different alternative embodiments for the double TFT structure to the one shown in FIG. 17A. This structure will enable reduced source to gate capacitance, which can cause crosstalk in certain images. The gate to drain crossover will be less damaging to image quality. One advantage of the embodiment of FIG. 17C is that there is only one crossover 1732 that may reduce parasitic capacitance.

Another manner of reducing the ill effects of TFT misalignment is shown in U.S. Pat. No. 5,097,297 to Nakazawa. FIG. 18 depicts a TFT 1800 made in the manner taught in the ‘297 patent. As may be seen in FIG. 18, gate line 1802 delivers the gate signal to gate electrode 1808. Source line 1804 sends image data to source electrodes 1806. When the gate electrode is activated, the image data is transferred to the pixel via

the drain electrode 1810. It is noted that this TFT embodiment contains only one gate crossover 1812 which aids in reducing parasitic capacitance.

Another set of TFT redesigns are shown in FIGS. 19 through 21 to handle the unevenness of parasitic capacitance that might be introduced by the above described TFT remapping. As TFTs are remapped on the panel, it is possible for some TFTs on the panel to be implemented in different corners or quadrants of a pixel area. For example, some TFTs may be constructed in the upper left hand corner of the pixel area, some in the upper right hand corner of the pixel area and so on. If all such TFTs were constructed the same way, then it would be likely that the source-drain orientation would be reversed for left hand corner and right hand corner implementation. Such non-uniformity of construction might introduce uneven parasitic capacitance in the case of a given TFT misalignment.

FIG. 19 is one embodiment of a TFT built with a reverse orientation 1902 as compared with a TFT built with a typical orientation 1904. For exemplary purposes, TFT 1904 is constructed within the upper left hand corner of its associated pixel in the usual manner—i.e. without any crossovers to avoid any introduced parasitic capacitance. It is noted that the source (S) and drain (D) electrodes are placed in a left-to-right fashion. TFT 1902 is shown constructed in the upper right hand corner of a pixel area in a reverse orientation—i.e. a crossover 1914 from source line 1906 is constructed so that the source electrode 1910 and drain electrode 1912 are also in left-to-right fashion. Thus, if there is a TFT misalignment in the horizontal direction, then TFTs 1902 and 1904 will receive the same amount of added parasitic capacitance—thus, keeping the panel’s defects uniform. It will be appreciated that although TFT 1902 and TFT 1904 are depicted side-by-side and connected to the same column, this is primarily for explanatory purposes. It is unlikely that two adjoining subpixels would share the same column/data line—thus, TFT 1904 and its associated pixel is provided to show the distinction between a normal TFT orientation and TFT 1902 in a reverse orientation.

FIG. 20 shows another embodiment of TFTs 1902 and 1904. As can be seen, a new crossover 2002 is added to TFT 1904 so as to balance the added parasitic capacitance via crossover 1914. FIG. 21 is yet another embodiment of TFTs 1902 and 1904. As may be seen here, the gate electrode crossover 1914 has been removed in favor of a gate line crossover 2102 which may have a lesser impact on individual pixel elements.

FIGS. 22 and 23 are embodiments of pixel elements with corners 2210 and 2310 removed to match the one corner removed containing the TFT structure. These pixel elements as designed here may balance the parasitic capacitances more than a normal pixel structure.

FIG. 24 is another embodiment of a pixel structure that employs at least one extra metal line 2410 that may help to shield the pixel element from the parasitic capacitances between the gate lines and the pixel element. Additionally, if a dot inversion scheme is employed, then the opposing polarities on both lines 2410 will also help to balance any parasitic capacitance between the source lines and the pixel elements.

What is claimed is:

1. A liquid crystal display comprising:

a display panel substantially comprising a plurality of a subpixel repeating group; the subpixel repeating group comprises at least two rows, each of said rows further comprising an even number of subpixels; wherein each row of subpixels comprises at least two same-colored subpixels;

each said subpixel having an associated thin film transistor (TFT) connected to a row line and a column line; said thin film transistor being formed in a corner of said subpixel in one of a group of quadrants with respect to said subpixel, the group comprising a first quadrant, a second quadrant, a third quadrant and a fourth quadrant; driver circuitry configured to send image signals and polarity signals to said subpixels; and wherein said display panel is partitioned into a plurality of sections along a row direction wherein said subpixels in each at a first section have their associated TFTs in a first quadrant and said subpixels in a second section have their TFTs in a second quadrant such that the polarity signal sent to same colored subpixels in said first section are different from polarity signals sent to same colored subpixels in said second section.

2. The liquid crystal display of claim 1 wherein said polarity signal comprises a 1x1 dot inversion polarity signal.

3. The liquid crystal display of claim 1 wherein said polarity signal comprises a 1x2 dot inversion polarity signal.

4. The liquid crystal display of claim 1 wherein the partitioning of said display panel occurs with frequency across said row direction such that parasitic capacitance effects are substantially abated.

5. The liquid crystal display of claim 1, wherein said subpixels in said first section are connected to an odd-numbered column line, and said subpixels in said second section are connected to an even-numbered column line.

6. The liquid crystal display of claim 1, wherein said subpixels in said first section are connected to an even-numbered column line, and said subpixels in said second section are connected to an odd-numbered column line.

7. The liquid crystal display of claim 1, wherein said subpixel repeating group comprises a first subpixel having a first color, a second subpixel having a second color different from the first color, a third color subpixel having a third color different from the first and second colors and a fourth subpixel having the third color in each of said rows.

8. The liquid crystal display of claim 7, wherein the first color is red, the second color is green and the third color is blue.

9. The liquid crystal display of claim 7, wherein the third subpixel has a size smaller than each of the first subpixel and the second subpixel, and the fourth subpixel has a size substantially the same as the third subpixel.

10. The liquid crystal display of claim 7, wherein the first subpixel in a first row and the second subpixel in a second row are disposed in a same column.

11. The liquid crystal display of claim 10, wherein the third subpixel in a first row and the third subpixel in a second row are disposed in a same column.

12. The liquid crystal display of claim 11, wherein the third subpixel of the first row is disposed between the first and second subpixels, and the second subpixel of the first row is disposed between the third and fourth subpixels.

13. The liquid crystal display of claim 12, wherein the first and second subpixels of the first row are connected to a first row line, and the third and fourth subpixels of the first row are connected to a second row line.

14. The liquid crystal display of claim 13, wherein the third and fourth subpixels of the second row are connected to the first row line, and the first and second subpixels of the second row are connected to a third row line.

15. The liquid crystal display of claim 12, wherein the first subpixel of the first row is connected to a first column line, and the second subpixel of the second row, which is disposed in the same column as the first subpixel of the first row, is connected to a second column line.

16. The liquid crystal display of claim 15, wherein the third subpixel of the second row is connected to the second column line, and the third subpixel of the first row, which is disposed in the same column as the third subpixel of the second row, is connected to a third column line.

17. The liquid crystal display of claim 12, wherein the first and third subpixels of the first row are connected to a first row line, and the second and fourth subpixels of the first row are connected to a second row line.

18. The liquid crystal display of claim 7, wherein the first subpixel in a first row and the first subpixel in a second row are disposed in a same column.

19. The liquid crystal display of claim 18, wherein the third subpixel in a first row and the third subpixel in a second row are disposed in a same column.

20. The liquid crystal display of claim 19, wherein the third subpixel of the first row is disposed between the first and second subpixels, and the second subpixel of the first row is disposed between the third and fourth subpixels.

* * * * *

专利名称(译)	用于非标准子像素排列的液晶显示器背板布局和寻址		
公开(公告)号	US8144094	公开(公告)日	2012-03-27
申请号	US12/147286	申请日	2008-06-26
[标]申请(专利权)人(译)	三星电子株式会社		
申请(专利权)人(译)	三星电子公司，		
当前申请(专利权)人(译)	三星DISPLAY CO.，LTD.		
[标]发明人	BROWN ELLIOTT CANDICE HELLEN CREDELLE THOMAS LLOYD SCHLEGEL MATTHEW OSBORNE HAN SEOK JIN		
发明人	BROWN ELLIOTT, CANDICE HELLEN CREDELLE, THOMAS LLOYD SCHLEGEL, MATTHEW OSBORNE HAN, SEOK JIN		
IPC分类号	G09G3/36 G02F1/1368		
CPC分类号	G02F1/1368 G09G3/3648 G09G3/3607 G09G2300/0452 G09G2300/0426 G09G3/3614		
审查员(译)	王，佳珍		
助理审查员(译)	周煜		
其他公开文献	US20080252581A1		
外部链接	Espacenet USPTO		

摘要(译)

公开了用于非标准子像素排列的液晶显示器底板布局和寻址。液晶显示器包括面板和多个晶体管。该面板基本上包括子像素重复组，该子像素重复组在第一方向上具有偶数个子像素。每个薄膜晶体管将一个子像素连接到一组象限中的一个象限中的交叉点处的行和列线。该组包括第一象限，第二象限，第三象限和第四象限，其中薄膜晶体管形成在与行和列线的交叉点相邻的背板结构中。薄膜晶体管也基本上形成在背板结构中的多于一个象限中。

