



US008045125B2

(12) **United States Patent**
Hirakata et al.

(10) **Patent No.:** **US 8,045,125 B2**
(45) **Date of Patent:** **Oct. 25, 2011**

(54) **LIQUID CRYSTAL DISPLAY DEVICE
HAVING A GAP RETAINING MEMBER
MADE OF RESIN FORMED DIRECTLY OVER
THE DRIVER CIRCUIT**

(52) **U.S. CL.** **349/155**

(58) **Field of Classification Search** 349/155-157
See application file for complete search history.

(75) Inventors: **Yoshiharu Hirakata**, Atsugi (JP);
Takeshi Nishi, Atsugi (JP); **Shunpei**
Yamazaki, Setagaya (JP)

(56) **References Cited**

U.S. PATENT DOCUMENTS

4,653,864 A *	3/1987	Baron et al.	349/156
4,874,461 A	10/1989	Sato et al.	
5,003,356 A *	3/1991	Wakai et al.	257/390
5,042,920 A *	8/1991	Yoshino et al.	349/106

(Continued)

FOREIGN PATENT DOCUMENTS

EP 0 457 328 11/1991

(Continued)

OTHER PUBLICATIONS

Pending Claims for U.S. Appl. No. 10/855,445.

Primary Examiner — David Nelms

Assistant Examiner — Dennis Y. Kim

(74) *Attorney, Agent, or Firm* — Eric J. Robinson; Robinson
Intellectual Property Law Office, P.C.

(*) Notice: Subject to any disclaimer, the term of this
patent is extended or adjusted under 35
U.S.C. 154(b) by 0 days.

(21) Appl. No.: **10/845,378**

(22) Filed: **May 14, 2004**

(65) **Prior Publication Data**

US 2004/0207789 A1 Oct. 21, 2004

Related U.S. Application Data

(62) Division of application No. 10/236,957, filed on Sep.
9, 2002, now Pat. No. 6,743,650, which is a division of
application No. 09/793,116, filed on Feb. 27, 2001,
now Pat. No. 6,465,268, which is a division of
application No. 09/083,041, filed on May 22, 1998,
now abandoned.

(30) **Foreign Application Priority Data**

May 22, 1997	(JP)	9-148540
May 26, 1997	(JP)	9-152805
Jun. 9, 1997	(JP)	9-167990
Jun. 23, 1997	(JP)	9-183024


(57) **ABSTRACT**

In an active matrix semiconductor display device in which pixel TFTs and driver circuit TFT are formed on the same substrate in an integral manner, the cell gap is controlled by gap retaining members that are disposed between a pixel area and driver circuit areas. This makes it possible to provide a uniform cell thickness profile over the entire semiconductor display device. Further, since conventional grainy spacers are not used, stress is not imposed on the driver circuit TFTs when a TFT substrate and an opposed substrate are bonded together. This prevents the driver circuit TFTs from being damaged.

(51) **Int. Cl.**
G02F 1/1339

(2006.01)

28 Claims, 30 Drawing Sheets



US 8,045,125 B2

Page 2

U.S. PATENT DOCUMENTS

5,103,331 A 4/1992 Taniguchi et al.
5,136,407 A * 8/1992 Clerc 349/146
5,148,301 A * 9/1992 Sawatsubashi et al. 349/153
5,162,933 A 11/1992 Kakuda et al.
5,200,846 A 4/1993 Hiroki et al.
5,208,687 A 5/1993 Yoshida et al.
5,232,549 A 8/1993 Cathey et al.
5,287,205 A 2/1994 Yamazaki et al.
5,379,139 A 1/1995 Sato et al.
5,381,255 A 1/1995 Ohnuma et al.
5,427,829 A 6/1995 Mochizuki et al.
5,486,126 A 1/1996 Cathey et al.
5,492,234 A 2/1996 Fox, III
5,499,128 A * 3/1996 Hasegawa et al. 349/155
5,568,288 A 10/1996 Yamazaki et al.
5,583,675 A * 12/1996 Yamada et al. 349/84
5,606,194 A 2/1997 Lebrun et al.
5,621,558 A * 4/1997 Shimada et al. 349/130
5,666,179 A * 9/1997 Koma 349/143
5,671,030 A 9/1997 Ohnuma et al.
5,691,793 A 11/1997 Watanabe et al.
5,710,609 A * 1/1998 Shimada 349/126
5,739,890 A 4/1998 Uda et al.
5,757,451 A 5/1998 Miyazaki et al.
5,764,320 A 6/1998 Konuma et al.
5,766,694 A 6/1998 West et al.
5,777,594 A 7/1998 Miyawaki
5,784,132 A * 7/1998 Hashimoto 349/44
5,805,252 A 9/1998 Shimada et al.
5,815,232 A 9/1998 Miyazaki et al.
5,831,710 A 11/1998 Colgan et al.
5,844,643 A 12/1998 Onishi et al.
5,880,803 A * 3/1999 Tamai et al. 349/156
5,917,572 A * 6/1999 Kurauchi et al. 349/156
5,933,205 A 8/1999 Yamazaki et al.
5,952,554 A 9/1999 Umeda
5,963,278 A 10/1999 Yamazaki et al.
5,969,784 A 10/1999 Miyazaki et al.
5,978,061 A * 11/1999 Miyazaki et al. 349/155
5,978,063 A 11/1999 Crawford et al.
5,980,349 A 11/1999 Hofmann et al.
6,011,607 A 1/2000 Yamazaki et al.
6,049,370 A * 4/2000 Smith et al. 349/156
6,067,144 A 5/2000 Murouchi
6,081,305 A 6/2000 Sato et al.
6,097,459 A 8/2000 Shimada et al.
6,236,445 B1 5/2001 Foschaar et al.
6,286,359 B1 9/2001 Umeda
6,287,733 B1 9/2001 Miyazaki et al.
6,288,764 B1 * 9/2001 Zhang et al. 349/152
6,355,942 B1 3/2002 Yamazaki et al.
6,436,815 B1 8/2002 Yamazaki et al.
6,437,367 B1 8/2002 Yamazaki et al.
6,445,437 B1 9/2002 Miyazaki et al.
6,703,643 B2 3/2004 Yamazaki et al.
6,888,608 B2 5/2005 Miyazaki et al.
7,420,628 B1 9/2008 Hiroki et al.
7,479,939 B1 1/2009 Hiroki et al.
7,489,367 B1 2/2009 Yamazaki et al.
7,538,849 B2 5/2009 Yamazaki et al.
7,646,441 B2 1/2010 Hiroki et al.
7,671,827 B2 3/2010 Hiroki et al.
7,701,523 B2 4/2010 Hiroki et al.
2002/0033790 A1 3/2002 Sato et al.
2002/0171800 A1 11/2002 Miyazaki et al.
2004/0218112 A1 11/2004 Hirakata et al.
2009/0190056 A1 7/2009 Yamazaki et al.
2009/0291612 A1 11/2009 Yamazaki et al.

FOREIGN PATENT DOCUMENTS

EP 0506027 A 9/1992
EP 0 508 592 10/1992
EP 708355 4/1996
EP 0 725 303 8/1996
EP 0 726 484 8/1996
EP 772071 5/1997

JP 58-085478 5/1983
JP 60-217337 10/1985
JP 61-184518 8/1986
JP 61-235814 10/1986
JP 62-024229 2/1987
JP 62-080624 4/1987
JP 63-050817 A 3/1988
JP 63-123023 5/1988
JP 64-024230 1/1989
JP 02-043518 2/1990
JP 02-091616 3/1990
JP 03-015824 A 1/1991
JP 03-062019 3/1991
JP 03-089320 4/1991
JP 03-127028 5/1991
JP 04-006029 1/1992
JP 04-030123 2/1992
JP 04-240821 8/1992
JP 04-338923 11/1992
JP 04-356021 12/1992
JP 05-100232 4/1993
JP 05-165060 6/1993
JP 5-281558 A 10/1993
JP 06-051319 2/1994
JP 06-067135 A 3/1994
JP 06-123874 A 5/1994
JP 06-123878 A 5/1994
JP 06-138489 A 5/1994
JP 06-222370 8/1994
JP 6-244104 A 9/1994
JP 6-265912 A 9/1994
JP 06-273735 9/1994
JP 06-289413 10/1994
JP 06-294965 10/1994
JP 06-301036 10/1994
JP 06-331970 12/1994
JP 06-347805 12/1994
JP 07-013164 1/1995
JP 07-084267 3/1995
JP 07-120766 5/1995
JP 07-181494 A 7/1995
JP 07-199222 A 8/1995
JP 07-507405 8/1995
JP 07-318973 A 12/1995
JP 07-325298 12/1995
JP 08-500910 1/1996
JP 08-076131 3/1996
JP 08-095051 4/1996
JP 08-101383 4/1996
JP 08-122768 5/1996
JP 08-220560 8/1996
JP 8-248427 A 9/1996
JP 08-262454 10/1996
JP 08-292426 11/1996
JP 08-320461 12/1996
JP 08-328000 12/1996
JP 08-328034 12/1996
JP 09-068698 3/1997
JP 9-73093 A 3/1997
JP 09-073099 3/1997
JP 09-080399 3/1997
JP 09-080485 3/1997
JP 09-120062 5/1997
JP 09-127525 5/1997
JP 9-197413 7/1997
JP 10-68955 A 3/1998
JP 10-133206 5/1998
KR 91-20473 12/1991
KR 1996-0032048 9/1996
KR 1997-0011949 3/1997
KR 97-16704 4/1997
KR 1997-0016705 4/1997
KR 211806 8/1999
KR 288371 5/2001
WO WO-94/17438 8/1994

* cited by examiner

FIG. 1A




FIG. 1B




FIG. 2A




FIG. 2B




FIG. 2C




FIG. 2D




FIG. 2E




FIG. 3A




FIG. 3B




FIG. 4A




FIG. 4B




FIG. 4C




FIG. 4D




FIG. 5A




FIG. 5B




FIG. 6




FIG. 7A




FIG. 7B




FIG. 7C




FIG. 7D




FIG. 8A




FIG. 8B




FIG. 8C




FIG. 9




FIG. 10




FIG. 11A




FIG. 11B




FIG. 11C




FIG. 12A




FIG. 12B




FIG. 13A




FIG. 13B




FIG. 13C




FIG. 14A




FIG. 14B




FIG. 15A




FIG. 15B




FIG. 16




FIG. 17




FIG. 18




FIG. 19




FIG. 20A




FIG. 20B




FIG. 20C




FIG. 20D




FIG. 20E




FIG. 21A




FIG. 21B




FIG. 22




FIG. 23




FIG. 24A




FIG. 24B




FIG. 25A




FIG. 25B




FIG. 26




FIG. 27




FIG. 28




FIG. 29A




FIG. 29B




FIG. 29C




FIG. 29D




FIG. 29E




FIG. 29F




FIG. 30A




FIG. 30B




FIG. 31




FIG. 32






FIG. 33








FIG. 37A
PRIOR ART





FIG. 37B
PRIOR ART



LIQUID CRYSTAL DISPLAY DEVICE HAVING A GAP RETAINING MEMBER MADE OF RESIN FORMED DIRECTLY OVER THE DRIVER CIRCUIT

BACKGROUND OF THE INVENTION

1. Field of the Invention

The present invention relates to a semiconductor display device using thin-film transistors. In particular, the invention relates to a semiconductor display device in which a pixel switching circuit and driver circuits are formed on the same substrate in an integral manner.

2. Description of the Related Art

In recent years, the techniques of forming semiconductor devices, such as thin-film transistors (TFTs), by using a semiconductor thin film formed on an inexpensive glass substrate have made rapid progress. This is because of increased demand for active matrix liquid crystal display devices.

In active matrix liquid crystal display devices, TFTs are provided for respective ones of hundreds of thousands to millions of pixel regions that are arranged in matrix and charge that enters or exits from each pixel electrode is controlled by the switching function of the associated TFT.

The basic configuration of an active matrix liquid crystal display device in which thin-film transistors are arranged will be described below with reference to FIGS. 34A and 34B. FIG. 34A is a sectional view obtained by cutting a liquid crystal display device by a plane perpendicular to a substrate, specifically taken along a chain line A-A' in FIG. 34B.

An insulating film (not shown) is formed on the surface of a transparent base substrate 1. Reference numeral 2 denotes an active layer of a TFT; 3, a gate electrode; 4, a data line; 5, a drain electrode; 6, an interlayer insulating film; 7, a black matrix; 8, a transparent conductive film as a pixel electrode; and 9, an alignment film.

In this specification, the structure including the base substrate 1 and the other members mentioned above (including the TFTs) is called an "TFT substrate." Although FIG. 34A focuses on a single pixel, actually the TFT substrate is composed of a pixel area including hundreds of thousands to millions of pixel switching TFTs (called pixel TFTs) and peripheral driver circuit areas including a number of TFTs for driving the pixel TFTs.

On the other hand, reference numerals 10-12 denote a transparent substrate, a transparent conductive film as an opposed electrode, and an alignment film, respectively. The structure including these members, which is opposed to the TFT substrate, is called an "opposed substrate."

As shown in FIG. 35A, the TFT substrate 20 and the opposed substrate 30 are subjected to an alignment treatment such as rubbing for giving proper alignment to a liquid crystal. Thereafter, to control a substrate interval (cell gap) between the TFT substrate 20 and the opposed substrate 30, grainy spacers 41 are uniformly scattered over the entire surface of the TFT substrate 20. Then, a sealing agent 42 is printed. The sealing agent 42 has a role of an adhesive for bonding the substrates 20 and 30 together as well as a role of a sealing material for sealing the space between the substrates 20 and 30 to prevent a liquid crystal material that will be injected there from leaking to the outside of the substrates.

FIG. 36 is a sectional view of the TFT substrate 20. Since the grainy spacers 41 are uniformly scattered over the entire surface of the TFT substrate 20 to control the cell gap, the spacers 41 exist in not only the pixel area 22 but also the peripheral driver circuit regions 23 as shown in FIG. 36. Usually, the pixel TFTs formed in the pixel area 22 are not

much different in device size from the driver circuit TFTs formed in the driver circuit areas 23. However, the black matrix for covering the pixel TFTs, the pixel electrodes that are transparent conductive films, and other members are formed in the pixel area 22. Further, in reflection-type liquid crystal display devices, a reflective electrode is formed in the pixel area 22. On the other hand, connection lines necessary to constitute CMOS circuits for driving the pixel TFTs are formed in the driver circuit areas 23. Therefore, there are differences in the height (distance) from the surface of the base substrate 1 between the pixel area 22 and the driver circuit areas 23.

A description will now be made of a case where the height as measured from the surface of the substrate 1 in the pixel area 11 is greater than in the driver circuit areas 23. The grainy spacers 41 are scattered in not only the pixel area 22 but also the driver circuit areas 23 by a wet or dry method. If the grainy spacers 41 have approximately uniform sizes, they have differences in the height as measured from the substrate 1 depending on their positions. Now, the height of the top of each spacer 41 in the pixel area 22 and that of the top of each spacer 41 in the driver circuit areas 23 are represented by h_p and h_d , respectively. As seen from FIG. 36, a height difference $\Delta h = h_p - h_d$ occurs due to the difference in height between the pixel area 22 and the driver circuit areas 23.

Then, as shown in FIG. 37A, the TFT substrate 20 and the opposed substrate 30 are bonded together with the sealing agent 42. Thereafter, the space between the TFT substrate 20 and the opposed substrate 30 are filled with a liquid crystal material 43 and a liquid crystal injection inlet 44 is sealed with a sealing material (see FIG. 37B). In this manner, an active matrix liquid crystal display device having the configuration shown in FIG. 34A is obtained.

However, the liquid crystal display device having the above configuration has the following problems.

Because of the height difference Δh that is caused by the difference in height between the pixel area 22 and the driver circuit areas 23, the cell gap cannot be made uniform, that is, a cell thickness variation occurs, when the TFT substrate 20 and the opposed substrate 30 are bonded together. Further, as shown in FIGS. 37A and 37B, strain occurs in the opposed substrate 30. Defects such as display unevenness and an interference fringe (on the top surface of the opposed substrate) may occur in a liquid crystal display device having a cell thickness variation and strain in the opposed substrate 30.

Where the height as measured from the substrate 1 in the driver circuit areas 23 is greater than in the pixel area 22, because of the above-described height difference Δh , unduly strong force is exerted on the spacers 41 that are scattered in the driver circuit areas 23 when the TFT substrate 20 and the opposed substrate 30 are bonded together. As a result, the driver circuit TFTs having a more complex structure than the pixel TFTs are damaged considerably, which adversely affects the yield of products.

Where grainy spacers 15 exist in the pixel area, disorder in image display (disclination) may be observed as shown in FIG. 34B because the alignment of the liquid crystal material is disordered in the vicinity of the spacers 15.

As described above, where the cell gap is controlled by using conventional grainy spacers, satisfactory display may not be obtained due to various factors.

In liquid crystal display devices that are commonly manufactured or manufactured as trial products, the cell gap appears to be set at 4-6 μm irrespective of the pixel pitch. However, in the future, liquid crystal panels will be required to have higher resolution and hence the pixel pitch will be increasingly reduced.

For example, projection-type liquid crystal display devices are desired to be able to display images having as high resolution as possible in view of the fact that the images are projected onto a screen in an enlarged manner. Also from the viewpoint of the cost, the optical system needs to be miniaturized and the panel size needs to be reduced. For the above reasons, in the future, it will be necessary to manufacture liquid crystal display devices having a pixel pitch of 40 μm or less, preferably 30 μm or less.

In liquid crystal display devices for displaying such high resolution images, even grainy spacers of several micrometers in diameter may deteriorate display quality when they exist in the effective display area.

Further, when a liquid crystal material is injected, the flow of the liquid crystal material forces conventional grainy spacers themselves to flow. As a result, a uniform spacer dispersion density profile may not be obtained, to cause a cell thickness variation.

Because of their characteristics, liquid crystal display devices using a ferroelectric liquid crystal that attract much attention recently and reflection-type liquid crystal display devices are required to have small cell gaps.

However, with conventional grainy spacers, it is generally difficult to produce a cell having a small, uniform-profile cell gap.

SUMMARY OF THE INVENTION

An object of the present invention is to provide a semiconductor display device that is free of a cell thickness variation and display unevenness by producing a cell having a small, uniform-profile cell gap that is hard to realize with conventional grainy spacers.

Another object of the invention is to prevent TFTs from being damaged by preventing unnecessary stress that would otherwise be exerted on the TFTs in bonding substrates together when conventional grainy spacers are used.

According to one aspect of the invention, there is provided an electro-optical device comprising a first substrate comprising a pixel area having a plurality of thin-film transistors and a plurality of pixel electrodes electrically connected to the respective thin-film transistors; a driver circuit area provided at a location separate from the pixel area and having a plurality of driver circuits having a plurality of thin-film transistors for driving the thin-film transistors in the pixel area; and a base substrate; a second substrate that confronts the first substrate; a plurality of gap retaining members; and a sealing member for bonding the first and second substrates together, wherein a distance from a surface of the base substrate to a surface of the pixel area is different from a distance from the surface of the base substrate to a surface of the driver circuit area and wherein the gap retaining members are formed in an area other than the pixel area and the driver circuit area. The above objects can be attained by this electro-optical device.

According to another aspect of the invention, there is provided an electro-optical device comprising a TFT substrate comprising a pixel area having a plurality of pixel electrodes arranged in matrix form and a plurality of pixel thin-film transistors electrically connected to the respective pixel electrodes; a driver circuit area having a driver circuit having a plurality of thin-film transistors for driving the pixel thin-film transistors; and a base substrate; an opposed substrate that confronts the TFT substrate; a display medium held between the TFT substrate and the opposed substrate, an optical response of the display medium being controlled by an application voltage; and a plurality of gap retaining members, wherein a distance from a surface of the base substrate to a

surface of the pixel area is different from a distance from the surface of the base substrate to a surface of the driver circuit area and wherein the gap retaining members are formed in an area other than the pixel area and the driver circuit area. The above objects can be attained by this electro-optical device.

The above-mentioned optical medium may be such that its optical characteristic is modulated in accordance with the application voltage.

The above-mentioned display medium may be a liquid crystal.

The above-mentioned display medium may be a mixed layer of a liquid crystal material and a polymer.

The above-mentioned display medium may be an electroluminescence element.

The above-mentioned gap retaining members may be formed around the pixel area.

The arrangement density of the above-mentioned gap retaining members may be uniform in the pixel area.

Each of the above-mentioned gap retaining members may be shaped like a cylinder.

Each of the above-mentioned gap retaining members may be shaped like an elliptical pole.

Each of the above-mentioned gap retaining members may be shaped like a polygonal prism.

Each of the above-mentioned gap retaining members may be shaped so as not to obstruct a flow of the liquid crystal when it is injected.

The side face of each of the above-mentioned gap retaining members may be tapered.

The above-mentioned gap retaining members may be made of one material selected from the group consisting of polyimide, acrylic, polyamide, and polyimideamide.

The above-mentioned gap retaining members may be made of an ultraviolet curable resin.

The above-mentioned gap retaining members may be made of an epoxy resin.

According to another aspect of the invention, the top surfaces of the respective gap retaining members on the side of one of the first and second substrates have been planarized by chemical mechanical polishing. In this electro-optical device, since the cell gap is controlled by planarizing the top surfaces of the gap retaining members, a small cell thickness having a uniform profile over the entire electro-optical device can be obtained. Even if the gap retaining members are formed on the pixel area or the driver circuits, a uniform cell thickness profile can be obtained.

To attain the above objects, according to another aspect of the invention, there is provided an electro-optical device comprising a first substrate comprising a pixel area having a plurality of pixel electrodes and switching elements connected to the respective pixel electrodes; a second substrate confronting the first substrate; and a gap retaining member that is provided on the second substrate and retains an interval between the first and second substrates.

To attain the above objects, according to a further aspect of the invention, there is provided an electro-optical device comprising a first substrate comprising a pixel area having a plurality of pixel electrodes and switching elements connected to the respective pixel electrodes; a second substrate confronting the first substrate; a liquid crystal sealed in a space between the first and second substrates; a first alignment film that is formed on a surface of the first substrate and orients a liquid crystal; a second alignment film that is formed on the second substrate and orients the liquid crystal; and a gap retaining member that is provided on the second substrate and retains an interval between the first and second substrates.

In the above two electro-optical devices, the use of the gap retaining members provides the following advantages. First, it is not longer necessary to use spacers. Second, since the height of the gap retaining members can be set as desired, the interval between the substrates can be determined as desired. Third, since the gap retaining members are fixed, they are not gathered unlike the conventional spacers. Therefore, point defects do not occur.

In the above two electro-optical devices, the position of the gap retaining members can be set as desired. For example, the gap retaining members can be provided in an area that substantially confronts the pixel area. In this case, it is preferable that the gap retaining members be provided at locations that are not used for display, for instance, on a black matrix of color filters and bus lines in the pixel area. Alternatively, by providing the gap retaining members in an area that does not confront the pixel area, the interval between the substrates can be retained without causing no influences on the display.

Where the invention is applied to an electro-optical device in which a first substrate (TFT substrate) is provided with a pixel area and a driver circuit area having driver circuits for driving switching elements that are provided in the pixel area, it is preferable that the gap retaining members be provided on a second substrate (opposed substrate) in an area that does not confront the driver circuit area. In this case, it is possible to prevent the driver circuits from being damaged or destroyed by stress that is imposed by the gap retaining members.

According to the invention, since the gap retaining members are provided on the second substrate, influences (solvent or etchant-related influences, mechanical impact, etc.) of the formation of the gap retaining members do not affect the first substrate. Provided with the pixel area and the driver circuits, the first substrate has a much higher integration density than the second substrate. In view of this, the gap retaining members are provided on the second substrate to minimize the number of processes that are executed on the first substrate.

Further, by providing the gap retaining members on the second substrate, the conditions that are set in selecting a material are relaxed. For example, where the invention is applied to a TFT-type liquid crystal display device, since pixel TFTs and driver circuit TFTs are formed in the first substrate (TFT substrate), it is necessary to select a material capable of providing a sufficiently large selective etching ratio to the material of those TFTs.

On the other hand, only such members as an opposed electrode and color filters are formed on the second substrate (opposed substrate), that is, the number of materials used in the second substrate is smaller than in the first substrate. Thus, the number of conditions to be set in selecting a material is small. Further, a material such as that of an etching liquid, an etching gas, or the like and means that are necessary to form the gap retaining members can be selected from wider ranges.

To make it possible to uniformize the interval between the substrates, it is preferable that the gap retaining members be made of a planarization material capable of canceling out the asperity of the base member. For example, the gap retaining members may be made of a resin material selected from polyimide, acrylic, polyamide, and polyimideamide, an ultra-violet curable resin, or a thermosetting resin as typified by an epoxy resin.

The above resin materials are frequently used as interlayer insulating films of the TFT substrate (first substrate). In such a case, it is difficult to provide a large selective etching ratio if the gap retaining members made of a resin material are provided on the TFT substrate. This is the reason why in the invention the gap retaining members are formed on the opposed substrate (second substrate).

BRIEF DESCRIPTION OF THE DRAWINGS

FIGS. 1A-1B are top views of a TFT substrate and an opposed substrate, respectively, according to a first embodiment of the present invention;

FIGS. 2A-2E and 3A-3B show a manufacturing process of the TFT substrate according to the first embodiment;

FIGS. 4A-4D show a manufacturing process of gap retaining members according to the first embodiment;

is FIGS. 5A and 5B are a top view and a perspective view, respectively, of an active matrix liquid crystal display device according to the first embodiment;

FIG. 6 is a sectional view of the active matrix liquid crystal display device according to the first embodiment;

FIGS. 7A-7D and 8A-8B show a manufacturing process of an active matrix liquid crystal display device according to a second embodiment of the invention;

FIG. 8C is an enlarged view of a gap retaining member according to the second embodiment;

FIG. 9 is a top view of the active matrix liquid crystal display device according to the second embodiment;

FIG. 10 is a top view of an active matrix liquid crystal display device according to a third embodiment of the invention;

FIGS. 11A-11C show a manufacturing process of an active matrix liquid crystal display device according to a fourth embodiment of the invention;

FIG. 12A is a top view of the active matrix liquid crystal display device according to the fourth embodiment;

FIG. 12B is an enlarged view showing a relationship between gap retaining members and a liquid crystal material flowing direction in the fourth embodiment;

FIGS. 13A-13C and 14A-14B show a process of forming gap retaining members according to a fifth embodiment of the invention;

FIGS. 15A and 15B are a top view and an enlarged perspective view, respectively, of an active matrix liquid crystal display device according to the fifth embodiment;

FIG. 16 is a top view of an active matrix liquid crystal display device according to a sixth embodiment of the invention;

FIG. 17 is a top view of an active matrix liquid crystal display device according to a seventh embodiment of the invention;

FIG. 18 is a schematic sectional view of a liquid crystal display device according to a tenth embodiment of the invention;

FIG. 19 is a sectional view of a TFT substrate according to the tenth embodiment;

FIGS. 20A-20E show a manufacturing process of an opposed substrate according to the tenth embodiment;

FIGS. 21A and 21B are a top view and an enlarged perspective view of the opposed substrate according to the tenth embodiment;

FIG. 22 is a top view of an opposed substrate according to a thirteenth embodiment of the invention;

FIG. 23 is a top view of an opposed substrate according to a fourteenth embodiment of the invention;

FIGS. 24A and 24B are top views of opposed substrates according to a fifteenth embodiment of the invention;

FIGS. 25A and 25B are a top view and an enlarged perspective view, respectively, of an opposed substrate according to a sixteenth embodiment of the invention;

FIG. 26 is a top view of another opposed substrate according to the sixteenth embodiment;

FIG. 27 is a top view of an opposed substrate according to a seventeenth embodiment of the invention;

FIG. 28 is a schematic perspective showing the configuration of a passive matrix liquid crystal panel according to an eighteenth embodiment of the invention;

FIGS. 29A-29F and 30A-30B show a manufacturing process of the passive matrix liquid crystal panel according to the eighteenth embodiment;

FIG. 31 is a schematic sectional view of the passive matrix liquid crystal panel according to the eighteenth embodiment;

FIG. 32 is a top view of a substrate showing an arrangement of gap retaining members according to the eighteenth embodiment;

FIG. 33 is a top view of a substrate showing an arrangement of gap retaining members according to a modification of the eighteenth embodiment;

FIGS. 34A and 34B are a sectional view and a plan view, respectively, of a conventional active matrix liquid crystal display device;

FIGS. 35A and 35B show a manufacturing process of the conventional active matrix liquid crystal display device;

FIG. 36 is a sectional view of a TFT substrate of the conventional active matrix liquid crystal display device; and

FIGS. 37A and 37B are sectional views of the conventional active matrix liquid crystal display device.

DETAILED DESCRIPTION OF THE PREFERRED EMBODIMENTS

Embodiment 1

This embodiment will be described with reference to FIGS. 1A-1B to 6. This embodiment is directed to a case where the invention is applied to an active matrix liquid crystal display device. FIG. 1A is a top view of a TFT substrate and FIG. 1B is a top view of an opposed substrate.

As shown in FIG. 1A, a TFT substrate 100 consists of a substrate 101 and a pixel area 102 and driver circuit areas 103 and 104 that are formed on the substrate 101. Pixel electrodes, TFTs that are connected to the respective pixel electrodes, and other members are arranged in the pixel area 102. Driver circuits for driving the TFTs in the pixel area 102 are arranged in the driver circuit areas 103 and 104.

As shown in FIG. 1B, an opposed substrate 200 consists of a substrate 201, an area 202 to confront the pixel area 102 of the TFT substrate 100, and areas 203 and 204 to confront the respective driver circuit areas 103 and 104. The TFT substrate 100 and the opposed substrate 200 are bonded together with a sealing agent 205 that is provided on a peripheral portion of the substrate 201. An opposed electrode is formed in the pixel-confronting area 202 of the opposed substrate 200.

As shown in FIG. 6, the TFT substrate 100 and the opposed substrate 200 confront each other, a liquid crystal 300 is injected through a liquid crystal injection inlet 206 into the space between the substrates 100 and 200, and the liquid crystal is sealed with a sealing agent 205. Alignment films for giving proper alignment to the liquid crystal are formed to constitute the surfaces of the TFT substrate 100 and the opposed substrate 200.

Next, a manufacturing method of the TFT substrate 100 will be described with reference to FIGS. 2A-2E and 3A-3B. The right-hand portions of FIGS. 2A-2E and 3A-3B show a manufacturing process of a TFT that is to be formed in the pixel area 102 and the left-hand portions show a manufacturing process of TFTs to be formed in the driver circuit areas 103 and 104, respectively.

First, as shown in FIG. 2A, a silicon oxide film as an undercoat insulating film 121 for preventing impurity diffusion from a glass substrate 101 is formed on the glass sub-

strate 101 at a thickness of 100-300 nm. The silicon oxide film may be formed by sputtering or plasma CVD in an oxygen atmosphere. In this embodiment, a 200-nm-thick silicon oxide film is formed by plasma CVD by using a TEOS gas as a material. If a quartz substrate is used as the substrate 101, the undercoat insulating film 121 can be omitted.

Then, an amorphous or polycrystalline silicon film is formed at a thickness of 30-150 nm, preferably 50-100 nm, by plasma CVD or LPCVD. To crystallize the silicon film, thermal annealing is performed at a temperature higher than 500° C., preferably 800°-900° C. After the silicon film is crystallized by thermal annealing, optical annealing may be performed to improve the crystallinity. Further, as disclosed in Japanese Unexamined Patent Publication No. Hei. 6-244104, the crystallization of silicon may be accelerated by adding such an element as nickel (catalyst element) in crystallizing the silicon film by thermal annealing.

In this embodiment, after a 50-nm-thick amorphous silicon film is formed by plasma CVD, hydrogen is removed by performing a heat treatment at 450° C. for one hour and then the amorphous silicon film is converted into a polycrystalline silicon film by illuminating it with excimer laser light. The polycrystalline silicon film is patterned into island-like active layers (a p-channel TFT active layer 122 and an n-channel TFT active layer 123) of peripheral driver circuit TFTs and an island-like active layer 124 of a pixel TFT. Although for convenience FIGS. 2A-2E show only three TFTs, actually millions of TFTs are formed at the same time.

A gate insulating film 125 is then formed. In this embodiment, a 120-nm-thick insulating film is formed by plasma CVD by using, as a material gas, a mixed gas of dinitrogen monoxide (N₂O) and monosilane (SiH₄).

Thereafter, a 300-nm-thick aluminum film is formed by sputtering and then patterned into gate electrodes 126-128.

Then, as shown in FIG. 2B, all the island-like active layers 122-124 are doped with phosphorus ions in a self-aligned manner by ion doping with the gate electrodes 126-128 used as a mask. Phosphine (PH₃) is used as a doping gas and the dose is set at 1×10^{12} to 5×10^{13} atoms/cm². As a result, weak n-type regions (n regions) 129-131 are formed.

Then, as shown in FIG. 2C, a photoresist mask 132 is formed so as to cover the entire p-channel TFT active layer 122 and a photoresist mask 134 is formed so as to cover part of the pixel TFT active layer 124. The mask 134 is formed so as to cover a portion that ends at positions distant from the respective ends of the gate electrode 128 by 3 μm as measured parallel with the gate electrode 128.

Then, phosphorus ions are again implanted by ion doping. Phosphine is used as a doping gas and the dose is set at 1×10^{14} to 5×10^{15} atoms/cm². As a result, sources/drains 135 and 136 are formed as strong n-type regions (n⁺ regions). In this doping step, no phosphorus ions are implanted into regions 137, covered with the mask 134, of the weak n-type regions (n⁻ regions) 131 of the pixel TFT active layer 124. Therefore, the regions 137 remain of the weak n type. The width x of the low-concentration impurity regions 137 is about 3 μm.

Then, as shown in FIG. 5D, the n-channel TFT active layers 123 and 124 are covered with a photoresist mask 138. Thereafter, boron is implanted into the island-like region 122 by ion doping by using diborane (B₂H₆) as a doping gas. The dose is set at 5×10^{14} to 8×10^{15} atoms/cm². Since the boron dose in this doping is higher than the phosphorus dose in the doping of the step of FIG. 2B, the weak n-type regions 130 are inverted to strong p-type regions 139.

Subsequently, thermal annealing is performed at 450°-850° C. for 0.5-3 hours to activate the doping impurities and restore the crystallinity of silicon. As a result of this

thermal annealing step, damage of the silicon film that has been caused by the doping steps is repaired.

As a result of the above doping steps, an n-type TFT having the strong n-type regions **135** as a source and a drain and a p-type TFT having strong p-type regions **139** as a source and a drain are formed in the driver circuit area **103** (**104**). Further, an n-type TFT having the strong n-type regions **136** as a source and a drain and the weak n-type low-concentration impurity regions **137** is formed in the pixel area **102** (see FIG. 2D).

Then, a first interlayer insulating film **140** is formed as shown in FIG. 2E. In this embodiment, a 500-nm-thick silicon nitride film is formed by plasma CVD. The first interlayer insulating film **140** may be another type of single layer film such as a silicon oxide film or a silicon oxynitride film, or a multilayered film of a silicon nitride film and a silicon oxide film or of a silicon nitride film and a silicon oxynitride film. Thereafter, contact holes are formed through the first interlayer insulating film **140** by etching it.

Thereafter, a titanium/aluminum/titanium multilayered film is formed by sputtering and then etched into driver circuit electrodes/interconnections **141-143** and pixel TFT electrodes/interconnections **144** and **145**. In this embodiment, the thickness of each titanium film is set at 100 nm and the thickness of the aluminum film is set at 300 nm.

Then, as shown in FIG. 3A, an organic resin film as a second interlayer insulating film **146** is formed at a thickness of 1.0-2.0 μm . The organic resin may be polyimide, polyamide, polyimideamide, polyacrylic, or the like. In this embodiment, a 1.5- μm -thick polyimide film is formed as the second interlayer insulating film **146**.

Then, a contact hole reaching the pixel TFT electrode **525** is formed by photolithography. Thereafter, as shown in FIG. 3B, a pixel electrode **147** is formed by forming a 300-nm-thick aluminum film to which titanium is added at 1 wt % and then patterning it.

In the pixel area **102** of the TFT substrate **100** shown in FIG. 18A, at least one TFT is provided for and electrically connected to each pixel electrode. Examples of driver circuits formed in the driver circuit areas **103** and **104** are a shift register and an address decoder. Other circuits may also be formed when necessary.

In this manner, driver circuit TFTs and pixel TFTs are formed in an integral manner in the driver circuit areas **103** and **104** and the pixel area **102**, respectively. In this embodiment, the number of pixels is set at 1,024 (vertical) $\times$ 768 (horizontal). In this specification, an area where pixel TFTs including the end pixel TFTs exist is called the pixel area **102** and an area where driver circuit TFTs including the end driver circuit TFTs exist is called the driver circuit area **103** (**104**).

The TFT substrate **100** is cleaned sufficiently to remove various chemicals such as etching liquids and resist removers that were used for the surface processing in forming the TFTs.

Next, a process of forming gap retaining members will be described. In the following description, the configurations of the driver circuit areas **103** and **104** where driver circuit TFTs **160** are formed and the pixel area **102** where pixel TFTs **150** are formed are simplified as shown in FIGS. 4A-4D. In FIGS. 4A-4D, for convenience, the scales of the respective parts are different.

First, as shown in FIG. 4B, a 2.2- μm -thick photosensitive polyimide film **301** is formed by spin coating. Thereafter, the substrate is left at the room temperature for 30 minutes to uniformize the thickness of the photosensitive polyimide film **301** over the entire TFT substrate **100** (leveling). Then, the TFT substrate **100** on which the photosensitive polyimide film **301** is formed is pre-baked at 120° C. for 3 minutes.

Then, the photosensitive polyimide film **301** is patterned in the following manner. As shown in FIG. 4C, after the photosensitive polyimide film **301** is covered with a photomask **302**, ultraviolet light is applied to the TFT substrate **100** from above. Subsequently, development is performed and then post-baking is performed at 280° C. for one hour. Patterned gap retaining members **303** are thus formed as shown in FIG. 4D.

FIG. 5A is a top view of the TFT substrate according to this embodiment, and FIG. 5B is an enlarged perspective view of a part of the TFT substrate that is indicated by a broken line in FIG. 5A. In FIGS. 5A and 5B, for convenience, the scales of the gap retaining members **303**, the pixel area **102**, and the driver circuit areas **103** and **104** are different from each other. In this embodiment, as shown in FIGS. 5A and 5B, the gap retaining members **303** are shaped like a cylinder of 10 μm in diameter and 2.2 μm in height. The gap retaining members **303** are formed at regular intervals of 30 μm so as to surround the pixel area **102** at a distance of about 70 μm from the end pixel TFTs. The arrangement density of the gap retaining members **303** in the vicinity of the liquid crystal injection inlet is set lower than in the other portions. It is preferable that the arrangement density of the gap retaining members **303** be uniform.

In the gap retaining members **303** of the invention, the accuracy of their height is important. In this embodiment, the height accuracy of the gap retaining members **303** is set at $\pm 0.1 \mu\text{m}$. On the other hand, it is sufficient that the positional accuracy of the gap retaining members **303** be about $\pm 10 \mu\text{m}$. In this embodiment, part of the gap retaining members **303** are formed between the pixel area **102** and the driver circuit areas **103** and **104**. In this embodiment, the intervals between the pixel area **102** and the driver circuit areas **103** and **104** are about 400 nm, which is sufficiently longer than the diameter of the gap retaining members **303**. Therefore, the positional accuracy of the gap retaining members **303** is not much important. The gap retaining members **303** are not formed inside the pixel area **102** and the driver circuit areas **103** and **104**.

Although in this embodiment the gap retaining members **303** are shaped like a cylinder, they may be shaped like an ellipse, a streamlined shape, or a polygon such as a triangle or a rectangle. The gap retaining members **303** may have any shape as long as they can control the gap between the TFT substrate (first substrate) **100** and the opposed substrate (second substrate) **200**. Although in this embodiment all the gap retaining members **303** have the same shape and are arranged at regular intervals, gap retaining members having plural kinds of shapes may be arranged at different intervals. Although in this embodiment the gap retaining members **303** are formed at the constant distance from the pixel area **102**, they may be formed at different distances from pixel area **102**. Further, although in this embodiment the gap retaining members **303** are formed so as to surround the pixel area **102**, they may be formed anywhere except the insides of the pixel area **102** and the driver circuit areas **103** and **104** as long as they can control the cell gap.

Then, alignment films are formed on the TFT substrate **100** and the opposed substrate **200**. Specifically, the TFT substrate **100** and the opposed substrate **200** are coated with polyimide-type vertical alignment films by one of spin coating, flexography, and screen printing. In this embodiment, 1,000-Å-thick alignment films are formed by spin coating. Then, the alignment films are cured by baking in which a hot wind of 180° C. is fed.

Then, rubbing is performed in which the surface of the opposed substrate **200**, i.e., the surface of the alignment film,

11

is rubbed in one direction with a buff cloth (fiber of rayon, nylon, or the like) having hair lengths of 2-3 mm. In this embodiment, rubbing is not performed on the TFT substrate 100 side.

Thereafter, a sealing agent 205 is applied to the opposed substrate 200 along its periphery (see FIG. 1B). Alternatively, the sealing agent 205 may be applied to the TFT substrate 100 side. The TFT substrate 100 and the opposed substrate 200 are then bonded together (see FIG. 6).

Then, a liquid crystal material 300 as a display medium is injected through a liquid crystal injection inlet 206, whereby the liquid crystal material 300 is held between the TFT substrate 100 and the opposed substrate 200. In this embodiment, since the gap retaining members 303 are shaped like a cylinder, the flow resistance that occurs between the liquid crystal material 300 and the surfaces of the gap retaining members 303 in injecting the liquid crystal material 300 is small. Therefore, the liquid crystal material 300 can be injected uniformly over the entire substrate surfaces. It is preferable that the gap retaining members 303 be shaped and arranged so as to reduce the flow resistance.

Then, after a sealing agent (not shown) is applied to the liquid crystal injection inlet 206, the sealing agent is cured by illuminating it with ultraviolet light. The liquid crystal material 300 is thus completely sealed in the cell.

When the display characteristics of cells actually manufactured in the above manner were checked, no interference fringe was observed on the cell surfaces. Further, superior display performance with no disclination was obtained.

Embodiment 2

In this embodiment, the steps until pixel TFTs and driver circuit TFTs are formed to constitute a TFT substrate are the same as in the first embodiment and hence are not described here.

After the pixel TFTs and the driver circuit TFTs are formed in an integral manner to constitute the TFT substrate, gap retaining members are formed on the TFT substrate as shown in FIG. 3B. A process of forming gap retaining members according to this embodiment will be described below with reference to FIGS. 7A-7D and 8A-8C. The configuration of FIG. 7A is the same as that of FIG. 4A.

First, as shown in FIG. 7B, a 2.2- μ m-thick photosensitive polyimide film 311 is formed by spin coating. Thereafter, the substrate is left at the room temperature for 30 minutes to uniformize the thickness of the photosensitive polyimide film 311 over the entire TFT substrate 100 (leveling). Then, the TFT substrate 100 on which the photosensitive polyimide film 311 is formed is pre-baked at 120° C. for 3 minutes.

Then, the photosensitive polyimide film 311 is patterned in the following manner. As shown in FIG. 7C, after the photosensitive polyimide film 311 is covered with a photomask 312, ultraviolet light is applied to the TFT substrate 100 from above. Subsequently, development is performed, the photomask 312 is removed, and then post-baking is performed at 280° C. for one hour. As a result, cylindrical gap retaining members 313 are formed (see FIG. 7D).

Thereafter, a resist film is applied uniformly and patterned into a desired pattern. In this embodiment, a resist film (not shown) is formed on the top faces of the cylindrical gap retaining members 313. Subsequently, as shown in FIG. 8A, the shape of the gap retaining members 313 is modified by applying oxygen plasma to those. Since the top surfaces of the gap retaining members 313 are protected by the resist film (not shown), only their side faces are etched (ashed), whereby gap retaining members 314 having tapered side faces are

12

formed as shown in FIG. 8B. After completion of the etching, the resist film is removed. FIG. 8C is an enlarged view of a gap retaining member 314. Each gap retaining member 314 is shaped like a truncated cone in which the bottom face diameter is 30 μ m, the top face diameter is 20 μ m, and the height is 2.2 μ m.

FIG. 9 is a top view of the TFT substrate 100 according to this embodiment. The patterned cell gas retaining members 314 have been formed by the above process. In this embodiment, as shown in FIG. 9, the gap retaining members 314 are formed so as to doubly surround the pixel area 102.

Thereafter, alignment films are formed on the TFT substrate 100 and the opposed substrate 200 in the same manner as in the first embodiment.

Then, rubbing is performed on the surface of the opposed substrate 200, i.e., the surface of the alignment film, and a sealing agent 315 is applied to the TFT substrate 100 (see FIG. 9). The TFT substrate 100 and the opposed substrate 200 are then bonded together (not shown). In FIG. 9, the same reference numerals as in FIGS. 1A and 1B denote the same members as in FIGS. 1A and 1B.

Then, a liquid crystal material as a display medium is injected through a liquid crystal injection inlet. In this embodiment, since the side faces of the gap retaining members 314 are tapered, the resistance that occurs between the liquid crystal material and the gap retaining members 314 in injecting the liquid crystal material is small. Therefore, the liquid crystal material can be injected uniformly over the entire substrates. Then, the liquid crystal material is completely sealed in the cell by sealing the liquid crystal injection inlet with a sealing agent (not shown).

The uniformity of the cell thickness can be improved by increasing the number of gap retaining members 314, particularly by increasing the number of gap retaining members 314 in the vicinity of the pixel area 102. When the display characteristics of cells actually manufactured in the above manner were checked, no interference fringe was observed on the cell surfaces. Further, superior display performance with no disclination was obtained.

Embodiment 3

This embodiment is different from the first embodiment only in the number and arrangement of gap retaining members. Since this embodiment is the same as the first or second embodiment in the other points, a manufacturing process will not be described. In FIG. 10, the same reference numerals as in FIGS. 1A and 1B and FIG. 9 denote the same members as in the latter figures. In this embodiment, a sealing agent 403 is formed on the TFT substrate 100 side.

In this embodiment, as shown in FIG. 10, gap retaining members 401 are formed on the TFT substrate 100 so as to surround the pixel area 102 and gap retaining members 402 are formed on the TFT substrate 100 so as to surround the driver circuit areas 103 and 104. The gap retaining members 401 and 402 are shaped like a cylinder of 30 μ m in diameter and 2.2 μ m in height.

Then, rubbing is performed on the surface of the opposed substrate 200, i.e., the surface of an alignment film, and a sealing agent 403 is applied to the TFT substrate 100 (see FIG. 10). The TFT substrate 100 and the opposed substrate 200 are then bonded together (not shown).

Then, a liquid crystal material as a display medium is injected through a liquid crystal injection inlet 404, and the liquid crystal material is completely sealed in the cell by sealing the liquid crystal injection inlet 404 with a sealing agent (not shown).

13

When the display characteristics of cells actually manufactured in the above manner were checked, no interference fringe was observed on the cell surfaces. Further, superior display performance with no disclination was obtained.

Embodiment 4

In this embodiment, the steps until pixel TFTs and driver circuit TFTs are formed to constitute a TFT substrate are the same as in the first embodiment and hence are not described here.

A TFT substrate **100** is produced as shown in FIG. 3B according to the steps described in the first embodiment. A process of forming gap retaining members according to this embodiment will be described below with reference to FIGS. 11A-11C.

The configuration of FIG. 11A is the same as that of FIG. 3B. In this embodiment, gap retaining members **503** are formed by printing on the TFT substrate **100** in which pixel TFTs **150** and driver circuit TFTs **160** are formed. In this embodiment, the gap retaining members **503** are made of a polyimide resin.

Specifically, as shown in FIG. 11B, gap retaining members **503** are formed by covering the TFT substrate **100** with a screen **501** and then printing a polyimide resin. In this embodiment, gap retaining members **503** of 1.1 μm in height are formed by a single printing operation. Gap retaining members **503** having a desired height are formed by repeating the steps of printing a polyimide resin, baking it for a while, and again printing a polyimide resin so that it is superimposed on the previous polyimide resin.

FIG. 12A is a top view showing the TFT substrate **100** on which the gap retaining members **503** are formed. In FIG. 12A, the same reference numerals as in FIGS. 1A and 1B and FIG. 9 denote the same members as in the latter figures. In this embodiment, a sealing member **511** is formed on the TFT substrate **100** side.

In this embodiment, the gap retaining members **503** are shaped like an elliptical pole in which the major axis length is 30 μm , the minor axis length is 15 μm , and the height is 2.2 μm , and are arranged so as to surround the pixel area **102**. Further, in this embodiment, the gap retaining members **503** are arranged so as to reduce the resistance that occurs between the gap retaining members **503** and a liquid crystal material in injecting the liquid crystal material. That is, the gap retaining members **503** are arranged so that the major axes of the gap retaining members **503** are parallel with the flowing direction of the liquid crystal material that is injected through a liquid crystal injection inlet (see FIG. 12B).

Then, alignment films are formed on the surfaces of the TFT substrate **100** and the opposed substrate **200**. Specifically, the TFT substrate **100** and the opposed substrate **200** are coated with 100-nm-thick, polyimide-type vertical alignment films (not shown) by one of spin coating, flexography, and screen printing. Then, the alignment films are cured by baking in which a hot wind of 180° C. is fed.

Thereafter, a sealing agent **511** is applied to a peripheral portion of the TFT substrate **100** so as to leave a liquid crystal injection inlet **512**, and the TFT substrate **100** and the opposed substrate **200** are bonded together (not shown).

Then, a liquid crystal material is injected through the liquid crystal injection inlet **512**. In this embodiment, the gap retaining members **503** are shaped like an elliptical pole and are arranged so as to reduce the resistance that occurs between the gap retaining members **503** and the liquid crystal material in

14

injecting the liquid crystal material. Therefore, the liquid crystal material can be injected uniformly over the entire substrates.

Thereafter, a sealing agent (not shown) is applied to the liquid crystal injection inlet **512** and then cured by illuminating it with ultraviolet light. The liquid crystal material is thus completely sealed in the cell.

Embodiment 5

This embodiment is directed to a method of forming gap retaining members that is different from in the first embodiment.

First, a TFT substrate **100** is produced according to the steps described in the first embodiment. The TFT substrate **100** is cleaned sufficiently to remove various chemicals such as etching liquids and resist removers that were used for the surface processing in forming the TFTs.

Next, a process of forming gap retaining members will be described with reference to FIGS. 13A-13C and 14A-14B. In these figures, for convenience, the scales of gap retaining members formed and the TFTs are made different from each other.

FIG. 13A shows the TFT substrate **100** that has been produced by the steps of the first embodiment. The configuration of FIG. 13A corresponds to that of FIG. 3B. Some reference numerals are omitted in FIG. 13A.

As shown in FIG. 13B, a 4.2- μm -thick photosensitive polyimide film **601** is formed by spin coating. Thereafter, the substrate is left at the room temperature for 30 minutes to uniformize the thickness of the photosensitive polyimide film **601** over the entire TFT substrate **100** (leveling). Then, the TFT substrate **100** on which the photosensitive polyimide film **601** is formed is pre-baked at 120° C. for 3 minutes.

Then, the top surface of the photosensitive polyimide film **601** is planarized by polishing it by CMP (chemical mechanical polishing). In this embodiment, slurry that is used in the CMP step is a colloid-like one in which a silica (SiO_2) fine powder is dispersed in an acid solution. As for the CMP conditions, each of the substrate and an abrasive cloth is rotated at 50 rpm and the polishing time is set at 3 minutes. The top surface of the photosensitive polyimide film **601** is planarized by the CMP step. The thickness of the planarize photosensitive polyimide film **601** was 3.2 μm . The CMP processing accuracy of the photosensitive polyimide film **601** was 0.1 μm .

Although in this embodiment the slurry that is used in the CMP step is one in which a silica fine powder is dispersed in an acid solution, slurry obtained by dispersing aluminum oxide (Al_2O_3), cerium oxide (CeO), or the like in an acid solution may also be used. It is desirable that the slurry be changed in accordance with the material that is subjected to CMP. Further, although in this embodiment CMP is performed for 3 minutes while each of the substrate and the abrasive cloth is rotated at 50 rpm, it is desirable that the optimum rotation speed and processing time be set for a material to be subjected to CMP.

The cell gap (interval between the substrates) is determined by the thickness of the photosensitive polyimide film **601** that has been subjected to CMP. Therefore, the thickness of the as-formed photosensitive polyimide film **601** may be set properly and the thickness to be reduced by CMP may be adjusted in accordance with the desired cell gap. In this manner, the desired cell gap can be obtained with high accuracy.

Although in this embodiment CMP is used in the step of polishing and planarizing the photosensitive polyimide film **601**, this step may be executed by any method as long as the

15

top surface of the photosensitive polyimide film **601** can be planarized with high accuracy. For example, etch back may also be used.

Then, the photosensitive polyimide film **601** is patterned. Specifically, as shown in FIG. **14A**, after the photosensitive polyimide film **601** is covered with a photomask **602**, ultraviolet light is applied to the TFT substrate **100** from above. Subsequently, development is performed and then post-baking is performed at 280° C. for one hour. As a result, patterned gap retaining members **603** are formed as shown in FIG. **14B**. In this specification, the CMP-processed faces of the gap retaining members are called top faces.

FIG. **15A** is a top view of the TFT substrate **100** according to this embodiment. FIG. **15B** is an enlarged perspective view of a part of FIG. **15A** that is indicated by a two-dot chain line. In FIGS. **15A** and **15B**, for convenience, the scales of the gap retaining members **603**, the pixel area **102**, and the driver circuit areas **103** and **104** are different from each other. The components in FIGS. **15A** and **15B** that are given the same reference numerals as in FIGS. **1A** and **1B** are the same as the corresponding components in FIGS. **1A** and **1B**.

In this embodiment, as shown in FIGS. **15A** and **15B**, the gap retaining members **603** are shaped like a cylinder of 4 μm in diameter and 3.2 μm in height. In this embodiment, the gap retaining members **603** are arranged randomly. Their arrangement density may be set at 40-160 mm^{-2} . In this embodiment, it is set at 50 mm^{-2} .

Although in this embodiment the gap retaining members **603** are shaped like a cylinder, they may be shaped like an ellipse, a streamlined shape, or a polygon such as a triangle or a rectangle. The gap retaining members **603** may have any shape as long as they can control the gap between the TFT substrate (first substrate) **100** and the opposed substrate (second substrate) **200**. Although in this embodiment all the gap retaining members **603** have the same shape, gap retaining members having plural kinds of shapes may be formed. Further, although in this embodiment the gap retaining members **603** are formed so that their arrangement density is uniform over the entire surface of the TFT substrate **100**, the gap retaining members **603** may be arranged at a higher density in a certain region.

Then, an opposed substrate **200** in which an opposed electrode is formed is prepared (see FIG. **1B**). In this embodiment, the opposed electrode that is formed in a pixel-confronting area **202** is made of ITO (indium tin oxide).

Then, alignment films (not shown) are formed on the TFT substrate **100** and the opposed substrate **200**. Specifically, the TFT substrate **100** and the opposed substrate **200** are coated with 1,000-Å-thick, polyimide-type vertical alignment films by spin coating. Then, the alignment films are cured by baking in which a hot wind of 180° C. is fed.

Then, rubbing is performed in which the surface of the opposed substrate **200**, i.e., the surface of the alignment film, is rubbed in one direction with a buff cloth (fiber of rayon, nylon, or the like) having hair lengths of 2-3 mm. In this embodiment, rubbing is not performed on the TFT substrate **100** side.

Thereafter, in this embodiment, a sealing agent **605** is applied to the opposed substrate **200** along its periphery so as to leave a liquid crystal injection inlet **606** (see FIG. **15A**). The TFT substrate **100** and the opposed substrate **200** are then bonded together.

Then, a liquid crystal material as a display medium is injected through the liquid crystal injection inlet **606**, whereby the liquid crystal material is held between the TV substrate **100** and the opposed substrate **200**. In this embodiment, since the gap retaining members **606** are shaped like a

16

cylinder, the flow resistance that occurs between the liquid crystal material and the surfaces of the gap retaining members **603** in injecting the liquid crystal material is small. Therefore, the liquid crystal material can be injected uniformly over the entire substrate surfaces. It is preferable that the gap retaining members **603** be shaped and arranged so as to reduce the flow resistance.

Then, after a sealing agent (not shown) is applied to the liquid crystal injection inlet **606**, the sealing agent is cured by illuminating it with ultraviolet light. The liquid crystal material is thus completely sealed in the cell.

When the display characteristics of cells actually manufactured in the above manner were checked, no interference fringe was observed on the cell surfaces. Further, superior display performance with no disclination was obtained.

Embodiment 6

This embodiment is different from the fifth embodiment in the area where gap retaining members are formed. This embodiment will be described with reference to FIG. **16**. The components in FIG. **16** that are given the same reference numerals as in FIGS. **15A** and **15B** are the same as the corresponding components in FIGS. **15A** and **15B**. Reference numeral **610** denotes gap retaining members; **101**, a substrate; **102**, a pixel area; **103** and **104**, driver circuit areas; **605**, a sealing agent; and **606**, a liquid crystal injection inlet.

In this embodiment, as shown in FIG. **16**, the gap retaining members **610** are formed at regular intervals in the pixel area **102** and the driver circuit areas **103** and **104**. It is preferable that in the pixel area **102** the gap retaining members **610** be formed in regions where signal lines and selection lines for the TFTs cross each other. The interval between the gap retaining members **610** in the pixel area **102** may be made different than in the driver circuit areas **103** and **104**.

Embodiment 7

This embodiment is different from the second and fifth embodiments in the area where gap retaining members are formed. This embodiment will be described with reference to FIG. **17**. The components in FIG. **17** that are given the same reference numerals as in FIGS. **15A** and **15B** are the same as the corresponding components in FIGS. **15A** and **15B**.

In this embodiment, as shown in FIG. **17**, gap retaining members **620** are formed in an area excluding the pixel area **102** and the driver circuit areas **103** and **104**.

In this embodiment, since the gap retaining members **620** do not exist in the pixel area **102** nor the driver circuit areas **103** and **104**, they do not decrease the effective aperture ratio as well as unnecessary stress is not exerted on the TFTs in the pixel area **102** and the driver circuit areas **103** and **104** in bonding the TFT substrate **100** and the opposed substrate **200** together. Therefore, the TFTs are not damaged and hence the yield of products will increase.

Embodiment 8

This embodiment is the same as the fifth, sixth, and seventh embodiment in the configuration of the TFT substrate **100** side, and is different from those embodiment in the configuration of the opposed substrate **200** side.

In an electro-optical device according to this embodiment, an organic resin film is formed after an opposed electrode is formed to constitute the opposed substrate **100**. The organic resin film serves as a leveling film. In this embodiment, the organic resin film is made of polyimide. Other examples of

17

the material of the organic resin film are acrylic, polyamide, and polyimideamide and the like.

Then, CMP is performed on the organic resin film in the same manner as in the fifth embodiment, whereby the organic resin film is leveled.

Thereafter, alignment films are formed on the TFT substrate **100** and the opposed substrate **200** and then rubbing is performed on the opposed substrate **200** side. The ensuing steps are the same as in the fifth embodiment.

In this embodiment, not only do the top faces of the gap retaining members provided on the TFT substrate **100** exist in the same plane but also the flatness of the top surface of the organic resin film provided on the opposed substrate **200** is secured. Therefore, the uniformity of the cell gap can even be improved. The opposed substrate **200** of this embodiment may be used in each of the first to fourth embodiments.

Embodiment 9

Although the first to eighth embodiments are directed to the case of using planar TFTs, naturally the invention is not limited by the TFT structure. Therefore, each TFT in the pixel area **102** and the driver circuit areas **103** and **104** may be an inverted staggered structure TFT or a multi-gate TFT.

Although in the first to eighth embodiments the gap retaining members are made of polyimide, other resins such as acrylic, polyamide, and polyimideamide may also be used. Further, the gap retaining members may be made of a thermosetting resin.

Although in the first to eighth embodiments the gap retaining members are formed on the TFT substrate **100**, they may be formed on the opposed substrate **200** or both of them. Even in such cases the gap retaining members may be formed according to the method of the fifth embodiment.

Although in the first to eighth embodiments the gap retaining members are made of polyimide, they may be made of other insulative materials.

Although the first to eighth embodiments are directed to the reflection-type electro-optical devices, transmission-type electro-optical devices may be formed by making some modifications such as using a transparent pixel electrode.

Although the first to eighth embodiments are directed to the case where a liquid crystal material is used as a display medium, the gap retaining members of the invention can also be with a mixed layer of a liquid crystal material and a polymer, that is, they can be used in a polymer dispersion type liquid crystal display device. Further, the electro-optical devices of the invention may use any other display media whose optical characteristic is modulated in response to the application voltage, such as an electroluminescence element.

Although in the first to eighth embodiments no particular reference is made to color display, color filters may be provided on the opposed substrate **200** side when color display is needed. The color filters are required to be uniform in thickness, i.e., flat, and superior in both heat resistance and resistance to chemicals.

Although in the first to eighth embodiments rubbing is performed on only the opposed substrate **200** side, rubbing may be performed on the TFT substrate **100** side or both substrates.

Although the first to eighth embodiments are directed to the active matrix electro-optical devices, it goes without saying that the invention can be applied to passive electro-optical devices that have no active elements such as TFTs.

Embodiment 10

This embodiment will be described with reference to FIG. **18** to FIGS. **21A** and **21B**. This embodiment is directed to a

18

case where the invention is applied to an active matrix liquid crystal display device and gap retaining members are formed on only the opposed substrate **200**. FIG. **18** is a schematic sectional view of a liquid crystal display device. The components in FIG. **18** that are given the same reference numerals as in FIGS. **1A** and **1B** are the same components as in FIGS. **1A** and **1B**.

As shown in FIG. **18**, a TFT substrate **100** and an opposed substrate **200** are bonded together with a sealing agent **205** that is provided on a peripheral portion of a substrate **201**. The opposed substrate **200** is provided with an opposed electrode **210** that confronts a pixel area **102** and gap retaining members **220** for retaining the gap between the TFT substrate **100** and the opposed substrate **200**.

A liquid crystal **300** is injected into the space between the TFT substrate **100** and the opposed substrate **200** through a liquid crystal injection inlet **206** and then sealed with a sealing agent **205**. The TFT substrate **100** and the opposed substrate **200** are provided with alignment films **110** and **230** for giving proper alignment to the liquid crystal **300**, respectively.

First, the TFT substrate **100** is produced according to the manufacturing method of the TFT substrate **100** described in the first embodiment (see FIGS. **2A-2E** and **3A-3B**). In the pixel area **102** of the TFT substrate **100** shown in FIG. **19**, at least one TFT is provided for and electrically connected to each pixel electrode. Examples of driver circuits formed in the driver circuit areas **103** and **104** are a shift register and an address decoder. Other circuits may also be formed when necessary.

After the configuration of FIG. **3B** is obtained, the TFT substrate **100** is cleaned sufficiently to remove various chemicals such as etching liquids and resist removers that were used for the surface processing in forming the TFTs. Then, an alignment film **110** is formed on the TFT substrate **100** as shown in FIG. **19** according to a method described later.

Next, a manufacturing process of the opposed substrate **200** will be described with reference to FIGS. **20A-20E**. As shown in FIG. **20A**, a transparent glass or quartz substrate is used as a substrate **201**. In this embodiment, a glass substrate is used. A transparent conductive film is formed on the glass substrate **201** and then patterned into an opposed electrode **210** in an area **202** to confront the pixel area **102** (see FIG. **20A**). In this embodiment, a 150-nm-thick ITO film is formed as the transparent conductive film.

If necessary, color filters and a black matrix are formed by a known method such as dyeing or printing before the formation of the opposed electrode **210**. The color filters are required to be uniform in thickness, i.e., flat, and superior in both heat resistance and resistance to chemicals.

Next, a process of forming the gap retaining members **220** will be described. In this embodiment, the gap retaining members **220** are formed by using polyimide which is one of photosensitive resin materials.

First, as shown in FIG. **20B**, a 3.2- μ m-thick photosensitive polyimide film **211** is formed by spin coating. Thereafter, the substrate is left at the room temperature for 30 minutes to uniformize the thickness of the photosensitive polyimide film **211** over the entire opposed substrate **200** (leveling). Then, the opposed substrate **200** on which the photosensitive polyimide film **211** is formed is pre-baked at 120° C. for 3 minutes.

Since the thickness of the photosensitive polyimide film **211** determines the cell gap (interval between the substrates), it may be set properly in accordance with the desired cell gap. For example, the thickness of the photosensitive polyimide film **211** may be determined so that the cell gap becomes about 4-6 μ m for a transmission-type liquid crystal display

device, about 2-3 μm for a reflection-type liquid crystal display device, and less than 2 μm for a ferroelectric liquid crystal display device. Since the liquid crystal display device of this embodiment is of a reflection type, the thickness of the photosensitive polyimide film **211** is set at 3.2 μm .

Then, the photosensitive polyimide film **211** is patterned. Specifically, after the photosensitive polyimide film **211** is covered with a photomask **212** as shown in FIG. 20C, ultraviolet light is applied from the mask **212** side. Subsequently, development is performed and then post-baking is performed at 280° C. for one hour. Patterned gap retaining members **220** are thus formed as shown in FIG. 20D.

FIGS. 21A and 21B are a top view and an enlarged perspective view, respectively, of the opposed substrate **200** in the state of FIG. 20D. As shown in FIGS. 21A and 21B, the gap retaining members **220** are shaped like a cylinder and replace the conventional spherical spacers. Therefore, the cylinder diameter and height of the gap retaining members **220** may be set at 1.5-2.5 μm and 2.0-5.0 μm , respectively. In this embodiment, the cylinder diameter is set at 3.0 μm and, to provide a cell gap of 3.0 μm , the cylinder height is set at 3.2 μm in the pixel-confronting area **202**. The height of the gap retaining members **220** in driver-circuit-confronting areas **203** and **204** is made greater than in the pixel-confronting area **202** by the total thickness of the opposed electrode **210**, the color filters, etc.

In this embodiment, the gap retaining members **220** are arranged randomly so as to function in the same manner as the conventional spherical spacers. Therefore, the density of the gap retaining members **220** may be set approximately equal to that of the conventional spherical spacers, i.e., about 40-160 mm^{-2} . In this embodiment, the gap retaining members **220** are arranged randomly at a density of 50 mm^{-2} . Since the gap retaining members **220** are arranged randomly over the entire opposed substrate **200**, the positional accuracy of the gap retaining members **220** is not very important, which means a large production margin.

Then, alignment films **110** and **230** are formed on the TFT substrate **100** and the opposed substrate **200**, respectively (see FIGS. 19 and 20E). The alignment films **110** and **230** are vertical alignment type polyimide films. The thickness of the alignment films **110** and **230** may be set at about 60-100 nm.

Specifically, after the TFT substrate **100** and the opposed substrate **200** are cleaned, they are coated with respective polyimide-type vertical alignment films by one of spin coating, flexography, and screen printing. In this embodiment, polyimide films are applied by spin coating. Then, the polyimide films are cured by performing preliminary baking at 80° C. for 5 minutes and then performing main baking by feeding a hot wind of 180° C. The alignment films **110** and **230** are thus formed at a thickness of 80 nm.

In FIG. 20E, the alignment film **230** is drawn so as not to cover the side faces and the top faces of the gap retaining members **220**. In this embodiment, since the polyimide film is formed by spin coating, there may occur a case that the polyimide film covers the side faces and the top faces of part of the gap retaining members **220**. Since the polyimide film (thickness: tens to hundreds of nanometers) is much thinner than the gap retaining members **220** (height: several micrometers) and it may not assume a complete film on vertical surfaces such as the side faces of the gap retaining members **220**, in FIG. 20E the alignment film **230** is shown so as to be formed on only the horizontal surface.

Although in this embodiment the alignment films **110** and **230** are made of polyimide, other resins such as acrylic, polyamide, and polyimideamide may also be used. Further, they may be made of a thermosetting resin.

Then, rubbing is performed in which each of the surface of the alignment film **110** on the TFT substrate **100** and the surface of the alignment film **230** on the opposed substrate **200** is rubbed in one direction with a buff cloth (fiber of rayon, nylon, or the like) having hair lengths of 2-3 mm. A TN mode alignment operation is performed in which the rubbing directions for the TFT substrate **100** and the opposed substrate **200** are perpendicular to each other.

In rubbing the TFT substrate **100**, electrostatic breakdown of the TFTs formed in the TFT substrate **100** is prevented by preventing generation of static electricity by using an ion blow apparatus or a humidifier.

On the other hand, in rubbing the opposed substrate **200**, the kind and the hair planting density of the buff cloth and the rubbing conditions such as the roller rotation speed are selected or set so as not to destroy the gap retaining members **220**.

Then, an ultraviolet curable resin as a sealing agent **205** is applied to a peripheral portion of the opposed substrate **200** so as to leave a liquid crystal injection inlet **206** (see FIG. 21A). Subsequently, the TFT substrate **100** and the opposed substrate **200** are opposed to each other and then pressed against each other so that the cell gap in the pixel area **102** comes equal to the height of the gap retaining members **220**. The sealing agent **205** is cured in this state. The sealing agent **205** may be applied to the TFT substrate **100** side.

Then, a liquid crystal material **300** as a display medium is injected through the liquid crystal injection inlet **206**, whereby the liquid crystal material is held between the TFT substrate **100** and the opposed substrate **200**. After a sealing agent is applied to the liquid crystal injection inlet **206**, the sealing agent is cured by illuminating it with ultraviolet light. The liquid crystal material **300** is thus completely sealed in the cell.

The configuration of FIG. 18 is obtained by the above steps.

Although in this embodiment the gap retaining members **220** are shaped like a cylinder, they may be shaped like an ellipse, a streamlined shape, or a polygon such as a triangle or a rectangle. The gap retaining members **220** may have any shape as long as they can control the gap between the TFT substrate (first substrate) **100** and the opposed substrate (second substrate) **200**.

Although this embodiment is directed to the reflection-type liquid crystal display device in which the pixel electrodes are made of a metal material, a transmission-type liquid crystal display device may also be configured because the TN mode type alignment operation is performed. In such a case, the pixel electrodes may be transparent conductive films of ITO, SnO_2 , or the like. Further, although this embodiment is of the TN mode type, other modes may also be employed; the rubbing may be performed in accordance with the mode.

Although this embodiment is directed to the case of using planar TFTs, naturally the invention is not limited by the TFT structure. Therefore, each TFT in the pixel area **102** and the driver circuit areas **103** and **104** may be an inverted staggered structure TFT or a multi-gate TFT. Further, this embodiment can be applied to an IPS-type liquid crystal panel in which also the opposed electrode is formed on the TFT substrate.

In this embodiment, since the gap retaining members **220** are made of a photosensitive resin material, their height can be set as desired, for instance, at less than 2 μm . Therefore, the cell gap of the liquid crystal display device can be made less than 2 μm . Therefore, the gap retaining members **220** of this embodiment are suitable for use in a liquid crystal panel of a ferroelectric liquid crystal display device or that of a projection-type liquid crystal display device.

21

Further, in this embodiment, since the gap retaining members **220** are fixed to the opposed substrate **200**, they are not gathered due to the flow of a liquid crystal, unlike the conventional spacers. Therefore, point defects due to gathering of spacers can be prevented.

Embodiment 11

Although in the tenth embodiment rubbing is performed on both of the TFT substrate **100** side and the opposed substrate **200** side. In this embodiment, rubbing is performed on only the alignment film **110** formed on the TFT substrate **100**. The other part of the manufacturing process of this embodiment is the same as in the tenth embodiment.

Since a buff cloth that is used in the rubbing step is a source of static electricity and dust, the yield of the liquid crystal display device strongly depends on the rubbing step. In this embodiment, to reduce the number of rubbing operations, rubbing is performed on only the TFT substrate **100** side.

As for the opposed substrate **200**, the height of the gap retaining members **220** is several micrometers and the thickness of the alignment film **230** is tens to hundreds of nanometers, and hence the gap retaining members **220** project to the liquid crystal side. Therefore, there is a possibility that the rubbing with the buff cloth damages or peels the gap retaining members **220**. In such a case, the thickness of the gap retaining members **220** vary, making it difficult to keep the cell gap uniform over the entire substrate or among substrates. Further, damaged or peeled gap retaining members **220** become a new source of dust.

Further, since the gap retaining members **220** project to the liquid crystal side, it is difficult to form grooves in the alignment film **230** in the intended manner, leaving a possibility that the liquid crystal **300** will not be given proper alignment. Since display cannot be performed if the liquid crystal **300** is not oriented properly, properly orienting the liquid crystal **300** is an important factor in increasing the production yield.

To avoid the above problems, in this embodiment, rubbing is performed on only the alignment film **110** formed on the TFT substrate **100**.

In this embodiment, as in the tenth embodiment, the alignment films **110** and **230** are vertical alignment type polyimide films. Rubbing is performed in such a manner that the surface of alignment film **110** formed on the TFT substrate **100** is rubbed in a predetermined direction with a buff cloth (fiber of rayon, nylon, or the like) having hair lengths of 2-3 mm. To prevent a reduction in the production yield of the TFT substrate **100**, it is important that a proper measure be taken to prevent generation of static electricity in the step of rubbing the TFT substrate **100**.

Embodiment 12

While in the eleventh embodiment rubbing is performed on only the TFT substrate **100** side, in this embodiment rubbing is performed on only the alignment film **230** formed on the opposed substrate **200**. The other part of the manufacturing process of this embodiment is the same as in the tenth embodiment (see FIG. 18).

Since a buff cloth that is used in the rubbing step is a source of static electricity and dust, the yield of the liquid crystal display device strongly depends on the rubbing step. In this embodiment, to reduce the number of rubbing operations, rubbing is performed on only the opposed substrate **200** side.

The buff cloth used in the rubbing step causes static electricity and dust, which may destroy the TFTs that are formed in the TFT substrate **100**. More steps are needed to produce

22

the TFT substrate **100** than to produce the opposed substrate **200**. Therefore, frequent occurrence of defects in TFT substrates **100** increases the manufacturing cost of the liquid crystal display device. This embodiment is intended to increase the production yield of the TFT substrate **100** by refraining from rubbing the TFT substrate **100** side.

In this embodiment, as in the tenth embodiment, the alignment films **110** and **230** are vertical alignment type polyimide films. Rubbing is performed in such a manner that the surface of alignment film **230** formed on the opposed substrate **200** is rubbed in a predetermined direction with a buff cloth (fiber of rayon, nylon, or the like) having hair lengths of 2-3 mm. The rubbing conditions are set so as not to damage or peel the gap retaining members **220** formed on the opposed substrate **200**.

Although the eleventh and twelfth embodiments are the same in that rubbing is performed on only one substrate side, they have different effects. A party who practice the invention may select a substrate to be subjected to rubbing in consideration of the manufacturing cost, the yield, and other factors.

Where rubbing is performed on only one of the alignment films as in the case of the eleventh and twelfth embodiments, available liquid crystal driving modes are restricted. However, the inventors have confirmed that the birefringence (ECB) mode is available.

On the other hand, where rubbing is performed on both alignment films as in the case of the tenth embodiment, there are advantages that available liquid crystal driving modes are not restricted and the liquid crystal can be oriented reliably though rubbing operations need to be performed one time more than in the eleventh and twelfth embodiments. Where the invention is applied to a polymer dispersion type liquid crystal display device, no alignment film rubbing operation is necessary.

Embodiment 13

This embodiment is directed to modification to the arrangement of the gap retaining members and is the same as the tenth embodiment in the other points. FIG. 22 is a top view of an opposed substrate according to this embodiment. The members in FIG. 22 that are given the same reference numerals as in FIGS. 21A and 21B are the same as the corresponding members in FIGS. 21A and 21B.

In the tenth embodiment, the gap retaining members **220** are arranged randomly on the entire opposed substrate **200** as shown in FIG. 21A. In contrast, in this embodiment, as shown in FIG. 22, gap retaining members **700** are arranged regularly in matrix form. The shape of the gap retaining members **700** are the same as in the tenth embodiment, that is, they are shaped like a cylinder of 2.0 μm in diameter and 3.2 μm in height. Also as in the case of the tenth embodiment, the gap retaining members **700** are arranged at a density of 50 mm^2 .

The gap retaining members **700** of this embodiment provides the same advantages as the gap retaining members **220** of the tenth embodiment.

Embodiment 14

This embodiment is directed to modification to the arrangement of the gap retaining members and is the same as the tenth embodiment in the other points. FIG. 23 is a top view of an opposed substrate according to this embodiment. The members in FIG. 23 that are given the same reference numerals as in FIGS. 21A and 21B are the same as the corresponding members in FIGS. 21A and 21B.

In the tenth embodiment, the gap retaining members **220** are arranged randomly on the entire opposed substrate **200** as

23

shown in FIG. 21A. In contrast, in this embodiment, as shown in FIG. 23, gap retaining members 710 are arranged randomly in the pixel-confronting area 202 so as not to be formed in the driver-circuit-confronting areas 203 and 204. The shape of the gap retaining members 710 are the same as in the tenth embodiment, that is, they are shaped like a cylinder of 2.0 μm in diameter and 3.2 μm in height. The gap retaining members 710 are arranged at a density of 60 mm^{-2} .

Since the TFTs in the driver circuit areas 103 and 104 have a higher integration density than the TFTs in the pixel area 102, they are prone to be broken by stress that is imposed by the spacers. In this embodiment, since no gap retaining members 710 are formed in the driver-circuit-confronting areas 203 and 204, when the TFT substrate 100 and the opposed substrate 200 are bonded together the gap retaining members 710 do not exert stress on the driver circuits formed in the TFT substrate 100. Therefore, the yield of the driver circuits can be increased.

In FIG. 23, there are gap retaining members 710 that partially exist outside the pixel-confronting area 202. This embodiment only requires that the gap retaining members 710 can retain the gap in the pixel area 202, and that the gap retaining members 710 not be formed in the driver-circuit-confronting areas 203 and 204.

In the tenth and thirteenth embodiments, the gap retaining members 220 are formed in the pixel-confronting area 202 and disclination is prone to occur around the gap retaining members 220. Therefore, where the gap retaining members 220 are formed in the pixel-confronting area 202, to prevent display defects, it is preferable that the gap retaining members 220 be formed in regions that do not contribute to the display, for instance, regions where a black matrix or bus lines of the TFT substrate 100 are formed.

Embodiment 15

This embodiment is directed to modification to the arrangement of the gap retaining members and is the same as the tenth embodiment in the other points. FIGS. 24A and 24B are top views of opposed substrates according to this embodiment. The members in FIGS. 24A and 24B that are given the same reference numerals as in FIGS. 21A and 21B are the same as the corresponding members in FIGS. 21A and 21B.

While in the fourteenth embodiment the gap retaining members 710 are not formed in the driver-circuit-confronting areas 203 and 204, in this embodiment gap retaining members are not formed in the driver-circuit-confronting areas 203 and 204 nor the pixel-confronting area 202.

There are a height difference between the pixel-confronting area 202 and the driver-circuit-confronting areas 203 and 204; in general, the height is greater in the pixel-confronting area 202. However, in the tenth embodiment, the height of the gap retaining members 220 from the substrate 201 to their top faces is made uniform over the entire opposed substrate 200. Therefore, as the height difference between the pixel-confronting area 202 and the driver-circuit-confronting areas 203 and 204 increases, it becomes more difficult to compensate for the height difference and a cell gap variation becomes more prone to occur in bonding the substrates 100 and 200 together.

In the tenth and thirteenth embodiments, since the gap retaining members 220 or 700 are formed on the entire opposed substrate 200, there is a possibility that gap retaining members 220 or 700 damage the TFTs that are formed in the pixel area 202 and the driver circuit areas 103 and 104.

This embodiment is directed to a method of forming gap retaining members that solves the above problems, that is,

24

prevents a cell gap variation as well as prevents the TFTs that are formed in the TFT substrate 100 from being damaged.

FIGS. 24A and 24B are top views of opposed substrates 200 according to this embodiment. The opposed substrates 200 are produced in the same manner as in the tenth embodiment.

In this embodiment, as shown in FIG. 24A, cylindrical gap retaining members 720 are arranged so as to surround the pixel-confronting area 202. Specifically, the gap retaining members 720 are shaped like a cylinder of 10 μm in diameter and 3.2 μm in height. The gap retaining members 720 are located so as to be separated by 70 μm from the end of the pixel area 102 of the TFT substrate 100 in the state that the substrates 100 and 200 are bonded together. The interval between the gap retaining members 720 are set at 30 μm . The arrangement density of the gap retaining members 720 in the vicinity of a liquid crystal injection inlet 206 is made lower than in the other portions to facilitate the flow of a liquid crystal.

The intervals between the pixel-confronting area 202 and the driver-circuit-confronting areas 203 and 204 are hundreds of micrometers, which is sufficiently longer than the diameter of the gap retaining members 720. Therefore, the manufacturing margin of the positions of the gap retaining members 720 is as large as about $\pm 10 \mu\text{m}$. On the other hand, the accuracy of the height of the gap retaining members 720 is an important factor in determining the cell gap, and is set at about $\pm 0.1 \mu\text{m}$ in this embodiment.

While in FIG. 24A the gap retaining members 720 are formed only around the pixel-confronting area 202, gap retaining members 721 and 722 may additionally be formed around the driver-circuit-confronting areas 203 and 204 as shown in FIG. 24B.

In this embodiment, the gap retaining members 720 are formed in the regions that do not overlap with the pixel area 102 nor the driver circuit areas 103 and 104 when the substrates 100 and 200 are bonded together. Therefore, the cell gap is determined by only the height of the gap retaining members 720 (and 721 and 722). Therefore, even if there is a height difference between the pixel area 102 and the driver circuit areas 103 and 104, the cell gap can be made uniform over the entire substrate or among different substrates.

Further, since the gap retaining members 720 do not press the pixel TFTs nor the driver circuit TFTs formed in the TFT substrate 100, the yield can be increased.

Although in this embodiment the gap retaining members 720 (and 721 and 722) are formed around the pixel-confronting area 202 (and the driver-circuit-confronting areas 203 and 204), the positions of the gap retaining members are not limited to those shown in FIGS. 24A and 24B. The gap retaining members may be formed anywhere except the pixel-confronting area 202 and the driver-circuit-confronting areas 203 and 204 as long as they can retain the cell gap.

Embodiment 16

This embodiment is a modification of the fifteenth embodiment. FIGS. 25A and 25B are a top view and an enlarged perspective view, respectively, of an opposed substrate according to this embodiment. The manufacturing method of the opposed substrate is the same as in the tenth embodiment, and members in FIGS. 25A and 25B that are given the same reference numerals as in FIGS. 21A and 21B are the same as the corresponding members in FIGS. 21A and 21B.

In this embodiment, a gap retaining member 730 is approximately shaped like a wall that erects from the substrate 201. The gap retaining member 730 surrounds a pixel-

25

confronting area **202** and is connected to the liquid crystal injection inlet **206**. The gap retaining member **730** is 20 μm in width and 3.2 μm in height and is separated from the end of the pixel-confronting area **202** by 50 μm .

In this embodiment, the gap retaining member **730** is formed in an area that does not overlap with any of the pixel area **102** and the driver circuit areas **103** and **104** when the substrates **100** and **200** are bonded together. Since the cell gap is determined by only the height of the gap retaining member **730**, the cell gap can be made uniform over the entire substrate or among different substrates even if there is a height difference between the pixel area **102** and the driver circuit areas **103** and **104**.

Since the gap retaining member **730** does not press the TFTs formed in the TFT substrate **100**, the yield can be increased.

Further, as shown in FIG. **26**, this embodiment has a feature that the gap retaining member **730** has a structure that enables sealing of a liquid crystal in the pixel area **102**. Because of the presence of the gap retaining member **730**, a liquid crystal is injected into only the space corresponding to the pixel area **102** and is not injected into the spaces corresponding to the driver circuit areas **103** and **104**. Therefore, the load capacitances of the driver circuits can be reduced and hence crosstalk can be made less prone to occur.

While in FIG. **25A** the gap retaining member **730** is formed only around the pixel-confronting area **202**, as shown in FIG. **26** wall-shaped gap retaining members **731** and **732** similar to the gap retaining member **730** may additionally be formed around the driver-circuit-confronting areas **203** and **204**.

In this embodiment, it is sufficient that the gap retaining member **730** has a structure that enables sealing of a liquid crystal in the pixel area **102**, and hence the shape of the gap retaining members **731** and **732** is not limited to the wall-like shape and may be a cylindrical shape, an elliptical pole shape, a rectangular prism shape, or a polygonal prism shape. The positions of the gap retaining members **731** and **732** are not limited to the neighborhood of the driver-circuit-confronting areas **203** and **204**; they may be formed anywhere except the pixel-confronting area **202** and the peripheral-circuit-confronting areas **203** and **204** as long as they can retain the cell gap.

Embodiment 17

This embodiment is a modification of the sixteenth embodiment. This embodiment has a feature that gap retaining members are configured so that a liquid crystal is injected into the space corresponding to the pixel area **102** but is not injected into the spaces corresponding to the driver circuit areas **103** and **104**. FIG. **27** is a top view of an opposed substrate according to this embodiment. The manufacturing method of the opposed substrate is the same as in the tenth embodiment, and members in FIG. **27** that are given the same reference numerals as in FIGS. **21A** and **21B** are the same as the corresponding members in FIGS. **21A** and **21B**.

In this embodiment, as shown in FIG. **27**, the driver-circuit-confronting areas **203** and **204** are surrounded by a wall-shaped gap retaining member **741** so that a liquid crystal **300** does not enter the driver circuit areas **103** and **104** in the state that the substrates **100** and **200** are bonded together.

In this embodiment, as shown in FIG. **27**, the gap retaining member **714** is approximately shaped like a wall that erects from the substrate **201**. The gap retaining member **714** is 20 μm in width and 3.2 μm in height and is separated from the end of the driver-circuit-confronting areas **203** and **204** by 50 μm .

26

In this embodiment, rectangular-prism-like gap retaining member **740** are arranged so as to surround the pixel-confronting area **202** so that a liquid crystal can flow into the pixel area **102**. Each gap retaining member **740** is shaped like a rectangular prism in which the long side length is 30 μm , the short side length is 15 μm , and the height is 3.2 μm . The gap retaining members **740** are separated from the end of the pixel-confronting area **202** by 70 μm , and the interval between adjacent ones of the gap retaining members **740** is set at 30 μm . The arrangement density of part of the gap retaining members **740** in the vicinity of the liquid crystal injection inlet **206** is made lower than in the other portions to facilitate injection of a liquid crystal.

Although the tenth to seventeenth embodiments are directed to the case where a liquid crystal material is used as a display medium, the invention can also be applied to a case of using a mixed layer of a liquid crystal and a polymer, that is, the invention can also be applied to a polymer dispersion type liquid crystal display device.

Embodiment 18

This embodiment is directed to a case where the invention is applied to an STN reflection type liquid crystal panel. FIG. **28** is a schematic perspective view of a liquid crystal panel according to this embodiment. As shown in FIG. **28**, striped reflective electrodes **1110**, an alignment film **1120**, and gap retaining members **1300** are provided on a glass substrate **1000**. To retain the cell gap, the gap retaining members **1300** are arranged uniformly over the entire substrate **1000**. On the other hand, transparent electrodes **1210** and an alignment film **1220** are provided on a glass substrate **1200**. The glass substrates **1000** and **1200** are opposed to each other with the alignment films **1120** and **1220** located inside. The interval between the glass substrates **1000** and **1200** is secured by the gap retaining members **1300**, and an STN liquid crystal is sealed in the space between the substrates **1000** and **1200**.

A manufacturing method of the reflection-type liquid crystal panel according to this embodiment will be described with reference to FIGS. **29A-29F** to **31**. First, to form reflective electrodes **1110**, a metal film is formed on a glass substrate **1000**. In this embodiment, a 400-nm-thick aluminum film is formed by sputtering and then patterned into striped reflective electrodes **1110** (see FIG. **29A**). The reflective electrodes **1110** extend in the direction perpendicular to the paper surface of FIGS. **29A-29F**.

Then, to form gap retaining members **1130**, a coating **910** is formed by using an insulative material. In this embodiment, a 3.5- μm -thick photosensitive polyimide film **910** is formed by spin coating and then left at the room temperature for 30 minutes (leveling) to uniformize the thickness of the photosensitive polyimide film **910** over the TFT substrate. Thereafter, the glass substrate **1000** on which the photosensitive polyimide film **910** is formed is pre-baked at 120° C. for 3 minutes (see FIG. **29B**).

Then, the top surface of the photosensitive polyimide film **910** is planarized by chemical mechanical polishing (CMP). In this embodiment, slurry that is used in the CMP step is a colloid-like one in which a silica (SiO_2) fine powder is dispersed in an acid solution. As for the CMP conditions, each of the substrate and an abrasive cloth is rotated at 50 rpm and the polishing time is set at 3 minutes. In this CMP step, the top 1- μm layer of the photosensitive polyimide film **910** is removed by polishing, whereby a polished photosensitive polyimide film **920** has a height of 2.6 μm as measured from the surfaces of the reflective electrodes **1110**.

Although in this embodiment the slurry that is used in the CMP step is one in which a silica fine powder is dispersed in an acid solution, slurry obtained by dispersing aluminum oxide (Al_2O_3), cerium oxide (CeO_2), or the like in an acid solution may also be used. It is desirable that the slurry be changed in accordance with the material that is subjected to CMP. Further, the optimum rotation speed of each of the substrate and an abrasive cloth and processing time may be determined in accordance with a material to be subjected to CMP and the polishing removal thickness.

The cell gap (interval between the substrates) is determined by the thickness of the photosensitive polyimide film 920 that has been obtained by CMP. Therefore, the thickness of the photosensitive polyimide film 910 before being subjected to CMP may be set properly in accordance with the desired cell gap and the polishing removal thickness.

Even if the thickness of the photosensitive polyimide film 910 before being subjected to CMP varies from one substrate to another, the thickness of the photosensitive polyimide film 920 can be made uniform among different substrates by adjusting the polishing removal thickness.

Then, to pattern the photosensitive polyimide film 920 that has been obtained by CMP, the photosensitive polyimide film 920 is covered with a photomask 930 as shown in FIG. 29D. Although in FIG. 29D the photomask 930 is drawn as if it were divided, actually it is an integral layer having circular openings.

Ultraviolet light is applied in the state of FIG. 29D. Subsequently, development is performed and then post-baking is performed at 280° C. for one hour. In this manner, as shown in FIG. 29E, portions of the photosensitive polyimide film 920 that have been illuminated with ultraviolet light remain and cylindrical gap retaining members 1300 are formed.

Then, a polyimide-type vertical alignment film 1120 is formed on the substrate 1000 by one of spin coating, flexography, and screen printing. In this embodiment, to reduce physical impact on the gap retaining members 1300, the alignment film 1120 is formed by spin coating. Thereafter, the polyimide film 1120 is cured by baking it by feeding a hot wind of 180° C. Settings are made so that after the curing the alignment film has a thickness of 100 nm (see FIG. 29F).

FIG. 32 is a top view of the substrate 100 in the state of FIG. 29F. In this embodiment, the gap retaining members 1300 are shaped like a cylinder with a circular cross-section in which the bottom face diameter is 3 μm and the height as measured from the surface of the alignment film 1120 is about 2.5 μm . The gap retaining members 1300 are arranged regularly at a density of 50 mm^{-2} . The arrangement density of the gap retaining members 1300 may be set at 40-160 mm^{-2} , which is approximately equal to the dispersion density of conventional spacers, in accordance with the strength of the gap retaining members 1300.

In this embodiment, the gap retaining members 1300 are formed at positions on the reflective electrodes 1110 where the top faces 1300a of the respective gap retaining members 1300 confront the transparent electrodes 1210 in the state that the glass substrates 1000 and 1200 are opposed to each other.

The surface (to contact a liquid crystal material) of each glass substrate 1000 or 1200 has periodic asperities due to the multilayered structure including the striped electrodes 1110 or 1210. In the state that the glass substrates 1000 and 1200 are opposed to each other, the cell gap varies periodically due to those asperities. In view of this, in this embodiment, all the gap retaining members 1300 are formed at positions having almost the same cell gap value and the heights of the respec-

tive gap retaining members 1300 are approximately equalized by CMP. In this manner, the cell gap is made uniform over the entire substrate.

In FIG. 29F, the alignment film 1120 is drawn so as not to cover the side faces and the top faces 1300a of the gap retaining members 1300. This is because in this embodiment the alignment film 1120 may not assume a complete film on the side faces and the top faces 1300a of the gap retaining members 1300 that are erected as shown in FIG. 29F, because the polyimide film is formed by spin coating and the polyimide film (thickness: tens to hundreds of nanometers) is much thinner than the gap retaining members 1300 (height: several micrometers). Thus, FIG. 29F shows only the alignment film 1120 that is formed on the horizontal surface and assumes a complete film.

Next, a process to be executed on the glass substrate 1200 will be described with reference to FIGS. 30A and 30B. Color filters 1230 are formed on the glass substrate 1200, and then a protective film 1240 made of an acrylic resin or an epoxy resin is formed on the color filters 1230. In this embodiment, a 1- μm -thick acrylic resin is formed as the protective film 1240 (see FIG. 30A). In FIG. 28, the color filters 1230 and the protective film 1240 are omitted.

Then, transparent conductive films of ITO (indium tin oxide), SnO_2 (tin oxide), or the like are formed as transparent electrodes 1210. In this embodiment, an ITO film is formed by sputtering and then patterned into striped transparent electrodes 1210. Thereafter, a polyimide-type vertical alignment film 1220 is formed by the same method as the alignment film 1120 is formed (see FIG. 30B).

Then, rubbing is performed on each of the alignment films 1120 and 1220. In this embodiment, each of the alignment films 1120 and 1220 is rubbed with a roller on which a buff cloth (fiber of rayon or nylon) having hair lengths of 2-3 mm is wound. The rubbing direction is set parallel with one of the diagonals of the glass substrate 1000 or 1200. The directions of rubbing on the alignment films 1120 and 1220 are set so as to be perpendicular to each other in the state that the glass substrates 1000 and 1200 are opposed to each other.

As for the glass substrate 1000, the gap retaining members 1300 project from the alignment film 1120. Therefore, there is a possibility that the gap retaining members 1300 are damaged or peeled. This problem can be avoided by properly adjusting the kind and the hair planting density of a buff cloth, the rotation speed of the roller, the number of rubbing operations, and other factors.

Then, a sealing agent for bonding the glass substrates 1000 and 1200 together is applied to one of the glass substrates 1000 and 1200. In this embodiment, a sealing agent made of an ultraviolet curable resin is applied to a peripheral portion of the glass substrate 1200 so as to leave a liquid crystal injection inlet. Thereafter, the glass substrates 1000 and 1200 are opposed to each other and pressed against each other so that the cell gap becomes equal to the height of the gap retaining members 1300. The sealing agent is cured in this state by illuminating it with ultraviolet light.

Then, a liquid crystal is injected through the liquid crystal injection inlet. Subsequently, a sealing agent is applied to the liquid crystal injection inlet and then cured by illuminating it with ultraviolet light. The liquid crystal is thus completely sealed in the cell. Then, a phase plate 1510, a polarizer 1520, and a forward scattering plate 1530 are provided on the back surface of the glass substrate 1200. As a result of the execution of the above steps, a full-color STN liquid crystal panel shown in FIG. 31 is completed.

FIG. 31 is a sectional view of the liquid crystal panel. In FIG. 31, the striped reflective electrodes 1110 extend in the

direction parallel with the paper surface and the striped transparent electrodes **1210** extend in the direction perpendicular to the paper surface.

In this embodiment, the reason why the gap retaining members **1300** are provided on the glass substrate **1000** side is that the color filters **1230** are provided on the glass substrate **1200** side. The gap retaining members **1300** are formed through chemical mechanical polishing, which involves application of physical force. In this embodiment, to minimize the rate of occurrence of defective products, the gap retaining members **1300** are provided on the glass substrate **1000** side where the color filters **1230** are not provided.

This embodiment is directed to the full-color panel. On the other hand, the color filters **1230** are not required in black-and-white display panels, three-panel-type projection display panels, etc. In such cases, the gap retaining members **1300** may be provided on either the glass substrate **1000** or **1200**. That is, the substrate to be provided with the gap retaining members **1300** may be selected so that the rate of occurrence of defective products is reduced in the manufacturing process.

Although this embodiment is directed to the reflection-type liquid crystal panel, the gap retaining members **1300** of this embodiment can be used in transmission-type panels.

Although in this embodiment the gap retaining members **1300** are arranged regularly, they may be arranged randomly, for example, as shown in FIG. **33**. Even in such a case the gap retaining members **1300** are not gathered at a single location unlike the conventional spacers, because their positions are determined by the photomask **930**.

Although in this embodiment the bottom face of each gap retaining member **1300** is a circle, it may be an ellipse or may have a streamlined shape or a polygonal shape such as a triangle or a rectangle. The gap retaining members **1300** may assume any shape as long as they can control the cell gap and provide sufficient strength. Although in this embodiment all the gap retaining members **1300** have the same shape, gap retaining members **1300** having plural kinds of shapes may be formed on the same substrate. In this embodiment, since the shape of the bottom face of each gap retaining member **1300** is determined by the photomask **930**, it can be changed easily with high accuracy.

Although in this embodiment the arrangement density of the gap retaining members **1300** is set uniform, it may be increased in a particular region, for instance, to increase the strength there. In this embodiment, since the arrangement density of each gap retaining member is determined by the photomask **930**, it can be changed easily with high accuracy.

Embodiment 19

While the eighteenth embodiment is directed to the STN liquid crystal panel, the invention can be applied to a liquid crystal panel using a ferroelectric liquid crystal. In this embodiment, in the reflection-type panel shown in FIG. **28**, the gap retaining members **1300** are formed so as to assume a cylinder in which the height as measured from the reflective electrodes **1110** is $1.5\text{ }\mu\text{m}$ and the bottom face is a circle of $2\text{ }\mu\text{m}$ in diameter. The manufacturing method, the positions of formation, and the arrangement density of the gap retaining members **1300** are the same as in the eighteenth embodiment.

The cell gap can be determined as desired by the gap retaining members **1300** and their positions of formation can be controlled. Further, the faces confronting the other substrate is made flat. Therefore, by virtue of the use of the gap retaining members **1300**, the cell gap that is smaller than the spiral pitch of a ferroelectric liquid crystal can be made uniform with high accuracy over the entire substrate.

Ferroelectric liquid crystals have features that no crosstalk occurs, the viewing angle is wide, and the switching speed is three orders or more higher than that of STN liquid crystals, and hence can realize high-resolution, large-screen displays even with the passive matrix driving scheme. Therefore, the use of the gap retaining members **1300** of this embodiment makes it possible to provide, at a low cost, a high-resolution, large-screen ferroelectric liquid crystal panel.

Further, an antiferroelectric liquid crystal can be used instead of a ferroelectric liquid crystal. Also in the case of using an antiferroelectric liquid crystal, the cell gap needs to be made less than $2\text{ }\mu\text{m}$ so that the spiral structure of the liquid crystal disappear. By using the gap retaining members **1300** of this embodiment, the cell gap can be made less than $1.5\text{ }\mu\text{m}$.

As described above, according to the invention, a semiconductor display device having a uniform cell thickness profile can be obtained. Further, according to the invention, since a desired cell gap can be secured without scattering grainy spacers, there can be prevented an event that unnecessary force is exerted on the driver circuit TFTs in bonding the substrates together, which leads to an increase in the yield of products.

According to another aspect of the invention, the accuracy of the cell gap can be made high because the top faces of the gap retaining members are planarized and the planarization is performed by chemical mechanical polishing. This makes it possible to provide an electro-optical device having a uniform cell thickness profile. Further, according to this aspect of the invention, since a desired cell gap can be secured without scattering grainy spacers, there can be prevented an event that unnecessary force is exerted on the driver circuit TFTs in bonding the substrates together, which leads to an increase in the yield of products.

According to a further aspect of the invention, since the gap retaining members are provided on the opposed substrate, influences (etchant-related influences, mechanical impact, etc.) of the formation of the gap retaining members do not affect the elements formed in the TFT substrate, which leads to an increase in yield.

Further, providing the gap retaining members on the opposed substrate makes it easier to select a material of the gap retaining members than providing those on the TFT substrates in which the switching elements such as TFTs are provided. Further, by providing the gap retaining members on the opposed substrate, materials such as an etchant and means that are necessary to form the gap retaining members can be selected from wider ranges.

What is claimed is:

1. A display device comprising:

- a first substrate;
- a switching element formed in a pixel area over the first substrate;
- an interlayer insulating film comprising an organic resin formed over the switching element;
- a pixel electrode formed over the interlayer insulating film and electrically connected to the switching element;
- a driver circuit comprising a thin film transistor formed over the first substrate;
- a second substrate opposed to the first substrate;
- a liquid crystal layer disposed between the first substrate and the second substrate;
- a plurality of first gap retaining members comprising a photosensitive resin material formed in the pixel area over the second substrate;
- a plurality of second gap retaining members comprising a photosensitive resin material formed directly over the driver circuit over the second substrate,

31

wherein an interval between the plurality of first gap retaining members is different from an interval between the plurality of second gap retaining members.

2. The display device according to claim 1 wherein said switching element comprises an inverted staggered thin film transistor.

3. The display device according to claim 1 wherein each of said plurality of first gap retaining members and said plurality of second gap retaining members comprises an ultraviolet curable resin.

4. The display device according to claim 1 wherein each of said plurality of first gap retaining members and said plurality of second gap retaining members comprises a photocurable polyimide.

5. The display device according to claim 1 wherein said plurality of first gap retaining members each has a streamlined shape.

6. The display device according to claim 1 wherein said plurality of first gap retaining members each has an ellipse shape.

7. The display device according to claim 1 wherein said plurality of first gap retaining members each has a polygon shape.

8. The display device according to claim 1 wherein said plurality of first gap retaining members and said plurality of second gap retaining members are arranged at a combined density of 40-160/mm².

9. The display device according to claim 1 further comprising an insulating film comprising silicon nitride between the switching element and the interlayer insulating film.

10. A display device comprising:

a first substrate;

a switching element formed in a pixel area over the first substrate;

an interlayer insulating film formed over the switching element;

a pixel electrode formed over the interlayer insulating film and electrically connected to the switching element;

a driver circuit comprising a thin film transistor formed over the first substrate;

a second substrate opposed to the first substrate;

a liquid crystal layer disposed between the first substrate and the second substrate;

a plurality of first gap retaining members comprising a photosensitive resin material formed in the pixel area over the second substrate;

a plurality of second gap retaining members comprising a photosensitive resin material formed directly over the driver circuit over the second substrate,

wherein an interval between the plurality of first gap retaining members is different from an interval between the plurality of second gap retaining members.

11. The display device according to claim 10 wherein said switching element comprises an inverted staggered thin film transistor.

12. The display device according to claim 10 wherein each of said plurality of first gap retaining members and said plurality of second gap retaining members comprises an ultraviolet curable resin.

13. The display device according to claim 10 wherein each of said plurality of first gap retaining members and said plurality of second gap retaining members comprises a photocurable polyimide.

32

14. The display device according to claim 10 wherein said plurality of first gap retaining members each has a streamlined shape.

15. The display device according to claim 10 wherein said plurality of first gap retaining members each has an ellipse shape.

16. The display device according to claim 10 wherein said plurality of first gap retaining members each has a polygon shape.

17. The display device according to claim 10 wherein said plurality of first gap retaining members and said plurality of second gap retaining members are arranged at a combined density of 40-160/mm².

18. The display device according to claim 10 further comprising an insulating film comprising silicon nitride between the switching element and the interlayer insulating film.

19. A display device comprising:

a first substrate;

a switching element in a pixel area over the first substrate;

an interlayer insulating film formed over the switching element;

a pixel electrode formed over the interlayer insulating film and electrically connected to the switching element;

a driver circuit comprising a thin film transistor formed over the first substrate;

a second substrate opposed to the first substrate;

a liquid crystal layer disposed between the first substrate and the second substrate;

a plurality of gap retaining members comprising a photosensitive resin material formed in the pixel area and directly over the driver circuit between the first substrate and the second substrate,

wherein a shape of at least one of the plurality of gap retaining members and a shape of at least another one of the plurality of gap retaining members are different, and wherein an interval between the gap retaining members in the pixel area is different from an interval between the gap retaining members directly over the driver circuit.

20. The display device according to claim 19 wherein said switching element comprises an inverted staggered thin film transistor.

21. The display device according to claim 19 wherein each of said plurality of gap retaining members comprises an ultraviolet curable resin.

22. The display device according to claim 19 wherein each of said plurality of gap retaining members comprises a photocurable polyimide.

23. The display device according to claim 19 wherein said plurality of gap retaining members each has a streamlined shape.

24. The display device according to claim 19 wherein said plurality of gap retaining members each has an ellipse shape.

25. The display device according to claim 19 wherein said plurality of gap retaining members each has a polygon shape.

26. The display device according to claim 19 wherein said plurality of gap retaining members are arranged at a combined density of 40-160/mm².

27. The display device according to claim 19 further comprising an insulating film comprising silicon nitride between the switching element and the interlayer insulating film.

28. The display device according to claim 19 wherein the interlayer insulating film comprises an organic resin.

* * * * *

专利名称(译)	具有由树脂制成的间隙保持构件的液晶显示装置直接形成在驱动电路上		
公开(公告)号	US8045125	公开(公告)日	2011-10-25
申请号	US10/845378	申请日	2004-05-14
[标]申请(专利权)人(译)	株式会社半导体能源研究所		
申请(专利权)人(译)	半导体能源研究所有限公司.		
当前申请(专利权)人(译)	半导体能源研究所有限公司.		
[标]发明人	HIRAKATA YOSHIHARU NISHI TAKESHI YAMAZAKI SHUNPEI		
发明人	HIRAKATA, YOSHIHARU NISHI, TAKESHI YAMAZAKI, SHUNPEI		
IPC分类号	G02F1/1339 G02F1/1362 H01L21/77 H01L21/84 H01L27/12		
CPC分类号	G02F1/13454 H01L27/1248 H01L27/1214 H01L27/12 G02F1/1339		
审查员(译)	内尔姆斯, DAVID		
优先权	1997148540 1997-05-22 JP 1997152805 1997-05-26 JP 1997167990 1997-06-09 JP 1997183024 1997-06-23 JP		
其他公开文献	US20040207789A1		
外部链接	Espacenet USPTO		

摘要(译)

在有源矩阵半导体显示装置中，像素TFT和驱动电路TFT以整体方式形成在同一基板上，单元间隙由设置在像素区域和驱动电路区域之间的间隙保持构件控制。这使得可以在整个半导体显示器件上提供均匀的单元厚度分布。此外，由于不使用传统的颗粒状间隔物，所以当TFT基板和相对基板接合在一起时，不会对驱动电路TFT施加应力。这可以防止驱动电路TFT被损坏。

