



US 20090185103A1

(19) **United States**
(12) **Patent Application Publication**
Han et al.

(10) **Pub. No.: US 2009/0185103 A1**
(43) **Pub. Date: Jul. 23, 2009**

(54) **TWO-WAY BACKLIGHT ASSEMBLY AND TWO-WAY LIQUID CRYSTAL DISPLAY APPARATUS HAVING THE SAME**

Continuation of application No. 10/679,400, filed on Oct. 7, 2003, now Pat. No. 7,001,059.

(76) Inventors: **Byung-Woong Han**, Incheon-si (KR); **Sang-Hee Lee**, Yongin-si (KR); **Jae-Kwang Kim**, Seoul (KR); **Young-Bee Chu**, Paldal-gu (KR); **Kyu-Seok Kim**, Giheung-eup (KR)

(30) **Foreign Application Priority Data**

Jun. 26, 2003 (KR) 2003-42007

Publication Classification

(51) **Int. Cl.**
G02F 1/13357 (2006.01)
G09F 13/00 (2006.01)
G02F 1/1333 (2006.01)
(52) **U.S. Cl.** **349/58; 362/97.1; 349/65**

Correspondence Address:
F. CHAU & ASSOCIATES, LLC
130 WOODBURY ROAD
WOODBURY, NY 11797 (US)

(57) **ABSTRACT**

In a two-way backlight assembly and a two-way LCD apparatus, the two-way backlight assembly provides light emitted from one light source to a first direction where a main LCD panel is placed and to a second direction where a sub LCD panel is placed. Also, a sub mold part for receiving the sub LCD panel comprises a black-colored material so as to prevent reflection of the light. Accordingly, thickness and power consumption of the backlight assembly may be reduced and display quality may be also improved by preventing leakage of the light at ends of the sub LCD panel.

(21) Appl. No.: **12/411,440**
(22) Filed: **Mar. 26, 2009**

Related U.S. Application Data

(63) Continuation of application No. 11/926,651, filed on Oct. 29, 2007, now Pat. No. 7,527,417, which is a continuation of application No. 11/326,197, filed on Jan. 5, 2006, now Pat. No. 7,290,918, which is a con-




FIG. 1




FIG. 2




FIG. 3




FIG. 4




FIG. 5




FIG. 6




FIG. 7




FIG. 8




FIG. 9




FIG. 10





FIG. 11



**TWO-WAY BACKLIGHT ASSEMBLY AND
TWO-WAY LIQUID CRYSTAL DISPLAY
APPARATUS HAVING THE SAME**

CROSS-REFERENCE TO RELATED
APPLICATION

[0001] This application is a continuation of U.S. application Ser. No. 11/926,651 filed on Oct. 29, 2007, which is a continuation of U.S. application Ser. No. 11/326,197 filed on Jan. 5, 2006 now U.S. Pat. No. 7,290,918, which is a continuation of U.S. application Ser. No. 10/679,400 filed on Oct. 7, 2003 now U.S. Pat. No. 7,001,059, which claims priority under 35 U.S.C. § 119 to Korean Patent Application No. 2003-42007 filed on Jun. 26, 2003, the disclosures of which are incorporated by reference herein in their entirety.

BACKGROUND OF THE INVENTION

[0002] 1. Field of the Invention

[0003] The present invention relates to a two-way backlight assembly and a two-way liquid crystal display apparatus (LCD) having the same, and more particularly to a two-way backlight assembly capable of displaying an image information in two directions opposite to each other and a two-way LCD apparatus having the same.

[0004] 2. Description of the Related Art

[0005] In general, an LCD apparatus, generally, displays an image using liquid crystal having a light transmittance varied in accordance with an intensity of an electric field.

[0006] An LCD apparatus having various characteristics, for example, such as a small size, low power consumption, a high resolution, etc., is widely applied to electronic instruments, for example, such as a notebook computer, a monitor, a mobile communication system and so on.

[0007] An LCD apparatus, usually, displays an image in one-way. However, a related technology to an LCD apparatus capable of displaying an image in two-way has been developed.

[0008] The LCD apparatus capable of displaying the image in two-way, in general, includes a main LCD panel for displaying a main image, a main backlight assembly for supplying light to the main LCD panel, a sub LCD panel for displaying a sub image and a sub backlight assembly for supplying light to the sub LCD panel.

[0009] Each of the main and sub backlight assemblies includes a light source for emitting the light, a light guide plate for changing a path of the light, a reflection plate for reflecting the light, and a receiving container for receiving the light source, light guide plate and reflection plate.

[0010] The main and sub backlight assemblies are manufactured as a module separated from each other and coupled to each other while the main and sub backlight assemblies are applied to the LCD apparatus so as to supply the light to the main and sub LCD panels, respectively.

[0011] However, when the main and sub backlight assemblies manufactured as the separated module are applied to the LCD apparatus, an entire thickness of the LCD apparatus may increase. Also, since the LCD apparatus has two light sources, two reflection plates and two receiving containers applied to

the main and sub backlight assemblies, a power consumption and a cost of manufacture of the LCD apparatus may also increase.

BRIEF SUMMARY OF THE INVENTION

[0012] The present invention provides a two-way backlight assembly capable of supplying light in two directions different from each other.

[0013] The present invention provides a two-way LCD apparatus having the above two-way backlight assembly.

[0014] In one aspect of the invention, a two-way backlight assembly includes a light source generating light, a main mold part receiving the light source and a light guide plate, a light-amount control sheet, a receiving container and sub mold part.

[0015] The light guide plate provides the light from the light source to a first exit surface and a second exit surface facing the first exit surface. The light-amount control sheet is disposed on the second exit surface so as to partially reflect or transmit the light from the second exit surface.

[0016] The receiving container is combined with the main mold part so as to fix the light-amount control sheet to the main mold part, and it has an opening through which the light is transmitted.

[0017] The sub mold part has a size equal to a size of the opening of the receiving container and is coupled to a rear surface of the receiving container. The sub mold part comprises a black-colored and/or a flat material.

[0018] The two-way backlight assembly further includes a first optical sheet disposed on the first exit surface so as to improve brightness of the light and a second optical sheet disposed on the opening and fixed by means of the sub mold part.

[0019] In another aspect of the invention, a two-way LCD apparatus includes a main backlight assembly, a sub backlight assembly, a main LCD panel assembly and a sub LCD panel assembly.

[0020] The main backlight assembly includes a light source generating light, a light guide part guiding the light from the light source to a first direction and a second direction opposite to the first direction, and a main mold part receiving the light source and the light guide part;

[0021] The sub backlight assembly is disposed in the second direction. The sub backlight assembly includes a first optical sheet improving optical properties of the light exited to the second direction and a sub mold part fixing the first optical sheet to the main mold part;

[0022] The main LCD panel assembly is disposed on the main backlight assembly to display a main image using the light provided from the main backlight assembly.

[0023] The sub LCD panel assembly is disposed on the sub backlight assembly to display a sub image using the light provided from the sub backlight assembly.

[0024] According to the two-way backlight assembly and the two-way LCD apparatus having same, the two-way LCD apparatus may provide the light to two directions different from each other using only one light source, thereby reducing thickness and power consumption of the backlight assembly.

[0025] Also, the LCD apparatus may prevent leakage of the light through the ends of the sub mold part because the sub mold part may comprise the black-colored or/and flat material.

BRIEF DESCRIPTION OF THE DRAWINGS

[0026] The above and other advantages of the present invention will become readily apparent by reference to the following detailed description when considered in conjunction with the accompanying drawings wherein:

[0027] FIG. 1 is a schematic view showing a two-way backlight assembly according to an exemplary embodiment of the present invention;

[0028] FIG. 2 is an exploded perspective view showing the two-way backlight assembly shown in FIG. 1;

[0029] FIG. 3 is a perspective view showing the main mold part shown in FIG. 2;

[0030] FIG. 4 is a perspective view showing the sub mold part combined with the receiving container shown in FIG. 2;

[0031] FIG. 5 is a perspective view showing the sub mold part shown in FIG. 5;

[0032] FIG. 6 is a schematic view illustrating a light-leaking phenomenon of the two-way backlight assembly shown in FIG. 2;

[0033] FIG. 7 is a cross-sectional view taken along the line D-D' of FIG. 6;

[0034] FIG. 8 is a schematic view showing a two-way backlight assembly according to another exemplary embodiment of the present invention;

[0035] FIG. 9 is an exploded perspective view showing the two-way backlight assembly shown in FIG. 8;

[0036] FIG. 10 is an exploded perspective view showing an LCD apparatus according to an exemplary embodiment of the present invention; and

[0037] FIG. 11 is a perspective view showing the main LCD panel assembly shown in FIG. 10.

DETAILED DESCRIPTION OF THE INVENTION

[0038] FIG. 1 is a schematic view showing a two-way backlight assembly according to an exemplary embodiment of the present invention.

[0039] Referring to FIG. 1, a two-way backlight assembly 100 includes a light source 110 for generating light, a light guide plate 120 for changing a path of the light, a reflection/transmission sheet 130, a first optical sheet 140 and a second optical sheet 150.

[0040] The light guide plate 120 includes a first exit surface 122 and a second exit surface 124 facing the first exit surface 122. The light guide plate 120 receives the light emitted from the light source 110 and outputs the received light through the first and second exit surfaces 122 and 124. That is, the light guide plate 120 changes the light, for example, such as a point light source, a line light source, etc., emitted from the light source into a surface light source to exit the changed light through the first and second exit surfaces 122 and 124.

[0041] The reflection/transmission sheet 130 is disposed on the second exit surface 124 of the light guide plate 120. The reflection/transmission sheet 130 reflects a portion of the light exited through the second exit surface 124 to the first exit surface 122 and transmits a remaining portion of the light exited through the second exit surface 124.

[0042] The reflection/transmission sheet 130 may have a sheet shape formed by foaming polyethylene terephthalate

resin (PET) or a plate shape. By adjusting a thickness of the reflection/transmission sheet 130, an amount of the reflected light from the reflection/transmission sheet 130 to the first exit surface 122 of the light guide plate 120 and an amount of the transmitted light through the reflection/transmission sheet 130 may be adjusted.

[0043] In this exemplary embodiment, the reflection/transmission sheet 130 is formed by foaming the PET. However, the reflection/transmission sheet 130 may be formed using any material that partially reflects and transmits the light.

[0044] A first optical sheet 140 is disposed on the first exit surface 122 of the light guide plate 120 and a second optical sheet 150 is disposed on the reflection/transmission sheet 130. In order to improve optical properties of the light exited through the first exit surface 122 of the light guide plate 120, the first optical sheet 140 includes a diffusion sheet for diffusing the light from the first exit surface 122 and at least one prism sheet. The second optical sheet 150 also includes a diffusion sheet and at least one prism sheet so as to improve brightness of the light exited through the reflection/transmission sheet 130.

[0045] In this exemplary embodiment, the second optical sheet 150 has a smaller size than that of the reflection/transmission sheet 130 and is placed at a center portion of the reflection/transmission sheet 130. The second optical sheet 150 may also have a same size as that of the reflection/transmission sheet 130.

[0046] As shown in FIG. 1, although the two-way backlight assembly 100 according to the exemplary embodiment of the present invention includes one light source 110, one light guide plate 120 and one reflection/transmission sheet 130, the two-way backlight assembly 100 may supply the light emitted from the light source 110 to two directions different from each other.

[0047] FIG. 2 is an exploded perspective view showing the two-way backlight assembly shown in FIG. 1.

[0048] Referring to FIG. 2, the two-way backlight assembly 100 further includes a main mold part 210 for receiving the light source 110 and light guide plate 120, a receiving container 220 for fixing the light guide plate 120 and reflection/transmission sheet 130 to the main mold part 210 and a sub mold part 230 for fixing the second optical sheet 150.

[0049] Particularly, the light guide plate 120 and reflection/transmission sheet 130 are successively received into the main mold part 210. The main mold part 210 is combined with the receiving container 220, thereby fixing the light guide plate 120 and reflection/transmission sheet 130 to the main mold part 210. Also, the main mold part 210 further provides a separate receiving space so as to receive the light source 110. When the light source 110 is received into the separate receiving space, a flexible printed circuit board (FPC) 240 is received into the separate receiving space so as to apply a driving power source to the light source 110.

[0050] For the light source 110, at least one light emitting diode (LED) or cold cathode fluorescent lamp (CCFL) may be used. The FPC 240 is electrically connected to the light source 110, and applies the driving power source externally provided to the light source 110.

[0051] The receiving container 220 is provided with an opening 224 formed at a bottom surface thereof, so that the light from the reflection/transmission sheet 130 may be provided to the second optical sheet 150 through the opening 224. The second optical sheet 150 is outwardly disposed on the opening 224 of the receiving container 220, and the sub

mold part **230** is coupled to the opening **224** so as to fix the second optical sheet **150** to the receiving container **220**.

[0052] As aforementioned above, the two-way backlight assembly **100** may supply two lights in two directions different from each other. One of the two lights is exited through the first exit surface **122** and first optical sheet **140**, and it is supplied to a first direction. Another one of the two lights is exited through the second exit surface **124**, reflection/transmission sheet **130** and opening **224** and supplied to a second direction opposite to the first direction.

[0053] FIG. 3 is a perspective view showing the main mold part shown in FIG. 2.

[0054] Referring to FIG. 3, the main mold part **210** includes first, second, third and fourth sidewalls **211**, **212**, **213** and **214** and the receiving space. The receiving space formed adjacent to the first sidewall **211** receives the light source **110** and FPC **240**. For a steady receiving of the first optical sheet **140**, the second sidewall **212** opposite to the first sidewall **211** and the third sidewall **213** connecting between the first and second sidewalls **211** and **212** have a thickness thicker than that of the first and fourth sidewalls **211** and **214**.

[0055] Hereinafter, the first sidewall **211** of the main mold part **210** will be described in detail.

[0056] The first sidewall **211** of the main mold part **210** includes a withdrawn portion **216**, a protruded portion **217**, a recessed portion **218** and a barrier wall **219**.

[0057] The withdrawn portion **216** is formed by partially cutting away an upper portion of the first sidewall **211**, and has a depth suitable for withdrawing a signal line (not shown) connected to the FPC **240**. The signal line outwardly withdrawn through the withdrawn portion **216** provides a driving power source that is externally provided to the FPC **240**, and the FPC **240** provides a predetermined power source to the light source **110**.

[0058] The protruded portion **217** is inwardly protruded from an inner wall of the first sidewall **211** toward the barrier wall **219** to support the FPC **240** disposed thereon. In this exemplary embodiment, the main mold part **210** includes a plurality of protruded portions spaced apart from each other and located at the recessed portion **218**, and the light source **110** is disposed between the protruded portions. The protruded portion **217** has a length substantially equal to that of the light source **110**.

[0059] The recessed portion **218** is formed between the protruded portions so as to receive the light source, for example, such as a light emitting diode or the like.

[0060] The barrier wall **219** is spaced apart from the protruded portion **217** in a predetermined distance, and is substantially parallel to the first sidewall **211**. The barrier wall **219** supports the FPC **240** disposed thereon, and fixes the light guide plate **120** disposed thereunder.

[0061] The main mold part **210** is combined with the receiving container **220** using engaging portions **211a**, **212a**, **213a**, **213b**, **214a** and **214b** formed with first, second, third and fourth sidewalls **211**, **212**, **213** and **214**.

[0062] FIG. 4 is a perspective view showing the sub mold part combined with the receiving container shown in FIG. 2. FIG. 5 is a perspective view showing the sub mold part shown in FIG. 4.

[0063] Referring to FIGS. 4 and 5, the receiving container **220** is provided with the opening **224** formed at the bottom surface thereof, and it is combined with the sub mold part **230** using protrusions **226** formed at ends of the opening **224**. Also, the receiving container **220** is provided with engaging

members **228** formed at four sidewalls thereof so as to be combined with the main mold part **210**. Each of the engaging members **228** is provided with an opening formed by cutting away a center portion thereof.

[0064] The openings of the engaging members **228** are engaged to the engaging portions **211a**, **212a**, **213a**, **213b**, **214a** and **214b**, respectively, so that the receiving container **220** is combined with the main mold part **210**.

[0065] The second optical sheet **150** has a size substantially equal to that of the opening **224** of the receiving container **220**, and is disposed at a position corresponding to the opening **224**. In this exemplary embodiment, the second optical sheet **150** includes the diffusion sheet and at least one prism sheet so as to improve optical properties of the light exited through the second exit surface **124** and supplied to the second direction.

[0066] Particularly, the diffusion sheet diffuses the light provided from the reflection/transmission sheet **130** and outputs through the opening **224** of the receiving container **220** such that the light exited through the opening **224** of the receiving container **220** has a uniform brightness distribution.

[0067] In this exemplary embodiment, the prism sheet is disposed on the diffusion sheet and narrows a viewing angle of the light provided from the diffusion sheet, thereby enhancing luminance of the light.

[0068] In order to fix the second optical sheet **150** to the opening of the receiving container **220**, the sub mold part **230** is combined with the receiving container **220**.

[0069] The sub mold part **230** has a rectangular-shaped frame having fifth, sixth, seventh and eighth sidewalls **231**, **233**, **235** and **237**. The fourth, sixth, seventh and eighth sidewalls **231**, **233**, **235** and **237** are provided with engaging recesses **232**, respectively to be engaged to the protrusions **226** formed at the ends of the opening **224** of the receiving container **220**.

[0070] Particularly, the engaging recesses **232** are formed by inwardly recessing outer surfaces of the fifth, sixth, seventh and eighth sidewalls **231**, **233**, **235** and **237**. Thus, when the protrusions **226** of the receiving container **220** are engaged into the engaging recesses **232** of the sub mold part **230** after the second optical sheet **150** is disposed at the position corresponding to the opening **224** of the receiving container **220**, the second optical sheet **150** and sub mold part **230** are fixed to the receiving container **220**.

[0071] The sub mold part **230** further includes a fixing member **234** inwardly formed at the fifth, sixth, seventh and eighth sidewalls **231**, **233**, **235** and **237** of the sub mold part **230**. The fixing member **234** may prevent deviation of the second optical sheet **150** therefrom, and guide a sub LCD panel assembly (not shown).

[0072] However, in case that an area through which the light is exited to the first direction is greater than an area through which the light is exited to the second direction, the light exited to the second direction may be leaked through ends of the sub mold part **230**. As a result, the backlight assembly **100** according to the exemplary embodiment of the present invention may not provide an image having uniformed brightness.

[0073] FIG. 6 is a schematic view illustrating a light-leaking phenomenon of the two-way backlight assembly shown in FIG. 2. FIG. 7 is a cross-sectional view taken along the line D-D' of FIG. 6.

[0074] Referring to FIGS. 6 and 7, the sub mold part **230** is installed on the center portion of the receiving container **220**

so as to provide the light to the second direction. Thus, the light exited through the second exit surface 124 of the light guide plate 120 is exited through the center portion on which the sub mold part 230 is disposed after transmitting the reflection/transmission sheet 130.

[0075] If the sub mold part 230 comprises a white-colored or a glossy material, the light provided to the sub mold part 230 may be reflected from an area "A" adjacent to the fifth sidewall 231 of the sub mold part 230, an area "B" adjacent to the sixth sidewall 233 and an area "C" adjacent to the seventh sidewall 235.

[0076] Accordingly, in order to prevent a reflection of the light from the ends of the sub mold part 230, the sub mold part 230 may comprise a black-colored or a flat material.

[0077] Also, the two-way backlight assembly 100 may further include a black-colored tape 240 adhered to positions on which the fifth, sixth, seventh and eighth sidewalls 231, 233, 235 and 237 are disposed.

[0078] Particularly, the black-colored tape 240 is partially disposed between the reflection/transmission sheet 130 and the fifth, sixth, seventh and eighth sidewalls 231, 233, 235 and 237 of the sub mold part 230. The black-colored tape 240 intercepts a light advancing towards the fifth, sixth, seventh and eighth sidewalls 231, 233, 235 and 237 of the sub mold part 230 among the light exited to the second direction, thereby preventing leakage of the light at the ends of the sub mold part 230.

[0079] As described above, the two-way backlight assembly 100 according to the exemplary embodiment of the present invention may supply the light emitted from the light source 110 to two directions different from each other using one light source 110 and one light guide plate 120. In addition, since the sub mold part 230 comprises the black-colored or flat material, the two-way backlight assembly 100 may prevent the leakage of the light at the ends of the sub mold part 230.

[0080] FIG. 8 is a schematic view showing a two-way backlight assembly according to another exemplary embodiment of the present invention. In FIG. 8, the same reference numerals denote the same elements in FIG. 1, and thus the detailed descriptions of the same elements will be omitted.

[0081] Referring to FIG. 8, a backlight assembly 400 according to another exemplary embodiment includes a light source 110, a light guide part 440 for changing a path of the light from the light source 110, a first optical sheet 140 and a second optical sheet 150.

[0082] The light guide part 440 includes a first light guide plate 410, a second light guide plate 420, and a reflection plate 430 disposed between the first and second light guide plates 410 and 420.

[0083] Particularly, a portion of the light emitted from the light source 110 is incident on the first light guide plate 410 and a remaining portion of the light emitted from the light source 110 is incident on the second light guide plate 420. The first light guide plate 410 includes a first light exit surface 412 facing the first optical sheet 140 and a first light reflection surface 414 facing the reflection plate 430. The second light guide plate 420 also includes a second light exit surface 422 facing the second optical sheet 150 and a second light reflection surface 424 facing the reflection plate 430.

[0084] A great portion of the light emitted from the light source 110 and incident on the first light guide plate 410 is directly exited through the first light exit surface 412, and a remaining portion of the light is exited through the first light

exit surface 412 after reflecting from the reflection plate 430. Similarly, a great portion of the light emitted from the light source 110 and incident on the second light guide plate 420 is directly exited through the second light exit surface 422, and a remaining portion of the light is exited through the second light exit surface 422 after reflecting from the reflection plate 430.

[0085] The second light guide plate 420 may have a size equal to or different from a size of the first light guide plate 410. In this exemplary embodiment, the second light guide plate 420 has a smaller size than that of the first light guide plate 410. Also, an incident surface 426 of the second light guide plate 420, on which the light emitted from the light source 110 is incident, is straight with an incident surface 416 of the first light guide plate 410.

[0086] The two-way backlight assembly 100 according to another exemplary embodiment of the present invention may supply the light emitted from the light source 110 to two directions different from each other by using one light source 110, two light guide plates 410 and 420 and one reflection/transmission sheet 430.

[0087] FIG. 9 is an exploded perspective view showing the two-way backlight assembly shown in FIG. 8.

[0088] Referring to FIG. 9, the two-way backlight assembly 400 includes the light source 110, the light guide part 440 for supplying the light emitted from the light source 110 to two directions different from each other, a main mold part 210 for receiving the light source 110 and light guide part 440, a receiving container 220 and a sub mold part 230.

[0089] The light guide part 440 includes the first light guide plate 410, second light guide plate 420 and reflection plate 430 disposed between the first and second light guide plates 410 and 420.

[0090] Particularly, the light emitted from the light source 110 is incident on the first and second light guide plates 410 and 420. In this exemplary embodiment, since the reflection plate 430 is disposed between the first and second light guide plates 410 and 420, the light incident on the first light guide plate 410 is reflected from the reflection plate 430 towards the first light exit surface 412, and the light incident on the second light guide plate 420 is reflected from the reflection plate 430 towards the second exit surface 422. Thus, the light incident on the first light guide plate 410 is provided to the first direction through the first light exit surface 412, and the light incident on the second light guide plate 420 is provided to the second direction opposite to the first direction through the second light exit surface 422.

[0091] The light guide part 440 is disposed between the main mold part 210 and receiving container 220.

[0092] The receiving container 220 is provided with an opening 224 formed at a bottom surface 222 corresponding to the second light guide plate 420, so that the light exited through the second exit surface 422 of the second light guide plate 420 may be provided to the second direction through the opening 224. The opening 224 is placed at a position adjacent to the light source 110 so as to allow the light emitted from the light source 110 to be easily incident on the second light guide plate 420.

[0093] In order to prevent leakage of the light at ends of the sub mold part 230, the sub mold part 230 coupled to the opening 224 of the receiving container 220 may comprise a black-colored or/and a flat material. Also, the two-way backlight assembly 100 may further include a black-colored tape disposed between a sidewall of the sub mold part 230 and

second light guide plate **420**, thereby preventing leakage of the light through the ends of the sub mold part **230**.

[0094] FIG. **10** is an exploded perspective view showing an LCD apparatus according to an exemplary embodiment of the present invention. In FIG. **10**, the same reference numerals denote the same elements in FIG. **2**, and thus the detailed descriptions of the same elements will be omitted.

[0095] Referring to FIG. **10**, an LCD apparatus **600** includes a main LCD panel assembly **610**, a sub LCD panel assembly **620** and a two-way backlight assembly **100**.

[0096] The two-way backlight assembly **100** includes a main backlight assembly **630** and a sub backlight assembly **640**.

[0097] The main LCD panel assembly **610** is disposed on the main backlight assembly **630**. The main LCD panel assembly **610** receives a light supplied to a first direction through a first exit surface **122** of a light guide plate **120** and a first optical sheet **140**, and displays a main image.

[0098] The sub LCD panel assembly **620** is disposed on the sub backlight assembly **640**. The sub LCD panel assembly **620** receives a light supplied to a second direction through a second exit surface **124** of a light guide plate **120**, a reflection/transmission sheet **130** and a second optical sheet **150**, and displays a sub image.

[0099] The main LCD panel assembly **610** may have a display size equal to that of the sub LCD panel assembly **620**. However, in this exemplary embodiment, the main LCD panel assembly **610** has the display size greater than that of the sub LCD panel assembly **620**.

[0100] In case that the display size of the sub LCD panel assembly **620** is smaller than the display size of the main LCD panel assembly **610**, the light provided to the sub mold assembly **230** may be leaked at ends of the sub mold part **230**. As a result, the two-way LCD apparatus **600** may not provide an image having uniformed brightness.

[0101] In order to prevent leakage of the light through ends of the sub mold part **230**, the sub mold part **230** may comprise a black-colored or/and a flat material. Also, the two-way LCD apparatus **600** may further include a black-colored tape disposed between a sidewall of the sub mold part **230** and reflection/transmission sheet **130**, thereby preventing leakage of the light through the ends of the sub mold part **230**.

[0102] The two-way LCD apparatus **600** may further include a main chassis **650** for preventing deviation of the main LCD panel assembly **610** from the main backlight assembly **630** and a sub chassis **660** for preventing deviation of the sub LCD panel assembly **620** from the sub backlight assembly **640**. The main chassis **650** and sub chassis **660** are combined with the main mold part **210** and receiving container **220**, respectively, so as to prevent deviation of the main and sub LCD panel assemblies **610** and **620**.

[0103] FIG. **11** is a perspective view showing the main LCD panel assembly shown in FIG. **10**. In this exemplary embodiment, the sub LCD panel assembly **620** has same elements as those of the main LCD panel assembly **610**, and thus a detailed description of the sub LCD panel assembly **620** will be omitted.

[0104] Referring to FIG. **11**, the main LCD panel assembly **610** includes an LCD panel **614**, a driving chip **616** and an FPC **618**.

[0105] The LCD panel **614** includes a first substrate **611**, a second substrate **612** facing the first substrate **611** and liquid crystal (not shown) disposed between the first and second substrates **611** and **612**.

[0106] Particularly, a plurality of pixels is formed on the second substrate **612** in a matrix configuration. Each of the pixels is provided with a gate line extended in a first direction and a data line. The data line is insulated from the gate line, and extended in a second direction substantially perpendicular to the first direction. A thin film transistor (TFT) is formed at a pixel area defined by the gate and data lines, and electrically connected to the gate and data lines.

[0107] The second substrate **612** includes the driving chip **616** formed on one end thereof so as to apply a driving signal to the gate and data lines. The driving chip **616** may include a data line chip and a gate line chip separated from each other, and the data line chip and gate line chip may be packed into one chip. The driving chip **616** is mounted on the end of the second substrate **612** through Chip-On-Glass process (COG).

[0108] The FPC **618** is further attached to the end of the second substrate **612** so as to apply a control signal for controlling the driving chip **616**. The FPC **618** may further include a timing controller for controlling a timing of the driving signal applied to the gate line and a memory for storing a data signal. The FPC **618** is electrically connected to the second substrate **612** by means of an anisotropic conductive film.

[0109] The two-way LCD apparatus **600** according to another exemplary embodiment of the present invention may supply the light to the first and second directions different from each other using the two-way backlight assembly **100** having one light source **110**, one light guide plate **120** and reflection/transmission sheet **130**. The light supplied to the first direction is provided to the main LCD panel assembly **610** and the light supplied to the second direction is provided to the sub LCD panel assembly **620**, so that the main and sub LCD panel assemblies **610** and **620** may display the main and sub images, respectively.

[0110] According to the two-way backlight assembly and two-way LCD apparatus having the same, the two-way LCD apparatus may provide the light to two directions different from each other using only one light source, thereby reducing thickness and power consumption of the backlight assembly.

[0111] Also, although the display size of the main LCD panel assembly is different from the display size of the sub LCD panel assembly, the LCD apparatus may prevent leakage of the light through the ends of the sub mold part because the sub mold part may comprise the black-colored or/and flat material.

[0112] Although the exemplary embodiments of the present invention have been described, it is understood that the present invention should not be limited to these exemplary embodiments, but various changes and modifications can be made by one ordinary skilled in the art within the spirit and scope of the present invention as hereinafter claimed.

What is claimed is:

1. A backlight assembly comprising:
 - a light source generating light;
 - a light guide part including a first exit surface and a second exit surface opposite to the first exit surface, the light guide part receiving the light from the light source and emitting the received light through the first and second exit surfaces;
 - a receiving container receiving the light source and light guide part, wherein the receiving container includes an opening; and
 - a leakage preventing member disposed around the opening to prevent a leakage of the light.

2. The backlight assembly of claim 1, wherein the receiving container comprises a protruding portion formed at one end of the opening.

3. The backlight assembly of claim 2, wherein the leakage preventing member contacts a side of the protruding portion.

4. The backlight assembly of claim 2, wherein the leakage preventing member comprises a black-colored tape.

5. The backlight assembly of claim 2, further comprising a reflection/transmission sheet disposed on the second exit surface of the light guide part.

6. The backlight assembly of claim 2, wherein the leakage preventing member comprises a mold part including an engaging recess corresponding to the protruding portion, the mold part comprising a flat material to prevent a reflection of light.

7. The backlight assembly of claim 2, wherein the leakage preventing member comprises a mold part including an engaging recess corresponding to the protruding portion, the mold part comprising a black-colored material to prevent a reflection of light.

8. The backlight assembly of claim 1, wherein the leakage preventing member comprises a black-colored material.

9. The backlight assembly of claim 1, wherein the leakage preventing member comprises a flat material.

10. The backlight assembly of claim 1, wherein the light guide part comprises a first light guide plate including the first exit surface and a second light guide plate including the second exit surface.

11. The backlight assembly of claim 10, wherein the light guide part further comprises a reflection plate disposed between the first and second light guide plates.

12. A liquid crystal display apparatus comprising:

a light source;

a light guide part including a first exit surface and a second exit surface opposite to the first exit surface;

a first liquid crystal display panel assembly disposed over the first exit surface of the light guide part;

a receiving container receiving the light source, the light guide part, and the first liquid crystal display panel assembly, wherein the receiving container includes an opening;

a second liquid crystal display panel assembly disposed below the opening; and

a leakage preventing member disposed around the opening to prevent a leakage of the light.

13. The liquid crystal display apparatus of claim 12, wherein the leakage preventing member comprises a portion overlapping with the light guide part and the first and second liquid crystal display panel assembly in a vertical direction.

14. The liquid crystal display apparatus of claim 12, wherein the receiving container comprises a protruding portion formed at one end of the opening.

15. The liquid crystal display apparatus of claim 14, wherein the leakage preventing member contacts a side of the protruding portion.

16. The liquid crystal display apparatus of claim 14, further comprising a reflection/transmission sheet disposed on the second exit surface of the light guide part.

17. The liquid crystal display apparatus of claim 12, further comprising a mold part coupled to the receiving container, wherein the mold part includes a plurality of sidewalls corresponding to the opening.

18. The liquid crystal display apparatus of claim 17, wherein the leakage preventing member is partially disposed between the light guide part and the plurality of sidewalls.

19. The liquid crystal display apparatus of claim 12, wherein the leakage preventing member comprises a black-colored material.

20. The liquid crystal display apparatus of claim 12, wherein the leakage preventing member comprises a flat material.

* * * * *

专利名称(译)	双向背光组件和具有该双向背光组件的双向液晶显示装置		
公开(公告)号	US20090185103A1	公开(公告)日	2009-07-23
申请号	US12/411440	申请日	2009-03-26
[标]申请(专利权)人(译)	韩BYUNG WOONG 李相熙 KIM JAE KWANG 褚杨BEE 金圭SEOK		
申请(专利权)人(译)	韩炳WOONG 李相熙 金宰KWANG 褚YOUNG-BEE 金圭硕		
当前申请(专利权)人(译)	韩炳WOONG 李相熙 金宰KWANG 褚YOUNG-BEE 金圭硕		
[标]发明人	HAN BYUNG WOONG LEE SANG HEE KIM JAE KWANG CHU YOUNG BEE KIM KYU SEOK		
发明人	HAN, BYUNG-WOONG LEE, SANG-HEE KIM, JAE-KWANG CHU, YOUNG-BEE KIM, KYU-SEOK		
IPC分类号	G02F1/13357 G09F13/00 G02F1/1333 G02F1/1335		
CPC分类号	G02B6/0063 G02B6/0088 G02F2001/133342 G02F1/133615 G02F1/133608		
优先权	1020030042007 2003-06-26 KR		
其他公开文献	US7922381		
外部链接	Espacenet USPTO		

摘要(译)

在双向背光组件和双向LCD装置中，双向背光组件将从一个光源发出的光提供到放置主LCD面板的第一方向和提供子LCD面板的第二方向。而且，用于接收子LCD面板的子模具部件包括黑色材料，以防止光的反射。因此，可以通过防止副LCD面板的端部处的光泄漏来减小背光组件的厚度和功耗并且还可以提高显示质量。

