

(19) World Intellectual Property Organization  
International Bureau(43) International Publication Date  
3 May 2007 (03.05.2007)

PCT

(10) International Publication Number  
WO 2007/050113 A1(51) International Patent Classification:  
G09G 3/32 (2006.01)

(74) Common Representative: EASTMAN KODAK COMPANY, 343 State Street, Rochester, New York 14650-2201 (US).

(21) International Application Number:  
PCT/US2006/005393

(81) Designated States (unless otherwise indicated, for every kind of national protection available): AE, AG, AL, AM, AT, AU, AZ, BA, BB, BG, BR, BW, BY, BZ, CA, CH, CN, CO, CR, CU, CZ, DE, DK, DM, DZ, EC, EE, EG, ES, FI, GB, GD, GE, GH, GM, HR, HU, ID, IL, IN, IS, JP, KE, KG, KM, KN, KP, KR, KZ, LC, LK, LR, LS, LT, LU, LV, LY, MA, MD, MG, MK, MN, MW, MX, MZ, NA, NG, NI, NO, NZ, OM, PG, PH, PL, PT, RO, RU, SC, SD, SE, SG, SK, SL, SM, SY, TJ, TM, TN, TR, TT, TZ, UA, UG, US, UZ, VC, VN, YU, ZA, ZM, ZW.

(22) International Filing Date:  
16 February 2006 (16.02.2006)

(84) Designated States (unless otherwise indicated, for every kind of regional protection available): ARIPO (BW, GH, GM, KE, LS, MW, MZ, NA, SD, SL, SZ, TZ, UG, ZM, ZW), Eurasian (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM), European (AT, BE, BG, CH, CY, CZ, DE, DK, EE, ES, FI, FR, GB, GR, HU, IE, IS, IT, LT, LU, LV, MC, NL, PL, PT, RO, SE, SI, SK, TR), OAPI (BF, BJ, CF, CG, CI, CM, GA, GN, GQ, GW, ML, MR, NE, SN, TD, TG).

(25) Filing Language: English

**Published:**

(26) Publication Language: English

— with international search report


(30) Priority Data:  
11/069,652 1 March 2005 (01.03.2005) US*[Continued on next page]*

(71) Applicant (for all designated States except US): EASTMAN KODAK COMPANY [US/US]; 343 State Street, Rochester, New York 14650-2201 (US).

(72) Inventors; and

(75) Inventors/Applicants (for US only): WINTERS, Dustin, Lee [US/US]; 63 Bainbridge Lane, Webster, New York 14580 (US). LUDWICKI, John, Edward [US/US]; 2 Knollwood Drive, Churchville, New York 14428 (US).

(54) Title: OLED DISPLAY WITH IMPROVED ACTIVE MATRIX CIRCUITRY



(57) **Abstract:** An OLED display for producing a multicolor image includes a plurality of pixels including three different colored addressable gamut-pixels (20r, 20g, 20b) and a fourth addressable within-gamut-pixel (20w), each pixel having a separately addressable organic light-emitting diode (10r) with first and second electrodes and one or more organic light emissive layers provided between the electrodes; active matrix circuitry including a separate power transistor (140r) for at least two of the three different colored addressable gamut-pixels for regulating current between a first and second voltage source (V1, Vc) through the organic light-emitting diode of the colored addressable gamut-pixel; and the active matrix circuitry including a power transistor for the fourth addressable within-gamut-pixel for regulating current between a third and fourth voltage source (V2, Vc) through the organic light-emitting diode of the fourth addressable within-gamut-pixel wherein at least three of the first, second, third, and fourth voltage sources provide different voltage levels .

WO 2007/050113 A1



*For two-letter codes and other abbreviations, refer to the "Guidance Notes on Codes and Abbreviations" appearing at the beginning of each regular issue of the PCT Gazette.*

**OLED DISPLAY WITH IMPROVED ACTIVE MATRIX CIRCUITRY****FIELD OF INVENTION**

This invention relates to active matrix circuitry for driving pixels in an OLED display.

5

**BACKGROUND OF THE INVENTION**

In the simplest form, an organic electroluminescent (EL) device is comprised of an organic electroluminescent media disposed between first and second electrodes serving as an anode for hole injection and a cathode for electron injection. The organic electroluminescent media supports recombination of holes and electrons 10 that yields emission of light. These devices are also commonly referred to as organic light-emitting diodes, or OLEDs. A basic organic EL element is described in U.S. Patent 4,356,429. In order to construct a pixelated OLED display that is useful as a display such as, for example, a television, computer monitor, cell phone display, or digital camera display, individual organic EL elements can be arranged as pixels in a 15 matrix pattern. These pixels can all be made to emit the same color, thereby producing a monochromatic display, or they can be made to produce multiple colors such as a three-pixel red, green, blue (RGB) display. For purposes of this disclosure, a pixel is considered the smallest individual unit, which can be independently stimulated to produce light. As such, the red pixel, the green pixel, and the blue pixel 20 are considered as three distinct pixels.

Color OLED displays have also recently been described that are constructed as to have four differently colored pixels. One type of OLED display having four differently colored pixels that are red, green, blue, and white in color is known as an RGBW design. Examples of such four pixel displays are shown in U.S. 25 Patent 6,771,028, U.S. Patent Application Publications 2002/0186214 A1, 2004/0113875 A1, and 2004/0201558 A1. Such RGBW displays can be constructed using a white organic EL emitting layer with red, green, and blue color filters for the red, green, and blue pixels, respectively. The white pixel area is left unfiltered. This design has the advantage that the organic electroluminescent media does not require 30 patterning between the differently colored pixels, thereby simplifying the manufacturing process. Furthermore,

inclusion of the unfiltered white pixel allows for the display of colors that are less than fully saturated at reduced power consumption compared to similar RGB displays having a white organic EL emitting layer with red, green, and blue filters for the red, green, and blue pixels, respectively.

5           OLED displays driven with active matrix circuitry have also been shown. Active matrix circuitry typically includes active circuit components such as multiple transistors and one or more capacitors per pixel as well as signal lines such as data, scan, and power lines, which are shared by the pixels of a row or column. Each pixel in an active matrix OLED display is provided with at least one power 10 transistor. A power transistor regulates the current flow to the pixel's organic EL element in response to a data signal provided on a data line. The power transistor draws current from a power line, which is electrically connected to a voltage source. This current is passed to the first electrode and the organic EL media of the pixel's organic EL element. The second electrode, which is disposed above the organic EL 15 media and the active matrix circuitry, is then electrically connected to a second voltage source, which completes the current path. Examples of organic EL displays driven by active matrix circuitry are shown in U.S. Patents 5,550,066, 6,281,634, and 6,456,013.

20           However, OLED displays driven by active matrix circuitry require that the voltage difference between the voltage source electrically connected to the power line and the voltage source electrically connected to the second electrode be sufficient to power all the pixels connected to said power line at their highest level of intensity. This voltage difference, or drop, is split between the organic EL element and the at least one power transistor. Therefore, when one or more pixels are at times operated 25 at a lower level of intensity, the supplied voltage is more than is required. In this case, the percentage of the voltage drop across the one or more power transistors in these pixels is increased. Since power consumption is a function of the current flow and the voltage drop, this extra voltage drop results in poor power efficiency.

30           Active matrix OLED displays have been shown where differently colored pixels are connected to the same power line, e.g. U.S. Patent 6,456,013. Also, active matrix OLED displays have been shown where adjacent columns of

pixels share the same power line in U.S. Patent 6,522,079. Similarly, examples where the same power line is shared by pixels of differing colors or pixels in adjacent rows for an RGBW type active matrix display are shown in U.S. Patent 6,771,028. However, if the differently colored pixels connected to a power line also differ in their required voltage level, this arrangement will also suffer from poor power efficiency.

### **SUMMARY OF THE INVENTION**

It is an object of the present invention to provide an OLED display with improved power efficiency.

This object is achieved by an OLED display for producing a multicolor image, comprising:

a) a plurality of pixels including three different colored addressable gamut-pixels and a fourth addressable within-gamut-pixel, each pixel having a separately addressable organic light-emitting diode with first and second electrodes and one or more organic light emissive layers provided between the electrodes;

b) active matrix circuitry including a separate power transistor for at least two of the three different colored addressable gamut-pixels for regulating current between a first and second voltage source through the organic light-emitting diode of the colored addressable gamut-pixel; and

c) the active matrix circuitry including a power transistor for the fourth addressable within-gamut-pixel for regulating current between a third and fourth voltage source through the organic light-emitting diode of the fourth addressable within-gamut-pixel wherein at least three of the first, second, third, and fourth voltage sources provide different voltage levels.

### **25 BRIEF DESCRIPTION OF THE DRAWINGS**

FIG. 1 depicts a circuit layout of the active matrix drive circuitry of a display according to the present invention;

FIG. 2 depicts the layout and wiring of a display according to an embodiment of the present invention;

30 FIG. 3 depicts the construction and layout of the components of the drive circuitry used to drive pixels of a display according to the present invention;

FIG. 4 depicts a cross sectional view along line X-X' of the display of FIG. 3; and

5 FIG. 5 depicts the construction and layout of the components of the drive circuitry used to drive pixels of a display according another embodiment of the present invention.

### **DETAILED DESCRIPTION OF THE INVENTION**

FIG. 1 shows a circuit schematic diagram for the active matrix drive circuitry of an active matrix type OLED display according to the present invention.

The display is an RGBW type OLED display having four differently colored pixels.

10 RGBW OLED displays are one example of a type of display that uses within-gamut-pixels to reduce power consumption compared to conventional RGB type displays.

Such RGBW OLED display devices are capable of displaying color images through the use of at least four differently color pixels. In an RGBW OLED display, at least three of the differently colored pixels, such as pixel **20r**, pixel **20g**, and pixel **20b** are

15 gamut-pixels that emit different colors, which determine the color gamut of the display. For example, gamut-pixels might emit light that is red, green, or blue in color. In this case, pixel **20r** is arranged to emit red light, pixel **20g** is arranged to emit green light, and pixel **20b** is arranged to emit blue light. Illuminating two or more of the gamut-pixels to varying intensities can produce other colors within the

20 color gamut. These new colors are referred to as within-gamut colors. Such an RGBW OLED display also has at least one additional pixel, such as pixel **20w**, that is a within-gamut-pixel, which is arranged to emit a within-gamut color light such as white. The term white is used in the present invention to indicate any light emission that is perceived as approximately white to a viewer. White is the most preferred

25 color for the within-gamut-pixel as it is approximately between the other three gamut-pixel colors. However, the present invention is not limited to a white pixel and other colors which are, for example, more blue, green, red, yellow, pink, or cyan in appearance can be also be employed. These within-gamut-pixels are more efficient

30 than at least one of the gamut-pixels and are typically more efficient than all of the gamut-pixels. Efficiency, which can be measured in (cd/A), is determined as the amount of light emitted from the device per unit of power, which can be measured

in, for example, watts (W). Power consumed by the device, in turn, is determined by the current flow required to produce the desired luminance multiplied by the applied voltage drop (V) across the organic light-emitting diode as well as any circuit components electrically connected between the organic light-emitting diode and the 5 voltage source. In an RGBW type display, within-gamut colors can also be displayed by illuminating the within-gamut-pixel in combination with one or more of the gamut-pixels at varying intensities. In this way, the RGBW OLED display can display within-gamut colors with improved power efficiency.

FIG. 1 shows the circuit layout of the active matrix drive circuitry for 10 several rows and columns of pixels. While only a limited number of rows and columns are shown, one skilled in the art can expand this design to a larger plurality of rows and columns. The active matrix drive circuitry is composed of signal lines such as select line **113**, capacitor line **114**, data line **112r**, data line **112g**, data line **112b**, data line **112w**, power line **111r**, power line **111g**, power line **111b**, and power 15 line **111w**. These signal lines are common to a row or a column of pixels as shown and are arranged to drive the pixels of the row or column. The active matrix drive circuitry further includes components such as select transistor **120r**, power transistor **140r**, and storage capacitor **130r**, which together with one of more of the signal lines are arranged to drive the organic light-emitting diode **10r** of pixel **20r**. The other 20 pixels are provided with similar components to drive the respective organic light-emitting diodes of the pixels. A common top electrode connection is connected to the cathodes of all the organic light-emitting diodes to complete the circuit. This common top electrode connection is electrically connected to a voltage source  $V_c$ . The present invention, however, is not limited to the case where the top electrode is 25 common. For example, the top electrode can alternately be common to a single column of pixels and each row of pixels can be provided with a different top electrode. These electrodes can be supplied with the same or different voltage levels. Other alternate configurations where individual top electrodes are provided for different rows or where each pixel is provided with its own isolated top electrode can 30 also be practiced.

The term electrical connection is used in this disclosure to indicate connection either directly by way of a conductor or indirectly through a component such as a switch, transistor, diode or the like. Power line **111r**, power line **111g**, and power line **111b** are electrically connected to voltage source V1 and power line **111w** 5 is electrically connected to voltage source V2. While the circuit of this example is shown with the organic light-emitting diode arranged in a particular bias with the cathode connected to the common connection and the anode connected to the power transistor, the opposite arrangement can also be employed by one skilled in the art and is included within the scope of the present invention.

10 The drive circuitry operates in a manner well known in the art. Each row of pixels is selected in turn by applying a voltage signal to the select line associated with the row, such as select line **113**, which turns on the select transistor, such as select transistor **120r**, for each pixel. The brightness level, or gray scale information, for each pixel is controlled by a voltage signal, which has been set on the 15 data lines, such as data line **112r**. The storage capacitor, such as storage capacitor **130r**, for each pixel is then charged to the voltage level of the data line associated with that pixel and maintains the data voltage until the row is selected again during the next image frame. The storage capacitor **130r** is connected to the gate terminal of the power transistor **140r**. Power transistor **140r** regulates the current flow through 20 its source and drain terminals and to the organic light-emitting diode **10r** in response to the voltage level held on its gate terminal by storage capacitor **130r**, thereby controlling the pixel's brightness. Each row is then unselected by applying a voltage signal to the select line, which turns off the select transistors. The data line signal values are then set to the levels desired for the next row and the select line of the next 25 row is turned on. This is repeated for every row of pixels.

As such, select lines are signal lines that serve the function of isolating a row of pixels so that the gray scale information can be loaded into the pixels of the row. Data lines are signal lines that provide the gray scale information to the pixels. This gray scale information can be in the form of a voltage or current signal. Power 30 lines are signal lines that provide a source of

electrical power to the organic light-emitting diodes of the pixels for maintaining the brightness level of the pixel, at least during the time when the pixels row is not selected by the select line. Typically, the power lines provide a source of electrical power to the organic light-emitting diode at all times when the pixels are illuminated.

5 Many different alternate types of circuit arrangements known in the art having various arrangements and numbers of circuit components and signal lines are constructed with signal lines serving these basic functions, and the present invention can be practiced on these alternate types of circuit arrangements by one skilled in the art. As such, the present invention is not limited to the specific circuit arrangement shown here. These  
10 alternate arrangements include, for example, current mirror type circuits such as shown in U.S. Patents 6,091,203, 6,501,466, 6,535,185 and 6,774,877 as well as the pixel circuits shown in U.S. Patent 6,229,506 and the pixel circuit described in U.S. Patent Application Publication 2004/0222746 A1.

V1 and V2 are voltage sources maintained at different levels with

15 respect to the voltage level of voltage source Vc. As previously described, pixel **20w**, which is a within-gamut-pixel, is constructed so as to be more efficient than pixel **20r**, pixel **20g**, or pixel **20b**, which are gamut-pixels. Therefore, the magnitude of the voltage drop across the organic light-emitting diode of pixel **20w** required to obtain a desired peak brightness is smaller than the magnitude of the voltage drop required  
20 across at least one of pixel **20r**, pixel **20g**, or pixel **20b**. OLED devices are not an ideal diode. An ideal diode has no resistance and, as such, can pass infinite current without increasing applied voltage above a turn-on voltage. OLED devices, on the other hand, are known to require higher applied voltage as current density is increased. A more efficient device requires a lower current to achieve comparable  
25 brightness. For cases where the within-gamut-pixel has approximately the same emitting area as the gamut-pixels, the within-gamut-pixel will require a lower current density. It can therefore be supplied with a lower magnitude voltage.

It is often desirable to design the display such that the emitting areas of the differently colored pixels are not the same. By adjusting the emitting areas of the  
30 differently colored pixels, the current densities used to achieve the

desired levels of brightness for each of the differently colored pixels are also adjusted. The luminance efficiency of OLED devices is known to decay with usage and this rate of decay decreases with decreased current density. Therefore, by individually adjusting the emitting areas of one or more of the differently colored pixels, the rate 5 of decay with usage can be adjusted. Therefore, the emitting areas of one or more of the differently colored pixels is preferably adjusted so that the luminance of the differently colored pixels decay at approximately the same rate over the life of the display. Since the colors of the gamut-pixels, also known as saturated colors, occur less frequently in typical images than the colors within the gamut, the within-gamut- 10 pixel usage is typically more frequent than that of the gamut-pixels. Therefore, the emitting area of the within-gamut-pixel is preferably made to be larger than the emitting areas of one or more of the gamut-pixels. This concept of adjusting the emitting areas of the pixels for an RGBW type OLED display is described in U.S. Patent Application Publication 2004/0201558 A1. This further deceases its current 15 density and therefore the required magnitude of supplied voltage. Therefore, by supplying a separate voltage source for within-gamut-pixels according to the present invention, power consumption is further reduced for OLED displays having within-gamut-pixels with emitting areas larger than that of the gamut-pixels.

Therefore, according to the present invention, the magnitude of the 20 voltage applied to the within-gamut-pixel, in this case pixel **20w**, which is the magnitude of  $V_2 - V_c$ , is less than the magnitude of the voltage applied to the gamut-pixels, in this case pixel **20r**, pixel **20g**, and pixel **20b**, which is the magnitude of  $V_1 - V_c$ . It is desirable to reduce the number of different voltage levels that need to be supplied to the display. Therefore, it is preferred that the power lines of the gamut- 25 pixels be provided the same voltage level, as shown, even though these pixels can have slightly differing efficiencies. Therefore, only three voltage levels, represented as  $V_1$ ,  $V_2$ , and  $V_c$  need be supplied to the power lines and common top electrode. However, some advantage can still be achieved according to the present invention, if one of the gamut-pixels is provided with yet another voltage level at its associate 30 power line.

Alternate configurations where the top electrodes are not common, as described previously, can be practiced by one skilled in the art. In this case, the multiple voltage levels can alternately be supplied to the multiple top electrodes or to both the multiple top electrodes and to multiple power lines. Such alternate 5 configurations are considered within the scope of the present invention.

A plurality of pixels having the same color, for example red (R), green (G), blue (B) or white (W), can be present in a plurality of rows and columns. It is preferred that all the pixels having the same color be connected the same voltage level. For example, a given column of pixels can include all red pixels and the entire 10 column is therefore preferably connected to the same power line, as shown.

Similarly, every fourth column of pixels can include all pixels of the same color. Therefore, the power lines for every fourth column can be connected together as well. The connecting of power lines of differing columns can be achieved by electrically connecting these power lines together with a conductor at one side of the display 15 outside the pixel area, as shown. Since, in the preferred embodiment of the present invention the power lines of all the gamut-pixels are connected to one voltage source and the power lines of the within-gamut-pixels are connected to a second voltage source, two different voltage sources need to be connected to the various power lines. This is preferably achieved by electrically connecting the power lines of plurality of 20 columns of the gamut-pixels together along one side of the display outside of the pixel area and electrically connecting the power lines of the plurality of columns of within-gamut-pixels together along the opposite side of the display outside the pixel area.

FIG. 2 shows a conceptual view of a display illustrating the layout and connections of the various parts and sections of a display according one embodiment 25 of the present invention. The display includes a pixel region 30, a connector region 40, a select line driver 50, and a data line driver 60. The select line driver 50 functions to selectively activate the select lines (not shown) for each row as previously described. The data line driver 60 serves to provide data signals to the data lines (not shown) for each column as previously described. The pixel region 30 30 includes the light-emitting pixels of the display. The regions outside of the pixel region 30 are non-light-emitting regions. The connector region 40

provides a plurality connector pads such a connector pad **41**, connector pad **42**, and connector pad **43**. These connector pads serve as a location for bonding of wires or cables that electrically connect the display to external power sources (not shown) or controlling circuits (not shown). For example, connector pad **41** serves as a  
5 connection for voltage source  $V_c$ , connector pad **42** serves as a connection for voltage source  $V_1$ , and connector pad **43** serves as a connection for voltage source  $V_2$ . It is preferable that the connector pads are all formed along one edge of the display to reduce the size for the non-light-emitting regions of the display as well as simplify the connection process. While, each of the voltages sources can be electrically connected  
10 to a single connector pad, multiple connector pads can also be used to provide a low resistance electrical connection to one or more of the voltage sources as described in U.S. Patent 6,531,815.

Connector pad **42** is electrically connected to the power lines of the gamut-pixels such as power line **111r**, power line **111g**, and power line **111b**. This electrical connection is formed on one side of the display out side of the pixel region **30**. This can be, for example, the same side of the display as the connector region **40**, between the pixel region **30** and the connector region **40**, as shown. Connector pad **43** is electrically connected to the power lines of the within-gamut-pixels such as power line **111w**. This electrical connection is also formed on one side of the display out  
15 side of the pixel region **30**. This can be, for example, the same side of the display as the data line driver **60**, between the pixel region **30** and the data line driver **60**, as shown.  
20

A layout diagram for the portions of the drive circuitry used to drive pixel **20r**, pixel **20g**, pixel **20b**, and pixel **20w** according to the present invention is shown in FIG. 3. FIG. 3 shows the construction and layout of the various circuit components such as select transistor **120r**, storage capacitor **130r**, and power transistor **140r**. The drive circuitry components are fabricated using known integrated circuit and thin film transistor fabrication technologies. Select transistor **120r** is formed from a first semiconductor region **121** using techniques well known in the art.  
25 Select transistor **120r** is shown as a double gate type transistor, however, this is not required for successful practice of the present invention and a single gate type  
30

transistor can also be used. Similarly, power

transistor **140r** is formed in a second semiconductor region **141**. The first semiconductor region **121** and second semiconductor region **141** are preferably formed from the same semiconductor layer. This semiconductor layer is preferably silicon such as polycrystalline or crystalline silicon, but can also be amorphous silicon. Other inorganic and organic semiconducting materials known in the art can also be used. This first semiconductor region **121** also forms one side of storage capacitor **130r**. Over the first semiconductor region **121** and second semiconductor region **141**, is an insulating layer (not shown) of a material such as silicon nitride that forms the gate insulator of select transistor **120r**, the gate insulator for power transistor **140r**, and the insulating layer of storage capacitor **130r**. The gate of select transistor **120r** is formed from part of select line **113**, which is formed in the first conductor layer. Power transistor **140r** has a separate power transistor gate **143** also preferably formed in the first conductor layer. The other electrode of storage capacitor **130r** is formed as part of capacitor line **114**, are also preferably formed from the first conductive layer. Power line **111r**, power line **111g**, power line **111b**, power line **111w**, data line **111r**, data line **111g**, data line **111b**, and data line **111w** are preferably formed from a second conductive layer. One or more of the signal lines, for example select line **113**, frequently cross at least one or more of the other signal lines, such as for example data line **112r**. As such, these signal lines are preferably fabricated from multiple conductive layers with at least one interlayer insulating layer (not shown) of a material such as silicon nitride disposed in between. The first electrode **181** of the organic light-emitting diode is connected to power transistor **140r**. An insulating layer (not shown) of a material such as silicon nitride is located between the first electrode **181** and the second conductive layer.

25                   Connections between layers are formed by etching holes (or vias) in the insulating layers such as via **122** connecting data line **112r** to the first semiconductor region **121**. Similarly, via **142** connects the power transistor gate **143** to first semiconductor region **121**, via **146** connects the second semiconductor region **141** to power line **111r**, and the via **145** connects the second semiconductor region **141** to the first electrode **181**.

First electrode **181** serves to provide electrical contact to the organic electroluminescent media of the organic light-emitting diodes. Over the perimeter edges first electrode data, an interpixel dielectric layer can be formed to cover the edges of the electrodes and reduce shorting defects as described below. Such 5 interpixel dielectric layers are also described in U.S. Patent 6,246,179. Opening **182** is made in the interpixel dielectric layer over the first electrode **181** to permit the first electrode **181** to make electrical contact with the organic electroluminescent media of the organic light-emitting diode. The emitting area of pixel **20r** is defined by the areas of the first electrode **181** that is in electrical contact with the organic 10 electroluminescent media. As such, the emitting area is the area of the first electrode **181** reduced by any area covered by dielectric material. Therefore, when an interpixel is used as described, the emitting area is the area of the opening, such as opening **182**, in the interpixel dielectric layer. While use of such an interpixel dielectric layer is preferred, it is not required for successful practice of the present invention.

15 In a preferred embodiment, color filter elements (not shown) are disposed in the path of the light produced in the emitting areas of the gamut-pixels so as to filter the color of the light prior to reaching the observer. The within-gamut-pixel can optionally be provided with a transparent filler material or a color filter element to slightly modify its color. Alternately, the present invention can also be 20 successfully practiced without providing a transparent filler material or color filter element for the within-gamut-pixel.

In a preferred embodiment of the present invention as shown in FIG. 3, the emitting area of the within-gamut-pixel (pixel **20w**) is made to be larger the emitting area of the gamut-pixels (pixel **20r**, pixel **20g**, and pixel **20b**), as previously 25 described. The emitting areas of the gamut-pixels can be made to be approximately the same (as shown) or can also be made to differ from one another. Since OLED devices are not ideal diodes but instead require increased voltage at higher current densities, increasing the emitting area of the within-gamut-pixel relative to the gamut-pixels further reduces the voltage required by the within-gamut-pixel relative to 30 voltage required by the gamut-pixels.

The current supplied to the organic light-emitting diode of each pixel is regulated by the power transistor of that pixel. For example, power transistor **140r** regulates the current supplied to the organic light-emitting diode of pixel **20r**. It is desirable to reduce the size of the power transistors, in terms of surface area on the substrate, in order to increase the area available for emitting areas or to allow for the pixels to be formed in a greater density or resolution. Each transistor is provided with a channel region, which has a length and a width. The channel region is the area of the semiconductor region covered by the gate electrode. For example, power transistor **140r** has a channel region with a width  $W_1$  and length  $L_1$  as shown.

Similarly, power transistor **140w** of pixel **20w** has a channel region with a width  $W_2$  and length  $L_2$ . Channel length is the dimension of the channel region between the two terminals of the transistor on either side of the transistor's gate. Channel width is the dimension of the channel region perpendicular to the channel length dimension.

The current flow through the power transistor when operated in saturation is given by the following well known equation:

$$I = \frac{\mu \times C'_{ox}}{2} \times \frac{W}{L} \times (V_{GS} - V_{TH})^2 \quad (\text{Equation 1})$$

where  $\mu$  is the carrier mobility,  $C'_{ox}$  is the gate capacitance per unit area,  $W$  is the width of the channel region,  $L$  is the length of the channel region,  $V_{GS}$  is the voltage between the gate and source terminals of the transistor, and  $V_{TH}$  is the threshold voltage of the transistor.

During operation, the value of  $V_{GS}$  is varied according to the gray scale information received from the data line. However, since the within-gamut-pixel is more efficient than the gamut-pixels, the current required to produce the desired peak brightness from the within-gamut-pixel is less than the current required to produce the desired peak brightness from the gamut-pixels. Therefore, the channel width to channel length ratio ( $W/L$ ) of the within-gamut-pixel is preferably reduced compared to the channel length ratio of the gamut-pixels. This can be achieved while retaining the same, or approximately the same, value of  $V_{GS}$  needed in order to achieve the desired peak brightness of all the pixels.

This can be accomplished, by making the channel width of the within-gamut-pixel, for example W2, smaller than the channel widths of the gamut-pixels, for example W1, as shown. This, in turn, results in the power transistor of the within-gamut-pixel being reduced in size relative to the power transistors of the gamut-pixels.

5 Furthermore, a data voltage source (not shown) is used to produce the gray scale information applied to the data line. In the case when the data signal is provided in the form of a voltage signal, the intermediate gray scale levels are represented by intermediate voltage levels produced from this data voltage source. If all gamut-pixels and within-gamut-pixels had the same channel width to channel  
10 length ratios, more intermediate voltage levels would need to be produced from this data voltage source in order to accommodate all the intermediate voltage levels for each gray scale level of each pixel. In this case, the within-gamut-pixel would use only a portion of the available intermediate voltage levels. However, by constructing the device such that the channel width to channel length ratio of the within-gamut-  
15 pixel is less than the channel width to channel length ratio of the gamut-pixels, the number of intermediate voltage levels can be reduced to achieve the same number of gray scale levels for all the pixels. In a preferred construction, the same voltage levels for the within-gamut-pixel and one or more gamut-pixels are used by adjusting the channel width to channel length ratios appropriately.

20 Finally, by constructing the device such that the channel width to channel length ratio of the within-gamut-pixel is less than channel length ratio of the gamut-pixels, the effect of noise in the gray scale information supplied to the within-gamut-pixel is reduced since the voltage level required to achieve the peak desired brightness is increased. In this way, the magnitude of noise in the form of variability  
25 in the voltage signal supplied to the power transistor is reduced compared to the magnitude of the data signal itself.

30 All the gamut-pixels can be made to have the same channel width to channel length ratios or these can vary from one another as well and still obtain one or more of these advantages. In the example shown in Fig. 3, L1 and L2 are made to be approximately the same while W1 and W2 are made to be different.

However, other examples where the lengths can be made to differ while the widths are made to be the same or both the lengths and widths differ can also be employed.

A cross-sectional view illustrating the vertical arrangement of the various layers of the OLED display of FIG. 3 along line X-X' is shown in FIG. 4.

5 From FIG. 4, it can be seen that pixel **20r**, pixel **20g**, pixel **20b**, and pixel **20w** are formed above substrate **100**. When electrically stimulated, these pixels produce light emission **280r**, **280g**, **280b** and **280w** respectively. Active matrix circuitry layers **200**, including insulating layer **202**, insulating layer **204**, and insulating layer **207** are shown. The formation of the interpixel dielectric layer **160** over the edges of the first 10 electrodes, such as first electrode **181**, can also be seen. In the case where light is viewed through the substrate, as shown, these first electrodes are preferably constructed of a material that is highly transparent such as indium tin oxide. However, the present invention is not limited to this configuration, and devices can be constructed which emit in the opposite direction. In this case, the first electrodes are 15 preferably constructed of a material, which is reflective such as aluminum or silver.

Each of the pixels further includes a portion of organic EL media **210**. There are numerous configurations of the organic EL media **210** layers wherein the present invention can be successfully practiced. For the organic EL media, a broadband or white light source that emits light at the wavelengths used by all the 20 pixels can be used to avoid the need for patterning the organic EL media between pixels. In this case, color filters elements, such as color filter element **230r**, color filter element **230g**, and color filter element **230b**, are provided for the gamut-pixels in the path of the light to produce the desired light colors from the white or broadband emission for a multi-color display. Pixels that are to emit the same white or 25 broadband emission as the organic EL media, such as pixel **20w**, can remain unfiltered. In this case, a transparent filler **230w** can optionally be provided in place of a color filter element. Some examples of organic EL media layers that emit broadband or white light are described, for example, in U.S. Patent 6,696,177. However, the present invention can also be made to work where each pixel has one or 30 more of the organic EL media layers separately

patterned for each pixel to emit differing colors for specific pixels. The organic EL media **210** is constructed of several layers such as; a hole injecting layer **211**, a hole transporting layer **212** that is disposed over the hole injecting layer **211**, a light-emitting layer **213** disposed over the hole transporting layer **212**, and an electron transporting layer **214** disposed over the light-emitting layer **213**. Alternate constructions of the organic EL media **210** having fewer or more layers can also be used to successfully practice the present invention. Organic EL media layers applied in the opposite order are also known in the art and can be applied to the present invention. These organic EL media layers include organic materials that are either small molecule materials or polymer materials as is known in the art. These organic EL media layers can be deposited by one or more of several methods known in the art such as, for example, thermal evaporation in a vacuum chamber, laser transfer from a donor substrate, or deposition from a solvent by spin coating or use of an ink jet print apparatus.

15                    Above the organic EL media **210**, a second electrode **220** is formed. For a configuration where the light is viewed through the substrate, as shown, this electrode is preferably highly reflective and can be composed of a metal such as aluminum or silver or magnesium silver alloy. However, in an alternate embodiment where the light is viewed in the opposite direction, this electrode should be highly 20 transparent and constructed of thin metals, such as silver with a thickness less than 25 nm, or transparent conductive oxides such as indium tin oxide, or combinations thereof. The second electrode **220** can also include an electron injecting layer (not shown) composed of a material such as lithium to aid in the injection of electrons. When a region of organic EL media **210** is stimulated by an electrical current between 25 a first electrode, such as first electrode **181**, and second electrode **220**, the region of organic EL media **210** produces light emission.

                          Most OLED displays are sensitive to moisture or oxygen, or both, so they are commonly sealed with an encapsulating means (not shown) in an inert atmosphere such as nitrogen or argon using metal or glass covers, along with a 30 desiccant such as alumina, bauxite, calcium sulfate, clays, silica gel, zeolites, alkaline metal oxides, alkaline earth metal oxides, sulfates, or metal halides and

perchlorates. Methods for encapsulation and desiccation include, but are not limited to, those described in U.S. Patent 6,226,890. In addition, barrier layers such as SiO<sub>x</sub>, Teflon, and alternating inorganic/polymeric layers are known in the art for encapsulation and can be applied to the present invention by one skilled in the art.

5 The examples described in FIG. 1 and FIG. 3 show the pixels arranged in a stripe pattern. A stripe pattern has the pixels of the same color aligned in the same column or row. However, the present invention is not limited to this case and alternate patterns where different colored pixels are arranged in the same columns or same rows can also be applied to the present invention. One pixel arrangement 10 pattern that is particularly useful is a quad pattern where the four differently colored pixels are arranged in a rectangular fashion involving two rows and two columns. Quad patterns are advantageous in that the all four differently colored pixels are close to each other, thereby reducing the perception of band defects when one or more of the pixels are not illuminated in an image or portion of an image.

15 A layout diagram for the portions of drive circuitry used to drive a quad pattern arrangement of three gamut-pixels, including pixel **20r**, pixel **20g**, and pixel **20b**, and one within-gamut-pixel, pixel **20w** according to an alternate embodiment of the present invention is shown in FIG. 5. Pixel **20r**, pixel **20g**, pixel **20b**, and pixel **20w** can be constructed to emit red (R) light, green (G) light, blue (B) 20 light, and (W) light, respectively. However, the present invention is not limited to these specific colors and other colors can also be applied to the present invention by one skilled in the art.

25 In order to provide a source of electric power to pixel **20r**, pixel **20g**, pixel **20b**, and pixel **20w**, two different power lines are provided including power line **111x** and power line **111w**. As in previous examples, the within-gamut-pixel, which is pixel **20w**, is electrically connected to power line **111w**. Specifically, power transistor **140w** is electrically connected to power line **111w** by way of a via as shown. In this alternate embodiment, the gamut-pixels, such as pixel **20r**, pixel **20g**, and pixel **20b** are connected to power line **111x**. Power line **111w** and power line **111x** are 30 electrically connected to two different voltage

sources (not shown) so that the magnitude of the voltage applied to the within-gamut-pixel is reduced compared to that of the gamut-pixels connected to power line **111x**.

In order to allow power line **111x** to be connected to pixel **20g**, power line **111w** should be crossed. This is preferably accomplished by conductive bridge **144** that is constructed in a different conductor layer than that of the power lines and is connected to power line **111x** through via **149** and to the power transistors of the pixels by via **147r** and via **147g**. It is preferable that the conductive bridge **144** be constructed in the same conductor layer as the select lines. Similarly, a connection should be made between data line **112r** and select transistor **120r** which crosses data line **112b**. This is achieved using conductive bridge **124**, which electrically connects to data line **112r** by way of via **125** and to select transistor **120r** by way of via **127**. Conductive bridge **124** is constructed in a different conductor layer than the data lines, preferably the same conductor layer as the select lines. A similar conductor bridge is provided for pixel **20g** as shown.

Since this arrangement provides only two power lines for the four differently colored pixels compared to the four shown for the stripe pattern of FIG. 3, the space occupied on the substrate by the power lines is reduced. Therefore, the pixels can be packed more densely, thereby enabling higher resolution displays. Also, particularly for the case where light is viewed through the substrate, the resolution can alternately be kept constant, and the size of the emitting areas of the pixels can be increased.

**PARTS LIST**

10b	light-emitting diode
10g	light-emitting diode
5 10r	light-emitting diode
10w	light-emitting diode
20b	pixel
20g	pixel
20r	pixel
10 20w	pixel
30	pixel region
40	connector region
41	connector pad
42	connector pad
15 43	connector pad
50	select line driver
60	data line driver
100	substrate
111b	power line
20 111g	power line
111r	power line
111w	power line
111x	power line
112b	data line
25 112g	data line
112r	data line
112w	data line
113	select line
114	capacitor line
30 120r	select transistor
121	first semiconductor region

**PARTS LIST (con't)**

	122	via
	124	conductive bridge
5	125	via
	127	via
	130r	storage capacitor
	140r	power transistor
	140w	power transistor
10	141	second semiconductor region
	142	via
	143	power transistor gate
	144	conductive bridge
	145	via
15	146	via
	147g	via
	147r	via
	149	via
	160	interpixel dielectric layer
20	181	first electrode
	182	opening
	200	active matrix circuitry layers
	202	insulating layer
	204	insulating layer
25	207	insulating layer
	210	organic EL media
	211	hole injecting layer
	212	hole transporting layer
	213	light-emitting layer
30	214	electron transporting layer
	220	second electrode

**PARTS LIST (con't)**

	230r	color filter element
	230g	color filter element
5	230b	color filter element
	230w	transparent filler
	280b	light emission
	280g	light emission
	280r	light emission
10	280w	light emission

**CLAIMS:**

1. An OLED display for producing a multicolor image, comprising:

5 a) a plurality of pixels including three different colored addressable gamut-pixels and a fourth addressable within-gamut-pixel, each pixel having a separately addressable organic light-emitting diode with first and second electrodes and one or more organic light emissive layers provided between the electrodes;

10 b) active matrix circuitry including a separate power transistor for at least two of the three different colored addressable gamut-pixels for regulating current between a first and second voltage source through the organic light-emitting diode of the colored addressable gamut-pixel; and

15 c) the active matrix circuitry including a power transistor for the fourth addressable within-gamut-pixel for regulating current between a third and fourth voltage source through the organic light-emitting diode of the fourth addressable within-gamut-pixel wherein at least three of the first, second, third, and fourth voltage sources provide different voltage levels.

20 2. An OLED display for producing a multicolor image, comprising:

25 a) a plurality of pixels including three different colored addressable gamut-pixels and a fourth addressable within-gamut-pixel, each pixel having a separately addressable organic light-emitting diode with first and second electrodes and one or more organic light emissive layers provided between the electrodes;

30 b) active matrix circuitry including a separate power transistor for at least two of the three different colored addressable gamut-pixels for regulating current between a first and second voltage source through the organic light-emitting diode of the colored addressable gamut-pixel;

c) the active matrix circuitry including a power transistor for the fourth addressable within-gamut-pixel for regulating current between a third and fourth voltage source through the organic light-emitting diode of the fourth addressable within-gamut-pixel; and

5 d) wherein the magnitude of the difference between the voltage levels of the third and fourth voltage sources is less than the magnitude of the difference between the voltage levels of the first and second voltage sources.

10 3. The OLED display of claim 2 wherein the three different colored addressable gamut-pixels respectively produce red, green, and blue light and the fourth addressable within-gamut-pixel produces white light.

15 4. The OLED display of claim 2 wherein the active matrix circuitry includes a separate power transistor for the three different colored addressable gamut-pixels for regulating current between the first and second voltage source through the organic light-emitting diode of the colored addressable gamut-pixel.

20 5. The OLED display of claim 2 wherein the second and fourth voltage sources are the same.

25 6. The OLED display of claim 2 wherein a power line is associated with the power transistor of each different colored addressable gamut-pixel to provide current from the first voltage source through the power transistor and into the corresponding organic light-emitting diode to the second voltage source.

7. The OLED display of claim 6 wherein the power lines associated with the power transistor of each of the different colored addressable gamut-pixels are connected together.

8. The OLED display of claim 6 wherein the power lines associated with the power transistor of the different colored addressable gamut-pixels are connected together on one side of the display.

5 9. The OLED display of claim 2 wherein a power line is associated with the power transistor of the fourth addressable within-gamut-pixel to provide current from the third voltage source through the power transistor and into the corresponding organic light-emitting diode to the fourth voltage source.

10 10. The OLED display of claim 9 further including a plurality of fourth addressable within-gamut-pixels and each of the power lines associated with the plurality of fourth addressable within-gamut-pixels are connected together.

15 11. The OLED display of claim 9 further including a plurality of fourth addressable within-gamut-pixels and each of the power lines associated with the plurality of fourth addressable within-gamut-pixels are connected together on one side of the display.

20 12. An OLED display for producing a multicolor image, comprising:

- a) a plurality of pixels including three different colored addressable gamut-pixels and a fourth addressable within-gamut-pixel, each pixel having a separately addressable organic light-emitting diode with first and second electrodes and one or more organic light emissive layers provided between the electrodes;
- b) active matrix circuitry including a separate power transistor for at least two of the three different colored addressable gamut-pixels for regulating current through the organic light-emitting diode of the colored addressable gamut-pixel wherein the power transistors of the at least two of the three different colored addressable gamut-pixels each have a channel region having a first channel width to channel length ratio; and

5 c) the active matrix circuitry including a power transistor for the fourth addressable within-gamut-pixel for regulating current through the organic light-emitting diode of the fourth addressable within-gamut-pixel wherein the power transistor of the fourth addressable within-gamut-pixel has a channel region having a second channel width to channel length ratio and wherein the first and second channel width to channel length ratios are different.

13. The OLED display of claim 12 wherein the first channel width to channel length ratio is greater than the second channel width to channel length ratio.


14. The OLED display of claim 12 wherein the active matrix circuitry includes a separate power transistor for all of the three different colored addressable gamut-pixels for regulating current through the organic light-emitting diode of the colored addressable gamut-pixel wherein all of the separate power transistors of the three different colored addressable gamut-pixels each have a channel region having the same channel width to channel length ratio.

15. The OLED display of claim 12 wherein the separate power  
transistors for at least two of the three different colored addressable gamut-pixels  
regulate current between a first and second voltage source through the organic light-  
emitting diode of the colored addressable gamut-pixel and the power transistor for the  
fourth addressable within-gamut-pixel regulates current between a third and fourth  
voltage source through the organic light-emitting diode of the fourth addressable  
within-gamut-pixel and magnitude of the difference between the voltage levels of the  
third and fourth voltage sources is less than the magnitude of the difference between  
the voltage levels of the first and second voltage sources.


16. The OLED display of claim 15 wherein the second and fourth  
30 voltage sources are the same.

17. The OLED display of claim 12 wherein the three different colored addressable gamut-pixels respectively produce red, green, and blue light and the fourth addressable within-gamut-pixel produces white light.

1/5

**FIG. 1**

2/5

**FIG. 2**

3/5




FIG. 3

4/5





FIG. 4

5/5



## INTERNATIONAL SEARCH REPORT

International application No  
PCT/US2006/005393

A. CLASSIFICATION OF SUBJECT MATTER  
INV. G09G3/32

According to International Patent Classification (IPC) or to both national classification and IPC

## B. FIELDS SEARCHED

Minimum documentation searched (classification system followed by classification symbols)  
G09G

Documentation searched other than minimum documentation to the extent that such documents are included in the fields searched

Electronic data base consulted during the international search (name of data base and, where practical, search terms used)

EPO-Internal

## C. DOCUMENTS CONSIDERED TO BE RELEVANT

Category*	Citation of document, with indication, where appropriate, of the relevant passages	Relevant to claim No.
P,X	WO 2005/088593 A (KONINKLIJKE PHILIPS ELECTRONICS N.V; HOPPENBROUWERS, JURGEN, J., L; VA) 22 September 2005 (2005-09-22) page 2, line 16 - page 5, line 32 page 7, line 23 - page 11, line 15; figures 1,2,4,7 -----	1
Y	EP 1 473 772 A (EASTMAN KODAK COMPANY) 3 November 2004 (2004-11-03) paragraphs [0008], [0009], [0017] - [0025], [0035] - [0037]; figures 11,12,14,15 -----	1-11
Y	US 6 771 028 B1 (WINTERS DUSTIN) 3 August 2004 (2004-08-03) cited in the application column 3, line 43 - column 5, line 37; figure 1 -----	1-11
	-/-	

Further documents are listed in the continuation of Box C.

See patent family annex.

## \* Special categories of cited documents :

- "A" document defining the general state of the art which is not considered to be of particular relevance
- "E" earlier document but published on or after the international filing date
- "L" document which may throw doubts on priority claim(s) or which is cited to establish the publication date of another citation or other special reason (as specified)
- "O" document referring to an oral disclosure, use, exhibition or other means
- "P" document published prior to the international filing date but later than the priority date claimed

- "T" later document published after the international filing date or priority date and not in conflict with the application but cited to understand the principle or theory underlying the invention
- "X" document of particular relevance; the claimed invention cannot be considered novel or cannot be considered to involve an inventive step when the document is taken alone
- "Y" document of particular relevance; the claimed invention cannot be considered to involve an inventive step when the document is combined with one or more other such documents, such combination being obvious to a person skilled in the art.
- "&" document member of the same patent family

Date of the actual completion of the international search  5 July 2006	Date of mailing of the international search report  26.01.2007
Name and mailing address of the ISA/ European Patent Office, P.B. 5818 Patentlaan 2 NL - 2280 HV Rijswijk Tel. (+31-70) 340-2040, Tx. 31 651 epo nl, Fax: (+31-70) 340-3016	Authorized officer  Harke, Michael

## INTERNATIONAL SEARCH REPORT

International application No.  
PCT/US2006/005393

### Box II Observations where certain claims were found unsearchable (Continuation of item 2 of first sheet)

This International Search Report has not been established in respect of certain claims under Article 17(2)(a) for the following reasons:

1.  Claims Nos.: because they relate to subject matter not required to be searched by this Authority, namely:
  
2.  Claims Nos.: because they relate to parts of the International Application that do not comply with the prescribed requirements to such an extent that no meaningful International Search can be carried out, specifically:
  
3.  Claims Nos.: because they are dependent claims and are not drafted in accordance with the second and third sentences of Rule 6.4(a).

### Box III Observations where unity of invention is lacking (Continuation of item 3 of first sheet)

This International Searching Authority found multiple inventions in this international application, as follows:

see additional sheet

1.  As all required additional search fees were timely paid by the applicant, this International Search Report covers all searchable claims.
  
2.  As all searchable claims could be searched without effort justifying an additional fee, this Authority did not invite payment of any additional fee.
  
3.  As only some of the required additional search fees were timely paid by the applicant, this International Search Report covers only those claims for which fees were paid, specifically claims Nos.:
  
4.  No required additional search fees were timely paid by the applicant. Consequently, this International Search Report is restricted to the invention first mentioned in the claims; it is covered by claims Nos.:

1-11

#### Remark on Protest

The additional search fees were accompanied by the applicant's protest.

No protest accompanied the payment of additional search fees.

FURTHER INFORMATION CONTINUED FROM PCT/ISA/ 210

This International Searching Authority found multiple (groups of) inventions in this international application, as follows:

1. claims: 1-11

The first invention concerns an OLED display for producing a multicolor image, comprising:

- a) a plurality of pixels including three different colored addressable gamut-pixels and a fourth addressable within-gamut-pixel, each pixel having a separately addressable organic light-emitting diode with first and second electrodes and one or more organic light emissive layers provided between the electrodes;
- b) active matrix circuitry including a separate power transistor for at least two of the three different colored addressable gamut-pixels for regulating current through the organic light-emitting diode of the colored addressable gamut-pixel; and
- c) the active matrix circuitry including a power transistor for the fourth addressable within-gamut-pixel for regulating current through the organic light-emitting diode of the fourth addressable within-gamut-pixel

wherein the current through the organic light-emitting diode of the colored addressable gamut-pixel is between a first and second voltage source, the current through the organic light-emitting diode of the fourth addressable within-gamut-pixel is between a third and fourth voltage source, and the magnitude of the difference between the voltage levels of the third and fourth voltage sources is less than the magnitude of the difference between the voltage levels of the first and second voltage sources.

---

2. claims: 12-17

FURTHER INFORMATION CONTINUED FROM PCT/ISA/ 210

The second invention concerns an OLED display for producing a multicolor image, comprising:

- a) a plurality of pixels including three different colored addressable gamut-pixels and a fourth addressable within-gamut-pixel, each pixel having a separately addressable organic light-emitting diode with first and second electrodes and one or more organic light emissive layers provided between the electrodes;
- b) active matrix circuitry including a separate power transistor for at least two of the three different colored addressable gamut-pixels for regulating current through the organic light-emitting diode of the colored addressable gamut-pixel; and
- c) the active matrix circuitry including a power transistor for the fourth addressable within-gamut-pixel for regulating current through the organic light-emitting diode of the fourth addressable within-gamut-pixel wherein the power transistors of the at least two of the three different colored addressable gamut-pixels each have a channel region having a first channel width to channel length ratio, the power transistor of the fourth addressable within-gamut-pixel has a channel region having a second channel width to channel length ratio, and the first and second channel width to channel length ratios are different.

---

## INTERNATIONAL SEARCH REPORT

International application No  
PCT/US2006/005393

## C(Continuation). DOCUMENTS CONSIDERED TO BE RELEVANT

Category*	Citation of document, with indication, where appropriate, of the relevant passages	Relevant to claim No.
Y	US 2003/122496 A1 (LEE HAN-SANG ET AL) 3 July 2003 (2003-07-03) paragraphs [0020], [0021], [0036] - [0050]; figures 2,8,9 -----	1-11
Y	WO 2004/021327 A (E.I. DU PONT DE NEMOURS AND COMPANY) 11 March 2004 (2004-03-11) abstract; figure 6 -----	1-11

# INTERNATIONAL SEARCH REPORT

Information on patent family members

International application No  
PCT/US2006/005393

Patent document cited in search report	Publication date	Patent family member(s)		Publication date
WO 2005088593	A 22-09-2005	NONE		
EP 1473772	A 03-11-2004	CN JP KR US	1551383 A 2004335467 A 20040094335 A 2004217694 A1	01-12-2004 25-11-2004 09-11-2004 04-11-2004
US 6771028	B1 03-08-2004	CN EP JP KR	1551079 A 1473690 A2 2004334204 A 20040094353 A	01-12-2004 03-11-2004 25-11-2004 09-11-2004
US 2003122496	A1 03-07-2003	KR	20030058210 A	07-07-2003
WO 2004021327	A 11-03-2004	AU CA CN EP JP KR	2003265682 A1 2496571 A1 1689063 A 1532609 A1 2005536778 T 20050058473 A	19-03-2004 11-03-2004 26-10-2005 25-05-2005 02-12-2005 16-06-2005

专利名称(译)	OLED显示器具有改进的有源矩阵电路		
公开(公告)号	<a href="#">EP1864277A1</a>	公开(公告)日	2007-12-12
申请号	EP2006844072	申请日	2006-02-16
[标]申请(专利权)人(译)	伊斯曼柯达公司		
申请(专利权)人(译)	伊士曼柯达公司		
当前申请(专利权)人(译)	全球OLED科技有限责任公司		
[标]发明人	WINTERS DUSTIN LEE LUDWICKI JOHN EDWARD		
发明人	WINTERS, DUSTIN, LEE LUDWICKI, JOHN, EDWARD		
IPC分类号	G09G3/32		
CPC分类号	G09G3/3233 G09G2300/0452 G09G2300/0809 G09G2300/0842 G09G2330/021 H01L27/3213 H01L27/3244 H01L27/3276		
优先权	11/069652 2005-03-01 US		
外部链接	<a href="#">Espacenet</a>		

**摘要(译)**

用于产生多色图像的OLED显示器包括多个像素，所述多个像素包括三个不同颜色的可寻址色域 - 像素 ( 20r , 20g , 20b ) 和第四可寻址色域内像素 ( 20w )，每个像素具有可单独寻址的有机光 - 发光二极管 ( 10r )，具有第一和第二电极以及设置在电极之间的一个或多个有机发光层;有源矩阵电路，包括用于三个不同颜色的可寻址色域像素中的至少两个的单独的功率晶体管 ( 140r )，用于通过有色可寻址的有机发光二极管调节第一和第二电压源 ( V1 , Vc ) 之间的电流;有源矩阵电路包括用于第四可寻址色域内像素的功率晶体管，用于通过第四可寻址色域内像素的有机发光二极管调节第三和第四电压源 ( V2 , Vc ) 之间的电流，其中第一，第二，第三和第四电压源中的至少三个提供不同的电压电平。