



(11) **EP 2 416 396 B1**

(12) **EUROPEAN PATENT SPECIFICATION**

(45) Date of publication and mention of the grant of the patent:
13.05.2015 Bulletin 2015/20

(51) Int Cl.:
H01L 51/50 (2006.01) **C09K 11/06** (2006.01)
H05B 33/26 (2006.01)

(21) Application number: **10758516.8**

(86) International application number:
PCT/JP2010/055177

(22) Date of filing: **25.03.2010**

(87) International publication number:
WO 2010/113743 (07.10.2010 Gazette 2010/40)

(54) **LIGHT-EMITTING ELEMENT MATERIAL AND LIGHT-EMITTING ELEMENT**

MATERIAL FÜR EIN LICHEMITTIERENDES ELEMENT UND LICHEMITTIERENDES ELEMENT
MATÉRIAU D'ÉLÉMENT ÉLECTROLUMINESCENT ET ÉLÉMENT ÉLECTROLUMINESCENT

(84) Designated Contracting States:
AT BE BG CH CY CZ DE DK EE ES FI FR GB GR HR HU IE IS IT LI LT LU LV MC MK MT NL NO PL PT RO SE SI SK SM TR

(30) Priority: **30.03.2009 JP 2009081410**
24.12.2009 JP 2009292004

(43) Date of publication of application:
08.02.2012 Bulletin 2012/06

(73) Proprietor: **Toray Industries, Inc.**
Tokyo 103-8666 (JP)

(72) Inventors:
• **NAKANO, Yohei**
Otsu-shi
Shiga 520-8558 (JP)
• **SUGIMOTO, Kazunori**
Otsu-shi
Shiga 520-8558 (JP)
• **NAGAO, Kazumasa**
Otsu-shi
Shiga 520-8558 (JP)
• **TANAKA, Daisaku**
Otsu-shi
Shiga 520-8558 (JP)

• **TOMINAGA, Tsuyoshi**
Otsu-shi
Shiga 520-8558 (JP)

(74) Representative: **Hager, Thomas Johannes**
Hoefer & Partner
Patentanwälte
Pilgersheimer Strasse 20
81543 München (DE)

(56) References cited:
EP-A1- 1 852 486 **EP-A1- 1 942 171**
EP-A1- 2 296 204 **EP-A2- 1 345 278**
WO-A1-2006/090772 **WO-A1-2007/029798**
WO-A1-2008/108256 **JP-A- 2004 319 424**
JP-A- 2004 319 424 **JP-A- 2009 246 354**
US-A1- 2004 234 809 **US-A1- 2006 240 283**

• **XING Y ET AL: "Carbazole-pyrene-based organic emitters for electroluminescent device",**
CHEMICAL PHYSICS LETTERS, ELSEVIER BV,
NL, vol. 408, no. 1-3, 7 June 2005 (2005-06-07),
pages 169-173, XP027647103, ISSN: 0009-2614,
DOI: 10.1016/J.CPLETT.2005.04.019 [retrieved on
2005-06-07]

EP 2 416 396 B1

Note: Within nine months of the publication of the mention of the grant of the European patent in the European Patent Bulletin, any person may give notice to the European Patent Office of opposition to that patent, in accordance with the Implementing Regulations. Notice of opposition shall not be deemed to have been filed until the opposition fee has been paid. (Art. 99(1) European Patent Convention).

Description

TECHNICAL FIELD

5 **[0001]** The present invention relates to a light emitting device which can convert an electric energy into light, and the light emitting device can be utilized in the fields of display equipments, flat panel displays, backlight, illumination, interiors, signs, advertising displays, electrophotographic machines and light signal generators.

BACKGROUND ART

10 **[0002]** Researches on an organic thin-film light emitting device in which electrons injected from a cathode and holes injected from an anode emit light when they are recombined in an organic fluorescent body held by both electrodes have been actively conducted in recent years. This light emitting device is characteristic for high luminance light emission in the form of a thin type and under a low driving voltage, and multicolor light emission due to selection of a fluorescent material, and has been paid attention.

15 **[0003]** Such researches have been studied by many research institutes since C. W. Tang et al. of Kodak Co., Ltd. showed that an organic thin-film device emits light at high luminance. A representative constitution of the organic thin-film light emitting device presented by the research group of Kodak Co., Ltd. is one such that a hole transporting diamine compound, 8-hydroxyquinoline aluminum which serves as an emissive layer, and Mg : Ag as a cathode are sequentially provided on an ITO glass substrate, and can emit green light of 1,000 cd/m² at a driving voltage of around 10V (see Non-Patent Document 1).

20 **[0004]** Since the organic thin-film light emitting device can afford a variety of light-emitted colors by using various fluorescent materials in an emissive layer, and studies of practical realization for displays and the like have been actively conducted. Among emissive materials emitting three primary colors, a research on a green emissive material is most advanced and, currently in a red emissive material and a blue emissive material, a research has been conducted intensively aiming at improvement in properties.

25 **[0005]** It is necessary that the organic thin-film light emitting device satisfies improvement in a luminance efficiency, reduction in a driving voltage and improvement in durability. Among them, when the luminance efficiency is low, outputting of an image requiring high luminance becomes impossible, and the amount of power consumed for outputting desired luminance is increased. For example, in order to improve the luminance efficiency, a variety of emissive materials have been developed (see, e.g., Patent Documents 1 to 4). In addition, electron transporting materials having pyrene as a basic skeleton have been developed (see, e.g., Patent Documents 5 to 7). In addition, techniques of doping a material used as an electron transporting layer with an alkali metal have been developed (see, e.g., Patent Documents 8 to 12).

35 PRIOR ART DOCUMENTS

PATENT DOCUMENTS

[0006]

- 40 Patent Document 1: International Publication WO 2007/29798 pamphlet
 Patent Document 2: International Publication WO 2008/108256 pamphlet
 Patent Document 3: JP-A No. 2007-131723 gazette
 Patent Document 4: International Publication WO 2006/90772 pamphlet
 45 Patent Document 5: European Patent Publication No. 1808912
 Patent Document 6: Chinese Patent Publication No. 101407493
 Patent Document 7: International Publication WO 2010/001817 pamphlet
 Patent Document 8: JP-A No. 2000-348864 gazette
 Patent Document 9: JP-A No. 2004-277377 gazette
 50 Patent Document 10: JP-A No. 2003-347060 gazette
 Patent Document 11: JP-A No. 2002-352961 gazette
 Patent Document 12: JP-A No. 2004-2297 gazette

NON-PATENT DOCUMENT

55 **[0007]** Non-Patent Document 1: "Applied Physics Letters", (USA), 1987, Vol.51, No.12, pp.913-915
 EP 1 942 171 A1 and EP 2 296 204 A1 disclose a light emitting device material containing a specific pyrene compound which enables production of a light emitting device material having high efficiency and excellent durability, and a light

emitting device. The pyrene compound includes a carbazolyl group at the pyrene skeleton. However, pyrene compounds comprising an aromatic heterocyclic group containing an electron accepting nitrogen are not disclosed.

JP 2004-319424 A discloses a device structure with low driving voltage by improving an electron transporting layer and an electron injection layer when forming an organic electroluminescent display device. This reference further discloses an organic electroluminescent display device having improved stability and life. This device comprises a first electrode and a second electrode formed on a substrate and at least one organic film layer including a light emitting layer between the first and second electrodes. A first organic film layer in contact with the second electrode layer is formed of an organic-metal complex compound, and a second organic film layer containing an organic-metal complex compound and a charge transporting layer material is included between the first organic film layer and the light emitting layer.

EP 1 852 486 A1 describes a light-emitting device material characterized by containing a specific pyrene compound. The pyrene compound comprises a directly bond heteroaryl group.

SUMMARY OF THE INVENTION

PROBLEMS TO BE SOLVED BY THE INVENTION

[0008] However, as described above, it is necessary that the organic thin-film light emitting device satisfies improvement in a luminance efficiency, reduction in a driving voltage and improvement in durability, particularly regarding a blue light emitting device, there are a few blue emissive materials which provide a device excellent in durability and having high reliance.


[0009] In addition, even when a compound used in an electron transporting layer is improved, conventionally known combinations as in Patent Documents 7 to 11 are insufficient in realization of both of low voltage driving and a high luminance efficiency.

[0010] An object of the present invention is to solve such conventional problems, and to provide a light emitting device material which enables an organic thin-film light emitting device realizing both of a high luminance efficiency and a low driving voltage, and a light emitting device using the same.

MEANS FOR SOLVING THE PROBLEMS

[0011] The present invention relates to a light emitting device material including a pyrene compound represented by the following general formula (1):

[Chemical formula 1]



[0012] R¹ to R⁷ may be the same or different, and are each selected from the group consisting of hydrogen, an alkyl group, a cycloalkyl group, a heterocyclic group, an alkenyl group, a cycloalkenyl group, an alkynyl group, an alkoxy group, an alkylthio group, an aryloxy group, an arylthioether group, an aryl group, a heteroaryl group, a halogen, a carbonyl group, a carboxyl group, an oxycarbonyl group, a carbamoyl group, an amino group, a silyl group, and -P(=O)R⁸R⁹. R⁸ and R⁹ are each an aryl group or a heteroaryl group, and adjacent substituents may form a ring. L¹ and L² may be the same or different, and L¹ is an arylene group and L² is a single bond or an arylene group. X is selected from the group consisting of an alkyl group, an aryl group, and a heteroaryl group. Ar¹ is an aromatic heterocyclic group containing electron-accepting nitrogen, and Ar² is an aryl group or a heteroaryl group, provided that when Ar² is a heteroaryl group, a dibenzofuranyl group, a dibenzothiophenyl group and a carbazolyl group are excluded.


ADVANTAGES OF THE INVENTION

[0013] According to the present invention, an organic electric field light emitting device realizing both of a high luminance efficiency and a low driving voltage can be provided.

MODE FOR CARRYING OUT THE INVENTION

[0014] A pyrene compound represented by the general formula (1) in the present invention will be described in detail.

[Chemical formula 2]



[0015] R¹ to R⁷ may be the same or different, and are each selected from the group consisting of hydrogen, an alkyl group, a cycloalkyl group, a heterocyclic group, an alkenyl group, a cycloalkenyl group, an alkynyl group, an alkoxy group, an alkylthio group, an aryloxy group, an arylthio group, an aryl group, a heteroaryl group, a halogen, a carbonyl group, a carboxyl group, an oxycarbonyl group, a carbamoyl group, an amino group, a silyl group, and -P(=O)R⁸R⁹. R⁸ and R⁹ are each an aryl group or a heteroaryl group, and adjacent substituents may form a ring. L¹ and L² may be the same or different, and L¹ is an arylene group and L² is a single bond or an arylene group. X is selected from the group consisting of an alkyl group, an aryl group and a heteroaryl group. Ar¹ is an aromatic heterocyclic group containing an electron-accepting nitrogen, and Ar² is an aryl group or a heteroaryl group, provided that when Ar² is a heteroaryl group, a dibenzofuranyl group, a dibenzothiophenyl group and a carbazolyl group are excluded.

[0016] Among these substituents, hydrogen may be deuterium. In addition, the alkyl group denotes a saturated aliphatic hydrocarbon group such as a methyl group, an ethyl group, a n-propyl group, an isopropyl group, a n-butyl group, a sec-butyl group, or a tert-butyl group, and this may or may not have a substituent. An additional substituent when substituted is not particularly limited, and examples thereof include an alkyl group, an aryl group, and a heteroaryl group, and this point is also common to the following descriptions. In addition, the number of carbon atoms in the alkyl group is not particularly limited, but from the viewpoints of easy availability and cost, it is in a range of usually 1 or more and 20 or less, more preferably 1 or more and 8 or less.

[0017] The cycloalkyl group denotes a saturated alicyclic hydrocarbon group such as a cyclopropyl group, a cyclohexyl group, a norbornyl group or an adamantyl group, and this may or may not have a substituent. The number of carbon atoms in portion of an alkyl group is not particularly limited, but is usually in a range of 3 or more and 20 or less.

[0018] The heterocyclic group denotes an aliphatic ring having an atom other than carbon in the ring, such as a pyran ring, a piperidine ring and cyclic amide, and this may or may not have a substituent. The number of carbon atoms in the heterocyclic group is not particularly limited, but is usually in a range of 2 or more and 20 or less.

[0019] The alkenyl group denotes an unsaturated aliphatic hydrocarbon group containing a double bond, such as a vinyl group, an allyl group or a butadienyl group, and this may or may not have a substituent. The number of carbon atoms in the alkenyl group is not particularly limited, but is usually in a range of 2 or more and 20 or less.

[0020] The cycloalkenyl group denotes an unsaturated alicyclic hydrocarbon group containing a double bond, such as a cyclopentenyl group, a cyclopentadienyl group or a cyclohexenyl group, and this may or may not have a substituent.

[0021] The alkynyl group denotes an unsaturated aliphatic hydrocarbon group containing a triple bond, such as an ethynyl group, and this may or may not have a substituent. The number of carbon atoms in the alkynyl group is not particularly limited, but is usually in a range of 2 or more and 20 or less.

[0022] The alkoxy group denotes a functional group in which an aliphatic hydrocarbon group is bound via an ether group, such as a methoxy group, an ethoxy group or a propoxy group, and this aliphatic hydrocarbon group may or may not have a substituent. The number of carbon atoms in the alkoxy group is not particularly limited, but is usually in a range of 1 or more and 20 or less.

[0023] The alkylthio group is a group in which the oxygen atom of an ether bond of the alkoxy group is substituted with a sulfur atom. The hydrocarbon group of the alkylthio group may or may not have a substituent. The number of carbon atoms in the alkylthio group is not particularly limited, but is usually in a range of 1 or more and 20 or less.

[0024] The aryloether group denotes a functional group in which an aromatic hydrocarbon group is bound via an ether bond, such as a phenoxy group, and the aromatic hydrocarbon group may or may not have a substituent. The number of carbon atoms in the aryloether group is not particularly limited, but is usually in a range of 6 or more and 40 or less.

[0025] The arylthioether group is a group in which the oxygen atom of an ether bond of the aryloether group is substituted with a sulfur atom. The aromatic hydrocarbon group in the aryloether group may or may not have a substituent. The number of carbon atoms in the aryloether group is not particularly limited, but is usually in a range of 6 or more and 40 or less.

[0026] The aryl group denotes an aromatic hydrocarbon group such as a phenyl group, a naphthyl group, a biphenyl group, a phenanthryl group, a terphenyl group, or a pyrenyl group. The aryl group may or may not have a substituent. The number of carbon atoms in the aryl group is not particularly limited, but is usually in a range of 6 or more and 40 or less.

[0027] The heteroaryl group denotes a cyclic aromatic group having one or a plurality of atoms other than carbon in the ring, such as a furanyl group, a thiophenyl group, a pyridyl group, a quinolinyl group, an isoquinolinyl group, a pyrazinyl group, a pyrimidyl group, a naphthyridyl group, a benzofuranyl group, a benzothiophenyl group, an indolyl group, dibenzofuranyl group, a dibenzothiophenyl group, or a carbazolyl group, and this may be unsubstituted or substituted. The number of carbon atoms in the heteroaryl group is not particularly limited, but is usually in a range of 2 or more and 30 or less.

[0028] The halogen atom denotes fluorine, chlorine, bromine or iodine.

[0029] The carbonyl group, the carboxyl group, the oxycarbonyl group, the carbamoyl group, the amino group, and the phosphine oxide group may or may not have a substituent, and examples of the substituent include an alkyl group, a cycloalkyl group, an aryl group, and a heteroaryl group, and these substituents may be further substituted.

[0030] The silyl group denotes a functional group having a bond with a silicon atom, such as a trimethylsilyl group, and this may or may not have a substituent. The number of carbon atoms in the silyl group is not particularly limited, but is usually in a range of 3 or more and 20 or less. In addition, the number of silicon is usually in a range of 1 or more and 6 or less.

[0031] The arylene group denotes a divalent group derived from an aromatic hydrocarbon group, such as a phenyl group, a naphthyl group, a biphenyl group, a phenanthryl group, a terphenyl group, or a pyrenyl group, and this may or may not have a substituent. The number of carbon atoms in the arylene group is not particularly limited, but is usually in a range of 6 or more and 40 or less. When L¹ and L² in the general formula (1) are each an arylene group, the arylene group may or may not have a substituent, and the number of carbon atoms including a substituent is in a range of 6 or more and 60 or less.

[0032] When adjacent substituents form a ring, arbitrary adjacent two substituents (e.g., R² and R³ in the general formula (1)) can be bound to each other to form a conjugated or non-conjugated fused ring. The fused ring may contain nitrogen, oxygen, sulfur, phosphorus and silicon atoms in addition to carbon as a constituent element of the fused ring, and may be further fused with another ring.

[0033] The aromatic heterocyclic group containing electron-accepting nitrogen denotes a cyclic aromatic group having at least one or a plurality of electron-accepting nitrogen atoms as an atom other than carbon in the ring, among the heteroaryl groups, such as a pyridyl group, a quinolinyl group, an isoquinolinyl group, a quinoxanyl group, a pyrazinyl group, a pyrimidyl group, a pyridazinyl group, a phenanthrolinyl group, an imidazopyridyl group, a triazolyl group, an acridyl group, a benzoimidazolyl group, a benzooxazolyl group, and a benzothiazolyl group. The aromatic heterocyclic group containing electron-accepting nitrogen may be unsubstituted or substituted. The number of electron-accepting nitrogen contained in the aromatic heterocyclic group containing electron-accepting nitrogen is not particularly limited, but is usually in a range of 1 or more and 3 or less. In addition, when the aromatic heterocyclic group containing electron-accepting nitrogen is substituted, the substituent is not particularly limited, but examples thereof include an alkyl group, an aryl group, and a heteroaryl group.

[0034] The electron-accepting nitrogen referred herein represents a nitrogen atom which forms a multiple bond between adjacent atoms. Since a nitrogen atom has high electronegativity, the multiple bond has an electron-accepting nature. For this reason, the aromatic heterocyclic ring containing electron-accepting nitrogen has high electron affinity. The pyrene compound of the present invention having electron-accepting nitrogen makes easy acceptance of electrons from a cathode having high electron affinity, and lower voltage driving becomes possible. In addition, since supply of electrons to an emissive layer is increased and a recombining probability is increased, a luminance efficiency is increased. The number of carbon atoms in the aromatic heterocyclic group containing electron-accepting nitrogen is not particularly limited, but is usually in a range of 2 or more and 30 or less. The connecting position of the aromatic heterocyclic group containing electron-accepting nitrogen may be any position and, for example, in the case of a pyridyl group, the position may be any of a 2-pyridyl group, a 3-pyridyl group or a 4-pyridyl group.

[0035] Among the aforementioned substituents, preferable examples of X include a methyl group, an ethyl group, a n-propyl group, an isopropyl group, a n-butyl group, a sec-butyl group, a tert-butyl group, an adamantyl group, a phenyl

group, a naphthyl group, a biphenyl group, a terphenyl group, a pyridyl group, a quinolinyl, a pyrazinyl group, a naphthyridyl group, a benzofuranyl group, and a benzothiophenyl group.

[0036] In addition, L¹ and L² are each independently preferably a phenylene group or a naphthylene group. More specific examples thereof include a 1,4-phenylene group, a 1,3-phenylene group, a 2,6-naphthylene group, and a 2,8-naphthylene group, more preferably a 1,4-phenylene group etc.

[0037] Ar¹ is preferably a pyridyl group, a quinolinyl group, an isoquinolinyl group, a quinoxanyl group, a pyrimidyl group, a phenanthrolinyl group, a benzo[d]imidazolyl group, an imidazo[1,2-a]pyridyl group etc. More specific examples thereof include a 2-pyridyl group, a 3-pyridyl group, a 4-pyridyl group, a 2-quinolinyl group, a 3-quinolinyl group, a 6-quinolinyl group, a 1-isoquinolinyl group, a 3-isoquinolinyl group, a 2-quinoxanyl group, a 5-pyrimidyl group, a 2-phenanthrolinyl group, a 1-benzo[d]imidazolyl group, a 2-benzo[d]imidazolyl group, a 2-imidazo[1,2-a]pyridyl group, and a 3-imidazo[1,2-a]pyridyl group, more preferably a 2-pyridyl group, a 3-pyridyl group etc.

[0038] Ar² is preferably a phenyl group, a naphthyl group, a phenanthryl group, a pyridyl group, a quinolinyl group, a quinoxanyl group, a pyrimidyl group, a phenanthrolinyl group, a benzo[d]imidazolyl group, an imidazo[1,2-a]pyridyl group etc. More specific examples thereof include a phenyl group, a 1-naphthyl group, a 2-naphthyl group, a 9-phenanthryl group, a 2-pyridyl group, a 3-pyridyl group, a 4-pyridyl group, a 2-quinolinyl group, a 3-quinolinyl group, a 6-quinolinyl group, a 2-quinoxanyl group, a 5-pyrimidyl group, a 2-phenanthrolinyl group, a 1-benzo[d]imidazolyl group, a 2-benzo[d]imidazolyl group, a 2-imidazo[1,2-a]pyridyl group, and a 3-imidazo[1,2-a]pyridyl group, more preferably a phenyl group, a 1-naphthyl group, a 2-naphthyl group, a 2-pyridyl group, a 3-pyridyl group etc.

[0039] The pyrene compound represented by the general formula (1) has a pyrene skeleton and an aromatic heterocyclic ring containing electron-accepting nitrogen in the molecule. Therefore, it becomes possible to realize both of high electron transporting property and electrochemical stability of the pyrene skeleton and high electron acceptability of the aromatic heterocyclic ring containing electron-accepting nitrogen, and thus, high electron injection transporting ability is exerted.

[0040] Further, introduction of a substituent selected from an alkyl group, an aryl group and a heteroaryl group in the 7-position (X) of the pyrene skeleton suppresses interaction between pyrene skeletons, and improves luminance efficiency and thin-film stability.

[0041] In addition, inter alia, it is preferable that L¹ is an arylene group. Since the aromatic heterocyclic ring containing electron-accepting nitrogen is weak to oxidation, binding via an arylene group rather than direct binding with the pyrene skeleton becomes more stable in electrochemical property. This generates the synergistic effect with high electron transporting property of the pyrene skeleton, and exerts higher electron injection transporting ability.


[0042] For synthesis of the pyrene compound represented by the general formula (1), known methods can be used. Examples of a method of introducing the aromatic heterocyclic ring containing electron-accepting nitrogen into the pyrene skeleton include, but are not limited to, a method of using a coupling reaction of a halogenated pyrene derivative and boronic acid or boronic acid ester of the aromatic heterocyclic ring containing electron-accepting nitrogen under a palladium or nickel catalyst.

[0043] Examples of a method of introducing an alkyl group into the 7-position of the pyrene skeleton include a method using the Friedel-Crafts reaction with halogenated alkyls such as t-BuCl, or a reduction reaction of pyrenecarboxaldehyde derivative or pyrenecarboxylic acid derivative, in the presence of Lewis acids such as AlCl₃. In addition, examples of a method of introducing an aryl group or a heteroaryl group into the 7-position of the pyrene skeleton include, but are not limited to, a method of introducing boronic acid ester into the 2-position of pyrene under an iridium catalyst and, thereafter, using a coupling reaction of pyreneboronic acid ester and halogenated aryl or halogenated heteroaryl under a palladium or nickel catalyst.


[0044] The pyrene compound represented by the general formula (1) is not particularly limited, but specifically the following examples are exemplified. In the following Examples, those formulas marked with "★" do not fall under the scope of the present invention.

[Chemical formula 3]


★[1]




★[2]




★[3]




★[4]




★[5]




★[6]




★[7]




★[8]




★[9]




[10]




[11]




★[12]



★[13]


















★[14]



★[15]




[Chemical formula 4]




[Chemical formula 5]


★ [31]




★ [32]




★ [33]




[34]




★ [35]




★ [36]




★ [37]




★ [38]




★ [39]




★ [40]




★ [41]




★ [42]




[43]




★ [44]



★ [45]




[Chemical formula 6]




[Chemical formula 7]


[81]




[62]




[63]




[64]




[65]




[66]




[67]




[68]




[69]




[70]




[71]




[72]




[73]




[74]




[75]


















[Chemical formula 8]




[Chemical formula 9]



[Chemical formula 10]



[Chemical formula 11]




[Chemical formula 12]


50

55


★ [136]




★ [137]




★ [138]




[139]




★ [140]




★ [141]




[142]




★ [143]




[144]




★ [145]




★ [146]




[147]




★ [148]















[149]




★ [150]



[Chemical formula 13]



[Chemical formula 14]



[0045] The pyrene compound represented by the general formula (1) in the present invention is used as a light emitting device material. Herein, the light emitting device material in the present invention represents a material used in any layer of light emitting devices, and also includes a material used in a protective film layer of a cathode, in addition to materials used in a hole transporting layer, an emissive layer and/or an electron transporting layer, as described later. Use of the pyrene compound represented by the general formula (1) in the present invention in any layer of light emitting devices can obtain a high luminance efficiency and a light emitting device of a low driving voltage.

[0046] Since the pyrene compound represented by the general formula (1) has high electron injection transporting ability, luminance efficiency and thin-film stability, it is preferable that it is used in an emissive layer or an electron transporting layer of a light emitting device. Particularly, since it has excellent electron injection transporting ability, it is preferably used in an electron transporting layer.

[0047] Then, embodiments of the light emitting device of the present invention will be described in detail. The light emitting device of the present invention has an anode and a cathode, and an organic layer interposing between the anode and the cathode, the organic layer includes at least an emissive layer, and the emissive layer emits light by an

electric energy.

[0048] Examples of the lamination constitution of the organic layer include, in addition to a constitution including only of an emissive layer, 1) hole transporting layer/emissive layer/electron transporting layer, 2) emissive layer/electron transporting layer, and 3) hole transporting layer/emissive layer. In addition, each of the layers may be in the form of a single layer or a plurality of layers. When the hole transporting layer and the electron transporting layer have a plurality of layers, layers on sides contacting with an electrode are each referred to as a hole injection layer and an electron injection layer in some cases, but in the following description, unless otherwise is indicated, a hole injection material is included in a hole transporting material, and an electron injection material is included in an electron transporting material, respectively.

[0049] In the light emitting device of the present invention, the anode and the cathode have a role for supplying a sufficient current for light emission of the device, and it is desirable that at least one of them is transparent or translucent in order to take out light. Usually, the anode formed on a substrate is made to be a transparent electrode.

[0050] Examples of a material used in the anode includes, but are not particularly limited to, electrically conductive metal oxides such as tin oxide, indium oxide, indium tin oxide (ITO), and indium zinc oxide (IZO), metals such as gold, silver, and chromium, inorganic electrically conductive substances such as copper iodide, and copper sulfide, and electrically conductive polymers such as polythiophene, polypyrrole, and polyaniline as far as the material is a material which can efficiently inject holes into the organic layer, and is transparent or translucent in order to take out light, and it is particularly desirable that ITO glass or Nesa glass is used. These electrode materials may be used alone, or a plurality of materials may be used by lamination or mixing. Since it is favorable that a sufficient current for light emission of the device can be supplied, the resistance of a transparent electrode is not limited, but from the viewpoint of the power consumed of the device, a low resistance is desirable. For example, an ITO substrate having 300 Ω / or lower functions as a device electrode, but since currently, it has become possible to supply a current to a substrate having around 10 Ω /, it is particularly desirable to use a substrate having a low resistance of 20 Ω / or lower. The thickness of ITO can be arbitrarily selected according to a resistance value, but ITO is usually used at a thickness between 100 to 300 nm in many cases.

[0051] In addition, in order to retain the mechanical strength of the light emitting device, it is preferable to form the light emitting device on a substrate. As the substrate, a glass substrate such as soda glass or alkali-free glass is suitably used. Since it is favorable that the thickness of a glass substrate has a sufficient thickness for retaining the mechanical strength, 0.5 mm or more is sufficient. Regarding the material of glass, since it is preferable that the amount of ions eluted from glass is low, alkali-free glass is preferable. Alternatively, since soda lime glass provided with a barrier coating such as SiO₂ is commercially available, it can also be used. Further, as far as the first electrode stably functions, it is not necessary that the substrate is glass and, for example, the anode may be formed on a plastic substrate. Examples of a method of forming an ITO film include, but are not particularly limited to, an electron beam method, a sputtering method and a chemical reaction method.

[0052] A material used in the cathode is not particularly limited, as far as it is a substance which can efficiently inject electrons into the emissive layer. Generally, metals such as platinum, gold, silver, copper, iron, tin, aluminum, and indium, or alloys or multilayer lamination of these metals with metals having a low work function such as lithium, sodium, potassium, calcium and magnesium are preferable. Among them, as a main component, aluminum, silver, and magnesium are preferable from the viewpoints of electric resistance value, easiness of making a film, stability of a film, and luminance efficiency. Particularly, when the material is constituted by magnesium and silver, electron injection into the electron transporting layer and the electron injection layer in the present invention becomes easy, and low voltage driving becomes possible, and therefore it is preferable.


[0053] Further, as a preferable example, lamination of metals such as platinum, gold, silver, copper, iron, tin, aluminum and indium, or alloys using these metals, inorganic substances such as silica, titania and silicon nitride, and organic polymer compounds such as polyvinyl alcohol, polyvinyl chloride and hydrocarbon-based polymer compound as a protective film layer on the cathode for protecting the cathode can be exemplified. Further, the pyrene compound represented by the general formula (1) can also be utilized as this protective film layer. However, in the case of a device structure for taking out light from the cathode side (top emission structure), the protective film layer is selected from materials having light permeability in a visible light region. Examples of a method of manufacturing these electrodes include, but are not particularly limited to, resistance heating, electron beam, sputtering, ion plating and coating.

[0054] The hole transporting layer is formed by a method of laminating or mixing one kind or two or more kinds of hole transporting materials, or a method of using a mixture of a hole transporting material and a polymer binder. Further, an inorganic salt such as iron chloride (III) may be added to the hole transporting material to form a hole transporting layer. It is necessary that the hole transporting material efficiently transports holes from a positive electrode between electrodes to which the electric field has been given, and it is desirable that a hole injection efficiency is high, and injected holes are transported at a good efficiency. For this reason, it is required that the material is a substance having suitable ionization potential, moreover, great hole mobility, further, excellent stability, and generating impurities that become a trap with difficulty at the time of manufacturing and at the time of use. Preferable examples of substances satisfying

such conditions include, but are not particularly limited to, heterocyclic compounds such as triphenylamine derivatives including 4,4'-bis(N-(3-methylphenyl)-N-phenylamino)biphenyl, 4,4'-bis(N-(1-naphthyl)-N-phenylamino)biphenyl, and 4,4',-4"-tris(3-methylphenyl(phenyl)amino)triphenylamine, biscarbazole derivatives including bis(N-allylcarbazole) or bis(N-alkylcarbazole), pyrazoline derivatives, stilbene-based compounds, hydrazone-based compounds, benzofuran derivatives and thiophene derivatives, oxadiazole derivatives, phthalocyanine derivatives, and porphyrin derivatives, fullerene derivatives and, as a polymer series, polycarbonate and styrene derivatives having the aforementioned monomers on a side chain, polythiophene, polyaniline, polyfluorene, polyvinylcarbazole and polysilane.

[0055] Further, inorganic compounds such as p-type Si, and p-type SiC can also be used. In addition, a compound represented by the following general formula (2), tetrafluorotetracyanoquinodimethane (4F-TCNQ) or molybdenum oxide can also be used.


[Chemical formula 15]



[0056] R¹⁰ to R¹⁵ may be the same or different, and are each selected from the group consisting of a halogen, a sulfonyl group, a carbonyl group, a nitro group, a cyano group, and a trifluoromethyl group.

[0057] Among them, when a compound (3) (1,4,5,8,9,12-hexaazatriphenylenehexacarbonitrile) is contained in the hole transporting layer or the hole injection layer, lower voltage driving is realized, and therefore it is preferable.

[Chemical formula 16]



[0058] In the present invention, the emissive layers may be in the form of a single layer or a plurality of layers, each of which is formed of a emissive material (host material, dopant material), and this may be a mixture of the host material and the dopant material, or the host material alone. That is, in the light emitting device of the present invention, only the host material or the dopant material may emit light, or both of the host material and the dopant material emit light, in each emissive layer. From the viewpoints that an electric energy is efficiently utilized, and light emission at high color purity is obtained, it is preferable that the emissive layer includes a mixture of the host material and the dopant material. In addition, the host material and the dopant material may be one kind or a combination of a plurality of kinds, respectively. The dopant material may be contained in a whole host material, or may be partially contained therein. The dopant material may be laminated, or may be dispersed. The dopant material can control an emitted color. Since when the amount of the dopant material is too large, concentration quenching occurs, it is used preferably in an amount of 20% by weight or less, further preferably 10% by weight or less relative to the host material. As a doping method, the dopant material can be co-evaporated with the host material, or the dopant material may be mixed with the host material in advance to be co-evaporated simultaneously.

[0059] Since the pyrene compound represented by the general formula (1) has high light emitting ability, it is suitably used as an emissive material. In addition, since the pyrene compound represented by the general formula (1) exhibits strong light emission in an ultraviolet to blue region (300 to 450 nm region), it can be suitably used as a blue emissive material. In addition, when it is used as a host-dopant-based emissive material, the pyrene compound of the present invention may be used as the dopant material, but due to excellent thin-film stability, it is suitably used as the host material.

[0060] Specific examples of the emissive material that can be used include, but are not particularly limited to, in addition to the pyrene compound represented by the general formula (1), fused ring derivatives such as anthracene and pyrene, metal chelated oxynoid compounds including tris(8-quinolinolate)aluminum, bisstyryl derivatives such as bisstyrylanthracene derivatives and distyrylbenzene derivatives, tetraphenylbutadiene derivatives, indene derivatives, coumarine derivatives, oxadiazole derivatives, pyrrolopyridine derivatives, perinone derivatives, cyclopentadiene derivatives, oxadiazole derivatives, thiadiazolopyridine derivatives, dibenzofuran derivatives, carbazole derivatives, and indolocarbazole derivatives and, as a polymer series, polyphenylenevinylene derivatives, polyparaphenylene derivatives, and polythiophene derivatives, which have hitherto been known as a light emitting body.

[0061] It is not necessary that the host material contained in the emissive material is limited to only one kind of the pyrene compound represented by the general formula (1), a plurality of pyrene compounds of the present invention may be used by mixing them, and one or more kinds of other host materials may be used by mixing with the pyrene compound of the present invention. Examples of the host material which can be mixed include, but are not particularly limited to, compounds having a fused aryl ring such as naphthalene, anthracene, phenanthrene, pyrene, chrysene, naphthacene, triphenylene, perylene, fluoranthene, fluorene, and indene, and derivatives thereof, aromatic amine derivatives such as N,N'-dinaphthyl-N,N'-diphenyl-4,4'-diphenyl-1,1'-diamine, metal chelated oxynoid compounds including tris(8-quinolinato)aluminum (III), bisstyryl derivatives such as distyrylbenzene derivatives, tetraphenylbutadiene derivatives, indene derivatives, coumarine derivatives, oxadiazole derivatives, pyrrolopyridine derivatives, perinone derivatives, cyclopentadiene derivatives, pyrrolopyrrole derivatives, thiadiazolopyridine derivatives, dibenzofuran derivatives, carbazole derivatives, indolocarbazole derivatives, and triazine derivatives and, as a polymer series, polyphenylenevinylene derivatives, polyparaphenylene derivatives, polyfluorene derivatives, polyvinylcarbazole derivatives, and polythiophene derivatives. Among them, as a host which is used when the emissive layer performs phosphorescence emission, metal chelated oxynoid compounds, dibenzofuran derivatives, carbazole derivatives, indolocarbazole derivatives, triazine derivatives etc. are suitably used.

[0062] Examples of the dopant material include, but are not particularly limited to, compounds having a fused aryl ring such as naphthalene, anthracene, phenanthrene, pyrene, chrysene, triphenylene, perylene, fluoranthene, fluorene, and indene, and derivatives thereof (e.g., 2-(benzothiazol-2-yl)-9,10-diphenylanthracene and 5,6,11,12-tetraphenylanthracene), compounds having a heteroaryl ring such as furan, pyrrole, thiophene, silole, 9-silafluorene, 9,9'-spirobisilafluorene, benzothiophene, benzofuran, indole, dibenzothiophene, dibenzofuran, imidazopyridine, phenanthroline, pyridine, pyrazine, naphthyridine, quinoxaline, pyrrolopyridine, and thioxanthene, and derivatives thereof, borane derivatives, distyrylbenzene derivatives, aminostyryl derivatives such as 4,4'-bis(2-(4-diphenylaminophenyl)ethenyl)biphenyl, 4,4'-bis(N-(stilben-4-yl)-N-phenylamino)stilbene, aromatic acetylene derivatives, tetraphenylbutadiene derivatives, stilbene derivatives, aldazine derivatives, pyrromethene derivatives, diketopyrrolo[3,4-c]pyrrole derivatives, coumarine derivatives such as 2,3,5,6-1H,4H-tetrahydro-9-(2'-benzothiazolyl)quinolizino[9,9a,1-g]coumarine,azole derivatives such as imidazole, thiazole, thiadiazole, carbazole, oxazole, oxadiazole, and triazole, and metal complexes thereof, and aromatic amine derivatives, a representative of which is N,N'-diphenyl-N,N'-di(3-methylphenyl)-4,4'-diphenyl-1,1'-di amine.

[0063] In addition, it is preferable that the dopant used when the emissive layer performs phosphorescence emission is a metal complex compound containing at least one metal selected from the group consisting of iridium (Ir), ruthenium (Ru), palladium (Pd), platinum (Pt), osmium (Os), and rhenium (Re). It is preferable that the ligand has a nitrogen-containing aromatic heterocyclic ring such as a phenylpyridine skeleton or a phenylquinoline skeleton. However, the complex is not limited thereto, and a suitable complex is selected in context with emitted color, device performance and host compound to be required.

[0064] In the present invention, the electron transporting layer is a layer in which electrons are injected from the cathode and, further, which transports the electrons. It is desired that the electron transporting layer has a high electron injection efficiency, and efficiently transports injected electrons. For this reason, it is required that the electron transporting layer is constituted by a substance having great electron affinity and, moreover, great mobility and, further, excellent stability, and generating impurities that become a trap with difficulty at the time of manufacturing and at the time of use. Particularly, when layers are laminated at a large thickness, since a low-molecular compound is crystallized etc., and the film quality is easily deteriorated, a compound having a molecular weight of 400 or more which retains stable film quality is preferable. However, when transportation balance between holes and electrons is considered, if the electron transporting layer mainly plays a role of being able to inhibiting holes from the anode from flowing to the cathode side without recombination, even when the layer is constituted by a material having not so high electron transporting ability, the effect of improving luminance efficiency becomes equivalent to that when the layer is constituted by a material having high electron transporting ability. Therefore, the electron transporting layer in the present invention also includes a hole inhibition layer

which can efficiently inhibit the transfer of holes as the same meaning.

[0065] The pyrene compound represented by the general formula (1) is a compound satisfying the aforementioned conditions, and since it has high electron injection transporting ability, it is also suitably used as the electron transporting material.

[0066] When the electron transporting layer further includes a donor compound, compatibility with the donor compound in the thin-film state is improved, and therefore higher electron injection transporting ability is exerted. Due to the action of this mixture layer, transportation of electrons from the cathode to the emissive layer is promoted, and both of a high luminance efficiency and a low driving voltage can be realized.

[0067] The electron transporting material used in the present invention is not necessarily limited to only one kind of the pyrene compound represented by the general formula (1), and a plurality of the pyrene compounds may be used by mixing them, or one or more kinds of other electron transporting materials may be used by mixing in such a range that the effect of the present invention is not imparted. Examples of the electron transporting material that can be mixed include, but are not particularly limited to, compounds having a fused aryl ring such as naphthalene, anthracene, and pyrene, and derivatives thereof, styryl-based aromatic ring derivatives, a representative of which is 4,4'-bis(diphenylethenyl)biphenyl, perylene derivatives, perinone derivatives, coumarine derivatives, naphthalimide derivatives, quinone derivatives such as anthraquinone and diphenquinone, phosphorus oxide derivatives, carbazole derivatives and indole derivatives, quinolinol complexes such as tris(8-quinolinolato)aluminum (III), hydroxyazole complexes such as hydroxyphenyloxazole complexes, azomethine complexes, tropolone metal complexes and flavonol metal complexes.

[0068] Then, the donor compound will be described. The donor compound in the present invention is a compound which makes easy electron injection into the electron transporting layer from the cathode or the electron injection layer and, further, improves electric conductivity of the electron transporting layer, by improving an electron injection barrier. That is, in the light emitting device of the present invention, it is more preferable that the electron transporting layer is doped with the donor compound in order to improve the electron transporting ability, in addition to the pyrene compound represented by the general formula (1).

[0069] Preferable examples of the donor compound in the present invention include an alkali metal, an inorganic salt containing an alkali metal, a complex of an alkali metal and an organic substance, an alkaline earth metal, an inorganic salt containing an alkaline earth metal, or a complex of an alkaline earth metal and an organic substance. Examples of the preferable kind of the alkali metal and the alkaline earth metal include alkali metals such as lithium, sodium and cesium, and alkaline earth metals such as magnesium and calcium, which have a low work function and have the great effect of improving electron transporting ability.

[0070] In addition, since evaporation in vacuum is easy, and handling is excellent, the state of inorganic salts or complexes with an organic substance is preferable rather than metal single substances. Further, from the viewpoints of easy handling in the atmospheric air, and easiness in control of the concentration to be added, the state of complexes with an organic substance is more preferable. Examples of the inorganic salts include oxides such as LiO, and Li₂O, nitrides, fluorides such as LiF, NaF, and KF, and carbonates such as Li₂CO₃, Na₂CO₃, K₂CO₃, Rb₂CO₃, and Cs₂CO₃. In addition, preferable examples of the alkali metal or the alkaline earth metal include lithium, from the view point of the low cost of raw materials and easy synthesis. In addition, preferable examples of the organic substance in complexes with an organic substance include quinolinol, benzoquinolinol, flavonol, hydroxyimidazopyridine, hydroxybenzazole, and hydroxytriazole. Among them, complexes of an alkali metal and an organic substance are preferable, complexes of lithium and an organic substance are more preferable, and lithium quinolinol is particularly preferable.

[0071] In addition, when the doping ratio of the donor compound in the electron transporting layer is suitable, the injection ratio of electrons into the electron transporting layer from the cathode or the electron injection layer is increased, and an energy barrier between the cathode and the electron injection layer, or between the electron injection layer and the electron transporting layer is reduced, and a driving voltage is reduced. A suitable doping concentration is different depending on a material or the film thickness of a doping region, the molar ratio of the organic compound and the donor compound is preferably in a range of 100:1 to 1:100, more preferably 10:1 to 1:10.

[0072] A method of doping the electron transporting layer with the donor compound to improve electron transporting ability exerts particularly the effect when the thickness of the thin-film layer is great. The method is particularly preferably used when the total thickness of the electron transporting layer and the emissive layer is 50 nm or more. For example, there is a method of utilizing the interference effect for improving luminance efficiency, and this improves efficiency of taking out light by matching the phase of light which is directly radiated from the emissive layer, and the phase of light which is reflected at the cathode. This optimal condition varies depending on the emission wavelength of light, and it results in 50 nm or more of the total thickness of the electron transporting layer and the emissive layer, and in the case of long wavelength light emission such as a red color, the thickness becomes near 100 nm in some cases.

[0073] The film thickness of the electron transporting layer to be doped may be part or all of the electron transporting layer, and as the film thickness of the whole electron transporting layer is greater, the greater concentration of doping is better. When part is doped, it is desirable to provide a doping region on at least an electron transporting layer/cathode interface and, the effect of reducing a voltage is obtained even doping is carried out around the cathode interface. On

the other hand, in the case where if the emissive layer is doped with the donor compound, it gives an adverse influence of reducing luminance efficiency, it is desirable to provide a non-doped region at an emissive layer/electron transporting layer interface.

[0074] Examples of a method of forming each of the aforementioned layers constituting the light emitting device include, but are not particularly limited to, resistance heating evaporation, electron beam evaporation, sputtering, a molecular lamination method, and a coating method, but usually, resistance heating evaporation or electron beam evaporation is preferable from the viewpoint of device property.

[0075] The thickness of the organic layer depends on the resistance value of an emissive substance and, therefore, it cannot be limited, but it is preferably 1 to 1000 nm. The film thickness of the emissive layer, the electron transporting layer and the hole transporting layer is preferably 1 nm or more and 200 nm or less, further preferably 5 nm or more and 100 nm or less, respectively.

[0076] The light emitting device of the present invention has a function of being able to convert an electric energy into light. Herein, as the electric energy, a direct current is mainly used, but a pulse current or an alternate current can also be used. A current value and a voltage value are not particularly limited, but when the power consumed and life of the device are considered, they should be selected so that the maximum luminance is obtained by a low energy as much as possible.

[0077] The light emitting device of the present invention is suitably used as a display which performs display by a matrix and/or segment system.

[0078] The matrix system is such that pixels for display are arranged two-dimensionally such as lattice-like arrangement or mosaic-like arrangement, and the population of pixels displays letters and images. The shape and size of the pixel are determined depending on utility. For example, for displaying images and letters on personal computers, monitors and televisions, a square pixel having one side of 300 μm or less is usually used and, in the case of a large display such as a display panel, a pixel having one side of an mm order is used. In the case of monochromatic display, pixels having the same color may be arranged, and in the case of color display, pixels having red, green and blue are arranged to perform display. In this case, typically, there are a delta type and a stripe type. A method of driving this matrix may be a passive matrix driving method and an active matrix. The passive matrix driving has a simple structure, but when operation property is considered, the active matrix is more excellent in some cases, and it is necessary that this is used depending on utility.

[0079] The segment system in the present invention is a system by which a pattern is formed so as to display predetermined information, and a region determined by arrangement of this pattern is made to emit light. Examples thereof include display of time and temperature in a digital watch and a thermometer, display of the operation state of audio instruments and electromagnetic cooking equipments, panel displays of automobiles and, the matrix display and the segment display may be present in the same panel.

[0080] The light emitting device of the present invention can also be preferably used as backlight of various instruments etc. Backlight is used mainly for the purpose of improving visibility of display equipments which do not spontaneously emit light, and is used in liquid crystal display equipments, clocks, audio equipments, automobile panels, display plates, signs etc. Particularly, the light emitting device of the present invention is preferably used in backlight for liquid crystal display equipments, inter alia, for personal computers which are studied to be thinned, and can provide backlight thinner and lighter than conventional backlight.

EXAMPLES

[0081] The present invention will be described by way of Examples, but the present invention is not limited thereto. In addition, the number of a compound in each of Examples described below indicates the number of the aforementioned compound.

Synthesis Example 1

Synthesis of Compound [1]

[0082] A mixed solution of 4.1 g of pyrene, 2 g of t-butyl chloride and 33 ml of dichloromethane was cooled to 0°C under a nitrogen stream, and 2.7 g of aluminum chloride was added. After this mixed solution was stirred at room temperature for 3 hours, 30 ml of water was added, and this was extracted with 30 ml of dichloromethane. The organic layer was washed with 20 ml of water two times, dried with magnesium sulfate, and evaporated. This was purified by silica gel column chromatography, and vacuum-dried to obtain 3 g (content 65%) of 2-t-butylpyrene.

[0083] Then, a mixed solution of 3 g (content 65%) of 2-t-butylpyrene, 50 ml of dichloromethane and 15 ml of methanol was cooled to 0°C under a nitrogen stream, and 3.3 g of benzyltrimethylammonium tribromide dissolved in 10 ml of dichloromethane was added dropwise. After this mixed solution was stirred at room temperature for 2 hours, 50 ml of

water was added, and this was extracted with 50 ml of dichloromethane. The organic layer was washed with 50 ml of water two times, dried with magnesium sulfate, and evaporated. To the resulting solid was added 10 ml of methanol, and the mixture was stirred for 10 minutes, and filtered. Further, 30 ml of hexane was added, and the mixture was stirred for 30 minutes, and filtered. After the resultant was vacuum dried, 2.3 g of 1-bromo-7-t-butylpyrene was obtained.

[0084] Then, a mixed solution of 2.3 g (content 79.2%) of 1-bromo-7-t-butylpyrene, 1.1 g of phenylboronic acid, 3.8 g of tripotassium phosphate, 0.58 g of tetrabutylammonium bromide, 12 mg of palladium acetate and 30 ml of dimethylformamide was heated and stirred at 130°C for 2 hours under a nitrogen stream. After the mixture was cooled to room temperature, 30 ml of water was added, and this was extracted with 50 ml of dichloromethane. The organic layer was washed with 20 ml of water two times, dried with magnesium sulfate, and evaporated. This was purified by silica gel column chromatography, and vacuum-dried to obtain 1.5 g of 7-t-butyl-1-phenylpyrene.

[0085] Then, a mixed solution of 1.5 g of 7-t-butyl-1-phenylpyrene, 25 ml of dichloromethane and 8 ml of methanol was cooled to 0°C under a nitrogen stream, and 1.7 g of benzyltrimethylammonium tribromide dissolved in 5 ml of dichloromethane was added dropwise. After this mixed solution was stirred at room temperature for 2 hours, 20 ml of water was added, and this was extracted with 20 ml of dichloromethane. The organic layer was washed with 20 ml of water two times, dried with magnesium sulfate, and evaporated. To the resulting solid was added 10 ml of methanol, and this was allowed to stand overnight. The precipitated solid was filtered, and vacuum-dried to obtain 1.9 g of 1-bromo-7-t-butyl-3-phenylpyrene.

[0086] Then, a mixed solution of 1.9 g of 1-bromo-7-t-butyl-3-phenylpyrene, 0.57 g of 3-pyridineboronic acid, 10 mg of palladium acetate, 24 mg of triphenylphosphine, 4.4 ml of an aqueous 2M sodium carbonate solution and 23 ml of dimethoxyethane was heated and stirred for 5 hours under a nitrogen stream and under refluxing. After the mixture was cooled to room temperature, 40 ml of water was added, and this was filtered. After the resultant was washed with 40 ml of methanol, this was purified by silica gel chromatography, and vacuum-dried to obtain 1.4 g of a pale yellowish white crystal.

[0087] ¹H-NMR analysis results of the resulting powder were as follows, and it was confirmed that the yellowish white crystal obtained above is Compound [1].

¹H-NMR(CDCl₃(d=ppm)): 1.61(s, 9H), 7.30-8.81(m, 16H).

[0088] In addition, Compound [1] was used as a light emitting device material after sublimation purification was performed at about 230°C under a pressure of 1×10^{-3} Pa using an oil diffusion pump. The HPLC purity (area% at a measurement wavelength 254 nm) was 99.4% before sublimation purification, and 99.6% after sublimation purification.

Synthesis Example 2

Synthesis of Compound [10]

[0089] A mixed solution of 150 g of pyrene, 75.52 g of t-butyl chloride and 742 ml of dichloromethane was cooled to 0°C under a nitrogen stream, and 98.9 g of aluminum chloride was added. After this mixed solution was stirred at room temperature for 3 hours, 1100 ml of water was added, and this was extracted with 1100 ml of dichloromethane. The organic layer was washed with 750 ml of water three times, dried with magnesium sulfate, and evaporated, and this was purified by methanol washing, and filtered. After the resultant was vacuum dried, 272 g (content 79.2%) of 2-t-butylpyrene was obtained.

[0090] Then, to a mixed solution of 77.15 g (content 79.2%) of 2-t-butylpyrene, and 1380 ml of tetrahydrofuran was added 123 g of N-bromosuccinimide under a nitrogen stream. This mixed solution was stirred at 30°C for about 8 hours, and this was filtered. After the resulting solid was washed with methanol, recrystallization with 1500 ml of toluene was carried out, and the resultant was vacuum dried to obtain 57.3 g of 1,3-dibromo-7-t-butylpyrene.

[0091] Then, a mixed solution of 20.0 g of 1,3-dibromo-7-t-butylpyrene, 16.52 g of 4-chlorophenylboronic acid, 0.034 g of bis(triphenylphosphine)dichloropalladium, 106 ml of an aqueous 2M sodium carbonate solution and 240 ml of 1, 2-dimethoxyethane was heated and stirred for about 5 hours under a nitrogen stream and under refluxing, and this was cooled to 5°C. After 240 ml of water was added, and the precipitated solid was filtered, the solid was washed with 125 ml of water two times and 125ml of methanol once. After the solid was vacuum dried, the gray solid was dissolved in 48 ml of toluene, 2 g of active carbon was added, this was stirred for about 15 minutes, and the active carbon was filtered. After the resulting filtrate was evaporated, 100 ml of hexane was added, and the mixture was stirred for about 1 hour, and filtered. After the resultant was vacuum dried, 7.7 g of 7-t-butyl-1,3-bis(4-chlorophenyl)pyrene was obtained.

[0092] Then, a mixed solution of 7.0 g of 7-t-butyl-1,3-bis(4-chlorophenyl)pyrene, 5.4 g of 3-pyridineboronic acid, 0.34 g of bis(dibenzylideneacetone)palladium, 0.26 g of tricyclohexylphosphine tetrafluoroborate, 53 ml of an aqueous 1.27 M tripotassium phosphate solution and 51 ml of 1, 4-dioxane was heated and stirred for about 8 hours under a nitrogen stream and under refluxing. After the mixture was cooled to room temperature, 100 ml of water was added, and this was extracted with 300 ml of toluene. The organic layer was washed with 100 ml of an aqueous sodium chloride solution two times, dried with magnesium sulfate, evaporated, and purified by silica gel column chromatography. The pale yellow

EP 2 416 396 B1

solid obtained by evaporation was washed with 50 ml of toluene, and 50 ml of methanol, and filtered. After vacuum drying, 7.2 g of a pale yellowish white crystal was obtained.

[0093] ¹H-NMR analysis results of the resulting powder were as follows, and it was confirmed that the pale yellowish white crystal obtained above is Compound [10].

¹H-NMR(CDCl₃(d=ppm)): 1.61 (9H, s), 7.43 (2H, dd, J = 4.6 Hz, 7.8 Hz), 7.77-7.85 (8H, m), 7.99-8.02 (3H, m), 8.07 (2H, d, J = 9.5 Hz), 8.24 (2H, d, J = 9.5 Hz), 8.24 (2H, s), 8.65 (2H, dd, J = 1.1 Hz, 4.9 Hz), 9.00 (2H, d, J = 1.9 Hz).

[0094] In addition, Compound [10] was used as a light emitting device material after sublimation purification at about 290°C under a pressure of 1×10^{-3} Pa using an oil diffusion pump. The HPLC purity (area% at a measurement wavelength 254 nm) was 99.8% before sublimation purification, and 99.9% after sublimation purification.

Synthesis Example 3

Synthesis of Compound [107]

[0095] To a mixed solution of 120 g (content 79.2%) of 2-t-butylpyrene, and 3000 ml of tetrahydrofuran was added 69.66 g of N-bromosuccinimide under a nitrogen stream. This mixed solution was stirred at 30°C for about 3 hours, and concentrated, 500 ml of methanol was added, and the mixture was stirred for about 1 hour, and filtered. To the resulting solid was added 500 ml of hexane, and the mixture was heated and stirred for about 1 hour, and filtered. After the resultant was vacuum dried, 106.9 g of 1-bromo-7-t-butylpyrene was obtained.

[0096] Then, a mixed solution of 106.9 g of 1-bromo-7-t-butylpyrene, 54.5 g of 4-chlorophenylboronic acid, 0.223 g of bis(triphenylphosphine) dichloropalladium, 350 ml of an aqueous 2M sodium carbonate solution and 1586 ml of 1,2-dimethoxyethane was heated and stirred for about 5 hours under a nitrogen stream and under refluxing. After the mixture was cooled to room temperature, 640 ml of water was added, and this was extracted with 1170 ml of toluene. The organic layer was washed with 640 ml of water two times, dried with magnesium sulfate, and evaporated, 270 ml of toluene and 1350 ml of methanol were added, and the mixture was stirred for about 2 hours, and filtered. After the resultant was vacuum dried, 105.16 g of 7-t-butyl-1-(4-chlorophenyl)pyrene was obtained.

[0097] Then, to a mixed solution of 100.6 g of 7-t-butyl-1-(4-chlorophenyl)pyrene, and 1638 ml of tetrahydrofuran was added 53.5 g of N-bromosuccinimide under a nitrogen stream. This mixed solution was stirred at 30°C for about 5 hours, and concentrated, 984 ml of methanol was added, and the mixture was stirred for about 1 hour, and filtered. To the resulting solid was added 539 ml of hexane, and the mixture was heated and stirred for about 1 hour, and filtered. After the resultant was vacuum dried, 112.0 g of 1-bromo-7-t-butyl-3-(4-chlorophenyl)pyrene was obtained.

[0098] Then, a mixed solution of 10.0 g of 1-bromo-7-t-butyl-3-(4-chlorophenyl)pyrene, 6.9 g of 4-(2-pyridylphenyl)boronic acid pinacolato ester, 0.016 g of bis(triphenylphosphine)palladium dichloride, 33 ml of an aqueous 1.5M sodium carbonate solution and 112 ml of 1,2-dimethoxyethane was heated and stirred for about 5 hours under a nitrogen stream and under refluxing. After the mixture was cooled to room temperature, 223 ml of water was added, and this was extracted with 236 ml of ethyl acetate. The organic layer was washed with 640 ml of an aqueous sodium chloride solution two times, dried with magnesium sulfate, and evaporated, 200 ml of 2-propanol was added, and the mixture was stirred for about 2 hours, and filtered. After the resultant was vacuum dried, 10.5 g of 1-(4-(2-pyridyl)phenyl)-3-(4-chlorophenyl)-7-t-butylpyrene was obtained.

[0099] Then, a mixed solution of 6.5 g of 1-(4-(2-pyridyl)phenyl)-3-(4-chlorophenyl)-7-t-butylpyrene, 1.68 g of 3-pyridineboronic acid, 0.143 g of bis(dibenzylideneacetone)palladium, 0.11 g of tricyclohexylphosphine tetrafluoroborate, 17 ml of an aqueous 1.27M tripotassium phosphate solution and 63 ml of 1,4-dioxane was heated and stirred for about 6 hours under a nitrogen stream and under refluxing. After the mixture was cooled to room temperature, 34 ml of water was added, and this was extracted with 70 ml of ethyl acetate. The organic layer was washed with 34 ml of an aqueous sodium chloride solution two times, dried with magnesium sulfate, and evaporated, 18 ml of ethyl acetate, and 72 ml of hexane were added, and the mixture was stirred for about 2 hours, and filtered. The resultant was purified by silica gel column chromatography, the pale yellow solid obtained by evaporation was recrystallized with 40 ml of ethyl acetate, and the solid obtained by filtration was vacuum-dried to obtain 4.1 g of a white crystal.

[0100] ¹H-NMR analysis results of the resulting powder were as follows, and it was confirmed that the white crystal obtained above is Compound [107].

¹H-NMR(CDCl₃(d=ppm)): 1.60 (9H, s), 7.23-7.31 (1H, m), 7.43 (1H, ddd, J = 1.1 Hz, 4.9 Hz, 7.8 Hz), 7.77-7.90 (8H, m), 7.98-8.11 (4H, m), 8.16-8.29 (6H, m), 8.65 (1H, dd, J = 1.6 Hz, 4.6 Hz), 8.76 (1H, dt, J = 0.5 Hz, 4.6 Hz), 9.00 (1H, dd, J = 0.5 Hz, 2.2 Hz).

[0101] In addition, Compound [107] was used as a light emitting device material after sublimation purification at about 300°C under a pressure of 1×10^{-3} Pa using an oil diffusion pump. The HPLC purity (area% at a measurement wavelength 254 nm) was 99.4% before sublimation purification, and 99.9% after sublimation purification.

Synthesis Example 4

Synthesis of Compound [91]

5 **[0102]** A mixed solution of 9.4 g of 1-bromo-7-t-butyl-3-(4-chlorophenyl)pyrene, 4.58 g of 4-biphenylboronic acid, 0.015 g of bis(triphenylphosphine)palladium dichloride, 23 ml of an aqueous 2M sodium carbonate solution and 105 ml of 1,2-dimethoxyethane was heated and stirred for about 4 hours under a nitrogen stream and under refluxing. After the mixture was cooled to room temperature, 141 ml of water was added, and this was extracted with 164 ml of toluene. The organic layer was washed with 141 ml of an aqueous sodium chloride solution two times, dried with magnesium sulfate, and evaporated, 33 ml of toluene and 132 ml of hexane were added, and the mixture was stirred for about 2 hours, and filtered. After the resultant was vacuum dried, 10.5 g of 1-(4-biphenyl)-3-(4-chlorophenyl)-7-t-butylpyrene was obtained.

10 **[0103]** Then, a mixed solution of 10.0 g of 1-(4-biphenyl)-3-(4-chlorophenyl)-7-t-butylpyrene, 2.6 g of 3-pyridineboronic acid, 0.22 g of bis(dibenzylideneacetone)palladium, 0.17 g of tricyclohexylphosphine tetrafluoroborate, 26 ml of an aqueous 1.27M tripotassium phosphate solution and 110 ml of 1,4-dioxane was heated and stirred for about 4 hours under a nitrogen stream and under refluxing. After the mixture was cooled to room temperature, 30 ml of water was added, and this was extracted with 100 ml of toluene. The organic layer was washed with 30 ml of an aqueous sodium chloride solution two times, dried with magnesium sulfate, and evaporated, 32 ml of toluene and 96 ml of hexane were added, and the mixture was stirred for about 2 hours, and filtered. The resultant was purified by silica gel column chromatography, the pale yellow solid obtained by evaporation was dissolved in 29 ml of toluene, 87 ml of methanol was added, and the mixture was stirred for about 2 hours, and filtered. The resulting solid was vacuum dried to obtain 8.9 g of a white crystal.

15 **[0104]** ¹H-NMR analysis results of the resulting powder were as follows, and it was confirmed that the white crystal obtained above is Compound [91].

25 ¹H-NMR (CDCl₃ (d=ppm)) : 1.60 (9H, s), 7.35-7.46 (2H, m), 7.51 (2H, t, J = 7.0 Hz), 7.70-7.85 (8H, m), 7.98-8.08 (4H, m), 8.22-8.30 (6H, m), 8.65 (1H, dd, J = 1.6 Hz, 4.6 Hz), 9.00 (1H, d, J = 1.9 Hz).

[0105] In addition, Compound [91] was used as a light emitting device material after sublimation purification at about 270°C under a pressure of 1 × 10⁻³ Pa using an oil diffusion pump. The HELC purity (area% at a measurement wavelength 254 nm) was 99.8% before sublimation purification, and 99.9% after sublimation purification.

30 Synthesis Example 5

Synthesis of Compound [63]

35 **[0106]** A mixed solution of 7.08 g of 1-bromo-7-t-butylpyrene, 4.57 g of 4-biphenylboronic acid, 0.075 g of bis(dibenzylideneacetone)palladium, 23 ml of an aqueous 2M sodium carbonate solution and 105 ml of 1,2-dimethoxyethane was heated and stirred for about 6 hours under a nitrogen stream and under refluxing. After the mixture was cooled to room temperature, 177 ml of water was added, and this was extracted with 200 ml of toluene. The organic layer was washed with 177 ml of an aqueous sodium chloride solution two times, dried with magnesium sulfate, and evaporated, 52 ml of methanol was added, and the mixture was stirred for about 2 hours, and filtered. After the mixture was vacuum dried, 8.65 g of 1-(4-biphenyl)-7-t-butylpyrene was obtained.

40 **[0107]** Then, to a mixed solution of 8.65 g of 1-(4-biphenyl)-7-t-butylpyrene, and 126 ml of tetrahydrofuran was added 4.1 g of N-bromosuccinimide under a nitrogen stream. This mixed solution was stirred at 30°C for about 3 hours, and concentrated, 126 ml of methanol was added, and the mixture was stirred for about 1 hour, and filtered. To the resulting solid was added 30 ml of tetrahydrofuran, the mixture was heated and dissolved, 180 ml of methanol was added, and the mixture was stirred for about 1 hour, and filtered. After the resultant was purified by silica gel column chromatography, the solid obtained by evaporation was washed with 126 ml of methanol, and vacuum dried to obtain 8.8 g of 1-bromo-3-(4-biphenyl)-7-t-butylpyrene.

45 **[0108]** Then, a mixed solution of 4.33 g of 1-bromo-3-(4-biphenyl)-7-t-butylpyrene, 2.76 g of 4-(2-pyridylphenyl)boronic acid pinacolato ester, 0.035 g of bis(dibenzylideneacetone)palladium, 60 ml of an aqueous 1.5M sodium carbonate solution and 44 ml of 1,2-dimethoxyethane was heated and stirred for about 6 hours under a nitrogen stream and under refluxing. After the mixture was cooled to room temperature, 120 ml of water was added, and this was extracted with 140 ml of toluene. The organic layer was washed with 120 ml of an aqueous sodium chloride solution two times, dried with magnesium sulfate, evaporated, and the resultant was purified by silica gel column chromatography. After the pale yellow solid obtained by evaporation was heated and dissolved in 30 ml of toluene, 150 ml of hexane was added, and the mixture was stirred for about 2 hours, and filtered. The resulting solid was vacuum dried to obtain 3.55 g of a white crystal.

55 **[0109]** ¹H-NMR analysis results of the resulting powder were as follows, and it was confirmed that the white crystal obtained above is Compound [63].

EP 2 416 396 B1

$^1\text{H-NMR}(\text{CDCl}_3 \text{ (d=ppm)})$: 1.60 (9H, s), 7.22-7.31 (1H, m), 7.36-7.94 (1H, m), 7.51 (2H, t, $J = 6.7$ Hz), 7.70-7.90 (10H, m), 8.04 (2H, t, $J = 2.4$ Hz), 8.07 (1H, d, $J = 2.2$ Hz), 8.16-8.30 (6H, m), 8.76 (1H, d, $J = 4.9$ Hz).

[0110] In addition, Compound [63] was used as a light emitting device material after sublimation purification at about 260°C under a pressure of 1×10^{-3} Pa using an oil diffusion pump. The HPLC purity (area% at a measurement wavelength 254 nm) was 99.8% before sublimation purification, and 99.9% after sublimation purification.

Synthesis Example 6

Synthesis of Compound [106]

[0111] A mixed solution of 15.0 g of 1,3-dibromo-7-t-butylpyrene, 22.3 g of 4-(2-pyridylphenyl)boronic acid pinacolato ester, 0.25 g of bis (triphenylphosphine) palladium dichloride, 107 ml of an aqueous 1.5M sodium carbonate solution and 180 ml of 1,2-dimethoxyethane was heated and stirred for about 6 hours under a nitrogen stream and under refluxing. After the mixture was cooled to room temperature, 151 ml of water was added, and this was extracted with 204 ml of toluene. The organic layer was washed with water three times, dried with magnesium sulfate, and evaporated, 30 ml of toluene and 120 ml of hexane were added, and the mixture was stirred for about 2 hours, and filtered. After the resultant was purified by silica gel column chromatography, the pale yellow solid obtained by evaporation was dissolved in 57 ml of toluene, 171 ml of methanol was added, and the mixture was stirred for about 2 hours, and filtered. The resulting solid was vacuum dried to obtain 18.25 g of a white crystal.

[0112] $^1\text{H-NMR}$ analysis results of the resulting powder were as follows, and it was confirmed that the white crystal obtained above is Compound [106].

$^1\text{H-NMR}(\text{CDCl}_3 \text{ (d=ppm)})$: 1.59 (9H, s), 7.17-7.31 (2H, m), 7.68-7.89 (8H, m), 8.05 (2H, d, $J = 9.2$ Hz), 8.05 (1H, s), 8.13-8.28 (8H, m), 8.76 (2H, d, $J = 5.1$ Hz).

[0113] In addition, Compound [106] was used as a light emitting device material after sublimation purification at about 290°C under a pressure of 1×10^{-3} Pa using an oil diffusion pump. The HPLC purity (area% at measurement wavelength 254 nm) was 99.8% before sublimation purification, and 99.9% after sublimation purification.

Synthesis Example 7

Synthesis of Compound [144]

[0114] A mixed solution of 2.0 g of 1, 3-dibromo-7-t-butylpyrene, 3. 5 g of 4-(2-quinolinyphenyl)boronic acid pinacol ester, 34 mg of bis(triphenylphosphine)dichloropalladium, 11 mL of an aqueous 2M sodium carbonate solution and 24 mL of 1,2-dimethoxyethane was heated and stirred for 5 hours under a nitrogen stream and under refluxing. After the mixture was cooled to room temperature, 50 mL of water was added, and this was stirred at room temperature for 1 hour. The precipitated solid was filtered, and washed with 70 mL of methanol. The resulting solid was purified by silica gel chromatography, recrystallized with 30mL of toluene, and filtered. The resulting solid was vacuum dried to obtain 2.2 g of a pale yellow powder.

[0115] $^1\text{H-NMR}$ analysis results of the resulting powder were as follows, and it was confirmed that the pale yellow powder obtained above is Compound [144].

$^1\text{H-NMR}(\text{CDCl}_3 \text{ (d=ppm)})$: 1.60 (9H, s), 7.57 (2H, t, $J = 6.8$ Hz), 7.77 (2H, dt, $J = 1.4$ Hz, 8.4 Hz), 7.88 (6H, d, $J = 8.4$ Hz), 7.99-8.11 (5H, m), 8.21-8.33 (7H, m), 8.25 (1H, s), 8.39 (4H, d, $J = 8.4$ Hz).

[0116] In addition, Compound [144] was used as a light emitting device material after sublimation purification at 320°C under a pressure of 1×10^{-3} Pa using an oil diffusion pump. The HPLC purity (area% at a measurement wavelength 254 nm) was 99.8% before sublimation purification, and 99.9% after sublimation purification.

Synthesis Example 8

Synthesis of Compound [93]

[0117] According to the same manner as in Synthesis Example 4 except that 9, 9-dimethylfluoren-2-yl boronic acid was used in place of 4-biphenylboronic acid, synthesis was performed to obtain a pale yellowish white crystal. $^1\text{H-NMR}$ analysis results of the resulting powder were as follows, and it was confirmed that the pale yellowish white crystal obtained above is Compound [93].

$^1\text{H-NMR}(\text{CDCl}_3 \text{ (d=ppm)})$: 1.58 (3H, s), 1.59 (3H, s), 1.60 (9H, s), 7.35-7.51 (4H, m), 7.66 (1H, dd, $J = 1.6$ Hz, 7.8 Hz), 7.73-7.92 (7H, m), 7.98-8.08 (4H, m), 8.20-8.30 (4H, m), 8.65 (1H, dd, $J = 1.6$ Hz, 4.9 Hz), 9.00 (1H, d, $J = 1.9$ Hz).

[0118] In addition, Compound [93] was used as a light emitting device material after sublimation purification at about 260°C under a pressure of 1×10^{-3} Pa using an oil diffusion pump. The HPLC purity (area% at a measurement wavelength

EP 2 416 396 B1

254 nm) was 99.5% before sublimation purification, and 99.7% after sublimation purification.

Synthesis Example 9

5 Synthesis of Compound [67]

[0119] A mixed solution of 10.0 g of 1-bromo-7-t-butyl-3-(4-chlorophenyl)pyrene, 5.86 g of 9,9-dimethylfluoren-2-yl boronic acid, 0.016 g of bis(triphenylphosphine)palladium dichloride, 33 ml of an aqueous 1.5M sodium carbonate solution and 112 ml of 1,2-dimethoxyethane was heated and stirred for 3 hours under a nitrogen stream and under refluxing. After the mixture was cooled to room temperature, 223 ml of water was added, and this was extracted with 236 ml of toluene. The organic layer was washed with 640 ml of an aqueous sodium chloride solution two times, dried with magnesium sulfate, and evaporated, 50 ml of 2-propanol was added, and the mixture was stirred for 2 hours, and filtered. After the mixture was vacuum dried, 9.5 g of 1-(4-chlorophenyl)-3-(9,9-dimethylfluoren-2-yl)-7-t-butylpyrene was obtained.

[0120] Then, a mixed solution of 4 g of 1-(4-chlorophenyl)-3-(9,9-dimethylfluoren-2-yl)-7-t-butylpyrene, 1.81 g of bis(pinacolato)diboron, 1.2 g of potassium acetate, 72 mg of bis(dibenzylideneacetone)palladium, 225 mg of S-Phos and 24 ml of 1,4-dioxane was heated and stirred for 4 hours under a nitrogen stream and under refluxing. After the mixture was cooled to room temperature, 932 mg of 2-bromopyridine dissolved in 6 ml of 1,4-dioxane, and 6 ml of an aqueous 5M tripotassium phosphate solution were added, and the mixture was heated and stirred for 4 hours under a nitrogen stream and under refluxing. After the mixture was cooled to room temperature, 30 ml of water was added, this was extracted with 100 ml of toluene. The organic layer was washed with 30 ml of an aqueous sodium chloride solution two times, dried with magnesium sulfate, evaporated, and the resultant was purified by silica gel column chromatography. After vacuum drying of the solid obtained by evaporation, 1.1 g of a pale yellowish white crystal was obtained.

[0121] ¹H-NMR analysis results of the resulting powder were as follows, and it was confirmed that the pale yellowish white crystal obtained above is Compound [67].

¹H-NMR(CDCl₃(d=ppm)): 1.58 (6H, s), 1.60 (9H, s), 7.26-7.31 (1H, m), 7.31-7.43 (2H, m), 7.46-7.51 (1H, m), 7.67 (1H, dd, J = 1.4 Hz, 7.6 Hz), 7.72-7.92 (7H, m), 8.01-8.08 (3H, m), 8.17-8.30 (6H, m), 8.76 (1H, d, J = 4.6 Hz)

[0122] In addition, Compound [67] was used as a light emitting device material after sublimation purification at about 260°C under a pressure of 1×10^{-3} Pa using an oil diffusion pump. The HPLC purity (area % at a measurement wavelength 254 nm) was 99.4% before sublimation purification, and 99.8% after sublimation purification.

Synthesis Example 10

35 Synthesis of Compound [86]

[0123] According to the same manner as in Synthesis Example 4 except that 3-quinolineboronic acid was used in place of 3-pyridineboronic acid, synthesis was performed to obtain a pale yellowish white crystal. ¹H-NMR analysis results of the resulting powder were as follows, and it was confirmed that the pale yellowish white crystal obtained above is Compound [86].

¹H-NMR(CDCl₃(d=ppm)): 1.60 (9H, s), 7.38-7.72 (1H, m), 7.51 (2H, t, J = 6.2 Hz), 7.61 (1H, t, J = 8.4 Hz), 7.69-7.90 (7H, m), 7.91-7.96 (4H, m), 8.02-8.09 (4H, m), 8.18 (1H, d, J = 8.6 Hz), 8.21-8.32 (4H, m), 8.44 (1H, d, J = 1.6 Hz), 9.33 (1H, d, J = 2.2 Hz).

[0124] In addition, Compound [86] was used as a light emitting device material after sublimation purification at about 300°C under a pressure of 1×10^{-3} Pa using an oil diffusion oil. The HPLC purity (area% at a measurement wavelength 254 nm) was 99.6% before sublimation purification, and 99.7% after sublimation purification.

Synthesis Example 11

50 Synthesis of Compound [120]

[0125] According to the same manner as in Synthesis Example 2 except that 3-quinolineboronic acid was used in place of 3-pyridineboronic acid, synthesis was performed to obtain a white crystal. ¹H-NMR analysis results of the resulting powder were as follows, and it was confirmed that the white crystal obtained above is Compound [120].

¹H-NMR(CDCl₃(d=ppm)): 1.60 (9H, s), 7.61 (2H, dt, J = 0.8 Hz, 7.0 Hz), 7.75 (2H, t, J = 6.8 Hz), 7.82-7.96 (10H, m), 8.07 (1H, s), 8.08 (2H, d, J = 9.5 Hz), 8.19 (2H, d, J = 7.8 Hz), 8.22-8.30 (4H, m), 8.44 (2H, d, J = 4.9 Hz), 9.33 (2H, d, J = 2.4 Hz).

[0126] In addition, Compound [120] was used as a light emitting device material after sublimation purification at about 340°C under a pressure of 1×10^{-3} Pa using an oil diffusion pump. The HPLC purity (area% at a measurement wavelength

EP 2 416 396 B1

254 nm) was 99.7% before sublimation purification, and 99.8% after sublimation purification.

Synthesis Example 12

5 Synthesis of Compound [177]

[0127] According to the same manner as in Synthesis Example 6 except that 3-(2-pyridylphenyl)boronic acid pinacolato ester was used in place of 4-(2-pyridylphenyl) boronic acid pinacolato ester, synthesis was performed to obtain a pale yellowish white crystal. ¹H-NMR analysis results of the resulting powder were as follows, and it was confirmed that the pale yellowish white crystal obtained above is Compound [177].

¹H-NMR (CDCl₃ (d=ppm)): 1.59 (9H, s), 7.21-7.28 (2H, m), 7.63-7.85 (8H, m), 8.07 (4H, dd, J = 9.5 Hz, 18.6 Hz), 8.12 (1H, dt, J = 1.6 Hz, 7.6 Hz), 8.20-8.30 (6H, m), 8.71 (2H, d, J = 4.9 Hz).

[0128] In addition, Compound [177] was used as a light emitting device material after sublimation purification at about 240°C under a pressure of 1×10^{-3} Pa using an oil diffusion pump. The HPLC purity (area% at a measurement wavelength 254 nm) was 99.7% before sublimation purification, and 99.9% after sublimation purification.

Synthesis Example 13

20 Synthesis of Compound [111]

[0129] A mixed solution of 3.0 g of 1-(4-(2-pyridyl)phenyl)-3-(4-chlorophenyl)-7-t-butylpyrene, 1.78 g of 4-(2-pyridylphenyl) boronic acid pinacolato ester, 66 mg of bis(dibenzylideneacetone)palladium, 50 mg of tricyclohexylphosphine tetrafluoroborate, 7.6 ml of an aqueous 1.27M tripotassium phosphate solution and 20 ml of 1,4-dioxane was heated and stirred for 3 hours under a nitrogen stream and under refluxing. After the mixture was cooled to room temperature, 40 ml of methanol was added, and this was filtered. The resulting solid was recrystallized with 40 ml of toluene, and filtered, and the resulting solid was vacuum dried to obtain 3.2 g of a pale yellowish white crystal.

[0130] ¹H-NMR analysis results of the resulting powder were as follows, and it was confirmed that the pale yellowish white crystal obtained above is Compound [111]. ¹H-NMR(CDCl₃(d=ppm)) : 1.60 (9H, s), 7.22-7.31 (2H, m), 7.73-7.92 (12H, m), 8.02-8.10 (3H, m), 8.11-8.30 (8H, m), 8.75 (2H, t, J = 5.9 Hz).



[0131] In addition, Compound [111] was used as a light emitting device material after sublimation purification at about 300°C under a pressure of 1×10^{-3} Pa using an oil diffusion pump. The HPLC purity (area% at a measurement wavelength 254 nm) was 99.4% before sublimation purification, and 99.9% after sublimation purification.

Reference Example 1

[0132] A glass substrate (manufactured by GEOMATEC Co.,Ltd., 11Ω/□, sputtered product) on which an ITO transparent electrically conductive film had been deposited in a thickness of 150 nm was cut into 38 × 46 mm, and this was subjected to etching. The resulting substrate was ultrasound-washed with "SEMICOCLEAN 56" (trade name, manufactured by Furuuchi Chemical Corporation) for 15 minutes, and washed with ultrapure water. This substrate was treated with UV-ozone for 1 hour immediately before manufacturing of a device, and placed in a vacuum evaporation equipment, and the air was evacuated until the degree of vacuum in the equipment became 5×10^{-4} Pa or lower. By a resistance heating method, first, as a hole injection material, copper phthalocyanine was evaporated in a thickness of 10 nm and, as a hole transporting material, 4,4'-bis(N-(1-naphthyl)-N-phenylamino)biphenyl was evaporated in a thickness of 50 nm. Then, Compound (H-1) as a host material, and Compound (D-1) as a dopant material were evaporated as an emissive material in a thickness of 40 nm so that the doping concentration became 5% by weight. Then, a layer in which Compound [1] and a donor compound (lithium fluoride) had been mixed was evaporated and laminated as an electron transporting layer in a thickness of 20 nm at a ratio of evaporation rate of 1 : 1 (=0.05 nm/s : 0.05 nm/s).

[0133] Then, after lithium fluoride was evaporated in a thickness of 0.5 nm, aluminum was evaporated in a thickness of 1000 nm to make a cathode, and a 5 × 5 mm square device was manufactured. The film thickness referred herein is a value displayed by a quartz oscillation-type film thickness monitor. When this light emitting device was direct-current driven at 10 mA/cm², high efficiency blue light emission at a driving voltage of 4.8 V and an external quantum efficiency of 5.0% was obtained.

[Chemical formula 17]



Reference Examples 2 to 4, 7, 8 and Examples 5, 6 and 9

25

[0134] According to the same manner as in Reference Example 1 except that materials described in Table 1 were used as the host material, the dopant material and the electron transporting layer, light emitting devices were manufactured. Results are shown in Table 1. In addition, in Table 1, 2E-1 is the following compound.

[Chemical formula 18]



(2E-1)

Comparative Examples 1 to 6


50

[0135] According to the same manner as in Reference Example 1 except that materials described in Table 1 were used as the host material, the dopant material, and the electron transporting material, light emitting devices were manufactured. Results are shown in Table 1. In addition, in Table 1, E-1, and E-2 are the following compounds.

[Chemical formula 19]

55

5




(E-1)

10

15

20

25



(E-2)

30

35

40

45

50

55

[Table 1]

	Light emitting material		Electron transporting layer		Cathode	External quantum efficiency (%)	Deriving voltage (V)
	Host material	Dopant material	Compound	Donor compound			
Reference Example 1	H-1	D-1	Compound [1]	Lithium fluoride	Al	5.0	4.8
Reference Example 2			Compound [1]	none	Al	4.2	4.9
Reference Example 3			Compound [53]	Lithium fluoride	Al	5.0	4.9
Reference Example 4			Compound [53]	none	Al	4.1	5.0
Example 5			Compound [56]	Lithium fluoride	Al	5.5	4.4
Example 6			Compound [56]	none	Al	5.0	4.7
Reference Example 7			Compound [1]	2E-1	Al	5.7	4.2
Reference Example 8			Compound [53]	2E-1	Al	5.6	4.3
Example 9			Compound [56]	2E-1	Al	5.9	4.0
Comparative Example 1	H-1	D-1	E-1	Lithium fluoride	Al	3.2	6.4
Comparative Example 2			E-1	2E-1	Al	3.4	6.2
Comparative Example 3			E-1	none	Al	2.5	7.8
Comparative Example 4			E-2	Lithium fluoride	Al	3.8	5.6
Comparative Example 5			E-2	2E-1	Al	3.9	5.5
Comparative Example 6			E-2	none	Al	3.0	5.8

Reference Examples 10 to 20

[0136] According to the same manner as in Reference Example 1 except that materials described in Table 2 were used as the host material, the dopant material, and the electron transporting layer, light emitting devices were manufactured. Results are shown in Table 2. In addition, in Table 2, H-2 to H-8, and D-2 to D-10 are the following compounds.

[Chemical formula 20]

10

15

20

25

30

35


40

45

50


55

5




(H-2)

10




(H-3)

15



(H-4)


20



(H-5)


25

30



(H-6)


35



(H-7)

40

45




(H-8)


50

55


[Chemical formula 21]




(D-2)




(D-3)




(D-4)




(D-5)




(D-6)




(D-7)



(D-8)



(D-9)



(D-10)

[Table 2]

	Light emitting material			Electron transporting layer		Cathode	External quantum efficiency (%)	Driving voltage M
	Host material	Dopant material	Emitting color	Compound	Donor compound	Metal		
Reference Example 10	H-1	D-2	Blue	Compound [1]	2E-1	Al	5.9	4.2
Reference Example 11		D-3	Blue			Al	5.8	4.1
Reference Example 12		D-4	Blue			Al	5.7	4.2
Reference Example 13	H-2	D-5	Blue			Al	7.2	4.9
Reference Example 14	H-3	D-6	Green	Compound [1]	2E-1	Al	7.3	4.5
Reference Example 15		D-7	Green			Al	7.2	4.5
Reference Example 16	H-4	D-8	Green			Al	11.3	5.0
Reference Example 17	H-5	D-9	Red	Compound [1]	2E-1	Al	5.0	4.6
Reference Example 18	H-6		Red			Al	6.2	4.5
Reference Example 19	H-7		Red			Al	6.0	4.5
Reference Example 20	H-8		D-10			Red	Al	10.1

Reference Example 21

[0137] A glass substrate (manufactured by GEOMATEC Co., Ltd., 11Ω/□, sputtered product) on which an ITO transparent electrically conductive film had been deposited in a thickness of 165 nm was cut into 38 × 46 mm, and this was subjected to etching. The resulting substrate was ultrasound-washed with "SEMICOCLEAN 56" (trade name, manufactured by Furuuchi Chemical Corporation) for 15 minutes, and washed with ultrapure water. This substrate was treated with UV-ozone for 1 hour immediately before manufacturing of a device, and placed in a vacuum evaporation equipment, and the air was evacuated until the degree of vacuum in the equipment became 5×10^{-4} Pa or lower. By a resistance heating method, first, as a hole injection material, 1,4,5,8,9,12-hexaazatriphenylenehexacarbonitrile was evaporated in a thickness of 10 nm and, as a hole transporting material, 4,4'-bis(N-(1-naphthyl)-N-phenylamino)biphenyl was evaporated in a thickness of 50 nm. Then, Compound (H-1) as a host material, and Compound (D-2) as a dopant material were evaporated as an emissive material in a thickness of 40 nm so that the doping concentration became 5% by weight. Then, a layer in which Compound [1] and a donor compound (2E-1: lithium quinolinol) had been mixed was laminated

EP 2 416 396 B1

as an electron transporting layer in a thickness of 10 nm at a ratio of evaporation rate of 1 : 1 (=0.05 nm/s : 0.05 nm/s).

[0138] Then, after lithium quinolinol was evaporated in a thickness of 1 nm, a co-evaporated film of magnesium and silver was evaporated in a thickness of 100 nm at a ratio of evaporation rate of magnesium : silver = 10 : 1 (= 0.5 nm/s : 0.05 nm/s) to make a cathode, and a 5 × 5 mm square device was manufactured. The film thickness referred herein is a value displayed by a quartz oscillation-type film thickness monitor. When this light emitting device was direct current-driven at 10 mA/cm², high efficiency blue light emission at a driving voltage of 3.9V and an external quantum efficiency of 6.2% was obtained.


Reference Example 22 and Example 23

[0139] According to the same manner as in Reference Example 21 except that materials described in Table 3 were used as the host material, the dopant material and the electron transporting layer, light emitting devices were manufactured. Results are shown in Table 3.


Comparative Examples 7 to 12

[0140] According to the same manner as in Reference Example 21 except that materials described in Table 3 were used as the electron transporting layer, light emitting devices were manufactured. Results are shown in Table 3. In addition, in Table 3, E-3 to E-8 are the following compounds.


[Chemical formula 22]




(E-3)




(E-4)




(E-5)



(E-6)



(E-7)



(E-8)

[Table 3]

	Light emitting material			Electron transporting layer		Cathode	External quantum efficiency (%)	Deriving voltage (V)
	Host material	Dopant material	Emitting color	Compound	Donor compound			
Reference Example 21	H-1	D-2	Blue	Compound [1]	2E-1	Mg/Ag	6.2	3.9
Reference Example 22			Blue	Compound [53]	2E-1	Mg/Ag	6.1	4.0
Example 23			Blue	Compound [56]	2E-1	Mg/Ag	6.4	3.7
Comparative Example 7			Blue	E-3	2E-1	Mg/Ag	3.9	4.6
Comparative Example 8			Blue	E-4	2E-1	Mg/Ag	4.9	4.5
Comparative Example 9			Blue	E-5	2E-1	Mg/Ag	4.8	4.8
Comparative Example 10			Blue	E-6	2E-1	Mg/Ag	5.1	4.7
Comparative Example 11			Blue	E-7	2E-1	Mg/Ag	4.6	4.7
Comparative Example 12			Blue	E-8	2E-1	Mg/Ag	5.2	4.6

Example 24

[0141] According to the same manner as in Reference Example 1 except that Compound [1] was used as the host material, and tris(8-quinolinolato)aluminum (III) was used as the electron transporting layer, a light emitting device was manufactured. When this light emitting device was direct current-driven at 10 mA/cm², high efficiency blue light emission at a driving voltage of 5.0 V and an external quantum efficiency of 4.8% was obtained.

Example 25

[0142] According to the same manner as in Example 24 except that Compound [91] was used as the host material, a light emitting device was manufactured. When this light emitting device was direct current-driven at 10 mA/cm², high efficiency blue light emission at a driving voltage of 4.9 V and an external quantum efficiency of 4.9% was obtained.


Example 26

[0143] According to the same manner as in Example 24 except that Compound [106] was used as the host material, a light emitting device was manufactured. When this light emitting device was direct current-driven at 10 mA/cm², high efficiency blue light emission at a driving voltage of 5.1 V and an external quantum efficiency of 4.6% was obtained.

Example 27

[0144] A glass substrate (manufactured by GEOMATEC Co., Ltd., 11Ω, sputtered product) on which an ITO transparent electrically conductive film had been deposited in a thickness of 165 nm was cut into 38 × 46 mm, and this was subjected to etching. The resulting substrate was ultrasound-washed with "SEMICOCLEAN 56" (trade name, manufactured by Furuuchi Chemical Corporation) for 15 minutes, and washed with ultrapure water. This substrate was treated with UV-ozone for 1 hour immediately before manufacturing of a device, and placed in a vacuum evaporation equipment, and the air was evacuated until the degree of vacuum in the equipment became 5 × 10⁻⁴ Pa or lower. By a resistance heating method, first, as a hole injection material, copper phthalocyanine was evaporated in a thickness of 10 nm and, as a hole transporting material, Compound (HT-1) was evaporated in a thickness of 50 nm. Then, Compound (H-1) as a host material, and Compound (D-1) as a dopant material were evaporated as an emissive material in a thickness of 40 nm so that the doping concentration became 5% by weight. Then, Compound [10] as an electron transporting layer was evaporated in a thickness of 20 nm. Then, after lithium fluoride was evaporated in a thickness of 0.5 nm, aluminum was evaporated in a thickness of 1000 nm to make a cathode, and a 5 × 5 square device was manufactured. The film thickness referred herein is a value displayed by a quartz oscillation-type film thickness monitor. When this light emitting device was direct current-driven at 10 mA/cm², high efficiency blue light emission at a driving voltage of 4.9 V and an external quantum efficiency of 4.6% was obtained.

[Chemical formula 23]



(HT-1)

Examples 28 to 32 and Reference Examples 33 to 35

[0145] According to the same manner as in Example 27 except that materials described in Table 4 were used as the electron transporting layer, light emitting devices were manufactured. Results are shown in Table 4.


Example 36

[0146] A layer in which Compound [10] and Compound [106] had been mixed was evaporated and laminated as an electron transporting layer in a thickness of 20 nm at a ratio of evaporation rate of 1 : 1 (=0.05 nm/s : 0.05 nm/s). According to the same manner as in 27 except for those described above, a light emitting device was manufactured. Results are shown in Table 4.

Example 37

[0147] According to the same manner as in Example 36 except that a layer in which Compound [10] and Compound (E-9) had been mixed was evaporated and laminated as the electron transporting layer in a thickness of 20 nm at a ratio of evaporation rate of 1 : 1 (=0.05 nm/s : 0.05 nm/s), a light emitting device was manufactured. Results are shown in Table 4. In addition, E-9 in Table 4 is the following compound.

[Chemical formula 24]



(E-9)

Comparative Examples 13 to 14

[0148] According to the same manner as in Example 27 except that materials described in Table 4 were used as the electron transporting layer, light emitting devices were manufactured. Results are shown in Table 4.

[Table 4]

	Light emitting material		Electron transporting layer		Cathode	External quantum efficiency (%)	Driving voltage (V)	
	Host material	Dopant material	Compound	Donor compound				Metal
Example 27	H-1	D-1	Compound [10]	none	Al	4.6	4.9	
Example 28			Compound [107]	none	Al	4.8	4.8	
Example 29			Compound [91]	none	Al	4.6	4.9	
Example 30			Compound [63]	none	Al	4.5	5.0	
Example 31			Compound [106]	none	Al	4.7	4.8	
Example 32			Compound [144]	none	Al	4.6	5.0	
Reference Example 33					Compound [1]	Al	4.2	5.1
Reference Example 34					Compound [26]	Al	4.0	5.2
Reference Example 35					Compound [32]	Al	4.0	5.1
Example 36					Compound [10]	Al	4.5	5.1
Example 37					Compound [10]	Al	4.6	5.0
Comparative Example 13					E-1	Al	2.5	7.7
Comparative Example 14					E-2	Al	3.0	5.7

Examples 38

5 [0149] A layer in which Compound [10] and a donor compound (lithium fluoride) had been mixed was evaporated and laminated as an electron transporting layer in a thickness of 20 nm at a ratio of evaporation rate of 1 : 1 (=0.05 nm/s : 0.05 nm/s). According to the same manner as in Example 27 except for those described above, a light emitting device was manufactured. Results are shown in Table 5.

Examples 39 to 43

10 [0150] According to the same manner as in Example 38 except that materials described in Table 5 were used as the electron transporting layer, light emitting devices were manufactured. Results are shown in Table 5.

Example 44

15 [0151] A layer in which Compound [10] and Donor Compound (2E-1) had been mixed was evaporated and laminated as an electron transporting layer in a thickness of 20 nm at a ratio of evaporation rate of 1 : 1 (=0.05 nm/s : 0.05 nm/s). According to the same manner as in Example 38 except for those described above, a light emitting device was manufactured. Results are shown in Table 5.

20 Examples 45 to 49

[0152] According to the same manner as in Example 44 except that materials described in Table 5 were used as the electron transporting layer, light emitting devices were manufactured. Results are shown in Table 5.

25 Example 50

30 [0153] A layer in which Compound [10] and Donor Compound (2E-1) had been mixed was evaporated and laminated as an electron transporting layer in a thickness of 20 nm at a ratio of evaporation rate of 7 : 3 (=0.07 nm/s : 0.03 nm/s). According to the same manner as in Example 44 except for those described above, a light emitting device was manufactured. Results are shown in Table 5.

Examples 51 to 55

35 [0154] According to the same manner as in Example 50 except that materials described in Table 5 were used as the electron transporting layer, light emitting devices were manufactured. Results are shown in Table 5.

Example 56

40 [0155] A layer in which Compound [10] and Donor Compound (2E-1) had been mixed was evaporated and laminated as an electron transporting layer in a thickness of 20 nm at a ratio of evaporation rate of 3 : 7 (=0.03 nm/s : 0.07 nm/s). According to the same manner as in Example 44 except for those described above, a light emitting device was manufactured. Results are shown in Table 5.

Examples 57 to 61

45 [0156] According to the same manner as in Example 56 except that materials described in Table 5 were used as the electron transporting layer, light emitting devices were manufactured. Results are shown in Table 5.

50

55

[Table 5]

	Light emitting material		Electron transporting layer				Cathode	External quantum efficiency (%)	Driving voltage (V)
	Host material	Dopant material	Emitting color	Compound	Donor compound	Mixing ratio			
Example 38	H-1	D-1	Blue	Compound [10]	Lithium fluoride	1:1	Al	5.2	4.6
Example 39			Blue	Compound [107]				5.1	4.5
Example 40			Blue	Compound [91]				5.2	4.6
Example 41			Blue	Compound [63]				5.2	4.7
Example 42			Blue	Compound [106]				5.1	4.5
Example 43			Blue	Compound [144]				5.0	4.6
Example 44			H-1	D-1				Blue	Compound [10]
Example 45	Blue	Compound [107]			5.8	4.1			
Example 46	Blue	Compound [91]			6.0	4.0			
Example 47	Blue	Compound [63]			5.8	4.1			
Example 48	Blue	Compound [106]			5.9	4.0			
Example 49	Blue	Compound [144]			5.7	4.1			
Example 50	H-1	D-1			Blue	Compound [10]	2E-1	7:3	Al
Example 51			Blue	Compound [107]	5.8	4.1			
Example 52			Blue	Compound [91]	5.9	4.1			
Example 53			Blue	Compound [63]	5.8	4.1			
Example 54			Blue	Compound [106]	6.0	3.9			
Example 55			Blue	Compound [144]	5.7	4.2			
Example 56			H-1	D-1	Blue	Compound [10]			
Example 57	Blue	Compound [107]			6.0	4.0			
Example 58	Blue	Compound [91]			5.9	4.0			
Example 59	Blue	Compound [63]			6.0	4.1			
Example 60	Blue	Compound [106]			6.2	3.8			
Example 61	Blue	Compound [144]			5.9	4.0			

Examples 62 to 109

[0157] According to the same manner as in Example 38 except that materials described in Table 6 were used as the host material and the dopant material, light emitting devices were manufactured. Results are shown in Table 6. In addition, in Table 6, D-11, and H-9 to H-12 are the following compounds.

[Chemical formula 25]

10

15

20

25

30






35

40

45

50

55



EP 2 416 396 B1

[Table 6]

	Light emitting material			Electron transporting layer		Cathode	External quantum efficiency (%)	Driving voltage (V)		
	Host material	Dopant material	Emitting color	Compound	Donor compound	Metal				
5	Example 62	H-1	D-2	Compound [107]	2E-1	Al	6.0	4.1		
10	Example 63		D-3				Blue	5.9	4.0	
	Example 64		D-4				Blue	5.8	4.1	
15	Example 65		D-11				Blue	6.0	4.1	
	Example 66	D-3	Blue				5.8	4.2		
20	Example 67						H-10	Blue	5.9	4.2
	Example 68						H-11	Blue	5.7	4.4
25	Example 69						H-12	Blue	5.8	4.3
	Example 70	H-2	D-5				Blue	7.4	4.7	
30	Example 71	H-3	D-6				Green	7.4	4.4	
	Example 72		D-7				Green	7.3	4.5	
35	Example 73	H-4	D-8				Green	11.3	4.9	
	Example 74	D-9	Red				5.2	4.5		
40	Example 75						H-6	Red	6.4	4.4
	Example 76						H-7	Red	6.1	4.5
45	Example 77						H-8	D-10	Red	10.3

50

55

EP 2 416 396 B1

(continued)

	Light emitting material			Electron transporting layer		Cathode	External quantum efficiency (%)	Driving voltage (V)	
	Host material	Dopant material	Emitting color	Compound	Donor compound	Metal			
5	Example 78	H-1	D-2	Compound [91]	2E-1	Al	6.0	4.0	
10	Example 79		D-3				Blue	6.0	3.9
	Example 80		D-4				Blue	5.9	3.9
15	Example 81		D-11				Blue	5.9	4.2
	Example 82	H-9	D-3				Blue	5.7	4.2
20	Example 83	H-10					Blue	5.8	4.2
	Example 84	H-11					Blue	5.8	4.3
25	Example 85	H-12					Blue	5.7	4.2
	Example 86	H-2	D-5				Blue	7.3	4.7
30	Example 87	H-3	D-6				Green	7.4	4.3
	Example 88		D-7				Green	7.3	4.6
35	Example 89	H-4	D-8				Green	11.2	4.9
	Example 90	H-5	D-9				Red	5.3	4.6
40	Example 91	H-6		Red	6.6	4.4			
	Example 92	H-7		Red	6.2	4.5			
45	Example 93	H-8		D-10	Red	10.1	5.0		

50

55

(continued)

	Light emitting material			Electron transporting layer		Cathode	External quantum efficiency (%)	Driving voltage (V)	
	Host material	Dopant material	Emitting color	Compound	Donor compound	Metal			
5	Example 94	H-1	D-2	Compound [106]	2E-1	Al	6.0	4.1	
10	Example 95		D-3				Blue	5.9	4.0
	Example 96		D-4				Blue	5.8	4.0
15	Example 97		D-11				Blue	6.1	4.0
	Example 98	H-9	D-3				Blue	5.8	4.1
20	Example 99	H-10					Blue	5.8	4.3
	Example 100	H-11					Blue	5.7	4.4
25	Example 101	H-12					Blue	5.8	4.2
	Example 102	H-2	D-5				Blue	7.3	4.8
30	Example 103	H-3	D-6				Green	7.5	4.3
	Example 104		D-7	Green	7.2	4.6			
35	Example 105	H-4	D-8	Green	11.2	4.9			
	Example 106	H-5	D-9	Red	5.3	4.5			
40	Example 107	H-6		Red	6.5	4.4			
	Example 108	H-7		Red	6.2	4.4			
45	Example 109	H-8		D-10	Red	10.2	4.9		


Example 110

[0158] A glass substrate (manufactured by GEOMATEC Co., Ltd., 11Ω, sputtered product) on which an ITO transparent electrically conductive film had been deposited in a thickness of 165 nm was cut into 38 × 46 mm, and this was subjected to etching. The resulting substrate was ultrasound-washed with "SEMICOCLEAN 56" (trade name, manufactured by Furuuchi Chemical Corporation) for 15 minutes, and washed with ultrapure water. This substrate was treated with UV-ozone for 1 hour immediately before manufacturing of a device, and placed in a vacuum evaporation equipment, and the air was evacuated until the degree of vacuum in the equipment became 5×10^{-4} Pa or lower. By a resistance heating method, first, as a hole injection material, Compound (HT-2) was laminated in a thickness of 65 nm, and 1,4,5,8,9,12-hexaazatriphenylenehexacarbonitrile was laminated in a thickness of 5 nm, sequentially. Compound (HT-3) as a hole transporting material was evaporated in a thickness of 60 nm. Then, Compound (H-1) as a host material, and Compound (D-3) as a dopant material were evaporated as an emissive material in a thickness of 20 nm so that the doping concen-

tration became 5% by weight. Then, a layer in which Compound [10] and donor compound (2E-1: lithium quinolinol) had been mixed was evaporated as an electron transporting layer in thickness of 30 nm at a ratio of evaporation rate of 1 : 1 (=0.05 nm/s : 0.05 nm/s).

[0159] Then, after lithium quinolinol was evaporated in a thickness of 5 nm, a co-evaporated film of magnesium and silver was evaporated in a thickness of 15 nm at a ratio of evaporation rate of magnesium : silver = 10 : 1 (=0.05 nm/s : 0.05 nm/s) to make a cathode, and a 5 × 5 mm square device was manufactured. The film thickness referred herein is a value displayed by a quartz oscillation-type film thickness monitor. When this light emitting device was direct current-driven at 10 mA/cm², high efficiency blue light emission at a driving voltage of 3.8 V and an external quantum efficiency of 6.3% was obtained.


[Chemical formula 26]



Examples 111 116, 118, 120 to 142, 144 to 147 and Reference Examples 117, 119 and 143

[0160] According to the same manner as in Example 110 except that materials described in Tables 7 and 8 were used as the electron transporting layer, light emitting devices were manufactured. Results are shown in Tables 7 and 8. In addition, in Tables 7 and 8, D-12 to D-14, and H-13 and H-14 are the following compounds.

[Chemical formula 27]



[Table 7]

	Light emitting material			Electron transporting layer		Cathode	External quantum efficiency (%)	Driving voltage M
	Host material	Dopant material	Emitting color	Compound	Donor compound	Metal		
5	H-1	D-3	Blue	Compound [10]	2E-1	Mg/Ag	6.3	3.8
10			Blue	Compound [107]			6.4	3.8
15			Blue	Compound [91]			6.5	3.7
15			Blue	Compound [63]			6.2	3.9
20			Blue	Compound [106]			6.3	3.7
20			Blue	Compound [144]			6.2	3.7
25	H-1	D-12	Blue	Compound [34]	2E-1	Mg/Ag	6.2	3.8
25			Blue	Compound [36]			5.8	4.4
30			Blue	Compound [46]			5.7	4.1
30			Blue	Compound [47]			5.7	4.4
35			Blue	Compound [49]			6.1	3.9
35			Blue	Compound [60]			6.2	3.8
40			Blue	Compound [65]			6.2	3.8
40			Blue	Compound [67]			6.3	3.9
45			Blue	Compound [86]			6.1	3.8
45			Blue	Compound [93]			6.2	3.7
50			Blue	Compound [111]			6.3	3.7
50			Blue	Compound [120]			6.1	3.9
55	Blue	Compound [177]	6.0	3.9				


[Table 8]

	Light emitting material			Electron transporting layer		Cathode	External quantum efficiency (%)	Driving voltage (V)					
	Host material	Dopant material	Emitting color	Compound	Donor compound	Metal							
5	Example 129	H-1	D-13	Blue	Compound [66]	2E-1	Mg/Ag	6.1	3.8				
10	Example 130			Blue	Compound [81]			6.0	3.9				
	Example 131			Blue	Compound [88]			6.2	3.7				
15	Example 132			Blue	Compound [96]			6.0	3.9				
	Example 133			Blue	Compound [105]			6.0	3.8				
20	Example 134			Blue	Compound [168]			5.6	4.2				
	Example 135			Blue	Compound [176]			6.3	3.7				
25	Example 136			H-13	D-13			Blue	Compound [76]	2E-1	Mg/Ag	6.0	3.9
	Example 137							Blue	Compound [82]			5.8	4.0
30	Example 138							Blue	Compound [85]			6.1	3.8
	Example 139	Blue	Compound [90]			6.2	3.7						
35	Example 140	Blue	Compound [94]			6.0	3.9						
	Example 141	H-1	D-14			Blue	Compound [112]	2E-1	Mg/Ag			6.2	3.7
40	Example 142			Blue	Compound [116]	6.1	3.8						
	Reference Example 143			Blue	Compound [160]	5.9	3.9						
45	Example 144			Blue	Compound [164]	5.6	4.2						
	Example 145			Blue	Compound [69]	6.2	3.8						
50	Example 146			H-143	D-14	Blue	Compound [97]			2E-1	Mg/Ag	6.0	3.9
55	Example 147					Blue	Compound [169]					5.7	4.2

Claims

1. A light emitting device material comprising a pyrene compound represented by the following general formula (1):


[Chemical formula 1]



R¹ to R⁷ may be the same or different, and are each selected from the group consisting of hydrogen, an alkyl group, a cycloalkyl group, a heterocyclic group, an alkenyl group, a cycloalkenyl group, an alkynyl group, an alkoxy group, an alkylthio group, an aryloxy group, an arylthio group, an aryl group, a heteroaryl group, a halogen, a carbonyl group, a carboxyl group, an oxycarbonyl group, a carbamoyl group, an amino group, a silyl group and -P(=O)R⁸R⁹. R⁸ and R⁹ are each an aryl group or a heteroaryl group, and adjacent substituents may form a ring. L¹ and L² may be the same or different, L¹ is an arylene group and L² is a single bond or an arylene group. X is selected from the group consisting of an alkyl group, an aryl group and a heteroaryl group. Ar¹ is an aromatic heterocyclic group containing electron-accepting nitrogen, and Ar² is an aryl group or a heteroaryl group, provided that when Ar² is a heteroaryl group, a dibenzofuranyl group, a dibenzothiophenyl group and a carbazolyl group are excluded.

2. The light emitting device material according to claim 1, wherein Ar¹ is an aromatic heterocyclic group containing electron-accepting nitrogen unsubstituted or substituted, and when substituted, the substituent is an alkyl group, an aryl group, a furanyl group, a thiophenyl group, a pyridyl group, a quinoliny group, an isoquinoliny group, a pyrazinyl group, a pyrimidyl group, a naphthyridyl group, a benzofuranyl group, a benzothiophenyl group, an indolyl group, a dibenzothiophenyl group, or a carbazolyl group.
3. A light emitting device comprising at least an emissive layer and an electron transporting layer between an anode and a cathode, and emitting light by an electric energy, wherein the light emitting device contains a pyrene compound represented by the following general formula (1) in any layer between the anode and the cathode:

[Chemical formula 2]



R¹ to R⁷ may be the same or different, and are each selected from the group consisting of hydrogen, an alkyl group,


a cycloalkyl group, a heterocyclic group, an alkenyl group, a cycloalkenyl group, an alkynyl group, an alkoxy group, an alkylthio group, an arylother group, an arylthioether group, an aryl group, a heteroaryl group, a halogen, a carbonyl group, a carboxyl group, an oxycarbonyl group, a carbamoyl group, an amino group, a silyl group and $-P(=O)R^8R^9$. R^8 and R^9 are each an aryl group or a heteroaryl group, and adjacent substituents may form a ring. L^1 and L^2 may be the same or different, L^1 is an arylene group and L^2 is a single bond or an arylene group. X is selected from the group consisting of an alkyl group, an aryl group and a heteroaryl group. Ar^1 is an aromatic heterocyclic group containing electron-accepting nitrogen, and Ar^2 is an aryl group or a heteroaryl group, provided that when Ar^2 is a heteroaryl group, a dibenzofuranyl group and a carbazolyl group are excluded.

4. The light emitting device according to claim 3, wherein Ar^1 is an aromatic heterocyclic group containing electron-accepting nitrogen unsubstituted or substituted, and when substituted, the substituent is an alkyl group, an aryl group, a furanyl group, a thiophenyl group, a pyridyl group, a quinolinyl group, an isoquinolinyl group, a pyrazinyl group, a pyrimidyl group, a naphthyridyl group, a benzofuranyl group, a benzothiophenyl group, an indolyl group, a dibenzothiophenyl group, or a carbazolyl group.
5. The light emitting device according to claim 3 or 4, which comprises the pyrene compound represented by the general formula (1) in the electron transporting layer.
6. The light emitting device according to claim 5, which comprises a donor compound in the electron transporting layer.
7. The light emitting device according to claim 6, wherein the donor compound is an alkali metal, an inorganic salt containing an alkali metal, a complex of an alkali metal and an organic substance, an alkaline earth metal, an inorganic salt containing an alkaline earth metal, or a complex of an alkaline earth metal and an organic substance.
8. The light emitting device according to claim 6, wherein the donor compound is a complex of an alkali metal and an organic substance or a complex of an alkaline earth metal and an organic substance.
9. The light emitting device according to claim 3 or 4, which comprises the pyrene compound represented by the general formula (1) in the emissive layer.
10. The light emitting device according to any one of claims 3 to 9, wherein the cathode is constituted by magnesium and silver.

Patentansprüche

1. Material für eine lichtemittierende Vorrichtung, umfassend eine Pyren-Verbindung, die durch die folgende allgemeine Formel (1) dargestellt ist:

[Chemische Formel 1]




wobei R^1 bis R^7 gleich oder unterschiedlich sein können und jeweils ausgewählt sind aus der Gruppe bestehend aus Wasserstoff, einer Alkylgruppe, einer Cycloalkylgruppe, einer heterocyclischen Gruppe, einer Alkenylgruppe,

einer Cycloalkenylgruppe, einer Alkynylgruppe, einer Alkoxygruppe, einer Alkylthiogruppe, einer Arylethergruppe, einer Arylthioethergruppe, einer Arylgruppe, einer Heteroarylgruppe, einem Halogen, einer Carbonylgruppe, einer Carboxylgruppe, einer Oxycarbonylgruppe, einer Carbamoylgruppe, einer Aminogruppe, einer Silylgruppe und -P (= O) R⁸R⁹, R⁸ und R⁹ jeweils eine Arylgruppe oder eine Heteroarylgruppe sind, und benachbarte Substituenten einen Ring bilden können, L¹ und L² gleich oder unterschiedlich sein können, L¹ eine Arylengruppe ist und L² eine Einfachbindung oder eine Arylengruppe ist, X ausgewählt ist aus der Gruppe bestehend aus einer Alkylgruppe, einer Arylgruppe und einer Heteroarylgruppe, Ar¹ eine aromatische heterocyclische Gruppe ist, die Elektronen aufnehmenden Stickstoff enthält, und Ar² eine Arylgruppe oder eine Heteroarylgruppe mit der Maßgabe ist, dass wenn Ar² eine Heteroarylgruppe ist, eine Dibenzofuranylgruppe, eine Dibenzothiophenylgruppe und eine Carbazolylgruppe ausgeschlossen sind.

2. Material für eine leuchtende Vorrichtung nach Anspruch 1, wobei Ar¹ eine aromatische heterocyclische Gruppe ist, die Elektronen aufnehmenden Stickstoff unsubstituiert oder substituiert enthält, und wenn substituiert, der Substituent eine Alkylgruppe, eine Arylgruppe, eine Furanylgruppe, eine Thiophenylgruppe, eine Pyridylgruppe, eine Chinolinylgruppe, eine Isochinolinylgruppe, eine Pyrazinylgruppe, eine Pyrimidinylgruppe, eine Naphthyridylgruppe, eine Benzofuranylgruppe, eine Benzothiophenylgruppe, eine Indolylgruppe, eine Dibenzothiophenylgruppe oder eine Carbazolylgruppe ist.
3. Leuchtende Vorrichtung, die mindestens eine emittierende Schicht und eine Elektronentransportschicht zwischen einer Anode und einer Kathode aufweist und Licht durch elektrische Energie emittiert, wobei die leuchtende Vorrichtung in jeder Schicht zwischen der Anode und der Kathode eine Pyren-Verbindung enthält, die durch die folgende allgemeine Formel (1) dargestellt ist:

[Chemische Formel 2]



wobei R¹ bis R⁷ gleich oder unterschiedlich sein können und jeweils ausgewählt sind aus der Gruppe, bestehend aus Wasserstoff, einer Alkylgruppe, einer Cycloalkylgruppe, einer heterocyclischen Gruppe, einer Alkenylgruppe, einer Cycloalkenylgruppe, einer Alkynylgruppe, einer Alkoxygruppe, einer Alkylthiogruppe, einer Arylethergruppe, einer Arylthioethergruppe, einer Arylgruppe, einer Heteroarylgruppe, einem Halogen, einer Carbonylgruppe, einer Carboxylgruppe, einer Oxycarbonylgruppe, einer Carbamoylgruppe, einer Aminogruppe, einer Silylgruppe und -P (= O) R⁸R⁹, R⁸ und R⁹ jeweils eine Arylgruppe oder eine Heteroarylgruppe sind, und benachbarte Substituenten einen Ring bilden können, L¹ und L² gleich oder unterschiedlich sein können, L¹ eine Arylengruppe ist und L² eine Einfachbindung oder eine Arylengruppe ist, X ausgewählt ist aus der Gruppe bestehend aus einer Alkylgruppe, einer Arylgruppe und einer Heteroarylgruppe, Ar¹ eine aromatische heterocyclische Gruppe ist, die Elektronen aufnehmenden Stickstoff enthält, und Ar² eine Arylgruppe oder eine Heteroarylgruppe mit der Maßgabe ist, dass wenn Ar² eine Heteroarylgruppe ist, eine Dibenzofuranylgruppe und eine Carbazolylgruppe ausgeschlossen sind.


4. Leuchtende Vorrichtung nach Anspruch 3, wobei Ar¹ eine aromatische heterocyclische Gruppe ist, die Elektronen aufnehmenden Stickstoff unsubstituiert oder substituiert enthält, und wenn substituiert, der Substituent eine Alkylgruppe, eine Arylgruppe, eine Furanylgruppe, eine Thiophenylgruppe, eine Pyridylgruppe, eine Chinolinylgruppe, eine Isochinolinylgruppe, eine Pyrazinylgruppe, eine Pyrimidinylgruppe, eine Naphthyridylgruppe, eine Benzofuranylgruppe, eine Benzothiophenylgruppe, eine Indolylgruppe, eine Dibenzothiophenylgruppe oder eine Carbazolylgruppe ist.

5. Lichtemittierende Vorrichtung nach Anspruch 3 oder 4, welche die durch die allgemeine Formel (1) dargestellte Pyren-Verbindung in der Elektronentransportschicht enthält.
6. Lichtemittierende Vorrichtung nach Anspruch 5, die eine Donorverbindung in der Elektronentransportschicht enthält.
7. Lichtemittierende Vorrichtung nach Anspruch 6, wobei die Donorverbindung ein Alkalimetall, ein anorganisches Salz, das ein Alkalimetall enthält, ein Komplex aus einem Alkalimetall und einer organischen Substanz, ein Erdalkalimetall, ein anorganisches Salz, das ein Erdalkalimetall enthält, oder ein Komplex aus einem Erdalkalimetall und einer organischen Substanz ist.
8. Lichtemittierende Vorrichtung nach Anspruch 6, wobei die Donorverbindung ein Komplex aus einem Alkalimetall und einer organischen Substanz oder ein Komplex aus einem Erdalkalimetall und einer organischen Substanz ist.
9. Lichtemittierende Vorrichtung nach Anspruch 3 oder 4, welche die durch die allgemeine Formel (1) dargestellte Pyren-Verbindung in der emittierenden Schicht enthält.
10. Lichtemittierende Vorrichtung nach einem der Ansprüche 3 bis 9, wobei die Kathode aus Magnesium und Silber zusammengesetzt ist.

Revendications

1. Matériau de dispositif électroluminescent comprenant un composé de pyrène représenté par la formule générale (1) suivante :

[Formule chimique 1]



(1)

R¹ à R⁷ peuvent être identiques ou différents, et sont choisis chacun dans le groupe constitué d'un atome d'hydrogène, d'un groupe alkyle, d'un groupe cycloalkyle, d'un groupe hétérocyclique, d'un groupe alcényle, d'un groupe cycloalcényle, d'un groupe alcynyle, d'un groupe alcoxy, d'un groupe alkylthio, d'un groupe aryléther, d'un groupe arylthioéther, d'un groupe aryle, d'un groupe hétéroaryle, d'un atome d'halogène, d'un groupe carbonyle, d'un groupe carboxyle, d'un groupe oxycarbonyle, d'un groupe carbamoyle, d'un groupe amino, d'un groupe silyle et de -P(=O)R⁸R⁹. R⁸ et R⁹ représentent chacun un groupe aryle ou un groupe hétéroaryle, et des substituants adjacents peuvent former un cycle. L¹ et L² peuvent être identiques ou différents, L¹ représente un groupe arylène et L² représente une liaison simple ou un groupe arylène. X est choisi dans le groupe constitué d'un groupe alkyle, d'un groupe aryle et d'un groupe hétéroaryle. Ar¹ représente un groupe hétérocyclique aromatique contenant de l'azote accepteur d'électrons, et Ar² représente un groupe aryle ou un groupe hétéroaryle, à condition que, lorsque Ar² représente un groupe hétéroaryle, un groupe dibenzofuranyle, un groupe dibenzothiophényle et un groupe carbazole soient exclus.

2. Matériau de dispositif électroluminescent selon la revendication 1, dans lequel Ar¹ représente un groupe hétérocyclique aromatique contenant de l'azote accepteur d'électrons non substitué ou substitué, et lorsqu'il est substitué, le substituant est un groupe alkyle, un groupe aryle, un groupe furanyle, un groupe thiophényle, un groupe pyridyle,

un groupe quinoléinyle, un groupe isoquinoléinyle, un groupe pyrazinyle, un groupe pyrimidyle, un groupe naphthyridyle, un groupe benzofuranyle, un groupe benzothiophényle, un groupe indolyle, un groupe dibenzothiophényle, ou un groupe carbazolyle.


- 5 3. Dispositif électroluminescent comprenant au moins une couche émissive et une couche de transport d'électrons entre une anode et une cathode, et émettant de la lumière par énergie électrique, où le dispositif électroluminescent contient un composé de pyrène représenté par la formule générale (1) suivante dans une couche quelconque entre l'anode et la cathode :

10

[Formule chimique 2]

15

20



25

30

35

R¹ à R⁷ peuvent être identiques ou différents, et sont chacun choisis dans le groupe constitué d'un atome d'hydrogène, d'un groupe alkyle, d'un groupe cycloalkyle, d'un groupe hétérocyclique, d'un groupe alcényle, d'un groupe cycloalcényle, d'un groupe alcynyle, d'un groupe alcoxy, d'un groupe alkylthio, d'un groupe aryléther, d'un groupe arylthioéther, d'un groupe aryle, d'un groupe hétéroaryle, d'un atome d'halogène, d'un groupe carbonyle, d'un groupe carboxyle, d'un groupe oxycarbonyle, d'un groupe carbamoyle, d'un groupe amino, d'un groupe silyle et de -P(=O)R⁸R⁹. R⁸ et R⁹ représentent chacun un groupe aryle ou un groupe hétéroaryle, et des substituants adjacents peuvent former un cycle. L¹ et L² peuvent être identiques ou différents, L¹ représente un groupe arylène et L² représente une liaison simple ou un groupe arylène. X est choisi dans le groupe constitué d'un groupe alkyle, d'un groupe aryle et d'un groupe hétéroaryle. Ar¹ représente un groupe hétérocyclique aromatique contenant de l'azote accepteur d'électrons, et Ar² représente un groupe aryle ou un groupe hétéroaryle, à condition que, lorsque Ar² représente un groupe hétéroaryle, un groupe dibenzofuranyle et un groupe carbazole soient exclus.

40

45

50

55

4. Dispositif électroluminescent selon la revendication 3, dans lequel Ar¹ représente un groupe hétérocyclique aromatique contenant de l'azote accepteur d'électrons non substitué ou substitué, et lorsqu'il est substitué, le substituant est un groupe alkyle, un groupe aryle, un groupe furanyle, un groupe thiophényle, un groupe pyridyle, un groupe quinoléinyle, un groupe isoquinoléinyle, un groupe pyrazinyle, un groupe pyrimidyle, un groupe naphthyridyle, un groupe benzofuranyle, un groupe benzothiophényle, un groupe indolyle, un groupe dibenzothiophényle, ou un groupe carbazolyle.
5. Dispositif électroluminescent selon la revendication 3 ou 4, qui comprend le composé de pyrène représenté par la formule générale (1) dans la couche de transport d'électrons.
6. Dispositif électroluminescent selon la revendication 5, qui comprend un composé donneur dans la couche de transport d'électrons.
7. Dispositif électroluminescent selon la revendication 6, dans lequel le composé donneur est un métal alcalin, un sel inorganique contenant un métal alcalin, un complexe d'un métal alcalin et d'une substance organique, un métal alcalino-terreux, un sel inorganique contenant un métal alcalino-terreux, ou un complexe d'un métal alcalino-terreux et d'une substance organique.
8. Dispositif électroluminescent selon la revendication 6, dans lequel le composé donneur est un complexe d'un métal alcalin et d'une substance organique ou un complexe d'un métal alcalino-terreux et d'une substance organique.
9. Dispositif électroluminescent selon la revendication 3 ou 4, qui comprend le composé de pyrène représenté par la

formule générale (1) dans la couche émissive.

- 10.** Dispositif électroluminescent selon l'une quelconque des revendications 3 à 9, dans lequel la cathode est constituée de magnésium et d'argent.

5

10

15

20

25

30

35

40

45

50

55

REFERENCES CITED IN THE DESCRIPTION

This list of references cited by the applicant is for the reader's convenience only. It does not form part of the European patent document. Even though great care has been taken in compiling the references, errors or omissions cannot be excluded and the EPO disclaims all liability in this regard.

Patent documents cited in the description

- WO 200729798 A [0006]
- WO 2008108256 A [0006]
- JP 2007131723 A [0006]
- WO 200690772 A [0006]
- EP 1808912 A [0006]
- CN 101407493 [0006]
- WO 2010001817 A [0006]
- JP 2000348864 A [0006]
- JP 2004277377 A [0006]
- JP 2003347060 A [0006]
- JP 2002352961 A [0006]
- JP 2004002297 A [0006]
- EP 1942171 A1 [0007]
- EP 2296204 A1 [0007]
- JP 2004319424 A [0007]
- EP 1852486 A1 [0007]

Non-patent literature cited in the description


- *Applied Physics Letters*, (USA), 1987, vol. 51 (12), 913-915 [0007]

专利名称(译)	发光元件材料和发光元件		
公开(公告)号	EP2416396B1	公开(公告)日	2015-05-13
申请号	EP2010758516	申请日	2010-03-25
[标]申请(专利权)人(译)	东丽株式会社		
申请(专利权)人(译)	TORAY INDUSTRIES, INC.		
当前申请(专利权)人(译)	TORAY INDUSTRIES, INC.		
[标]发明人	NAKANO YOHEI SUGIMOTO KAZUNORI NAGAO KAZUMASA TANAKA DAISAKU TOMINAGA TSUYOSHI		
发明人	NAKANO, YOHEI SUGIMOTO, KAZUNORI NAGAO, KAZUMASA TANAKA, DAISAKU TOMINAGA, TSUYOSHI		
IPC分类号	H01L51/50 C09K11/06 H05B33/26		
CPC分类号	C09K11/06 C09B57/00 C09B57/001 C09K2211/1011 H01L51/0054 H01L51/0056 H01L51/0058 H01L51/006 H01L51/0072 H01L51/5012 H01L51/5052 Y10S428/917 Y10T428/265 Y10T428/31504		
优先权	2009081410 2009-03-30 JP 2009292004 2009-12-24 JP		
其他公开文献	EP2416396A4 EP2416396A1		
外部链接	Espacenet		

摘要(译)

本发明公开了一种有机电致发光元件，其通过在构成发光元件的一层中含有包含特定苝化合物的发光元件材料，优选在光线下，实现了高发光效率和低驱动电压。- 发光层或电子传输层。

[Chemical formula 1]



(1)