



(11) **EP 2 797 134 A1**

(12) **EUROPEAN PATENT APPLICATION**

(43) Date of publication:
29.10.2014 Bulletin 2014/44

(51) Int Cl.:
H01L 51/52 (2006.01) H01L 27/32 (2006.01)

(21) Application number: **14155124.2**

(22) Date of filing: **14.02.2014**

(84) Designated Contracting States:
AL AT BE BG CH CY CZ DE DK EE ES FI FR GB GR HR HU IE IS IT LI LT LU LV MC MK MT NL NO PL PT RO RS SE SI SK SM TR
Designated Extension States:
BA ME

(72) Inventors:
• **Park, Ok-Kyung**
Hwaseong-si (KR)
• **Yun, Su Yeon**
Seoul (KR)

(30) Priority: **26.04.2013 KR 20130046996**

(74) Representative: **Gulde & Partner**
Patent- und Rechtsanwaltskanzlei mbB
Wallstraße 58/59
10179 Berlin (DE)


(71) Applicant: **Samsung Display Co., Ltd.**
Yongin-City, Gyeonggi-Do, 446-711 (KR)

(54) **Organic light emitting diode display**

(57) An organic light emitting diode (OLED) display includes: a first electrode (E1) around a center point (CP) of a virtual square (VS); second electrodes (E2) around a first vertex (P1) and a second vertex (P2) diagonal to the first vertex (P2) of the virtual square (VS), the second electrodes (E2) being separated from each other and with the center point (CP) of the virtual square (VS) interposed therebetween; third electrodes (E3) around a third vertex (P3) and a fourth vertex (P4) of the virtual square (VS), the third electrodes (E3) being separated from each other and with the center point (CP) of the virtual square (VS) interposed therebetween; a pixel defining layer (PDL) partially on the first electrode (E1), the second electrodes (E2), and the third electrodes (E3), and partially exposing the first electrode (E1), the second electrodes (E2), and the third electrodes (E3); and four spacers (SP1, SP2, SP3, SP4) disposed as islands on the pixel defining layer (PDL) and corresponding to four sides (V1, V2, V3, V4) of the virtual square (VS).

FIG. 1

1000



EP 2 797 134 A1

Description**BACKGROUND**5 **(a) Field**

[0001] Aspects of embodiments of the present invention relate to an organic light emitting diode (OLED) display.

10 **(b) Description of the Related Art**

[0002] A display device is a device for displaying an image. Recently, OLED displays have received attention. Since OLED displays have self-emission characteristics and do not require separate light sources, which is unlike liquid crystal display devices, it is possible to reduce their thickness and weight when compared to those of older technologies. Further, OLED displays have high-quality characteristics such as low power consumption, high luminance, and high response speed.

[0003] In general, an OLED display includes a first substrate, a first electrode disposed on the first substrate, a pixel defining layer including an opening that exposes the first electrode, an organic emission layer disposed on the first electrode corresponding to the opening, a second electrode disposed on the organic emission layer, and a second substrate disposed on the first electrode.

20 [0004] A more recent OLED display may further include a spacer disposed on a pixel defining layer to reduce or minimize interference due to the second substrate by increasing a gap between an organic emission layer and the second substrate. However, in a conventional OLED display including a spacer, the spacer is simply disposed on an unopened portion of the pixel defining layer without regard to the shape of the opening included in the pixel defining layer.

25 [0005] The above information disclosed in this Background section is only for enhancement of understanding of the background of the present invention and therefore it may contain information that does not form the prior art that is already known in this country to a person of ordinary skill in the art.

SUMMARY

30 [0006] Embodiments of the present invention relate to a pixel alignment structure of an organic light emitting device. More particularly, embodiments of the present invention relate to a pixel structure including an OLED and spacers disposed on a pixel defining layer that exposes a first electrode of the OLED.

35 [0007] Embodiments of the present invention provide for an OLED display including spacers disposed on a pixel defining layer, wherein the shape of openings included in the pixel defining layer is designed to reduce or minimize interference of a substrate with respect to an organic emission layer by increasing an area ratio of the spacers in the entire area of the OLED display.

40 [0008] In an embodiment of the present invention, an organic light emitting diode (OLED) display is provided. The OLED display includes: a first electrode around a center point of a virtual square; second electrodes around a first vertex and a second vertex diagonal to the first vertex of the virtual square, the second electrodes being separated from each other and with the center point of the virtual square interposed therebetween; third electrodes around a third vertex and a fourth vertex of the virtual square, the third electrodes being separated from each other and with the center point of the virtual square interposed therebetween; a pixel defining layer partially on the first electrode, the second electrodes, and the third electrodes, and partially exposing the first electrode, the second electrodes, and the third electrodes; and four spacers disposed as islands on the pixel defining layer and corresponding to four sides of the virtual square.

45 [0009] The pixel defining layer may have a first opening that exposes the first electrode and has a first polygon shape whose center coincides with the center point of the virtual square, second openings that expose the second electrodes and have second polygonal shapes whose centers coincide with the first vertex and the second vertex, and third openings that expose the third electrodes and have third polygonal shapes whose centers coincide with the third vertex and the fourth vertex.

50 [0010] Distances between the center point of the virtual square and centers of the four spacers may be the same.

[0011] Each of the four spacers may have a square shape.

[0012] Alternatively, each of the spacers may have a rectangle shape having long sides that are bisected by a respective one of the four sides of the virtual square.

[0013] Each of the second openings and the third openings may have a larger area compared to that of the first opening.

55 [0014] Each of the second openings may have a larger area than that of each of the third openings.

[0015] At least one of the first polygonal shape, the second polygonal shapes, or the third polygonal shapes may be an octagon.

[0016] Preferably, the first polygonal shape may be an octagon, and one of the second polygonal shapes and one of

the third polygonal shapes may be a hexagon and a quadrilateral.

[0017] The first opening may include a plurality of first openings, and neighboring ones of the plurality of first openings may have symmetrical octagonal shapes.

5 [0018] Distances between the first opening and each of the second openings, and distances between the first opening and each of the third openings may be a same first length.

[0019] Distances between each of the second openings and each of the third openings may be a same second length, and distances between the neighboring ones of the plurality of first openings may be a same third length that is longer than each of the first length and the second length.

10 [0020] The OLED display may further include a first organic emission layer on the first electrode corresponding to the first opening, second organic emission layers on the second electrodes and corresponding to the second openings, and third organic emission layers on the third electrodes and corresponding to the third openings.

[0021] The first organic emission layer may be configured to emit a first color light, the second organic emission layers may be configured to emit a second color light different from the first color light, and the third organic emission layers may be configured to emit a third color light different from the first color light and the second color light.

15 [0022] Preferably, the first color light may be green, and the second color light and the third color light may be blue and red.

[0023] According to one embodiment of the present invention, spacers are provided on a pixel defining layer of the OLED display in consideration of the shape of openings included in the pixel defining layer to reduce or minimize interference of a substrate with respect to an organic emission layer by increasing an area ratio of the spacers to the entire area.

20

BRIEF DESCRIPTION OF THE DRAWINGS

[0024]

25 FIG. 1 partially shows a plane surface of an OLED display according to a first embodiment of the present invention. FIG. 2 is a cross-sectional view of FIG. 1 taken along the line II-II. FIG. 3 partially shows a plane surface of an OLED display according to a second embodiment of the present invention.

30 DETAILED DESCRIPTION

[0025] In the following detailed description, only certain embodiments of the present invention have been shown and described, simply by way of illustration. As those skilled in the art would realize, the described embodiments may be modified in various different ways, all without departing from the scope of the present invention. Accordingly, the drawings and description are to be regarded as illustrative in nature and not restrictive. Like reference numerals designate like elements throughout the specification. In addition, the size and thickness of each configuration shown in the drawings may be arbitrarily shown for better understanding and ease of description, but the present invention is not limited thereto.

35 [0026] In addition, unless explicitly described to the contrary, the word "comprise" and variations such as "comprises" or "comprising" will be understood to imply the inclusion of stated elements but not the exclusion of any other elements. Throughout, when a first element is described as being "coupled" to a second element, it may be directly coupled (e.g., connected) to the second element or indirectly coupled (e.g., electrically connected) to the second element via one or more third elements. Herein, the use of the term "may," when describing embodiments of the present invention, refers to "one or more embodiments of the present invention." In addition, the use of alternative language, such as "or," when describing embodiments of the present invention, refers to "one or more embodiments of the present invention" for each corresponding item listed.

40 [0027] Hereinafter, an OLED display 1000 according to a first embodiment of the present invention will be described with reference to FIG. 1 and FIG. 2. FIG. 1 partially shows a plane surface of the OLED display 1000. For convenience, a first electrode, a pixel defining layer, an organic emission layer, and a spacer are mainly illustrated in FIG. 1. FIG. 2 is a cross-sectional view of FIG. 1 taken along the line II-II.

50 [0028] As shown in FIG. 1 and FIG. 2, the OLED display 1000 includes a first substrate SU1, a circuit portion PC, a first electrode E1, a second electrode E2, a third electrode E3, a pixel defining layer PDL, a first organic emission layer OL1, a second organic emission layer OL2, a third organic emission layer OL3, a first spacer SP1, a second spacer SP2, a third spacer SP3, a fourth spacer SP4, a common electrode CE, and a second substrate SU2.

55 [0029] The first substrate SU1 is formed of an insulating substrate made of glass, quartz, ceramic, plastic, or the like. In addition, when the first substrate SU1 is made of plastic, the OLED display 1000 may have a flexible, stretchable, or rollable characteristic.

[0030] The circuit portion PC is disposed on the first substrate SU1, and may include wires including one or more scan lines, data lines, driving power lines, common power lines, pixel circuits, and the like. Each pixel circuit may correspond

to one pixel and may include two or more thin film transistors (TFTs) coupled to the wires, one or more capacitors, and the like. The circuit portion PC may be formed to have various structures known to one of ordinary skill in the art.

[0031] The first electrode E1 is positioned on the circuit part PC, and is coupled to one of the TFTs of the circuit part PC. A central area of the first electrode E1 is positioned at a center point CP of a virtual square VS.

[0032] Here, the virtual square VS includes the center point CP, a first vertex P1, a second vertex P2, a third vertex P3, a fourth vertex P4, a first side V1, a second side V2, a third side V3, and a fourth side V4. In further detail, the first side V1 of the virtual square VS connects between the first vertex P1 and the third vertex P3, the second side V2 connects between the third vertex P3 and the second vertex P2, the third side V3 connects between the second vertex P2 and the fourth vertex P4, and the fourth side V4 connects between the fourth vertex P4 and the first vertex P1. In addition, the first vertex P1 and the second vertex P2 of the virtual square VS are diagonal to each other (with the center point CP interposed therebetween), the third vertex P3 and the fourth vertex P4 are diagonal to each other (with the center point CP interposed therebetween), and both the third vertex P3 and the fourth vertex P4 neighbor both the first vertex P1 and the second vertex P2.

[0033] The first side V1, the second side V2, the third side V3, and the fourth side V4 have the same length such that the virtual square VS is formed. The first electrode E1 may have various polygonal shapes, and a center area of the first electrode E1 is exposed by a first opening portion (or first opening) OM1 of the pixel defining layer PDL.

[0034] The second electrode E2 is disposed on the circuit portion PC and is separated from the first electrode E1. The second electrode E2 is coupled to a TFT of the circuit portion PC. Within and around the virtual square VS, the second electrode E2 is provided as a pair of second electrodes E2, and the second electrodes E2 are separated from each other, with the first electrode E1 interposed therebetween. Respective center areas of the second electrodes E2 are disposed on the first vertex P1 and the second vertex P2 of the virtual square VS. The second electrode E2 may have various polygonal shapes, and the center area of the second electrode E2 may be exposed by a second opening portion (or second opening) OM2 of the pixel defining layer PDL.

[0035] The third electrode E3 is separated from the first electrode E1 and the second electrode E2, and is disposed on the circuit portion PC. The third electrode E3 is coupled to one of the TFTs of the circuit portion PC. Within and around the virtual square VS, the third electrode E3 is provided as a pair of third electrodes E3, and the third electrodes E3 are separated from each other, with the first electrode E1 interposed therebetween. Center regions of the respective third electrodes E3 are disposed on the third vertex P3 and the fourth vertex P4 of the virtual square VS. The third electrode E3 may have various polygonal shapes, and the center area of the third electrode E3 is exposed by a third opening portion (or third opening) OM3 of the pixel defining layer PDL.

[0036] The second electrodes E2 and the third electrodes E3 are disposed on and around the vertices of the virtual square VS, with the first electrode E1 interposed therebetween. That is, the second electrodes E2 and the third electrodes E3 surround the first electrode E1, which is disposed on and around the center CP of the virtual square. The first electrode E1, the second electrodes E2, and the third electrodes E3 may be anodes or cathodes functioning as hole injection electrodes. The first electrode E1, the second electrodes E2, and the third electrodes E3 may be formed as light transmissive electrodes or light reflective electrodes.

[0037] The pixel defining layer PDL is disposed on the first electrode E1, the second electrode E2, and the third electrode E3, and covers the edge of each of the first electrode E1, the second electrode E2, and the third electrode E3. The pixel defining layer PDL includes the first opening portion OM1, the second opening portion OM2, and the third opening portion OM3, respectively exposing the first electrode E1, the second electrode E2, and the third electrode E3.

[0038] The first opening OM1 exposes the first electrode E1, and has a first polygonal shape, for example, an octagon. The first opening OM1 is separated from the third opening OM3 and the second opening OM2, and the center of the first opening OM1 coincides with the center point CP of the virtual square VS. The first opening OM1 has a smaller area compared to the second opening OM2 and the third opening OM3 that neighbor the first opening OM1. While the first opening OM1 in FIG. 1 is formed in the shape of an octagon, the shape of the first opening OM1 is not limited thereto. In other embodiments, the first opening OM1 may have various polygonal shapes such as a triangle, a quadrilateral, a pentagon, a hexagon, a heptagon, or the like.

[0039] While the above description focused on a single virtual square VS having a single first electrode E1, the OLED display 1000 has a plurality of virtual squares VS, each centered with a different one of a corresponding plurality of first electrodes E1 and first openings OM1. In the OLED display 1000 of FIG. 1, all neighboring (e.g., sharing a same row or column) first openings OM1 among the plurality of first openings OM1 have symmetric octagonal shapes (that are mirror images of each other), while all diagonal first openings OM1 have the same octagonal shape. In other embodiments, each of the plurality of first openings OM1 may have the same octagonal shape.

[0040] In the OLED display 1000 of FIG. 1, a first organic emission layer OL1 for emitting green light is disposed on each first electrode E1 that is exposed by its corresponding first opening OM1. In other embodiments, an organic emission layer for emitting light of various colors such as blue, red, or white may be disposed on each first electrode E1 that is exposed by its corresponding first opening OM1.

[0041] In and around the vertices P1 and P2 of the virtual square VS, the second openings OM2 expose the second

electrodes E2, and have a second polygonal shape, for example, a hexagon. The second openings OM2 are separated from each of the third openings OM3 and the first opening OM1, and the centers of the second openings OM2 coincide with the first vertex P1 and the second vertex P2 of the virtual square VS. Each of the second openings OM2 has a larger area compared to each of the first opening OM1 and the third openings OM3. The second openings OM2 in FIG. 1 have a hexagonal shape, but the present invention is not limited thereto. In other embodiments, the second openings OM2 may have various polygonal shapes such as triangles, quadrilaterals, pentagons, hexagons, heptagons, octagons, or the like.

[0042] The OLED display 1000 of FIG. 1 has a plurality of second openings OM2 that have the same hexagonal shape. The plurality of second openings OM2 are separated from each other, with each pair of diagonal second openings OM2 sharing a first opening OM1 therebetween. In the OLED display 1000 of FIG. 1, second organic emission layers OL2 for emitting blue light are disposed on the second electrodes E2 that are exposed by the second openings OM2. In other embodiments, organic emission layers for emitting light of various colors such as green, red, or white may be disposed on the second electrodes E2 that are exposed by the second openings OM2.

[0043] In and around the virtual square VS, the third openings OM3 expose the third electrodes E3, and have a third polygonal shape, for example, a quadrilateral. The third openings OM3 are separated from each of the first opening OM1 and the second openings OM2, and the centers of the third openings OM3 coincide with the third vertex P3 and the fourth vertex P4 of the virtual square VS. Each of the third openings OM3 has a larger area compared to its neighboring first opening OM1 and has a smaller area compared to each of its neighboring second openings OM2. The third openings OM3 have a quadrilateral shape (in this case, a parallelogram shape), but the present invention is not limited thereto. In other embodiments, the third openings OM3 may have various polygonal shapes such as triangles, pentagons, hexagons, heptagons, octagons, or the like.

[0044] The OLED display 1000 has a plurality of third openings OM3 that have the same quadrilateral shape. The plurality of third openings OM3 are separated from each other, with each pair of diagonal third openings OM3 sharing a first opening OM1 therebetween. In the OLED display 1000 of FIG. 1, third organic emission layers OL3 for emitting red light are disposed on the third electrodes E3 exposed by the third openings OM3. In other embodiments, organic emission layers for emitting light of various colors such as blue, green, or white may be disposed on the third electrodes E3 that are exposed by the third openings OM3.

[0045] One of the shapes, such as the first polygon, the second polygon, or the third polygon of the first opening OM1, the second opening OM2, or the third opening OM3, respectively, may have an octagonal shape. In the OLED display 1000, the plurality of first openings OM1 are sequentially arranged along virtual first lines (e.g., rows or columns), and the plurality of second openings OM2 and the plurality of third openings OM3 are respectively alternately arranged on virtual second lines (e.g., rows or columns). The virtual first lines are offset by half a pixel from the virtual second lines such that within and around each virtual square VS, the second openings OM2 of which the centers coincide with the first vertex P1 and the second vertex P2 and the third openings OM3 of which the centers coincide with the third vertex P3 and the fourth vertex P4 surround the first opening OM1 of the virtual square VS.

[0046] As described, the center of the first opening OM1 coincides with the center point of the virtual square VS, the centers of the second openings OM2 coincide with the first vertex P1 and the second vertex P2, the centers of the third openings OM3 coincide with the third vertex P3 and the fourth vertex P4, and the second openings OM2 and the third openings OM3 surround the first opening OM1 of the virtual square VS. In the

[0047] OLED display 1000 of FIG. 1, all first openings OM1, all second openings OM2, and all third openings OM3 respectively have the same polygonal (octagonal, hexagonal, and quadrilateral) shapes so that, within each virtual square VS, a distance between the first opening OM1 and each of the second openings OM2, and a distance between the first opening OM1 and each of the third opening OM3 is the same first length L1, and a distance between each of the second openings OM2 and each of the third openings OM3 is the same second length L2 that is different from the first length L1. Furthermore, between neighboring virtual squares VS, a distance between respective first openings OM1 is the same third length L3 that is longer than each of the first length L1 and the second length L2.

[0048] The first organic emission layer OL1 is disposed on each of the first electrodes E1 corresponding to one of the first openings OM1. In the OLED display of FIG. 1, the first organic emission layer OL1 includes an organic material for emitting green light and thus, emits green light. In other embodiments, the first organic emission layer OL1 may include an organic material for emitting red, blue, or white light, and in this case, the first organic emission layer OL1 emits red light, blue light, or white light.

[0049] The second organic emission layer OL2 is disposed on each of the second electrodes E2 corresponding to one of the second openings OM2. In the OLED display of FIG. 1, the second organic emission layer OL2 includes an organic material for emitting blue light and thus, emits blue light. In other embodiments, the second organic emission layer OL2 may include an organic material for emitting red, green, or white light, and in this case, the second organic emission layer OL2 emits red light, green light, or white light.

[0050] The third organic emission layer OL3 is disposed on each of the third electrodes E3 corresponding to one of the third openings OM1. In the OLED display of FIG. 1, the third organic emission layer OL3 includes an organic material

for emitting red light and thus, emits red light. In other embodiments, the third organic emission layer OL3 may include an organic material for emitting blue, green, or white light, and in this case, the third organic emission layer OL3 emits blue light, green light, or white light.

[0051] Thus, in the OLED display of FIG. 1, the first organic emission layer OL1, the second organic emission layer OL2, and the third organic emission layer OL3 respectively emit light of different colors (green, blue, and red, respectively). In other embodiments, the first organic emission layer OL1, the second organic emission layer OL2, and the third organic emission layer OL3 may emit light of the same color (such as white).

[0052] The first spacer SP1 is disposed between the first vertex P1 and the third vertex P3 corresponding to the first side V1 among the four sides of the virtual square VS. The first spacer SP1 is disposed as an island between the corresponding second opening OM2 and third opening OM3, and has a first center C1, which is the center of the first spacer SP1, that lies on the first side V1. The first spacer SP1 is formed in the shape of a rectangle having long sides bisected by the first side V1 through the first center C1.

[0053] The second spacer SP2 is disposed between the third vertex P3 and the second vertex P2 corresponding to the second side V2 among the four sides of the virtual square VS. The second spacer SP2 is disposed as an island between the corresponding third opening OM3 and second opening OM2, and has a second center C2, which is the center of the second spacer SP2, that lies on the second side V2 of the second center C2. The second spacer SP2 is formed in the shape of a rectangle having long sides bisected by the second side V2 through the second center C2.

[0054] The third spacer SP3 is disposed between the second vertex P2 and the fourth vertex P4 corresponding to the third side V3 among the four sides of the virtual square VS. The third spacer SP3 is disposed as an island between the corresponding second opening OM2 and third opening OM3, and has a third center C3, which is the center of the third spacer SP3, that lies on the third side V3. The third spacer SP3 is formed in the shape of a rectangle having long sides bisected by the third side V3 through the third center C3.

[0055] The fourth spacer SP4 is disposed between the fourth vertex P4 and the first vertex P1 corresponding to the fourth side V4 among the four sides of the virtual square VS. The fourth spacer SP4 is disposed as an island between the corresponding third opening OM3 and second opening OM2, and has a fourth center C4, which is the center of the fourth spacer SP4, that lies on the fourth side V4. The fourth spacer SP4 is formed in the shape of a rectangle having long sides bisected by the fourth side V4 through the fourth center C4.

[0056] As described, the first spacer SP1, the second spacer SP2, the third spacer SP3, and the fourth spacer SP4 are respectively disposed as islands corresponding to the four sides, that is, the first side V1, the second side V2, the third side V3, and the fourth side V4 of the virtual square VS, and are also formed in the shape of rectangles respectively having long sides bisected respectively by the first side V1, the second side V2, the third side V3, and the fourth side V4 through the first center C1, the second center C2, the third center C3, and the fourth center C4, so that the area ratio occupied by the first spacers SP1, the second spacers SP2, the third spacers SP3, and the fourth spacers SP4 in the entire area of the OLED display 1000 can be increased without interfering with the distances respectively set between the first openings OM1, the second openings OM2, and the third openings OM3.

[0057] The first spacer SP1, the second spacer SP2, the third spacer SP3, and the fourth spacer SP4 may be formed of the same or different material of the pixel defining layer PDL, and may include at least one of an organic material, an inorganic material, a metal, glass, or the like.

[0058] As described, within each virtual square VS, the centers C1, C2, C3, and C4 of each of the first spacer SP1, the second spacer SP2, the third spacer SP3, and the fourth spacer SP4 that neighbor the center point CP of the virtual square VS lie on a respective one of the first side V1, the second side V2, the third side V3, and the fourth side V4 so that distances between the respective centers C1, C2, C3, and C4 of the first spacer SP1, the second spacer SP2, the third spacer SP3, and the fourth spacer SP4, and the center point CP of the virtual square VS have the same length D.

[0059] In FIG. 1, the first spacer SP1, the second spacer SP2, the third spacer SP3, and the fourth spacer SP4 have rectangular shapes, but in other embodiments, they may have other polygonal shapes such as triangles, other quadrilaterals, pentagons, hexagons, heptagons, octagons, nonagons, or the like, or closed loop shapes formed by extension of a curved line.

[0060] The common electrode CE is disposed on the first organic emission layers OL1, the second organic emission layers OL2, and the third organic emission layers OL3 throughout the entire surface of the first substrate SU1, and may be a cathode functioning as an electron injection electrode, or an anode. The common electrode CE may be formed as a light transmissive electrode or a light reflective electrode.

[0061] In FIG. 2, the common electrode CE is disposed on the first spacer SP1. In another embodiment of the present invention, the common electrode CE may be disposed between the pixel defining layer PDL and the first spacer SP1.

[0062] The second substrate SU2 is formed of an insulating substrate made of glass, quartz, ceramic, plastic, or the like. In addition, when the second substrate SU2 and the first substrate SU1 are made of plastic, the OLED display may have a flexible, stretchable, or rollable characteristic.

[0063] As described above, in the OLED display 1000, within each virtual square VS, gaps of the first length L1 are formed between the first opening OM1 and each of the second openings OM2, and between the first opening OM1 and

each of the third openings OM3. In addition, between neighboring virtual squares VS, gaps of the third length L3 that are longer than the first length L1 are formed between the neighboring first openings OM1 so that deposition reliability in a deposition process that uses fine metal masks that form the green organic emission layer, the blue organic emission layer, and the red organic emission layer respectively included in the first opening OM1, the second opening OM2, and the third opening OM3 can be improved. That is, deposition reliability of the OLED display 1000 can be improved.

[0064] In addition, in the OLED display 1000, within and around each virtual square VS, the second openings OM2 and the third openings OM3 are alternately arranged to surround the first opening OM1 so that an aperture ratio of each of the first opening OM1, the second openings OM2, and the third openings OM3 can be improved. Accordingly, manufacturing time and manufacturing cost of the OLED display can be reduced and quality of an image displayed by the OLED display can be improved. That is, image quality of the OLED display 1000 can be improved.

[0065] Further, in the OLED display 1000, the second openings OM2 for emitting blue light have corresponding second organic emission layers OL2 that have a shorter life span compared to those of other color pixels. Accordingly, each second opening OM2 has a larger area compared to those of the first opening OM1 and the third opening OM3 so that deterioration of the life span of the whole OLED display can be suppressed. That is, the life span of the OLED display 1000 can be improved.

[0066] As described above, in the OLED display 1000, the first opening OM1, the second opening OM2, and the third opening OM3 have polygonal shapes such as an octagon, a hexagon, a quadrilateral, or the like. Within or around each virtual square VS, the center of the first opening OM1 coincides with the center point CP of the virtual square VS, the centers of the second openings OM2 respectively coincide with the first vertex P1 and the second vertex P2, and the centers of the third openings OM3 respectively coincide with the third vertex P3 and the fourth vertex P4 to improve deposition reliability of the organic emission layer and also improve an aperture ratio of each of the first, second, and third openings OM1, OM2, and OM3 during the deposition process using the fine metal masks in consideration of a deposition process of the organic emission layer, which is another manufacturing feature of the OLED display 1000.

[0067] That is, the OLED display 1000 including the octagon-shaped first, hexagon-shaped second, and quadrilateral-shaped third openings OM1, OM2, and OM3 can be provided, and, in the OLED display 1000, deposition reliability of the organic emission layers can be improved, the life span of the organic emission layers can be improved, and the aperture ratio of each of the first openings OM1, the second openings OM2, and the third openings OM3 can be improved.

[0068] Further, in the OLED display 1000, within and around each virtual square VS, the first spacer SP1, the second spacer SP2, the third spacer SP3, and the fourth spacer SP4 are disposed as islands respectively corresponding to the first side V1, the second side V2, the third side V3, and the fourth side V4 in consideration of the shapes of the first, second, and third openings OM1, OM2, and OM3 such that the first, second, third, and fourth spacers SP1, SP2, SP3, and SP4 of which centers have the same distance D to the center point CP to which the center of the first opening OM1 coincides. Thus, the first, second, third, and fourth spacers SP1, SP2, SP3, and SP4 do not interfere with distances set between the first, second, and third openings OM1, OM2, and OM3 and also maintain a consistent ratio of the area occupied by the first, second, third, and fourth spacers SP1, SP2, SP3, and SP4 when the entire area of the OLED display 1000 is increased. Accordingly, interference of the second substrate SU2 with respect to the first organic emission layers OL1, the second organic emission layers OL2, and the third organic emission layers OL3 can be reduced or minimized, regardless of how many virtual squares VS make up the OLED display 1000.

[0069] As described, the OLED display 1000 includes the octagonal-shaped first opening OM1, the hexagonal-shaped second opening OM2, and the quadrilateral-shaped third opening OM3 in consideration of improvement of deposition reliability of the organic emission layers, improvement of life span of the organic emission layers, and improvement of the aperture ratio of each of the first, second, and third openings OM1, OM2, and OM3, and also includes the first spacer SP1, the second spacer SP2, the third spacer SP3, and the fourth spacer SP4 in consideration of the shapes of the first opening OM1, the second opening OM2, and the third opening OM3 so that the deposition reliability and life span of the organic emission layers can be improved, the aperture ratio of each of the first, second, and third openings OM1, OM2, and OM3 can be improved, and the entire mechanical reliability can be improved.

[0070] Hereinafter, an OLED display 1002 according to a second embodiment of the present invention will be described with reference to FIG. 3. For convenience of description, only features distinguished from those of the first embodiment above may be extracted and described, and portions for which the description is omitted follow the first embodiment. In addition, the same constituent elements of both embodiments will be described by using the same reference numerals as the first embodiment.

[0071] FIG. 3 partially shows a plane surface of the OLED display 1002. As shown in FIG. 3, an OLED display 1002 includes a first spacer SP1, a second spacer SP2, a third spacer SP3, and a fourth spacer SP4, and they are respectively formed in the shape of a square.

[0072] The first spacer SP1, the second spacer SP2, the third spacer SP3, and the fourth spacer SP4 are respectively disposed as islands on a pixel defining layer PDL corresponding to four sides, namely a first side V1, a second side V2, a third side V3, and a fourth side V4, of a virtual square VS. In addition, the centers of the first to fourth spacers SP1 to SP4 respectively lie on the first side V1, the second side V2, the third side V3, and the fourth side V4.

[0073] As described, the OLED display 1002 includes a first opening OM1, a second opening OM2, and a third opening OM3 respectively formed in the shape of an octagon, a hexagon, and a quadrilateral in consideration of improvement in deposition reliability of organic emission layers, improvement in life span of the organic emission layers, and improvement in aperture ratios of the first, second, and third openings OM1, OM2, and OM3, and also includes a first spacer SP1, a second spacer SP2, a third spacer SP3, and a fourth spacer SP4 in consideration of the shapes of the first, second, and third openings OM1, OM2, and OM3 such that the deposition reliability of the organic emission layers can be improved, the life span of the organic emission layers can be improved, and the entire mechanical reliability of the OLED display 1002 can be improved.

[0074] While the present invention has been described in connection with what is presently considered to be practical embodiments, it is to be understood that the invention is not limited to the disclosed embodiments, but, on the contrary, is intended to cover various modifications and equivalent arrangements included within the scope of the appended claims, and their equivalents.

Description of some symbols

[0075]

first electrode	E1
second electrode	E2
third electrode	E3
pixel defining layer	PDL
spacer	SP1, SP2, SP3, SP4

Claims

1. An organic light emitting diode (OLED) display comprising:

- a first electrode (E1), the center of the first electrode (E1) being located on a center point (CP) of a virtual square (VS);
- second electrodes (E2), the center of the second electrode (E2) being located on a first vertex (P1) and a second vertex (P2) diagonal to the first vertex (P1) of the virtual square (VS), the second electrodes (E2) being separated from each other and with the center point (CP) of the virtual square (VS) interposed therebetween;
- third electrodes (E3), the center of the third electrode (E3) being located on a third vertex (P3) and a fourth vertex (P4) of the virtual square (VS), the third electrodes (E3) being separated from each other and with the center point (CP) of the virtual square (VP) interposed therebetween;
- a pixel defining layer (PDL) partially covering the first electrode (E1), the second electrodes (E2), and the third electrodes (E3), and partially exposing the first electrode (E1), the second electrodes (E2), and the third electrodes (E3); and
- four spacers (SP1, SP2, SP3, Sp4) disposed as islands on the pixel defining layer and having centers on the corresponding one of the four sides (V1, V2, V3, V4) of the virtual square (VS).

2. The OLED display of claim 1, wherein the pixel defining layer (PDL) has:

- a first opening (OM1) that exposes the first electrode (E1) and has a first polygon shape whose center coincides with the center point (CP) of the virtual square (VS);
- second openings (OM2) that expose the second electrodes (E2) and have second polygonal shapes whose centers coincide with the first vertex (P1) and the second vertex (P2) of the virtual square (VS); and
- third openings (OM3) that expose the third electrodes (E3) and have third polygonal shapes whose centers coincide with the third vertex (P3) and the fourth vertex (P4) of the virtual square (VS).

3. The OLED display of claim 2, wherein at least one of the first polygonal shape, the second polygonal shapes, or the third polygonal shapes is an octagon.

4. The OLED display of claim 2, wherein the first polygonal shape is an octagon, and one of the second polygonal shapes and one of the third polygonal shapes are a hexagon and a quadrilateral.

5. The OLED display of claim 4, wherein

the first opening (OM1) includes a plurality of first openings (OM1), and neighboring ones of the plurality of first openings have symmetrical octagonal shapes.

- 5
6. The OLED display of one of claims 2 to 5, wherein distances between the first opening (OM1) and each of the second openings (OM2), and distances between the first opening (OM1) and each of the third openings (OM3) are a same first length (L1).
- 10
7. The OLED display of claim 6, wherein distances between each of the second openings (OM2) and each of the neighbouring third openings (OM3) is a same second length (L2), and distances between the neighboring ones of the plurality of first openings (OM1) is a same third length that is longer than each of the first length (L1) and the second length (L2).
- 15
8. The OLED display of one of the preceding claims 2, wherein the distance (D) between the center point (CP) of the virtual square (VS) and the centers of the four spacers (SP1, SP2, SP3, SP4) is the same for all spacers (SP1, SP2, SP3, SP4).
- 20
9. The OLED display of one of the preceding claims, wherein each of the four spacers (SP1, SP2, SP3, SP4) has a square shape.
- 25
10. The OLED display of one of claims 1 to 8, wherein each of the spacers (SP1, SP2, SP3, SP4) has a rectangular shape having long sides that are bisected by a respective one of the four sides (V1, V2, V3, V4) of the virtual square (VS).
- 30
11. The OLED display of one of claims 2 to 10, wherein each of the second openings (OM2) and the third openings (OM3) has a larger area compared to that of the first opening (OM1).
- 35
12. The OLED display of claim 11, wherein each of the second openings (OM2) has a larger area than that of each of the third openings (OM3).
- 40
13. The OLED display of one of claims 2 to 12, further comprising:
a first organic emission layer (OL1) on an area of the first electrode (E1) corresponding to the first opening (OM1);
second organic emission layers (OL2) on an area of the second electrodes (E2) corresponding to the second openings (OM2); and
third organic emission layers (OL3) on an area of the third electrodes (E3) corresponding to the third openings (OM3).
- 45
14. The OLED display of claim 13, wherein the first organic emission layer (OL1) is configured to emit a first color light, the second organic emission layers (OL2) are configured to emit a second color light different from the first color light, and the third organic emission layers (OL3) are configured to emit a third color light different from the first color light and the second color light.
- 50
15. The OLED display of claim 14, wherein the first color light is green, and the second color light and the third color light are blue and red.
- 55

FIG. 1

1000




FIG. 2





FIG. 3

1002





EUROPEAN SEARCH REPORT

Application Number
EP 14 15 5124

5

10

15

20

25

30

35

40

45

50

55

DOCUMENTS CONSIDERED TO BE RELEVANT			
Category	Citation of document with indication, where appropriate, of relevant passages	Relevant to claim	CLASSIFICATION OF THE APPLICATION (IPC)
X	JP 2004 192813 A (TOSHIBA MATSUSHITA DISPLAY TEC) 8 July 2004 (2004-07-08)	1,8	INV. H01L51/52 H01L27/32
Y	* figures 1,2 * * paragraphs [0016] - [0018], [0023], [0054] *	2-7,9, 13-15	
X	US 2012/313844 A1 (IM JA-HYUN [KR] ET AL) 13 December 2012 (2012-12-13)	1,2,6-8, 10,11,13	TECHNICAL FIELDS SEARCHED (IPC) H01L
Y	* paragraphs [0049], [0060], [0086], [0087], [0091]; figures 7-11 *	12	
Y	WO 2005/067352 A1 (SAMSUNG ELECTRONICS CO LTD [KR]; CHUNG JIN-KOO [KR]; CHOI JOON-HOO [KR] 21 July 2005 (2005-07-21)	2-7, 13-15	
Y	* paragraph [0043]; figure 3 *		
Y	US 2008/001525 A1 (CHAO CHING-IAN [TW] ET AL) 3 January 2008 (2008-01-03)	12	
A	* figures 4a,4b *	4,5,11, 13-15	
Y	JP 2011 076760 A (TOPPAN PRINTING CO LTD) 14 April 2011 (2011-04-14)	9	
A	* paragraph [0060] *		
A	US 2010/033084 A1 (KO JUNG-WOO [KR] ET AL) 11 February 2010 (2010-02-11)	1-15	
	* the whole document *		
The present search report has been drawn up for all claims			
Place of search The Hague		Date of completion of the search 26 June 2014	Examiner De Laere, Ann
CATEGORY OF CITED DOCUMENTS		T : theory or principle underlying the invention E : earlier patent document, but published on, or after the filing date D : document cited in the application L : document cited for other reasons & : member of the same patent family, corresponding document	
X : particularly relevant if taken alone Y : particularly relevant if combined with another document of the same category A : technological background O : non-written disclosure P : intermediate document			

EPO FORM 1503 03/82 (P04/C01)

ANNEX TO THE EUROPEAN SEARCH REPORT
ON EUROPEAN PATENT APPLICATION NO.

EP 14 15 5124

5

This annex lists the patent family members relating to the patent documents cited in the above-mentioned European search report.
The members are as contained in the European Patent Office EDP file on
The European Patent Office is in no way liable for these particulars which are merely given for the purpose of information.

26-06-2014

10

Patent document cited in search report		Publication date	Patent family member(s)	Publication date
JP 2004192813	A	08-07-2004	NONE	

US 2012313844	A1	13-12-2012	KR 20120137884 A	24-12-2012
			US 2012313844 A1	13-12-2012

WO 2005067352	A1	21-07-2005	JP 2007518237 A	05-07-2007
			US 2005264177 A1	01-12-2005
			WO 2005067352 A1	21-07-2005

US 2008001525	A1	03-01-2008	CN 101051648 A	10-10-2007
			JP 2008015521 A	24-01-2008
			TW 200802221 A	01-01-2008
			US 2008001525 A1	03-01-2008

JP 2011076760	A	14-04-2011	NONE	

US 2010033084	A1	11-02-2010	KR 20100003243 A	07-01-2010
			US 2010033084 A1	11-02-2010

15

20

25

30

35

40

45

50

55

EPO FORM P0459

For more details about this annex : see Official Journal of the European Patent Office, No. 12/82

专利名称(译)	有机发光二极管显示器		
公开(公告)号	EP2797134A1	公开(公告)日	2014-10-29
申请号	EP2014155124	申请日	2014-02-14
[标]申请(专利权)人(译)	三星显示有限公司		
申请(专利权)人(译)	三星DISPLAY CO., LTD.		
当前申请(专利权)人(译)	三星DISPLAY CO., LTD.		
[标]发明人	PARK OK KYUNG YUN SU YEON		
发明人	PARK, OK-KYUNG YUN, SU YEON		
IPC分类号	H01L51/52 H01L27/32		
CPC分类号	G09G3/3208 G09G2300/0452 H01L27/3216 H01L27/3218 H01L27/3246 H01L51/525 H01L27/3262 H01L27/3276 H01L51/5036 H01L51/504 H01L51/5203 G02F1/1362		
优先权	1020130046996 2013-04-26 KR		
外部链接	Espacenet		

摘要(译)

有机发光二极管 (OLED) 显示器包括：围绕虚拟正方形 (VS) 的中心点 (CP) 的第一电极 (E1)；围绕第一顶点 (P1) 的第二电极 (E2) 和与虚拟正方形 (VS) 的第一顶点 (P2) 对角的第二顶点 (P2)，第二电极/ E2) 彼此分开并且与中心分离虚拟方块 (VS) 的点 (CP) 介于它们之间；虚拟正方形 (VS) 的第三顶点 (P3) 和第四顶点 (P4) 周围的第三电极 (E3)，第三电极 (E3) 彼此分开并与虚拟正方形的中心点 (CP) 分开 (VS) 插入其间；像素限定层 (PDL) 部分地在第一电极 (E1)，第二电极 (E2) 和第三电极 (E3) 上，并且部分地暴露第一电极 (E1)，第二电极 (E2) 和第三电极 (E3)；四个间隔物 (SP1, SP2, SP3, SP4) 在像素限定层 (PDL) 上设置为岛状，并且对应于虚拟方块 (VS) 的四个边 (V1, V2, V3, V4)。

FIG. 1

1000

