



(11)

EP 2 950 348 B1

(12)

EUROPEAN PATENT SPECIFICATION

(45) Date of publication and mention of the grant of the patent:
08.04.2020 Bulletin 2020/15

(51) Int Cl.:
H01L 27/32 (2006.01) **H01L 51/56 (2006.01)**

(21) Application number: **13872526.2**

(86) International application number:
PCT/CN2013/091180

(22) Date of filing: **31.12.2013**

(87) International publication number:
WO 2014/114178 (31.07.2014 Gazette 2014/31)

(54) PIXEL STRUCTURE FOR OLED DISPLAY SCREEN

PIXELSTRUKTUR FÜR EINEN OLED-ANZEIGEBILDSCHIRM

STRUCTURE DE PIXELS POUR ÉCRAN D'AFFICHAGE OLED

(84) Designated Contracting States:
**AL AT BE BG CH CY CZ DE DK EE ES FI FR GB
GR HR HU IE IS IT LI LT LU LV MC MK MT NL NO
PL PT RO RS SE SI SK SM TR**

- **QIU, Yong**
Beijing 100085 (CN)
- **ZHANG, Shenfu**
Kunshan
Jiangsu 215300 (CN)

(30) Priority: **24.01.2013 CN 201310026524**

(74) Representative: **D'Hallewijn, Nele Veerle Trees
Gertrudis
Arnold & Siedsma
Bezuidenhoutseweg 57
2594 AC The Hague (NL)**

(43) Date of publication of application:
02.12.2015 Bulletin 2015/49

(56) References cited:
CN-A- 1 917 228 **CN-A- 101 752 407**
CN-A- 102 262 854 **CN-A- 103 123 927**
CN-U- 203 260 585 **JP-A- H03 233 593**
US-A1- 2006 087 226 **US-A1- 2008 001 525**
US-A1- 2009 322 215

(73) Proprietors:
• **Kunshan Visionox Display Co., Ltd.**
Kunshan Jiangsu
215300 (CN)

• **Kunshan Go-Visionox Opto-Electronics Co., Ltd.**
KunShan City, Jiangsu 215300 (CN)

(72) Inventors:
• **PENG, Chaochi**
Kunshan
Jiangsu 215300 (CN)

Note: Within nine months of the publication of the mention of the grant of the European patent in the European Patent Bulletin, any person may give notice to the European Patent Office of opposition to that patent, in accordance with the Implementing Regulations. Notice of opposition shall not be deemed to have been filed until the opposition fee has been paid. (Art. 99(1) European Patent Convention).

Description

FIELD OF THE INVENTION

[0001] The present disclosure relates generally to the field of display technique, and specifically to a high resolution pixel structure and a fine metal mask corresponding to the pixel structure.

BACKGROUND OF THE INVENTION

[0002] Compared with traditional LCD display mode, it is not necessary for OLED display technique to use backlights. The OLED display technique has the property of self-illumination, a very thin organic material film and a glass substrate are used, and the organic material can glow when an electric current passes through it. Therefore an OLED display can provide significant power savings, can be lighter and thinner, and can tolerate a wider range of temperature variation than LCDs, with a wider viewing angle. The light-emitting layer of the OLED screen is composed by organic light-emitting components formed on corresponding pixel locations on an array substrate by using evaporation film technology to organic materials through a fine metal mask. The OLED screen should be colorized for color display. The side-by-side mode has the best effect on colorized screen. In the side-by-side mode, there are red, green and blue (R, G and B) three sub pixels in a pixel, and every sub pixel has an independent light-emitting component. Because the organic light-emitting materials of red, green and blue three sub pixels are different, in the production process, it needs to evaporate three different kinds of organic materials to red, green and blue three-color light-emitting sub pixels on the corresponding locations by a metal mask, and the color-ratio of the combination of the three colors is adjusted to create true color. In this way, the red, green and blue constitute three-color OLED components emit light independently to form a pixel.

[0003] The production of the pixel per inch (PPI) OLED screen has focused on fine metal mask with good mechanical stability, and the key to the fine metal mask is the arrangement of pixels and sub pixels.

[0004] According to the arrangement of the pixel array, there are a few kinds of opening methods of the metal mask existing in industry as follows.

Slit Mode

[0005] Fig.1 shows a traditional pixel arrangement arranged side by side. The light-emitting layer of the OLED display is composed by pixel cells 100 arranged on a substrate 10 in multi-row and multi-column. For the pixel arrangement as shown in Fig. 1, there are red (R) 102, green (G) 103 and blue (B) 100 three sub pixels parallel to each other in one pixel cell 100. In order to form the pixel arrangement, the corresponding metal mask is shown in Fig. 2.

[0006] Fig. 2 shows a metal mask used to form one of the sub pixels (R sub pixel) in the pixel structure as shown in Fig. 1 on the OLED display substrate. It will be appreciated that the rest sub pixels (G and B) can be formed by a metal mask having the same above structure due to each sub pixel having the same patterning.

[0007] The metal mask includes a metal substrate 20 and a rectangular opening 200 thereon. Wherein, the number of the opening can be determined by the number of the pixel required by the resolution of the OLED display. Fig. 2 shows four columns of openings 200. A section 201 between adjacent two openings 200 forms an unopened metal strip of the metal substrate 20. As shown in Fig. 1, the opening method of the metal mask is that one opening 200 is shared by all the sub pixels in the same column (for example, R sub pixels) in the OLED screen. Thus the opening 200 of the metal mask is relative long in length. With the increase in display size, the length of the opening of the metal mask needs to be increased.

[0008] This shows Slit Mode is easy to make and use the metal mask for low-resolution OLED screens due to which the number of pixels is small that the space between adjacent openings 200 is relative large, i.e., the width of the metal strip is relative wide.

[0009] However, the above opening mode needs a fine metal mask when used for a high resolution screen. The space between adjacent openings 200 is reduced for the increase in the number of pixels, i.e., the metal strip 201 is relative fine. This creates a problem that the metal strip is likely to be out of shape under the influence of magnetic field lines of the magnetic board during the use of the metal mask, resulting in color mixing caused by the spread of different color materials in among pixels, and resulting in low yield during production. Moreover, this kind of metal mask is easy to be damaged or deformed in the process of using, cleaning and storing, with a low repetitive use rate, and the screen produced by this mode has a high cost due to the high cost of the metal mask.

Slot Mode

[0010] In view of the above problem, a metal mask solution with a slot is provided, as shown in Fig. 3, to form the arrangement of pixels as shown in Fig. 1. As Fig. 3, the opening mode of the metal mask is that based on Slit Mode the locations corresponding to the spaces between the sub pixels as shown in Fig.1 and corresponding to the openings 200 as shown in Fig. 2 are provided with metal bridges 301 connecting adjacent metal strips, so that one long opening 200 as shown in Fig. 2 is changed into a plurality of openings units 300 corresponding to the sub pixel structure as shown in Fig. 1.

[0011] This opening mode makes the metal strip of the metal mask stronger to resolve the above problem that the metal strip is likely to be out of shape under the influence of magnetic field lines and external force in Slit Mode. However in view of the precision of long size of

the metal mask that adequate distance must be maintained between the sub pixel and the bridge in order to avoid shadow effect in sub pixels when evaporation, the reduction in the length between bottoms of the sub pixel will affect the opening rate of every sub pixel.

[0012] To solve this problem, a United States patent No. 20110128262A1 discloses another pixel structure different from the above pixel structure, as shown in Fig. 4. The pixel structure includes a plurality of pixel units 400 arranged in multi-row and multi-column, each pixel is composed of red, green and blue three sub pixels, where the blue sub pixel has the largest surface area due to fastest attenuation of blue light, while the red and green sub pixels are arranged on one side of the blue sub pixel and respectively arranged on the upper and lower locations along the long side of the blue sub pixel.

[0013] The pixel units 400 are arranged repeatedly to form a pixels array. The arrangement of the pixel structure makes the spaces between the openings of the metal mask corresponding to the red and green sub pixels (as Figs. 5-6) are relatively large that high-resolution display can be achieved to some extent.

[0014] However, the blue sub pixels in the pixel array are aligned as Fig.1, so that their corresponding metal mask must use the opening mode as the above Slit or Slot (as Fig. 7). Because both the above Slit Mode and Slot Mode have defects, the opening mode of the blue metal mask (B mask) of the arrangement of the pixel array as shown in Fig. 4 seriously affects the opening rate of the sub pixel and the resolution further upgrade.

[0015] US 2006/0087226 discloses a plate-shaped vapor deposition mask for use with an OLED substrate. The mask is provided with through holes corresponding to a plurality of organic light-emitting elements formed on the substrate.

[0016] US 2008/0001525 discloses a color display panel formed with a plurality of pixels in a matrix with a row direction and a column direction, wherein each pixel comprises a first subpixel, a second sub-pixel and a third sub-pixel adjacently aligned along the row direction of the pixel matrix, and a red light emission zone, a green light emission zone and a blue light emission zone.

[0017] US 2009/0322215 discloses an organic light emitting device. The organic light emitting device includes a blue subpixel that is larger than a red subpixel and a green subpixel. The red subpixel and the green subpixel have the same layered structure such that the red subpixel and the green subpixel are formed by using the same shadow mask. JPH 03233593 discloses an electroluminescent display with rectangular red, green and blue sub-pixels, wherein the green and blue subpixels are aligned along the long side of the red sub-pixel.

SUMMARY OF THE INVENTION

[0018] In view of the above, an object of the disclosure is to provide new arrangements of sub pixels and a pixel array to make the fine metal mask have high mechanical

stability and easy to be produced, so as to improved the production of high resolution OLED screen well and reduce production costs.

[0019] In order to solve the above technical problem, the present disclosure uses the following technical solution.

[0020] The pixel structure for OLED display, according to the invention, has the features of claim 1. The pixel structure for OLED display includes multi-row pixel unit groups, each pixel unit group includes a plurality of pixel units arranged repeatedly in sequence, and each pixel unit includes a first sub pixel, a second sub pixel and a third sub pixel, wherein the same sub pixels of the pixel units in adjacent two rows are arranged in dislocation in a horizontal direction.

[0021] The second sub pixel and the third sub pixel are lined up along one of the sides of the first sub pixel in each pixel unit, and the arrangement of the first sub pixel, the second sub pixel and the third sub pixel of the pixel unit of the pixel unit group in an even row is formed by flipping the pixel unit of the pixel unit group in an odd row horizontally to 180°.

[0022] The second sub pixel and the third sub pixel are lined up along one of the sides of the first sub pixel in each pixel unit, and the pixel unit group in an even row is arranged to be offset by a first distance with respect to the pixel unit group in an odd row in a horizontal direction.

[0023] The pixel unit group in an even row is arranged to be offset to left by a second distance or be offset to right by a third distance with respect to the pixel unit group in an odd row in a horizontal direction.

[0024] Preferably, the first sub pixel, the second sub pixel and the third sub pixel in each pixel unit are arranged in a specified order, and the arrangement of the sub pixels of the pixel unit of an odd row is different from that of an even row.

[0025] Preferably, the first sub pixel, the second sub pixel and the third sub pixel in each pixel unit are arranged side by side, and the pixel unit group in an even row is arranged to be offset by a first distance with respect to the pixel unit group in an odd row in a horizontal direction.

[0026] Preferably, the pixel unit group in an even row is arranged to be offset to left by a second distance or be offset to right by a third distance with respect to the pixel unit group in an odd row in a horizontal direction.

[0027] Preferably, the first sub pixel, the second sub pixel and the third sub pixel are shaped rectangles.

[0028] The pixel unit has a shape of square, the first sub pixel has a shape of rectangle, the second sub pixel and the third sub pixel are aligned vertically along the long side of the first sub pixel, and the length of the long side of the first sub pixel is larger than two-thirds of the side length of the pixel unit.

[0029] The area of the first sub pixel is larger than that of the second sub pixel and that of the third sub pixel, and is smaller than half of the area of the pixel unit.

[0030] Preferably, the area of the first sub pixel is twice

as that of at least one sub pixel of the second sub pixel and the third sub pixel.

[0031] Optionally, the area of the second sub pixel or the third sub pixel can be larger than the area of each of the remaining two sub pixels. 5

[0032] Optionally, the area of the second sub pixel or the third sub pixel is twice as that of at least one of the remaining two sub pixels.

[0033] Preferably, the scope of the first distance offset in a horizontal direction is to make same sub pixels in adjacent two rows be arranged in dislocation in the horizontal direction. 10

[0034] Preferably, the second distance offset to the left or the third distance offset to the right make same sub pixels in adjacent two rows be arranged in dislocation in a horizontal direction. 15

[0035] Preferably, the scope of the dislocation between the first sub pixels in the pixel unit in an even row and the first sub pixels in the pixel unit in an odd row in a horizontal direction makes the spaces between the first sub pixel in an even row and adjacent two first sub pixels in adjacent odd rows are the same. 20

[0036] Preferably, the first sub pixel is a blue pixel, the second sub pixel is a red pixel, and the third sub pixel is a green pixel. 25

[0037] Optionally, the second or third sub pixel can be a blue pixel, and the remaining two sub pixels are a red pixel and a green pixel. 30

[0038] Also disclosed is a metal mask for making sub pixels in a pixel structure of OLED display.

[0039] This metal mask for making sub pixels in a pixel structure of an OLED display includes a substrate including a plurality of openings arranged in turn in rows and columns, where the opening is configured to form the sub pixel and the openings in an even row and the openings in an odd row are arranged in dislocation in a horizontal direction. 35

[0040] Preferably, the distances between the opening in an even row and adjacent two openings in adjacent odd rows are the same. 40

[0041] The further object of the disclosure is to provide an OLED display, which includes any pixel structure as above.

[0042] The pixel structure and its corresponding metal mask and OLED display of the present disclosure has the following advantages.

[0043] The distance between the corresponding openings of the sub pixels are widened when making the corresponding metal mask to enhance the strength of the metal mask that a pixel unit of a smaller size can be produced under the consideration of process condition, so as to improve the resolution of the OLED display. 45

BRIEF DESCRIPTION OF THE DRAWINGS

[0044]

Fig. 1 is a schematic diagram illustrating a traditional

Slit Mode for pixel arrangement.

Fig. 2 is a schematic diagram illustrating openings of a metal mask corresponding to Slit Mode.

Fig. 3 is a schematic diagram illustrating a structure of a metal mask corresponding to Slit Mode.

Fig. 4 is a schematic diagram illustrating a pixel structure according to another arrangement in the prior art.

Fig. 5 is a schematic diagram illustrating a structure of a metal mask corresponding to green pixels in the pixel structure as Fig. 4.

Fig. 6 is a schematic diagram illustrating a structure of a metal mask corresponding to red pixels in the pixel structure as Fig. 4.

Fig. 7 is a schematic diagram illustrating a structure of a metal mask corresponding to blue pixels in the pixel structure as Fig. 4.

Figs. 8 (a)-(c) are schematic diagrams illustrating a pixel structure according to two non-inventive examples and an inventive embodiment of the present disclosure.

Fig. 8 (a1) is a schematic diagram illustrating a scope of a first distance in the pixel structure as Fig. 8 (a).

Fig. 9 is a schematic diagram illustrating a pixel unit flipped horizontally from a pixel unit in the pixel structure as Fig. 8 (b).

Fig. 10 is a schematic diagram illustrating a location of the blue pixel in the pixel structure as Fig. 8 (a)-(c).

Figs. 11 (a)-(c) are schematic diagrams illustrating metal masks of sub pixels corresponding to the pixel structure as Fig. 8 (a)-(c).

Fig. 12 is a schematic diagram illustrating a metal mask according to an optimal embodiment of the present disclosure.

Figs. 13 (a)-(c) are schematic diagrams illustrating pixel structures according to other two non-inventive examples and an other inventive embodiment of the present disclosure.

Figs. 14 (a)-(c) are schematic diagrams illustrating pixel structures according to further non-inventive examples of the present disclosure.

DETAILED DESCRIPTION OF THE INVENTION

[0045] In the following description of embodiments, reference is made to the accompanying drawings which form a part hereof, and in which it is shown by way of illustration specific embodiments of the present disclosure that can be practiced. It is to be understood that other embodiments can be used and structural changes can be made without departing from the scope of the disclosed embodiments.

[0046] Figs. 8 (a)-8(c) illustrate a pixel structure of the OLED display according to two non-inventive examples and an inventive embodiment of the present invention.

[0047] Wherein, a pixel structure 50A is located on a substrate (not shown). The pixel structure 50A includes multi-row pixel unit groups (denoted with the dotted box),

a plurality of pixel unit groups in odd rows 50Ai includes pixel units 500A arranged repeatedly, and a plurality of pixel unit groups in even rows 50Aj includes pixel units 501A arranged repeatedly.

[0048] Wherein, each pixel unit 500A or 501A is a square, each pixel unit 500A or 501A includes red (R), green (G), and blue (B) three sub pixels. It's important to note that such square or rectangle described herein is only a general description for the shape of the sub pixel, and in which minor modification may be made in practice, for example, four corners of the square or rectangle can be rounded with a curve, as shown in Fig. 8 (a1).

[0049] As shown in Fig. 8(a), the sub pixel such as the blue sub pixel (B) of the pixel unit 500A in an odd row and the sub pixel such as the blue sub pixel (B) of the pixel unit 501A in an even row are arranged in dislocation in a horizontal direction, i.e., they are not aligned in vertical direction. Such pixel structure widens the distance between the corresponding openings of the sub pixels when making the corresponding metal mask to enhance the strength of the metal mask that a pixel unit of a smaller size can be produced under the consideration of process condition, so as to improve the resolution of the OLED display.

[0050] Wherein, the three sub pixels in the pixel unit 500A in odd rows or in the pixel unit 501A in even rows can be arranged as that the blue sub pixel (B) is arranged on the left half of the pixel unit 500A or 501A and the red sub pixel (R) and the green sub pixel (G) are lined up along the right side of the blue sub pixel (B) and on the right half of the pixel unit 500A or 501A.

As shown in Fig. 8 (a), the pixel unit 501A of the pixel unit group in an even row and the pixel unit 500A of the pixel unit group in an odd row are arranged in dislocation in a horizontal direction. Namely, the pixel unit group in an even row is arranged to be offset by a first distance $\Delta 1$ left or right to the pixel unit group in an odd row in the horizontal direction and arranged closely to the pixel unit group in the odd row. Wherein, the pixel unit group in an even row arranged to be offset by a first distance $\Delta 1$ left or right to the pixel unit group in an odd row makes corresponding sub pixels in adjacent two rows of pixel unit groups are arranged in dislocation in the horizontal direction. The scope of the first distance $\Delta 1$ can be less than the distance between adjacent two same sub pixels in the same row.

[0051] For example, as shown in Fig. 8 (a1), the distance between left boundaries of the blue sub pixels (B1 and B2) in adjacent two pixel units 500A in the pixel unit group in an odd row is AE, and the scope of the first distance $\Delta 1$ can be chosen to a distance less than AE.

[0052] In one example not forming part of the present invention, the scope of the first distance $\Delta 1$ can be chosen that the left boundary of the blue sub pixel (B) of the pixel unit 501A of the pixel unit group in an even row is in the vertical center line of AE, i.e., the sub pixel of the pixel unit 501A of the pixel unit group in an even row is located in the middle position of two same sub pixels of adjacent

two pixel units in a adjacent pixel unit group in an odd row.

[0053] In this way, the distance between the opening of the corresponding sub pixel in an odd row and the corresponding sub pixel in an even row can be maximized to enhance the strength of the metal mask that a pixel unit of a smallest size can be produced under the consideration of process condition, so as to put more pixel units in a display panel with a certain area to achieve the production of high resolution OLED display.

[0054] Wherein, the red, green and blue three sub pixels in the pixel units 500A or 501A can be squares or rectangles. Moreover, the area of the pixel unit 500A or 501A and the three sub pixels can be determined by the resolution of the OLED display demands.

[0055] In one embodiment, the areas of the red and green sub pixels are the same, and the distance between the red sub pixel or the green sub pixel and the blue sub pixel are the same. In addition, in one embodiment, suitable area ratios between each sub pixel can be determined by the luminescent capability and life of the organic light-emitting material and white balance. In one embodiment, in view of the blue-light emitting material having low luminescent capability and short life among existing materials and the requirement of white balance, the area of the blue sub pixel is chosen to be larger than the area of the red sub pixel or the green sub pixel.

[0056] In one embodiment, the blue sub pixel has a shape of rectangle, and the red sub pixel and the green sub pixel are aligned along the long side of the blue sub pixel.

[0057] In one embodiment, the length of the long side of the blue sub pixel is larger than two-thirds of the side length of the pixel unit.

[0058] In one embodiment, the opening area of the blue sub pixel is about twice as that of the red sub pixel or green sub pixel.

[0059] Accordingly, spaces are needed between the blue, red and green pixels, so the area of the blue sub pixel is less than half of the area of the pixel unit 500A or 501A.

[0060] Fig. 10 shows the positional relation between the sub pixels, where B-B' is a vertical center line of the pixel unit, and A-A' is a vertical center line of horizontal spacing between the blue sub pixel and the closest sub pixel thereto of the red and the green sub pixels. Wherein, the vertical center line of horizontal spacing between the blue sub pixel and the closest sub pixel (for example, the red sub pixel) thereto of the red and the green sub pixels A-A' and the blue sub pixel are on the same side of the vertical center line of the pixel unit B-B'. Wherein the locations of A-A' and B-B' in the pixel 500 or 501 do not overlap.

[0061] It can be seen that each same sub pixel of every two adjacent rows can be arranged in dislocation in a horizontal direction by arranging the pixel unit group in an even row and the pixel unit group in an odd row to be offset by a first distance in the horizontal direction. In this way, the openings of adjacent rows in the metal mask

are arranged in dislocation when creating the metal mask of the sub pixels, such as the metal mask of the blue sub pixels, as Fig. 11a. The arrangement of the openings in the metal mask corresponding to the red sub pixels and the green sub pixels as shown in Fig. 11 (b) and Fig. 11 (c). In this way, the strength of the metal mask can be enhanced. Under the same process conditions, compared with the aligned arrangement of sub pixels in adjacent two rows of pixel unit groups in the prior art, the structure of the sub pixels of adjacent rows arranged in dislocation of the present disclosure widens the available distance between the openings of the same sub pixels that a pixel unit of a smaller size can be produced to achieve the production of the high resolution OLED display.

[0062] In one embodiment, the scope of distance offset makes the blue sub pixel in even rows be in the middle of two adjacent blue sub pixels in adjacent two odd rows that the distance between the blue sub pixels in an even row and two adjacent blue sub pixels in an adjacent odd row are the same. The intention of the pixel structure can make the spaces between the adjacent blue sub pixels be maximized. Accordingly, the distances between openings in the metal mask for making blue sub pixels also can be maximized, and as shown in Fig. 12, the distance between the opening B and the opening B is significantly improved to enhance the strength of the metal mask that a pixel unit of a smaller size can be produced under the consideration of process condition, so as to achieve the production of the high resolution OLED display.

[0063] Fig. 8 (b) is a schematic diagram illustrating a pixel structure 50B according to another non-inventive example of the present disclosure.

[0064] The difference between the pixel structure shown in Fig. 8 (b) and the pixel structure shown in Fig. 8 (a) is that left and right boundaries of the pixel unit 500B and 501B in the pixel unit group in the odd row 50Bi and the pixel unit group in the even row 50Bj are lined up. And the pixel unit 501B in the even row shown in Fig. 8 (b) is aligned to the pixel unit 500B by flipping the pixel unit 500B in the odd row horizontally to 180°, as shown in Fig. 9, to make the sub pixels in the pixel unit 501B and the sub pixels in the pixel unit 500B be arranged in dislocation in a horizontal direction.

[0065] Namely, if the red and green sub pixels in the pixel unit 500B in the odd row are lined up along the right side of the blue sub pixel, the red and green sub pixels in the pixel unit 501B in the even row are lined up along the left side of the blue sub pixel.

[0066] In one example, the red, green and blue three sub pixels in the pixel units 500B or 501B can be squares or rectangles.

[0067] In one example, the areas of the red and green sub pixels are the same, and the distances between the red sub pixel and the blue sub pixel and between the green sub pixel and the blue sub pixel are the same.

[0068] In one example, the blue sub pixel has a shape of rectangle, and the red sub pixel and the green sub

pixel are aligned along the long side of the blue sub pixel.

[0069] In one example, the length of the long side of the blue sub pixel is larger than two-thirds of the side length of the pixel unit.

[0070] In one example, the opening area of the blue sub pixel is about twice as that of the red sub pixel or green sub pixel.

[0071] In one example, the area of the blue sub pixel is less than half of the area of the pixel unit 500B or 501B.

[0072] It can be seen that each same sub pixel of every two adjacent rows can be arranged in dislocation in a horizontal direction by flipping the sub pixels in each pixel unit in the odd row and the even row horizontally to 180° instead of arranging the pixel unit group in the even row to be offset by a distance with respect to the pixel unit group in the odd row in the horizontal direction. This structure can obtain the benefits of the above structure of the sub pixels of adjacent rows arranged in dislocation, and because the pixel units in the odd row and the pixel unit in the even row (taking the pixel unit as a whole) are aligned, there is no blank area on the edge of the display, so as to achieve a better display effect.

[0073] In one embodiment, the openings of adjacent rows in the metal mask are arranged in dislocation by the pixel structure of the above embodiment when making the metal mask corresponding to the sub pixels, such as making the metal mask of the blue sub pixel, as shown in Fig. 10. Similarly, the strength of the metal mask can be enhanced and the production of the high resolution OLED display can be achieved.

[0074] Fig. 8 (c) is a schematic diagram illustrating a pixel structure 50C according to an inventive embodiment of the present disclosure.

[0075] Wherein, the difference between the pixel structure shown in Fig. 8 (c) and the pixel structure shown in Fig. 8 (b) is that in the pixel structure 50C the pixel unit group 50Ci in the even row is arranged to be offset by a second distance $\Delta 2$ left (or right) to the pixel unit group 50Cj in the odd row in a horizontal direction and lined up on a adjacent row of the odd row.

[0076] In one embodiment, the red, green and blue three sub pixels in the pixel units 500A or 501A can be squares or rectangles.

[0077] In one embodiment, the areas of the red and green sub pixels can be the same, and the distance between the red sub pixel or the green sub pixel and the blue sub pixel can be the same.

[0078] In one embodiment, the blue sub pixel has a shape of rectangle, and the red sub pixel and the green sub pixel are aligned along the long side of the blue sub pixel.

[0079] In one embodiment, the length of the long side of the blue sub pixel is larger than two-thirds of the side length of the pixel unit.

[0080] In one embodiment, the area of the blue sub pixel is larger than that of the red sub pixel or that of the green sub pixel.

[0081] In one embodiment, the opening area of the

blue sub pixel is about twice as that of the red sub pixel or green sub pixel.

[0082] In one embodiment, the area of the blue sub pixel is less than half of the area of the pixel unit 500A or 501A.

[0083] It's important to note that the pixel unit group can be arranged to be offset by a second distance $\Delta 2$ to the left and also can be arranged to be offset by a third distance to the right (not shown). Fig. 8 (c) only shows the even row is offset by a second distance $\Delta 2$ left to the odd row in a horizontal direction. Wherein, the scope of the second distance and the scope of the third distance make same sub pixels in adjacent two rows be arranged in dislocation in the horizontal direction.

[0084] It should be understood that the scope of the second distance and the scope of the third distance are determined by the horizontal distance between the adjacent same sub pixels in the same column of pixels units in adjacent two rows, and can be implemented by arranging the same sub pixels in adjacent two rows in dislocation in a horizontal direction.

[0085] In one embodiment, the scope of distance offset makes the blue sub pixel in even rows be in the middle of two adjacent blue sub pixels in adjacent two odd rows that the distance between the blue sub pixels in an even row and two adjacent blue sub pixels in an adjacent odd row are the same, as the positional relation between the blue sub pixels shown in Fig. 8 (c) at doubleheaded arrow. In this way, the spaces between the adjacent blue sub pixels can be maximized, and the distances between corresponding openings of the sub pixels in the metal mask can be maximized when making the pixel structure, so as to enhance the strength of the metal mask that a pixel unit of a smaller size can be produced under the consideration of process condition and the production of the high resolution OLED display can be achieved.

[0086] It should be understood that Figs. 8 (a) - 8 (c) only show three kinds of pixel structures for examples. Actually, the pixel units in the odd row and the pixel units in the even row can be interchanged. Fig. 10 is a schematic diagram illustrating a metal mask 60B of the blue sub pixel corresponding to the pixel structure as shown in Figs. 8 (a) - 8 (c), where the location of the openings are used to form the blue sub pixels. It should be understood that Fig. 10 only shows the arrangement of the opening of the metal mask of the blue sub pixel, while the area of the opening and the specific location of the opening in the metal mask are made based on actual pixel structures.

[0087] Take the blue sub pixel for instance. It can be seen that the spaces between openings in the metal mask can be enlarged due to the specific arrangement of the pixel unit of the present disclosure and the specific arrangement of the blue sub pixel, so as to solve the problem of Slit Mode and Slot Mode in the prior art.

[0088] In one embodiment, when the openings of the blue sub pixels in the even row are located in the middle of the openings of two adjacent blue sub pixels in adja-

cent two odd rows, the distances between the openings B in the metal mask 60B are widest, as shown in Fig. 12.

[0089] Figs. 13 (a)-(c) are schematic diagrams illustrating pixel structures 70A-70C according to another two non-inventive examples and an other inventive embodiment modified from the non-inventive examples and the inventive embodiment as shown in Fig. 8 (a) - 8 (c).

[0090] Wherein, the different from the pixel structures as shown in Fig. 8 (a) - 8 (c) is that the blue sub pixel and the green sub pixel are lined up along one side of the red sub pixel.

[0091] In one embodiment, the area of the blue sub pixel is larger than that of the red sub pixel or the green sub pixel.

[0092] In one embodiment, the red, green and blue three sub pixels in the pixel units 500C or 501C can be squares, rectangles or other shapes.

[0093] In one embodiment, the red sub pixel has a shape of rectangle, and the blue sub pixel and the green sub pixel are aligned along the long side of the red sub pixel.

[0094] In one embodiment, the length of the long side of the red sub pixel is larger than two-thirds of the side length of the pixel unit.

[0095] In one embodiment, the area of the blue sub pixel and that of the green sub pixel are the same.

[0096] In one embodiment, the opening area of the blue sub pixel is about twice as that of the red sub pixel or green sub pixel.

[0097] In one embodiment, the area of the blue sub pixel is less than half of the area of the pixel unit 500C or 501C.

[0098] Similar to some examples described above, same sub pixels in adjacent two rows can be arranged in dislocation in a horizontal direction by arranging the pixel unit groups in adjacent two rows to be offset by a first distance in the horizontal direction, as shown in Fig. 13 (a), flipping the pixel units in the odd row (or even row) horizontally to 180° to form the pixel units in the even row (or odd row), as shown in Fig. 13 (b), or arranging the pixel unit groups in adjacent two rows to be offset by a second distance in the horizontal direction based on the pixel structure as Fig. 13 (b), as shown in Fig. 13 (c).

[0099] Thus, the pixel structures as shown in Fig. 13 (a)-(c) enlarge the distance between the same sub pixels and the distances between corresponding openings of the sub pixels in the metal mask can be enlarged when making the pixel structure, so as to achieve the production of the high resolution OLED display.

[0100] Figs. 14 (a)-(c) are schematic diagrams illustrating pixel structures 80A-80C according to further non-inventive examples of the present disclosure. The pixel units in the rows can be arranged side-by-side, as shown in the figure.

[0101] Fig. 14 (a) shows a pixel structure that the pixel units in the odd row and the even row are arranged in a same order, where the pixel unit group in the even row is arranged to be offset by a distance with respect to the

pixel unit group in the odd row in a horizontal direction.

[0102] The scope of the offset distance makes the same sub pixels in adjacent two rows be arranged in dislocation, similar to the first embodiment.

[0103] Fig 14 (b) shows a structure that the sub pixels in the pixel unit 500A of the pixel unit group in the odd row and the sub pixels in the pixel unit 501A of the pixel unit group in the even row are arranged in different orders.

[0104] Namely, if the arrangement of the sub pixels in the pixel unit in the odd row is B, R and G, the arrangement of the sub pixels in the pixel unit in the even row is R, G and B or G, B and R. On the one hand, the left and right boundaries of the pixel units of the pixel unit group in the odd row and the even row can be aligned that the pixel units in the odd row and the even row are aligned on the left and right edges of the display to better use of the area to achieve a better display effect. Meanwhile, the same sub pixels in adjacent two rows are arranged in dislocation due to different arrangements of the same sub pixels in the pixel units in the even row and those in the odd row, so as to enhance the strength of the metal mask and achieve the production of the high resolution OLED display mentioned in the above embodiments.

[0105] On the other hand, because the arrangements of the sub pixels in pixel units in the even rows are the same, and the arrangements of the sub pixels in pixel units in the odd rows are the same, such regular arrangement structure makes the production of TFT drive back-planes and the design of corresponding drive circuits easier. On the contrary, if the arrangements of the pixels in the odd rows and the even rows are irregular or arranged in a complicated order, complex designs of TFT back-plane and drive circuit are needed to display wanted images.

[0106] In one example, as shown in Fig. 14 (b), the length of the red sub pixels R and the green sub pixels G in the pixel units of the pixel unit group in the odd row and the red sub pixels R and the green sub pixels G in corresponding pixel units in the even row is shorter than that of the blue sub pixel (not shown). The pixel structure can widen the distance between the corresponding openings of the sub pixels in the metal mask to enhance the strength of the metal mask and improve the resolution of the OLED display mentioned in the above examples.

[0107] Fig. 14 (c) shows a pixel structure that the unit pixel group in the even row is arranged to be offset by a distance in a horizontal direction based on the pixel unit structure as shown in Fig. 14 (b).

[0108] In addition, the present disclosure also provides an OLED display using the above pixel structures.

[0109] It can be understood that the pixel unit group can be arranged to be offset by a distance to the left and also can be arranged to be offset by a distance to the right, and the scope of the offset distance makes the sub pixels in adjacent two rows be arranged in dislocation.

[0110] Similar to the above examples, the arrangement as shown in Fig. 14 also can achieve the opening

effect of the metal mask of the present disclosure.

[0111] The above embodiments are chosen and described in order to explain the principles of the present disclosure and their practical application so as to activate others skilled in the art to utilize the present disclosure and various embodiments and with various modifications as are suited to the particular use contemplated. Accordingly, the scope of the present disclosure is defined by the appended claims rather than the foregoing description and the exemplary embodiments described therein.

Claims

15. 1. A pixel structure for OLED display, comprising a plurality rows (50Ci) of pixel unit groups, wherein each pixel unit group comprises a plurality of pixel units (500C) arranged repeatedly in sequence, each pixel unit comprising a first sub pixel (B), a second sub pixel (R) and a third sub pixel (G);
 20. wherein in each pixel unit, the second sub pixel (R) and the third sub pixel (G) are lined up along one of the sides of the first sub pixel (B); and in the pixel unit group in an even row, the arrangement of the first sub pixel, the second sub pixel and the third sub pixel of the pixel unit is formed by flipping the pixel unit of the pixel unit group in an odd row horizontally by 180°;
 25. **characterized in that** the first sub pixel (B) and a vertical center line (A-A') of horizontal spacing between said first sub pixel (B) and the closest sub pixel thereto of the second sub pixel (R) and the third sub pixel (G) are on the same side of a vertical center line (B-B') of the pixel unit; and that the vertical center line (A-A') of horizontal spacing and the vertical center line (B-B') of the pixel unit do not overlap;
 30. **in that** the pixel unit (500C) has a shape of square, the first sub pixel (B) has a shape of rectangle, the second sub pixel (R) and the third sub pixel (G) are aligned vertically along the long side of the first sub pixel (B), and the length of the long side of the first sub pixel (B) is larger than two-thirds of the side length of the pixel unit (500C);
 35. **in that** the area of the first sub pixel (B) is larger than that of the second sub pixel (R) and that of the third sub pixel (G), and is smaller than half of the area of the pixel unit (500C); and
 40. **in that** the pixel unit group in the even row is arranged to be offset by a first distance with respect to the pixel unit group in the odd row in a horizontal direction, so that the same sub pixels of two adjacent rows of pixel units are arranged in dislocation in a horizontal direction and so that the distances from the first sub pixel in an even row to two adjacent first sub pixels in an odd row adjacent to the even row are the same.

45. 2. The pixel structure of claim 1, **characterized in that**

the first sub pixel, the second sub pixel and the third sub pixel are shaped rectangles.

3. The pixel structure of claim 1, **characterized in that** the area of the first sub pixel is twice as that of at least one of the second and third sub pixels. 5
4. The pixel structure of claim 1, **characterized in that** the first sub pixel is a blue pixel, the second sub pixel is a red pixel and the third sub pixel is a green pixel. 10
5. An OLED display, **characterized in that** the display comprises the pixel structure of any of claims 1 to 4.

Patentansprüche

1. Pixelstruktur für eine OLED-Anzeige, die eine Vielzahl von Zeilen (50Ci) von Pixeleinheitengruppen umfasst, wobei jede Pixeleinheitengruppe eine Vielzahl von Pixeleinheiten (500C) umfasst, die wiederholt nacheinander angeordnet sind, wobei jede Pixeleinheit ein erstes Subpixel (B), ein zweites Subpixel (R) und ein drittes Subpixel (G) umfasst; wobei in jeder Pixeleinheit das zweite Subpixel (R) und das dritte Subpixel (G) entlang einer der Seiten des ersten Subpixels (B) angeordnet sind; und in der Pixeleinheitengruppe einer geraden Zeile die Anordnung des ersten Subpixels, des zweiten Subpixels und des dritten Subpixels der Pixeleinheit gebildet wird, indem die Pixeleinheit der Pixeleinheitengruppe einer ungeraden Zeile horizontal um 180° gedreht wird;
dadurch gekennzeichnet, dass das erste Subpixel (B) und eine vertikale Mittellinie (A-A') eines horizontalen Abstands zwischen dem ersten Subpixel (B) und dem dazu nächstgelegenen Subpixel aus dem zweiten Subpixel (R) und dem dritten Subpixel (G) sich auf der selben Seite einer vertikalen Mittellinie (B-B') der Pixeleinheit befinden; und **dass** sich die vertikale Mittellinie (A-A') des horizontalen Abstands und die vertikale Mittellinie (B-B') der Pixeleinheit nicht überlappen;
dadurch, dass die Pixeleinheit (500C) die Form eines Quadrats aufweist, das erste Subpixel (B) die Form eines Rechtecks aufweist, das zweite Subpixel (R) und das dritte Subpixel (G) vertikal entlang der langen Seite des ersten Subpixels (B) ausgerichtet sind, und dass die Länge der langen Seite des ersten Subpixels (B) größer als zwei Drittel der Seitenlänge der Pixeleinheit (500C) ist;
dadurch, dass die Fläche des ersten Subpixels (B) größer als die des zweiten Subpixels (R) und die des dritten Subpixels (G) ist, und kleiner als die Hälfte der Fläche der Pixeleinheit (500C) ist; und
dadurch, dass die Pixeleinheitengruppe in der geraden Zeile so angeordnet ist, dass sie in horizontaler Richtung um einen ersten Abstand gegenüber

der Pixeleinheitengruppe in der ungeraden Zeile versetzt ist, so dass die gleichen Subpixel von zwei benachbarten Reihen von Pixeleinheiten in horizontaler Richtung im Versatz angeordnet sind, und so dass die Abstände von dem ersten Subpixel in einer geraden Zeile zu zwei benachbarten ersten Subpixeln in einer ungeraden Zeile neben der geraden Zeile gleich sind.

2. Pixelstruktur nach Anspruch 1, die **dadurch gekennzeichnet ist, dass** das erste Subpixel, das zweite Subpixel und das dritte Subpixel als Rechtecke geformt sind. 15
3. Pixelstruktur nach Anspruch 1, die **dadurch gekennzeichnet ist, dass** die Fläche des ersten Subpixels doppelt so groß ist wie die des zweiten und/oder des dritten Subpixels. 20
4. Pixelstruktur nach Anspruch 1, die **dadurch gekennzeichnet ist, dass** es sich bei dem ersten Subpixel um ein blaues Pixel handelt, bei dem zweiten Subpixel um ein rotes Pixel, und bei dem dritten Subpixel um ein grünes Pixel. 25
5. OLED-Anzeige, die **dadurch gekennzeichnet ist, dass** die Anzeige die Pixelstruktur nach einem der Ansprüche 1 bis 4 umfasst. 30

Revendications

1. Structure de pixels pour un écran OLED, comprenant une pluralité de rangées (50Ci) de groupes d'unités formant pixel, chaque groupe d'unités formant pixel comprenant une pluralité d'unités formant pixel (500C) agencées de façon ordonnée et répétée, chaque unité formant pixel comprenant un premier sous-pixel (B), un deuxième sous-pixel (R) et un troisième sous-pixel (G) ; et dans laquelle dans chaque unité formant pixel, le deuxième sous-pixel (R) et le troisième sous-pixel (G) sont alignés le long d'un des côtés du premier sous-pixel (B) ; et dans le groupe d'unités formant pixel d'une rangée paire, l'agencement du premier sous-pixel, du deuxième sous-pixel et du troisième sous-pixel de l'unité formant pixel est formé en retournant l'unité formant pixel du groupe d'unités formant pixel d'une rangée impaire horizontalement de 180° ; **caractérisée en ce que** le premier sous-pixel (B) et une ligne médiane verticale (A-A') au sein d'un espace horizontal entre ledit premier sous-pixel (B) et le sous-pixel le plus proche de celui-ci parmi le deuxième sous-pixel (R) et le troisième sous-pixel (G) sont du même côté d'une ligne médiane verticale (B-B') de l'unité formant pixel ; et **en ce que** la ligne médiane verticale (A-A') au sein de l'espace horizontal et la ligne médiane verticale (B-B') de l'uni-

té formant pixel ne se chevauchent pas ;
en ce que l'unité formant pixel (500C) a la forme
d'un carré, le premier sous-pixel (B) a la forme d'un
rectangle, le deuxième sous-pixel (R) et le troisième
sous-pixel (G) sont alignés verticalement le long du 5
côté long du premier sous-pixel (B), et la longueur
du côté long du premier sous-pixel (B) est supérieure
aux deux tiers de la longueur du côté de l'unité for-
mant pixel (500C) ;
en ce que la superficie du premier sous-pixel (B) est 10
supérieure à celle du deuxième sous-pixel (R) et à
celle du troisième sous-pixel (G), et est inférieure à
la moitié de la superficie de l'unité formant pixel
(500C) ; et
en ce que le groupe d'unités formant pixel de la ran- 15
gée paire est agencé pour être décalé d'une premiè-
re distance par rapport au groupe d'unités formant
pixel de la rangée impaire dans un sens horizontal,
de façon que les mêmes sous-pixels de deux ran- 20
gées adjacentes d'unités formant pixel sont agencés
en dislocation dans un sens horizontal et de façon
que les distances entre le premier sous-pixel d'une
rangée paire et deux premiers sous-pixels adjacents
d'une rangée impaire adjacente à la rangée paire 25
soient les mêmes.

2. Structure de pixels selon la revendication 1, **carac-
térisé en ce que** le premier sous-pixel, le deuxième
sous-pixel et le troisième sous-pixel sont de forme
rectangulaire. 30
3. Structure de pixels selon la revendication 1, **carac-
térisé en ce que** la superficie du premier sous-pixel
fait deux fois celle du deuxième et/ou du troisième
sous-pixel. 35
4. Structure de pixels selon la revendication 1, **carac-
térisé en ce que** le premier sous-pixel est un pixel
bleu, le deuxième sous-pixel est un pixel rouge et le
troisième sous-pixel est un pixel vert. 40
5. Écran OLED, **caractérisé en ce qu'il comprend la**
structure de pixels selon l'une quelconque des re-
vendications 1 à 4. 45

50

55




Fig. 1




Fig. 2




Fig. 3




Fig. 4




Fig. 5




Fig. 6




Fig. 7




Fig. 8(a)




Fig. 8(a1)




Fig. 8(b)




Fig. 8(c)




Fig. 9




Fig. 10




Fig. 11(a)




Fig. 11(b)




Fig. 11(c)




Fig. 12




Fig. 13(a)




Fig. 13(b)




Fig. 13(c)




Fig. 14(a)




Fig. 14(b)




Fig. 14(c)

REFERENCES CITED IN THE DESCRIPTION

This list of references cited by the applicant is for the reader's convenience only. It does not form part of the European patent document. Even though great care has been taken in compiling the references, errors or omissions cannot be excluded and the EPO disclaims all liability in this regard.

Patent documents cited in the description

- US 20110128262 A1 [0012]
- US 20060087226 A [0015]
- US 20080001525 A [0016]
- US 20090322215 A [0017]
- JP H03233593 B [0017]

| | | | |
|----------------|--|---------|------------|
| 专利名称(译) | OLED显示屏的像素结构 | | |
| 公开(公告)号 | EP2950348B1 | 公开(公告)日 | 2020-04-08 |
| 申请号 | EP2013872526 | 申请日 | 2013-12-31 |
| [标]申请(专利权)人(译) | 昆山维信诺显示技术有限公司 昆山国显光电有限公司 | | |
| 申请(专利权)人(译) | 昆山维信诺显示CO. , LTD. 昆山GO-维信诺光电科技有限公司. | | |
| 当前申请(专利权)人(译) | 昆山维信诺显示CO. , LTD. 昆山GO-维信诺光电科技有限公司. | | |
| [标]发明人 | PENG CHAOCHI QIU YONG ZHANG SHENFU | | |
| 发明人 | PENG, CHAOCHI QIU, YONG ZHANG, SHENFU | | |
| IPC分类号 | H01L27/32 H01L51/56 | | |
| CPC分类号 | H01L27/3216 H01L27/3218 H01L27/3211 | | |
| 优先权 | 201310026524.3 2013-01-24 CN | | |
| 其他公开文献 | EP2950348A1 EP2950348A4 | | |
| 外部链接 | Espacenet | | |

摘要(译)

公开了一种用于OLED显示器的像素结构。像素结构包括多行像素单元组，每个像素单元组包括依次重复排列的多个像素单元，每个像素单元包括第一子像素，第二子像素和第三子像素，其中同一子像素相邻两行中的像素单元的像素在水平方向上错位排列。当制造相应的金属掩模时，像素结构可以加宽子像素的相应开口之间的距离，以增强金属掩模的强度，从而可以在考虑工艺条件的情况下生产出尺寸较小的像素单元，从而提高OLED显示器的分辨率。




Fig. 1