



(11)

EP 3 594 931 A1

(12)

EUROPEAN PATENT APPLICATION
published in accordance with Art. 153(4) EPC

(43) Date of publication:
15.01.2020 Bulletin 2020/03

(51) Int Cl.:
G09G 3/32 ^(2016.01)

(21) Application number: **18764209.5**

(86) International application number:
PCT/CN2018/078170

(22) Date of filing: **06.03.2018**

(87) International publication number:
WO 2018/161902 (13.09.2018 Gazette 2018/37)

(84) Designated Contracting States:
AL AT BE BG CH CY CZ DE DK EE ES FI FR GB GR HR HU IE IS IT LI LT LU LV MC MK MT NL NO PL PT RO RS SE SI SK SM TR
Designated Extension States:
BA ME
Designated Validation States:
KH MA MD TN

(72) Inventors:
• **ZHANG, Shuhuan**
Jiangsu 215300 (CN)
• **JIANG, Haibin**
Jiangsu 215300 (CN)
• **CHEN, Xinquan**
Jiangsu 215300 (CN)

(30) Priority: **10.03.2017 CN 201710142298**

(74) Representative: **Kraus & Weisert**
Patentanwälte PartGmbB
Thomas-Wimmer-Ring 15
80539 München (DE)

(71) Applicant: **Kunshan Go-Visionox**
Opto-Electronics Co., Ltd.
Kunshan City, Jiangsu 215300 (CN)

(54) **METHOD FOR DRIVING DISPLAY DEVICE**

(57) The present application discloses a method for driving a display apparatus. The display apparatus includes an OLED and a driver transistor. An anode of the OLED is connected to a source of the driver transistor, a drain of the driver transistor is connected to a positive power supply, a cathode of the OLED is connected to a negative power supply, and a voltage difference between the positive power supply and the negative power supply is in a range from 7.1 V to 9.6 V. In this way, a high order

grayscale unsmooth transition phenomenon of a module caused by a relatively low division voltage of the driver transistor because of a relatively high division voltage of the OLED can be effectively eliminated, and the driver transistor can keep working in a saturated region, thereby avoiding occurrence of the high order grayscale unsmooth transition phenomenon and improving a production yield.




Fig. 3

Description

TECHNICAL FIELD

[0001] The present application relates to the field of display, particularly to a method for driving a display apparatus.

BACKGROUND

[0002] A flat panel display apparatus has many advantages such as a slim body, power saving, and no radiation, and therefore, is widely applied. Existing flat panel display apparatuses mainly include Liquid Crystal Displays (LCDs) and Organic Light-Emitting Diode (OLED) display apparatuses.

[0003] The OLED display apparatus is a main force in next-generation flat panel display apparatuses. Compared with other flat panel display apparatuses represented by the LCD, the OLED display apparatus has many advantages such as low costs, self-illumination, a wide angle of view, a low voltage, a low power consumption, a all-solid-state display, anti-vibration, a high reliability, and a quick response.

[0004] The OLED display apparatus may include a plurality of pixel cells. Each pixel cell includes an OLED as a light-emitting element of the pixel cell. And the OLED display apparatus may further include a driver chip. The driver chip is configured to provide a data signal V_{data} (that is, a Gamma voltage displayed on different gray-scales, usually including 0 to 255 scales) to each pixel cell. Brightness of the OLED is controlled by a magnitude of a current flowing through the OLED, and a high order grayscale unsmooth transition phenomenon exists in existing OLED display apparatuses, and severely affects a normal use of existing OLED display apparatuses.

SUMMARY OF THE INVENTION

[0005] An objective of the present application is to provide a method for driving a display apparatus, to alleviate a high order grayscale unsmooth transition phenomenon.

[0006] To resolve the foregoing technical problem, the present application provides a method for driving a display apparatus, wherein the display apparatus includes an OLED and a driver transistor, an anode of the OLED connected to a source of the driver transistor, and the method including:

connecting a drain of the driver transistor to a positive power supply;
connecting a cathode of the OLED to a negative power supply; and
configuring a voltage difference between the positive power supply and the negative power supply in a range from 7.1 V to 9.6 V.

[0007] Optionally, for the method for driving a display apparatus, a voltage provided by the positive power supply has a fixed value, and a voltage provided by the negative power supply is an adjustable voltage.

[0008] Optionally, for the method for driving a display apparatus, the voltage provided by the positive power supply ranges from 4 V to 5 V.

[0009] Optionally, for the method for driving a display apparatus, the voltage provided by the negative power supply ranges from -5 V to -2.5 V.

[0010] Optionally, for the method for driving a display apparatus, the voltage difference between the positive power supply and the negative power supply is configured in a range from 8.1 V to 9.1 V.

[0011] Optionally, for the method for driving a display apparatus, the voltage provided by the negative power supply ranges from -4.5 V to -3.5 V.

[0012] Optionally, for the method for driving a display apparatus, a voltage provided by the positive power supply is an adjustable voltage, and a voltage provided by the negative power supply has a fixed value.

[0013] Optionally, for the method for driving a display apparatus, a drain-source voltage of the driver transistor is as follows:

V_{ds} =a voltage of the positive power supply-a voltage of the negative power supply- V_{oled} , where V_{ds} is the drain-source voltage of the driver transistor, and V_{oled} is a voltage of two terminals of the OLED.

[0014] Optionally, for the method for driving a display apparatus, the display apparatus further includes a capacitor, and a gate of the driver transistor is connected to the positive power supply through the capacitor.

[0015] Optionally, for the method for driving a display apparatus, the display apparatus has a 2T1C structure or a 4T1C structure or a 6T1C structure or a 7T1C structure.

[0016] In the method for driving a display apparatus provided by the present application, the display apparatus includes an OLED and a driver transistor. An anode of the OLED is connected to a source of the driver transistor. A drain of the driver transistor is connected to a positive power supply. A cathode of the OLED is connected to a negative power supply, and a voltage difference between the positive power supply and the negative power supply is configured in a range from 7.1 V to 9.6 V. In this way, a high order grayscale unsmooth transition phenomenon of a module caused by a relatively low division voltage of the driver transistor because of a relatively high division voltage of the OLED can be effectively eliminated, and the driver transistor can keep working in a saturated region, thereby avoiding occurrence of the high order grayscale unsmooth transition phenomenon and improving a production yield.

BRIEF DESCRIPTION OF THE DRAWINGS

[0017]

FIG. 1 is a schematic diagram of an output characteristic curve of a driver transistor of a display apparatus;

FIG. 2 is a schematic structural diagram of a display apparatus according to the present application; and
FIG. 3 is a flowchart of a method for driving a display apparatus according to the present application.

DETAILED DESCRIPTION

[0018] The method for driving a display apparatus of the present application is described below in more details with reference to the schematic diagrams, where preferred embodiments of the present application are presented. It should be understood that a person skilled in the art can modify the present application described herein while still achieving advantageous effects of the present application. Therefore, the following descriptions should be understood as being well-known to a person skilled in the art, and are not intended to limit the present application.

[0019] The present application is described in more details in the following paragraphs by using examples with reference to the accompanying drawings. The advantages and features of the present application are more comprehensible according to the following descriptions and claims. It should be noted that the accompanying drawings are all in simplified forms, with the only intention to facilitate convenience and clarity in explaining the objectives of the embodiments of the present application.

[0020] The high order grayscale unsmooth transition phenomenon has been studied by the inventor, and according to a great amount of experimental analysis, the inventor found that under same brightness (that is, a magnitude of a current flowing through the OLED is unchanged) and on a high order grayscale, a relatively high division voltage of the OLED leads to a relatively low division voltage of the drain-source voltage of the driver transistor connected to the OLED in the circuit. Hence, in the output characteristic curve (a horizontal coordinate represents a drain-source voltage, and a vertical coordinate presents a drain current) of the driver transistor as shown in FIG. 1, a magnitude of a drain-source voltage of the driver transistor corresponding to a gray scale V255 is moved from a solid line arrow A to a dashed line arrow B, that is, the driver transistor switches from the saturated region 20 to a variable resistance region 10 (a left half part of a curve L1 corresponds to the variable resistance region 10, a right half part corresponds to the saturated region 20, and the output characteristic curve further includes a breakdown region, which is not shown in the figure). Consequently, a current flowing through the driver transistor and the OLED is unstable, and forms a high

order grayscale unsmooth transition phenomenon.

[0021] Based on this, the present application provides a method for driving a display apparatus, where the display apparatus includes an OLED and a driver transistor, and an anode of the OLED is connected to a source of the driver transistor. In this method, a drain of the driver transistor is connected to a positive power supply, a cathode of the OLED is connected to a negative power supply, and a voltage difference between the positive power supply and the negative power supply is configured in a range from 7.1 V to 9.6 V.

[0022] Preferred embodiments of the method for driving a display apparatus are exemplified below, to clearly describe the content of the present application. It should be clarified that the content of the present application is not limited to the following embodiments. Other improvements made by a person of ordinary skill in the art through common technical methods also fall within the scope of the content of the present application.

[0023] The method for driving a display apparatus of the present application is described below in great detail with reference to FIG. 2 and FIG. 3.

[0024] In the method for driving a display apparatus of the present application, the display apparatus includes an OLED D1 (Organic Light-Emitting Diode) and a driver transistor DTFT (Driver Thin Film Transistor), where an anode of the OLED is connected to a source of the driver transistor DTFT. As shown in FIG. 3, the method includes:

step S11: connecting a drain of the driver transistor DTFT to a positive power supply V_{dd}.

step S12: connecting a cathode of the OLED to a negative power supply V_{ss}.

step S13: configuring a voltage difference between the positive power supply V_{dd} and the negative power supply V_{ss} in a range from 7.1 V to 9.6 V.

step S11 and step S12 can be performed in another sequence, for example, be simultaneously performed.

[0025] In an embodiment, a voltage provided by the positive power supply V_{dd} has a fixed value, and a voltage provided by the negative power supply V_{ss} is adjustable. The voltage provided by the positive power supply V_{dd} can be selected from a range of 4 V to 5 V. For example, the voltage provided by the positive power supply V_{dd} is 4.6 V, and the voltage provided by the negative power supply V_{ss} ranges from -5 V to -2.5 V. Considering that external environmental factors (such as a temperature and material) also affect a working voltage of the driver transistor DTFT, the voltage of the negative power supply V_{ss} may have a specific variation range so as to ensure that the driver transistor DTFT is in the saturated region. Further, the voltage of negative power supply V_{ss} also relates to power consumption of the display apparatus. This embodiment may further define that a voltage difference between the positive power supply V_{dd} and the

negative power supply V_{ss} ranges from 8.1 V to 9.1 V. Similarly, in an example where the voltage provided by the positive power supply V_{dd} is 4.6 V, the selectable voltage of the negative power supply V_{ss} ranges from -4.5 V to -3.5 V. Such a voltage range is obtained by taking the foregoing factors into consideration. The voltage range not only can ensure that the driver transistor DTFT is in the saturated region so as to improve a high order grayscale color accuracy, but also can make power consumption of the display apparatus fall within an acceptable range, and can further enable the display apparatus to endure an impact of most environments (for example, cloudy and rainy weather).

[0026] It can be understood that in the method for driving a display apparatus of the present application, the voltage provided by the positive power supply V_{dd} may alternatively be adjustable, and the voltage provided by the negative power supply V_{ss} may have a fixed value, provided that the voltage difference between the positive power supply and the negative power supply is configured in a range from 7.1 V to 9.6 V to ensure that the driver transistor DTFT is in the saturated region so as to improve a high order grayscale color accuracy, and further to avoid a high order grayscale unsmooth transition phenomenon of a module. FIG. 2 provides a schematic diagram of a display apparatus of the present application. As shown in FIG. 2, a drain-source voltage V_{ds} of the driver transistor DTFT=a positive power supply voltage V_{dd} - a negative power supply voltage V_{ss} - V_{oled} , where the V_{oled} is a voltage between the two terminals of the OLED. It is certain that when a device is normal, the V_{oled} is unchanged, so that in the present application, configuring a voltage difference between the positive power supply V_{dd} and the negative power supply V_{ss} (that is, the positive power supply voltage V_{dd} -the negative power supply voltage V_{ss}) in a range from 7.1 V to 9.6 V, for example, 8.0 V, 8.2 V, 8.3 V, 8.5 V, 8.7 V, and 8.9 V or the like, can increase the drain-source voltage V_{ds} of the driver transistor DTFT. With combined reference to FIG. 1, the increased V_{ds} can make it easier for the driver transistor DTFT to work in the saturated region, thereby avoiding a fluctuation of a current flowing through the driver transistor and the OLED caused by a fluctuation of resistance of the driver transistor so that occurrence of a high order grayscale unsmooth transition phenomenon is avoided.

[0027] In positive power supply voltages V_{dd} and negative power supply voltages V_{ss} generated by most power supply ICs, the positive power supply voltage V_{dd} is fixed. Hence, in the foregoing text, the voltage of the negative power supply V_{ss} is limited to a particular range to achieve an objective of alleviating a high order grayscale unsmooth transition phenomenon. It can be understood that, in a case in which the positive power supply voltage V_{dd} is adjustable, the method of the present application can still be used. For example, the negative power supply voltage V_{ss} may be fixed, and a range of the positive power supply voltage V_{dd} may be limited, provided that

a voltage difference between the positive power supply voltage V_{dd} and the negative power supply voltage V_{ss} is configured to range from 7.1 V to 9.6 V. In addition, alternatively, both of the positive power supply voltage V_{dd} and the negative power supply voltage V_{ss} may be adjustable, provided that the voltage difference between the positive power supply voltage V_{dd} and the negative power supply voltage V_{ss} is configured to range from 7.1 V to 9.6 V. Based on the disclosure of the present application, a person skilled in the art knows how to design.

[0028] With continued reference to FIG. 2, the display apparatus further includes a capacitor C1, where a gate of the driver transistor DTFT is connected to the positive power supply V_{dd} through the capacitor C1.

[0029] As shown in FIG. 2, the method of the present application is applied by using a 7T1C structure (7 thin film transistors and 1 capacitor). The 7T1C structure may be as follows.

[0030] The display apparatus further includes: a first switch transistor M1 (as shown in FIG. 2, each of the transistors in this embodiment is a PMOS). A source of the first switch transistor M1 is connected to a data signal power supply V_{data} . The data signal power supply V_{data} provides a Gamma voltage for different gray scales, and a drain of the first switch transistor M1 is connected to the drain of the driver transistor DTFT. The display apparatus further includes a second switch transistor M2. A source of the second switch transistor M2 is connected to the drain of the driver transistor DTFT, and a drain of the second switch transistor M2 is connected to the positive power supply V_{dd} . The display apparatus further includes a third switch transistor M3. A drain of the third switch transistor M3 is connected to the gate of the driver transistor DTFT, a source of the third switch transistor M3 is connected to a reference power supply V_{ref} , and a gate of the third switch transistor M3 is connected to a first scan power supply Scan1. The display apparatus further includes a fourth switch transistor M4 and a fifth switch transistor M5. A source of the fourth switch transistor M4 is connected to the gate of the driver transistor DTFT, a drain of the fourth switch transistor M4 is connected a source of the fifth switch transistor M5, and a gate of the fourth switch transistor M4 is connected to a second scan power supply Scan2. A drain of the fifth switch transistor M5 is connected to the anode of the OLED, a source of the fifth switch transistor M5 is further connected to the source of the driver transistor DTFT, and a gate of the fifth switch transistor M5 is connected to an emission power supply EM. A gate of the second switch transistor M2 is connected to the emission power supply EM, and a gate of the first switch transistor M1 is connected to the second scan power supply Scan2. The display apparatus further includes a sixth switch transistor M6, a source of the sixth switch transistor M6 is connected to the reference power supply V_{ref} , a drain of the sixth switch transistor is connected to the anode of the OLED, and a gate of the sixth switch transistor M6 is connected to the first scan power supply Scan1.

[0031] In conclusion, in the method for driving a display apparatus provided by the present application, the display apparatus includes an OLED and a driver transistor. An anode of the OLED is connected to a source of the driver transistor, a drain of the driver transistor is connected to a positive power supply, and a cathode of the OLED is connected to a negative power supply so that a voltage difference between the positive power supply and the negative power supply is configured to range from 7.1 V to 9.6 V. In this way, a high order grayscale unsmooth transition phenomenon of a module caused by a relatively low division voltage of the driver transistor because of a relatively high division voltage of the OLED can be effectively eliminated, and the driver transistor can keep working in a saturated region, thereby avoiding the occurrence of the high order grayscale unsmooth transition phenomenon and improving a production yield.

[0032] It should be noted that although the foregoing text is described by using an example of a 7T1C structure (7 thin film transistors and 1 capacitor), in fact, connection relationships among the first to fifth switch transistors may have some changes. In addition, the driving method is also applicable to driving a display apparatus having another quantity of thin film transistors and/or capacitors, for example, may be applied to driving a display apparatus of a structure such as 2T1C, 4T1C, or 6T1C and the like. However, specific structures such as 2T1C, 4T1C, and 6T1C are well-known to a person skilled in the art. On the basis of the 7T1C structure in the foregoing text, a person skilled in the art can know a structure to which the driving method of the present application is applicable, which are not described herein by using examples one by one.

[0033] Apparently, a person skilled in the art can make various modifications and variations on the present application without departing from the spirit and scope of the present application. Hence, if the modifications and variations on the present application belong to the present application and the scope of its equivalent technology, the present application is also intended to cover the modifications and variations.

Claims

1. A method for driving a display apparatus, wherein the display apparatus comprises an OLED and a driver transistor, an anode of the OLED connected to a source of the driver transistor, the method comprising:

connecting a drain of the driver transistor to a positive power supply;
connecting a cathode of the OLED to a negative power supply; and
conducting a voltage difference between the positive power supply and the negative power supply in a range from 7.1 V to 9.6 V.

2. The method for driving a display apparatus according to claim 1, wherein a voltage provided by the positive power supply has a fixed value, and a voltage provided by the negative power supply is an adjustable voltage.
3. The method for driving a display apparatus according to claim 2, wherein the voltage provided by the positive power supply ranges from 4 V to 5 V.
4. The method for driving a display apparatus according to claim 2, wherein the voltage provided by the negative power supply ranges from -5 V to -2.5 V.
5. The method for driving a display apparatus according to claim 2, wherein the voltage difference between the positive power supply and the negative power supply is configured in a range from 8.1 V to 9.1 V.
6. The method for driving a display apparatus according to claim 5, wherein the voltage provided by the negative power supply ranges from -4.5 V to -3.5 V.
7. The method for driving a display apparatus according to claim 1, wherein a voltage provided by the positive power supply is an adjustable voltage, and a voltage provided by the negative power supply has a fixed value.
8. The method for driving a display apparatus according to claim 1, wherein a drain-source voltage of the driver transistor is as follows:

V_{ds} =a voltage of the positive power supply-a voltage of the negative power supply- V_{oled} ,
 V_{ds} is the drain-source voltage of the driver transistor, and V_{oled} is a voltage between two terminals of the OLED.

9. The method for driving a display apparatus according to claim 1, wherein the display apparatus further comprises a capacitor, a gate of the driver transistor connected to the positive power supply through the capacitor.
10. The method for driving a display apparatus according to claim 9, wherein the display apparatus has a 2T1C structure or a 4T1C structure or a 6T1C structure or a 7T1C structure.




Fig. 1




Fig.2




Fig. 3

INTERNATIONAL SEARCH REPORT

International application No.
PCT/CN2018/078170

A. CLASSIFICATION OF SUBJECT MATTER		
G09G 3/32 (2016.01) i		
According to International Patent Classification (IPC) or to both national classification and IPC		
B. FIELDS SEARCHED		
Minimum documentation searched (classification system followed by classification symbols)		
G09G; G06F		
Documentation searched other than minimum documentation to the extent that such documents are included in the fields searched		
Electronic data base consulted during the international search (name of data base and, where practicable, search terms used)		
CNTXT, CNABS: 发光二极管, 显示, 驱动, 晶体管, 开关, 漏, 源, 正, 电压, 电源, 负, 阴极, 阳极; VEN, USTXT, WOTXT, EPTXT: OLED, switch, drive, TFT, drain, source, positive, negative, voltage, transistor		
C. DOCUMENTS CONSIDERED TO BE RELEVANT		
Category*	Citation of document, with indication, where appropriate, of the relevant passages	Relevant to claim No.
X	CN 103646629 A (TRULY SEMICONDUCTORS CO., LTD.) 19 March 2014 (19.03.2014), description, paragraphs [0034]-[0053], and figures 3, 6 and 7	1-10
A	CN 105405403 A (KUNSHAN GOVISIONOX OPTOELECTRONICS CO., LTD.) 16 March 2016 (16.03.2016), entire document	1-10
A	CN 102640091 A (GLOBAL OLED TECHNOLOGY LLC.) 15 August 2012 (15.08.2012), entire document	1-10
A	CN 104751786 A (LG DISPLAY CO., LTD.) 01 July 2015 (01.07.2015), entire document	1-10
A	US 8248329 B2 (YAMAMOTO, TETSURO et al.) 21 August 2012 (21.08.2012), entire document	1-10
☐ Further documents are listed in the continuation of Box C. ☒ See patent family annex.		
* Special categories of cited documents:	"T" later document published after the international filing date or priority date and not in conflict with the application but cited to understand the principle or theory underlying the invention "X" document of particular relevance; the claimed invention cannot be considered novel or cannot be considered to involve an inventive step when the document is taken alone "Y" document of particular relevance; the claimed invention cannot be considered to involve an inventive step when the document is combined with one or more other such documents, such combination being obvious to a person skilled in the art "&" document member of the same patent family	
"A" document defining the general state of the art which is not considered to be of particular relevance		
"E" earlier application or patent but published on or after the international filing date		
"L" document which may throw doubts on priority claim(s) or which is cited to establish the publication date of another citation or other special reason (as specified)		
"O" document referring to an oral disclosure, use, exhibition or other means		
"P" document published prior to the international filing date but later than the priority date claimed		
Date of the actual completion of the international search	Date of mailing of the international search report	
24 April 2018	15 May 2018	
Name and mailing address of the ISA State Intellectual Property Office of the P. R. China No. 6, Xitucheng Road, Jimenqiao Haidian District, Beijing 100088, China Facsimile No. (86-10) 62019451	Authorized officer LIU, Yan Telephone No. (86-20) 28950530	

Form PCT/ISA/210 (second sheet) (July 2009)

INTERNATIONAL SEARCH REPORT
 Information on patent family members

 International application No.
 PCT/CN2018/078170

Patent Documents referred in the Report	Publication Date	Patent Family	Publication Date
CN 103646629 A	19 March 2014	CN 103646629 B	08 June 2016
CN 105405403 A	16 March 2016	None	
CN 102640091 A	15 August 2012	KR 20120114245 A	16 October 2012
		JP 2011118079 A	16 June 2011
		EP 2507688 A1	10 October 2012
		EP 2507688 A4	24 April 2013
		JP 5491835 B2	14 May 2014
		US 2013021228 A1	24 January 2013
		WO 2011068773 A1	09 June 2011
		TW I520119 B	01 February 2016
		TW 201128611 A	16 August 2011
CN 104751786 A	01 July 2015	KR 20150079315 A	08 July 2015
		EP 2889867 B1	08 November 2017
		US 9659528 B2	23 May 2017
		EP 2889867 A1	01 July 2015
		CN 104751786 B	12 December 2017
		US 2015187274 A1	02 July 2015
US 8248329 B2	21 August 2012	JP 2009133914 A	18 June 2009
		US 2009135111 A1	28 May 2009

专利名称(译)	控制显示装置的方法		
公开(公告)号	EP3594931A4	公开(公告)日	2020-01-22
申请号	EP2018764209	申请日	2018-03-06
[标]申请(专利权)人(译)	昆山国显光电有限公司		
申请(专利权)人(译)	昆山GO-维信诺光电科技有限公司.		
当前申请(专利权)人(译)	昆山GO-维信诺光电科技有限公司.		
[标]发明人	ZHANG SHUHUAN JIANG HAIBIN CHEN XINQUAN		
发明人	ZHANG, SHUHUAN JIANG, HAIBIN CHEN, XINQUAN		
IPC分类号	G09G3/32		
CPC分类号	G09G3/3208 G09G3/3233 G09G2330/00 G09G3/32 G09G3/2007 G09G3/3258 G09G2320/0233 G09G2330/02		
优先权	201710142298.3 2017-03-10 CN		
其他公开文献	EP3594931A1		
外部链接	Espacenet		

摘要(译)

本申请公开了一种用于驱动显示装置的方法。该显示装置包括OLED和驱动器晶体管。OLED的阳极连接到驱动晶体管的源极，驱动晶体管的漏极连接到正电源，OLED的阴极连接到负电源，并且正电源之间的电压差 电源和负电源的范围为7.1 V至9.6V。这样，由于驱动晶体管的相对较低的分压，驱动晶体管的相对较低的分压导致了模块的高阶灰度不平滑过渡现象。可以有效地消除OLED，并且驱动晶体管可以在饱和区域保持工作，从而避免了高阶灰度不平滑过渡现象的发生，提高了生产良率。