



US008268455B2

(12) **United States Patent**
Kamatani et al.

(10) **Patent No.:** **US 8,268,455 B2**
 (45) **Date of Patent:** **Sep. 18, 2012**

(54) **ORGANIC COMPOUND FOR
 LIGHT-EMITTING DEVICE,
 LIGHT-EMITTING DEVICE, AND IMAGE
 DISPLAY APPARATUS**

(75) Inventors: **Jun Kamatani**, Tokyo (JP); **Ryota
 Ooishi**, Yokohama (JP); **Shinjiro
 Okada**, Kamakura (JP); **Takao
 Takiguchi**, Tokyo (JP)

(73) Assignee: **Canon Kabushiki Kaisha**, Tokyo (JP)

(*) Notice: Subject to any disclaimer, the term of this
 patent is extended or adjusted under 35
 U.S.C. 154(b) by 1178 days.

(21) Appl. No.: **11/686,030**

(22) Filed: **Mar. 14, 2007**

(65) **Prior Publication Data**

US 2007/0231600 A1 Oct. 4, 2007

(30) **Foreign Application Priority Data**

Mar. 31, 2006 (JP) 2006-099893

(51) **Int. Cl.**
H01L 51/54 (2006.01)
C09K 11/06 (2006.01)

(52) **U.S. Cl.** **428/690**; 428/917; 313/504; 313/506;
 257/40; 546/10; 548/103

(58) **Field of Classification Search** 428/690,
 428/917, 411.1, 336; 313/502-509; 257/40,
 257/88, 104, E51; 548/101, 103
 See application file for complete search history.

(56) **References Cited**

U.S. PATENT DOCUMENTS

7,589,203 B2 9/2009 Stossel et al.
 2002/0064681 A1 5/2002 Takiguchi et al.
 2005/0253135 A1* 11/2005 Stossel et al. 257/40
 2005/0266153 A1* 12/2005 Suzuri et al. 427/66

2006/0280968 A1 12/2006 Kamatani et al.
 2007/0228940 A1 10/2007 Hashimoto et al.
 2007/0232803 A1 10/2007 Kamatani et al.

FOREIGN PATENT DOCUMENTS

JP 2003-146996 A 5/2003
 JP 2006-507279 A 3/2006

OTHER PUBLICATIONS

Vincett, et al.; "Electrical Conduction and Low Voltage Blue
 Electroluminescence in Vacuum-Deposited Organic Films"; Thin
 Solid Films; vol. 94, p. 171-183 (1982).
 Burroughes, et al.; "Light-Emitting Diodes Based on Conjugated
 Polymers", Nature, vol. 347, p. 539-541 (1990).
 O'Brien, et al.; Improved Energy Transfer in Electrophosphorescent
 Devices, Applied Physics Letters, vol. 74, No. 3, pp. 442-444 (1999).
 Baldo, et al.; "Very High-Efficiency Green Organic Light-Emitting
 Devices Based on Electrophosphorescence", Applied Physics Let-
 ters, vol. 75, No. 1, pp. 4-6 (1999).
 Chen, et al., "Recent Developments in Molecular Organic
 Electroluminescent Materials", Macromol. Symp., vol. 125, pp. 1-48
 (1997).
 Xie, et al.; "Reduction of Self-Quenching . . . Molecules"; *Adv.
 Mater.* vol. 13, No. 16, pp. 1245-1248 (2001).

* cited by examiner


Primary Examiner — Jennifer Chriss


Assistant Examiner — J. L. Yang

(74) *Attorney, Agent, or Firm* — Fitzpatrick, Cella, Harper &
 Scinto

(57) **ABSTRACT**

A light-emitting device is provided which uses an organic
 compound to emit light with high luminance and extremely
 high efficiency. The organic compound is composed of a
 metal complex having monovalent bidentate ligands. The
 light-emitting device includes a pair of electrodes which are
 an anode and a cathode, and plural organic compound layers
 interposed between the electrodes, in which at least one layer
 of the organic compound layers contains a metal complex
 represented by the following structural formula. The light-
 emitting device is an organic electroluminescent device using
 the light-emitting device in which the layer including the
 organic compound is a light-emitting layer.





3 Claims, 4 Drawing Sheets



FIG. 1*FIG. 2*



FIG. 3**FIG. 4**




FIG. 5*FIG. 6*

FIG. 7

1

ORGANIC COMPOUND FOR LIGHT-EMITTING DEVICE, LIGHT-EMITTING DEVICE, AND IMAGE DISPLAY APPARATUS

BACKGROUND OF THE INVENTION

1. Field of the Invention


The present invention relates to a novel organic compound for a light-emitting device, a light-emitting device which is used for a plane light source or a flat panel display, and to an image display apparatus.

2. Description of the Related Art

In an old example of an organic light-emitting device, a voltage has been applied to an anthracene evaporated film to emit light (see, Thin Solid Films, 94 (1982), 171). In recent years, applied research has been vigorously conducted on a transformation of an organic light-emitting device into a light-emitting device having high-speed response and high efficiency, including developments of materials for the device. This is because the organic light-emitting device has such advantages that its area can be increased more easily than an inorganic light-emitting device, desired colors can be developed through the developments of various new materials, and it can be operated at a low voltage.


For example, as discussed in Macromol. Symp. 125, 1 to 48 (1997), an organic EL device is generally composed of a transparent substrate, a pair of upper and lower electrodes formed on the transparent substrate, and an organic layer interposed between therebetween including a light-emitting layer.

Recently, investigation has been made into a device utilizing not only conventional light emission utilizing fluorescence ascribable to a transition from an excited singlet state to a ground state but also phosphorescence via a triplet exciton as typified by technologies described in each of "Improved energy transfer in electrophosphorescent device", D. F. O'Brien et al., Applied Physics Letters, Vol 74, No 3, p 422 (1999) and "Very high-efficiency green organic light-emitting devices based on electrophosphorescence", M. A. Baldo et al., Applied Physics Letters, Vol 75, No 1, p 4 (1999). In each of those documents, an organic layer having a four-layer structure has been mainly used. The organic layer includes, from an anode side, a hole-transporting layer, a light-emitting layer, an exciton diffusion-prevention layer, and an electron-transporting layer. Materials used are a carrier-transporting material and a phosphorescent material Ir(ppy)₃ shown below.




2


-continued




a-NPD



CBP



BCP



A variety of light ranging from ultraviolet light to infrared light can be emitted by changing the types of fluorescent organic compounds. In recent years, active research has been conducted on various compounds.

In addition to an organic light-emitting device using any one of the low-molecular-weight materials as described above, an organic light-emitting device using a conjugated polymer has been reported by the group at the University of Cambridge (see, Nature, 347, 539 (1990)). In this report, there has been observed light emission from a single layer by forming polyphenylenevinylene (PPV) into a film by means of a coating system.

As described above, an organic light-emitting device has recently showed significant progress. The organic light-emitting device can be transformed into a high-speed response, thin, and lightweight light-emitting device which can be driven at a low applied voltage and has high luminance and a variety of emission wavelengths, thus suggesting possibilities of a wide variety of applications.

However, under the present conditions, a light output higher in luminance and higher conversion efficiency are being sought. In addition, there still remain a large number of problems in terms of durability such as changes over time

during long-term use and deterioration due to an atmospheric gases containing oxygen or moisture.


SUMMARY OF THE INVENTION

The present invention has been made in view of the above-mentioned background art. An object of the present invention is to provide a highly durable light-emitting device which emits light with high efficiency and high luminance for a long period of time, and an organic compound to be used for the light-emitting device. Further, the present invention is aimed at providing a light-emitting device which can easily be produced at a relatively low cost, and an image display apparatus using the light-emitting device of the present invention.

The present invention relates to a metal complex having monovalent bidentate ligands, in which a metal atom is bound with each of moieties in aromatic ring structures of the ligands. The aromatic ring structures each of which is bound with the metal are covalently bound with each other, and each of the aromatic ring structures shares at least 2 carbon atoms with an alicyclic structure in the metal complex. A metal complex having those structures can provide a light-emitting device having high performance in terms of efficiency and durability which have not been achieved in the conventional organic EL device.

According to the present invention, there is provided an organic compound for a light-emitting device (hereinafter, sometimes abbreviated as "organic compound") as described below.

That is, according to one aspect of the present invention, there is provided an organic compound for a light-emitting device, including a metal complex having monovalent ligands each having a partial structure which is represented by the following general formula (1):



where A and B each independently represent an aromatic ring structure which may contain a hetero atom(s) which is(are) bound with a metal atom M, and are covalently bound with each other; A' represents a structure including an alicyclic structure whose alicyclic moiety shares at least 2 carbon-carbon bonds with the aromatic ring A, and B' represents a structure including an alicyclic structure whose alicyclic moiety shares at least 2 carbon-carbon bonds with the aromatic ring B, provided that a carbon atom(s) of at least one of the alicyclic structures A' and B' may be replaced by a hetero atom(s); the alicyclic structures may have substituents; when the alicyclic structures have no hetero atoms, the substituents are selected from the group consisting of a hydrogen atom, a halogen atom, a linear or branched alkyl group having 1 to 20 carbon atoms (in which one or unadjacent two or more methylene groups in the alkyl group may be replaced by at least one group selected from the group consisting of —O—, —S—, —CO—, —CO—O—, —O—CO—, —CH=CH— and —C≡C—, and one or two or more methylene groups in the alkyl group may be replaced by at least one of an arylene group which may be substituted and a divalent heterocyclic group which may be substituted, and one or two or more hydrogen atoms in the alkyl group may be replaced by a




fluorine atom), an amino group which may be substituted, a silyl group which may be substituted, an aryl group which may be substituted, and a heterocyclic group which may be substituted; when the alicyclic structures have hetero atoms, the substituents are selected from the group consisting of a hydrogen atom, a linear or branched alkyl group having 1 to 20 carbon atoms (in which one or unadjacent two or more methylene groups in the alkyl group may be replaced by at least one group selected from the group consisting of —O—, —S—, —CO—, —CO—O—, —O—CO—, —CH=CH— and —C≡C—, and one or two or more methylene groups in the alkyl group may be replaced by at least one of an arylene group which may be substituted and a divalent heterocyclic group which may be substituted, and one or two or more hydrogen atoms in the alkyl group may be replaced by a fluorine atom), an amino group which may be substituted, a silyl group which may be substituted, an aryl group which may be substituted, and a heterocyclic group which may be substituted; and M represents a metal atom selected from the group consisting of Ir, Rh, Cu, Zn, Re, Os, and Eu.

It is preferable that the metal complex has in its molecule a central metal of Ir and a skeleton represented by the general formula (1) in the one aspect of the present invention.

In addition, according to another aspect of the present invention, an organic compound for a light-emitting device is provided including a metal complex represented by the general formula (2):




where L_m and L'_n represent bidentate ligands different from each other, m represents an integer of 1 to 3 and n represents an integer of 0 to 2, provided that $m+n$ is 3; and a partial structure ML_m is represented by the general formula (3), and a partial structure ML'_n is represented by any one of the general formulae (4), (5), and (6):



5

-continued



where N represents a nitrogen atom and C represents a carbon atom; A and B each independently represent an aromatic ring structure which may contain a hetero atom(s) which is(are) bound with a metal atom M, and are covalently bound with each other; A' represents a structure containing an alicyclic structure whose alicyclic moiety shares at least 2 carbon-carbon bonds with the aromatic ring A, and B' represents a structure containing an alicyclic structure whose alicyclic moiety shares at least 2 carbon-carbon bonds with the aromatic ring B, provided that a carbon atom(s) of at least one of the alicyclic structures A' and B' may be replaced by a hetero atom(s); the alicyclic structures may have substituents; when the alicyclic structures have no hetero atoms, the substituents are selected from the group consisting of a hydrogen atom, a halogen atom, a linear or branched alkyl group having 1 to 20 carbon atoms (in which one or unadjacent two or more methylene groups in the alkyl group may be replaced by at least one group selected from the group consisting of —O—, —S—, —CO—, —CO—O—, —O—CO—, —CH=CH— and —C≡C—, and one or two or more methylene groups in the alkyl may be replaced by at least one of an arylene group which may be substituted and a divalent heterocyclic group which may be substituted, and one or two or more hydrogen atoms in the alkyl group may be replaced by a fluorine atom), an amino group which may be substituted, a silyl group which may be substituted, an aryl group which may be substituted, and a heterocyclic group which may be substituted; when the alicyclic structures have hetero atoms, the substituents are selected from the group consisting of a hydrogen atom, a linear or branched alkyl group having 1 to 20 carbon atoms (in which one or unadjacent two or more methylene groups in the alkyl group may be replaced by at least one group selected from the group consisting of —O—, —S—, —CO—, —CO—O—, —O—CO—, —CH=CH— and —C≡C—, and one or two or more methylene groups in the alkyl group may be replaced by at least one of an arylene group which may be substituted and a divalent heterocyclic group which may be substituted, and one or two or more hydrogen atoms in the alkyl group may be replaced by a fluorine atom), an amino group which may be substituted, a silyl group which may be substituted, an aryl group which may be substituted, a pyrenyl group, a phenanthrenyl group, a chrysenyl group, a fluoranthrenyl group, a triphenylenyl group, and a heterocyclic group which may be substituted; A'' represents a cyclic group which may be substituted and is bound with a metal atom Ir via a carbon atom, and B'' represents a cyclic group which may be substituted and is bound with a metal atom M via a nitrogen atom, where A'' and B'' are covalently bound with each other; E and G are each independently a linear or branched alkyl group having 1 to 20 carbon atoms in which one or two or more hydrogen atoms in the alkyl group may be replaced by a fluorine atom, or an aromatic ring group which may have at least one substituent selected from the group consisting of a halogen atom, a cyano group, a nitro group, a trialkylsilyl group whose alkyl groups are each independently a linear or branched alkyl group having 1 to 8 carbon atoms,

6

- (6) and a linear or branched alkyl group having 1 to 20 carbon atoms (in which one or unadjacent two or more methylene groups in the alkyl group may be replaced by at least one group selected from the group consisting of —O—, —S—, —CO—, —CO—O—, —O—CO—, —CH=CH— and —C≡C—, and one or two or more hydrogen atoms in the alkyl group may be replaced by a fluorine atom); and J represents any one of a hydrogen atom, a halogen atom, a linear or branched alkyl group having 1 to 20 carbon atoms in which one or two or more hydrogen atoms in the alkyl group may be replaced by a fluorine atom, and an aromatic ring group which may have at least one substituent selected from the group consisting of a halogen atom, a cyano group, a nitro group, a trialkylsilyl group whose alkyl groups are each independently a linear or branched alkyl group having 1 to 8 carbon atoms, a linear or branched alkyl group having 1 to 20 carbon atoms (in which one or unadjacent two or more methylene groups in the alkyl group may be replaced by at least one group selected from the group consisting of —O—, —S—, —CO—, —CO—O—, —O—CO—, —CH=CH— and —C≡C—, and one or two or more hydrogen atoms in the alkyl group may be replaced by a fluorine atom).

Specific examples of the aromatic ring structures represented by A and B include a phenyl group, a naphthyl group, a fluorenyl group, an anthracenyl group, a fluoranthrenyl group, a pyrenyl group, a thienyl group, a piridyl group, an imidazolyl group, an oxazolyl group, a quinolyl group, an isoquinolyl group, a pyrazyl group, and triazolyl group.

Specific examples of the alicyclic structures represented by A' and B' include a cyclohexyl group, a cyclopentanyl group, and a norbornyl group.

In addition, according to the present invention, in a light-emitting device including a plurality of organic compound layers, at least one layer of the organic compound layers contains at least one of the above-mentioned organic compounds.

The organic compound layer is preferably a light-emitting layer.

The light-emitting layer preferably contains a plurality of phosphorescent materials.

The light-emitting layer preferably includes at least one of the above-mentioned organic compounds.

The organic compound layer is preferably a hole-transporting layer.

The organic compound layer is preferably an electron-transporting layer.

In addition, according to the present invention, there is provided an image display apparatus including the light-emitting device and a unit for supplying an electric signal to the light-emitting device.

The organic compound of the present invention for a light-emitting device is a highly efficient phosphorescent material suitable for emitting blue to red light.

The light-emitting device using the organic compound of the present invention, in particular, an organic light-emitting device using the organic compound as a light-emitting material for a light-emitting layer generates light having high luminance with high efficiency, has high durability, and can be produced easily at a relatively low cost.

It should be noted that the light-emitting device of the present invention includes an organic light-emitting device (also referred to as "organic electroluminescent device" or "organic EL device").

The present invention can provide a light-emitting device which can generate luminescence with high efficiency, can maintain high luminance for a long-term and has high durability, and organic compounds to be used for the light-emitting device.

ting device. Further, the present invention can provide a light-emitting device which can be produced easily at a relatively low cost. In addition, the present invention can provide an image display apparatus using the light-emitting device of the present invention.

Further features of the present invention will become apparent from the following description of exemplary embodiments with reference to the attached drawings.

BRIEF DESCRIPTION OF THE DRAWINGS

FIG. 1 shows an example of the organic EL device of the present invention.

FIG. 2 shows another example of the organic EL device of the present invention.

FIG. 3 shows another example of the organic EL device of the present invention.

FIG. 4 is a schematical view of a passive type of organic EL device.

FIG. 5 shows a pixel circuit of a panel.

FIG. 6 is a schematic view illustrating an example of a TFT substrate to be used in the present invention.

FIG. 7 shows another example of the organic EL device of the present invention.

DESCRIPTION OF THE EMBODIMENTS

Hereinafter, the present invention will be described in detail.

FIGS. 1, 2 and 3 show basic device structures of the light-emitting device of the present invention.


First, reference characters in the drawings are explained as follows: **11** denotes a metal electrode; **12**, a light-emitting layer; **13**, a hole-transporting layer; **14**, a transparent electrode; **15**, a transparent substrate; **16**, an electron-transporting layer; **17**, an exciton diffusion-prevention layer; **18**, a metal electrode layer; and **19**, a metal electrode layer.

As shown in FIG. 1, an organic EL device generally includes, on a transparent substrate **15**, a transparent electrode **14** having a thickness of 50 to 200 nm, an organic film layer composed of plural layers, and a metal electrode **11** facing the transparent electrode through the organic film layer. The transparent electrode **14** and the metal electrode **11** serve as a pair of electrodes.

FIG. 1 shows an example in which the organic layers include a light-emitting layer **12** and a hole-transporting layer **13**. ITO having a large work function is used for the transparent electrode **14** to facilitate the hole injection from the transparent electrode **14** into the hole-transporting layer **13**. A metal material having a small work function such as aluminum, magnesium or an alloy thereof is used for the metal electrode **11** to facilitate the electron injection into the organic layers.

The organic compound of the present invention is used for the light-emitting layer **12**. A material having electron-donating properties such as a triphenyl diamine derivative typified by α -NPD represented by the following structural formula can also be appropriately used for the hole-transporting layer **13**.

α -NPD



The device having the above-mentioned constitution exhibits electrical rectifying properties. When an electric field is applied in such a manner that the metal electrode **11** serves as a cathode and the transparent electrode **14** serves as an anode, electrons are injected from the metal electrode **11** to the light-emitting layer **12** and holes are injected from the transparent electrode **14**.

The injected holes and electrons are recombined in the light-emitting layer **12** to generate excitons, thereby emitting light. In this case, the hole-transporting layer **13** serves as an electron-blocking layer, and the recombination efficiency at the interface between the light-emitting layer **12** and the hole-transporting layer **13** increases, whereby the light emission efficiency increases.

In FIG. 2, an electron-transporting layer **16** is interposed between the metal electrode **11** and the light-emitting layer **12** in FIG. 1. In this case, emission efficiency is increased by separating a light emitting function from electron- and hole-transporting functions to provide a carrier blocking structure having improved effectiveness. An oxadiazole derivative can be used for the electron-transporting layer **16**.

As shown in FIG. 3, it is also preferable to employ a four-layer structure composed of, from the side of the transparent electrode **14** as an anode, the hole-transporting layer **13**, the light-emitting layer **12**, an exciton diffusion-prevention layer **17**, the electron-transporting layer **16**, and the metal electrode **11**.

The organic compound of the present invention is a metal complex having monovalent bidentate ligands, in which a metal atom is bound with each of moieties in aromatic ring structures of the ligands. The aromatic ring structures are covalently bound with each other, and each of the aromatic ring structures shares at least 2 carbon atoms with an alicyclic structure in the metal complex. In this skeleton, an aromatic ring structure present for each conformation is directly bound with an alicyclic structure, whereby concentration quenching among molecules is suppressed, thus the organic compound having the skeleton can be used in a light-emitting layer in a high concentration, even 100%. There is an example of an organic compound in which one of two aromatic ring structures is bound with an alicyclic structure (see, Adv. Mater. 2001, 13, No. 16, August 16). However, in this case, it is difficult to completely suppress the overlapping of aromatic rings among molecules. Further, it is possible to realize transfer and recombination of charges in a molecule by allowing an alicyclic structure to have an aromatic ring structure without conjugation with a ligand so that a complex has a charge-transporting portion. In addition, it is possible to control emission wavelengths by replacing a carbon atom in an alicyclic portion with a hetero atom. Further, it is possible to form a light-emitting layer by incorporating a portion having the skeleton into a polymer.

9

The light-emitting device having high efficiency of the present invention can be applied to products which require energy saving or high luminance. Examples of applications include a light source for a display apparatus, an illumination apparatus and a printer, and a backlight for a liquid crystal display apparatus. The application of the light-emitting device of the present invention to a display apparatus can provide a lightweight and energy-saving flat panel display with a high level of visibility. In addition, as the light source for a printer, a laser light source for a laser beam printer which is widely used at present can be replaced by the light-emitting device of the present invention. In this respect, independently addressable devices are arranged in an array, and a photosensitive drum is exposed to light in a desired manner to form images. The use of the light-emitting device of the present invention can significantly reduce the volume of an apparatus. The light-emitting device of the present invention is expected to provide an energy-saving effect on the illumination apparatus or the backlight.

The light-emitting device of the present invention may be applied to a display in such a manner that the light-emitting device is driven using an active-matrix TFT drive circuit.

An example of the light-emitting device of the present invention in which an active-matrix substrate is used will be described below with reference to FIGS. 4, 5 and 6.

FIG. 4 schematically illustrates an example of a passive type of organic EL device. In FIG. 4, 21 denotes a glass substrate; 22, an ITO electrode; 23, an organic compound layer; and 24, a cathode. The panel is equipped with a scanning signal driver, an information signal driver, and a current supply source, which are connected respectively to gate selection lines, information signal lines, and current supply lines. A pixel circuit shown in FIG. 5 is placed at the intersection point between the gate selection line and the information signal line. The scanning signal driver sequentially selects the gate selection lines G1, G2, G3, . . . , Gn, and in synchronization therewith, image signals are applied to the gate selection lines from the information signal driver.

Next, the operation of the pixel circuit will be described. In the pixel circuit, when a selected signal is applied to the gate selection line, TFT 1 is turned on to supply an image signal to Cadd so that a gate potential of TFT 2 is determined. Electric current is supplied to the EL device from the current supply line according to the gate potential of TFT 2. Since the gate potential of TFT 2 is retained in Cadd until TFT 1 is again scanned and selected, the gate potential of TFT 2 continues to flow in the EL device until the next scanning is performed. Thus, it is possible to emit light constantly during a one frame period of time.

FIG. 6 schematically illustrates an example of a TFT substrate to be used in the present invention. A p-Si layer is formed on a glass substrate, and necessary impurities are doped in channel, drain and source regions, respectively. A gate electrode is formed thereon through a gate-insulating film, and a drain electrode and a source electrode are so formed as to be connected to the drain region and the source region. On the electrodes, an insulating layer and an ITO electrode as a pixel electrode are superposed, and the ITO electrode and the drain electrode are connected through a contact hole.

In the present invention, a switching device is not particularly limited, and any one of a single-crystal silicon substrate, an MIM device and an a-Si type device can easily be adopted.

An organic EL display panel can be obtained by sequentially superposing a multi-layered or single-layered organic EL layer/cathode layer on the ITO electrode. The display panel using the organic compound of the present invention


10

can be driven to constantly display images with good image quality for a long period of time.


Specific structural formulae of organic compounds used in the present invention are shown below.

However, those formulae are intended merely for showing representative examples, and the present invention is not limited thereto.


A1



A2







A3



11

-continued



12

-continued

A4

5

10

15

20

A5

25

30

35

A6

40

45





50

A7

55

60

65



A8




A9

A10

A11

13

-continued



14

-continued

A12

5

10

15

20

25

A13

30

35

40

45




A14

50

55

60

65






A15

A16

A17

15

-continued



16

-continued

A18

5

10

15

20

25

A19

30

35

40






45

A20 50

55

60

65



A21

A22




A23

A24

A25

17

-continued



18

-continued

A26

5

10

15

20

A27

25

30

35

A28

40



45

50

55

60

65






A29

A30

19

-continued



20


-continued

A31

5

10

15




A34

20

25

30



A35


A32

35

40

45

50




A36

A33

55

60





65



A37

21

-continued

**22**


-continued

A38

5

10

15




A42

A39

20

25

30



A43

A40


40

45

50

A41

55




A44


A45

60

65







A46



23

-continued



24

-continued

A47

5

10

A48

15

20

25

A49

35

40

45




A50

50

55

60

65






A51

A52

A53

25

-continued



A54

5

10

15

20

25

A55

30

35

40

45

50

A56





55

60

65

26

-continued



A57





A58

A59

A60

27

-continued

**28**

-continued

A61

5

10

15

A62

20

25

30

A63

35

40

45

50

A64

55

60





65

A65

A66





A67

A68



29

-continued

**30**

-continued

A69

5

10

15

20

A70 25

30

35

A71 40

45

50

A72

55

60





65

A73

A74




A75

A76



31

-continued

**32**

-continued

A77

5

10

15

20

25

A78

30

35

40

45





A79

50

55

60

65



A80





A81

A82

A83

33

-continued



34


-continued

A84

5

10

15




A88

A85

20

25

30



A89

A86


35

40

45

50

A87




A90

55

60


65



A91

35

-continued



In addition, when the organic compound of the present invention is used for an organic compound layer such as a light-emitting layer of a light-emitting device, the organic compound layer such as a light-emitting layer contains the organic compound of the present invention in a content of 5% by weight or more, preferably 10% by weight or more and 100% by weight or less, and more preferably 51% by weight or more and 100% by weight or less.


EXAMPLES

Hereinafter, the present invention will be described specifically by way of examples. However, the present invention is not limited to these examples.

Representative synthesis examples concerning synthesis methods necessary for synthesizing exemplified compounds are shown below.


Example 1

Synthesis of Exemplified Compound No. A60




8.12 g (32 mmole) of Compound B1, 40 ml of pyridine (Compound B2), and 3.84 g (32 mmole) of iodine were fed into a 100-ml egg-plant type flask, and stirred at 110° C. for 6 hours in a stream of nitrogen. After filtering the reaction solution, the filtrate was washed with ethanol, and the precipitated crystal was filtered out to yield 19.0 g of crystals of Compound B3 which seemed to contain the pyridine solvent.

36




15.0 g of Compound B3, 3.8 g (25 mmol) of Compound B4, 4.0 g (52 mmole) or ammonium acetate, and 40 ml of DMF were fed into a 100-ml three-necked flask, and stirred at 75° C. for 6 hours in a stream of nitrogen. The reaction product was cooled to room temperature. A precipitate was transferred to 80 ml of water, extracted five times with 300 ml of hexane for each time, and dried over magnesium sulfate, followed by filtration and concentration. After that, silica gel chromatography (toluene:hexane=1:1) was performed to fractionate a target product, and the target product was concentrated to yield 7.5 g of a white solid (Compound B5).




1.89 g (5 mmole) of an iridium (III) trihydrate, 3.67 g (11 mmole) of Compound B5, 90 ml of ethoxyethanol, and 30 ml of water were fed into a 200-ml three-necked flask, and stirred

37


at room temperature for 30 minutes under a stream of nitrogen, followed by stirring at 100° C. for 10 hours. The reaction product was cooled to room temperature. A precipitate was filtrated out and washed with water and then with ethanol. The resultant product was dried under reduced pressure at room temperature to yield 3.8 g (75% yield) of a yellow powder of Compound B6.



B6



B7



A60


100 ml of ethoxyethanol, 1.67 g (1 mmole) of Compound B6, 0.2 g (2 mmole) of acetyl acetone (Compound B7), and 0.85 g (8 mmole) of sodium carbonate were fed into a 200-ml three-necked flask, and stirred at room temperature for 1 hour under a stream of nitrogen, followed by stirring at 100° C. for 7 hours. The reaction product was cooled with ice, and a precipitate was filtrated out and washed with water. The precipitate was washed with ethanol and dissolved in chloroform, followed by filtration of insoluble substances. The filtrate was concentrated and subjected to recrystallization with

38

chloroform/methanol to yield 1.2 g (72% yield) of a yellow powder of Exemplified Compound No. A60.

Example 2

Synthesis of Exemplified Compound No. A2



A2

3.21 g (10 mmole) of Compound B5, 0.93 g (1 mmole) of Exemplified Compound No. A60, and 50 ml of glycerol were fed into a 100-ml three-necked flask, and heated and stirred at around 180° C. for 8 hours under a stream of nitrogen. The reaction product was cooled to room temperature and poured into 170 ml of 1 N hydrochloric acid. A precipitate was filtrated out and washed with water, followed by drying under reduced pressure at 100° C. for 5 hours. The precipitate was purified by silica gel column chromatography using chloroform as an eluent to yield 0.15 g (13% yield) of a red powder of Exemplified Compound No. A2.


Exemplified Compound No. A2 was confirmed to have M^+ of 1,099.54 according to MALDI-TOF MS and λ_{max} =521 nm (in toluene).

39


Example 3

40


Synthesis of Exemplified Compound No. A37



B7



B8




B8

41

-continued

42



A37

A reaction as described in the above-mentioned reaction formulae is carried out using iridium (III) trihydride, Compound B7, silver (I) oxide, and dehydrated THF to yield Exemplified Compound No. A37.

Example 4

In this example, a device having 3 organic layers shown in FIG. 7 was used as a device constitution. A pattern of ITO (transparent electrode **14**) having a thickness of 100 nm was so formed on a glass substrate (transparent substrate **15**) as to have an electrode area of 3.14 mm². The following organic layers and electrode layers were successively formed on the ITO substrate through vacuum evaporation according to resistance heating in a vacuum chamber at 10⁻⁴ Pa to produce a device. Hole-transporting layer **13** (40 nm): Compound A of the following formula

Light-emitting layer **12** (5 nm): Exemplified Compound No. A2


Electron-transporting layer **16** (30 nm): Bphen of the following formula

Metal electrode layer **18** (15 nm): KF

Metal electrode layer **19** (100 nm): Al


An electric current was applied to the device, and light emission was confirmed.

Compound A :



-continued

Bphen:



Example 5

In the device constitution shown in Example 4, a device having the following constitution was produced.

Hole-transporting layer **13** (40 nm): Compound A1

Light-emitting layer **12** (40 nm): 30% by weight of CBP+ Exemplified Compound No. A2

Electron-transporting layer **16** (30 nm): Bphen

Metal electrode layer **18** (15 nm): KF

Metal electrode layer **19** (100 nm): Al

Electric current was applied to the device, and light emission was confirmed with an emission peak at 525 nm.

Example 6

In the device constitution shown in Example 4, a device having the following constitution was produced

Hole-transporting layer **13** (40 nm): Compound A1

Light-emitting layer **12** (10 nm): Exemplified Compound No. A65

Electron-transporting layer **16** (30 nm): Bphen

Metal electrode layer **18** (15 nm): KF

Metal electrode layer **19** (100 nm): Al

Electric current was applied to the device, and light emission was confirmed.

Example 7

In the device constitution shown in Example 4, a device having the following constitution was produced.

Hole-transporting layer **13** (40 nm): Compound A1

Light-emitting layer **12** (10 nm): Exemplified Compound No. A10

Electron-transporting layer **16** (30 nm): Bphen

43

Metal electrode layer **18** (15 nm): KF

Metal electrode layer **19** (100 nm): Al

Electric current was applied to the device, and light emission was confirmed.

Example 8


PEDOT (for use in organic EL) manufactured by Bayer AG was applied onto an ITO substrate to have a thickness of 40 nm by spin coating at 1,000 rpm for 20 seconds. The resultant layer was dried in a vacuum chamber at 120° C. for 1 hour. An organic film (light-emitting layer **12**) was formed on the resultant film to have a thickness of 50 nm by spin coating under a nitrogen atmosphere at 2,000 rpm for 20 seconds using a solution containing the following components.

Dehydrated chlorobenzene: 10 g

Exemplified Compound No. A2: 92 mg

Compound B: 8 mg

Compound B:



After the formation of the organic film, the organic film was dried under the same conditions as in the case of forming the PEDOT film.

The substrate thus produced was set in a vacuum evaporation chamber to form a film of Bphen in a thickness of 40 nm by vacuum evaporation deposition. The organic layers had a total film thickness of 130 nm.

Next, a cathode (metal electrode **11**) having the following constitution was formed.

Metal electrode layer **1** (15 nm): an Al/Li alloy (Li content of 1.8% by weight)

Metal electrode layer **2** (100 nm): Al

After the completion of film formation, the device was taken out for evaluation.

A DC voltage was applied to the device in such a manner that a minus voltage was applied to the metal electrode **11** and a plus voltage was applied to the transparent electrode **14** to evaluate the device properties. Electric current was applied to the device, and light emission was observed.

44


The organic compound of the present invention including a metal complex in which an alicyclic structure is directly bound to an aromatic ring structure present for each conformation can be used for a light-emitting material for a light-emitting device.

While the present invention has been described with reference to exemplary embodiments, it is to be understood that the invention is not limited to the disclosed exemplary embodiments. The scope of the following claims is to be accorded the broadest interpretation so as to encompass all such modifications and equivalent structures and functions.

This application claims the benefit of Japanese Patent Application No. 2006-099893, filed Mar. 31, 2006, which is hereby incorporated by reference herein in its entirety.

What is claimed is:

1. A compound for a light-emitting device which is represented by the following general formula (7):



wherein C represents an alicyclic structure and the alicyclic structure may have a linear or branched alkyl group having 1 to 20 carbon atoms as a substituent.

2. A light-emitting device comprising a pair of electrodes and a light-emitting layer disposed between the pair of electrodes, wherein the light-emitting layer comprises the compound according to claim 1.

3. A display apparatus comprising the light-emitting device according to claim 2 and a drive portion connected to the light-emitting device.

* * * * *

专利名称(译)	用于发光装置的有机化合物，发光装置和图像显示装置		
公开(公告)号	US8268455	公开(公告)日	2012-09-18
申请号	US11/686030	申请日	2007-03-14
[标]申请(专利权)人(译)	佳能株式会社		
申请(专利权)人(译)	佳能株式会社		
当前申请(专利权)人(译)	佳能株式会社		
[标]发明人	KAMATANI JUN OOISHI RYOTA OKADA SHINJIRO TAKIGUCHI TAKAO		
发明人	KAMATANI, JUN OOISHI, RYOTA OKADA, SHINJIRO TAKIGUCHI, TAKAO		
IPC分类号	H01L51/54 C09K11/06		
CPC分类号	C07F15/0033 C09K11/06 H01L51/0085 H05B33/14 C09K2211/1011 C09K2211/1029 C09K2211/1033 C09K2211/1044 C09K2211/1088 C09K2211/1092 C09K2211/185 H01L51/0037 H01L51/0042 H01L51/0059 H01L51/5016 H01L51/5048		
优先权	2006099893 2006-03-31 JP		
其他公开文献	US20070231600A1		
外部链接	Espacenet USPTO		

摘要(译)

提供一种发光装置，其使用有机化合物以高亮度和极高效率发光。有机化合物由具有一价二齿配体的金属配合物组成。发光装置包括作为阳极和阴极的一对电极，以及插入在电极之间的多个有机化合物层，其中至少一层有机化合物层含有由以下结构式表示的金属络合物。发光器件是使用发光器件的有机电致发光器件，其中包含有机化合物的层是发光层。

