

US007691491B2

### (12) United States Patent

Saitoh et al.

### (10) **Patent No.:**

US 7,691,491 B2

#### (45) **Date of Patent:**

Apr. 6, 2010

# (54) MONOAMINOFLUORENE COMPOUND AND ORGANIC LIGHT-EMITTING DEVICE USING THE SAME

(75) Inventors: Akihito Saitoh, Yokohama (JP); Mizuho

Hiraoka, Kawasaki (JP); Koichi Suzuki, Yokohama (JP); Akihiro Senoo, Kawasaki (JP); Hiroshi Tanabe, Yokohama (JP); Naoki Yamada, Komae

(JP); Chika Negishi, Kawasaki (JP)

(73) Assignee: Canon Kabushiki Kaisha, Tokyo (JP)

(\*) Notice: Subject to any disclaimer, the term of this

patent is extended or adjusted under 35 U.S.C. 154(b) by 878 days.

(21) Appl. No.: 10/525,194

(22) PCT Filed: Aug. 12, 2003
 (86) PCT No.: PCT/JP03/10260

§ 371 (c)(1),

(2), (4) Date: Feb. 22, 2005

(87) PCT Pub. No.: WO2004/020387

PCT Pub. Date: Mar. 11, 2004

(65) **Prior Publication Data** 

US 2006/0166034 A1 Jul. 27, 2006

(30) Foreign Application Priority Data

Aug. 30, 2002 (JP) ...... 2002-252846

(51) **Int. Cl.** 

 H01L 51/54
 (2006.01)

 C07C 211/00
 (2006.01)

 C07D 209/82
 (2006.01)

 C07D 221/02
 (2006.01)

564/429; 564/433; 548/440; 546/94

See application file for complete search history.

#### (56) References Cited

#### U.S. PATENT DOCUMENTS

(Continued)

#### FOREIGN PATENT DOCUMENTS

EP 0 821 277 A1 1/1998

(Continued)

#### OTHER PUBLICATIONS


Proceedings of SPIE, (1998), 3472, p. 70-79.\*

(Continued)


Primary Examiner—Dawn Garrett (74) Attorney, Agent, or Firm—Fitzpatrick, Cella, Harper & Scinto

#### (57) ABSTRACT

Novel monoaminofluorene compounds are provided, and organic light-emitting devices which exhibit good luminescence hue of extremely high purity and have optical output with high luminescence efficiency, high luminance and longer operating life are provided using the compounds. The monoaminofluorene compound represented by the following general formula [1]:



14 Claims, 3 Drawing Sheets



	U.S. I	PATENT	DOCUMENTS
4,885,211	A	12/1989	Tang et al 428/457
5,130,303	A	7/1992	Tokailin et al 313/504
5,151,629	A	9/1992	VanSlyke 313/504
5,227,252	A	7/1993	Murayama et al 428/690
5,247,190	A	9/1993	Friend et al 257/40
5,317,169	A	5/1994	Nakano et al 257/40
5,382,477	A	1/1995	Saito et al 428/690
5,409,783	A	4/1995	Tang et al 428/690
5,514,878	A	5/1996	Holmes et al 257/40
5,672,678	A	9/1997	Holmes et al 528/373
5,726,457	A	3/1998	Nakano et al 257/40
5,989,737	A *	11/1999	Xie et al 428/690
6,093,864	A	7/2000	Tokailin et al 585/25
6,743,948	B1	6/2004	Hosokawa et al 564/426
6,916,555	B2	7/2005	Suzuki et al 428/690
7,241,513	B2*	7/2007	Suzuki et al 428/690
2003/0039838	A1*	2/2003	Chen et al 428/411.1
2003/0065190	A1	4/2003	Spreitzer et al 548/134
2003/0072966	A1	4/2003	Hosokawa et al 428/690
2004/0253389	A1*	12/2004	Suzuki et al 428/1.1
2005/0038296	A1	2/2005	Hosokawa et al 564/426
2005/0106414	A1*	5/2005	Saitoh et al 428/690

#### FOREIGN PATENT DOCUMENTS

EP	1221434 A1	10/2002
JР	02-247278	10/1990
JP	03-255190	11/1991
JР	04-145192	5/1992
JР	09-227576	9/1992
JР	05-202356	8/1993
JР	05-247460	9/1993
JP	7-43920	7/1995
JP	07-281464	10/1995

JP	08-044096	2/1996
JP	09-202878	8/1997
JP	09-281728	10/1997
JP	11-144873	5/1999
JP	11-144875	5/1999
JP	11-184109	7/1999
JP	11-312587	11/1999
JP	2000-327639	11/2000
JP	2001-010996	1/2001
JP	2001-052868	2/2001
JP	2001-66809	3/2001
JP	2001-192651	7/2001
JP	2001-196177	7/2001
JP	2002-8866	11/2002
JP	2003-128651 A	* 5/2003
WO	97/33323	9/1997
WO	99/40655	8/1999
WO	WO 00/39247	* 7/2000
WO	2004/020372 A1	3/2004

#### OTHER PUBLICATIONS

Chemistry of Materials, (2000), 12(5), pp. 1184-1186.\*

Machine generated translation of Description section of JP 2003-128651 A published May 2003.\*

Machine generated translation of Examples section of JP 2003-

128651 A published May 2003.\*

Machine generated translation of Claims section of JP 2003-128651 A published May 2003.\*

Tang, et al; "Organic Electroluminescent Devices"; Appl. Phys. Lett. vol. 51, No. 12, pp. 913-915 (1987).

Burroughes, et al; Light-emitting diodes based on conjugated polymers; Nature, vol. 347, pp. 539-541 (1990).
Kelley et al., "Synthesis of Bridged Oligophenylenes from Fluorene", J. Chem. Research (S),1997, 446-447.

<sup>\*</sup> cited by examiner

FIG. 1




FIG. 2




FIG. 3




FIG. 4




FIG. 5





FIG. 6



1

# MONOAMINOFLUORENE COMPOUND AND ORGANIC LIGHT-EMITTING DEVICE USING THE SAME

#### TECHNICAL FIELD

The present invention relates to a monoaminofluorene compound and an organic light-emitting device, more particularly to a light-emitting device using an organic compound which emits light by applying an electric field to a thin 10 film of the organic compound.

#### BACKGROUND ART

An organic light-emitting device is a device having a thin film containing a fluorescent organic compound interposed between an anode and a cathode, in which excitons of the fluorescent compound are generated by injecting electrons and holes (positive holes) from each electrode into the compound and the light emitted when these excitons return to the ground state is utilized.

In a research by Eastman Kodak Company in 1987 (Appl. Phys. Lett. 51, 913 (1987)), luminescence on the order of 1000 cd/m² upon application of voltage on the order of 10 V was reported in relation to a device having a function separate type two-layer structure using ITO for the anode, and magnesium silver alloy for the cathode, respectively, and using aluminum quinolinol complex as an electron-transporting material as well as a light-emitting material and tripheny-lamine derivative as a hole-transporting material. Relevant patents include U.S. Pat. Nos. 4,539,507, 4,720,432, 4,885, 211, etc.

Moreover, luminescence ranging from ultraviolet to infrared rays can be obtained by changing the kind of fluorescent organic compound, and, recently, studies on various compounds are actively conducted. For example, such studies are described in U.S. Pat. Nos. 5,151,629, 5,409,783, 5,382,477, Japanese Patent Application Laid-Open No. 2-247278, Japanese Patent Application Laid-Open No. 3-255190, Japanese Patent Application Laid-Open No. 5-202356, Japanese Patent Application Laid-Open No. 9-202878, Japanese Patent Application Laid-Open No. 9-227576, etc.

In addition to the organic light-emitting devices using low molecular materials as mentioned above, an organic light-emitting device using a conjugated polymer was reported by a group in Cambridge University (Nature, 347, 539 (1990)). This report confirms that luminescence occurs in a single layer film which is formed of poly(phenylene vinylene) (PPV) using a coating system. Related patents of the organic light-emitting device using conjugated polymer include U.S. Pat. Nos. 5,247,190, 5,514,878, 5,672,678, Japanese Patent Application Laid-Open No. 4-145192, Japanese Patent Application Laid-Open No. 5-247460, etc.

The latest progress in the organic light-emitting device is remarkable in this way, and the features thereof facilitate production of light-emitting devices imparted with high luminance at low applied voltage, diversity of luminescence wavelength, high-speed response, thin shape and lightweight, thereby suggesting possibility for a wide variety of applications

However, there still remain many problems in respect of durability, such as change with the passage of time by prolonged use, degradation by atmospheric gas containing oxygen, humidity, etc. Furthermore, when the application to a full 65 color display and the like is envisaged, optical output of further higher luminance or higher conversion efficiency, and

2

luminescence in blue, green and red of high color purity are required under the present condition.

For example, although diamine compounds as a luminescent material were disclosed in Japanese Patent Application Laid-Open No. 2001-52868, blue luminescence of high color purity (chromaticity coordinate: x, y=0.14-0.15, 0.09-0.10) was not obtained. An example using a compound having the similar diamino structure was also disclosed in Japanese Patent Application Laid-Open No. 2001-196177, but the compound was used as a hole injection layer, and there was no description of the use as a light-emitting layer and light-emitting properties thereof such as luminescence color and efficiency.

#### DISCLOSURE OF THE INVENTION


The present invention has been made to solve these problems of the prior art, and an object of the present invention is to provide a novel monoamino compound.

Another object of the present invention is to provide an organic light-emitting device exhibiting good luminescence hue of extremely high purity and high luminance optical output with a high efficiency and a longer operating life.

Still another object of the present invention is to provide an organic light-emitting device which can be readily manufactured at relatively low cost.

The inventors of the present invention conducted intensive study in order to solve the above-mentioned problems and came to complete the present invention.

That is, the monoaminofluorene compound of the present invention is characterized in that it is represented by the following general formula [1] or [2].



wherein  $X_1$  is a divalent group selected from the group consisting of substituted or unsubstituted alkylene, aralkylene, arylene and heterocyclic ring groups, and alkylene, aralkylene, alkenylene, amino, silyl, carbonyl, ether and thioether groups having a linking group consisting of a substituted or unsubstituted arylene or divalent heterocyclic ring group, or  $X_1$  may be a direct bond;

 $\rm X_2$  is a group selected from the group consisting of a hydrogen atom, a halogen group, substituted or unsubstituted alkyl, aralkyl, alkenyl, alkynyl, alkoxy, aryl, heterocyclic ring and sulfide groups, a substituted silyl group and a cyano group;

 $\rm Y_1$  and  $\rm Y_2$  may be the same or different and are groups selected from the group consisting of substituted or unsubstituted alkyl, aralkyl, aryl and heterocyclic ring groups, substituted or unsubstituted alkylene, aralkylene, alkenylene, amino and silyl groups having a linking group consisting of a substituted or unsubstituted arylene or divalent heterocyclic ring group, and unsubstituted carbonyl, ether and thioether groups having a linking group consisting of a substituted or unsubstituted arylene or divalent heterocyclic ring group;

 $Y_1$  and  $Y_2$ , or  $X_1$ ,  $Y_1$  and  $Y_2$  may also join together to form

10

3

 $\rm R_1$  and  $\rm R_2$  may be the same or different and are groups selected from the group consisting of a hydrogen atom, and substituted or unsubstituted alkyl, aralkyl and aryl groups; and

n is an integer of 2 to 10 when  $X_1$  is a direct bond and  $X_2$  is  $\,^5$  a hydrogen atom, and otherwise an integer of 1 to 10.

$$Y_3$$
 $N-X_3$ 
 $X_4$ 
 $X_4$ 
 $X_5$ 

wherein  $X_3$  and  $X_4$  may be the same or different and are divalent groups selected from the group consisting of a substituted or unsubstituted alkylene, aralkylene, arylene and heterocyclic ring groups, substituted or unsubstituted alkylene, aralkylene, alkenylene, amino and silyl groups having a linking group consisting of a substituted or unsubstituted arylene or divalent heterocyclic ring group, unsubstituted carbonyl, ether and thioether groups, or  $X_3$  may be a direct bond:

 $X_5$  is a group selected from the group consisting of a hydrogen atom, a halogen group, substituted or unsubstituted alkyl, aralkyl, alkenyl, alkynyl, alkoxy, aryl, heterocyclic ring and sulfide groups, a substituted silyl group, and a cyano group;

 $\rm Y_3$  and  $\rm Y_4$  may be the same or different and are groups selected from the group consisting of substituted or unsubstituted alkyl, aralkyl, aryl and heterocyclic ring groups, substituted or unsubstituted alkylene, aralkylene, alkenylene, amino and silyl groups having a linking group consisting of a substituted or unsubstituted arylene or divalent heterocyclic ring group, and unsubstituted carbonyl, ether and thioether groups having a linking group consisting of a substituted or unsubstituted arylene or divalent heterocyclic ring group;

 $Y_3$  and  $Y_4$ , or  $X_3$ ,  $Y_3$  and  $Y_4$  may also join together to form  $_{40}$  a ring;

 $\rm R_3$  to  $\rm R_6$  may be the same or different and are groups selected from the group consisting of a hydrogen atom, and substituted or unsubstituted alkyl, aralkyl and aryl groups; and

each of p and q is an integer not less than one and p+q is an integer of 2 to 10.

In the organic light-emitting device of the present invention comprising a pair of electrodes which consist of an anode and a cathode and one or more layers which are interposed between the electrodes and contain an organic compound, the at least one layer containing the organic compound preferably contains at least one compound represented by the abovementioned general formula [1] or [2].

#### BRIEF DESCRIPTION OF DRAWINGS

FIG. 1 is a cross-sectional view showing an example of the organic light-emitting device according to the present invention:

FIG. 2 is a cross-sectional view showing another example of the organic light-emitting device according to the present invention;

FIG. 3 is a cross-sectional view showing another example 65 of the organic light-emitting device according to the present invention;

4

FIG. 4 is a cross-sectional view showing another example of the organic light-emitting device according to the present invention:

FIG. 5 is a cross-sectional view showing another example of the organic light-emitting device according to the present invention; and

FIG. 6 is a cross-sectional view showing another example of the organic light-emitting device according to the present invention.

## BEST MODE FOR CARRYING OUT THE INVENTION

The present invention will be described in detail below.

The monoaminofluorene compound of the present invention is described first.

The monoaminofluorene compound of the present invention is represented by the above-mentioned general formula [1] or [2].

The monoaminofluorene compound of the present invention can mainly be used as an organic light-emitting device material, and when it is used as a light-emitting device material, devices having high color purity, high luminescence efficiency and a longer operating life can respectively be obtained even in a single layer. Furthermore, a luminescence spectrum with a narrower half-value width, i.e., luminescence more excellent in color purity is obtained by introducing fluorene having a rigid structure into the main chain of the molecule. Furthermore, since the Stokes shift is suppressed, a shift of the luminescence wavelength is suppressed, and it is also possible to shift the absorption even toward a longer wavelength side, and when it is used as a dopant material, use of a host material which has a luminescence spectrum in a relatively longer wavelength side is also enabled.

Each of the monoaminofluorene compounds of the present invention can be used for the purpose of both dopant material and host material in a light-emitting layer to provide a device having high color purity, high luminescence efficiency, and longer operating life, and in particular can be used as a dopant material in combination with a suitable host material of easily causing energy transfer to provide a device holding high color purity luminescence and having higher efficiency.

Specific examples of the substituents in the above-mentioned general formulae [1] and [2] are shown below.

Examples of the substituted or unsubstituted linear or cyclic alkyl group include methyl group, ethyl group, n-propyl group, n-butyl group, n-hexyl group, n-decyl group, isopropyl group, iso-butyl group, tert-butyl group, tert-octyl group, trifluoromethyl group, cyclohexyl group, cyclohexylmethyl group, but, of course, are not limited to these.

Examples of the substituted or unsubstituted aralkyl group include benzyl group, phenethyl group, but, of course, are not limited to these.

Examples of the substituted or unsubstituted aryl group include phenyl group, 4-methylphenyl group, 4-methoxyphenyl group, 4-ethylphenyl group, 4-fluorophenyl group, 3,5-dimethylphenyl group, triphenylamino group, biphenyl group, terphenyl group, naphthyl group, anthracenyl group, phenanthrenyl group, pyrenyl group, tetracenyl group, pentacenyl group, fluorenyl group, triphenylenyl group, perylenyl group, but, of course, are not limited to these.

Examples of the substituted or unsubstituted heterocyclic ring group include pyrrolyl group, pyridyl group, bipyridyl group, methylpyridyl group, terpyrrolyl group, thienyl group, terthienyl group, propyl thienyl group, furyl group, quinolyl

5

group, carbazolyl group, oxazolyl group, oxadiazolyl group, thiazolyl group, thiadiazolyl group, but, of course, are not limited to these.

Examples of the substituted or unsubstituted alkylene group include methylene group, ethylene group, propylene group, iso-propylene group, butylene group, tert-butylene group, hexylene group, heptylene group, cyclohexylene group, cyclohexylmethylene group, but, of course, are not limited to these.

Examples of the substituted or unsubstituted aralkylene 10 group include benzylene group, phenylethylene group, phenethylene group, but, of course, are not limited to these.

Examples of the substituted or unsubstituted arylene group include phenylene group, biphenylene group, 2,3,5,6-tetrafluorophenylene group, 2,5-dimethylphenylene group, naphtylene group, anthracenylene group, phenanthrenylene group, tetracenylene group, pentacenylene group, perylenylene group, but, of course, are not limited to these.

Examples of the substituted or unsubstituted divalent heterocyclic ring group include furanylene group, pyrrolylene <sup>20</sup> group, pyridinylene group, terpyridinylene group, thiophenylene group, terthiophenylene group, oxazolylene group, thiazolylene group, carbazolylene, but, of course, are not limited to these.

Examples of the substituted or unsubstituted alkenyl group  $^{25}$  include vinyl group, allyl group (2-propenyl group), 1-propenyl group, iso-propenyl group, 2-butenyl group, but, of course, are not limited to these.

Examples of the substituted or unsubstituted amino group include amino group, methylamino group, ethylamino group, dimethylamino group, diethylamino group, methylethylamino group, benzylamino group, methylbenzylamino group, dibenzylamino group, anilino group, diphenylamino group, phenyltolylamino group, ditolylamino group, dianisolylamino group, but, of course, are not limited to these.

Examples of the substituted or unsubstituted carbonyl group include acetyl group, propionyl group, isobutyryl group, methacryloyl group, benzoyl group, naphtoyl group, anthranyl group, toluoyl group, but, of course, are not limited to these.

6

Examples of the substituted or unsubstituted alkoxy group include methoxy group, ethoxy group, propoxy group, 2-ethyl-octyloxy group, phenoxy group, 4-butylphenoxy group, benzyloxy group, but, of course, are not limited to these.

Examples of the substituted or unsubstituted sulfide group include methylsulfide group, ethylsulfide group, phenylsulfide group, 4-methylphenylsulfide group, but, of course, are not limited to these.

Examples of the substituent group which the above-mentioned substituent groups may have include alkyl groups such as methyl group, ethyl group, n-propyl group, iso-propyl group, ter-butyl group, octyl group, benzyl group and phenethyl group, an aralkyl group, alkoxy groups such as methoxy group, ethoxy group, propoxy group, 2-ethyl-octyloxy group, phenoxy group, 4-butylphenoxy group and benzyloxy group, aryl groups such as phenyl group, 4-methylphenyl group, 4-ethylphenyl group, 3-chlorophenyl group, 3,5-dimethylphenyl group, triphenylamino group, biphenyl group, terphenyl group, naphthyl group, anthryl group, phenanthryl group and pyrenyl group, a heterocyclic ring group such as pyridyl group, bipyridyl group, methylpyridyl group, thienyl group, terthienyl group, propylthienyl group, furyl group, quinolyl group, carbazolyl group and N-ethylcarbazolyl group, a halogen group, cyano group, and nitro group, but, of course, are not limited to these.

Typical examples of the compound represented by the general formulae [1] and [2] are shown below but are not limited to these compounds.

$$\begin{array}{c} X_1 \\ X_2 \\ X_2 \end{array}$$

TABLE 1

				IABLE I		
	n	R1, R2	X1	X2	Y1	Y2
1 2	1	Me Me	Direct bond Direct bond	Ph Ph	Ph Me	Ph Me
3	1	Me	Direct bond	Ph	Ph	
4	1	Me	Direct bond	Ph	Ph	
5	1	Me	Direct bond	Ph	Ph -	Me Me

TABLE 1-continued

				17 IBBE 1 CORE		
	n	R1, R2	X1	X2	Y1	Y2
6	1	Me	Direct bond	Ph	Ph	
7	1	Me	Direct bond	Ph	Ph	
8	1	Me	Direct bond	Ph	Ph	
9	1	Me	Direct bond		Me	————Me
10	1	Me	Direct bond			
					Me	Me
11	1	Me	Direct bond	<u> </u>		Me
12	1	Me	Direct bond		Me	————Me
13	1	Me		Н	Ph	Ph
14	1	Me		Н	Me	Me
15	1	Me		H -	Ph	
			\ <u>_</u> /			

TABLE 1-continued

	n	R1, R2	X1	X2	Y1	Y2
16	1	Me		Н	Ph	
17	1	Me		Н	Ph	
18	1	Me		Н	Ph	
19	1	Me		Ph	Ph	Ph
20	1	Me		Ph	———Me	Me

TABLE 2

	n	R1, R2	X1	X2	Y1	Y2
21	1	Me		Ph	Ph	
22	1	Me		Ph	Ph	Me Me
23	1	Me			Me	Me
24	1	Me			Me Me	Me
25	1	Me			Ph	

TABLE 2-continued

n	R1, R2	X1	X2	Y1	Y2
26 1	Me			————Me	———Me
27 1	Me			————Me	————Me
28 1	Me			Ph	
29 1	Me	Me	Н	Me	Me
30 1	Me	Me'	н	Me	Me
31 1	Me	F F		Me	————Me
32 1	Me	F F	н	Me	Me
33 1	Me		Н	Me	Me
34 1	Me		н	Me	————Me

X1

R1, R2

Y2

TABLE 2-continued

	n	R1, R2	X1	X2	<b>Y</b> 1	Y2
35	1	Me			———Me	Me Me
36	1	Me		н	————Me	————Me

TABLE 3

Y1

X2

37 1	Me		Н	Me	Me
38 1	n-Bu		Н	Me	———Me
39 1	n-Bu			———Me	Me
40 1	Ph		Н	Me	———Me
41 1	Ph			————Me	————Me
42 2	Me	Direct bond	Н	Ph	Ph
43 2	Me	Direct bond	Н	Me	———Me
44 2	Ме	Direct bond	Н	Me Si Me	Me   Me   Me   Me   Me   Me   Me   Me
45 2	Ме	Direct bond	Н	Ph	

TABLE 3-continued

				TABLE 3-conti	nued	
	n	R1, R2	X1	X2	Y1	Y2
46	2	Me	Direct bond	Н	Ph	
47	2	Me	Direct bond	Н	Ph	Me Me
48	2	Me	Direct bond	Н	Ph	
49	2	Me	Direct bond	Н	Ph	
50	2	Me	Direct bond	Н	Ph	
51	2	Me	Direct bond	Ph	Me	Me
52	2	Me	Direct bond	Ph	Ph	
53	2	Me	Direct bond	Ph	Ph	Me Me
54	2	Me	Direct bond	Ph	Ph	<b>—</b>
55	2	Me	Direct bond		Me	Me
56	2	Me	Direct bond		Me	Me

TABLE 4

_						
_		R1, R2	X1	X2	Y1	Y2
57	2	Me	Direct bond		Me	Me
58	2	Ме	Direct bond		Me	Me
59	2	Me		Н	Ph	Ph
60	2	Me		Н	Me	Me
61	2	Ме		Н	-0-0	0
62	2	Me		Н	Ph	
63	2	Me		Н	Ph	
64	2	Me		Н	Ph	Me Me
65	2	Me		Н	Ph	
66	2	Me		Н	Ph	
67	2	Ме		Н	Ph	

TABLE 4-continued

				-continued	
n	R1, R2	X1	X2	Y1	Y2
68 2	. Me		Н	Ph	
69 2	. Me		Ph	Ph	Ph
70 2	. Me		Ph	Me	Me
71 2	. Me		Ph	Ph	
72 2	. Me		Ph	Ph	Me Me
73 2	. Me		Ph	Ph	
74 2	. Me			Me	Me
75 2	. Me			Me	Me
76 2	. Me			Ph	

TABLE 5

	n	R1, R2	X1	X2	Y1	Y2
77	2	Me			Me	Me

TABLE 5-continued

	n	R1, R2	X1	X2	Y1	Y2
78	2	Me				Te Me
79	2	Me			Ph	
80	2	Me	Me	н -	M	re Me
81	2	Me	F F	н	M	de Me
82	2	Me	F F		M	re Me
83	2	Me	-0-	н -	M	re Me
84	2	Me		н -	M	Te Me
85	2	Me		н -	M	de Me
86	2	Me			M	re Me

TABLE 5-continued

				II IBEE 5 COMMISCO		
	n	R1, R2	X1	X2	Y1	Y2
87	2	Ме		Н	Me	Me
88	2	Ме		Н	Me	Me
89	2	n-Bu		Н	Me	Me
90	2	n-Bu			Me	Me
91	3	Me	Direct bond	Н	Ph	Ph
92	3	Me	Direct bond	Н	Me	Me
93	3	Me	Direct bond	Н	Ph	
94	3	Me	Direct bond	Н	Ph	

TABLE 6

	n	R1, R2	X1	X2	Y1	Y2
95	3	Me	Direct bond	Н	Ph	Me Me
96	3	Me	Direct bond	Н	Ph	
97	3	Me	Direct bond	Н	Ph	

TABLE 6-continued

				IABLE 6-co	onunued	
	n	R1, R2	X1	X2	Y1	Y2
98	3	Me	Direct bond	Н	Ph	
99	3	Me	Direct bond	Н	Ph	
100	3	Me	Direct bond	Н -		
101	3	Me	Direct bond	Н	Me	Me
102	3	Me	Direct bond	Ph	Ph	
103	3	Me	Direct bond	Ph	Ph	Me Me
104	3	Me	Direct bond	Ph	Ph	
105	3	Me	Direct bond		Me	Me
106	3	Me	Direct bond		————Me	Me Me
107	3	Me	Direct bond		Me	Me
108	3	Me	Direct bond		————Me	Me Me

TABLE 6-continued

n R1, R2	X1	X2	Y1	Y2
109 3 Me		Н	Me	Me Me
110 3 Me		Н	Ph	
111 3 Me		Н	Ph	Me Me
112 3 Me		Н	Ph	
113 3 Me		Н	Ph	
114 3 Me		Н	Ph	

TABLE 7

	n	R1, R2	X1	X2	Y1	Y2
115	3	Me		Ph	Me	e Me
116	3	Me			Me	e Me
117	3	Me			Me	e Me
118	3	Me			Ph	

TABLE 7-continued

	n	R1, R2	X1	X2	Y1	Y2
119	3	Me			Me	Me Me
120	3	Me			Ph	
121	3	Me	Me	Н	Me	Me
122	3	Me	F	Н	Me	Me Me
123	3	Me	F		Me	Me Me
124	3	Me		Н		Me Me
125	3	Me		Н	Me	Me
126	3	Me		Н	Me	Me
127	3	Me			Me	Me Me

TABLE 7-continued

	n	R1, R2	X1	X2	Y1	Y2
128	3	Me		Н -	Me	Me Me
129	3	Me		Н -	Me Me	————Me
130	3	n-Bu		Н -	Me Me	
131	3	n-Bu			Me	Me

TABLE 8

	n	R1, R2	X1	X2	Y1	Y2
132	3	Me	Direct bond	Н	Ph	Ph
133	3	Me	Direct bond	Н	Me	Me
134	3	Me	Direct bond	Н	Ph	
135	3	Me	Direct bond	Н	Ph	
136	3	Me	Direct bond	Н	Ph	Me Me
137	3	Me	Direct bond	Н	Ph	
138	3	Me	Direct bond	Н	Ph	

TABLE 8-continued

	n	R1, R2	X1	X2	Y1	Y2
139	3	Me	Direct bond	Н	Ph	
140	3	Me	Direct bond	Н	Ph	
141	3	Me	Direct bond	Н -		
142	4	Me		Н	Me	Me
143	4	Me		Н	Ph	
144	4	Me		Н	Ph	
145	4	Me			Me	Me
146	4	Me			Me	Me
147	4	Me			Ph	
148	4	Me	Me	Н	Me Me	————Me

TABLE 8-continued

	n	R1, R2	X1	X2	Y1	Y2
149	4	Ме	F F	Н	Me	Me Me
150	4	Me		Н	Me	Me

				TABLE 9		
	n	R1, R2	X1	X2	Y1	Y2
151	4	Ме		Н	————Me	,Me
152	4	Me		Н.	Me	Me Me
153	4	Me		Н	————Me	Me Me
154	4	n-Bu		Н	Me	Me Me
155	4	n-Bu			Me	Me Me
	\ N-		Me Me Me	Me	[1]-156	

TABLE 9-continued

TABLE 10

	p, q	R3, R4	R5, R6	X3	X4	X5	Y3	Y4
1	1, 1	Me	Me	Single bond		H —	Ме	Ph
2	1,1	Me	Me	Single bond		Н	Ph	Ph
3	1, 1	Me	Me	Single bond		H —	Me	Me

TABLE 10-continued

	p, q	R3, R4	R5, R6	X3	X4	X5	Y3	Y4
4	1,1	Me	n-Bu	Single bond		Н	Me	Me
5	1,1	n-Bu	n-Bu	Single bond		Н	Me	Me
6	1,1	Me	Me	Single bond		Н		
7	1,1	Me	Me	Single bond		Н -		
8	1,1	Me	Me	Single bond		Н	Ph	
9	1,1	Me	Me	Single bond		H —	Ph	
10	1,1	Me	Me	Single bond		H —	Ph	Me Me
11	1,1	Me	Me	Single bond		Н	Ph	
12	1,1	Me	Me	Single bond		Н	Ph	
13	1,1	Me	Me	Single bond		Н	Ph	
14	1,1	Me	Me	Single bond		Н	Ph	

TABLE 10-continued

	p, q	R3, R4	R5, R6	X3	X4	X5	Y3	Y4
15	1,1	Me	Me	Single bond	Me	Н	Me	Me
16	1,1	Me	Me	Single bond	Me	Н	Ph	
17	1,1	Me	Me	Single bond	F F	Н	Me	Me
18	1,1	Me	Ме	Single bond	F	н	Ph	
19	1,1	Me	Me	Single bond	\sqrt{s}	. Н	————Me	Me
20	1,1	Me	Me	Single bond	s	. н	Ph	
21	1,1	Me	Me	Single bond		Н	Me	————Me

TABLE 11

	p, q	R3, R4	R5, R6	X3	X4
22	1,1	Me	Me	Single bond	
23	1,1	Me	Me	Single bond	Me Si 

TABLE 11-continued

				TABLE 11-co	ontinued
24	1,1	Me	Me	Single bond	Me 
25	1,1	Me	Me	Single bond	~~~~~~~~~~~~~~~~~~~~~~~~~~~~~~~~~~~~~~
26	1,1	Me	Me	Single bond	
27	1, 1	Me	Me	Single bond	
28	1,1	Me	Me	Single bond	
29	1, 1	Me	Me	Single bond	
30	1,1	Me	Me	Single bond	
31	1,1	Me	Me	Single bond	
32	1,1	Me	Me	Single bond	
33	1, 1	Me	Me	Single bond	
34	1, 2	Me	Me	Single bond	

TABLE 11-continued

				TABLE 11-conti	nued
35	1, 2	Me	Me	Single bond	
36	1,2	Me	Me	Single bond	
37	1, 2	Me	Me	Single bond	
38	1,2	Me	Ме	Single bond	F F
39	1,2	Me	Me	Single bond	Me 
40	1,1	Me	Me		
41	1,1	Me	Me		
42	1,1	Me	Ме	F	
			X5	Y3	Y4
		2	12 H	Ph	
		2	.3 Н	Me Me	Me
		2	14 H	Ph	
		2	25 Н —	Me	Me

TABLE 11-continued

TABLE 11-continued

TABLE 12

	p, q	R3, R4	R5, R6	X3	X4
43	1,1	Me	Me		
44	1,1	Me	n-Bu		
45	1,1	n-Bu	n-Bu		
46	1,1	Me	Ме		Me
47	1,1	Me	Ме		F F
48	1, 1	Me	Me		S
49	1,1	Me	Me		
50	1,1	Me	Me		Me   Si       Me

TABLE 12-continued

51	1,1	Me	Me		Me C Me
52	1,1	Me	Me		
53	1,1	Me	Me		
54	1,1	Me	Me		
55	1,1	Me	Me		
56	1,1	Me	Me		
57	1, 2	Me	Me		Me   Si       Me
58	1, 2	Me	Me		
59	1,1	Me	Me	Single bond	
60	1,1	Me	Me	Single bond	
61	1,1	Me	Me	Single bond	

TABLE 12-continued

		12-continued
62 1,1 Me	Me Single bor	
	X5	Y3 Y4
43	Н	Me
44	Н	Me
45	Н	Me
46	Н	Me
47	Н	Me
48	Н	Me
49	Н	Me Me
50	н	
51	н	Me
52	Н	Me Me
53	Н	Me Me
54	Н	Me
55	Н	Me
56	Н	Me
57	Н	Me

TABLE 12-continued

TABLE 13

	p, q	R3, R4	R5, R6	X3	X4	X5
63	1,1	Ме	Ме	Single bond		
64	1,1	Me	Me	Single bond		
65	1,1	Me	Me			Ph
66	1,1	Me	Me			
67	1,1	Me	Me			

TABLE 13-continued

				IADLE	3-continued	
68	1,1	Me	Me			
69	1, 1	Me	Me			
70	1,1	Me	Me			
71	2, 2	Me	Me	Single bond		Н
72	2, 2	Me	Me	Single bond		Н
73	2, 2	Me	Me	Single bond		Н
74	2, 2	Me	n-Bu	Single bond		Н
75	2, 2	n-Bu	n-Bu	Single bond		Н
76	2, 2	Me	Me	Single bond		Н
77	2, 2	Me	Me	Single bond		Н
78	2, 2	Me	Me	Single bond		Н
79	2, 2	Me	Me	Single bond		Н
80	2, 2	Me	Me	Single bond		Н
81	2, 2	Me	Me	Single bond		Н

TABLE 13-continued

TABLE 13-continued									
82	2, 2	Me	Me	Single bond		н			
83	2, 2	Me	Me	Single bond		н			
84	2, 2	Me	Me	Single bond		Н			
				Y3		Y4			
		6	3		Ме	Me			
		6	4		Ме	Me			
		6	5		Ме	Me			
		6	6		Ме	Me			
		6	7		Ме	Me			
		6	8		Me	Me			
		6	9		Me	Me			
		7	0		Ме	Me			
		7 7	1 2	Me Ph		Ph Ph			
		7	3		Ме	Me			
		7	4		Ме	————Me			
		7	5		Ме	Me			
		7	6						

TABLE 13-continued

[3]

55

TABLE 13-continued

Next, the organic light-emitting device of the present invention will be described in detail.

The organic light-emitting device of the present invention is an organic light-emitting device comprising: a pair of electrodes which consist of an anode and a cathode, and one or more layers which are interposed between the electrodes and contain an organic compound, wherein at least one layer of the layers containing an organic compound contains at least one of the monoaminofluorene compounds represented by the above-mentioned general formula [1] or [2].

Moreover, it is preferable that the layer containing the compound represented by the above-mentioned general formula [1] or [2] contains at least one of the compounds represented by following general formulae [3] to [7], and it is more preferable that the layer containing the compound represented by the above-mentioned general formula [1] or [2] is a light-emitting layer.

$$Ar_{2} \xrightarrow{Ar_{1}} R_{9}$$

$$Ar_{3} = R_{8}$$

wherein  $Ar_1$  to  $Ar_3$  may be the same or different and are groups selected from the group consisting of substituted or unsubstituted aryl and heterocyclic ring groups, and either one of them may be a hydrogen atom, a substituted or unsubstituted alkyl group, or a substituted or unsubstituted aralkyl group; and  $R_7$  to  $R_9$  are groups selected from the group consisting of a hydrogen atom, a halogen group, substituted or unsubstituted alkyl and aralkyl groups, a substituted amino group and a cyano group.

$$Ar_5$$
 $R_{10}$ 
 $R_{10}$ 

wherein Ar<sub>4</sub> to Ar<sub>7</sub> may be the same or different and are groups selected from the group consisting of substituted or

unsubstituted aryl and heterocyclic ring groups; and  $R_{10}$  and  $R_{11}$  are groups selected from the group consisting of a hydrogen atom, a halogen group, substituted or unsubstituted alkyl and aralkyl groups, a substituted amino group and a cyano group.

$$\begin{array}{c}
Ar_{9} \\
Ar_{10} \\
Ar_{11}
\end{array}$$

$$\begin{array}{c}
Ar_{12} \\
Ar_{11}
\end{array}$$

wherein  ${\rm Ar_8}$  to  ${\rm Ar_{12}}$  may be the same or different and are groups selected from the group consisting of substituted or unsubstituted aryl and heterocyclic ring groups; and  ${\rm R_{12}}$  is a group selected from the group consisting of a hydrogen atom, a halogen group, substituted or unsubstituted alkyl, aralkyl, aryl and heterocyclic ring groups, a substituted amino group and a cyano group.

$$Ar_{13}$$
 $R_{13}$ 
 $Ar_{15}$ 
 $Ar_{14}$ 
 $Ar_{16}$ 
 $R_{16}$ 

wherein  $Ar_{13}$  to  $Ar_{16}$  may be the same or different and are groups selected from the group consisting of substituted or unsubstituted aryl and heterocyclic ring groups, and up to any three of them may be a hydrogen atom, a halogen group, a substituted or unsubstituted alkyl group and a substituted or unsubstituted aralkyl group; and  $R_{13}$  to  $R_{16}$  are groups selected from the group consisting of a hydrogen atom, a halogen group, substituted or unsubstituted alkyl, aralkyl, aryl and heterocyclic ring groups, a substituted amino group and a cyano group.

$$R_{19}$$
 $R_{17}$ 
 $R_{18}$ 
 $R_{20}$ 
 $R_{21}$ 

wherein  $R_{17}$  and  $R_{18}$  are groups selected from the group consisting of a hydrogen atom and substituted or unsubstituted alkyl, aralkyl and aryl groups, and  $R_{17}$ 's and  $R_{18}$ 's bound to different fluorene moieties may be the same or 15 different and R<sub>17</sub> and R<sub>18</sub> bound to the same fluorene moiety may be the same or different;  $R_{19}$  to  $R_{22}$  are groups selected from the group consisting of a hydrogen atom, a halogen group, substituted or unsubstituted alkyl and aralkyl and alkoxy groups, a substituted silyl group and a cyano group; 20 the compound represented by general formulae [3] to [7] are and s is an integer of 2 to 5.

Although the compounds represented by general formulae [3] to [7] can be used for the purpose of both the dopant material and host material in a light-emitting layer respectively to obtain a device with high color purity, high luminescence efficiency and longer operating life, a device holding high color purity luminescence and having even higher luminescence efficiency can be obtained with the combination of a compound represented by the general formula [1] or [2] as a dopant material with a suitable host material which easily causes energy transfer, for example, the compounds represented by general formulae [3] to [7]. The dopant concentration in the host material is preferably from 0.01% to 50% by weight, more preferably from 0.5% to 10% by weight.

Specific examples of the substituents in general formulae [3] to [7] are the same as those referred to in the abovementioned general formulae [1] and [2]. Typical examples of given below but the present invention is not limited to these.

$$Ar_{2} \xrightarrow{Ar_{1}} R_{9}$$

$$Ar_{3} \xrightarrow{R_{7}} R_{8}$$

$$\begin{array}{c} A_{r_{4}} \\ A_{r_{5}} \\ A_{r_{7}} \end{array}$$

$$\begin{array}{c} A_{r_{4}} \\ A_{r_{7}} \\ A_{r_{7}} \end{array}$$

$$\begin{array}{c} A_{r_{4}} \\ A_{r_{7}} \\ A_{r_{7}} \end{array}$$

$$[4]-14 \qquad [5]$$


$$N \longrightarrow Ar_{9} \longrightarrow Ar_{12}$$

$$Ar_{10} \longrightarrow Ar_{12}$$

$$Ar_{11} \longrightarrow Ar_{12}$$

[5]-3

[6]



The preferable examples of the organic light-emitting device of the present invention are shown in FIGS. 1 to 6.

FIG. 1 is a cross-sectional view showing an example of the organic light-emitting device according to the present invention. FIG. 1 shows a structure in which an anode 2, a light-emitting layer 3 and a cathode 4 are formed on a substrate 1 in this order. The light-emitting device used here is useful in the case where it has all the properties of hole-transporting ability, electron-transporting ability and the light-emitting ability by itself, or in the case where compounds having each of these properties respectively are mixed and used.

FIG. 2 is a cross-sectional view showing another example of the organic light-emitting device according to the present invention. FIG. 2 shows a structure in which an anode 2, a hole-transporting layer 5, an electron-transporting layer 6 and a cathode 4 are formed on a substrate 1 in this order. This 45 structure is useful in the case where a light-emitting material having either one or both of hole-transporting ability and electron-transporting ability is used for the respective layer in combination with a hole-transporting or electron-transporting compound which has no light-emitting properties. A light-emitting layer 3 consists of either the hole-transporting layer 5 or the electron-transporting layer 6 in this case.

FIG. 3 is a cross-sectional view showing another example of the organic light-emitting device of the present invention. FIG. 3 shows a structure in which an anode 2, a hole-transporting layer 5, a light-emitting layer 3, an electron-transporting layer 6 and a cathode 4 are formed on a substrate 1 in this order. Since this structure separates the functions of carrier transport and luminescence, it can be used in a suitable combination with compounds having hole-transporting ability, electron-transporting ability and light-emitting ability, thus extremely enhancing the flexibility of selection of materials and enabling various compounds which differ in luminescence wavelength to be used, thereby enabling diversification of luminescence hue. Furthermore, it also becomes possible to effectively confine each of the carriers or excitons in the 65 light-emitting layer 3 positioned in the middle, and to aim at improvement in luminescence efficiency.

FIG. 4 is a cross-sectional view showing another example of the organic light-emitting device of the present invention. FIG. 4 shows a structure in which a hole injecting layer 7 is inserted in the side of an anode 2 as compared with that of FIG. 3 and that has an effect in improving the close contact of the anode 2 and a hole-transporting layer 5 or improving hole injecting properties and is effective for reduction in voltage.

FIGS. 5 and 6 are cross-sectional views showing other examples of the organic light-emitting device of the present invention. FIGS. 5 and 6 show structures in which a layer inhibiting holes or excitons from escaping to the side of a cathode 4 (hole blocking layer 8) is inserted between a light-emitting layer 3 and an electron-transporting layer 6, in comparison with the structures of FIGS. 3 and 4. By using a compound having a very high ionization potential as the hole blocking layer 8, these structures are effective for improving the luminescence efficiency.

However, FIGS. 1 to 6 merely show very fundamental device structures, and the construction of the organic light-emitting device using the compound of the present invention is not limited to these. For example, various layer configurations can be taken including providing an insulating layer on the interface between the electrode and the organic layer, providing an adhesive layer or interference layer, or making a hole-transporting layer consisting of two layers different in ionization potential.

The monoaminofluorene compound represented by the general formula [1] or [2] used for the present invention can be used in any embodiment of FIGS. 1 to 6.

Especially the organic layer using the compound of the present invention is useful as a light-emitting layer, an electron-transporting layer or a hole-transporting layer, and the layer formed by the vacuum evaporation method, the solution applying method or the like is excellent in stability with the passage of time since crystallization thereof cannot readily take place.

Although the present invention uses the monoaminofluorene compound represented by the general formula [1] or [2] particularly as a component of a light-emitting layer, it can

also be used, if needed, together with a hole-transporting compound, a luminescent compound or an electron-transporting compound known in the art.

Examples of these compounds are given below.

Hole-transporting Compound

Electron-transporting Light-emitting Material

45

50

-continued

-continued

Light-emitting Material

$$C_{2}H_{5}$$
 $C_{2}H_{5}$ 
 $C_{2}H_{5}$ 
 $C_{2}H_{5}$ 
 $C_{2}H_{5}$ 

$$H_3C$$
 $CN$ 
 $C_2H_5$ 
 $C_2H_5$ 
 $C_2H_5$ 

$$C_2H_5$$
 $C_2H_5$ 
 $C$ 

Matrix Material of Light-emitting Layer and Electron-transporting Material

$$H_3C$$
 $CH$ 
 $CH$ 
 $CH$ 
 $CH$ 
 $CH$ 

Hole-transporting Polymer Material

$$\begin{array}{c} CH - CH_2 \frac{1}{12} \\ PVC_2 \end{array}$$

30

35

113

Light-emitting and Electron-transporting Polymer Material

$$C_{6}H_{13}O$$
 $C_{6}H_{13}O$ 
 $C_{6}H_{13}O$ 
 $C_{6}H_{13}O$ 
 $C_{12}H_{25}$ 
 $C_{12}H_{25}$ 
 $C_{12}H_{25}$ 
 $C_{12}H_{25}$ 
 $C_{12}H_{25}$ 
 $C_{6}H_{13}O$ 

In the organic light-emitting device of the present invention, the layer containing the monoaminofluorene compound represented by the general formula [1] or [2] and the layer consisting of other organic compounds can be generally formed into a thin film by the vacuum evaporation method or by the applying method by dissolving the compounds in a suitable solvent. When film forming is conducted especially by the applying method, the film can also be formed in combination with a suitable binding resin.

The above-mentioned binding resin can be selected from a wide range of binding resins and examples thereof include poly(vinyl carbazole) resin, polycarbonate resin, polyester resin, polyallylate resin, polystyrene resin, acrylic resin, 50 methacrylic resin, butyral resin, poly(vinyl acetal) resin, diallyl phthalate resin, phenol resin, epoxy resin, silicone resin, polysulphone resin, urea resin, etc. but are not limited to these. These resins may be used alone or mixed as a copolymerized polymer of one or more types of them.

As an anode material, those having as high a work function as possible is suitable, and for example, a metal element such as gold, platinum, nickel, palladium, cobalt, selenium, and vanadium, or alloys thereof, and metal oxides such as tin oxide, zinc oxide, indium tin oxide (ITO) and indium zinc 60 oxide can be used. Conductive polymers such as polyaniline, polypyrrole, polythiophene and polyphenylenesulfide can also be used. These electrode substances may be used alone and two or more of them can also be used in combination.

On the other hand, as a cathode material, those having a low 65 work function is suitable and a metal element such as lithium, sodium, potassium, calcium, magnesium, aluminum, indium,

114

silver, lead, tin and chromium or alloys of two or more thereof can be used. Use of a metal oxide such as indium tin oxide (ITO) is also possible. The cathode may be in a single layer structure or can take a multilayer structure.

Substrate used in the present invention is not limited, but a non-transparent plate such as metal substrate and ceramics substrate, a transparent plate such as glass, quartz, and a plastic sheet can be used. It is also possible to use a color filter film, a fluorescent color conversion filter film, a dielectric reflective film, etc. on the substrate to control the color of the emitted light.

In addition, a protection layer or seal layer can also be provided on the formed device in order to prevent contact with oxygen, moisture, etc. The protection layer may include inorganic material films such as a diamond thin film, a metal oxide film and a metal nitride film, polymer films such as those of a fluororesin, polyparaxylene, polyethylene, silicone resin and polystyrene resin as well as light curable resin, etc. Moreover, the device may be covered with glass, a gas impermeable film, metal, etc., and the device itself may be packaged in a suitable sealing resin.

Hereainfter, the present invention will be described by non-limiting examples still more specifically.

### **EXAMPLE 1**

Preparation Process of Example Compound No. [1]-43

2 g (6.25 mmol) of 2-iodo-9,9-dimethylfluorene and 1.5 g (4.12 mmol) of 2-(dihydroxyboranyl)-9,9-dimethylfluorene were dissolved in the mixed solvent (80 ml of degassed toluene and 40 ml of ethanol) and agitated under nitrogen flow, and 41 ml of sodium carbonate solution which was prepared by dissolving 9 g of anhydrous sodium carbonate in 45 ml of water was added dropwise thereto. After agitating for 30 minutes, 238 mg (0.206 mmol) of tetrakis(triphenylphosphine) palladium was added. Heating with agitation was carried out on the oil bath heated at 80° C. for about 5 hours. After cooling the reaction solution to room temperature, 50 ml of 25 water and 50 ml of ethyl acetate were added, the aqueous layer and the organic layer were separated, the aqueous layer was further extracted with toluene and ethyl acetate, and the extract combined with the above organic layer was dried over magnesium sulfate. The solvent was evaporated, the residual  $\ _{30}$ substance was refined by silica gel column chromatography (toluene:hexane=1:2), and 1.5 g of bis(9,9-dimethylfluorene) was obtained.

116

4.2 g (10.9 mmol) of bis(9,9-dimethylfluorene), 1.38 g (5.43 mmol) of iodine and 0.5 g of 50% sulfuric acid were dissolved in 80 ml of methanol and agitated with heating on the oil bath heated at 60° C., and about 1 g of 35% by weight aqueous hydrogen peroxide was added dropwise thereto. After cooling the reaction solution to room temperature, 30 ml of water was added and the deposited crude crystal was separated by filtration. The crude crystal was refined by silica gel column chromatography (toluene:hexane=1:2), and 5.0 g of monoiodide of bis(9,9-dimethylfluorene) was obtained.

113 mg (0.2 mmol) of palladium bis(benzylideneacetone) and 120 mg (0.6 mmol) of tri-tert-butylphosphine were dissolved in 40 ml of toluene under nitrogen flow, and agitated at room temperature for 15 minutes. 1.02 g (2 mmol) of monoiodide of bis(9,9-dimethylfluorene) dissolved in 50 ml of toluene was added dropwise thereto, and agitated for 30 minutes. 0.59 g (3 mmol) of bis(4-methylphenyl)amine dissolved in 50 ml of toluene was also added dropwise thereto, and subsequently 0.43 g (4.5 mmol) of sodium tert-butoxide was added. Heating with agitation was carried out on the oil bath heated at 120° C. for about 8 hours. After cooling the reaction solution to room temperature, 50 ml of water was added, the aqueous layer and the organic layer were separated, the aqueous layer was further extracted with toluene and ethyl acetate, and the extract combined with the above organic layer was dried over magnesium sulfate. The solvent was evaporated, the residual substance was refined by silica gel column chromatography (toluene:hexane=1:2), and 0.93 g of example compound [1]-43 was obtained.

# EXAMPLE 2

Preparation Process of Example Compound No. [1]-60

1.02 g (2 mmol) of monoiodide of bis(9,9-dimethylfluorene) and 0.97 g (3 mmol) of bis(4-methylphenyl)aminobenzene-4-boronic acid were dissolved and agitated under nitrogen flow in the mixed solvent (140 ml of degassed toluene and 70 ml of ethanol), and 30 ml of sodium carbonate solution 5 which was prepared by dissolving 6 g of anhydrous sodium carbonate in 30 ml of water was added dropwise thereto. After agitating for 30 minutes, 174 mg (0.15 mmol) of tetrakis (triphenylphosphine)palladium was added. Heating with agitation was carried out on the oil bath heated at 80° C. for about 5 hours. After cooling the reaction solution to room temperature, 70 ml of water and 70 ml of ethyl acetate were added, the aqueous layer and the organic layer were separated, the aqueous layer was further extracted with toluene and ethyl acetate, and the extract combined with the above organic layer was dried over magnesium sulfate. The solvent was evaporated, 15 the residual substance was refined by silica gel column chromatography (toluene:hexane=1:2), and 1 g of example compound [1]-60 was obtained.

### **EXAMPLE 3**

Preparation Process of Example Compound No. [2]-40

118

6.94 g (21.7 mmol) of 2-iodo-9,9-dimethylfluorene and 1 g (7.25 mmol) of 1,4-phenylenebis(boronic acid) were dissolved and agitated under nitrogen flow in the mixed solvent (120 ml of degassed toluene and 60 ml of ethanol), and 145 ml of sodium carbonate solution which was prepared by dissolving 30 g of anhydrous sodium carbonate in 150 ml of water was added dropwise thereto. After agitating for 30 minutes, 840 mg (0.727 mmol) of tetrakis(triphenylphosphine) palladium was added. Heating with agitation was carried out on the oil bath heated at 80° C. for about 3 hours. After cooling the reaction solution to room temperature, 50 ml of water and 50 ml of ethyl acetate were added, the aqueous layer and the organic layer were separated, the aqueous layer was further extracted with toluene and ethyl acetate, and the extract combined with the above organic layer was dried over magnesium sulfate. The solvent was evaporated, the residual substance was refined by silica gel column chromatography (toluene: hexane=1:2), and 3.02 g of 1,4-phenylenebis(9,9-dimeth-<sub>20</sub> ylfluorene) was obtained.

5.04~g~(10.9~mmol)~of~1,4-phenylenebis(9,9-dimethylfluorene), 1.38~g~(5.43~mmol)~of~iodine~and~0.5~g~of~50% sulfuric acid were dissolved in 120 ml of methanol. Heating with

agitation was carried out on the oil bath heated at 60° C., and about 1 g of 35 wt % aqueous hydrogen peroxide was added dropwise thereto. After cooling the reaction solution to room temperature, 30 ml of water was added and the deposited crude crystal was separated by filtration. The crude crystal says refined by silica gel column chromatography (toluene: hexane=1:2), and 5.9 g of monoiodide of 1,4-phenylenebis (9,9-dimethylfluorene) was obtained.

1.18 g (2 mmol) of monoiodide of 1,4-phenylenebis(9,9dimethylfluorene) and 0.97 g (3 mmol) of bis(4-methylphe- 10 nyl)aminobenzene-4-boronic acid were dissolved and agitated under nitrogen flow in the mixed solvent (100 ml of degassed toluene and 50 ml of ethanol), and 30 ml of sodium carbonate solution which was prepared by dissolving 6 g of anhydrous sodium carbonate in 30 ml of water was added 15 dropwise thereto. After agitating for 30 minutes, 174 mg (0.15 mmol) of tetrakis(triphenylphosphine)palladium was added. Heating with agitation was carried out on the oil bath heated at 80° C. for about 5 hours. After cooling the reaction solution to room temperature, 60 ml of water and 60 ml of 20 ethyl acetate were added, the aqueous layer and the organic layer were separated, the aqueous layer was further extracted with toluene and ethyl acetate, and the extract combined with the above organic layer was dried over magnesium sulfate. The solvent was evaporated, the residual substance was 25 refined by silica gel column chromatography (toluene:hexane=1:2), and 1.09 g of example compound [2]-40 was obtained.

### **EXAMPLE 4**

The organic light-emitting device of the structure shown in FIG. 3 was prepared by the process shown below.

A glass substrate as the substrate 1 on which a film of indium tin oxide (ITO) having a film thickness of 120 nm as  $_{35}$  the anode 2 was formed by sputtering method was used as a transparent conductive support substrate. This substrate was subjected to ultrasonic washing in acetone and isopropyl alcohol (IPA) subsequently, boil-washed in IPA and dried. It was further subjected to UV/ozone washing and used as a  $_{40}$  transparent conductive support substrate.

The compound shown by the following structural formula was used as a hole-transporting material and a chloroform solution thereof was adjusted so that the concentration thereof was 0.5% by weight.

This solution was dropped on the above ITO electrode (anode 2), and spin coating was performed first by rotation at 500 RPM for 10 seconds followed by rotation at 1000 RPM for 1 minute to form a film. It was subsequently dried in a vacuum oven at 80° C. for 10 minutes, and the solvent in the thin film was removed completely. The thickness of the formed TPD film (hole-transporting layer 5) was 50 nm.

Next, vacuum evaporation of the above-mentioned 65 example compound No. [1]-43 was carried out to deposit the compound on the hole-transporting layer **5**, and the 20 nm-

120

thick light-emitting layer 3 was formed. The degree of vacuum at the time of vacuum evaporation was  $1.0 \times 10^{-4}$  Pa, and the film forming speed was 0.2 to 0.3 nm/sec.

Furthermore, aluminum quinolinol (Alq3) was formed into a film of 40 nm in thickness as an electron-transporting layer 6 by vacuum evaporation method. The degree of vacuum at the time of the vacuum evaporation of these organic layers was  $1.0 \times 10^{-4}$  Pa, and the film forming speed was 0.2 to 0.3 nm/sec.

Next, using the vacuum evaporation source material consisting of an aluminum-lithium alloy (lithium concentration 1 atom %), a metal film with a thickness of 10 nm was formed by vacuum evaporation method on the above organic layer, the aluminum film with a thickness of 150 nm was further prepared by vacuum evaporation method, and the organic light-emitting device comprising an aluminum-lithium alloy film as an electron injection electrode (cathode 4) was prepared. The degree of vacuum at the time of vacuum evaporation was  $1.0 \times 10^{-4}$  Pa, and the film forming speed was 1.0 to 1.2 nm/sec.

The obtained organic EL device was covered with a glass plate for protection in dry air atmosphere, and sealed with an acrylic resin based adhesive so that the device might not be degraded by adsorption of moisture.

6V was applied to the thus obtained device by using an ITO electrode (anode 2) as a positive electrode and an Al—Li electrode (cathode 4) as a negative electrode. As the result, and blue luminescence of 780 cd/m² of luminance, maximum luminance of 5900 cd/m², and luminescence efficiency 0.73 lm/W were observed.

# EXAMPLES 5 TO 13

Devices were formed in the same way as in Example 4 except that example compound [1]-43 was replaced with the example compounds shown in Table 14 and evaluated in the same way. The results are shown in Table 14.

TABLE 14

Example	Example compound No.	Applied voltage (V)	Luminance (cd/m²)	Maximum luminance (cd/m²)	Efficiency (1m/W)
5	[1]-16	7	680	5000	0.57
6	[1]-49	6	880	6700	0.75
7	[1]-60	6	840	6100	0.83
8	[1]-92	6	900	6600	0.77
9	[1]-95	6	1000	6800	0.85
10	[1]-158	6	820	6400	0.72
11	[2]-17	6	820	5700	0.80
12	[2]-65	6	980	6800	0.87
13	[2]-85	6	810	5900	0.68

### EXAMPLE 14

A device was formed in the same way as in Example 4 except that example compound No. [1]-60 and example compound No. [3]-1 were co-deposited (5:100 in weight ratio) to form 20 nm-thick light-emitting layer 3.

6V was applied to the thus obtained device by using an ITO electrode (anode 2) as a positive electrode and an Al—Li electrode (cathode 4) as a negative electrode. As the result,

10

15

121

blue luminescence of  $4200 \text{ cd/m}^2$  of luminance, maximum luminance of  $9600 \text{ cd/m}^2$ , and luminescence efficiency 1.20 lm/W were observed.

# EXAMPLES 15 TO 23

Devices were formed in the same way as in Example 10 except that example compound [1]-60 was replaced with the example compounds shown in Table 15 and evaluated in the same way. The results are shown in Table 15.

TABLE 15

Example	Example compound No.	Applied voltage (V)	Luminance (cd/m²)	Maximum luminance (cd/m²)	Efficiency (1m/W)
15	[1]-6	7	2900	6500	0.67
16	[1]-47	6	6800	17200	1.74
17	[1]-49	6	6300	16600	1.62
18	[1]-80	6	5100	11500	1.30
19	[1]-91	6	5200	13100	1.42
20	[1]-99	6	6900	16500	1.80
21	[2]-17	6	4600	11700	1.28
22	[2]-65	6	6100	14200	1.52
23	[2]-85	6	5100	11900	1.39

#### **EXAMPLE 24**

A device was formed in the same way as in Example 4 except that example compound No. [1]-43 and example compound No. [3]-15 were co-deposited (5:100 in weight ratio) to form 20 nm-thick light-emitting layer 3.

6V was applied to the thus obtained device by using an ITO electrode (anode 2) as a positive electrode and an Al—Li electrode (cathode 4) as a negative electrode. As the result, blue luminescence of 3900 cd/m² of luminance, maximum luminance of 10500 cd/m², and luminescence efficiency 1.12 lm/W were observed.

### **EXAMPLE 25**

A device was formed in the same way as in Example 24 except that example compound No. [1]-43 was replaced with example compound No. [2]-40.

The thus obtained device along with an ITO electrode (anode 2) as a positive electrode and an Al—Li electrode (cathode 4) as a negative electrode was used on the applied voltage of 6 V, and blue luminescence of 4200 cd/m² of luminance, maximum luminance of 13100 cd/m², and luminescence efficiency 1.125 lm/W were observed.

### **EXAMPLE 26**

A device was formed in the same way as in Example 4 except that example compound No. [1]-92 and example compound No. [4]-1 were co-deposited (5:100 in weight ratio) to 55 form 20 nm-thick light-emitting layer 3.

6V was applied to the thus obtained device by using an ITO electrode (anode 2) as a positive electrode and an Al—Li electrode (cathode 4) as a negative electrode. As the result, blue luminescence of 6000 cd/m² of luminance, maximum 60 luminance of 12200 cd/m², and luminescence efficiency 1.45 lm/W was observed.

### EXAMPLES 27 TO 30

Devices were formed in the same way as in Example 26 except that example compound No. [1]-92 was replaced with

122

the example compounds shown in Table 6 and evaluated in the same way. The results are shown in Table 16.

TABLE 16

	Example	Example compound No.	Applied voltage (V)	Luminance (cd/m <sup>2</sup> )	Maximum luminance (cd/m²)	Efficiency (1m/W)
)	27 28 29 30	[1]-66 [1]-158 [2]-17 [2]-65	6 6 6	5600 3900 5300 6600	11800 9800 14100 15400	1.33 1.17 1.47 1.61

# EXAMPLE 31

A device was formed in the same way as in Example 4 except that example compound No. [1]-60 and the above-mentioned example compound No. [5]-1 were co-deposited (5:100 in weight ratio) to form 20 nm-thick light-emitting laver 3.

6V was applied to the thus obtained device by using an ITO electrode (anode 2) as a positive electrode and an Al—Li electrode (cathode 4) as a negative electrode. As the result, blue luminescence of 4500 cd/m² of luminance, maximum luminance of 13700 cd/m², and luminescence efficiency 1.35 lm/W were observed.

### **EXAMPLE 32**

A device was formed in the same way as in Example 31 except that example compound No. [1]-60 was replaced with example compound No. [2]-40.

6V was applied to the thus obtained device by using an ITO electrode (anode 2) as a positive electrode and an Al—Li electrode (cathode 4) as a negative electrode. As the result, blue luminescence of 4900 cd/m² of luminance, maximum luminance of 15200 cd/m², and luminescence efficiency 1.45 lm/W were observed.

# EXAMPLE 33

A device was formed in the same way as in Example 4 except that example compound No. [1]-60 and example compound No. [6]-2 were co-deposited (5:100 in weight ratio) to form 20 nm-thick light-emitting layer 3.

6V was applied to the thus obtained device along with an ITO electrode (anode 2) as a positive electrode and an Al—Li electrode (cathode 4) as a negative electrode. As the result, blue luminescence of 4700 cd/m² of luminance, maximum luminance of 15800 cd/m², and luminescence efficiency 1.65 lm/W were observed.

# EXAMPLE 34

A device was formed in the same way as in Example 33 except that example compound No. [6]-2 was replaced with example compound No. [6]-9.

6V was applied to the thus obtained device by using an ITO electrode (anode 2) as a positive electrode and an Al—Li electrode (cathode 4) as a negative electrode. As the result, blue luminescence of 5900 cd/m² of luminance, maximum luminance of 18200 cd/m², and luminescence efficiency 1.85 lm/W were observed.

# **EXAMPLE 35**

A device was formed in the same way as in Example 4 except that example compound No. [1]-92 and the above-

35

 $6\mathrm{V}$  was applied to the thus obtained device by using an ITO electrode (anode **2**) as a positive electrode and an Al—Li electrode (cathode **4**) as a negative electrode. As the result,  $^5$  blue luminescence of  $5100~\text{cd/m}^2$  of luminance, maximum luminance of  $12300~\text{cd/m}^2$ , and luminescence efficiency 1.38~lm/W were observed.

### EXAMPLES 36 TO 43

The luminescence spectra of the devices formed in Examples 4, 15, 21, 26, 31, 33, 34 and 35 were observed by

# **124** EXAMPLE 46

Voltage was applied to the device formed in Example 13 for 100 hours under nitrogen atmosphere while maintaining the current density at 7.0 mA/cm² and degradation in luminance was found to be small as the initial luminance of 480 cd/m² was changed to 420 cd/m² after 100 hours.

#### COMPARATIVE EXAMPLE 1

A device was formed in the same way as in Example 4 except that the following styryl compound was used as a light-emitting layer.

MCPD-7000 and the CIE chromaticity coordinates were measured. The results are shown in Table 17.

TABLE 17

Example	Device example No.	CIE chromaticity coordinate (x, y)
36	4	0.15, 0.10
37	15	0.15, 0.10
38	21	0.15, 0.11
39	26	0.15, 0,10
40	31	0.16, 0.10
41	33	0.15, 0.09
42	34	0.15, 0.09
43	35	0.15, 0.11

### **EXAMPLE 44**

A device was formed in the same way as in Example 4 device that example compound No. [7]-1 and example compound No. [2]-65 were co-deposited (5:100 in weight ratio) to form 20 nm-thick light-emitting layer 3.

6V was applied to the thus obtained device by using an ITO electrode (anode 2) as a positive electrode and an Al—Li  $^{50}$  electrode (cathode 4) as a negative electrode. As the result, blue luminescence of  $4700~\text{cd/m}^2$  of luminance, maximum luminance of  $11100~\text{cd/m}^2$ , and luminescence efficiency 1.30~lm/W were observed.

# **EXAMPLE 45**

A device was formed in the same way as in Example 4 except that example compound No. [1]-43 and example compound No. [2]-65 were co-deposited (5:100 in weight ratio) to 60 form 20 nm-thick light-emitting layer 3.

6V was applied to the thus obtained device by using an ITO electrode (anode 2) as a positive electrode and an Al—Li electrode (cathode 4) as a negative electrode. As the result, blue luminescence of 5900 cd/m² of luminance, maximum 65 luminance of 12600 cd/m², and luminescence efficiency 1.39 lm/W were observed.

10V was applied to the thus obtained device by using an ITO electrode (anode 2) as a positive electrode and an Al—Li  $_{30}$  electrode (cathode 4) as a negative electrode. As the result, greenish blue white luminescence of  $120\,\text{cd/m}^2$  of luminance, maximum luminance of  $3800\,\text{cd/m}^2$ , and luminescence efficiency  $0.17\,\text{lm/W}$  were observed.

# COMPARATIVE EXAMPLE 2

A device was formed in the same way as in Example 4 except that the above styryl compound and example compound No. [4]-1 were co-deposited (5:100 in weight ratio) to form 20 nm-thick light-emitting layer 3.

 $10\mathrm{V}$  was applied to the thus obtained device along with an ITO electrode (anode 2) as a positive electrode and an Al—Li electrode (cathode 4) as a negative electrode. As the result, greenish blue white luminescence of 125 cd/m $^2$  of luminance, maximum luminance of 4500 cd/m $^2$ , and luminescence efficiency 0.30 lm/W were observed.

# COMPARATIVE EXAMPLE 3

The luminescence spectrum of the device formed in Comparative Example 2 was observed by MCPD-7000 and the CIE chromaticity coordinate measured was (x,y)=(0.16,0.30).

As described by way of embodiments and examples, the organic light-emitting device using the monoaminofluorene compound represented by the general formula [1] or [2] of the present invention, used in a single layer or in a mixed layer of dopant/host, enables high luminance luminescence when applied with a low voltage and is also excellent in color purity and durability. Furthermore, the device can be formed using vacuum evaporation, the casting method or the like, and a device having a large area can be readily produced at a relatively low cost.

The invention claimed is:

1. A monoaminofluorene compound selected from the following compounds:

-continued

2. A monoaminofluorene compound selected from the following compounds:

3. An organic light-emitting device comprising: a pair of electrodes which consist of an anode and a cathode, and one or more layers which are interposed between the electrodes

and contain an organic compound, wherein at least one of the layers containing the organic compound is a light-emitting layer and contains at least one of the following compounds:

**4.** An organic light-emitting device comprising: a pair of electrodes which consist of an anode and a cathode, and one or more layers which are interposed between the electrodes and contain an organic compound, wherein at least one of the layers containing the organic compound is a light-emitting layer and contains at least one of the following compounds:

132

atom, a halogen group, substituted or unsubstituted alkyl and aralkyl groups, a substituted amino group and a cyano group.

6. The organic light-emitting device according to claim 4,

6. The organic light-emitting device according to claim 4, wherein the layer containing the organic compound contains at least one additional compound represented by the following general formula [3]:

35

5. The organic light-emitting device according to claim 3, wherein the layer containing the organic compound contains at least one additional compound represented by the following general formula [3]:

$$Ar_3$$
 $R_7$ 
 $R_9$ 
 $R_7$ 

where  $Ar_1$  to  $Ar_3$  may be the same or different and are groups selected from the group consisting of substituted or unsubstituted aryl and heterocyclic ring groups, and either one of them may be a hydrogen atom, a substituted or unsubstituted alkyl group, or a substituted or unsubstituted aralkyl group; and

$$\begin{array}{c}
Ar_{5} \\
Ar_{6} \\
Ar_{7}
\end{array}$$

$$\begin{array}{c}
R_{11} \\
R_{10}
\end{array}$$

$$\begin{array}{c}
60
\end{array}$$

where  $Ar_4$  to  $Ar_7$  may be the same or different and are groups selected from the group consisting of substituted or unsubstituted aryl and heterocyclic ring groups; and  $R_{10}$  and  $R_{11}$  are groups selected from the group consisting of a hydrogen

$$Ar_{2} \xrightarrow{Ar_{1}} R_{9}$$

$$Ar_{3} \xrightarrow{R_{7}} R_{8}$$

where  $Ar_1$  to  $Ar_3$  may be the same or different and are groups selected from the group consisting of substituted or unsubstituted aryl and heterocyclic ring groups, and either one of them may be a hydrogen atom, a substituted or unsubstituted alkyl group, or a substituted or unsubstituted aralkyl group; and

- R<sub>7</sub> to R<sub>9</sub> are groups selected from the group consisting of a hydrogen atom, a halogen group, substituted or unsubstituted alkyl and aralkyl groups, a substituted amino group and a cyano group.
- 7. The organic light-emitting device according to claim 3, wherein the layer containing the organic compound contains at least one additional compound represented by the following general formula [4]:

$$\begin{array}{c}
Ar_{9} \\
Ar_{10} \\
Ar_{11}
\end{array}$$

$$\begin{array}{c}
Ar_{12} \\
Ar_{12}
\end{array}$$

where  $Ar_8$  to  $Ar_{12}$  may be the same or different and are groups selected from the group consisting of substituted or unsubstituted aryl and heterocyclic ring groups; and  $R_{12}$  is a group selected from the group consisting of a hydrogen atom, a

[4]

10

133

halogen group, substituted or unsubstituted alkyl, aralkyl, aryl and heterocyclic ring groups, a substituted amino group and a cyano group.

8. The organic light-emitting device according to claim 4, wherein the layer containing the organic compound contains 5 at least one additional compound represented by the following general formula [4]:

$$Ar_{5} = R_{11}$$

$$Ar_{6} = R_{10}$$

$$Ar_{7} = R_{10}$$

where  $Ar_4$  to  $Ar_7$  may be the same or different and are groups selected from the group consisting of substituted or unsubstituted aryl and heterocyclic ring groups; and  $R_{10}$  and  $R_{11}$  are groups selected from the group consisting of a hydrogen atom, a halogen group, substituted or unsubstituted alkyl and aralkyl groups, a substituted amino group and a cyano group.

9. The organic light-emitting device according to claim 3, wherein the layer containing the organic compound contains at least one additional compound represented by the following general formula [5]:

 $R_7$  to  $R_9$  are groups selected from the group consisting of a hydrogen atom, a halogen group, substituted or unsubstituted alkyl and aralkyl groups, a substituted amino group and a cyano group.

10. The organic light-emitting device according to claim 4, wherein the layer containing the organic compound contains at least one additional compound represented by the following general formula [5]:

$$Ar_{9} \xrightarrow{Ar_{8}} R_{12}$$

$$Ar_{10} \xrightarrow{Ar_{11}} Ar_{12}$$

where  $\rm Ar_8$  to  $\rm Ar_{12}$  may be the same or different and are groups selected from the group consisting of substituted or unsubstituted aryl and heterocyclic ring groups; and  $\rm R_{12}$  is a group selected from the group consisting of a hydrogen atom, a halogen group, substituted or unsubstituted alkyl, aralkyl,  $\rm ^{45}$  aryl and heterocyclic ring groups, a substituted amino group and a cyano group.

11. The organic light-emitting device according to claim 3, wherein the layer containing the organic compound contains at least one additional compound represented by the following general formula [6]:

$$Ar_{13}$$

$$R_{13}$$

$$Ar_{14}$$

$$Ar_{16}$$

$$R_{16}$$

60

where  $Ar_{13}$  to  $Ar_{16}$  may be the same or different and are groups selected from the group consisting of substituted or unsubstituted aryl and heterocyclic ring groups, and up to any three of them may be a hydrogen atom, a halogen group, a 65 substituted or unsubstituted alkyl group and a substituted or unsubstituted aralkyl group; and  $R_{13}$  to  $R_{16}$  are groups

134


selected from the group consisting of a hydrogen atom, a halogen group, substituted or unsubstituted alkyl, aralkyl, aryl and heterocyclic ring groups, a substituted amino group and a cyano group.

12. The organic light-emitting device according to claim 4, wherein the layer containing the organic compound contains at least one additional compound represented by the following general formula [6]:

$$Ar_{13}$$
 $R_{13}$ 
 $Ar_{15}$ 
 $Ar_{16}$ 
 $Ar_{16}$ 
 $R_{16}$ 


where  ${\rm Ar_{13}}$  to  ${\rm Ar_{16}}$  may be the same or different and are groups selected from the group consisting of substituted or unsubstituted aryl and heterocyclic ring groups, and up to any three of them may be a hydrogen atom, a halogen group, a substituted or unsubstituted alkyl group and a substituted or unsubstituted aralkyl group; and  ${\rm R_{13}}$  to  ${\rm R_{16}}$  are groups selected from the group consisting of a hydrogen atom, a halogen group, substituted or unsubstituted alkyl, aralkyl, aryl and heterocyclic ring groups, a substituted amino group and a cyano group.

13. The organic light-emitting device according to claim 3, wherein the layer containing the organic compound contains at least one additional compound represented by the following general formula [7]:



where  $R_{17}$  and  $R_{18}$  are groups selected from the group consisting of a hydrogen atom and substituted or unsubstituted alkyl, aralkyl and aryl groups, and  $R_{17}$  and  $R_{18}$  bound to different fluorene moieties may be the same or different and  $R_{17}$  and  $R_{18}$  bound to the same fluorene moiety may be the same or different; and  $R_{19}$  to  $R_{22}$  are groups selected from the group consisting of a hydrogen atom, a halogen group, substituted or unsubstituted alkyl and aralkyl and alkoxy groups, a substituted silyl group and a cyano group; and s is an integer of 2 to 5.

14. The organic light-emitting device according to claim 4, wherein the layer containing the organic compound contains at least one additional compound represented by the following general formula [7]:



where  $R_{17}$  and  $R_{18}$  are groups selected from the group consisting of a hydrogen atom and substituted or unsubstituted

alkyl, aralkyl and aryl groups, and  $R_{17}$  and  $R_{18}$  bound to different fluorene moieties may be the same or different and  $R_{17}$  and  $R_{18}$  bound to the same fluorene moiety may be the same or different;  $R_{19}$  to  $R_{22}$  are groups selected from the group consisting of a hydrogen atom, a halogen group, sub-

136

stituted or unsubstituted alkyl and aralkyl and alkoxy groups, a substituted silyl group and a cyano group; and s is as integer of 2 to 5.

\* \* \* \* \*



专利名称(译)	单氨基芴化合物和使用其的有机发	光装置		
公开(公告)号	<u>US7691491</u>	公开(公告)日	2010-04-06	
申请号	US10/525194	申请日	2003-08-12	
[标]申请(专利权)人(译)	佳能株式会社			
申请(专利权)人(译)	佳能株式会社			
当前申请(专利权)人(译)	佳能株式会社			
[标]发明人	SAITOH AKIHITO HIRAOKA MIZUHO SUZUKI KOICHI SENOO AKIHIRO TANABE HIROSHI YAMADA NAOKI NEGISHI CHIKA			
发明人	SAITOH, AKIHITO HIRAOKA, MIZUHO SUZUKI, KOICHI SENOO, AKIHIRO TANABE, HIROSHI YAMADA, NAOKI NEGISHI, CHIKA			
IPC分类号	H01L51/54 C07C211/00 C07D209/82 C07D221/02 H01L51/50 C07C211/61 C09K11/06 H01L51/00 H01L51/30			
CPC分类号	C07C211/61 C09K11/06 H01L51/0039 H01L51/0058 H01L51/0059 H01L51/006 H01L51/0072 Y10S428 /917 C09K2211/1007 C09K2211/1011 C09K2211/1014 C09K2211/1029 H01L51/0035 H01L51/0036 H01L51/0038 H01L51/005 H01L51/0054 H01L51/0055 H01L51/0067 H01L51/0068 H01L51/007 H01L51/0077 H01L51/0078 H01L51/0081 H01L51/0094 H01L51/5012 H01L2251/308 C07C2103/18 C07C2603/18			
优先权	2002252846 2002-08-30 JP			
其他公开文献	US20060166034A1			
外部链接	Espacenet USPTO			

# 摘要(译)

提供了新型单氨基芴化合物,并且使用这些化合物提供了具有极高纯度的良好发光色调并具有高发光效率,高亮度和更长工作寿命的光学输出的有机发光器件。由以下通式[1]表示的单氨基芴化合物:

