



US009461277B2

(12) **United States Patent**
Oh et al.

(10) **Patent No.:** **US 9,461,277 B2**
(45) **Date of Patent:** **Oct. 4, 2016**

(54) **ORGANIC LIGHT EMITTING DISPLAY APPARATUS**

USPC 257/59, 72, 40
See application file for complete search history.

(71) Applicant: **SAMSUNG DISPLAY CO., LTD.**,
Yongin, Gyeonggi-Do (KR)

(56) **References Cited**

(72) Inventors: **Eon-Seok Oh**, Yongin (KR);
Seung-Wook Chang, Yongin (KR);
Young-Hee Lee, Yongin (KR)

U.S. PATENT DOCUMENTS

6,274,198 B1 8/2001 Dautartas
6,371,451 B1 4/2002 Choi

(Continued)

(73) Assignee: **Samsung Display Co., Ltd.**, Yongin-si (KR)

FOREIGN PATENT DOCUMENTS

(*) Notice: Subject to any disclaimer, the term of this patent is extended or adjusted under 35 U.S.C. 154(b) by 0 days.

EP 1 413 644 A2 4/2004
EP 1 518 940 A1 3/2005

(Continued)

(21) Appl. No.: **13/901,529**

OTHER PUBLICATIONS

(22) Filed: **May 23, 2013**

Patent Abstracts of Japan and English Machine Translation of JP 11-144865, 32 pages.

(65) **Prior Publication Data**

US 2014/0014924 A1 Jan. 16, 2014

(Continued)

(30) **Foreign Application Priority Data**

Jul. 10, 2012 (KR) 10-2012-0075139
Dec. 26, 2012 (KR) 10-2012-0153709

Primary Examiner — Selim Ahmed

(74) *Attorney, Agent, or Firm* — Lewis Roca Rothgerber Christie LLP

(51) **Int. Cl.**

H01L 51/56 (2006.01)
H01L 51/52 (2006.01)
H01L 27/32 (2006.01)
H01L 51/00 (2006.01)

(Continued)

(57) **ABSTRACT**

An organic light emitting display apparatus includes: a substrate; an insulation layer on the substrate and including first regions that are arranged along a first direction and second regions that are adjacent to the first regions and are arranged along the first direction; first lines on the insulation layer to cover the first regions and including first organic light-emitting layers; and second lines on the insulation layer to cover the second regions and including second organic light-emitting layers different from the first organic light-emitting layers. A portion of the first regions and a portion of the second regions facing each other are not parallel to the first direction.



(52) **U.S. Cl.**

CPC **H01L 51/56** (2013.01); **C23C 14/042** (2013.01); **C23C 14/12** (2013.01); **H01L 27/3218** (2013.01); **H01L 51/0011** (2013.01); **H01L 51/52** (2013.01)

28 Claims, 16 Drawing Sheets

(58) **Field of Classification Search**

CPC H01L 51/56; H01L 51/52; H01L 33/02; H01L 51/0011; H01L 27/3218; C23C 14/042



(51)	Int. Cl.		JP	2006-275433	A	10/2006
	C23C 14/04	(2006.01)	JP	2007-047293	A	2/2007
			JP	2007-242436	A	9/2007
	C23C 14/12	(2006.01)	JP	2008-121098	A	5/2008
			JP	2009-019243	A	1/2009

(56) **References Cited**

U.S. PATENT DOCUMENTS

6,443,597	B1	9/2002	Natori	JP	2009-87910	A	4/2009
6,749,906	B2	6/2004	Van Slyke	KR	10-0257219	B1	2/2000
6,995,035	B2	2/2006	Cok et al.	KR	10-2000-0019254	A	4/2000
7,495,389	B2	2/2009	Noguchi et al.	KR	10-2000-0023929	A	5/2000
7,601,439	B2	10/2009	Chun et al.	KR	2001-0030175	A	4/2001
7,776,457	B2	8/2010	Lee et al.	KR	10-2001-0039298	A	5/2001
2001/0006827	A1	7/2001	Yamazaki et al.	KR	10-2001-0059939	A	7/2001
2002/0017245	A1	2/2002	Tsubaki et al.	KR	10-2002-0000201	A	1/2002
2002/0076847	A1	6/2002	Yamada et al.	KR	10-2002-0050922	A	6/2002
2002/0168577	A1	11/2002	Yoon	KR	10-2002-0090934	A	12/2002
2003/0101937	A1	6/2003	Van Slyke et al.	KR	10-2002-0091457	A	12/2002
2003/0168013	A1	9/2003	Freeman et al.	KR	10-0405080	B1	11/2003
2003/0221614	A1	12/2003	Kang et al.	KR	10-2003-0091947	A	12/2003
2003/0232563	A1	12/2003	Kamiyama et al.	KR	10-2003-0093959	A	12/2003
2004/0115338	A1	6/2004	Yoneda	KR	10-2004-0050045	A	6/2004
2004/0127066	A1	7/2004	Jung	KR	10-2004-0069281	A	8/2004
2004/0134428	A1	7/2004	Sasaki et al.	KR	10-2004-0084747	A	10/2004
2004/0142108	A1	7/2004	Atobe et al.	KR	10-0463212	B1	12/2004
2004/0144321	A1	7/2004	Grace et al.	KR	10-0483487	B1	4/2005
2004/0194702	A1	10/2004	Sasaki et al.	KR	10-0520159	B1	10/2005
2005/0016461	A1	1/2005	Klug et al.	KR	10-2006-0008602	A	1/2006
2005/0031836	A1	2/2005	Hirai	KR	10-2006-0018745	A	3/2006
2005/0037136	A1	2/2005	Yamamoto	KR	10-2006-0045225	A	5/2006
2005/0166842	A1	8/2005	Sakamoto	KR	10-2006-0051746	A	5/2006
2005/0258741	A1*	11/2005	Kim H01L 27/3246 313/503	KR	10-2006-0053926	A	5/2006
				KR	10-2006-0059323	A	6/2006
				KR	10-2006-0073367	A	6/2006
				KR	10-2006-0080475	A	7/2006
				KR	10-2006-0080481	A	7/2006
				KR	10-2006-0080482	A	7/2006
				KR	10-2006-0083510	A	7/2006
2006/0066231	A1	3/2006	Nishikawa et al.	KR	10-2006-0104675	A	10/2006
2006/0144325	A1	7/2006	Jung et al.	KR	10-2006-0104677	A	10/2006
2006/0174829	A1	8/2006	An et al.	KR	10-2006-0109627	A	10/2006
2006/0205101	A1	9/2006	Lee et al.	KR	10-2006-0109627	A	10/2006
2006/0244696	A1	11/2006	Jung et al.	KR	10-0635903	B1	10/2006
2007/0075955	A1	4/2007	Jung et al.	KR	10-2006-0114477	A	11/2006
2007/0077358	A1	4/2007	Jeong et al.	KR	10-2006-0114573	A	11/2006
2007/0178708	A1	8/2007	Ukigaya	KR	10-0646160	B1	11/2006
2008/0018236	A1	1/2008	Arai et al.	KR	10-0687007	B1	2/2007
2008/0115729	A1	5/2008	Oda et al.	KR	10-2007-0025164	A	3/2007
2008/0131587	A1	6/2008	Boroson et al.	KR	10-0696547	B1	3/2007
2008/0216741	A1	9/2008	Ling et al.	KR	10-0697663	B1	3/2007
2009/0017192	A1	1/2009	Matsuura	KR	10-0698033	B1	3/2007
2009/0232976	A1	9/2009	Yoon et al.	KR	10-0700466	B1	3/2007
2010/0219427	A1*	9/2010	Fukuda 257/89	KR	10-2007-0035796	A	4/2007
2010/0328197	A1	12/2010	Lee et al.	KR	10-2007-0037848	A	4/2007
2011/0052791	A1	3/2011	Jo et al.	KR	10-0711885	B1	4/2007
2011/0068331	A1	3/2011	Koh et al.	KR	10-2007-0050793	A	5/2007
2011/0266944	A1*	11/2011	Song et al. 313/504	KR	10-0723627	B1	6/2007
2012/0097992	A1	4/2012	Jeong	KR	10-0726132	B1	6/2007
2012/0107984	A1*	5/2012	Oh et al. 438/34	KR	10-2007-0078713	A	8/2007
2012/0175605	A1	7/2012	Shin et al.	KR	10-2007-0080635	A	8/2007
2012/0299023	A1	11/2012	Lee et al.	KR	10-2007-0101842	A	10/2007
				KR	10-2007-0105595	A	10/2007
				KR	10-0770653	B1	10/2007

FOREIGN PATENT DOCUMENTS

JP	04-272170	A	9/1992	KR	10-2008-0001184	A	1/2008
JP	11-144865	A	5/1999	KR	10-0797787	B1	1/2008
JP	2000-068054		3/2000	KR	10-0800125	B1	1/2008
JP	2001-052862	A	2/2001	KR	10-0815265	B1	3/2008
JP	2001-093667	A	4/2001	KR	10-0823508	B1	4/2008
JP	2002-175878	A	6/2002	KR	10-0827760	B1	5/2008
JP	2003-3250	A	1/2003	KR	10-0839380	B1	6/2008
JP	2003-077662	A	3/2003	KR	10-2008-0060400	A	7/2008
JP	2003-157973	A	5/2003	KR	10-2008-0061132	A	7/2008
JP	2003-297562	A	10/2003	KR	10-2008-0062212	A	7/2008
JP	2004-043898	A	2/2004	KR	10-2008-0088737	A	10/2008
JP	2004-103269	A	4/2004	KR	10-2009-0017910	A	2/2009
JP	2004-103341	A	4/2004	KR	10-2009-0038733	A	4/2009
JP	2004-199919	A	7/2004	KR	10-2009-0097453	A	9/2009
JP	2005-044592	A	2/2005	KR	10-0961110	B1	6/2010
JP	2005-235568	A	9/2005	KR	10-2010-0138139	A	12/2010
JP	2005-293968	A	10/2005	KR	10-2011-0021090	A	3/2011
JP	2005-296737	A	10/2005	KR	10-2011-0022512	A	3/2011
				KR	10-2011-0032589	A	3/2011

(56) **References Cited**

FOREIGN PATENT DOCUMENTS

KR	10-2011-0120213 A	11/2011
KR	10-2011-0138787 A	12/2011
KR	10-2012-0042155 A	5/2012
KR	10-2012-0080855 A	7/2012
KR	10-2012-0131545 A	12/2012

OTHER PUBLICATIONS

Patent Abstracts of Japan and English Machine Translation of JP 2007-242436 A, 26 pages.

Korean Reg. Det. Certificate dated Nov. 30, 2011 for Application No. KR 10-2009-0056530, 5 pages.

Patent Abstracts of Japan and English Machine Translation of JP 2001-052862 A, 20 pages.

Patent Abstracts of Japan and English Machine Translation of JP 2003-3250 A, 25 pages.

Korean Patent Abstracts, Publication No. 10-2002-0086047 A, dated Nov. 18, 2002, for corresponding Korean Patent No. 10-0405080, 2 pages.

Korean Patent Abstracts, Publication No. 10-2002-0088662 A, dated Nov. 29, 2002, for corresponding Korean Patent No. 10-0463212, 2 pages.

Korean Patent Abstracts, Publication No. 10-2005-0045619 A, dated May 17, 2005, for corresponding Korean Patent No. 10-0520159, 2 pages.

Korean Patent Abstracts, Publication No. 10-2004-0062203 A, dated Jul. 7, 2004, for corresponding Korean Patent No. 10-0646160, 2 pages.

Korean Patent Abstracts, Publication No. 10-2006-0101987 A, dated Sep. 27, 2006, for corresponding Korean Patent No. 10-0687007, 2 pages.

Korean Patent Abstracts, Publication No. 10-2002-0056238 A, dated Jul. 10, 2002, for corresponding Korean Patent No. 10-0698033, 2 pages.

Korean Patent Abstracts, Publication No. 10-2005-0078637 A, dated Aug. 5, 2005, for corresponding Korean Patent No. 10-0700466, 2 pages.

Korean Patent Abstracts, Publication No. 10-2007-0025164 A, dated Mar. 8, 2007, for corresponding Korean Patent No. 10-0711885, 2 pages.

Korean Patent Abstracts, Publication No. 10-2002-0034272 A, dated May 9, 2002, for corresponding Korean Patent No. 10-0726132, 2 pages.

Korean Patent Abstracts, Publication No. 10-2006-0126267 A, dated Dec. 7, 2006, for corresponding Korean Patent No. 10-0797787, 2 pages.

Korean Patent Abstracts, Publication No. 2008-0002189 A, dated Jan. 4, 2008, for corresponding Korean Patent No. 10-0800125 B1, 1 page.

Korean Patent Abstracts, Publication No. 10-2007-0050793 A, dated May 16, 2007, for corresponding Korean Patent No. 10-0815265, 2 pages.

Korean Patent Abstracts, Publication No. 10-2001-0062735 A, dated Jul. 7, 2001, for corresponding Korean Patent No. 10-0827760, 2 pages.

Korean Patent Abstracts, Publication No. 10-2008-0038650 A, dated May 7, 2008, for corresponding Korean Patent No. 10-0839380, 2 pages.

Korean Patent Abstracts, Publication No. 10-2010-0027524 A, dated Mar. 11, 2010, for corresponding Korean Patent No. KR 10-0961110, 1 page.

* cited by examiner

FIG. 1




FIG. 2




FIG. 3




FIG. 4




FIG. 5




FIG. 6




FIG. 7




FIG. 8




FIG. 9




FIG. 10




FIG. 11




FIG. 12




FIG. 13




FIG. 14




FIG. 15




FIG. 16




FIG. 17




FIG. 18




FIG. 19




FIG. 20




FIG. 21




FIG. 22




FIG. 23





FIG. 24



ORGANIC LIGHT EMITTING DISPLAY APPARATUS

CROSS-REFERENCE TO RELATED PATENT APPLICATIONS

This application claims priority to and the benefit of Korean Patent Application No. 10-2012-0075139, filed on Jul. 10, 2012, and Korean Patent Application No. 10-2012-0153709, filed on Dec. 26, 2012, in the Korean Intellectual Property Office, the disclosures of both of which are incorporated herein in their entirety by reference.

BACKGROUND

1. Field

The present invention relates to an organic light emitting display apparatus and a method of manufacturing of the same.

2. Description of the Related Art

Organic light-emitting display devices have wider viewing angles, better contrast characteristics, and faster response speeds than other display devices, and thus have drawn attention as a next-generation display device.

An organic light-emitting display device includes intermediate layers, including an emission layer disposed between a first electrode and a second electrode that are arranged opposite to each other. The electrodes and the intermediate layers may be formed using various methods, one of which is an independent deposition method. When an organic light-emitting display device is manufactured by using the deposition method, a fine metal mask (FMM) having the same pattern as that of an organic layer to be formed is disposed to closely contact a substrate on which the organic layer and the like are formed, and an organic layer material is deposited on the FMM to form the organic layer having the desired pattern.

However, the deposition method using such an FMM presents difficulties in manufacturing larger organic light-emitting display devices using a large mother glass. For example, when such a large mask is used, the mask may bend due to its own weight, thereby distorting a pattern. Such disadvantages are not conducive for the recent trend towards high-definition patterns.

Moreover, processes of aligning a substrate and an FMM to closely contact each other, performing deposition thereon, and separating the FMM from the substrate are time-consuming, resulting in a long manufacturing time and low production efficiency.

Information disclosed in this Background section was known to the inventors of the present invention before achieving the present invention or is technical information acquired in the process of achieving the present invention. Therefore, it may contain information that does not form the prior art or information that was already known in this country to a person of ordinary skill in the art prior to the time the present invention was made by the inventors.

SUMMARY

Embodiments according to the present invention provide a method of manufacturing an organic light emitting display apparatus that is suitable for use in the mass production of a large substrate and enables high-definition patterning and organic light-emitting display devices manufactured using the method.

According to an aspect of the present invention, there is provided an organic light emitting display apparatus including: a substrate; an insulation layer on the substrate and including first regions that are arranged along a first direction and second regions that are adjacent to the first regions and are arranged along the first direction; first lines on the insulation layer to cover the first regions and including first organic light-emitting layers; and second lines on the insulation layer to cover the second regions and including second organic light-emitting layers different from the first organic light-emitting layers, wherein a portion of the first regions and a portion of the second regions facing each other are not parallel to the first direction.

The portions of the first regions and the second regions facing each other may not be parallel to edges of the first lines and the second lines.

The first regions and the second regions may have polygonal shapes with angled corners, and an angled corner may be located at where the portions of the first regions and the second regions face each other.

The first regions and the second regions may have shapes including curved lines, and at least one of the curved lines may be located at where the portions of the first regions and the second regions face each other.

The portions of the first regions and the second regions facing each other may not be parallel to each other.

The first lines and the second lines may overlap each other at least partially.

The first regions and the second regions may have openings formed in the insulation layer.

The first organic light-emitting layer may be formed by using an organic layer deposition apparatus, and a slanted side between top and bottom sides of the first organic light-emitting layer that is farther from a center of the first region may be longer than another slanted side between the top and bottom sides.

The first organic light-emitting layer may be formed by using an organic layer deposition apparatus, and a length of a slanted side between top and bottom sides of the first organic light-emitting layer formed farther from a center of the first region may be larger than lengths of slanted sides between respective top and bottom sides of the other first organic light-emitting layers formed close to the center of the first region.

The first organic light-emitting layer may be formed by using an organic layer deposition apparatus, and two opposite slanted sides between top and bottom sides of the first organic light-emitting layer at a center of the first region may have substantially the same length.

The first organic light-emitting layer may be formed by using an organic layer deposition apparatus, and the first organic light-emitting layers at the first region may be substantially symmetrically arranged about a center of the first region.

The substrate may have a size of 40 inches or more.

The first and second organic light-emitting layers may have a non-uniform thickness.

According to another aspect of the present invention, a method of manufacturing an organic light emitting display apparatus is provided. The method includes: forming an insulation layer on a substrate; forming openings that are defined as first regions arranged along a first direction and second regions that are adjacent to the first regions and are arranged along the first direction in the insulation layer; forming first lines including first organic light-emitting layers on the insulation layer to cover the first regions by moving the substrate in relation to a first deposition assem-

bly that is spaced from the substrate, such that a first organic light-emitting material emitted from the first deposition assembly is deposited on the substrate; and forming second lines including second organic light-emitting layers different from the first organic light-emitting layers on the insulation layer to cover the second regions by moving the substrate in relation to a second deposition assembly that is spaced from the substrate, such that a second organic light-emitting material different from the first organic light-emitting material emitted from the second deposition assembly is deposited on the substrate, wherein a portion of the first regions and a portion of the second regions facing each other are not parallel to the first direction.

The first regions and the second regions may have polygonal shapes with angled corners, and an angled corner may be located at where the portions of the first regions and the second regions face each other.

The first regions and the second regions may have shapes including curved lines, and at least one of the curved lines may be located at where the portions of the first regions and the second regions face each other.

The portions of the first regions and the second regions facing each other may not be parallel to each other.

The first deposition assembly may include: a deposition source configured to emit a deposition material; a deposition source nozzle unit at one side of the deposition source and including a plurality of deposition source nozzles; and a patterning slit sheet facing the deposition source nozzle unit and including a plurality of patterning slits, and the first organic light-emitting material emitted by the deposition source may pass through the patterning slit sheet and may be deposited to form the first organic light-emitting layers.

The patterning slit sheet may be smaller than the substrate in at least one of the first direction or a second direction perpendicular to the first direction.

The plurality of deposition source nozzles may be arranged at the deposition source nozzle unit along the first direction, the plurality of patterning slits may be arranged at the patterning slit sheet along the first direction, and the first deposition assembly may further include a shielding plate assembly including a plurality of shielding plates arranged between the deposition source nozzle unit and the patterning slit sheet along the first direction and partitioning a space between the deposition source nozzle unit and the patterning slit sheet into a plurality of deposition spaces.

The plurality of deposition source nozzles may be arranged at the deposition source nozzle unit along the first direction, and the plurality of patterning slits may be arranged at the patterning slit sheet along a second direction perpendicular to the first direction.

The deposition source, the deposition source nozzle unit, and the patterning slit sheet may be connected to one another via a connecting member and may be formed as a single body.

The connecting member may guide a path in which the deposition material moves.

The forming of the first lines and the forming of the second lines may respectively include depositing on the substrate the first organic light-emitting material and the second organic light-emitting material emitted respectively by the deposition source of the first deposition assembly and a deposition source of the second deposition assembly while the substrate is spaced from and is being moved with respect to the first and second deposition assemblies of a thin-film deposition apparatus. The thin-film deposition apparatus may include: a conveyer unit including a transfer unit on which the substrate is fixed to move therewith; a first

conveyer unit, which moves the transfer unit on which the substrate is fixed in a first direction; and a second conveyer unit, which moves the transfer unit from which the substrate is detached after deposition in a direction opposite to the first direction; a loading unit in which the substrate is fixed to the transfer unit; a deposition unit including a chamber maintained at a vacuum, and the first and second deposition assemblies; and an unloading unit in which the substrate is detached from the transfer unit after the substrate passes through the deposition unit and deposition thereon is completed.

The transfer unit may be configured to move back and forth between the first conveyer unit and the second conveyer unit, and the substrate fixed to the transfer unit may be spaced apart from the first and second deposition assemblies while being transported by the first conveyer unit.

The first conveyer unit may move the transfer unit to the loading unit, the deposition unit, and the unloading unit in the order stated.

The first conveyer unit and the second conveyer unit may pass through the deposition unit.

The first conveyer unit and the second conveyer unit may be arranged next to each other in a vertical direction.

BRIEF DESCRIPTION OF THE DRAWINGS

The above and other features and aspects of the present invention will become more apparent by describing in detail exemplary embodiments thereof with reference to the attached drawings in which:

FIG. 1 is a schematic plan view illustrating a structure of a thin-film deposition apparatus according to an embodiment of the present invention;

FIG. 2 is a schematic side view of a deposition unit of the thin-film deposition apparatus of FIG. 1, according to an embodiment of the present invention;

FIG. 3 is a schematic perspective view showing the deposition unit of FIG. 1;

FIG. 4 is a schematic sectional view of the deposition unit of FIG. 3;

FIG. 5 is a schematic perspective view of an organic layer deposition assembly according to another embodiment of the present invention;

FIG. 6 is a schematic sectional view of the organic layer deposition assembly of FIG. 5;

FIG. 7 is a schematic plan view of the organic layer deposition assembly of FIG. 5;

FIG. 8 is a schematic perspective view of an organic layer deposition assembly according to another embodiment of the present invention;

FIG. 9 is a schematic perspective view of an organic layer deposition assembly according to another embodiment of the present invention;

FIG. 10 is a diagram illustrating a structure in which patterning slits are arranged at equal intervals in a patterning slit sheet of the thin-film deposition apparatus of FIG. 3;

FIG. 11 is a diagram illustrating organic layers formed on a substrate by using the patterning slit sheet of FIG. 10, according to an embodiment of the present invention;

FIG. 12 is a plan view of an organic light emitting display apparatus according to an embodiment of the present invention, which is manufactured by using a thin-film deposition apparatus as described above;

FIG. 13 is a cross-sectional view obtained along the line III-III of FIG. 12;

FIG. 14 is a plan view showing that color mixtures occurs in FIG. 12;

FIG. 15 is a cross-sectional view obtained along the line V-V of FIG. 14; and

FIGS. 16 through 24 are plan views of organic light emitting display apparatuses according to other embodiments of the present invention.

DETAILED DESCRIPTION

References will now be made in detail to embodiments of the present invention, examples of which are illustrated in the accompanying drawings, wherein like reference numerals refer to the like elements throughout. The embodiments are described below in order to explain aspects of the present invention by referring to the figures. Expressions such as "at least one of," when preceding a list of elements, modify the entire list of elements and do not modify the individual elements of the list.

FIG. 1 is a schematic plan view illustrating a structure of a thin-film deposition apparatus (e.g., an organic layer deposition apparatus) 1 according to an embodiment of the present invention. FIG. 2 is a schematic side view of a deposition unit 100 of the thin-film deposition apparatus 1 of FIG. 1, according to an embodiment of the present invention.

Referring to FIGS. 1 and 2, the thin-film deposition apparatus 1 includes the deposition unit 100, a loading unit 200, an unloading unit 300, and a conveyer unit 400 (refer to FIGS. 3 and 4).

The loading unit 200 may include a first rack 212, a transport chamber 214, a first inversion chamber 218, and a buffer chamber 219.

A plurality of substrates 2 (for example, one substrate 2 is shown in FIGS. 3-9) onto which a deposition material has not yet been applied are stacked up on the first rack 212. A transport robot included in the transport chamber 214 picks up one of the substrates 2 from the first rack 212, places it on a transfer unit 430 transferred by a second conveyer unit 420, and moves the transfer unit 430 on which the substrate 2 is placed into the first inversion chamber 218.

The first inversion chamber 218 is located adjacent to the transport chamber 214. The first inversion chamber 218 includes a first inversion robot that inverts the transfer unit 430 and then loads it on a first conveyer unit 410 of the deposition unit 100.

Referring to FIG. 1, the transport robot of the transport chamber 214 places one of the substrates 2 on a top surface of the transfer unit 430, and the transfer unit 430 on which the substrate 2 is placed is then transferred into the first inversion chamber 218. The first inversion robot of the first inversion chamber 218 inverts the transfer unit 430 so that the substrate 2 is turned upside down in the deposition unit 100.

The unloading unit 300 is configured to operate in an opposite manner to the loading unit 200 described above. Specifically, a second inversion robot in a second inversion chamber 328 inverts the transfer unit 430, which has passed through the deposition unit 100 while the substrate 2 is placed on the transfer unit 430, and then moves the transfer unit 430 on which the substrate 2 is placed into an ejection chamber 324. Then, an ejection robot takes the transfer unit 430 on which the substrate 2 is placed out of the ejection chamber 324, separates the substrate 2 from the transfer unit 430, and then loads the substrate 2 on a second rack 322. The transfer unit 430, separated from the substrate 2, is returned to the loading unit 200 via the second conveyer unit 420.

However, the present invention is not limited to the above example. For example, when placing the substrate 2 on the

transfer unit 430, the substrate 2 may be fixed (or attached) onto a bottom surface of the transfer unit 430 and then moved into the deposition unit 100. In such an embodiment, for example, the first inversion robot of the first inversion chamber 218 and the second inversion robot of the second inversion chamber 328 may be omitted.

The deposition unit 100 may include at least one chamber for deposition. In one embodiment, as illustrated in FIGS. 1 and 2, the deposition unit 100 includes a chamber 101 in which a plurality of organic layer deposition assemblies (100-1)(100-2) . . . (100-n) may be located. Referring to FIG. 1, 11 organic layer deposition assemblies, i.e., a first organic layer deposition assembly (100-1), a second organic layer deposition assembly (100-2), through an eleventh organic layer deposition assembly (100-11), are located in the chamber 101, but the number of organic layer deposition assemblies may vary with a desired deposition material and deposition conditions. The chamber 101 is maintained in vacuum during a deposition process.

In the embodiment illustrated in FIG. 1, the transfer unit 430 with the substrate 2 fixed (or attached) thereon may be moved at least to the deposition unit 100 or may be moved sequentially to the loading unit 200, the deposition unit 100, and the unloading unit 300, by the first conveyer unit 410, and the transfer unit 430 that is separated from the substrate 2 in the unloading unit 300 may be moved back to the loading unit 200 by the second conveyer unit 420.

The first conveyer unit 410 passes through the chamber 101 when passing through the deposition unit 100, and the second conveyer unit 420 conveys (or transports) the transfer unit 430 from which the substrate 2 is separated.

In the present embodiment, the thin-film deposition apparatus 1 is configured such that the first conveyer unit 410 and the second conveyer unit 420 are respectively disposed above and below so that after the transfer unit 430, on which deposition has been completed while passing through the first conveyer unit 410, is separated from the substrate 2 in the unloading unit 300, the transfer unit 430 is returned to the loading unit 200 via the second conveyer unit 420 formed below the first conveyer unit 410, whereby the thin-film deposition apparatus 1 may have an improved space utilization efficiency.

In an embodiment, the deposition unit 100 of FIG. 1 may further include a deposition source replacement unit 190 located at a side of each organic layer deposition assembly. Although not particularly illustrated in the drawings, the deposition source replacement unit 190 may be formed as a cassette-type that may be drawn to the outside from each organic layer deposition assembly. Thus, a deposition source 110 (refer to FIG. 3) of the organic layer deposition assembly 100-1 may be easily replaced.

FIG. 3 is a schematic perspective view showing the deposition unit 100 of FIG. 1, and FIG. 4 is a schematic sectional view of the deposition unit 100 of FIG. 3. While the dotted boundary line in FIG. 1 designated with the reference numeral 101 appears to indicate a chamber that is larger than the chamber 101 as illustrated in FIGS. 3 and 4, the chamber 101 according to the embodiments of the present invention may include a single conveyer unit 400 or multiple conveyer units that are parallel to each other, and embodiments of the present invention are not limited to any particular chamber size.

Referring to FIGS. 3 and 4, the deposition unit 100 of the thin-film deposition apparatus 1 includes at least one organic layer deposition assembly 100-1 and a conveyer unit 400.

Hereinafter, an overall structure of the deposition unit 100 will be described.

The chamber **101** may be formed as a hollow box type and accommodate the at least one organic layer deposition assembly **100-1** and the transfer unit **430**. In another descriptive manner, a foot **102** is formed so as to fix the deposition unit **100** on the ground, a lower housing **103** is located on the foot **102**, and an upper housing **104** is located on the lower housing **103**. The chamber **101** accommodates both the lower housing **103** and the upper housing **104**. In this regard, a connection part of the lower housing **103** and the chamber **101** is sealed so that the inside of the chamber **101** is completely isolated from the outside. Due to the structure in which the lower housing **103** and the upper housing **104** are located on the foot **102** fixed on the ground, the lower housing **103** and the upper housing **104** may be maintained in a fixed position even though the chamber **101** is repeatedly contracted and expanded. Thus, the lower housing **103** and the upper housing **104** may serve as a reference frame in the deposition unit **100**.

The upper housing **104** includes the organic layer deposition assembly **100-1** and the first conveyer unit **410** of the conveyer unit **400**, and the lower housing **103** includes the second conveyer unit **420** of the conveyer unit **400**. While the transfer unit **430** is cyclically moving between the first conveyer unit **410** and the second conveyer unit **420**, a deposition process is continuously performed.

Hereinafter, constituents of the organic layer deposition assembly **100-1** are described in detail.

The first organic layer deposition assembly **100-1** includes the deposition source **110**, a deposition source nozzle unit **120**, the patterning slit sheet **130**, a first stage **150**, a second stage **160**, a camera **170**, and a sensor **180**. In this regard, all the elements illustrated in FIGS. **3** and **4** may be arranged in the chamber **101** maintained in an appropriate vacuum state. This structure is used to achieve the linearity of a deposition material.

For example, in order to deposit a deposition material **115** that has been discharged from the deposition source **110** and passed through the deposition source nozzle unit **120** and the patterning slit sheet **130**, onto the substrate **2** in a desired pattern, it is desirable to maintain the chamber (not shown) in the same vacuum state as that used in a deposition method using a fine metal mask (FMM). In addition, the temperature of the patterning slit sheet **130** needs to be sufficiently lower than that of the deposition source **110** because thermal expansion of the patterning slit sheet **130** by temperatures may be reduced or minimized when the temperature of the patterning slit sheet **130** is sufficiently low.

The substrate **2** on which the deposition material **115** is to be deposited is arranged in the chamber **101**. The substrate **2** may be a substrate for a flat panel display device. For example, a large substrate, such as a mother glass, for manufacturing a plurality of flat panel displays, may be used as the substrate **2**.

According to the present embodiment, the deposition process may be performed with the substrate **2** being moved relative to the organic layer deposition assembly **100-1**.

In a conventional deposition method using an FMM, the size of the FMM is the same as that of a substrate. Thus, as the size of the substrate increases, the size of the FMM also increases. Due to these problems, it is difficult to fabricate the FMM and to align the FMM in a precise pattern by elongation of the FMM.

To address these problems, in the organic layer deposition assembly **100-1** according to the present embodiment, deposition may be performed while the organic layer deposition assembly **100-1** and the substrate **2** are moved relative to each other. In other words, deposition may be continuously

performed while the substrate **2**, which faces the organic layer deposition assembly **100-1**, is moved in a Y-axis direction. That is, deposition is performed in a scanning manner while the substrate **2** is moved in a direction of arrow A illustrated in FIG. **3**. Although the substrate **2** is illustrated as being moved in the Y-axis direction in the chamber **101** in FIG. **3** when deposition is performed, the present invention is not limited thereto. For example, deposition may be performed while the organic layer deposition assembly **100-1** is moved in the Y-axis direction and the substrate **2** is held in a fixed position.

Thus, in the organic layer deposition assembly **100-1**, the patterning slit sheet **130** may be smaller (e.g., much smaller) than an FMM used in a conventional deposition method. In other words, in the organic layer deposition assembly **100-1**, deposition is continuously performed, i.e., in a scanning manner, while the substrate **2** is moved in the Y-axis direction. Thus, at least one of the lengths of the patterning slit sheet **130** in X-axis and Y-axis directions may be much less than a length of the substrate **2**. Because the patterning slit sheet **130** may be formed smaller (e.g., much smaller) than the FMM used in a conventional deposition method, it is relatively easy to manufacture the patterning slit sheet **130**. That is, the small patterning slit sheet **130** is more suitable in view of all the manufacturing processes, including etching followed by precise elongation, welding, transferring, and washing processes, than the FMM used in a conventional deposition method. In addition, this is more suitable for manufacturing a relatively large display device.

In order to perform deposition while the organic layer deposition assembly **100-1** and the substrate **2** are moved relative to each other as described above, the organic layer deposition assembly **100-1** and the substrate **2** may be spaced apart from each other by a certain distance (e.g., a gap). This is described below in detail.

The deposition source **110** that contains and heats the deposition material **115** is located at a side opposite to a side in which the substrate **2** is located in the chamber. As the deposition material **115** contained in the deposition source **110** is vaporized, deposition is performed on the substrate **2**.

The deposition source **110** includes a crucible **111** that is filled with the deposition material **115** and a heater **112** that heats the crucible **111** so as to vaporize the deposition material **115** toward a side of the crucible **111** filled with the deposition material **115**, in particular, toward the deposition source nozzle unit **120**.

The deposition source nozzle unit **120**, in one embodiment, is located at a side of the deposition source **110** facing the substrate **2**. In this regard, the organic layer deposition assemblies according to the present embodiment each may include different deposition nozzles in performing deposition for forming common layers and pattern layers. In other words, although not shown in FIG. **3**, a plurality of deposition source nozzles **121** may be arranged along the Y-axis direction, which is the direction in which the substrate **2** is scanned, at a deposition source nozzle unit for forming a pattern layer. Therefore, by forming the deposition source nozzles **121** such that the number of the deposition source nozzles **121** in the X-axis direction is only **1**, formation of shadow may be reduced (e.g., significantly reduced). Alternatively, in other embodiments, a plurality of deposition source nozzles may be formed along the X-axis direction at a deposition source nozzle unit for forming a common layer. By doing so, a thickness uniformity of the common layer may be improved.

In one embodiment, the patterning slit sheet **130** may be located between the deposition source **110** and the substrate

2. The patterning slit sheet **130** may further include a frame having a shape similar to a window frame. The patterning slit sheet **130** includes a plurality of patterning slits **131** arranged along the X-axis direction. The deposition material **115** that has been vaporized in the deposition source **110** passes through the deposition source nozzle unit **120** and the patterning slit sheet **130** and is then deposited onto the substrate **2**. In this regard, the patterning slit sheet **130** may be formed using the same method as that used to form an FMM, in particular, a stripe-type mask, e.g., etching. In this regard, a total number of patterning slits **131** may be more than a total number of deposition source nozzles **121**.

In one embodiment, the deposition source **110** (and the deposition source nozzle unit **120** combined thereto) and the patterning slit sheet **130** may be spaced apart from each other by a certain distance (e.g., a gap).

As described above, deposition is performed while the organic layer deposition assembly **100-1** is moved relative to the substrate **2**. In order for the organic layer deposition assembly **100-1** to be moved relative to the substrate **2**, the patterning slit sheet **130** is spaced apart from the substrate **2** by a certain distance (e.g., a gap).

In a conventional deposition method using an FMM, deposition is typically performed with the FMM in close contact with a substrate in order to prevent formation of shadows on the substrate. However, when the FMM is formed in close contact with the substrate, defects due to the contact between the substrate and the FMM may occur. In addition, because it is difficult to move the mask with respect to the substrate, the mask and the substrate have the same size. Accordingly, the mask becomes larger as the size of a display device increases. However, it is difficult to form a large mask.

To address these problems, in the organic layer deposition assembly **100-1** according to the present embodiment, the patterning slit sheet **130** is formed spaced apart by a certain distance (e.g., a gap) from the substrate **2** on which a deposition material is to be deposited.

According to the present embodiment, deposition may be performed while a mask formed smaller than a substrate is moved with respect to the substrate, and thus, it is relatively easy to manufacture the mask. In addition, defects due to contact between the substrate and the mask may be prevented. In addition, because it is unnecessary to closely contact the substrate with the mask during a deposition process, a manufacturing speed may be improved.

Hereinafter, particular disposition of each element of the upper housing **104** will be described.

The deposition source **110** and the deposition source nozzle unit **120** are located at a bottom portion of the upper housing **104**. Accommodation portions **104-1** are respectively formed on both sides of the deposition source **110** and the deposition source nozzle unit **120** to have a protruding shape. The first stage **150**, the second stage **160**, and the patterning slit sheet **130** are sequentially formed (or located) on the accommodation portions **104-1** in this order.

In this regard, the first stage **150** is formed to move in X-axis and Y-axis directions so that the first stage **150** aligns the patterning slit sheet **130** in the X-axis and Y-axis directions. That is, the first stage **150** includes a plurality of actuators so that the first stage **150** is moved in the X-axis and Y-axis directions with respect to the upper housing **104**.

The second stage **160** is formed to move in a Z-axis direction so as to align the patterning slit sheet **130** in the Z-axis direction. That is, the second stage **160** includes a plurality of actuators and is formed to move in the Z-axis direction with respect to the first stage **150**.

The patterning slit sheet **130** is located on the second stage **160**. The patterning slit sheet **130** is located on the first stage **150** and the second stage **160** so as to move in the X-axis, Y-axis, and Z-axis directions, and thus, an alignment, in particular, a real-time alignment, between the substrate **2** and the patterning slit sheet **130**, may be performed.

In addition, the upper housing **104**, the first stage **150**, and the second stage **160** may guide a flow path of the deposition material **115** such that the deposition material **115** discharged through the deposition source nozzles **121** is not dispersed outside the flow path. That is, the flow path of the deposition material **115** is sealed by the upper housing **104**, the first stage **150**, and the second stage **160**, and thus, the movement of the deposition material **115** in the X-axis and Y-axis directions may be simultaneously guided thereby.

A shielding member **140** for preventing organic materials from being deposited on a non-layer forming region of the substrate **2** may further be arranged between the patterning slit sheet **130** and the deposition source **110**. Although not shown in detail, the shielding member **140** may include two plates adjacent to each other. Because the non-layer forming region of the substrate **2** is covered by the shielding member **140**, deposition of organic materials on the non-layer forming region of the substrate **2** may be reduced or prevented without a separate structure.

Hereinafter, the conveyer unit **400** that conveys (or transports) the substrate **2**, on which the deposition material **115** is to be deposited, is described in detail. Referring to FIGS. **3** and **4**, the conveyer unit **400** includes the first conveyer unit **410**, the second conveyer unit **420**, and the transfer unit **430**.

The first conveyer unit **410** conveys (or transports) in an in-line manner the transfer unit **430**, including the carrier **431** and an electrostatic chuck **432** attached thereto, and the substrate **2** attached to the transfer unit **430** so that an organic layer may be formed on the substrate **2** by the organic layer deposition assembly **100-1**. The first conveyer unit **410** includes a coil **411**, guide members **412**, upper magnetically suspended bearings (e.g., magnetically levitating bearings or magnetic levitation bearings) (not shown), side magnetically suspended bearings (e.g., magnetically levitating bearings or magnetic levitation bearings) (not shown), and gap sensors (not shown). In one embodiment, the magnetically suspended bearings and the gap sensor are mounted on the guide members **412**.

The second conveyer unit **420** returns to the loading unit **200** the transfer unit **430** from which the substrate **2** has been separated in the unloading unit **300** after one deposition cycle is completed while the transfer unit **430** is passing through the deposition unit **100**. The second conveyer unit **420** includes a coil **421**, roller guides **422**, and a charging track **423**.

The transfer unit **430** includes the carrier **431** that is conveyed (e.g., transported) along the first conveyer unit **410** and the second conveyer unit **420** and the electrostatic chuck **432** that is combined on (or attached to) a surface of the carrier **431**. The substrate **2** is attached to the electrostatic chuck **432**.

Hereinafter, each element of the conveyer unit **400** will be described in more detail.

The carrier **431** of the transfer unit **430** will now be described in detail.

The carrier **431** includes a main body part **431a**, a magnetic rail (e.g., a linear motor system (LMS) magnet) **431b**, contactless power supply (CPS) modules **431c**, a power supply unit **431d**, and guide grooves **431e**.

The main body part **431a** constitutes a base part of the carrier **431** and may be formed of a magnetic material such as iron. In this regard, due to a respective repulsive force and/or an attractive force between the main body part **431a** and the respective upper and side magnetically suspended bearings (e.g., magnetic levitation bearings), which are described below, the carrier **431** may be maintained spaced apart from the guide members **412** by a certain distance (e.g., a gap).

The guide grooves **431e** may be respectively formed at both sides of the main body part **431a** and each may accommodate a guide protrusion **412e** of the guide member **412**.

The magnetic rail **431b** may be formed along a center line of the main body part **431a** in a direction where the main body part **431a** proceeds. The LMS magnet **431b** and the coil **411**, which are described below, may be combined with each other to constitute a linear motor, and the carrier **431** may be conveyed in an arrow A direction by the linear motor.

The CPS modules **431c** and the power supply unit **431d** may be respectively formed on both sides of the LMS magnet **431b** in the main body part **431a**. The power supply unit **431d** includes a battery (e.g., a rechargeable battery) that provides power so that the electrostatic chuck **432** can chuck (e.g., fix or hold) the substrate **2** and maintains operation. The CPS modules **431c** are a wireless charging module that charges the power supply unit **431d**. For example, the charging track **423** formed in the second conveyer unit **420**, which is described below, is connected to an inverter (not shown), and thus, when the carrier **431** is transferred into the second conveyer unit **420**, a magnetic field is formed between the charging track **423** and the CPS modules **431c** so as to supply power to the CPS module **431c**. The power supplied to the CPS modules **431c** is used to charge the power supply unit **431d**.

The electrostatic chuck **432** may include an electrode embedded in a main body formed of ceramic, wherein the electrode is supplied with power. The substrate **2** is attached onto a surface of the main body of the electrostatic chuck **432** as a suitable voltage or a relatively high voltage (e.g., a high voltage) is applied to the electrode.

Next, an operation of the transfer unit **430** will be described in detail.

The magnetic rail **431b** of the main body unit **431a** may be combined with the coils **411** and constitute a driving unit. Here, the driving unit may be a linear motor. Compared to a slide guiding system, a linear motor is a device with precise or highly precise position determination due to a relatively small friction coefficient and little positioning errors. As described above, a linear motor may include the coils **411** and the magnetic rail **431b**, wherein the magnetic rail **431b** may be linearly arranged in the carrier **431**, and the plurality of coils **411** may be arranged at a region in the chamber **101** to face the magnetic rail **431b**. As described above, the magnetic rail **431b** is arranged on the carrier **431**, which is a moving object, instead of the coils **411**, and thus the carrier **431** may be driven without applying power to the carrier **431**. Here, the coils **411** are formed in an atmosphere (ATM) box and are installed in an atmosphere, whereas the magnetic rail **431b** is attached to the carrier **431**, such that the carrier **431** may move in the vacuum chamber **101**.

Hereinafter, the first conveyer unit **410** and the transfer unit **430** are described in detail.

Referring to FIG. 4, the first conveyer unit **410** conveys (e.g., transports) the electrostatic chuck **432** that fixes the substrate **2** and the carrier **431** that conveys (e.g., transports) the electrostatic chuck **432**. In this regard, the first conveyer

unit **410** includes the coil **411**, the guide members **412**, the upper magnetically suspended bearings (e.g., the upper magnetic levitation bearings), the side magnetically suspended bearings (e.g., the side magnetic levitation bearings), and the gap sensors.

The coil **411** and the guide members **412** are formed (or located) inside the upper housing **104**. The coil **411** is formed (or located) in an upper portion of the upper housing **104**, and the guide members **421** are respectively formed on both inner sides of the upper housing **104**.

The guide members **412** guide the carrier **431** to move in a direction. In this regard, the guide members **412** are formed to pass through the deposition unit **100**.

The side magnetically suspended bearings (e.g., the side magnetic levitation bearings) are each located at the guide member **412** so as to respectively correspond to both sides of the carrier **431**. The side magnetically suspended bearings (e.g., the side magnetic levitation bearings) cause a distance between the carrier **431** and the guide member **412** so that the carrier **431** is moved along the guide members **412** in non-contact with the guide members **412**. That is, a repulsive force occurring between the side magnetically suspended bearing (e.g., the side magnetic levitation bearing) on the left side and the carrier **431**, which is a magnetic material, and a repulsive force occurring between the side magnetically suspended bearing (e.g., the side magnetic levitation bearing) on the right side and the carrier **431**, maintain equilibrium or substantial equilibrium, and thus, there is a constant distance (e.g., a substantially constant gap) between the carrier **431** and the respective guide members **412**.

Each upper magnetically suspended bearing (e.g., upper magnetic levitation bearing) may be located at the guide member **412** so as to be above the carrier **431**. The upper magnetically suspended bearings (e.g., the upper magnetic levitation bearings) enable the carrier **431** to be moved along the guide members **412** in non-contact with the first and second accommodation parts **412a** and **412b** of the guide members **412** and with a distance (e.g., a gap) therebetween maintained constantly (or substantially constantly). That is, an attractive force occurring between the upper magnetically suspended bearing (e.g., the upper magnetic levitation bearing) and the carrier **431**, which is a magnetic material, and gravity, maintain equilibrium or substantial equilibrium, and thus, there is a constant distance or a substantially constant distance between the carrier **431** and the respective guide members **412**.

Each guide member **412** may further include the gap sensor. The gap sensor may measure a distance between the carrier **431** and the guide member **412**. Furthermore, the gap sensor may be disposed at a side of the side magnetically suspended bearing (e.g., the side magnetic levitation bearing). The gap sensor may measure a distance between a side surface of the carrier **431** and the side magnetically suspended bearing (e.g., the side magnetic levitation bearing).

Magnetic forces of the upper and side magnetically suspended bearings (e.g., magnetic levitation bearings) may vary according to values measured by the gap sensors, and thus, distances between the carrier **431** and the respective guide members **412** may be adjusted in real time. That is, a precise transfer of the carrier **431** may be feedback controlled using the upper and side magnetically suspended bearings (e.g., magnetic levitation bearings) and the gap sensors.

Hereinafter, the second conveyer unit **420** and the transfer unit **430** are described in detail.

Referring back to FIG. 4, the second conveyer unit **420** returns the electrostatic chuck **432** from which the substrate

2 has been separated in the unloading unit **300** and the carrier **431** that carries the electrostatic chuck **432** to the loading unit **200**. In this regard, the second conveyer unit **420** includes the coil **421**, the roller guides **422**, and the charging track **423**.

For example, the coil **421**, the roller guides **422**, and the charging track **423** may be positioned inside the lower housing **103**. The coil **421** and the charging track **423** may be located at a top inner surface of the lower housing **103**, and the roller guides **422** may be located at both inner sides of the lower housing **103**. The coil **421** may be located in an ATM box, similar to the coil **411** of the first conveyer unit **410**.

Similar to the first conveyer unit **410**, the second conveyer unit **410** may also include the coil **421**. Also, the magnetic rail (e.g., the LMS magnet) **431b** of the main body part **431a** of the carrier **431** and the coil **421** are combined with each other to constitute an operation unit. In this regard, the operation unit may be a linear motor. The carrier **431** may be moved by the linear motor along a direction opposite to the direction of arrow A illustrated in FIG. 3.

The roller guides **422** guide the carrier **431** to move in a direction. In this regard, the roller guides **422** are formed to pass through the deposition unit **100**.

The second conveyer unit **420** is used in a process of returning the carrier **431** from which the substrate **2** has been separated and not in a process of depositing an organic material on the substrate **2**, and thus, position accuracy (or positional accuracy) thereof is not needed as by the first conveyer unit **410**. Therefore, magnetic suspension is applied to the first conveyer unit **410** that requires high position accuracy, thereby obtaining position accuracy, and a conventional roller method is applied to the second conveyer unit **420** that requires relatively low position accuracy, thereby reducing manufacturing costs and simplifying a structure of the thin-film deposition apparatus. Although not illustrated in FIG. 4, the magnetic suspension (e.g., magnetic levitation) may also be applied to the second conveyer unit **420** as in the first conveyer unit **410**.

The organic layer deposition assemblies **100-1** of the apparatus for organic material deposition (e.g., a thin film deposition apparatus or an organic layer deposition apparatus) **1** according to an embodiment of the present invention may include cameras **170** and sensors **180** for alignment. For example, the cameras **170** may align a first mark (not shown) formed on the frame of the patterning slit sheet **130** and a second mark (not shown) formed on the substrate **2** in real-time. The sensors **180** may be confocal sensors. As described above, because a distance between the substrate **2** and the patterning slit sheet **130** is measurable in real time using the cameras **170** and the sensors **180**, the substrate **2** may be aligned with the patterning slit sheet **130** in real time, whereby position accuracy of a pattern may be improved (e.g., significantly improved).

A thin film, such as an organic layer of an organic light emitting display apparatus, may be formed by using the thin film deposition apparatus (e.g., the organic layer deposition apparatus). Detailed descriptions thereof will be given below.

FIG. 5 is a schematic perspective view of an organic layer deposition assembly **700** according to another embodiment of the present invention, FIG. 6 is a schematic sectional view of the organic layer deposition assembly **700** of FIG. 5, and FIG. 7 is a schematic plan view of the organic layer deposition assembly **700** of FIG. 5.

Referring to FIGS. 5 through 7, the organic layer deposition assembly **700** includes a deposition source **710**, a

deposition source nozzle unit **720**, a shielding plate assembly (e.g., a barrier assembly or a barrier plate assembly) **730**, and a patterning slit sheet **750**.

Here, the deposition source **710** includes a crucible **711** filled with a deposition material **715** and a heater **712** for evaporating the deposition material **715** that is filled in the crucible **711** toward the deposition source nozzle unit **720** by heating the crucible **711**. The deposition source nozzle unit **720** is arranged at one side of the deposition source **710**, wherein a plurality of deposition source nozzles **721** are arranged along the X-axis direction at the deposition source nozzle unit **720**.

The shielding plate assembly **730** is arranged at one side of the deposition source nozzle unit **720**. The shielding plate assembly **730** includes a plurality of shielding plates **731** and a shielding plate frame **732** arranged outside (e.g., around or surrounding) the shielding plates **731**. The plurality of shielding plates **731** may be arranged next to one another along the X-axis direction. Here, the shielding plates **731** may be formed at a constant or substantially constant interval. Furthermore, each of the shielding plates **731** extends on the Y-Z plane and may have a rectangular shape. The plurality of shielding plates **731** arranged as described above define or partition the space between the deposition source nozzle unit **720** and the patterning slit sheet **750** into a plurality of deposition spaces S. In other words, in the organic layer deposition assembly **700** according to the present embodiment, the deposition spaces S are defined or partitioned by the shielding plates **731** with respect to the respective deposition source nozzles **721** which emit deposition materials, as shown in FIG. 5. As described above, by defining or partitioning the space between the deposition source nozzle unit **720** and the patterning slit sheet **750** into the plurality of deposition spaces S, a deposition material emitted by a deposition source nozzle **721** passes through the respective patterning slits **751** and is deposited onto the substrate **2** without being mixed with deposition materials emitted by the other deposition source nozzles **721**. In other words, the shielding plates **731** guide paths in which deposition materials move, such that the deposition materials emitted by the respective deposition source nozzles **721** move straight or substantially straight in the Z-axis direction without being dispersed.

As described above, by securing straight-going property of deposition materials by arranging the shielding plates **731**, the size of a shadow formed on a substrate may be reduced (e.g., significantly reduced), and thus the organic layer deposition assembly **700** and the substrate **2** may be spaced apart (e.g., by a predetermined distance) from each other.

The patterning slit sheet **750** is further arranged between the deposition source **710** and the substrate **2**. The patterning slit sheet **750** includes a frame **755** which is formed in a window frame-like shape, wherein a plurality of patterning slits **751** are formed in (e.g., arranged along) the patterning slit sheet **750** in the X-axis direction. The evaporated deposition material **715** in the deposition source **710** passes through the deposition source nozzle unit **720** and the patterning slit sheet **750** and moves toward the substrate **2**, which is the target object.

FIG. 8 is a schematic perspective view of an organic layer deposition assembly **800** according to another embodiment of the present invention.

The organic layer deposition assembly **800** according to the embodiment shown in FIG. 8 includes a deposition source **810**, a deposition source nozzle unit **820**, a first shielding plate assembly (e.g., a first barrier plate assembly)

830, a second shielding plate assembly (e.g., a second barrier plate assembly) **840**, and a patterning slit sheet **850**. Here, the deposition source **810**, the first shielding plate assembly **830**, and the patterning slit sheet **850** are identical or substantially identical to those according to the embodiment shown in FIG. 5, and thus detailed descriptions thereof is omitted. The present embodiment differs from the previous embodiment in that the second shielding plate assembly **840** is located at one side of the first shielding plate assembly **830**.

For example, the second shielding plate assembly **840** includes a plurality of second shielding plates (e.g., barrier plates) **841** and a second shielding plate frame **842** arranged outside (e.g., around or surrounding) the second shielding plates **841**. The plurality of second shielding plates **841** may be arranged next to one another along the X-axis direction. Furthermore, the plurality of second shielding plates **841** may be formed at a constant or substantially constant interval. Furthermore, each of the second shielding plates **841** is formed to be parallel to the Y-Z plane, that is, perpendicular to the X-axis direction. The patterning slit sheet **850** includes a plurality of patterning slits **851** arranged along the X-direction.

The plurality of first shielding plates **831** and the plurality of second shielding plates **841** arranged as described above define or partition the space between the deposition source nozzle unit **820** and the patterning slit sheet **850**. In other words, deposition spaces are defined by the first shielding plates **831** and the second shielding plates **841** for the respective deposition source nozzles **821** which jet (e.g., emit or discharge) deposition materials.

Here, the second shielding plates **841** may be arranged in correspondence to the first shielding plates **831**, respectively. In other words, the second shielding plates **841** may be aligned with the first shielding plates **831**, respectively. In other words, the first shielding plate **831** and the second shielding plate **841** corresponding to each other are arranged on same respective planes. Although it is shown that the thickness of the first shielding plate **831** is identical or substantially identical to the thickness of the second shielding plate **841** along the X-axis direction, the present invention is not limited thereto. In other words, the second shielding plates **841**, which need to be precisely aligned with patterning slits **851**, may be formed to have relatively small thickness, whereas the first shielding plates **831**, which do not need to be precisely aligned, may be formed to have relatively large thickness for ease of manufacturing.

FIG. 9 is a schematic perspective view of an organic layer deposition assembly **900** according to another embodiment of the present invention.

Referring to FIG. 9, the organic layer deposition assembly **900** according to the present embodiment includes a deposition source **910**, a deposition source nozzle unit **920**, and a patterning slit sheet **950**.

Here, the deposition source **910** includes a crucible **911** filled with a deposition material **915** and a heater **912** for evaporating the deposition material **915** that is filled in the crucible **911** toward the deposition source nozzle unit **920** by heating the crucible **911**. The deposition source nozzle unit **920** is arranged at one side of the deposition source **910**, wherein a plurality of deposition source nozzles **921** are formed along the Y-axis direction at the deposition source nozzle unit **920**.

The patterning slit sheet **950** and a frame **955** are further arranged between the deposition source **910** and the substrate **2**, and a plurality of patterning slits **951** are formed at the patterning slit sheet **950** along the X-axis direction.

Furthermore, the deposition source **910**, the deposition source nozzle unit **920**, and the patterning slit sheet **950** are combined with one another via a connecting member (or connecting members) **935**.

The present embodiment differs from the previous embodiments in the arrangement of the deposition source nozzles **921** arranged at the deposition source nozzle unit **920**. Detailed description thereof is given below.

The deposition source nozzle unit **920** is arranged at one side of the deposition source **910**, and more particularly, the side of the deposition source **910** facing the substrate **2**. Furthermore, the plurality of deposition source nozzles **921** are formed at the deposition source nozzle unit **920** along the Y-axis direction (that is, the direction in which the substrate **2** is scanned or moved). Here, the plurality of deposition source nozzles **921** may be formed at a constant or substantially constant interval. An evaporated deposition material **915** in the deposition source **910** passes through the deposition source nozzles **921** of the deposition source nozzle unit **920** and moves toward the substrate **2**, which is the target object. As a result, the plurality of deposition source nozzles **921** are formed in a single organic layer deposition assembly **900** along the direction in which the substrate **2** is scanned. In this case, if the plurality of deposition source nozzles **921** were arranged along the X-axis direction, distances between the respective deposition source nozzles **921** and a patterning slit **951** would differ, and a shadow may be formed by the deposition material **915** emitted by the deposition source nozzle **921** that is the farthest away from the patterning slit **951**. Therefore, formation of a shadow may be reduced (or significantly reduced) by forming the deposition source nozzles **921**, such that only one deposition source nozzle **921** is arranged along the X-axis direction. Furthermore, because the plurality of deposition source nozzles **921** are arranged along the scanning direction, even if fluxes of the respective deposition source nozzles **921** differ, the differences may be offset and deposition uniformity may be maintained constantly or substantially constantly.

Hereinafter, a structure of an organic layer formed using the thin-film deposition apparatus **1** described above is described in detail.

FIG. 10 is a diagram illustrating a structure in which the patterning slits **131** are arranged at equal intervals in the patterning slit sheet **130** of the thin-film deposition apparatus **1** including the deposition unit **100** of FIG. 3, according to an embodiment of the present invention. FIG. 11 is a diagram illustrating organic layers formed on the substrate **2** by using the patterning slit sheet **130** of FIG. 10, according to an embodiment of the present invention.

FIGS. 10 and 11 schematically illustrate the patterning slit sheet **130** in which the patterning slits **131** are arranged at equal intervals. That is, in FIG. 10, the patterning slits **131** satisfy the following condition: $I_1=I_2=I_3=I_4$.

In this embodiment, an incident angle of a deposition material discharged along a center line C of a deposition space S is substantially perpendicular to the substrate **2**. Thus, an organic layer P_1 formed using the deposition material that has passed through a patterning slit $131a$ has a minimum (or reduced) size of a shadow, and a right-side shadow SR_1 and a left-side shadow SL_1 are formed symmetrical to (or symmetrically with) each other.

However, a critical incident angle θ of the deposition material that passes through patterning slits located farther from the center line C of the deposition space S gradually increases, and thus, in one embodiment, the critical incident angle θ of the deposition material that passes through the

outermost patterning slit **131e** is approximately 55° . Accordingly, the deposition material is incident at an inclination with respect to the patterning slit **131e**, and an organic layer P_5 formed using the deposition material that has passed through the patterning slit **131e** has the largest shadow. For example, a left-side shadow SL_5 is larger than a right-side shadow SR_5 .

That is, as the critical incident angle θ of the deposition material increases, the size of the shadow also increases. For example, the size of the shadow at a position farther from the center line C of the deposition space S increases. In addition, the critical incident angle θ of the deposition material increases as a distance between the center line C of the deposition space S and the respective patterning slits increases. Thus, organic layers formed using the deposition material that passes through the patterning slits located farther from the center line C of the deposition space S have a relatively larger shadow size. For example, of the shadows on both sides of the respective organic layers, the size of the shadow at a position farther from the center line C of the deposition space S is larger than that of the other.

That is, referring to FIG. 11, the organic layers formed on the left side of the center line C of the deposition space S have a structure in which a left hypotenuse (e.g., a slanted side on the left between top and bottom sides) is larger than a right hypotenuse (e.g., a slanted side on the right between the top and bottom sides), and the organic layers formed on the right side of the center line C of the deposition space S have a structure in which a right hypotenuse (e.g., a right slanted side) is larger than a left hypotenuse (e.g., a left slanted side).

In addition, in the organic layers formed on the left side of the center line C of the deposition space S , the length of the left hypotenuse (e.g., the left slanted side) increases towards the left. In the organic layers formed on the right side of the center line C of the deposition space S , the length of the right hypotenuse (e.g., the right slanted side) increases towards the right. Consequently, the organic layers formed in the deposition space S may be formed symmetrical to each other about the center line C of the deposition space S . This structure will now be described in further detail.

The deposition material that passes through a patterning slit **131b** passes through the patterning slit **131b** at a critical incident angle of θ_b , and an organic layer P_2 formed using the deposition material that has passed through the patterning slit **131b** has a left-side shadow having a size of SL_2 . Similarly, the deposition material that passes through a patterning slit **131c** passes through the patterning slit **131c** at a critical incident angle of θ_c , and an organic layer P_3 formed using the deposition material that has passed through the patterning slit **131c** has a left-side shadow having a size of SL_3 . Similarly, the deposition material that passes through a patterning slit **131d** passes through the patterning slit **131d** at a critical incident angle of θ_d , and an organic layer P_4 formed using the deposition material that has passed through the patterning slit **131d** has a left-side shadow having a size of SL_4 . Similarly, the deposition material that passes through the patterning slit **131e** passes through the patterning slit **131e** at a critical incident angle of θ_e , and an organic layer P_5 formed using the deposition material that has passed through the patterning slit **131e** has a left-side shadow having a size of SL_5 .

In this regard, the critical incident angles satisfy the following condition: $\theta_b < \theta_c < \theta_d < \theta_e$, and thus, the sizes of the shadows of the organic layers also satisfy the following condition: $SL_1 < SL_2 < SL_3 < SL_4 < SL_5$.

FIG. 12 is a plan view of an organic light emitting display apparatus according to an embodiment of the present invention, which is manufactured by using a thin-film deposition apparatus as described above according to one or more suitable embodiments of the present invention. FIG. 13 is a cross-sectional view obtained along the line III-III of FIG. 12. In FIG. 12, for convenience of explanation, two each of first through third sub-pixels **SP1**, **SP2**, and **SP3** from among a plurality of pixels are shown.

Referring to FIGS. 12 and 13, an organic light emitting display apparatus is formed on a bottom substrate **21**. The bottom substrate **21** may be formed of a glass material, a plastic material, a metal, or any other suitable material that is known to one of ordinary skill in the art.

A plurality of pixels are formed on the bottom substrate **21**, where each of the pixels may include a plurality of sub-pixels **SP1**, **SP2**, and **SP3** which emit different colors from one another. According to an embodiment of the present invention as shown in FIGS. 12 and 13, each pixel P includes a first sub-pixel **SP1**, a second sub-pixel **SP2**, and a third sub-pixel **SP3**. The first sub-pixel **SP1**, the second sub-pixel **SP2**, and the third sub-pixel **SP3** may be sub-pixels for emitting red light, green light, and blue light, respectively. However, the present invention is not limited thereto, and the first sub-pixel **SP1**, the second sub-pixel **SP2**, and the third sub-pixel **SP3** may be used to emit any of various color combinations of light for representing white color.

As shown in FIG. 13, a driving circuit **22** is arranged at each sub-pixel. Each driving circuit **22** may include at least one TFT (not shown) and at least one capacitor (not shown).

A first insulation layer **23** covers the driving circuits **22**. A plurality of pixel electrodes **251** that are electrically connected to the respective driving circuit **22** are formed on the first insulation layer **23**. Each of the pixel electrodes **251** is independently located (e.g., separated or spaced from each other) in correspondence to each of the sub-pixels.

A second insulation layer **24** is formed on the first insulation layer **23**. The second insulation layer **24** is formed to cover the pixel electrodes **251** and defines a light-emitting region by partially exposing the pixel electrodes **251** by forming first through third openings.

The first openings, the second openings, and the third openings may be located in correspondence to the first sub-pixel **SP1**, the second sub-pixel **SP2**, and the third sub-pixel **SP3**, respectively. Meanwhile, the first openings define first light-emitting regions **241**, the second openings define second light-emitting regions **242**, and the third openings define third light-emitting regions **243**.

A plurality of first lines **261**, a plurality of second lines **262**, and a plurality of third lines **263** are formed on the second insulation layer **24** to cover the first light-emitting regions **241**, the second light-emitting regions **242**, and the third light-emitting regions **243**, respectively.

In one embodiment, the first lines **261** include a first organic light-emitting layer, e.g., a red organic light-emitting layer.

In one embodiment, the second lines **262** include a second organic light-emitting layer, e.g., a green organic light-emitting layer.

In one embodiment, the third lines **263** include a third organic light-emitting layer, e.g., a blue organic light-emitting layer.

Next, a counter electrode **252** is formed to cover the first lines **261**, the second lines **262**, and the third lines **263**. The counter electrode **252** may be a common electrode formed to be common to all of the pixels P .

The pixel electrodes **251** may be formed as a transparent electrode or a reflective electrode. Such a transparent electrode may be formed of indium tin oxide (ITO), indium zinc oxide (IZO), zinc oxide (ZnO), or indium oxide (In₂O₃). Such a reflective electrode may be formed by forming a reflective layer from silver (Ag), magnesium (Mg), aluminum (Al), platinum (Pt), palladium (Pd), gold (Au), nickel (Ni), neodymium (Nd), iridium (Ir), chromium (Cr) and/or a compound thereof, and forming a layer of ITO, IZO, ZnO, or In₂O₃ on the reflective layer. The pixel electrodes **251** may be formed by forming a layer by, for example, sputtering, and then patterning the layer by, for example, photolithography.

The counter electrode **252** may also be formed as a transparent electrode or a reflective electrode. When the counter electrode **252** is formed as a transparent electrode, the counter electrode **252** is used as a cathode. To this end, such a transparent electrode may be formed by forming a thin-film using a metal having a low work function, such as lithium (Li), calcium (Ca), lithium fluoride/calcium (LiF/Ca), lithium fluoride/aluminum (LiF/Al), aluminum (Al), silver (Ag), magnesium (Mg), and/or a compound thereof and forming an auxiliary electrode layer or a bus electrode line thereon from ITO, IZO, ZnO, In₂O₃, or the like. When the second electrode **62** is formed as a reflective electrode, the reflective layer may be formed by thickly depositing Li, Ca, LiF/Ca, LiF/Al, Al, Ag, Mg, and/or a compound thereof on the entire surface of the organic layer **63**. The counter electrode **252** may be formed using any suitable organic layer deposition apparatus described above according to embodiments of the present invention.

Functional organic layers other than the first lines **261**, the second lines **262**, and the third lines **263** may be further arranged between the pixel electrodes **251** and the counter electrode **252**.

The functional organic layers may be single layers or composite layers in which a hole injection layer (HIL), a hole transport layer (HTL), an electron transport layer (ETL), and an electron injection layer (EIL) are stacked.

The first lines **261**, the second lines **262**, and the third lines **263** are successively deposited by using the organic layer deposition apparatus as described above.

In other words, as shown in FIG. **13**, as the bottom substrate **21a**, on which the second insulation layer **24** including the first light-emitting regions **241**, the second light-emitting regions **242**, and the third light-emitting regions **243**, is formed, passes through the deposition unit **100** at which the plurality of organic layer deposition assemblies **100-1** through **100-n** are arranged, organic layers including the first lines **261**, the second lines **262**, the third lines **263**, and functional organic layers are formed.

Because formations of the organic layers are successively performed along the direction indicated by the arrow A in FIG. **3**, the first lines **261**, the second lines **262**, and the third lines **263** extend in a first direction Y, which is parallel to the direction indicated by the arrow A in FIG. **3**, as shown in FIG. **12**.

Here, from among the first lines **261**, the second lines **262**, and the third lines **263**, the first line **261** and the second line **262** adjacent to each other in a second direction X that is perpendicular to the first direction Y may overlap each other as shown in FIGS. **12** and **13**. The reason thereof is that, because the patterning slit sheet **130** and the substrate **2** are scanned some distance apart from each other, a formed organic layer is formed with some shadow as shown in FIG. **11**.

If the first lines **261**, the second lines **262**, and the third lines **263** are formed using the deposition method as described above, shadow formation on an organic layer is inevitable. Therefore, as shown in FIGS. **12** and **13**, the first line **261** and the second line **262** that are adjacent to each other in the second direction X partially overlap each other, the second line **262** and the third line **263** adjacent to each other in a second direction D2 partially overlap each other, and the third line **263** and the first line **261** adjacent to each other in the second direction D2 partially overlap each other.

Here, the first line **261** and the second line **262**, the second line **262** and the third line **263**, and the third line **263** and the first line **261** overlap on the second insulation layer **24**. In detail, the first line **261** and the second line **262** overlap each other at a first gap G1 between the first light-emitting regions **241** and the second light-emitting regions **242**, and the second line **262** and the third line **263** overlap each other at a second gap G2 between the second light-emitting regions **242** and the third light-emitting regions **243**.

Furthermore, the first lines **261** through the third lines **263** do not overlap openings of adjacent lines. In other words, the first lines **261** do not overlap second openings **242** that are openings covered by the adjacent second lines **262** and third openings **243** that are openings covered by the adjacent third lines **263**. The second lines **262** do not overlap first openings **241** that are openings covered by the adjacent first lines **261** and the third openings **243** that are openings covered by the adjacent third lines **263**. The third lines **263** do not overlap the first openings **241** that are covered by the adjacent first lines **261** and the second openings **242** that are openings covered by the adjacent second lines **262**.

However, if subtle misalignment or significant shadow occurs between the substrate **2** and the patterning slit sheet **130**, overlapping of lines adjacent to each other may extend into other light-emitting regions over the second insulation layer **24**. Therefore, as shown in FIG. **14** and the portion F of FIG. **15**, the first lines **261** extend into the second light-emitting regions **242** and cause color mixtures and stains in the second light-emitting regions **242**. Due to the color mixtures and stains, problems including deterioration of light emitting efficiency and/or reduction of lifespan of an OLED may occur. Furthermore, a defective product with dislocated color coordinates and visible stains may be produced.

Therefore, embodiments of the present invention provide a light-emitting region for reducing color mixtures and stains in the first sub-pixels SP1, the second sub-pixels SP2, and the third sub-pixels SP3.

For example, according to embodiments of the present invention, in the first light-emitting regions **241** and the second light-emitting regions **242**, a portion of the first light-emitting regions **241** and a portion of the second light-emitting regions **242** facing each other are not parallel to the first direction Y or edges of the first lines **261** or the second lines **262**. To this end, if the first light-emitting regions **241** and the second light-emitting regions **242** have polygonal shapes with angled corners as shown in FIGS. **12** through **15**, angled corners are located at where the first light-emitting regions **241** and the second light-emitting regions **242** face each other.

If, unlike in FIGS. **12** through **15**, the portion of the second light-emitting regions **242** adjacent to the first lines **261** is parallel to the edge of the first lines **261** and the light-emitting regions have rectangular shapes, color mixtures and stains may occur at a larger area than in FIGS. **12** through **15** when the first lines **261** extend into the second light-emitting regions **242**. However, to resolve the problem,

if overlap lateral length of the second light-emitting regions **242** is reduced or width of the second light-emitting regions **242** in the second direction X is reduced, light-emitting area is reduced, and thus light-emitting efficiency is deteriorated.

However, according to embodiments of the present invention, color mixtures and stains due to adjacent lines may be minimized or reduced without deteriorating light-emitting efficiency.

FIGS. **12** through **15** show that the first through third light-emitting regions **241**, **242**, and **243** have hexagonal honeycomb-like shapes. FIG. **16** shows that the first through third light-emitting regions **241**, **242**, and **243** have rhombus-like shapes. FIG. **17** shows that the first through third light-emitting regions **241**, **242**, and **243** have pentagonal shapes. As shown in FIGS. **12** through **17**, if the first through third light-emitting regions **241**, **242**, and **243** have polygonal shapes with angled corners, an angled corner is located at where portions of the first light-emitting regions **241** and second light-emitting regions **242** face each other. Therefore, even if an adjacent line extends into another light-emitting region as shown in FIG. **14**, an area at which color mixture occurs may be reduced.

Meanwhile, if the first through third light-emitting regions **241**, **242**, and **243** have triangular shapes as shown in FIGS. **18** and **19** or the first through third light-emitting regions **241**, **242**, and **243** have trapezoidal shapes as shown in FIG. **20**, portions of the first light-emitting regions **241** and the second light-emitting regions **242** facing each other are not parallel to each other. Therefore, even if an adjacent line extends into another light-emitting region as shown in FIG. **14**, an area at which color mixture occurs may be reduced.

Furthermore, if the first through third light-emitting regions **241**, **242**, and **243** have parallelogram-like shapes as shown in FIG. **21**, portions of the first light-emitting regions **241** and the second light-emitting regions **242** facing each other are not parallel to edges of the lines (**261**, **262**, and **263** of FIG. **14**). Therefore, even if an adjacent line extends into another light-emitting region as shown in FIG. **14**, an area at which color mixture occurs may be reduced.

Furthermore, if the first through third light-emitting regions **241**, **242**, and **243** have shapes including curved lines as shown in FIGS. **22-24**, the curved lines are located at where portions of the first light-emitting regions **241** and the second light-emitting regions **242** face each other. Therefore, even if an adjacent line extends into another light-emitting region as shown in FIG. **14**, an area at which color mixture occurs may be reduced.

Although the above descriptions are given in relation to the first lines **261** and the second lines **262** and the first light-emitting regions **241** and the second light-emitting regions **242** for convenience of explanation, the present invention may also be identically applied in relation to the second lines **262** and the third lines **263** and the second light-emitting regions **242** and the third openings **243**, and in relation to the first lines **261** and the third lines **263** and the first light-emitting regions **241** and the third light-emitting regions **243**.

The present invention is not limited to the embodiments shown in FIGS. **12** through **24**, and any of various shapes may be applied to the light-emitting regions of the present invention as long as color mixtures due to adjacent lines may be minimized. Furthermore, the light-emitting regions on a single substrate may have a combination of the above shapes.

Meanwhile, widths **W1**, **W2**, and **W3** of the lines **261**, **262**, and **263** may be the same or may differ from one another according to shadow effectiveness. Meanwhile, the

gaps **G1** and **G2** may be formed in any of various manners based on various factors including widths of lines and the overall pixel size.

Although a few embodiments of the present invention have been shown and described, it would be appreciated by those skilled in the art that changes may be made in this embodiment without departing from the principles and spirit of the invention, the scope of which is defined in the claims and their equivalents.

What is claimed is:

1. An organic light emitting display apparatus comprising: a substrate; an insulation layer on the substrate and having a plurality of first openings defining first light-emitting regions that are arranged along a first direction and a plurality of second openings defining second light-emitting regions that are adjacent to the first light-emitting regions and are arranged along the first direction; first lines on the insulation layer to cover the first light-emitting regions and comprising first organic light-emitting layers; and second lines on the insulation layer to cover the second light-emitting regions and comprising second organic light-emitting layers different from the first organic light-emitting layers, wherein an edge portion of the first light-emitting regions and an edge portion of the second light-emitting regions facing each other and extending parallel to a surface of the substrate are not parallel to the first direction, and wherein the first lines and the second lines overlap each other at least partially in a plan view.
2. The organic light emitting display apparatus of claim 1, wherein the edge portions of the first light-emitting regions and the second light-emitting regions facing each other are not parallel to edges of the first lines and the second lines.
3. The organic light emitting display apparatus of claim 1, wherein the first light-emitting regions and the second light-emitting regions have polygonal shapes with angled corners, and the first light-emitting regions and the second light-emitting regions each have an angled corner that is located at where the edge portions of the first light-emitting regions and the second light-emitting regions face each other.
4. The organic light emitting display apparatus of claim 1, wherein the first light-emitting regions and the second light-emitting regions have shapes including curved lines, and at least one of the curved lines is located at where the edge portions of the first light-emitting regions and the second light-emitting regions face each other.
5. The organic light emitting display apparatus of claim 1, wherein the edge portions of the first light-emitting regions and the second light-emitting regions facing each other are not parallel to each other.
6. The organic light emitting display apparatus of claim 1, wherein the first organic light-emitting layer is formed by using an organic layer deposition apparatus, and a slanted side between top and bottom sides of the first organic light-emitting layer that is farther from a center of one of the first light-emitting regions is longer than another slanted side between the top and bottom sides.
7. The organic light emitting display apparatus of claim 1, wherein the first organic light-emitting layer is formed by using an organic layer deposition apparatus, and

a length of a slanted side between top and bottom sides of the first organic light-emitting layer formed farther from a center of one of the first light-emitting regions is larger than lengths of slanted sides between respective top and bottom sides of other ones of the first organic light-emitting layers formed close to the center of the one of the first light-emitting regions.

8. The organic light emitting display apparatus of claim 1, wherein the first organic light-emitting layer is formed by using an organic layer deposition apparatus, and two opposite slanted sides between top and bottom sides of the first organic light-emitting layer at a center of one of the first light-emitting regions have substantially the same length.

9. The organic light emitting display apparatus of claim 1, wherein the first organic light-emitting layer is formed by using an organic layer deposition apparatus, and the first organic light-emitting layers at one of the first light-emitting regions are substantially symmetrically arranged about a center of the one of the first light-emitting regions.

10. The organic light emitting display apparatus of claim 1, wherein the substrate has a size of 40 inches or more.

11. The organic light emitting display apparatus of claim 1, wherein the first and second organic light-emitting layers have a non-uniform thickness.

12. The organic light emitting display apparatus of claim 1, wherein each of the first light-emitting regions are defined by at least three edge portions, and at least two of the edge portions of each of the first light-emitting regions have lengths that are different from each other.

13. The organic light emitting display apparatus of claim 1, wherein a length of the first light-emitting regions in the first direction is greater than a width of the first light-emitting regions in a direction crossing the first direction.

14. A method of manufacturing an organic light emitting display apparatus, the method comprising:

forming an insulation layer on a substrate;
forming a first plurality of openings defining first light-emitting regions that are arranged along a first direction and a second plurality of openings defining second light-emitting regions that are adjacent to the first regions and are arranged along the first direction in the insulation layer;

forming first lines including first organic light-emitting layers on the insulation layer to cover the first light-emitting regions by moving the substrate in relation to a first deposition assembly that is spaced from the substrate, such that a first organic light-emitting material emitted from the first deposition assembly is deposited on the substrate; and

forming second lines including second organic light-emitting layers different from the first organic light-emitting layers on the insulation layer to cover the second light-emitting regions by moving the substrate in relation to a second deposition assembly that is spaced from the substrate, such that a second organic light-emitting material different from the first organic light-emitting material emitted from the second deposition assembly is deposited on the substrate,

wherein an edge portion of the first light-emitting regions and an edge portion of the second light-emitting regions facing each other and extending parallel to a surface of the substrate are not parallel to the first direction, and

wherein the first lines and the second lines overlap each other at least partially in a plan view.

15. The method of claim 14, wherein the first light-emitting regions and the second light-emitting regions have polygonal shapes with angled corners, and

the first light-emitting region and the second light-emitting regions each have an angled corner that is located at where the edge portions of the first light-emitting regions and the second light-emitting regions face each other.

16. The method of claim 14, wherein the first light-emitting regions and the second light-emitting regions have shapes including curved lines, and

at least one of the curved lines is located at where the edge portions of the first light-emitting regions and the second light-emitting regions face each other.

17. The method of claim 14, wherein the edge portions of the first light-emitting regions and the second light-emitting regions facing each other are not parallel to each other.

18. The method of claim 14, wherein the first deposition assembly comprises:

a deposition source configured to emit a deposition material;

a deposition source nozzle unit at one side of the deposition source and comprising a plurality of deposition source nozzles; and

a patterning slit sheet facing the deposition source nozzle unit and comprising a plurality of patterning slits, and the first organic light-emitting material emitted by the deposition source passes through the patterning slit sheet and is deposited to form the first organic light-emitting layers.

19. The method of claim 18, wherein the patterning slit sheet is smaller than the substrate in at least one of the first direction or a second direction perpendicular to the first direction.

20. The method of claim 18, wherein the plurality of deposition source nozzles are arranged at the deposition source nozzle unit along the first direction,

the plurality of patterning slits are arranged at the patterning slit sheet along the first direction, and

the first deposition assembly further comprises a shielding plate assembly comprising a plurality of shielding plates arranged between the deposition source nozzle unit and the patterning slit sheet along the first direction and partitioning a space between the deposition source nozzle unit and the patterning slit sheet into a plurality of deposition spaces.

21. The method of claim 18, wherein the plurality of deposition source nozzles are arranged at the deposition source nozzle unit along the first direction, and

the plurality of patterning slits are arranged at the patterning slit sheet along a second direction perpendicular to the first direction.

22. The method of claim 21, wherein the deposition source, the deposition source nozzle unit, and the patterning slit sheet are connected to one another via a connecting member and are formed as a single body.

23. The method of claim 22, wherein the connecting member guides a path in which the deposition material moves.

24. The method of claim 18, wherein the forming of the first lines and the forming of the second lines respectively comprise depositing on the substrate the first organic light-emitting material and the second organic light-emitting material emitted respectively by the deposition source of the first deposition assembly and a deposition source of the second deposition assembly while the substrate is spaced from and is being moved with respect to the first and second

deposition assemblies of a thin-film deposition apparatus, the thin-film deposition apparatus comprising:

- a conveyer unit comprising a transfer unit on which the substrate is fixed to move therewith;
- a first conveyer unit, which moves the transfer unit on 5 which the substrate is fixed in a first direction; and
- a second conveyer unit, which moves the transfer unit from which the substrate is detached after deposition in a direction opposite to the first direction;
- a loading unit in which the substrate is fixed to the transfer 10 unit;
- a deposition unit comprising:
 - a chamber maintained at a vacuum; and
 - the first and second deposition assemblies; and
- an unloading unit in which the substrate is detached from 15 the transfer unit after the substrate passes through the deposition unit and deposition thereon is completed.

25. The method of claim **24**, wherein the transfer unit is configured to move back and forth between the first conveyer unit and the second conveyer unit, and 20 the substrate fixed to the transfer unit is spaced apart from the first and second deposition assemblies while being transported by the first conveyer unit.

26. The method of claim **25**, wherein the first conveyer unit moves the transfer unit to the loading unit, the deposition unit, and the unloading unit in the order stated. 25

27. The method of claim **24**, wherein the first conveyer unit and the second conveyer unit pass through the deposition unit.

28. The method of claim **24**, wherein the first conveyer 30 unit and the second conveyer unit are arranged next to each other in a vertical direction.

* * * * *

专利名称(译)	有机发光显示装置		
公开(公告)号	US9461277	公开(公告)日	2016-10-04
申请号	US13/901529	申请日	2013-05-23
[标]申请(专利权)人(译)	三星显示有限公司		
申请(专利权)人(译)	三星DISPLAY CO. , LTD.		
当前申请(专利权)人(译)	三星DISPLAY CO. , LTD.		
[标]发明人	OH EON SEOK CHANG SEUNG WOOK LEE YOUNG HEE		
发明人	OH, EON-SEOK CHANG, SEUNG-WOOK LEE, YOUNG-HEE		
IPC分类号	H01L51/56 C23C14/12 C23C14/04 H01L51/00 H01L51/52 H01L27/32		
CPC分类号	H01L51/56 C23C14/042 C23C14/12 H01L27/3218 H01L51/0011 H01L51/52		
审查员(译)	AHMED , SELIM		
优先权	1020120075139 2012-07-10 KR 1020120153709 2012-12-26 KR		
其他公开文献	US20140014924A1		
外部链接	Espacenet USPTO		

摘要(译)

一种有机发光显示装置包括：基板；在基板上的绝缘层，并包括沿第一方向和邻近于第一区域和沿所述第一方向排列的第二区域布置的第一区；在绝缘层上的第一线，以覆盖第一区域和包括第一有机发光层；和绝缘层上的第二线以覆盖第二区域和包括第一有机发光层不同的第二有机发光层。所述第一区域的一部分，并彼此面对的的第二区域的一部分不平行于第一方向。

