



US 20140071175A1

(19) **United States**

(12) **Patent Application Publication**
Yang et al.

(10) **Pub. No.: US 2014/0071175 A1**

(43) **Pub. Date: Mar. 13, 2014**

(54) **ORGANIC LIGHT EMITTING DISPLAY
DEVICE AND DRIVING METHOD THEREOF**

(30) **Foreign Application Priority Data**

Sep. 12, 2012 (KR) 10-2012-0100881

(71) Applicant: **SAMSUNG DISPLAY CO., LTD.**,
Yongin-city (KR)

Publication Classification

(72) Inventors: **Ji-Yeon Yang**, Yongin-city (KR);
Geun-Young Jeong, Yongin-city (KR);
Takeshi Kato, Yongin-city (KR);
Myung-Ho Lee, Yongin-city (KR)

(51) **Int. Cl.**
G09G 3/32 (2006.01)

(52) **U.S. Cl.**
CPC **G09G 3/3208** (2013.01)
USPC **345/690**

(73) Assignee: **Samsung Display Co., Ltd.**, Yongin-city
(KR)

(57) **ABSTRACT**

An organic light emitting display device and a driving method thereof are disclosed. The display device has sub-pixels of multiple colors. In one aspect, the organic light emitting display device detects sub-pixels which are positioned at the edges of the panel. Data for the sub-pixels on the edges are reduced so that colors on the edges are less observable.

(21) Appl. No.: **13/752,154**

(22) Filed: **Jan. 28, 2013**




FIG. 1




FIG. 2A




FIG. 2B




FIG. 2C




FIG. 2D




FIG. 3A




FIG. 3B




FIG. 3C




FIG. 3D




FIG. 4




FIG. 5





FIG. 6



ORGANIC LIGHT EMITTING DISPLAY DEVICE AND DRIVING METHOD THEREOF

CROSS-REFERENCE TO RELATED APPLICATIONS

[0001] This application claims priority to and the benefit of Korean Patent Application No. 10-2012-0100881, filed on Sep. 12, 2012, in the Korean Intellectual Property Office, the entire content of which is incorporated herein by reference.

BACKGROUND

[0002] 1. Field

[0003] The disclosed technology relates to an organic light emitting display device and a driving method thereof, and more particularly, to an organic light emitting display device and a driving method thereof having high image quality.

[0004] 2. Description of the Related Technology

[0005] An organic light emitting display (OLED) device is used to display an image using organic light emitting diodes that are self-luminescent elements. Such a display device is widely used as a next-generation display device because of its excellent luminance and color purity.

[0006] In display devices, pixels include red sub-pixels, green sub-pixels and blue sub-pixels, and accordingly, various color images are displayed.

[0007] The red sub-pixels, the green sub-pixels and the blue sub-pixels may be arranged in various configurations. The red sub-pixels, the green sub-pixels and the blue sub-pixels are generally arranged linearly, for example, such that sub-pixels of the same color are arranged in a column.

[0008] If the sub-pixels are linearly arranged, an aperture ratio is reduced by black non-emitting structure positioned between the respective sub-pixels, and the ability to display a high-resolution image is degraded.

[0009] To solve such a problem, "ClairVoyante Laboratories Inc." has proposed a pixel arrangement structure, entitled as "The Pentile Matrix Color Pixel Arrangement." In the Pentile matrix color pixel arrangement, red and blue sub-pixels are alternately formed on the same column, and green sub-pixels are formed on an adjacent column. Furthermore, color pixel arrangement, the number of sub-pixels is decreased to approximately $\frac{2}{3}$ of that in the linear arrangement, a high aperture ratio is achieved. Such an arrangement may be applied in an OLED display device to display a high-resolution image and to improve image quality by using a structure in which does use the linear arrangement. However, in the Pentile arrangement, green and red colors are seen as lines (greenish and pinkish) at edges of the OLED display device.

SUMMARY OF CERTAIN INVENTIVE ASPECTS

[0010] One inventive aspect is an organic light emitting display device. The display device includes a pixel unit having a plurality of sub-pixels, a scan driver configured to drive scan lines coupled to the sub-pixels, a data driver configured to drive data lines coupled to the sub-pixels and positioned in a direction intersecting the scan lines, and a data processor configured to receive a first data and to generate a second data based on the first data. The data processor generates the second data by changing grayscale values of the first data for sub-pixels positioned at edges of the pixel unit.

[0011] Another inventive aspect is a method of driving an organic light emitting display device. The method includes

sensing a sub-pixel color arrangement of a display panel, and generating second data by changing grayscale values of first data to be supplied to sub-pixels positioned at edges of the panel, according to the sub-pixel color arrangement.

BRIEF DESCRIPTION OF THE DRAWINGS

[0012] The accompanying drawings, together with the specification, illustrate exemplary embodiments, and, together with the description, serve to explain certain inventive features, aspects, and principles.

[0013] FIG. 1 is a view illustrating a pixel arrangement structure of an organic light emitting display device according to an embodiment.

[0014] FIGS. 2A to 2D are views illustrating patterns of data corresponding to positions of a panel.

[0015] FIGS. 3A to 3D are views illustrating states in which specific colors are recognized in the form of lines, corresponding to positions of the panel.

[0016] FIG. 4 is a block diagram illustrating an organic light emitting display device according to an embodiment.

[0017] FIG. 5 is a block diagram illustrating a data processor according to an embodiment.

[0018] FIG. 6 is a flowchart illustrating an operation of a dimming unit according to an embodiment.

DETAILED DESCRIPTION OF CERTAIN INVENTIVE EMBODIMENTS

[0019] Hereinafter, certain exemplary embodiments are described with reference to the accompanying drawings. Here, when a first element is described as being coupled to a second element, the first element may be directly coupled to the second element or may be indirectly coupled to the second element via a third element. Further, some of the elements that are not essential to the complete understanding are omitted for clarity. Also, like reference numerals generally refer to like elements throughout.

[0020] FIG. 1 is a view illustrating a pixel arrangement structure of an organic light emitting display device according to an embodiment. Referring to FIG. 1, in the organic light emitting display device according to this embodiment, red and blue sub-pixels R and B are repetitively arranged on a particular column, and a green sub-pixel is repetitively arranged adjacent to the particular column. That is, the sub-pixels R, G and B are arranged in a Pentile matrix form.

[0021] Red and green sub-pixels R and G or blue and green sub-pixels B and G are arranged in each pixel region 100. In each pixel region 100, the red and green sub-pixels R and G are positioned in a diagonal direction. In this case, the interval between the red and green sub-pixels R and G may be a high-resolution panel. Similarly, the blue and green sub-pixels B and G are also positioned in a diagonal direction. Meanwhile, in some embodiments of the organic light emitting display device, the sub-pixels R, G, B and G positioned in two adjacent pixel regions 100 constitute one pixel to be driven.

[0022] In the pixel arrangement structure of some embodiments, the green sub-pixel G may be formed to have a narrower area than the red and blue sub-pixels R and B, in consideration of light emitting efficiency. The blue sub-pixel B may be formed to have a wider area than the red sub-pixel R, in consideration of the light emitting efficiency. The areas of the sub-pixels R, G and B may be changed in consideration of the light emitting efficiency.

[0023] Meanwhile, in a case where a panel having the pixel arrangement structure of some embodiments is used in a portable device, data is changed and supplied depending on a change in position of the panel. For example, in a case where the panel is driven at a normal position, the data is supplied in a first pattern (R, G, B, G, . . .) as shown in FIG. 2A. In a case where the panel is rotated to the left side at 90 degrees, the data is supplied in a second pattern (G, B, G, R, . . .) as shown in FIG. 2B. In a case where the panel is rotated to the right side at 90 degrees, the data is supplied in a third pattern (B, G, R, G, . . .) as shown in FIG. 2C. In a case where the panel is vertically reversed, the data is supplied in a fourth pattern (G, R, G, B, . . .) as shown in FIG. 2D. However, in the organic light emitting display device of some embodiments in which the sub-pixels are arranged in the Pentile matrix form, there is a problem in that one color is seen at an edge of the panel.

[0024] Practically, in a case where the data is input in the first pattern, as shown in FIG. 3A, a pinkish strip may be strongly recognized at upper and left edges, and a greenish stripe is strongly recognized at a right edge. Similarly, in a case where the data is supplied in the second to fourth patterns, pinkish and greenish stripes are strongly recognized at edges as shown in FIGS. 3B to 3D.

[0025] To solve such a problem, a dimming process may be performed on data supplied to sub-pixels R, G and B positioned at the edges of the panel. Here, the dimming process refers to a process of reducing the grayscale value of the data supplied to the edges of the panel so as to prevent the color from being strongly recognized along the edges.

[0026] FIG. 4 is a block diagram illustrating an organic light emitting display device according to an embodiment. Referring to FIG. 4, the organic light emitting display device according to this embodiment includes a scan driver 10 for driving scan lines S1 to Sn, a data driver 20 for driving data lines D1 to Dm, a timing controller 50 for controlling the scan driver 10 and the data driver 20, and a data processor 30 for generating a second data data2 by performing a dimming process on a first data data1 supplied from the outside thereof.

[0027] The sub-pixels R, G and B are arranged into a structure, as shown in FIG. 1, in a pixel unit 40 in which the scan lines S1 to Sn and the data lines D1 to Dm intersect with each other. The scan driver 10 supplies a scan signal to the scan lines S1 to Sn. Here, the scan driver 10 may supply the scan signal in a forward or reverse direction, corresponding to the position of a panel. The data driver 20 generates a data signal using the second data data2, and supplies the generated data signal to the data lines D1 to Dm in synchronization with the scan signal. Then, the data signal is supplied to sub-pixels R, G and B selected by the scan signal. The timing controller 50 supplies a control signal (not shown) for controlling the scan driver 10 and the data driver 20. The timing controller 50 provides, to the data driver 20, the second data data2 supplied from the data processor 30. The data processor 30 generates the second data data2 by detecting a pattern (one of the first to fourth patterns) of data and performing a dimming process on the first data data1, corresponding to the detected pattern. Practically, the data processor 30 generates the second data data2 by reducing the grayscale value of the first data data1 to be supplied outermost sub-pixels of the panel so that a specific color is not recognized at an edge of the panel. The detailed operation of the data processor 30 will be described later.

[0028] FIG. 5 is a block diagram illustrating the data processor according to an embodiment. Referring to FIG. 5, the

data processor 30 according to this embodiment includes a sub-pixel rendering (SPR) unit 32 and a dimming unit 34.

[0029] The SPR unit 32 operates according to an algorithm for improving readability of characters, etc. Any one of various algorithms currently known in the art may be applied with the SPR unit 32 in conjunction with a Pentile pixel arrangement. Additionally, the SPR unit 32 may be omitted in some embodiments. The dimming unit 34 generates the second data data2 by controlling the grayscale values of the first data data1 to be supplied sub-pixels positioned at the outermost edges of the panel, corresponding to the pattern of data.

[0030] FIG. 6 is a flowchart illustrating a method of operating the dimming unit according to an embodiment. Referring to FIG. 6, the dimming unit 34 checks whether or not the first data data1 input thereto is a data of the first or last line. Practically, as shown FIGS. 3A to 3D, the first data data1 supplied to the first and last lines is generated as the second data data2 by performing a dimming process on the first data data1.

[0031] The dimming unit 34 generates the second data data2 by performing a dimming process on the first data data1 to be supplied to the first and last pixels positioned on each of the lines other than the first and last lines. That is, the dimming unit 34 generates the second data data2 by reducing the grayscale values of the first data data1 to be supplied to sub-pixels R, G and B positioned at edges of the panel, and supplies the generated second data data2 to the timing controller 50.

[0032] The operation of the dimming unit 34 will be described in further detail. The dimming unit 34 decides whether or not the first data data1 input from the outside thereof is a data to be supplied to the first line (S200). In a case where it is decided in step S200 that the first data data1 is the data to be supplied to the first line, the dimming unit 34 checks a pattern of the data pattern (S202). Here, the pattern of the data is divided into first, second, third and fourth patterns as shown in FIGS. 3A to 3D.

[0033] In a case where it is decided in step S202 that the pattern of the data is the first pattern, the dimming unit 34 decides whether or not the first data data1 is supplied to the first pixel of the first line (S204).

[0034] In a case where it is decided in step 204 that the first data data1 is supplied to the first pixel, the dimming unit 34 decides whether the pattern of the data is the second or fourth pattern (S206). Here, the pattern of the data has been decided as the first pattern in step S202, and hence the dimming unit 34 generates the second data data2 by performing a dimming process on the first data data1 to be supplied to red and blue sub-pixels R and B (S214) (dimming process of R and B positioned at upper edge/left edge of FIG. 3).

[0035] In a case where the first data data1 does not correspond to the first pixel in step S204, the dimming unit 34 decides whether or not the first data data1 is input to the last pixel of the first line (S210). If it is decided in step S210 that the first data data1 is supplied to the last pixel, the dimming unit 34 decides whether the pattern of the data is the first or third pattern (S212). Here, the pattern of the data has been decided as the first pattern in step S202, and hence the dimming unit 34 performs a dimming process on the first data data1 corresponding to red, blue and green sub-pixels R, B and G2 (dimming process of R, B and G positioned at upper edge/right edge of FIG. 3A). Here, that the green sub-pixel is designated by G2 means that the green sub-pixel is positioned in the same pixel region 100 as the blue sub-pixel B. For convenience of illustration, the green sub-pixel positioned in

the same pixel region 100 as the red sub-pixel R is designated by G1. Meanwhile, in a case where it is decided in step S210 that the first data data1 is not input to the last pixel, i.e., in a case where the first data data1 is input to one of the pixels positioned between the first and last pixels, the dimming unit 34 performs a dimming process on the first data data1, corresponding to the red and blue sub-pixels R and B (S214). As described above, in a case where the data of the first pattern is input, the dimming unit 34 generates the second data data2 by performing a dimming process on the first data data1 corresponding to sub-pixels positioned at the upper edge while passing through steps S202 to S214.

[0036] In a case where it is decided in step S202 that the pattern of the data is the second pattern, the dimming unit 34 decides whether or not the first data data1 is supplied to the first pixel of the first line (S204).

[0037] If it is decided in step 204 that the first data data1 is supplied to the first pixel, the dimming unit 34 decides whether the pattern of the data is the second or fourth pattern (S206). Here, the pattern of the data has been decided as the second pattern in step S202, the dimming unit 34 generates the second data data2 by performing a dimming process on the first data data1 when the first data data1 is supplied to the red, blue and green sub-pixels R, B and G2 included in the first pixel (S208) (dimming process of R, B and G positioned at upper edge/left edge of FIG. 3B).

[0038] In a case where the first data data1 does not correspond to the first pixel in step S204, the dimming unit 34 decides whether or not the first data data1 is input to the last pixel (S210). In a case where it is decided in step S210 that the first data data1 is supplied to the last pixel, the dimming unit 34 decides whether the pattern of the data is the first or third pattern (S212). Here, the pattern of the data has been decided as the second pattern in step 202, and hence the dimming unit 34 performs a dimming process on the first data data1 corresponding to the red and blue sub-pixels R and B (S214) (dimming process of R and B positioned at upper edge/right edge of FIG. 3B). Meanwhile, in a case where it is not decided in step S210 that the first data data1 is input to the last pixel, i.e., in a case where the first data data1 is input to one of the pixels positioned between the first and last pixels, the dimming unit 34 performs a dimming process on the first data data1 corresponding to the red and blue sub-pixels R and B (S214). As described above, in a case where the data of the second pattern is input, the dimming unit 34 generates the second data data2 by performing a dimming process on the first data data1 corresponding to sub-pixels positioned at the upper edge while passing through steps S202 to S214.

[0039] In a case where it is decided in step S202 that the pattern of the data is the third pattern, the dimming unit 34 decides whether or not the first data data1 is supplied to the first pixel (S304).

[0040] If it is decided in step S304 that the first data data1 is supplied to the first pixel, the dimming unit 34 decides whether the pattern of the data is the first or third pattern (S306). Here, the pattern of the data has been decided as the third pattern in step S202, and hence the dimming unit 34 generates the second data data2 by performing a dimming process on the first data data1 to be supplied to the green sub-pixels G1 and G2 and the blue sub-pixel B, which are included in the first pixel (S308) (dimming process of B, G and G positioned at upper edge/left edge of FIG. 3C).

[0041] In a case where the first data data1 does not correspond to the first pixel in step S304, the dimming unit 34

decides whether or not the first data data1 is input to the last pixel of the first line (S310). If it is decided in step S310 that the first data data1 is supplied to the last pixel, the dimming unit 34 decides whether the pattern of the data is the second or fourth pattern (S312). Here, the pattern of the data has been decided as the third pattern in step S202, and hence the dimming unit 34 performs a dimming process of the first data data1 corresponding to the green sub-pixels G1 and G2 (S314) (dimming process of G and G positioned at upper edge/right edge of FIG. 3C). Meanwhile, in a case where it is not decided in step S310 that the first data data1 is input to the last pixel, i.e., in a case where the first data data1 is input to one of the pixels between the first and last pixels, the dimming unit 34 performs a dimming process corresponding to the green sub-pixels G1 and G2 (S314). As described above, in a case where the data of the third pattern is input, the dimming unit 34 generates the second data data2 by performing a dimming process on the first data data1 corresponding to the sub-pixels positioned at the upper edge while passing through step S202, and S304 to S314.

[0042] In a case where it is decided in step S202 that the pattern of the data is the fourth pattern, the dimming unit 34 decides whether or not the first data data1 is supplied to the first pixel (S304).

[0043] If it is decided in step S304 that the first data data1 is supplied to the first pixel, the dimming unit 34 decides whether the pattern of the data is the first or third pattern (S306). Here, the pattern of the data has been decided as the fourth pattern in step S202, and hence the dimming unit 34 generates the second data data2 by performing a dimming process on the first data data1 to be supplied to the green sub-pixels G1 and G2 included in the first pixel (S314) (dimming process of G and G positioned at upper edge/left edge of FIG. 3D).

[0044] In a case where the first data data1 does not correspond to the first pixel in step S304, the dimming unit 34 decides whether or not the first data data1 is input to the last pixel (S310). If it is decided in step S310 that the first data data1 is supplied to the last pixel, the dimming unit 34 decides whether the pattern of the data is the second or fourth pattern (S312). Here, the pattern of the data has been decided as the fourth pattern in step S202, and hence the dimming unit 34 generates the second data data2 by performing a dimming process on the first data data1 to be supplied to the green sub-pixels G1 and G2 and the blue sub-pixel B, which are included in the last pixel (S308) (dimming process of G, G and B positioned at upper edge/right edge of FIG. 3D). Meanwhile, in a case where it is not decided in step S310 that the first data data1 is input to the last pixel, i.e., in a case where the first data data1 is input to one of the pixels between the first and last pixels, the dimming unit 34 generates the second data data2 by performing a dimming process on the first data data1 corresponding to the sub-pixels positioned at the upper edge while passing through steps S202 and S304 to S314.

[0045] Meanwhile, it is not decided in step S200 that the first data data1 is the data to be supplied to the first line, the dimming unit 34 decides whether or not the first data data1 is a data to be supplied to the last line (S300). In a case where it is decided in step S300 that the first data data1 is the data to be supplied to the last line, the dimming unit 34 checks a pattern of the data (S302).

[0046] In a case where it is decided in step S302 that the pattern of the data is the first pattern, the dimming unit 34 decides whether the first data data1 is supplied to the first or

last pixel of the last line (S304 and S310). In a case where it is decided in step S304 that the first data data1 is supplied to the first pixel, the dimming unit 34 decides whether the pattern of the data is the first or third pattern (S306). Here, the pattern of the data has been decided as the first pattern in step S302, and hence the dimming unit 34 generates the second data data2 by performing a dimming process on the first data data1 to be supplied to the green pixels G1 and G2 and the blue pixel B, which are included in the first pixel (S308) (dimming process of B, G and G positioned at lower edge/left edge of FIG. 3A).

[0047] In a case where it is decided in step S310 that the first data data1 is supplied to the last pixel, the dimming unit 34 decides whether the pattern of the data is the second or fourth pattern (S312). Here, the pattern of the data has been decided as the first pattern in step S302, the dimming unit 34 generated the second data data2 by performing a dimming process on the first data data1 to be supplied to the green sub-pixels G1 and G2 included in the last pixel (S314) (dimming process of G and G positioned at lower edge/right edge of FIG. 3A). Meanwhile, it is not decided in step S310 that the first data data1 is not input to the last pixel, i.e., in a case where the first data data1 is input to one of the pixels between the first and last pixels, the dimming unit 34 performs a dimming process of the first data data1 corresponding to the green sub-pixels G1 and G2 (S314). As described above, in a case where the data of the first pattern is input, the dimming unit 34 generates the second data data2 by performing a dimming process on the first data data1 corresponding to sub-pixels positioned at a lower edge while passing through steps S302 to S314.

[0048] In a case where it is decided in step S302 that the pattern of the data is the second pattern, the dimming unit 34 decides whether the first data data1 is supplied to the first or last pixel (S304 and S310). In a case where it is decided in step 304 that the first data data1 is supplied to the first pixel, the dimming unit 34 decides whether the pattern of the data is the first or third pattern (S306). Here, the pattern of the data has been decided as the second pattern in step S302, and hence the dimming unit 34 generates the second data data2 by performing a dimming process on the first data data1 to be supplied to the green sub-pixels G1 and G2 included in the first pixel (S314) (dimming process of G and G positioned at lower edge/left edge of FIG. 3B).

[0049] In a case where it is decided in step S310 that the first data data1 is supplied to the last pixel, the dimming unit 34 decides whether the pattern of the data is the second or fourth pattern (S312). Here, the pattern of the data has been decided as the second pattern in step S302, and hence the dimming unit 34 generates the second data data2 by performing a dimming process on the first data data1 to be supplied to the green sub-pixels G1 and G2 and the blue sub-pixel B, which are included in the last pixel (S308) (dimming process of G, G and B positioned at lower edge/right edge of FIG. 3B). Meanwhile, in a case where it is not decided in step S310 that the first data data1 is input to the last pixel, i.e., in a case where the first data data1 is input to one of the pixels between the first and last pixels, the dimming unit 34 performs a dimming process on the first data data1 corresponding to the green sub-pixels G1 and G2 (S314). As described above, in a case where the data of the second pattern is input, the dimming unit 34 generates the second data data2 by performing a dimming process on the first data data1 corresponding to the sub-pixels positioned at the lower edge while passing through steps S302 to S314.

[0050] In a case where it is decided in step S302 that the pattern of the data is the third pattern, the dimming unit 34 decides whether the first data data1 is supplied to the first or last pixel (S204 and S210). In a case where it is decided at step S204 that the first data data1 is supplied to the first pixel, the dimming unit 34 decides whether the pattern of the data is the second or fourth pattern (S206). Here, the pattern of the data has been decided as the third pattern in step S302, and hence the dimming unit 34 generates the second data data2 by performing a dimming process on the first data data1 to be supplied to the red and blue sub-pixels R and B included in the first pixel (S214) (dimming process of R and B positioned at lower edge/left edge of FIG. 3C).

[0051] In a case where it is decided in step S210 that the first data data1 is supplied to the last pixel, the dimming unit 34 decides whether the pattern of the data is the first or third pattern (S212). Here, the pattern of the data has been decided as the third pattern in step S302, and hence the dimming unit 34 generates the second data data2 by performing a dimming process on the first data data1 to be supplied to the red, blue and green sub-pixels R, B and G included in the last pixel (S208) (dimming process of R, B and G positioned at lower edge/right edge of FIG. 3C). Meanwhile, in a case where it is not decided in step S210 that the first data data1 is input to the last pixel, i.e., in a case where the first data data1 is input to one of the pixels between the first and last pixels, the dimming unit 34 performs a dimming process on the first data data1 corresponding to the red and blue sub-pixels R and B (S214). As described above, in a case where the data of the third pattern is input, the dimming unit 34 generates the second data data2 by performing a dimming process on the first data data1 corresponding to the sub-pixels positioned at the lower edge while passing through steps S302 and S204 to S214.

[0052] In a case where it is decided in step S302 that the pattern of the data is the fourth pattern, the dimming unit 34 decides whether the first data data1 is supplied to the first or last pixel (S204 and S210). In a case where it is decided in step S204 that the first data data1 is supplied to the first pixel, the dimming unit 34 decides whether the pattern of the data is the second or fourth pattern (S206). Here, the pattern of the data has been decided as the fourth pattern in step S302, and hence the dimming unit 34 generates the second data data2 by performing a dimming process on the first data data1 to be supplied to the red, blue and green sub-pixels R, B and G2 included in the first pixel (S208) (dimming process of G, B and R positioned at lower edge/left edge of FIG. 3D).

[0053] In a case where it is decided in step S210 that the first data data1 is supplied to the last pixel, the dimming unit 34 decides whether the pattern of the data is the first or third pattern (S212). Here, the pattern of the data has been decided as the fourth pattern in step S302, and hence the dimming unit 34 generates the second data data2 by performing a dimming process on the first data data1 to be supplied to the red and blue sub-pixels R and B included in the last pixel (S214) (dimming process of R and B positioned at lower edge/right edge) of FIG. 3D). Meanwhile, in a case where it is not decided in step S210 that the first data data1 is input to the last pixel, i.e., in a case where the first data data1 is input to one of the pixels between the first and last pixels, the dimming unit 34 performs a dimming process on the first data data1 corresponding to the red and blue sub-pixels R and B (S214). As described above, in a case where the data of the fourth pattern is input, the dimming unit 34 generates the second data data2 by performing a dimming process on the first data data1

corresponding to the sub-pixels positioned at the lower edge while passing through steps S302 and S204 to S214.

[0054] Meanwhile, in a case where it is not decided in step S300 that the first data data1 is the data to be supplied to the last line, i.e., in a case where the first data data1 is a data to be supplied to one of the lines between the first and last lines, the dimming unit 34 checks a pattern of the data (S400).

[0055] In a case where it is decided in step S400 that the pattern of the data is the first or second pattern, the dimming unit 34 decides whether or not the first data data1 is supplied to the first or last sub-pixel (S402 and S411).

[0056] In a case where it is decided in step S402 that the first data data1 is a data corresponding to the first sub-pixel, the dimming unit 34 decides whether or not the pattern of the data is the first pattern (S404). In a case where it is decided in step S404 that the pattern of the data is the first pattern, the dimming unit 34 decides whether or not the first data data1 is supplied to an odd-numbered line (S406). In a case where it is decided in step S406 that the first data data1 is supplied to the odd-numbered line, the dimming unit 34 performing a dimming process on the first data data1 by deciding that the first data data1 is a data to be supplied to the red sub-pixel R (S408). In a case where it is decided in step S406 that the first data data1 is not supplied to the odd-numbered line, the dimming unit 34 performs a dimming process on the first data data1 by deciding that the first data data1 is a data to be supplied to the blue sub-pixel B (S410).

[0057] In a case where it is not decided in step S404 that the pattern of the data is the first pattern, the dimming unit 34 decides whether or not the first data data1 is supplied to the odd-numbered line (S414). In a case where it is decided in step S414 that the first data data1 is supplied to the odd-numbered line, the dimming unit 34 performs a dimming process on the first data data1 by deciding that the first data data1 is a data to be supplied to the green sub-pixel G2 (S416). In a case where it is decided in step S414 that the first data data1 is not supplied to the odd-numbered line, the dimming unit 34 performs a dimming process on the first data data1 by deciding that the first data data1 is the data to be supplied to the green sub-pixel G1 (S418).

[0058] In a case where it is decided in step S411 that the first data data1 is a data corresponding to the last sub-pixel, the dimming unit 34 decides whether or not the pattern of the data is the first pattern (S412). In a case where it is decided in step S412 that the pattern of the data is the first pattern, the dimming unit 34 decides whether or not the first data data1 is supplied to the odd-numbered line (S414). In a case where it is decided in step S414 that the first data data1 is supplied to the odd-numbered line, the dimming unit 34 performs a dimming process on the first data data1 by deciding that the first data data1 is the data to be supplied to the green sub-pixel G2 (S416). In a case where it is decided in step S414 that the first data data1 is not supplied to the odd-numbered line, the dimming unit 34 performs a dimming process on the first data data1 by deciding that the first data data1 is the data to be supplied to the green sub-pixel G1 (S418).

[0059] In a case where it is not decided in step S412 that the pattern of the data is the first pattern, the dimming unit 34 decides whether or not the first data data1 is supplied to the odd-numbered line (S406). In a case where it is decided in step S406 that the first data data1 is supplied to the odd-numbered line, the dimming unit 34 performs a dimming process on the first data data1 by deciding that the first data data1 is a data to be supplied to the red sub-pixel R (S408). In

a case where it is decided in step S406 that the first data data1 is not supplied to the odd-numbered line, the dimming unit 34 performs a dimming process on the first data data1 by deciding that the first data data1 is a data to be supplied to the blue sub-pixel B (S410).

[0060] Practically, in a case where the data of the first or second pattern is input, the dimming unit 34 performs a dimming process on the first data data1 to be supplied to the sub-pixels positioned at edges of the other lines except the first and last lines, i.e., the first and last sub-pixels, using steps S400 to S418.

[0061] In a case where it is decided in step S400 that the pattern of the data is the third or fourth pattern, the dimming unit 34 decides whether the first data data1 is supplied to the first or last sub-pixel (S421 and S425).

[0062] In a case where it is decided in step S421 that the first data data1 is a data corresponding to the first sub-pixel, the dimming unit 34 decides whether or not the pattern of the data is the third pattern (S420). In a case where it is decided in step S420 that the pattern of the data is the third pattern, the dimming unit 34 decides whether or not the first data data1 is supplied to the odd-numbered line (S422). In a case where it is decided in step S422 that the first data data1 is supplied to the odd-numbered line, the dimming unit 34 performs a dimming process of the first data data1 by deciding that the first data data1 is a data to be supplied to the blue sub-pixel B (S410). In a case where it is decided in step S422 that the first data data1 is not supplied to the odd-numbered line, the dimming unit 34 performs a dimming process on the first data data1 by deciding that the first data data1 is a data to be supplied to the red sub-pixel R (S408).

[0063] In a case where it is not decided in step S420 that the pattern of the data is the third pattern, the dimming unit 34 decides whether or not the first data data1 is supplied to the odd-numbered line (S424). In a case where it is decided in step S424 that the first data data1 is supplied to the odd-numbered line, the dimming unit 34 performs a dimming process of the first data data1 by deciding that the first data data1 is a data to be supplied to the green sub-pixel G1 (S418). In a case where it is decided in step S424 that the first data data1 is not supplied to the odd-numbered line, the dimming unit 34 performs a dimming process on the first data data1 by deciding that the first data data1 is a data to be supplied to the green sub-pixel G2 (S416).

[0064] In a case where it is decided in step S425 that the first data data1 is a data corresponding to the last sub-pixel, the dimming unit 34 decides whether or not the pattern of the data is the third pattern (S426). In a case where it is decided in step S426 that the pattern of the data is the third pattern, the dimming unit 34 decides whether or not the first data data1 is supplied to the odd-numbered line (S424). In a case where it is decided in step S424 that the first data data1 is supplied to the odd-numbered line, the dimming unit 34 performs a dimming process of the first data data1 by deciding that the first data data1 is the data to be supplied to the green sub-pixel G1 (S418). In a case where it is decided in step S424 that the first data data1 is not supplied to the odd-numbered line, the dimming unit 34 performs a dimming process on the first data data1 by deciding that the first data data1 is the data to be supplied to the green sub-pixel G2 (S416).

[0065] In a case where it is not decided in step S426 that the pattern of the data is the third pattern, the dimming unit 34 decides whether or not the first data data1 is supplied to the odd-numbered line (S422). In a case where it is decided in

step S422 that the first data data1 is supplied to the odd-numbered line, the dimming unit 34 performs a dimming process on the first data data1 by deciding that the first data data1 is a data to be supplied to the blue sub-pixel B (S410). In a case where it is decided in step S422 that the first data data1 is not supplied to the odd-numbered line, the dimming unit 34 performs a dimming process on the first data data1 by deciding that the first data data1 is a data to be supplied to the red sub-pixel R (S408).

[0066] Practically, in a case where the data of the third or fourth pattern is input, the dimming unit 34 performs a dimming process while repetitively performing the aforementioned procedure on the sub-pixels positioned at the edges of the other lines except the first and last lines, i.e., the first and last sub-pixels.

[0067] As described above, the dimming unit 34 performs a dimming process on data to be supplied to the sub-pixels positioned at the edges of the panel corresponding to the first, second, third and fourth patterns of the data while being driven as shown in FIG. 6. Here, a dimming value corresponding to each of the sub-pixels R, B, G1 and G2 is experimentally determined in consideration of the resolution, inch and light emitting efficiency of the panel. For example, the dimming unit 34 may generate the second data data2 by performing a dimming process on the first data data1 so that the luminance of the sub-pixels is lowered by a factor of $\frac{1}{2}$, corresponding to the red and blue sub-pixels R and B. The dimming unit 34 may generate the second data data2 by performing a dimming process on the first data data1 so that the luminance of the green sub-pixel G1 is lowered by a factor of $\frac{3}{5}$ and the luminance of the green sub-pixel G2 is lowered to $\frac{4}{5}$.

[0068] That is, the dimming unit 34 can detect the red sub-pixel R, the blue sub-pixel B and the green sub-pixels G1 and G2, which are positioned at the edges of the panel, while being driven as shown in FIG. 5. Accordingly, various dimming processes are possible.

[0069] While the various features and aspects have been described in connection with certain exemplary embodiments, it is to be understood that the invention is not limited to the disclosed embodiments, but, on the contrary, is intended to cover various modifications and equivalent arrangements.

What is claimed is:

1. An organic light emitting display device, comprising:
 - a pixel unit including a plurality of sub-pixels;
 - a scan driver configured to drive scan lines coupled to the sub-pixels;
 - a data driver configured to drive data lines coupled to the sub-pixels and positioned in a direction intersecting the scan lines; and
 - a data processor configured to receive a first data and to generate a second data based on the first data, wherein the data processor generates the second data by changing grayscale values of the first data for sub-pixels positioned at edges of the pixel unit.
2. The organic light emitting display device according to claim 1, wherein the data processor comprises a dimming unit that generates the second data.
3. The organic light emitting display device according to claim 2, wherein the dimming unit generates the second data by reducing the grayscale values of the first data.
4. The organic light emitting display device according to claim 2, wherein the dimming unit generates the second data

by changing the grayscale values of the first data for sub-pixels positioned at four outermost edges of the pixel unit.

5. The organic light emitting display device according to claim 1, wherein pixel regions are provided to the pixel unit, and any one of blue and red sub-pixels and a green sub-pixel are arranged in a diagonal direction in each pixel region.

6. The organic light emitting display device according to claim 5, wherein red and blue sub-pixels are repetitively arranged in a particular column of the pixel unit, and green sub-pixels are repetitively arranged in a column adjacent to the particular column.

7. A method of driving an organic light emitting display device, the method comprising:

sensing a sub-pixel color arrangement of a display panel; and

generating second data by changing grayscale values of first data to be supplied to sub-pixels positioned at edges of the panel, according to the sub-pixel color arrangement.

8. The method according to claim 7, wherein the display panel includes pixel regions, and any one of blue and red sub-pixels and a green sub-pixels are arranged in a diagonal direction in each pixel region.

9. The method according to claim 8, wherein the red and blue sub-pixels are repetitively arranged in a particular column of the panel, and the green sub-pixels are repetitively arranged in a column adjacent to the particular column.

10. The method according to claim 8, wherein a blue sub-pixel, a red sub-pixel and two green sub-pixels, arranged in two adjacent pixel regions, constitute a pixel.

11. The method according to claim 7, wherein the second data is generated by reducing the grayscale values of the first data.

12. The method according to claim 7, wherein generating the second data comprises:

deciding whether the first data is a data for the first line, the last line or the other lines of the display panel;

generating the second data by changing the grayscale value of the first data supplied to all sub-pixels positioned in the first line when the first data is for the first line;

generating the second data by changing the grayscale values of the first data supplied to all sub-pixels positioned in the last line when the first data is for the last line; and

generating the second data by changing the grayscale values of the first data supplied to the first and last sub-pixels of a line when the first data is for a line other than the first and last lines.

13. The method according to claim 12, wherein generating the second data corresponding to the first line comprises:

generating the second data by changing the grayscale values of the first data for sub-pixels positioned at outermost edges for the sub-pixels included in the first and last pixels; and

generating the second data by changing the grayscale values of the first data for sub-pixels positioned at outermost edges for the sub-pixels not included in the first and last pixels.

14. The method according to claim 12, wherein generating the second data corresponding to the last line comprises:

generating the second data by changing the grayscale values of the first data for sub-pixels positioned at outermost edges for the sub-pixels included in the first and last pixels; and

generating the second data by changing the grayscale values of the first data for sub-pixels positioned at outermost edges for the sub-pixels not included in the first and last pixels.

15. The method according to claim **12**, wherein generating the second data corresponding to the other lines comprises:

deciding whether the first data is for the first or last sub-pixel;

generating the second data by changing the grayscale values of the first data when it is decided that the first data is for the first sub-pixel; and

generating the second data by changing the grayscale values of the first data when it is decided that the first data is for the last sub-pixel.

16. The method according to claim **15**, further comprising deciding whether the first and last sub-pixels are positioned on an odd-numbered or even-numbered line.

* * * * *

专利名称(译)	有机发光显示装置及其驱动方法		
公开(公告)号	US20140071175A1	公开(公告)日	2014-03-13
申请号	US13/752154	申请日	2013-01-28
[标]申请(专利权)人(译)	三星显示有限公司		
申请(专利权)人(译)	三星DISPLAY CO. , LTD.		
当前申请(专利权)人(译)	三星DISPLAY CO. , LTD.		
[标]发明人	YANG JI YEON JEONG GEUN YOUNG KATO TAKESHI LEE MYUNG HO		
发明人	YANG, JI-YEON JEONG, GEUN-YOUNG KATO, TAKESHI LEE, MYUNG-HO		
IPC分类号	G09G3/32		
CPC分类号	G09G3/3208 G09G3/20 G09G2300/0426 G09G2300/0452 G09G2300/0465 G09G2310/0232 G09G2320/0242 G09G3/3233 G09G3/3291 H01L27/3216 H01L51/5203		
优先权	1020120100881 2012-09-12 KR		
其他公开文献	US10147351		
外部链接	Espacenet USPTO		

摘要(译)

公开了一种有机发光显示装置及其驱动方法。显示装置具有多种颜色的子像素。在一个方面，有机发光显示装置检测位于面板边缘的子像素。边缘上的子像素的数据减少，使得边缘上的颜色较不可观察。

