



US010224482B2

(12) **United States Patent**
Lee et al.

(10) **Patent No.:** **US 10,224,482 B2**
(45) **Date of Patent:** ***Mar. 5, 2019**

(54) **MASKS, METHOD TO INSPECT AND ADJUST MASK POSITION, AND METHOD TO PATTERN PIXELS OF ORGANIC LIGHT-EMITTING DISPLAY DEVICE UTILIZING THE MASKS**

(52) **U.S. Cl.**
CPC **H01L 51/0011** (2013.01); **H01L 27/3211** (2013.01); **H01L 27/3223** (2013.01);
(Continued)

(58) **Field of Classification Search**
CPC .. **H01L 51/0011**; **H01L 27/3211**; **H01L 51/56**; **H01L 27/1288**; **H01L 27/3244**;
(Continued)

(71) Applicant: **Samsung Display Co., Ltd.**, Yongin-si (KR)

(72) Inventors: **Sangshin Lee**, Yongin-si (KR); **Dongjin Ha**, Yongin-si (KR); **Mingoo Kang**, Yongin-si (KR); **Ohseob Kwon**, Yongin-si (KR); **Sangmin Yi**, Yongin-si (KR)

(56) **References Cited**

U.S. PATENT DOCUMENTS

9,705,082 B2* 7/2017 Lee H01L 27/3223
2010/0026173 A1 2/2010 Lhee et al.
2014/0071030 A1 3/2014 Lee

FOREIGN PATENT DOCUMENTS

KR 10-1999-0031827 5/1999
KR 10-2007-0072271 7/2007
(Continued)

OTHER PUBLICATIONS

Notice of Allowance dated Dec. 27, 2016, in U.S. Appl. No. 14/883,989.

(Continued)

Primary Examiner — Caleen Sullivan

(74) *Attorney, Agent, or Firm* — H.C. Park & Associates, PLC

(73) Assignee: **Samsung Display Co., Ltd.**, Yongin-si (KR)

(*) Notice: Subject to any disclaimer, the term of this patent is extended or adjusted under 35 U.S.C. 154(b) by 0 days.

This patent is subject to a terminal disclaimer.

(21) Appl. No.: **15/630,877**

(22) Filed: **Jun. 22, 2017**

(65) **Prior Publication Data**

US 2017/0288143 A1 Oct. 5, 2017

Related U.S. Application Data

(63) Continuation of application No. 14/883,989, filed on Oct. 15, 2015, now Pat. No. 9,705,082.

(30) **Foreign Application Priority Data**

May 19, 2015 (KR) 10-2015-0069351

(51) **Int. Cl.**


H01L 51/00 (2006.01)
H01L 51/56 (2006.01)

(Continued)

(57) **ABSTRACT**

A method for pixel patterning and pixel position inspection of an organic light-emitting display device includes: forming, on a substrate using a first mask, a thin film layer of a first color corresponding to a first pixel pattern and a first pixel positioning pattern for inspecting a position of a first pixel; shifting, by a determined pitch, the first mask from a position associated with forming the thin film layer of the first color; aligning the shifted first mask with respect to the substrate; and forming, on the substrate using the shifted first mask, a thin film layer of a second color corresponding to the

(Continued)



first pixel pattern and another first pixel positioning pattern for inspecting a position of a second pixel.

51/5012; C23C 14/042; C23C 14/12; C23C 14/24; H05B 33/10; C08L 33/02; C08L 79/02; C08L 2203/204; C08K 3/346

17 Claims, 9 Drawing Sheets

USPC 438/14
See application file for complete search history.

(56) **References Cited**

FOREIGN PATENT DOCUMENTS

- (51) **Int. Cl.**
H01L 27/32 (2006.01)
H01L 51/50 (2006.01)
- (52) **U.S. Cl.**
 CPC *H01L 51/56* (2013.01); *H01L 51/5012* (2013.01); *H01L 51/5088* (2013.01)
- (58) **Field of Classification Search**
 CPC ... H01L 27/12; H01L 51/5056; H01L 27/322; H01L 27/3262; H01L 27/3218; H01L 27/3248; H01L 51/0008; H01L 51/5036; H01L 31/0481; H01L 51/5088; H01L

KR	10-2010-0015176	2/2010
KR	10-2014-0035239	3/2014
KR	10-2014-0086346	7/2014

OTHER PUBLICATIONS

Notice of Allowance dated Mar. 7, 2017, in U.S. Appl. No. 14/883,989.
Notice of Allowance dated Apr. 10, 2017, in U.S. Appl. No. 14/883,989.

* cited by examiner

FIG. 1




FIG. 2




FIG. 3




FIG. 4A




FIG. 4B




FIG. 4C

FIG. 4D




FIG. 5A




FIG. 5B




FIG. 5C




FIG. 5D




FIG. 6A




FIG. 6B

180°
⇒





FIG. 6C

FIG. 6D



1

**MASKS, METHOD TO INSPECT AND
ADJUST MASK POSITON, AND METHOD
TO PATTERN PIXELS OF ORGANIC
LIGHT-EMITTING DISPLAY DEVICE
UTILIZING THE MASKS**

CROSS-REFERENCE TO RELATED
APPLICATION

This application is a Continuation of U.S. patent appli-
cation Ser. No. 14/883,989, filed Oct. 15, 2015, and claims
priority from and the benefit of Korean Patent Application
No. 10-2015-0069351, filed May 19, 2015, each of which is
incorporated by reference for all purposes as if fully set forth
herein.

BACKGROUND

Field

Exemplary embodiments relate to formation of thin films,
and, more particularly, to a mask and a method of forming
and inspecting the position accuracy of a thin film pattern via
a deposition process utilizing the mask.

Discussion

Vapor deposition typically involves generating vapor
from a deposition source and allowing the vapor to adhere
to a substrate surface. For instance, a mask may be disposed
on (or over) a substrate, and vapor from a deposition source
may be allowed to pass through openings in a mask and on
the substrate to form a desired thin film pattern on the
substrate. Such thin film manufacturing techniques may be
used to form thin film pattern associated with flat panel
display devices, such as an organic light-emitting device
(OLED). For example, the thin film pattern may correspond
to a thin film pixel pattern.

The above information disclosed in this Background
section is only for enhancement of understanding of the
background of the inventive concept, and, therefore, it may
contain information that does not form the prior art that is
already known in this country to a person of ordinary skill
in the art.

SUMMARY

Exemplary embodiments provide a mask used to form a
thin film pixel pattern for an organic light-emitting display
device.

Exemplary embodiments provide a method for pixel
patterning and inspecting pixel positioning in an organic
light-emitting display device.

Additional aspects will be set forth in part in the descrip-
tion which follows, and, in part, will be apparent from the
disclosure, or may be learned by practice of the inventive
concept.

According to one or more exemplary embodiments, a
method for pixel patterning and pixel position inspection of
an organic light-emitting display device includes: forming,
on a substrate using a first mask, a thin film layer of a first
color corresponding to a first pixel pattern and a first pixel
positioning pattern for inspecting a position of a first pixel;
shifting, by a determined pitch, the first mask from a position
associated with forming the thin film layer of the first color;
aligning the shifted first mask with respect to the substrate;
and forming, on the substrate using the shifted first mask, a

2

thin film layer of a second color corresponding to the first
pixel pattern and another first pixel positioning pattern for
inspectng a position of a second pixel.

According to one or more exemplary embodiments, a
pixel patterning mask for an organic light-emitting display
device includes: a pixel pattern; a first inspection pattern for
inspectng a first pixel position, the first inspection pattern
being configured to facilitate measurement of position accu-
racy of a thin film layer formed on a substrate via the pixel
pattern; and a second inspection pattern for inspectng a
second pixel position, the second inspection pattern being
configured to facilitate measurement of position accuracy of
a thin film layer formed on the substrate via the pixel pattern.
The second inspection pattern is formed in a different
position than the first inspection pattern.

The foregoing general description and the following
detailed description are exemplary and explanatory and are
intended to provide further explanation of the claimed
subject matter.

BRIEF DESCRIPTION OF THE DRAWINGS

The accompanying drawings, which are included to pro-
vide a further understanding of the inventive concept, and
are incorporated in and constitute a part of this specification,
illustrate exemplary embodiments of the inventive concept,
and, together with the description, serve to explain princi-
ples of the inventive concept.

FIG. 1 is a schematic view of a thin film deposition
apparatus, according to one or more exemplary embodi-
ments.

FIG. 2 is a cross-sectional view of a unit pixel structure
of an organic light-emitting display device that may be
formed via the thin film deposition apparatus of FIG. 1,
according to one or more exemplary embodiments.

FIG. 3 is a plan view of marks and thin film patterns
formed on a substrate that may be utilized to accurately
position a mask in association with a pixel for thin film
deposition, according to one or more exemplary embodi-
ments.

FIGS. 4A, 4B, 4C, and 4D illustrate a method of pattern-
ing an emission layer of a first pixel and an emission layer
of a second pixel using a first mask, according to one or
more exemplary embodiments.

FIGS. 5A, 5B, 5C, and 5D illustrate a method of pattern-
ing an emission layer of a first pixel and an auxiliary layer
of the first pixel using the first mask of FIGS. 4A, 4B, 4C,
and 4D, according to one or more exemplary embodiments.

FIGS. 6A, 6B, 6C, and 6D illustrate a method of pattern-
ing an emission layer of a third pixel and an auxiliary layer
of the third pixel using a second mask, according to one or
more exemplary embodiments.

DETAILED DESCRIPTION OF THE
ILLUSTRATED EMBODIMENTS

In the following description, for the purposes of expla-
nation, numerous specific details are set forth in order to
provide a thorough understanding of various exemplary
embodiments. It is apparent, however, that various exem-
plary embodiments may be practiced without these specific
details or with one or more equivalent arrangements. In
other instances, well-known structures and devices are
shown in block diagram form in order to avoid unnecessarily
obscuring various exemplary embodiments.

In the accompanying figures, the size and relative sizes of layers, films, panels, regions, etc., may be exaggerated for clarity and descriptive purposes. Also, like reference numerals denote like elements.

When an element or layer is referred to as being “on,” “connected to,” or “coupled to” another element or layer, it may be directly on, connected to, or coupled to the other element or layer or intervening elements or layers may be present. When, however, an element or layer is referred to as being “directly on,” “directly connected to,” or “directly coupled to” another element or layer, there are no intervening elements or layers present. For the purposes of this disclosure, “at least one of X, Y, and Z” and “at least one selected from the group consisting of X, Y, and Z” may be construed as X only, Y only, Z only, or any combination of two or more of X, Y, and Z, such as, for instance, XYZ, XYY, YZ, and ZZ. Like numbers refer to like elements throughout. As used herein, the term “and/or” includes any and all combinations of one or more of the associated listed items.

Although the terms “first,” “second,” etc. may be used herein to describe various elements, components, regions, layers, and/or sections, these elements, components, regions, layers, and/or sections should not be limited by these terms. These terms are used to distinguish one element, component, region, layer, and/or section from another element, component, region, layer, and/or section. Thus, a first element, component, region, layer, and/or section discussed below could be termed a second element, component, region, layer, and/or section without departing from the teachings of the present disclosure.

Spatially relative terms, such as “beneath,” “below,” “lower,” “above,” “upper,” and the like, may be used herein for descriptive purposes, and, thereby, to describe one element or feature’s relationship to another element(s) or feature(s) as illustrated in the drawings. Spatially relative terms are intended to encompass different orientations of an apparatus in use, operation, and/or manufacture in addition to the orientation depicted in the drawings. For example, if the apparatus in the drawings is turned over, elements described as “below” or “beneath” other elements or features would then be oriented “above” the other elements or features. Thus, the exemplary term “below” can encompass both an orientation of above and below. Furthermore, the apparatus may be otherwise oriented (e.g., rotated 90 degrees or at other orientations), and, as such, the spatially relative descriptors used herein interpreted accordingly.

The terminology used herein is for the purpose of describing particular embodiments and is not intended to be limiting. As used herein, the singular forms, “a,” “an,” and “the” are intended to include the plural forms as well, unless the context clearly indicates otherwise. Moreover, the terms “comprises,” “comprising,” “includes,” and/or “including,” when used in this specification, specify the presence of stated features, integers, steps, operations, elements, components, and/or groups thereof, but do not preclude the presence or addition of one or more other features, integers, steps, operations, elements, components, and/or groups thereof. Unless stated otherwise, a specific process order may be performed differently than described. For example, two consecutively described processes may be performed substantially at the same time or performed in an order opposite to the described order.

Various exemplary embodiments are described herein with reference to sectional illustrations that are schematic illustrations of idealized exemplary embodiments and/or intermediate structures. As such, variations from the shapes

of the illustrations as a result, for example, of manufacturing techniques and/or tolerances, are to be expected. Thus, exemplary embodiments disclosed herein should not be construed as limited to the particular illustrated shapes of regions, but are to include deviations in shapes that result from, for instance, manufacturing. For example, an implanted region illustrated as a rectangle will, typically, have rounded or curved features and/or a gradient of implant concentration at its edges rather than a binary change from implanted to non-implanted region. Likewise, a buried region formed by implantation may result in some implantation in the region between the buried region and the surface through which the implantation takes place. Thus, the regions illustrated in the drawings are schematic in nature and their shapes are not intended to illustrate the actual shape of a region of a device and are not intended to be limiting.

Unless otherwise defined, all terms (including technical and scientific terms) used herein have the same meaning as commonly understood by one of ordinary skill in the art to which this disclosure is a part. Terms, such as those defined in commonly used dictionaries, should be interpreted as having a meaning that is consistent with their meaning in the context of the relevant art and will not be interpreted in an idealized or overly formal sense, unless expressly so defined herein.

FIG. 1 is a schematic view of a thin film deposition apparatus, according to one or more exemplary embodiments.

As seen in FIG. 1, the thin film deposition apparatus includes a mask **200** for forming a desired pattern on a substrate **300**, which is a deposition object, and a deposition source unit **100**. The deposition source unit **100** may be configured to reciprocate back and forth inside a chamber **400** and to spray (or otherwise release) a deposition gas toward the substrate **300**. Accordingly, when the deposition source unit **100** sprays the deposition gas inside the chamber **400**, the deposition gas may pass through openings formed in the mask **200** and may be deposited on the substrate **300** to form a thin film in a determined pattern.

FIG. 2 is a cross-sectional view of a unit pixel structure of an organic light-emitting display device that may be formed via the thin film deposition apparatus of FIG. 1, according to one or more exemplary embodiments. For example, substrate **300** of FIG. 1 may be substrate **300** of the organic light-emitting display device of FIG. 2. The unit pixel may include three color sub-pixels, e.g., a red (R) sub-pixel, a green (G) sub-pixel, and a blue (B) sub-pixel. It is contemplated, however, that any suitable color and number of sub-pixels may be formed utilized in association with exemplary embodiments described herein. For descriptive convenience, the various sub-pixels of the unit pixel will, hereinafter, be referred to as pixels.

Referring to FIG. 2, the unit pixel may include a buffer layer **330** formed on the substrate **300**, a thin film transistor TFT_R for a red pixel R, a thin film transistor TFT_G for a green pixel G, and a thin film transistor TFT_B for a blue pixel B disposed on a surface (e.g., an upper surface) of the buffer layer **330**. Each of the thin film transistors TFT_R, TFT_G, and TFT_B may include a semiconductor active layer **331**, a gate insulating layer **332** covering the semiconductor active layer **331**, and a gate electrode **333** disposed on the gate insulating layer **332**, e.g., on an upper surface of the gate insulating layer **332**. An interlayer insulating layer **334** is formed to cover the gate electrode **333**. A source electrode **335** and a drain electrode **336** are formed on the upper portion of the interlayer insulating layer **334**. The source

electrode **335** and the drain electrode **336** contact a source region and a drain region of the semiconductor active layer **331**, respectively, via corresponding contact holes formed in the gate insulating layer **332** and the interlayer insulating layer **334**.

Corresponding pixel electrodes **320_R**, **320_G**, and **320_B** of respective organic light-emitting devices EL_R, EL_G, and EL_B are connected to the source electrodes **335** and drain electrodes **336** of the color pixels, respectively. The respective pixel electrodes **320_R**, **320_G**, and **320_B** may be formed on a planarization layer **337**. A pixel-defining layer **338** may cover the pixel electrodes **320_R**, **320_G**, and **320_B**. An interlayer including emission layers **323_R**, **323_G**, and **323_B** and an auxiliary layer is formed on the pixel electrodes **320_R**, **320_G**, and **320_B**. An opposite electrode **326** is formed on the respective interlayers.

The auxiliary layer includes hole injection layers **321_R** and **321_G**, a hole transport layer **322**, an electron transport layer **324**, and an electron injection layer **325**. As seen in FIG. 2, the hole injection layers **321_R** and **321_G** are not disposed in association with the blue pixel B, but are disposed in association with the red pixel R and the green pixel G. The hole injection layers **321_R** and **321_G** are disposed in association with the emission layers **323_R** and **323_G**. In this manner, the emission layers **323_R** and **323_G** overlap the hole injection layers **321_R** and **321_G**. As with the opposite electrode **326**, the hole transport layer **322**, the electron transport layer **324**, and the electron injection layer **325** are common layers formed in association with each pixel region. As such, the opposite electrode **326**, the hole transport layer **322**, the electron transport layer **324**, and the electron injection layer **325** may be formed via an open mask without any specific pattern or, in other words, may be formed to cover an entire surface of an underlying layer on the substrate **300**. The emission layer **323_R** of the red pixel R and the emission layer **323_B** of the blue pixel B have the same pattern, but are spaced apart from one another by a determined pitch corresponding to an interval between the red pixel R and the blue pixel B.

According to one or more exemplary embodiments, a method is provided to form the emission layers **323_R**, **323_G**, and **323_B** and the hole injection layers **321_R** and **321_G** in accurate positions, with accurate patterning, and with accurate overlapping conditions. In this manner, a mask utilized to form the emission layers **323_R** and **323_B** may be different than the mask utilized to form the emission layer **323_G**. Furthermore, one or more masks utilized to form the hole injection layers **321_R** and **321_G** may not be utilized to form a portion of the blue pixel B, as the blue pixel B does not include a hole injection layer. To this end, the emission layers **323_R**, **323_G**, and **323_B** and the hole injection layers **321_R** and **321_G** should be patterned at an accurate positions in each pixel. When, however, a mask is not at an accurate position, the position of a thin film deposited on the substrate **300** may be offset from an expected position and this may reduce the display quality of the pixel. To help prevent (or at least reduce) the potential for such an offset of a mask, the method may include a process of accurately measuring a pixel position to accurately deposit a thin film in association therewith.

FIG. 3 is a plan view of marks and thin film patterns formed on a substrate that may be utilized to accurately position a mask in association with a pixel for thin film deposition, according to one or more exemplary embodiments.

To measure for deposition position accuracy, marks M (as shown in FIG. 3) may be formed on a first side of a substrate

300, and patterns G1', R1', G2', and R2' (as shown in FIGS. 4A and 6A) may be utilized to form thin film layers G1, R1, B, G2, and R2 for inspection. Thin film layers G1, R1, B, G2, and R2 may be formed on reference central points C1 that are aligned in a first direction D1 with virtual extension lines extending from the marks M. In this manner, when the emission layers **323_R**, **323_G**, and **323_B** and the hole injection layers **321_R** and **321_G** are formed, the thin film layers G1, R1, B, G2, and R2 for inspection may also be deposited and formed on the substrate **300**. Accordingly, when the mask is accurately positioned, central points C2 of the thin film layers G1, R1, B, G2, and R2 for inspection will coincide with the reference central points C1 that are associated with the marks M. However, when the mask is not accurately positioned, and, thereby, offset in, for instance, a second direction D2, the central points C2 of the thin film layers G1, R1, B, G2, and R2 for inspection will not coincide with the reference central points C1 associated with the marks M. Instead, a gap interval in the second direction D2 will exist between the reference central points C1 and the central points C2 as exemplified in FIG. 3. The gap interval may be measured as an offset misalignment of the mask. The measured gap interval may be utilized to reposition the mask so that the offset may be removed for a next deposition process.

Although not illustrated, it is also contemplated that one or more marks may be formed on a second side of the substrate **300** that is perpendicular (or substantially perpendicular) to the first side of the substrate **300** (or formed in another portion of the substrate) to measure and adjust for positioning accuracy associated with the first direction D1. That is, a gap interval may also be measured in the first direction D1 based on an offset of the reference central point C1 and the central point C2 in the first direction D1. In this manner, the mask may be accurately positioned in both the first direction D1 and the second direction D2.

An exemplary method to form the emission layers **323_R**, **323_G**, and **323_B**, the hole injection layers **321_R** and **321_G**, and respective thin film layers G1, R1, B, G2, and R2 for inspection will be described in association with FIGS. 4A, 4B, 4C, 4D, 5A, 5B, 5C, 5D, 6A, 6B, 6C, and 6D.

FIGS. 4A, 4B, 4C, and 4D illustrate a method of patterning an emission layer of a first pixel and an emission layer of a second pixel using a first mask, according to one or more exemplary embodiments. For instance, the emission layer of the first pixel may be emission layer **323_R** of a red pixel R and the emission layer of the second pixel may be emission layer **323_B** of a blue pixel B. To this end, the first mask will be referred to as mask **210a**.

As illustrated in FIGS. 4A and 4B, the first mask **210a** may include first pixel patterns in an active area **211** and a dummy area **212** disposed outside the active area **211**, a pattern R1' for inspecting a first pixel position, and a pattern R2' for inspecting a second pixel position. The active area **211** is a pattern region for actually forming the emission layers **323_R**, **323_G**, and **323_B** and the hole injection layers **321_R** and **321_G**. The dummy area **212** is a marginal pattern region disposed outside the active area **211**, e.g., surrounding the active area **211**. The pattern R1' for inspecting the first pixel position is a pattern for forming a thin film layer R1 for a first inspection, as seen in FIG. 4C. The pattern R1' is formed when the emission layer **323_R** of a pixel R is formed. The pattern R2' for inspecting the second pixel position is a pattern for forming a thin film layer R2 for a third inspection, as seen in FIGS. 4C and 4D.

According to one or more exemplary embodiments, the pattern R2' for inspecting the second pixel position may not

be used during a process of forming the emission layer 323_R of the red pixel R and the emission layer 323_B of the blue pixel B. For example, the pattern R2' for inspecting the second pixel position may be an opening formed in the first mask 210a, and, as such, the thin film layer R2 for a third inspection is formed on the substrate 300 during the deposition process shown in FIGS. 4C and 4D. It is noted, however, that the thin film layer R2 for the third inspection is formed at a location different from the marks M, such that the thin film layer R2 for the third inspection is not used for the first inspection. Further, the thin film layer R2 will not interfere with the first inspection.

When the emission layer 323_R of the red pixel R is formed using the first mask 210a, the first mask 210a is aligned on the substrate 300 and deposition is performed as seen in FIG. 4A. In this manner, thin film layers 301, 302, R1, and R2 of a red (R) color (hereinafter referred to as a first color) are formed on the substrate 300, as seen in FIG. 4C. An active area 301 and a dummy area 302 of the thin film layers of the first color are formed on areas of the substrate 300 that correspond to the first pixel patterns in the active area 211 and the dummy area 212 of the first mask 210a, respectively. Thin film layers R1 and R2 for the first inspection and the third inspection are formed on areas corresponding to the patterns R1' and R2' for inspecting the first and second pixel positions of the first mask 210a, respectively. The thin film layer corresponding to the active area 301 will become the emission layer 323_R of the red pixel R.

To inspect whether the thin film layers 301, 302, R1, and R2 of the first color including the emission layer 323_R of the red pixel R are accurately formed, the positions of the thin film layer R1 for the first inspection and the central points C1 and C2 associated with the marks M are compared as described with reference to FIG. 3. When it is determined that an offset of the first mask 210a exists as a result of the comparison, the position of the first mask 210a is adjusted so that the offset may be eliminated (or at least reduced) when the next thin film layers 301, 302, R1, and R2 of the first color are formed.

According to one or more exemplary embodiments, first mask 210a is used to form the emission layer 323_R of the pixel R may be used even when the emission layer 323_B of the pixel B is formed. It is contemplated, however, that the first mask 210a may be used to form the emission layer 323_R of the red pixel R, but not used to form the emission layer 323_B of the blue pixel B. In this manner, another first mask 210a may be used.

As illustrated in FIG. 4A, the first mask 210a is disposed over the substrate 300, and, as seen in FIG. 4B, the first mask 210a is shifted by a determined pitch and aligned with the substrate 300 based, at least in part, on the formation of the emission layer 323_R of the red pixel R. That is, because the emission layer 323_R of the red pixel R and the emission layer 323_B of the blue pixel B have the same pattern that would otherwise overlap each other if the emission layer 323_R of the red pixel R were moved by a determined pitch over the emission layer 323_B of the blue pixel B, the first mask 210a may be moved by the determined pitch to form the emission layer 323_B of the blue pixel B. As such, when the first mask 210a, which is used to form the emission layer 323_R of the red pixel R, is shifted by the determined pitch, the pattern of the emission layer 323_R of the red pixel R may be formed as the emission layer 323_B of the blue pixel B. The shift distance may be adjusted by 1 pitch, 3 pitches, etc., by taking into account the determined pitch. To this end,

it is noted that the shifting of first mask 210a should be performed in a shifting direction within a width "d" of the dummy area.

Accordingly, as seen in FIG. 4B, when the first mask 210a is shifted by the determined pitch with respect to the substrate 300, the first pixel patterns of the active area and the dummy area 211 and 212 and the patterns R1' and R2' for inspecting the first and second pixel positions will also be shifted and aligned. As such, when a deposition process is performed, thin film layers 301, 302, B, and R2 of a blue (B) color (referred to hereinafter as a second color) are formed and are shifted from the thin film layers of the first color by the determined pitch, as seen by comparing FIGS. 4C and 4D. An active area 301 and a dummy area 302 of the thin film layers of the second color are formed on areas of the substrate 300 that correspond to the first pixel patterns of the active area 211 and the dummy area 212 of the first mask 210a, respectively. To this end, the thin film layer B for a second inspection and the thin film layer R2 for a third inspection are formed on areas that correspond to the patterns R1' and R2' for inspecting the first and second pixel positions of the first mask 210a, respectively. In this manner, the thin film layer corresponding to the active area 301 will become the emission layer 323_B of the blue pixel B.

To inspect whether the thin film layers 301, 302, B, and R2 of the second color and the emission layer 323_B of the blue pixel B are accurately formed, the positions of the thin film layer B of the second inspection and the central points C1 and C2 associated with the marks M are compared with each other as described with reference to FIG. 3. When it is determined that an offset of the first mask 210a exists as a result of the comparison, the position of the first mask 210a may be adjusted so that the offset may be canceled (or at least reduced) when the next thin film layers 301, 302, B, and R2 of the second color are formed.

The first mask 210a may also be used to form the hole injection layer 321_R, which is an auxiliary layer of the red pixel R.

FIGS. 5A, 5B, 5C, and 5D illustrate a method of patterning an emission layer of a first pixel and an auxiliary layer of the first pixel using the first mask of FIGS. 4A, 4B, 4C, and 4D, according to one or more exemplary embodiments. As previously mentioned, the first pixel may be a red pixel R, such that the emission layer of the first pixel may be emission layer 323_R of the red pixel R and the auxiliary layer of the first pixel may be hole injection layer 321_R of the red pixel R.

Referring to FIGS. 5A, 5B, 5C, and 5D, the thin film layers 301, 302, R1, and R2 of the first color are formed by disposing the first mask 210a over substrate 300 and performing deposition as in FIGS. 5A and 5C. After the thin film layers 301, 302, R1, and R2 of the first color are formed, a process of correcting an offset by comparing the positions of the thin film layer R1 for the first inspection and the central points C1 and C2 associated with the marks M is performed. The correction process is the same as described in FIGS. 4A and 4C, and, as such, duplicative descriptions are omitted to avoid obscuring exemplary embodiments.

The first mask 210a is used to form the hole injection layer 321_R, which is an auxiliary layer (referred to hereinafter as a first auxiliary layer) of the red pixel R. It is noted, however, that a portion of the first mask 210a used to form the emission layer 323_R of the red pixel R is different from a section portion of the first mask 210a used to form the hole injection layer 321_R of the red pixel. It is also contemplated that a different first mask may be utilized to form the hole injection layer 321_R of the red pixel R.

As illustrated in FIG. 5A, the first mask **210a** is disposed over substrate **300**. The first mask **210a** is rotated by 180 degrees from a position associated with forming the emission layer **323_R** of the red pixel R. To this end, the rotated configuration of first mask **210a** is aligned with respect to the substrate **300**. That is, because the emission layer **323_R** of the red pixel R and the hole injection layer **321_R** of the red pixel R are thin film layers of the same pattern formed in the same position, the first mask **210a** of the same kind as the one used to form the emission layer **323_R** of the red pixel R may be used. Also because a pattern of the same shape as the one used to form the emission layer **323_R** of the red pixel R is repeatedly formed, the pattern may be maintained without change even when the first mask **210a** is rotated by 180 degrees. It is noted, however, that some offset may occur, but this offset may be determined and adjusted for via the next offset correction process.

When the first mask **210a** is rotated by 180 degrees, the above-described pattern **R2'** for inspecting the second pixel position corresponds to a position that may be compared with the mark **M** on the substrate **300**. In this manner, when deposition is performed, the thin film layers **301**, **302**, **R1**, and **R2** associated with the first auxiliary layer are formed as in FIG. 5D. The thin film layer corresponding to the active area **301** will become the hole injection layer **321_R** of the red pixel R.

To inspect whether the thin film layers **301**, **302**, **R1**, and **R2** of the first auxiliary layer including the hole injection layer **321_R** of the red pixel R are accurately formed, the positions of the thin film layer **R2** of the third inspection and the central points **C1** and **C2** of the marks **M** may be compared with each other as described with reference to FIG. 3. When it is determined that an offset of the first mask **210a** exists as a result of the comparison, the position of the first mask **210a** may be adjusted so that the offset may be canceled (or at least reduced) when the next thin film layers **301**, **302**, **R1**, and **R2** of the first auxiliary layer are formed.

Although the formation of the emission layer **323_R** of the red pixel R has been described first for descriptive convenience, the hole injection layer **321_R** of the red pixel R is formed before the emission layer **323_R** of the red pixel R based on the stacking sequence as described in association with FIG. 2. In this manner, because the emission layers **323_R** of the red pixels R, the emission layers **323_B** of the blue pixels B, and the hole injection layers **321_R** of the red pixels R may be formed using the same first mask **210a**, the potential for error decreases, as well as reducing in manufacturing time and cost. Moreover, it is easier to manage the overall manufacturing process.

FIGS. 6A, 6B, 6C, and 6D illustrate a method of patterning an emission layer of a third pixel and an auxiliary layer of the third pixel using a second mask, according to one or more exemplary embodiments. For instance, the emission layer of the third pixel may be emission layer **323_G** of a green pixel G and the auxiliary layer of the third pixel may be hole injection layer **321_G** of the green pixel G. The second mask will be referred to as mask **210b**.

Given that the emission layer **323_G** and the hole injection layer **321_G** of the green pixel G have a pattern different from that of the red pixel R and the blue pixel B, the emission layer **323_G** and the hole injection layer **321_G** are not formed by shifting or rotating the first mask **210a**, but, instead, are formed using a second mask **210b** having second pixel patterns in the active area **213** and the dummy area **214**, and patterns **G1'**, **G2'** for inspecting third and fourth pixel positions for the green pixel G.

According to one or more exemplary embodiments, the second mask **210b** is aligned on the substrate **300** as in FIG. 6A and deposition is performed. Thin film layers **303**, **304**, **G1**, and **G2** of a green (G) color (referred to hereinafter as third color) are formed on the substrate **300** as in FIG. 6C. An active area **303** and a dummy area **304** of the thin film layer of the third color are formed on areas of the substrate **300** that correspond to the second pixel patterns in the active area **213** and the dummy area **214** of the second mask **210b**, respectively. The thin film layers **G1** and **G2** for fourth and fifth inspection are formed on areas that correspond to the patterns **G1'** and **G2'** for inspecting the third and fourth pixel positions of the second mask **210b**, respectively. The thin film layer corresponding to the active area **303** will become the emission layer **323_G** of the green pixel G.

To inspect whether the thin film layers **303**, **304**, **G1**, and **G2** of the third color including the emission layer **323_G** of the green pixel G are accurately formed, the positions of the thin film layer **G1** of the fourth inspection and the central points **C1** and **C2** associated with the marks **M** are compared with each other as described with reference to FIG. 3. When it is determined that an offset of the second mask **210b** exists as a result of the comparison, the position of the second mask **210b** may be adjusted so that the offset may be canceled (or at least reduced) when the next thin film layers **303**, **304**, **G1**, and **G2** of the third color are formed.

The second mask **210b** may also be utilized to form the hole injection layer **321_G**, which is an auxiliary layer (referred to hereinafter as a second auxiliary layer) of the green pixel G. It is contemplated, however, that the second mask **210b** used when the emission layer **323_G** of the green pixel G is formed may not be used when the hole injection layer **321_G** of the green pixel G is formed, but, instead, another second mask **210b** may be used.

As illustrated in FIG. 6A, the second mask **210b** is disposed over substrate **300**. The second mask **210b** is rotated by 180 degrees from a position of forming the emission layer **323_G** of the green pixel G and aligned with respect to the substrate **300**. That is, because the emission layer **323_G** of the green pixel G and the hole injection layer **321_G** of the green pixel G are thin film layers having the same pattern formed in the same position, the second mask **210b** may be used. Further, because a pattern of the same shape is repeatedly formed, the pattern may be maintained without change even when the second mask **210b** is rotated by 180 degrees. It is noted, however, that some offset may occur, but this offset may be adjusted via the next offset correction process.

Moreover, when the second mask **210b** is rotated by 180 degrees, the above-described pattern **G2'** for inspecting the fifth pixel position corresponds to a position that may be compared with the mark **M** on the substrate **300**. In this manner, when deposition is performed, the thin film layers **303**, **304**, **G1**, and **G2** of the second auxiliary layer may be formed as in FIG. 6D. The thin film layer corresponding to the active area **303** will become the hole injection layer **321_G** of the green pixel G.

To inspect whether the thin film layers **303**, **304**, **G1**, and **G2** of the second auxiliary layer including the hole injection layer **321_G** of the green pixel G are accurately formed, the positions of the thin film layer **G2** of the fifth inspection and the central points **C1** and **C2** associated with the marks **M** are compared with each other as described with reference to FIG. 3. When it is determined that an offset of the second mask **210b** exists as a result of the comparison, the position of the second mask **210b** may be adjusted so that the offset

may be canceled (or at least reduced) when the next thin film layers **303**, **304**, **G1**, and **G2** of the second auxiliary layer are formed.

Although the formation of the emission layer **323_G** of the green pixel **G** has been described first for descriptive convenience, the hole injection layer **321_G** of the green pixel **G** is formed before the emission layer **323_G** of the green pixel **G** based on a stacking sequence as described in association with FIG. **2**. In this manner, because the emission layer **323_G** of the green pixel **G** and the hole injection layer **321_G** of the green pixel **G** may be formed using the same second mask **210b**, the potential for error decreases, as well as reducing in manufacturing time and cost. Moreover, it is easier to manage the overall manufacturing process.

Accordingly, all of the emission layers **323_R**, **323_G**, and **323_B** of the red, green, and blue pixels **R**, **G**, **B**, and the hole injection layers **321_R** and **321_G** of the red and green pixels **R** and **G** may be formed using two masks, e.g., the first mask **210a** and the second mask **210b**, in two different orientations. In this manner, exemplary embodiments enable the potential for error to decrease, as well as enable reductions in manufacturing time and cost. Moreover, it is easier to manage the overall manufacturing process and productivity may increase.

Although certain exemplary embodiments and implementations have been described herein, other embodiments and modifications will be apparent from this description. Accordingly, the inventive concept is not limited to such embodiments, but rather to the broader scope of the presented claims and various obvious modifications and equivalent arrangements.

What is claimed is:

1. An organic light-emitting display device comprising:
 - a substrate;
 - a first color emission layer on the substrate;
 - a second color emission layer on the substrate, the second color emission layer being spaced apart from the first color emission layer by a determined pitch,
 - a third color emission layer on the substrate, the third color emission layer being spaced apart from the first color emission layer and the second color emission layer,
 - wherein, in a plan view, patterns of the first color emission layer and the second color emission layer are equivalent; and
 - wherein, in a cross-sectional view, patterns of the first color emission layer and the second color emission layer are different from one another.
2. The organic light-emitting display device of claim **1**, wherein:
 - the substrate comprises:
 - an active area in a central portion; and
 - a dummy area outside the active area;
 - the first emission layer is arranged in the active area; and
 - the second emission layer is arranged in the active area and the dummy area.
3. The organic light-emitting display device of claim **1**, wherein the determined pitch is less than or equal to a width of the dummy area in a direction of the determined pitch.
4. The organic light-emitting display device of claim **3**, wherein, in the direction of the determined pitch, an end portion of the second emission layer is arranged in the dummy area.
5. The organic light-emitting display device of claim **1**, wherein the first color emission layer comprises a red emission layer, the second color emission layer comprises a

blue emission layer, and the third color emission layer comprises a green emission layer.

6. The organic light-emitting display device of claim **1**, further comprising:

- a first pixel electrode on the substrate; and
 - a second pixel electrode on the substrate,
- wherein, in a direction normal to the substrate, a distance between the first pixel electrode and the first color emission layer is greater than a distance between the second pixel electrode and the second color emission layer.

7. The organic light-emitting display device of claim **1**, further comprising:

- a first alignment mark on the substrate;
- a second alignment mark on the substrate; and
- a third alignment mark on the substrate,

wherein:

- a first imaginary line extends, in a plan view, through the first color emission layer, the second color emission layer, and the first alignment mark;
- a second imaginary line crossing the first imaginary line extends, in the plan view, through the first color emission layer; and
- a third imaginary line crossing the first imaginary line extends, in the plan view, through the second color emission layer.

8. The organic light-emitting display device of claim **7**, further comprising:

- a fourth alignment mark on the substrate,

wherein:

- a fourth imaginary line extends, in the plan view, through the second alignment mark, the third alignment mark, and the fourth alignment mark; and
- a fifth imaginary line crossing the fourth imaginary line extends, in the plan view, through the first alignment mark and the fourth alignment mark.

9. The organic light-emitting display device of claim **8**, wherein:

- shapes of the first alignment mark, the second alignment mark, and the third alignment mark are equivalent; and
- shapes of the first alignment mark and the fourth alignment mark are different.

10. An electroluminescent display device comprising:

- a substrate comprising:
 - an active area in a central portion; and
 - a dummy area outside the active area;
- a first color emission layer on the substrate in the active area;
- a second color emission layer on the substrate in the active area and the dummy area, the second color emission layer being spaced apart from the first color emission layer,
- wherein patterns of the first color emission layer and the second color emission layer are equivalent.

11. The electroluminescent display device of claim **10**, wherein the patterns of the first color emission layer and the second color emission layer are equivalent in a plan view.

12. The electroluminescent display device of claim **10**, wherein a pitch between the first color emission layer and the second color emission layer is less than or equal to a width of the dummy area in a direction of the pitch.

13. The electroluminescent display device of claim **12**, wherein, in the direction of the pitch, an end portion of the second emission layer is arranged in the dummy area.

14. The electroluminescent display device of claim **10**, further comprising:

13

a third color emission layer on the substrate, the third color emission layer being spaced apart from the first color emission layer and the second color emission layer.

15. The electroluminescent display device of claim **14**,
5 wherein the first color emission layer comprises a red emission layer, the second color emission layer comprises a blue emission layer, and the third color emission layer comprises a green emission layer.

16. The electroluminescent display device of claim **10**,
10 further comprising:

a first alignment mark on the substrate;
a second alignment mark on the substrate; and
a third alignment mark on the substrate,
wherein:

15 a first imaginary line extends, in a view normal to the substrate, through the first color emission layer, the second color emission layer, and the first alignment mark;

14

a second imaginary line crossing the first imaginary line extends, in the view, through the first color emission layer; and

a third imaginary line crossing the first imaginary line extends, in the view, through the second color emission layer.

17. The electroluminescent display device of claim **16**, further comprising:

a fourth alignment mark on the substrate,
wherein:

a fourth imaginary line extends, in the view, through the second alignment mark, the third alignment mark, and the fourth alignment mark; and

a fifth imaginary line crossing the fourth imaginary line extends, in the view, through the first alignment mark and the fourth alignment mark.

* * * * *

专利名称(译)	掩模，检查和调整掩模位置的方法，以及利用掩模对有机发光显示装置的像素进行图案化的方法		
公开(公告)号	US10224482	公开(公告)日	2019-03-05
申请号	US15/630877	申请日	2017-06-22
[标]申请(专利权)人(译)	三星显示有限公司		
申请(专利权)人(译)	三星DISPLAY CO. , LTD.		
当前申请(专利权)人(译)	三星DISPLAY CO. , LTD.		
[标]发明人	LEE SANGSHIN HA DONGJIN KANG MINGOO KWON OHSEOB YI SANGMIN		
发明人	LEE, SANGSHIN HA, DONGJIN KANG, MINGOO KWON, OHSEOB YI, SANGMIN		
IPC分类号	H01L51/00 H01L51/56 H01L27/32 H01L51/50		
CPC分类号	H01L51/0011 H01L27/3211 H01L51/56 H01L27/3223 H01L51/5088 H01L51/5012 H01L51/0031		
优先权	1020150069351 2015-05-19 KR		
其他公开文献	US20170288143A1		
外部链接	Espacenet		

摘要(译)

一种用于有机发光显示装置的像素图案化和像素位置检查的方法，包括：使用第一掩模在基板上形成对应于第一像素图案的第一颜色的薄膜层和用于第一像素定位图案的第一像素定位图案。检查第一个像素的位置；从与形成第一颜色的薄膜层相关的位置移动第一掩模，确定间距；将移位的第一掩模相对于基板对准；使用所述移位的第一掩模在所述基板上形成与所述第一像素图案对应的第二颜色的薄膜层和用于检查第二像素的位置的另一第一像素定位图案。

