



US009985215B2

(12) **United States Patent**  
**Adachi et al.**

(10) **Patent No.:** **US 9,985,215 B2**  
(45) **Date of Patent:** **May 29, 2018**

- (54) **LIGHT-EMITTING MATERIAL, AND ORGANIC LIGHT-EMITTING ELEMENT**  
(71) Applicant: **KYUSHU UNIVERSITY NATIONAL UNIVERSITY CORPORATION**, Fukuoka-shi, Fukuoka (JP)  
(72) Inventors: **Chihaya Adachi**, Fukuoka (JP); **Tetsuya Nakagawa**, Fukuoka (JP); **Jie Li**, Fukuoka (JP)  
(73) Assignee: **KYULUX, INC.**, Fukuoka (JP)  
(\*) Notice: Subject to any disclaimer, the term of this patent is extended or adjusted under 35 U.S.C. 154(b) by 887 days.

- (21) Appl. No.: **14/383,971**  
(22) PCT Filed: **Mar. 7, 2013**  
(86) PCT No.: **PCT/JP2013/056245**  
§ 371 (c)(1),  
(2) Date: **Sep. 9, 2014**  
(87) PCT Pub. No.: **WO2013/133359**  
PCT Pub. Date: **Sep. 12, 2013**

- (65) **Prior Publication Data**  
US 2015/0048338 A1 Feb. 19, 2015

- (30) **Foreign Application Priority Data**  
Mar. 9, 2012 (JP) ..... 2012-053437

- (51) **Int. Cl.**  
**H01L 51/50** (2006.01)  
**H01L 51/00** (2006.01)  
(Continued)  
(52) **U.S. Cl.**  
CPC ..... **H01L 51/0061** (2013.01); **C07D 487/16** (2013.01); **C09K 11/06** (2013.01);  
(Continued)

- (58) **Field of Classification Search**  
CPC combination set(s) only.  
See application file for complete search history.

(56) **References Cited**

U.S. PATENT DOCUMENTS

2011/0297925 A1 12/2011 Breuning  
2012/0091884 A1 7/2012 MacDonald et al.

FOREIGN PATENT DOCUMENTS

CN 101223174 A 7/2008  
CN 102317408 A 1/2012

(Continued)

OTHER PUBLICATIONS

Japanese Office Action dated Aug. 10, 2016 in corresponding Japanese Patent appl. No. 2014-503534 with English translation of excerpts from Japanese original.

(Continued)


*Primary Examiner* — Jennifer A Chriss

*Assistant Examiner* — Sean M DeGuire


(74) *Attorney, Agent, or Firm* — Browdy and Neimark, PLLC

(57) **ABSTRACT**

The compound represented by the following general formula is useful as a light-emitting material for an organic light-emitting device.  $Z^1$ ,  $Z^2$  and  $Z^3$  in the following general formula each independently represent a substituent.



**7 Claims, 5 Drawing Sheets**



- |      |  |                        |                |   |                             |
|------|--|------------------------|----------------|---|-----------------------------|
| (51) | <b>Int. Cl.</b><br><b>C07D 487/16</b><br><b>C09K 11/06</b> | (2006.01)<br>(2006.01) | WO<br>WO<br>WO | 2010000614 A1<br>2010094378 A1<br>2010132953 A1 | 1/2010<br>8/2010<br>11/2010 |
|------|--|------------------------|----------------|---|-----------------------------|

- (52) **U.S. Cl.**  
CPC ..... *C09K 2211/1007* (2013.01); *C09K 2211/1014* (2013.01); *C09K 2211/1074* (2013.01); *H01L 51/0067* (2013.01); *H01L 51/0072* (2013.01); *H01L 51/5012* (2013.01)

## OTHER PUBLICATIONS

(56) **References Cited**

## FOREIGN PATENT DOCUMENTS

JP	2004-182737 A	7/2004
JP	2000-506916 A	6/2006
JP	2006267981 A	10/2006
WO	97/33323 A	9/1997
WO	2007006807 A1	1/2007
WO	2008083974 A1	7/2008
WO	2008083975 A1	7/2008

Chinese Office Action dated Apr. 10, 2015 in corresponding Chinese Patent appl. No. 201380013353.9 with English translation.

Kroke, E. et al "Alkalicymelurates, M<sub>3</sub>[C<sub>6</sub>N<sub>7</sub>O<sub>3</sub>]-xH<sub>2</sub>O, M = Li, Na, K, Rb, Cs:UV-luminescent and thermally very stable ionic tri-s-triazine derivatives†" Dalton Trans. 3900-3908 (Aug. 2004).

Traber, B. et al "Donor-Substituted Heptaazaphenylene as a Non-linear Optically Active Molecule with Multiple Charge-Transfer Transitions[‡]" Eur. J. Org. Chem. 4387-4390 (2004).

Zheng, W. et al "Theroretical Study of 1,3,4,6,7,9,9b-Heptaazaphenylene and Its Ten Derivatives" J. Phys. Chem. A 108:97-706 (2004).

International search report, dated Jun. 13, 2014. Application No. 2013056245.

International preliminary report, dated Sep. 12, 2014. Application No. 2013056245.

Fig. 1




Fig. 2




Fig. 3




Fig. 4




Fig. 5




Fig. 6




Fig. 7




Fig. 8





Fig. 9



## 1

LIGHT-EMITTING MATERIAL, AND  
ORGANIC LIGHT-EMITTING ELEMENT

## TECHNICAL FIELD

The present invention relates to a light-emitting material having a heptaazaphenalene structure, and an organic light-emitting device, such as an organic electroluminescent device (organic EL device), using the light-emitting material.

## BACKGROUND ART

Compounds having a heptaazaphenalene structure and their use have been variously studied. For example, it has been found that a compound having a heptaazaphenalene structure is useful as an ultraviolet ray absorbent and may be applied to cosmetics and medical drugs (see, for example, PTLs 1 to 3).

The application of a compound having a heptaazaphenalene structure to an organic light-emitting device has not been studied for a long time. In recent years, however, it has been found that a compound having a heptaazaphenalene structure is useful as a hole injection material (see PTL 4).

## CITATION LIST

## Patent Literatures

PTL 1: WO 2008/83974

PTL 2: WO 2008/83975

PTL 3: WO 2007/6807

PTL 4: WO 2010/614

## SUMMARY OF INVENTION

## Technical Problem

As described above, a compound having a heptaazaphenalene structure has been variously studied, and a slight proposal for application thereof to an organic electroluminescent device has also been made. However, all the compounds having a heptaazaphenalene structure have not yet been entirely studied. In particular, there is no literature found that confirms specific usefulness of a compound having a heptaazaphenalene structure as a light-emitting material of an organic electroluminescent device. Furthermore, there is no literature found that discusses the relationship between the chemical structure of a compound having a heptaazaphenalene structure and the usefulness of the compound as a light-emitting material. Accordingly, it is currently difficult to estimate the usefulness as a light-emitting material based on the chemical structure. In consideration of the problems, the present inventors have studied the usefulness as a light-emitting material of a compound having a heptaazaphenalene structure, and have further studied for obtaining useful knowledge. The inventors have also earnestly studied for providing a general formula of a compound that is useful as a light-emitting material to generalize a useful light-emitting material.

## Solution to Problem


As a result of earnest investigations for achieving the aforementioned objects, the inventors have found that a

## 2

particular compound having a heptaazaphenalene structure is useful as a light-emitting material of an organic light-emitting device. In particular, the inventors have firstly found a compound that is useful as a delayed fluorescent material and a compound that has an extremely high light emission efficiency in compounds having a heptaazaphenalene structure, and have clarified that an excellent organic light-emitting device that has not been proposed may be provided inexpensively. Light emission efficiency is defined and hereafter used for mean photoluminescence quantum efficiency, electroluminescence quantum efficiency, or both as appropriate. Based on the knowledge, the inventors thus provide the invention described hereinbelow as a measure for solving the problems.

(1) A light-emitting material containing a compound represented by the following general formula (1):

General Formula (1)



wherein in the general formula (1), Z¹, Z² and Z³ each independently represent a substituent.


(2) The light-emitting material according to the item (1), wherein Z¹, Z² and Z³ in the general formula (1) are the same as each other.

(3) The light-emitting material according to the item (1) or (2), wherein Z¹, Z² and Z³ in the general formula (1) each independently represent a substituted amino group, a substituted or unsubstituted aryl group or a substituted or unsubstituted heteroaryl group.

(4) The light-emitting material according to the item (1) or (2), wherein Z¹, Z² and Z³ in the general formula (1) each independently represent a substituted or unsubstituted diarylamino group.

(5) The light-emitting material according to the item (4), wherein the compound has a structure represented by the following general formula (2):

General Formula (2)




wherein in the general formula (2), Ar¹, Ar², Ar³, Ar⁴, Ar⁵ and Ar⁶ each independently represent a substituted or unsubstituted aryl group.



3

(6) The light-emitting material according to the item (1) or (2), wherein  $Z^1$ ,  $Z^2$  and  $Z^3$  in the general formula (1) each independently represent an aryl group substituted by a substituted or unsubstituted diarylamino group.

(7) The light-emitting material according to the item (6), wherein the compound has a structure represented by the following general formula (3):



wherein in the general formula (3),  $Ar^{11}$ ,  $Ar^{12}$ ,  $Ar^{13}$ ,  $Ar^{14}$ ,  $Ar^{15}$  and  $Ar^{16}$  each independently represent a substituted or unsubstituted aryl group.

(8) A delayed fluorescence emitter having a structure represented by the general formula (1).

(9) An organic light-emitting device containing the light-emitting material according to any one of the items (1) to (8) as a light-emitting material.

(10) The organic light-emitting device according to the item (9), which is an organic electroluminescent device containing an anode, a cathode, and at least one organic layer containing a light-emitting layer between the anode and the cathode, and contains the light-emitting material in the light-emitting layer.

(11) The organic light-emitting device according to the item (9) or (10), which emits delayed fluorescent light.

#### Advantageous Effects of Invention

The compound represented by the general formula (1) is useful as a light-emitting material of an organic light-emitting device. The group of the compounds represented by the general formula (1) includes one that exhibits emission of delayed fluorescent light and one that has an extremely high light emission efficiency. The organic light-emitting device of the invention includes one that exhibits emission of delayed fluorescent light and one that has an extremely high light emission efficiency.

4

#### BRIEF DESCRIPTION OF THE DRAWINGS

FIG. 1 is a schematic cross sectional view showing an example of a layer structure of an organic electroluminescent device.

FIG. 2 is a photoluminescent light emission spectrum in Example 1.

FIG. 3 is a graph showing a photoluminescent transient decay in Example 1.

FIG. 4 is an electroluminescent light emission spectrum in Example 1.

FIG. 5 is a photoluminescent light emission spectrum in Example 2.

FIG. 6 is a graph showing a photoluminescent transient decay in Example 2.

FIG. 7 is an electroluminescent light emission spectrum in Example 2.

FIG. 8 is a graph showing electric current density-voltage characteristics-luminance characteristics of an organic electroluminescent device in Example 2.


FIG. 9 is a graph showing external quantum efficiency-electric current density characteristics of the organic electroluminescent device in Example 2.

#### DESCRIPTION OF EMBODIMENTS

The contents of the invention will be described in detail below. The constitutional elements may be described below with reference to representative embodiments and specific examples of the invention, but the invention is not limited to the embodiments and the examples. In the present specification, a numerical range expressed by "from X to Y" means a range including the numerals X and Y as the lower limit and the upper limit, respectively.

Compound Represented by General Formula (1)

The compound of the invention has a structure represented by the following general formula (1).



In the general formula (1),  $Z^1$ ,  $Z^2$  and  $Z^3$  each independently represent a substituent. The substituent referred to herein means atoms or atomic groups other than a hydrogen atom.

Preferred examples of the substituent represented by  $Z^1$ ,  $Z^2$  and  $Z^3$  include a substituted amino group, a substituted or unsubstituted aryl group and a substituted or unsubstituted heteroaryl group.  $Z^1$ ,  $Z^2$  and  $Z^3$  may be the same as or different from each other. What is preferred is the case where  $Z^1$ ,  $Z^2$  and  $Z^3$  are the same as each other.

The substituted amino group that may be represented by  $Z^1$ ,  $Z^2$  and  $Z^3$  is a group having a structure represented by  $—N(R^1)(R^2)$ , wherein  $R^1$  and  $R^2$  each independently represent a substituent.  $R^1$  and  $R^2$  each are preferably a substituted or unsubstituted alkyl group, a substituted or unsubstituted aryl group or a substituted or unsubstituted heteroaryl group, more preferably a substituted or unsubstituted aryl group or a substituted or unsubstituted heteroaryl group, and further preferably a substituted or unsubstituted aryl group.  $R^1$  and  $R^2$  may be the same as or different from each other, and are preferably the same as each other.  $R^1$  and  $R^2$  may be bonded to each other to form a cyclic structure. Specific examples of the group forming the cyclic structure include a carbazolyl group. Particularly preferred examples of the substituted amino group that may be represented by  $Z^1$ ,  $Z^2$  and  $Z^3$  include a substituted or unsubstituted diarylamino group, and specific examples thereof include a diphenylamino group and a di(4-fluorophenyl) amino group.

The aryl group that may be represented by  $Z^1$ ,  $Z^2$  and  $Z^3$  may be formed of only one aromatic ring or may have a structure containing two or more aromatic rings that are fused to each other. The aryl group preferably has from 6 to 22 carbon atoms, more preferably from 6 to 18 carbon atoms, further preferably from 6 to 14 carbon atoms, and still further preferably from 6 to 10 carbon atoms (i.e., a phenyl group, a 1-naphthyl group or a 2-naphthyl group). The aryl group may be substituted, and the substituent in this case is preferably a halogen atom, a substituted amino group, a substituted or unsubstituted alkyl group, a substituted or unsubstituted aryl group or a substituted or unsubstituted heteroaryl group, and more preferably a halogen atom or a substituted amino group. In the case where the aryl group that may be represented by  $Z^1$ ,  $Z^2$  and  $Z^3$  is substituted, the number of the substituent is preferably from 1 to 5, more preferably from 1 to 4, and further preferably from 1 to 3. In the case where the aryl group has plural substituents, the substituents may be the same as or different from each other. Particularly preferred examples of the substituted or unsubstituted aryl group that may be represented by  $Z^1$ ,  $Z^2$  and  $Z^3$  include an aryl group that is substituted by a diarylamino group. Specific examples thereof include a 4-(diphenylamino)phenyl group, a 4-(di(4-tert-butylphenyl)amino)phenyl group, a 4-(di(4-methylphenyl)amino)phenyl group, a 4-(di(4-ethylphenyl)amino)phenyl group, a 4-(di(4-propylphenyl)amino)phenyl group, a 4-(di(4-isopropylphenyl)amino)phenyl group, a 4-(di(3,5-dimethylphenyl)amino)phenyl group, a 4-(di(3,5-diethylphenyl)amino)phenyl group, a 4-(di(2,4,6-trimethylphenyl)amino)phenyl group, a 4-(di(1-naphthyl)amino)phenyl group and a 4-(di(2-naphthyl)amino)phenyl group.

The heteroaryl group that may be represented by  $Z^1$ ,  $Z^2$  and  $Z^3$  may be formed of only one ring or may have a structure containing two or more rings that are fused to each other. The heteroaryl group preferably has from 3 to 21 carbon atoms, more preferably from 3 to 17 carbon atoms, further preferably from 3 to 13 carbon atoms, and still further preferably from 3 to 9 carbon atoms. The heteroaryl group may be substituted, and the substituent in this case is preferably a halogen atom, a substituted amino group, a substituted or unsubstituted alkyl group, a substituted or


unsubstituted aryl group or a substituted or unsubstituted heteroaryl group, and more preferably a halogen atom or a substituted amino group. In the case where the heteroaryl group that may be represented by  $Z^1$ ,  $Z^2$  and  $Z^3$  is substituted, the number of the substituent is preferably from 1 to 4, more preferably from 1 to 3, and further preferably from 1 or 2. In the case where the heteroaryl group has plural substituents, the substituents may be the same as or different from each other.

The alkyl group referred to herein may be either linear, branched or cyclic. What is preferred is a linear or branched alkyl group. The alkyl group preferably has from 1 to 20 carbon atoms, more preferably from 1 to 12 carbon atoms, further preferably from 1 to 6 carbon atoms, and still further preferably from 1 to 3 carbon atoms (i.e., a methyl group, an ethyl group, a n-propyl group or an isopropyl group). Examples of the cyclic alkyl group include a cyclopentyl group, a cyclohexyl group and a cycloheptyl group.

The halogen atom referred to herein is preferably a fluorine atom, a chlorine atom, a bromine atom or an iodine atom, more preferably a fluorine atom, a chlorine atom or a bromine atom, and further preferably a fluorine atom or a chlorine atom.


Examples of the substituent on the alkyl group, the aryl group and the heteroaryl group include a substituted or unsubstituted alkyl group, a substituted or unsubstituted aryl group, a substituted or unsubstituted heteroaryl group, a substituted or unsubstituted alkoxy group, a substituted or unsubstituted aryloxy group and a substituted or unsubstituted heteroaryloxy group. The preferred ranges of the alkyl group, the aryl group and the heteroaryl group that may be used as the substituent are the same as described above. The alkoxy group that may be used as the substituent may be either linear, branched or cyclic. What is preferred is a linear or branched alkoxy group. The alkoxy group preferably has from 1 to 20 carbon atoms, more preferably from 1 to 12 carbon atoms, further preferably from 1 to 6 carbon atoms, still further preferably from 1 to 3 carbon atoms (i.e., a methoxy group, an ethoxy group, a n-propoxy group or an isopropoxy group). Examples of the cyclic alkoxy group include a cyclopentyloxy group, a cyclohexyloxy group and a cycloheptyloxy group. The aryloxy group that may be used as the substituent may be formed of only one aromatic ring or may have a structure containing two or more aromatic rings that are fused to each other. The aryloxy group preferably has from 6 to 22 carbon atoms, more preferably from 6 to 18 carbon atoms, further preferably from 6 to 14 carbon atoms, and still further preferably from 6 to 10 carbon atoms (i.e., a phenyloxy group, a 1-naphthyloxy group or a 2-naphthyloxy group). The heteroaryloxy group that may be used as the substituent may be formed of only one ring or may have a structure containing two or more rings that are fused to each other. The heteroaryloxy group preferably has from 3 to 21 carbon atoms, more preferably from 3 to 17 carbon atoms, further preferably from 3 to 13 carbon atoms, and still further preferably from 3 to 9 carbon atoms.

The compound of the invention preferably has a structure represented by the following general formula (2).



In the general formula (2), Ar<sup>1</sup>, Ar<sup>2</sup>, Ar<sup>3</sup>, Ar<sup>4</sup>, Ar<sup>5</sup> and Ar<sup>6</sup> each independently represent a substituted or unsubstituted aryl group. Ar<sup>1</sup>, Ar<sup>2</sup>, Ar<sup>3</sup>, Ar<sup>4</sup>, Ar<sup>5</sup> and Ar<sup>6</sup> may be the same as or different from each other, and what is preferred is the case where all Ar<sup>1</sup>, Ar<sup>2</sup>, Ar<sup>3</sup>, Ar<sup>4</sup>, Ar<sup>5</sup> and Ar<sup>6</sup> are the same as each other. Ar<sup>1</sup> and Ar<sup>2</sup> may be bonded to form a cyclic structure with the N atom. Ar<sup>3</sup> and Ar<sup>4</sup> may be bonded to form a cyclic structure with the N atom. Ar<sup>5</sup> and Ar<sup>6</sup> may be bonded to form a cyclic structure with the N atom. For descriptions and specific examples for the substituted or unsubstituted aryl group that may be represented by Ar<sup>1</sup>, Ar<sup>2</sup>, Ar<sup>3</sup>, Ar<sup>4</sup>, Ar<sup>5</sup> and Ar<sup>6</sup>, reference may be made to the descriptions and the specific examples of the substituted or unsubstituted aryl group in the description for the general formula (1).

Specific examples of the compound represented by the general formula (2) include a compound represented by the following structural formula.



Specific examples of the compound represented by the general formula (2) include compounds described in the following table. In the table, all Ar<sup>1</sup>, Ar<sup>2</sup>, Ar<sup>3</sup>, Ar<sup>4</sup>, Ar<sup>5</sup> and Ar<sup>6</sup> are the same as each other, and are collectively referred to as Ar.

TABLE 1


Compound No.	Ar
2	4-fluorophenyl
3	3-fluorophenyl
4	2-fluorophenyl
5	3,5-difluorophenyl
6	2,4,6-trifluorophenyl

TABLE 1-continued

Compound No.	Ar
7	4-methylphenyl
8	3-methylphenyl
9	2-methylphenyl
10	3,5-dimethylphenyl
11	2,4,6-trimethylphenyl
12	4-ethylphenyl
13	3-ethylphenyl
14	2-ethylphenyl
15	3,5-diethylphenyl
16	4-propylphenyl
17	3-propylphenyl
18	3,5-dipropylphenyl
19	4-tert-butylphenyl
20	3-tert-butylphenyl
21	3,5-di-tert-butylphenyl
22	1-naphthyl
23	2-naphthyl

The compound of the invention preferably has a structure represented by the following general formula (3). The group of the compounds represented by the general formula (3) is preferred particularly in the high light emission efficiency thereof.


General Formula (3)



In the general formula (3), Ar<sup>11</sup>, Ar<sup>12</sup>, Ar<sup>13</sup>, Ar<sup>14</sup>, Ar<sup>15</sup> and Ar<sup>16</sup> each independently represent a substituted or unsubstituted aryl group. Ar<sup>11</sup>, Ar<sup>12</sup>, Ar<sup>13</sup>, Ar<sup>14</sup>, Ar<sup>15</sup> and Ar<sup>16</sup> may be the same as or different from each other, and what is preferred is the case where all Ar<sup>11</sup>, Ar<sup>12</sup>, Ar<sup>13</sup>, Ar<sup>14</sup>, Ar<sup>15</sup> and Ar<sup>16</sup> are the same as each other. Ar<sup>11</sup> and Ar<sup>12</sup> may be bonded to form a cyclic structure with the N atom. Ar<sup>13</sup> and Ar<sup>14</sup> may be bonded to form a cyclic structure with the N atom. Ar<sup>15</sup> and Ar<sup>16</sup> may be bonded to form a cyclic structure with the N atom. For descriptions and specific examples for the substituted or unsubstituted aryl group that may be represented by Ar<sup>11</sup>, Ar<sup>12</sup>, Ar<sup>13</sup>, Ar<sup>14</sup>, Ar<sup>15</sup> and Ar<sup>16</sup>, reference may be made to the descriptions and the specific examples of the substituted or unsubstituted aryl group in the description for the general formula (1).

Specific examples of the compound represented by the general formula (3) include a compound represented by the following structural formula.

Compound 101



Specific examples of the compound represented by the general formula (3) include compounds described in the following table. In the table, all Ar<sup>11</sup>, Ar<sup>12</sup>, Ar<sup>13</sup>, Ar<sup>14</sup>, Ar<sup>15</sup> and Ar<sup>16</sup> are the same as each other, and are collectively referred to as Ar.

TABLE 2

Compound No.	Ar
102	4-fluorophenyl
103	3-fluorophenyl
104	2-fluorophenyl
105	3,5-difluorophenyl
106	2,4,6-trifluorophenyl
107	4-methylphenyl
108	3-methylphenyl
109	2-methylphenyl
110	3,5-dimethylphenyl
111	2,4,6-trimethylphenyl
112	4-ethylphenyl
113	3-ethylphenyl
114	2-ethylphenyl
115	3,5-diethylphenyl
116	4-propylphenyl
117	3-propylphenyl
118	3,5-dipropylphenyl
119	4-tert-butylphenyl
120	3-tert-butylphenyl
121	3,5-di-tert-butylphenyl
122	1-naphthyl
123	2-naphthyl

#### Synthesis Method of Compound Represented by General Formula (1)

The synthesis method of the compound represented by the general formula (1) is not particularly limited. The compound represented by the general formula (1) may be synthesized by combining known synthesis methods and conditions appropriately. For example, the compound may be synthesized by appropriately selecting, combining and

applying the synthesis method described in the paragraphs 0039 to 0049 in JP-A-2009-501194. The compound represented by the general formula (1) may also be synthesized by combining other known synthesis reactions.

#### Organic Light-Emitting Device

The compound represented by the general formula (1) of the invention is useful as a light-emitting material of an organic light-emitting device. The compound represented by the general formula (1) of the invention thus may be effectively used as a light-emitting material in a light-emitting layer of an organic light-emitting device. The compound represented by the general formula (1) includes a delayed fluorescent material (delayed fluorescence emitter) emitting delayed fluorescent light. Accordingly, the invention also relates to an invention of a delayed fluorescence emitter having a structure represented by the general formula (1), an invention of the use of the compound represented by the general formula (1) as a delayed fluorescence emitter, and an invention of a method of emitting delayed fluorescent light with the compound represented by the general formula (1). An organic light-emitting device using the compound as a light-emitting material has features that the device emits delayed fluorescent light and has a high light emission efficiency. The principle of the features will be described as follows for an organic electroluminescent device as an example.

In an organic electroluminescent device, carriers injected from an anode and a cathode form an excited state for the light-emitting material, from which light is emitted. In the case of a carrier injection type organic electroluminescent device, in general, excitons that are excited to the excited singlet state are 25% of the total excitons generated, and the remaining 75% thereof are excited to the excited triplet state. Accordingly, the use of phosphorescence, which is light emission from the excited triplet state, provides a high energy utilization. However, the excited triplet state has a

long lifetime and thus causes saturation of the excited state and deactivation of energy through mutual action with the excitons in the excited triplet state, and therefore the quantum efficiency of phosphorescence may generally be often not high. A delayed fluorescent material emits fluorescent light through the mechanism that excitons excited in the triplet state, which can be formed directly in that state or indirectly processes such as intersystem crossing from a singlet state, transits to the excited triplet state after reverse intersystem crossing or the like, and then transits to the excited singlet state after reverse intersystem crossing due to triplet-triplet annihilation or absorption of thermal energy, thereby emitting fluorescent light. It is considered that among the materials, a thermal activation type delayed fluorescent material emitting light through absorption of thermal energy is particularly useful for an organic electroluminescent device. In the case where a delayed fluorescent material is used in an organic electroluminescent device, the excitons in the excited singlet state normally emit fluorescent light. On the other hand, the excitons in the excited triplet state emit fluorescent light through intersystem crossing to the excited singlet state by absorbing the heat generated by the device. At this time, the light emitted through reverse intersystem crossing from the excited triplet state to the excited singlet state has the same wavelength as fluorescent light since it is light emission from the excited singlet state, but has a longer lifetime (light emission lifetime) than the normal fluorescent light and phosphorescent light, and thus the light is observed as fluorescent light that is delayed from the normal fluorescent light and phosphorescent light. The light may be defined as delayed fluorescent light. The use of the thermal activation type exciton transition mechanism may raise the proportion of the compound in the excited singlet state, which is generally formed in a proportion only of 25%, to 25% or more through the absorption of the thermal energy after the carrier injection. A compound that emits strong fluorescent light and delayed fluorescent light at a low temperature of lower than 100° C. undergoes the intersystem crossing from the excited triplet state to the excited singlet state sufficiently with the heat of the device, thereby emitting delayed fluorescent light, and thus the use of the compound may drastically enhance the light emission efficiency.

The use of the compound represented by the general formula (1) of the invention as a light-emitting material of a light-emitting layer may provide an excellent organic light-emitting device, such as an organic photoluminescent device (organic PL device) and an organic electroluminescent device (organic EL device). The organic photoluminescent device has a structure containing a substrate having formed thereon at least a light-emitting layer. The organic electroluminescent device has a structure containing at least an anode, a cathode and an organic layer formed between the anode and the cathode. The organic layer contains at least a light-emitting layer, and may be formed only of a light-emitting layer, or may have one or more organic layers in addition to the light-emitting layer. Examples of the organic layer include a hole transporting layer, a hole injection layer, an electron barrier layer, a hole barrier layer, an electron injection layer, an electron transporting layer and an exciton barrier layer. The hole transporting layer may be a hole injection and transporting layer having a hole injection function, and the electron transporting layer may be an electron injection and transporting layer having an electron injection function. A specific structural example of an organic electroluminescent device is shown in FIG. 1. In FIG. 1, the numeral 1 denotes a substrate, 2 denotes an

anode, 3 denotes a hole injection layer, 4 denotes a hole transporting layer, 5 denotes a light-emitting layer, 6 denotes an electron transporting layer, and 7 denotes a cathode.

The members and the layers of the organic electroluminescent device will be described below. The descriptions for the substrate and the light-emitting layer may also be applied to the substrate and the light-emitting layer of the organic photoluminescent device.

#### Substrate

The organic electroluminescent device of the invention is preferably supported by a substrate. The substrate is not particularly limited and may be those that have been commonly used in an organic electroluminescent device, and examples thereof used include those formed of glass, transparent plastics, quartz and silicon.

#### Anode

The anode of the organic electroluminescent device used is preferably formed of as an electrode material, a metal, an alloy or an electroconductive compound each having a large work function (4 eV or more), or a mixture thereof. Specific examples of the electrode material include a metal, such as Au, and an electroconductive transparent material, such as CuI, indium tin oxide (ITO), SnO<sub>2</sub> and ZnO. A material that is amorphous and is capable of forming a transparent electroconductive film, such as IDIXO (In<sub>2</sub>O<sub>3</sub>—ZnO), may also be used. The anode may be formed in such a manner that the electrode material is formed into a thin film by such a method as vapor deposition or sputtering, and the film is patterned into a desired shape by a photolithography method, or in the case where the pattern may not require high accuracy (for example, approximately 100 μm or more), the pattern may be formed with a mask having a desired shape on vapor deposition or sputtering of the electrode material. Alternatively, in the case where a material capable of being applied as a coating, such as an organic electroconductive compound, is used, a wet film forming method, such as a printing method and a coating method, may be used. In the case where emitted light is to be taken out through the anode, the anode preferably has a transmittance of more than 10%, and the anode preferably has a sheet resistance of several hundred Ohm per square or less. The thickness thereof may be generally selected from a range of from 10 to 1,000 nm, and preferably from 10 to 200 nm, while depending on the material used.

#### Cathode

The cathode is preferably formed of as an electrode material, a metal having a small work function (4 eV or less) (referred to as an electron injection metal), an alloy or an electroconductive compound each having a small work function (4 eV or less), or a mixture thereof. Specific examples of the electrode material include sodium, a sodium-potassium alloy, magnesium, lithium, a magnesium-copper mixture, a magnesium-silver mixture, a magnesium-aluminum mixture, a magnesium-indium mixture, an aluminum-aluminum oxide (Al<sub>2</sub>O<sub>3</sub>) mixture, indium, a lithium-aluminum mixture, and a rare earth metal. Among these, a mixture of an electron injection metal and a second metal that is a stable metal having a larger work function than the electron injection metal, for example, a magnesium-silver mixture, a magnesium-aluminum mixture, a magnesium-indium mixture, an aluminum-aluminum oxide (Al<sub>2</sub>O<sub>3</sub>) mixture, a lithium-aluminum mixture, and aluminum, are preferred from the standpoint of the electron injection property and the durability against oxidation and the like. The cathode may be produced by forming the electrode material into a thin film by such a method as vapor deposition or sputtering. The cathode preferably has a sheet resistance of

several hundred Ohm per square or less, and the thickness thereof may be generally selected from a range of from 10 nm to 5  $\mu$ m, and preferably from 50 to 200 nm. For transmitting the emitted light, any one of the anode and the cathode of the organic electroluminescent device is preferably transparent or translucent, thereby enhancing the light emission luminance.

The cathode may be formed with the electroconductive transparent materials described for the anode, thereby forming a transparent or translucent cathode, and by applying the cathode, a device having an anode and a cathode, both of which have transmittance, may be produced.

#### Light-Emitting Layer

The light-emitting layer is a layer, in which holes and electrons injected from the anode and the cathode, respectively, are recombined to form excitons, and then the layer emits light. A light-emitting material may be solely used as the light-emitting layer, but the light-emitting layer preferably contains a light-emitting material and a host material. The light-emitting material used may be one kind or two or more kinds selected from the group of compounds represented by the general formula (1) of the invention. In order that the organic electroluminescent device and the organic photoluminescent device of the invention exhibit a high light emission efficiency, it is important that the singlet excitons and the triplet excitons generated in the light-emitting material are confined in the light-emitting material. Accordingly, a host material is preferably used in addition to the light-emitting material in the light-emitting layer. The host material used may be an organic compound that has excited singlet energy and excited triplet energy, at least one of which is higher than those of the light-emitting material of the invention. As a result, the singlet excitons and the triplet excitons generated in the light-emitting material of the invention are capable of being confined in the molecules of the light-emitting material of the invention, thereby eliciting the light emission efficiency thereof sufficiently. There may be cases where a high light emission efficiency is obtained even though the singlet excitons and the triplet excitons may not be confined sufficiently, and therefore a host material capable of achieving a high light emission efficiency may be used in the invention without any particular limitation. In the organic light-emitting device and the organic electroluminescent device of the invention, the light emission occurs in the light-emitting material of the invention contained in the light-emitting layer. The emitted light contains both fluorescent light and delayed fluorescent light. However, a part of the emitted light may contain emitted light from the host material, or the emitted light may partially contain emitted light from the host material.

In the case where the host material is used, the amount of the compound of the invention as the light-emitting material contained in the light-emitting layer is preferably 0.1% by weight or more, and more preferably 1% by weight or more, and is preferably 50% by weight or less, more preferably 20% by weight or less, and further preferably 10% by weight or less.

The host material in the light-emitting layer is preferably an organic compound that has a hole transporting function and an electron transporting function, prevents the emitted light from being increased in wavelength, and has a high glass transition temperature.

#### Injection Layer

The injection layer is a layer that is provided between the electrode and the organic layer, for decreasing the driving voltage and enhancing the light emission luminance, and includes a hole injection layer and an electron injection

layer, which may be provided between the anode and the light-emitting layer or the hole transporting layer and between the cathode and the light-emitting layer or the electron transporting layer. The injection layer may be provided depending on necessity.

#### Barrier Layer

The barrier layer is a layer that is capable of inhibiting charges (electrons or holes) and/or excitons present in the light-emitting layer from diffusing outside the light-emitting layer. The electron barrier layer may be disposed between the light-emitting layer and the hole transporting layer, and inhibits electrons from passing through the light-emitting layer toward the hole transporting layer. Similarly, the hole barrier layer may be disposed between the light-emitting layer and the electron transporting layer, and inhibits holes from passing through the light-emitting layer toward the electron transporting layer. The barrier layer may also be used for inhibiting excitons from diffusing outside the light-emitting layer. Thus, the electron barrier layer and the hole barrier layer each may also have a function as an exciton barrier layer. The electron barrier layer or the exciton barrier layer referred to herein means a layer that has both the functions of an electron barrier layer and an exciton barrier layer by one layer.

#### Hole Barrier Layer

The hole barrier layer has the function of an electron transporting layer in a broad sense. The hole barrier layer has a function of inhibiting holes from reaching the electron transporting layer while transporting electrons, and thereby enhances the recombination probability of electrons and holes in the light-emitting layer. As the material for the hole barrier layer, the materials for the electron transporting layer described later may be used depending on necessity.

#### Electron Barrier Layer

The electron barrier layer has the function of transporting holes in a broad sense. The electron barrier layer has a function of inhibiting electrons from reaching the hole transporting layer while transporting holes, and thereby enhances the recombination probability of electrons and holes in the light-emitting layer.

#### Exciton Barrier Layer

The exciton barrier layer is a layer for inhibiting excitons generated through recombination of holes and electrons in the light-emitting layer from diffusing to the charge transporting layer, and the use of the layer inserted enables effective confinement of excitons in the light-emitting layer, and thereby enhances the light emission efficiency of the device. The exciton barrier layer may be inserted adjacent to the light-emitting layer on any of the side of the anode and the side of the cathode, and on both the sides. Specifically, in the case where the exciton barrier layer is present on the side of the anode, the layer may be inserted between the hole transporting layer and the light-emitting layer and adjacent to the light-emitting layer, and in the case where the layer is inserted on the side of the cathode, the layer may be inserted between the light-emitting layer and the cathode and adjacent to the light-emitting layer. Between the anode and the exciton barrier layer that is adjacent to the light-emitting layer on the side of the anode, a hole injection layer, an electron barrier layer and the like may be provided, and between the cathode and the exciton barrier layer that is adjacent to the light-emitting layer on the side of the cathode, an electron injection layer, an electron transporting layer, a hole barrier layer and the like may be provided. In the case where the barrier layer is provided, the material used for the barrier layer preferably has excited singlet energy and lowest excited triplet energy, at least one of

15

which is higher than the excited singlet energy and the lowest excited triplet energy of the light-emitting material, respectively.

#### Hole Transporting Layer






The hole transporting layer is formed of a hole transporting material having a function of transporting holes, and the hole transporting layer may be provided as a single layer or plural layers.

The hole transporting material has one of injection or transporting property of holes and barrier property of electrons, and may be any of an organic material and an inorganic material. Examples of known hole transporting materials that may be used herein include a triazole derivative, an oxadiazole derivative, an imidazole derivative, a carbazole derivative, an indolocarbazole derivative, a pol-  
 5  
 10  
 15  
 20  
 25  
 30  
 35  
 40  
 45  
 50  
 55  
 60  
 65  
 70  
 75  
 80  
 85  
 90  
 95  
 100  
 105  
 110  
 115  
 120  
 125  
 130  
 135  
 140  
 145  
 150  
 155  
 160  
 165  
 170  
 175  
 180  
 185  
 190  
 195  
 200  
 205  
 210  
 215  
 220  
 225  
 230  
 235  
 240  
 245  
 250  
 255  
 260  
 265  
 270  
 275  
 280  
 285  
 290  
 295  
 300  
 305  
 310  
 315  
 320  
 325  
 330  
 335  
 340  
 345  
 350  
 355  
 360  
 365  
 370  
 375  
 380  
 385  
 390  
 395  
 400  
 405  
 410  
 415  
 420  
 425  
 430  
 435  
 440  
 445  
 450  
 455  
 460  
 465  
 470  
 475  
 480  
 485  
 490  
 495  
 500  
 505  
 510  
 515  
 520  
 525  
 530  
 535  
 540  
 545  
 550  
 555  
 560  
 565  
 570  
 575  
 580  
 585  
 590  
 595  
 600  
 605  
 610  
 615  
 620  
 625  
 630  
 635  
 640  
 645  
 650  
 655  
 660  
 665  
 670  
 675  
 680  
 685  
 690  
 695  
 700  
 705  
 710  
 715  
 720  
 725  
 730  
 735  
 740  
 745  
 750  
 755  
 760  
 765  
 770  
 775  
 780  
 785  
 790  
 795  
 800  
 805  
 810  
 815  
 820  
 825  
 830  
 835  
 840  
 845  
 850  
 855  
 860  
 865  
 870  
 875  
 880  
 885  
 890  
 895  
 900  
 905  
 910  
 915  
 920  
 925  
 930  
 935  
 940  
 945  
 950  
 955  
 960  
 965  
 970  
 975  
 980  
 985  
 990  
 995  
 1000  
 1005  
 1010  
 1015  
 1020  
 1025  
 1030  
 1035  
 1040  
 1045  
 1050  
 1055  
 1060  
 1065  
 1070  
 1075  
 1080  
 1085  
 1090  
 1095  
 1100  
 1105  
 1110  
 1115  
 1120  
 1125  
 1130  
 1135  
 1140  
 1145  
 1150  
 1155  
 1160  
 1165  
 1170  
 1175  
 1180  
 1185  
 1190  
 1195  
 1200  
 1205  
 1210  
 1215  
 1220  
 1225  
 1230  
 1235  
 1240  
 1245  
 1250  
 1255  
 1260  
 1265  
 1270  
 1275  
 1280  
 1285  
 1290  
 1295  
 1300  
 1305  
 1310  
 1315  
 1320  
 1325  
 1330  
 1335  
 1340  
 1345  
 1350  
 1355  
 1360  
 1365  
 1370  
 1375  
 1380  
 1385  
 1390  
 1395  
 1400  
 1405  
 1410  
 1415  
 1420  
 1425  
 1430  
 1435  
 1440  
 1445  
 1450  
 1455  
 1460  
 1465  
 1470  
 1475  
 1480  
 1485  
 1490  
 1495  
 1500  
 1505  
 1510  
 1515  
 1520  
 1525  
 1530  
 1535  
 1540  
 1545  
 1550  
 1555  
 1560  
 1565  
 1570  
 1575  
 1580  
 1585  
 1590  
 1595  
 1600  
 1605  
 1610  
 1615  
 1620  
 1625  
 1630  
 1635  
 1640  
 1645  
 1650  
 1655  
 1660  
 1665  
 1670  
 1675  
 1680  
 1685  
 1690  
 1695  
 1700  
 1705  
 1710  
 1715  
 1720  
 1725  
 1730  
 1735  
 1740  
 1745  
 1750  
 1755  
 1760  
 1765  
 1770  
 1775  
 1780  
 1785  
 1790  
 1795  
 1800  
 1805  
 1810  
 1815  
 1820  
 1825  
 1830  
 1835  
 1840  
 1845  
 1850  
 1855  
 1860  
 1865  
 1870  
 1875  
 1880  
 1885  
 1890  
 1895  
 1900  
 1905  
 1910  
 1915  
 1920  
 1925  
 1930  
 1935  
 1940  
 1945  
 1950  
 1955  
 1960  
 1965  
 1970  
 1975  
 1980  
 1985  
 1990  
 1995  
 2000  
 2005  
 2010  
 2015  
 2020  
 2025  
 2030  
 2035  
 2040  
 2045  
 2050  
 2055  
 2060  
 2065  
 2070  
 2075  
 2080  
 2085  
 2090  
 2095  
 2100  
 2105  
 2110  
 2115  
 2120  
 2125  
 2130  
 2135  
 2140  
 2145  
 2150  
 2155  
 2160  
 2165  
 2170  
 2175  
 2180  
 2185  
 2190  
 2195  
 2200  
 2205  
 2210  
 2215  
 2220  
 2225  
 2230  
 2235  
 2240  
 2245  
 2250  
 2255  
 2260  
 2265  
 2270  
 2275  
 2280  
 2285  
 2290  
 2295  
 2300  
 2305  
 2310  
 2315  
 2320  
 2325  
 2330  
 2335  
 2340  
 2345  
 2350  
 2355  
 2360  
 2365  
 2370  
 2375  
 2380  
 2385  
 2390  
 2395  
 2400  
 2405  
 2410  
 2415  
 2420  
 2425  
 2430  
 2435  
 2440  
 2445  
 2450  
 2455  
 2460  
 2465  
 2470  
 2475  
 2480  
 2485  
 2490  
 2495  
 2500  
 2505  
 2510  
 2515  
 2520  
 2525  
 2530  
 2535  
 2540  
 2545  
 2550  
 2555  
 2560  
 2565  
 2570  
 2575  
 2580  
 2585  
 2590  
 2595  
 2600  
 2605  
 2610  
 2615  
 2620  
 2625  
 2630  
 2635  
 2640  
 2645  
 2650  
 2655  
 2660  
 2665  
 2670  
 2675  
 2680  
 2685  
 2690  
 2695  
 2700  
 2705  
 2710  
 2715  
 2720  
 2725  
 2730  
 2735  
 2740  
 2745  
 2750  
 2755  
 2760  
 2765  
 2770  
 2775  
 2780  
 2785  
 2790  
 2795  
 2800  
 2805  
 2810  
 2815  
 2820  
 2825  
 2830  
 2835  
 2840  
 2845  
 2850  
 2855  
 2860  
 2865  
 2870  
 2875  
 2880  
 2885  
 2890  
 2895  
 2900  
 2905  
 2910  
 2915  
 2920  
 2925  
 2930  
 2935  
 2940  
 2945  
 2950  
 2955  
 2960  
 2965  
 2970  
 2975  
 2980  
 2985  
 2990  
 2995  
 3000  
 3005  
 3010  
 3015  
 3020  
 3025  
 3030  
 3035  
 3040  
 3045  
 3050  
 3055  
 3060  
 3065  
 3070  
 3075  
 3080  
 3085  
 3090  
 3095  
 3100  
 3105  
 3110  
 3115  
 3120  
 3125  
 3130  
 3135  
 3140  
 3145  
 3150  
 3155  
 3160  
 3165  
 3170  
 3175  
 3180  
 3185  
 3190  
 3195  
 3200  
 3205  
 3210  
 3215  
 3220  
 3225  
 3230  
 3235  
 3240  
 3245  
 3250  
 3255  
 3260  
 3265  
 3270  
 3275  
 3280  
 3285  
 3290  
 3295  
 3300  
 3305  
 3310  
 3315  
 3320  
 3325  
 3330  
 3335  
 3340  
 3345  
 3350  
 3355  
 3360  
 3365  
 3370  
 3375  
 3380  
 3385  
 3390  
 3395  
 3400  
 3405  
 3410  
 3415  
 3420  
 3425  
 3430  
 3435  
 3440  
 3445  
 3450  
 3455  
 3460  
 3465  
 3470  
 3475  
 3480  
 3485  
 3490  
 3495  
 3500  
 3505  
 3510  
 3515  
 3520  
 3525  
 3530  
 3535  
 3540  
 3545  
 3550  
 3555  
 3560  
 3565  
 3570  
 3575  
 3580  
 3585  
 3590  
 3595  
 3600  
 3605  
 3610  
 3615  
 3620  
 3625  
 3630  
 3635  
 3640  
 3645  
 3650  
 3655  
 3660  
 3665  
 3670  
 3675  
 3680  
 3685  
 3690  
 3695  
 3700  
 3705  
 3710  
 3715  
 3720  
 3725  
 3730  
 3735  
 3740  
 3745  
 3750  
 3755  
 3760  
 3765  
 3770  
 3775  
 3780  
 3785  
 3790  
 3795  
 3800  
 3805  
 3810  
 3815  
 3820  
 3825  
 3830  
 3835  
 3840  
 3845  
 3850  
 3855  
 3860  
 3865  
 3870  
 3875  
 3880  
 3885  
 3890  
 3895  
 3900  
 3905  
 3910  
 3915  
 3920  
 3925  
 3930  
 3935  
 3940  
 3945  
 3950  
 3955  
 3960  
 3965  
 3970  
 3975  
 3980  
 3985  
 3990  
 3995  
 4000  
 4005  
 4010  
 4015  
 4020  
 4025  
 4030  
 4035  
 4040  
 4045  
 4050  
 4055  
 4060  
 4065  
 4070  
 4075  
 4080  
 4085  
 4090  
 4095  
 4100  
 4105  
 4110  
 4115  
 4120  
 4125  
 4130  
 4135  
 4140  
 4145  
 4150  
 4155  
 4160  
 4165  
 4170  
 4175  
 4180  
 4185  
 4190  
 4195  
 4200  
 4205  
 4210  
 4215  
 4220  
 4225  
 4230  
 4235  
 4240  
 4245  
 4250  
 4255  
 4260  
 4265  
 4270  
 4275  
 4280  
 4285  
 4290  
 4295  
 4300  
 4305  
 4310  
 4315  
 4320  
 4325  
 4330  
 4335  
 4340  
 4345  
 4350  
 4355  
 4360  
 4365  
 4370  
 4375  
 4380  
 4385  
 4390  
 4395  
 4400  
 4405  
 4410  
 4415  
 4420  
 4425  
 4430  
 4435  
 4440  
 4445  
 4450  
 4455  
 4460  
 4465  
 4470  
 4475  
 4480  
 4485  
 4490  
 4495  
 4500  
 4505  
 4510  
 4515  
 4520  
 4525  
 4530  
 4535  
 4540  
 4545  
 4550  
 4555  
 4560  
 4565  
 4570  
 4575  
 4580  
 4585  
 4590  
 4595  
 4600  
 4605  
 4610  
 4615  
 4620  
 4625  
 4630  
 4635  
 4640  
 4645  
 4650  
 4655  
 4660  
 4665  
 4670  
 4675  
 4680  
 4685  
 4690  
 4695  
 4700  
 4705  
 4710  
 4715  
 4720  
 4725  
 4730  
 4735  
 4740  
 4745  
 4750  
 4755  
 4760  
 4765  
 4770  
 4775  
 4780  
 4785  
 4790  
 4795  
 4800  
 4805  
 4810  
 4815  
 4820  
 4825  
 4830  
 4835  
 4840  
 4845  
 4850  
 4855  
 4860  
 4865  
 4870  
 4875  
 4880  
 4885  
 4890  
 4895  
 4900  
 4905  
 4910  
 4915  
 4920  
 4925  
 4930  
 4935  
 4940  
 4945  
 4950  
 4955  
 4960  
 4965  
 4970  
 4975  
 4980  
 4985  
 4990  
 4995  
 5000  
 5005  
 5010  
 5015  
 5020  
 5025  
 5030  
 5035  
 5040  
 5045  
 5050  
 5055  
 5060  
 5065  
 5070  
 5075  
 5080  
 5085  
 5090  
 5095  
 5100  
 5105  
 5110  
 5115  
 5120  
 5125  
 5130  
 5135  
 5140  
 5145  
 5150  
 5155  
 5160  
 5165  
 5170  
 5175  
 5180  
 5185  
 5190  
 5195  
 5200  
 5205  
 5210  
 5215  
 5220  
 5225  
 5230  
 5235  
 5240  
 5245  
 5250  
 5255  
 5260  
 5265  
 5270  
 5275  
 5280  
 5285  
 5290  
 5295  
 5300  
 5305  
 5310  
 5315  
 5320  
 5325  
 5330  
 5335  
 5340  
 5345  
 5350  
 5355  
 5360  
 5365  
 5370  
 5375  
 5380  
 5385  
 5390  
 5395  
 5400  
 5405  
 5410  
 5415  
 5420  
 5425  
 5430  
 5435  
 5440  
 5445  
 5450  
 5455  
 5460  
 5465  
 5470  
 5475  
 5480  
 5485  
 5490  
 5495  
 5500  
 5505  
 5510  
 5515  
 5520  
 5525  
 5530  
 5535  
 5540  
 5545  
 5550  
 5555  
 5560  
 5565  
 5570  
 5575  
 5580  
 5585  
 5590  
 5595  
 5600  
 5605  
 5610  
 5615  
 5620  
 5625  
 5630  
 5635  
 5640  
 5645  
 5650  
 5655  
 5660  
 5665  
 5670  
 5675  
 5680  
 5685  
 5690  
 5695  
 5700  
 5705  
 5710  
 5715  
 5720  
 5725  
 5730  
 5735  
 5740  
 5745  
 5750  
 5755  
 5760  
 5765  
 5770  
 5775  
 5780  
 5785  
 5790  
 5795  
 5800  
 5805  
 5810  
 5815  
 5820  
 5825  
 5830  
 5835  
 5840  
 5845  
 5850  
 5855  
 5860  
 5865  
 5870  
 5875  
 5880  
 5885  
 5890  
 5895  
 5900  
 5905  
 5910  
 5915  
 5920  
 5925  
 5930  
 5935  
 5940  
 5945  
 5950  
 5955  
 5960  
 5965  
 5970  
 5975  
 5980  
 5985  
 5990  
 5995  
 6000  
 6005  
 6010  
 6015  
 6020  
 6025  
 6030  
 6035  
 6040  
 6045  
 6050  
 6055  
 6060  
 6065  
 6070  
 6075  
 6080  
 6085  
 6090  
 6095  
 6100  
 6105  
 6110  
 6115  
 6120  
 6125  
 6130  
 6135  
 6140  
 6145  
 6150  
 6155  
 6160  
 6165  
 6170  
 6175  
 6180  
 6185  
 6190  
 6195  
 6200  
 6205  
 6210  
 6215  
 6220  
 6225  
 6230  
 6235  
 6240  
 6245  
 6250  
 6255  
 6260  
 6265  
 6270  
 6275  
 6280  
 6285  
 6290  
 6295  
 6300  
 6305  
 6310  
 6315  
 6320  
 6325  
 6330  
 6335  
 6340  
 6345  
 6350  
 6355  
 6360  
 6365  
 6370  
 6375  
 6380  
 6385  
 6390  
 6395  
 6400  
 6405  
 6410  
 6415  
 6420  
 6425  
 6430  
 6435  
 6440  
 6445  
 6450  
 6455  
 6460  
 6465  
 6470  
 6475  
 6480  
 6485  
 6490  
 6495  
 6500  
 6505  
 6510  
 6515  
 6520  
 6525  
 6530  
 6535  
 6540  
 6545  
 6550  
 6555  
 6560  
 6565  
 6570  
 6575  
 6580  
 6585  
 6590  
 6595  
 6600  
 6605  
 6610  
 6615  
 6620  
 6625  
 6630  
 6635  
 6640  
 6645  
 6650  
 6655  
 6660  
 6665  
 6670  
 6675  
 6680  
 6685  
 6690  
 6695  
 6700  
 6705  
 6710  
 6715  
 6720  
 6725  
 6730  
 6735  
 6740  
 6745  
 6750  
 6755  
 6760  
 6765  
 6770  
 6775  
 6780  
 6785  
 6790  
 6795  
 6800  
 680

17


18

-continued










19



20











-continued




21

22

-continued









23



-continued








24



25

26


-continued







27

28

-continued




Preferred examples of a compound that may be used as the hole injection material are shown below.



29


30

-continued




30






Preferred examples of a compound that may be used as the hole transporting material are shown below.



32




34









35



-continued







36




37

-continued




38





39



40




R =




41

42

-continued






43



-continued

44

Preferred examples of a compound that may be used as the electron barrier material are shown below.



-continued

25

30

35

40


45

50

55


60

65




Preferred examples of a compound that may be used as the hole barrier material are shown below.

45




46

-continued



**47**


-continued

**48**









-continued

5

10







Preferred examples of a compound that may be used as the electron transporting material are shown below.




49

50







-continued



R =:



R = H












51




52

-continued




**53****54**

-continued




35

Preferred examples of a compound that may be used as the electron injection material are shown below.




40



45

Preferred examples of a compound as a material that may be added are shown below. For example, the compound may be added as a stabilizing material.





50

55

60



65

-continued



55

-continued



The organic electroluminescent device thus produced by the aforementioned method emits light on application of an electric field between the anode and the cathode of the device. In this case, when the light emission is caused by the excited singlet energy, light having a wavelength that corresponds to the energy level thereof may be confirmed as fluorescent light and delayed fluorescent light. When the light emission is caused by the excited triplet energy, light having a wavelength that corresponds to the energy level thereof may be confirmed as phosphorescent light. The normal fluorescent light has a shorter light emission lifetime than the delayed fluorescent light, and thus the light emission lifetime may be distinguished between the fluorescent light and the delayed fluorescent light.

The phosphorescent light may substantially not be observed with a normal organic compound, such as the compound of the invention, at room temperature since the excited triplet energy is converted to heat of the like due to the instability thereof, and is immediately deactivated with a short lifetime. The excited triplet energy of the normal organic compound may be measured by observing light emission under an extremely low temperature condition.

The organic electroluminescent device of the invention may be applied to any of a single device, a device having a structure with plural devices disposed in an array, and a device having anodes and cathodes disposed in an X-Y matrix. According to the invention, an organic light-emitting device that is largely improved in light emission efficiency may be obtained by adding the compound represented by the general formula (1) in the light-emitting layer. The organic light-emitting device, such as the organic electroluminescent device, of the invention may be applied to a further wide range of purposes. For example, an organic electroluminescent display apparatus may be produced with the organic electroluminescent device of the invention, and for the details thereof, reference may be made to S. Tokito, C. Adachi and H. Murata, "Yuki EL Display" (Organic EL Display) (Ohmsha, Ltd.). In particular, the organic electrolu-

56

minescent device of the invention may be applied to organic electroluminescent illumination and backlight which are highly demanded.

## EXAMPLE

The features of the invention will be described more specifically with reference to examples below. The materials, processes, procedures and the like shown below may be appropriately modified unless they deviate from the substance of the invention. Accordingly, the scope of the invention is not construed as being limited to the specific examples shown below.

### Example 1

#### (1) Production of Organic Photoluminescent Device (Organic PL Device)

6% by weight of the compound 1 and PYD2 were formed into a film on a quartz substrate by vapor co-deposition, and measured for PL light emission spectrum, PL quantum efficiency and PL transient decay. The PL light emission spectrum at an excitation wavelength of 337 nm is shown in FIG. 2. The vapor co-deposited film showed blue light emission and showed a high PL quantum efficiency of 32%.



For investigating the delayed fluorescence characteristics of the compound 1, the vapor co-deposited film was then measured for PL transient decay with a streak camera. The measurement result is shown in FIG. 3. The PL transient decay curve well agreed with the fitting of two components. In the measurement under bubbling with a nitrogen gas, a component having a short lifetime of 4 ns and a component having a long lifetime of 1.2  $\mu$ s were observed, whereas in the measurement without a nitrogen gas bubbled, a component having a short lifetime of 5 ns and a component having a long lifetime of 256 ns were observed. Accordingly, delayed fluorescence derived from the long lifetime component was observed in addition to the fluorescent light with a short lifetime with the compound 1.

#### (2) Production of Organic Electroluminescent Device (Organic EL Device)


An organic electroluminescent device having the layer structure shown in FIG. 1 was produced in the following manner.

Indium tin oxide (ITO) was formed into a film having a thickness of approximately from 30 to 100 nm on glass, and  $\alpha$ -NPD was further formed into a film having a thickness of 60 nm thereon. Subsequently, 6% by weight of the compound 1 and PYD2 were formed into a film having a thickness of 20 nm by vapor co-deposition, which was designated as a light-emitting layer. Bphen was further formed into a film having a thickness of 40 nm thereon. Subsequently, magnesium-silver (MgAg) was vacuum vapor-deposited to a thickness of 100 nm, and then aluminum (Al) was vapor-deposited to a thickness of 20 nm, thereby completing an organic electroluminescent device having the layer structure shown in FIG. 1. The EL light emission spectrum of the organic EL device thus produced is shown in FIG. 4. The EL spectrum well agreed with the PL spectrum shown in FIG. 2, and thus it was confirmed that the light emission from the device was derived from the compound 1.

57

 $\alpha$ -NPD

PDY2



BPhen

Example 2

## (1) Production of Organic Photoluminescent Device

6% by weight of the compound 101 and PYD2 were formed into a film on a quartz substrate by vapor co-deposition, and measured for PL light emission spectrum and PL quantum efficiency. The PL light emission spectrum at an excitation wavelength of 337 nm is shown in FIG. 5. The vapor co-deposited film showed red light emission and showed a high PL quantum efficiency of 91%. The results of the measurement of PL transient decay with a streak camera at 77 K, 100 K, 150 K, 200 K, 250 K and 300 K are shown in FIG. 6. It was confirmed from FIG. 6 that the delayed fluorescence depends on the temperature.

## (2) Production of Organic Electroluminescent Device

An organic electroluminescent device having the layer structure shown in FIG. 1 was produced in the following manner.

Indium tin oxide (ITO) was formed into a film having a thickness of approximately from 30 to 100 nm on glass, and  $\alpha$ -NPD was further formed into a film having a thickness of 60 nm thereon. Subsequently, 6% by weight of the compound 101 and PYD2 were formed into a film having a thickness of 20 nm by vapor co-deposition, which was designated as a light-emitting layer. Bphen was further formed into a film having a thickness of 40 nm thereon.

58

Subsequently, magnesium-silver (Mg/Ag) was vapor-deposited to a thickness of 100 nm, and then aluminum (Al) was vapor-deposited to a thickness of 20 nm, thereby completing an organic electroluminescent device having the layer structure shown in FIG. 1. The electroluminescence (EL) spectrum is shown in FIG. 7. The EL spectrum well agreed with the PL spectrum, and thus it was confirmed that the light emission from the device was derived from the compound 101. The electric current density-voltage characteristics-luminance characteristics are shown in FIG. 8, and the external quantum efficiency-electric current density characteristics are shown in FIG. 9. It was confirmed that the external quantum efficiency was as high as 13.85%.

## Example 3

The usefulness of the compounds 2 to 23 and the compounds 102 to 123 may be confirmed as similar to Examples 1 and 2.

## INDUSTRIAL APPLICABILITY

The compound represented by the general formula (1) is useful as a light-emitting material of an organic light-emitting device. The compound represented by the general formula (1) includes one that exhibits emission of delayed fluorescent light and one that has an extremely high light emission efficiency. Accordingly, an organic light-emitting device using the compound represented by the general formula (1) as a light-emitting material exhibits emission of delayed fluorescent light and has a high light emission efficiency, and thus is significantly useful. Consequently, the invention has high industrial applicability.


## REFERENCE SIGNS LIST

- 1 substrate
- 2 anode
- 3 hole injection layer
- 4 hole transporting layer
- 5 light-emitting layer
- 6 electron transporting layer
- 7 cathode

The invention claimed is:

1. A light-emitting material comprising a compound represented by the following formula (1):

Formula (1)




59

wherein  $Z^1$ ,  $Z^2$  and  $Z^3$  each independently represent an aryl group substituted by a substituted or unsubstituted diarylamino group.

2. The light-emitting material according to claim 1, wherein  $Z^1$ ,  $Z^2$  and  $Z^3$  in the formula (1) are the same.

3. The light-emitting material according to claim 1, wherein the compound has a structure represented by the following formula (3):




wherein  $Ar^{11}$ ,  $Ar^{12}$ ,  $Ar^{13}$ ,  $Ar^{14}$ ,  $Ar^{15}$  and  $Ar^{16}$  each independently represent a substituted or unsubstituted aryl group.

4. A delayed fluorescence emitter having a structure represented by the following formula (1):

60


Formula (1)



wherein  $Z^1$ ,  $Z^2$  and  $Z^3$  each independently represent an aryl group substituted by a substituted or unsubstituted diarylamino group.

5. An organic light-emitting device comprising as a light-emitting material a compound represented by the following formula (1):

Formula (1)



wherein  $Z^1$ ,  $Z^2$  and  $Z^3$  each independently represent an aryl group substituted by a substituted or unsubstituted diarylamino group.

6. The organic light-emitting device according to claim 5, which is an organic electroluminescent device containing an anode, a cathode, and at least one organic layer containing a light-emitting layer between the anode and the cathode, and contains the light-emitting material in the light-emitting layer.

7. The organic light-emitting device according to claim 5, which emits delayed fluorescent light.

\* \* \* \* \*

专利名称(译)	发光材料和有机发光元件		
公开(公告)号	<a href="#">US9985215</a>	公开(公告)日	2018-05-29
申请号	US14/383971	申请日	2013-03-07
[标]申请(专利权)人(译)	国立大学法人九州大学		
申请(专利权)人(译)	九州大学国立大学法人		
当前申请(专利权)人(译)	KYULUX , INC.		
[标]发明人	ADACHI CHIHAYA NAKAGAWA TETSUYA LI JIE		
发明人	ADACHI, CHIHAYA NAKAGAWA, TETSUYA LI, JIE		
IPC分类号	H01L51/50 H01L51/00 C07D487/16 C09K11/06		
CPC分类号	H01L51/0061 C07D487/16 C09K11/06 C09K2211/1007 H01L51/5012 C09K2211/1074 H01L51/0067 H01L51/0072 C09K2211/1014		
优先权	2012053437 2012-03-09 JP		
其他公开文献	US20150048338A1		
外部链接	<a href="#">Espacenet</a> <a href="#">USPTO</a>		

#### 摘要(译)

由以下通式表示的化合物可用作有机发光器件的发光材料。以下通式中的Z 1 , Z 2 和Z 3 各自独立地表示取代基。

