



US010347703B2

(12) **United States Patent**  
**Park et al.**

(10) **Patent No.:** **US 10,347,703 B2**  
(45) **Date of Patent:** **\*Jul. 9, 2019**

(54) **ORGANIC LIGHT-EMITTING DIODE DISPLAY**

(58) **Field of Classification Search**  
None  
See application file for complete search history.

(71) Applicant: **Samsung Display Co., Ltd.**, Yongin-si, Gyeonggi-do (KR)

(56) **References Cited**

(72) Inventors: **Ok-Kyung Park**, Hwaseong-si (KR);  
**Su Yeon Yun**, Seoul (KR)

U.S. PATENT DOCUMENTS

(73) Assignee: **Samsung Display Co., Ltd.**, Yongin-si (KR)

4,642,619 A 2/1987 Togashi  
6,366,025 B1 4/2002 Yamada  
(Continued)

(\* ) Notice: Subject to any disclaimer, the term of this patent is extended or adjusted under 35 U.S.C. 154(b) by 0 days.  
  
This patent is subject to a terminal disclaimer.

FOREIGN PATENT DOCUMENTS

CN 101009304 A 8/2007  
CN 101449382 A 6/2009  
(Continued)

OTHER PUBLICATIONS

(21) Appl. No.: **15/688,760**

EPO Search Report dated Jul. 8, 2013, for corresponding European Patent application 13157562.3, (6 pages).  
(Continued)

(22) Filed: **Aug. 28, 2017**

(65) **Prior Publication Data**  
US 2017/0358640 A1 Dec. 14, 2017

*Primary Examiner* — Dung A. Le  
(74) *Attorney, Agent, or Firm* — Lewis Roca Rothgerber Christie LLP

**Related U.S. Application Data**

(63) Continuation of application No. 15/090,591, filed on Apr. 4, 2016, now Pat. No. 9,837,476, which is a  
(Continued)

(57) **ABSTRACT**

An organic light emitting diode (OLED) display includes: a first electrode around a center point of a virtual tetragon, e.g., a virtual square; second electrodes around a first vertex and a second vertex diagonal to the first vertex of the virtual square, the second electrodes being separated from each other and with the center point of the virtual square interposed therebetween; third electrodes around a third vertex and a fourth vertex of the virtual square, the third electrodes being separated from each other and with the center point of the virtual square interposed therebetween; a pixel defining layer partially on the first electrode, the second electrodes, and the third electrodes, and partially exposing the first electrode, the second electrodes, and the third electrodes; and four spacers disposed as islands on the pixel defining layer and corresponding to four sides of the virtual square.

(30) **Foreign Application Priority Data**


Apr. 26, 2013 (KR) ..... 10-2013-0046996

(51) **Int. Cl.**  
**H01L 27/32** (2006.01)  
**H01L 51/52** (2006.01)  
**G02F 1/1362** (2006.01)

(52) **U.S. Cl.**  
CPC ..... **H01L 27/3262** (2013.01); **H01L 27/3216** (2013.01); **H01L 27/3218** (2013.01);  
(Continued)

**20 Claims, 3 Drawing Sheets**

1000



**Related U.S. Application Data**

continuation of application No. 14/059,356, filed on Oct. 21, 2013, now Pat. No. 9,431,469.

(52) **U.S. Cl.**

CPC ..... **H01L 27/3246** (2013.01); **H01L 27/3276** (2013.01); **H01L 51/525** (2013.01); **G02F 1/1362** (2013.01)

(56) **References Cited**

U.S. PATENT DOCUMENTS

6,867,549	B2	3/2005	Cok et al.	
6,882,364	B1	4/2005	Inuiya et al.	
7,274,383	B1	9/2007	Brown Elliot	
8,026,669	B2	9/2011	Kawasaki et al.	
8,330,352	B2	12/2012	Sung et al.	
8,350,468	B2	1/2013	Ko et al.	
8,354,789	B2	1/2013	Kim et al.	
9,837,476	B2*	12/2017	Park .....	H01L 27/3262
2002/0015110	A1	2/2002	Brown Elliott	
2002/0070909	A1	6/2002	Asano et al.	
2002/0113195	A1	8/2002	Osada	
2003/0128179	A1	7/2003	Credelle	
2004/0108818	A1	6/2004	Cok et al.	
2004/0183764	A1	9/2004	Kim et al.	
2004/0246426	A1	12/2004	Wang et al.	
2005/0001542	A1	1/2005	Kiguchi	
2005/0162079	A1	7/2005	Sakamoto	
2006/0152531	A1	7/2006	Lin et al.	
2006/0274090	A1	12/2006	Koyama et al.	
2008/0001525	A1	1/2008	Chao et al.	
2008/0001527	A1	1/2008	Koo et al.	
2008/0273793	A1	11/2008	Oishi	
2008/0308819	A1	12/2008	Louwsma et al.	
2009/0302331	A1	12/2009	Smith et al.	
2010/0033084	A1	2/2010	Ko et al.	
2010/0133994	A1	6/2010	Song et al.	
2010/0171440	A1	7/2010	Satou et al.	
2011/0012820	A1	1/2011	Kim et al.	
2011/0291550	A1	12/2011	Kim et al.	
2012/0056531	A1	3/2012	Park et al.	
2012/0086330	A1	4/2012	Umeda et al.	
2012/0287605	A1	11/2012	Chen et al.	
2012/0313844	A1	12/2012	Im et al.	
2012/0319564	A1	12/2012	Ghosh et al.	
2013/0037827	A1	2/2013	Levermore et al.	
2013/0057521	A1	3/2013	Kim	
2013/0127689	A1	5/2013	Gollier	
2015/0192834	A1	7/2015	Morinaga et al.	

FOREIGN PATENT DOCUMENTS

CN	103311266	A	9/2013
CN	203260586	U	10/2013
CN	105206647	A	12/2015
GB	2 437 110	A	10/2007
JP	3-36239		5/1991
JP	10-39791		2/1998
JP	2000-235891	A	8/2000
JP	2003-203770	A	7/2003
JP	2004-507773		3/2004
JP	2004-179028	A	6/2004
JP	2004-192813		7/2004
JP	2005-5227	A	1/2005
JP	2006-18195	A	1/2006

JP	2006-309182	A	11/2006
JP	2008-015521	A	1/2008
JP	2010-153173	A	7/2010
JP	2011-076760		4/2011
KR	10-0742370	B1	7/2007
KR	10-0807524	B1	2/2008
KR	10-2008-0111130		12/2008
KR	10-2009-0017910	A	2/2009
KR	10-2011-0023996	A	3/2011
KR	10-2011-0106565	A	9/2011
KR	10-2011-0129531		12/2011
KR	10-2012-0022967		3/2012
TW	1328207	B	8/2010
WO	WO 2004/073356	A1	8/2004
WO	WO 2005/067352	A1	7/2005

OTHER PUBLICATIONS

EPO Search Report dated Dec. 20, 2013, for European Patent application 13178648.5, (9 pages).

EPO Search Report dated Jul. 9, 2014, for corresponding European Patent application 14155124.2, (8 pages).

JPO Office action dated Feb. 16, 2016, for corresponding Japanese Patent application 2012-108855, (5 pages).

Korean Patent Abstracts for Korean Publication 1020070055908 dated May 31, 2007, corresponding to Korean Patent 10-0742370 dated Jul. 24, 2007, listed above.

KIPO Office action dated Jul. 11, 2016, with English translation, for Korean Patent application 10-2016-0047800, (11 pages).

SIPO Office action dated Mar. 11, 2015, corresponding to Chinese Patent application 201310035429.X, (7 pages).

Taiwan Office action dated Mar. 30, 2015, corresponding to Taiwanese Patent application 102101000, (7 pages).

TIPO Office Action dated Oct. 11, 2016, corresponding to Taiwanese Patent Application No. 102124953 (6 pages).

U.S. Office action dated Nov. 7, 2014, for cross reference U.S. Appl. No. 13/614,197, (16 pages).

U.S. Office action dated Mar. 12, 2015, for cross reference U.S. Appl. No. 13/614,197, (13 pages).

U.S. Office action dated Jun. 30, 2015 issued in U.S. Appl. No. 13/872,018, (22 pages).

U.S. Office action dated Jul. 15, 2015 issued in U.S. Appl. No. 13/614,197, (12 pages).

U.S. Office action dated Oct. 16, 2015 issued in U.S. Appl. No. 13/872,018, (16 pages).

U.S. Office action dated Dec. 2, 2015, for cross reference U.S. Appl. No. 13/614,197, (12 pages).

U.S. Office Action dated Aug. 29, 2014 issued in cross-reference U.S. Appl. No. 14/059,356 (14 pages).

U.S. Office action dated Feb. 29, 2016, for cross reference U.S. Appl. No. 13/872,018, (15 pages).

U.S. Office action dated Apr. 7, 2016, for cross reference U.S. Appl. No. 13/614,197, (13 pages).

U.S. Office Action dated Sep. 2, 2016, issued in cross-reference U.S. Appl. No. 13/872,018 (15 pages).

U.S. Office Action dated Oct. 14, 2016, issued in cross-reference U.S. Appl. No. 13/614,197 (12 pages).

U.S. Office Action dated Dec. 30, 2016, for U.S. Appl. No. 13/872,018 (14 pages).

U.S. Office Action dated May 11, 2017, issued in cross-reference U.S. Appl. No. 13/872,018 (16 pages).

U.S. Office Action dated Jul. 11, 2018, issued in U.S. Appl. No. 15/811,599 19 (pages).

\* cited by examiner

FIG. 1

1000




FIG. 2





FIG. 3

1002



## ORGANIC LIGHT-EMITTING DIODE DISPLAY

### CROSS-REFERENCE TO RELATED APPLICATION

This application is a continuation of U.S. patent application Ser. No. 15/090,591, filed Apr. 4, 2016, which is a continuation of U.S. patent application Ser. No. 14/059,356, filed Oct. 21, 2013, now U.S. Pat. No. 9,431,469, which claims priority to and the benefit of Korean Patent Application No. 10-2013-0046996, filed Apr. 26, 2013, the entire contents of all of which are incorporated herein by reference.

### BACKGROUND

#### (a) Field

Aspects of embodiments of the present invention relate to an organic light emitting diode (OLED) display.

#### (b) Description of the Related Art

A display device is a device for displaying an image. Recently, OLED displays have received attention. Since OLED displays have self-emission characteristics and do not require separate light sources, which is unlike liquid crystal display devices, it is possible to reduce their thickness and weight when compared to those of older technologies. Further, OLED displays have high-quality characteristics such as low power consumption, high luminance, and high response speed.

In general, an OLED display includes a first substrate, a first electrode disposed on the first substrate, a pixel defining layer including an opening that exposes the first electrode, an organic emission layer disposed on the first electrode corresponding to the opening, a second electrode disposed on the organic emission layer, and a second substrate disposed on the first electrode.

A more recent OLED display may further include a spacer disposed on a pixel defining layer to reduce or minimize interference due to the second substrate by increasing a gap between an organic emission layer and the second substrate. However, in a conventional OLED display including a spacer, the spacer is simply disposed on an unopened portion of the pixel defining layer without regard to the shape of the opening included in the pixel defining layer.

The above information disclosed in this Background section is only for enhancement of understanding of the background of the present invention and therefore it may contain information that does not form the prior art that is already known in this country to a person of ordinary skill in the art.

### SUMMARY

Embodiments of the present invention relate to a pixel alignment structure of an organic light emitting device. More particularly, embodiments of the present invention relate to a pixel structure including an OLED and spacers disposed on a pixel defining layer that exposes a first electrode of the OLED.

Embodiments of the present invention provide for an OLED display including spacers disposed on a pixel defining layer and considering the shape of openings included in the pixel defining layer to reduce or minimize interference of a substrate with respect to an organic emission layer by increasing an area ratio of the spacers in the entire area of the OLED display.

In an embodiment of the present invention, an organic light emitting diode (OLED) display is provided. The OLED display includes: a first electrode around a center point of a virtual tetragon, e.g., a virtual square; second electrodes around a first vertex and a second vertex diagonal to the first vertex of the virtual square, the second electrodes being separated from each other and with the center point of the virtual square interposed therebetween; third electrodes around a third vertex and a fourth vertex of the virtual square, the third electrodes being separated from each other and with the center point of the virtual square interposed therebetween; a pixel defining layer partially on the first electrode, the second electrodes, and the third electrodes, and partially exposing the first electrode, the second electrodes, and the third electrodes; and four spacers disposed as islands on the pixel defining layer and corresponding to four sides of the virtual square.

The pixel defining layer may have a first opening that exposes the first electrode and has a first polygon shape whose center coincides with the center point of the virtual square, second openings that expose the second electrodes and have second polygonal shapes whose centers coincide with the first vertex and the second vertex, and third openings that expose the third electrodes and have third polygonal shapes whose centers coincide with the third vertex and the fourth vertex.

Distances between the center point of the virtual square and centers of the four spacers may be the same.

Each of the four spacers may have a square shape.

Each of the spacers may have a rectangle shape having long sides that are bisected by a respective one of the four sides of the virtual square.

Each of the second openings and the third openings may have a larger area compared to that of the first opening.

Each of the second openings may have a larger area than that of each of the third openings.

At least one of the first polygonal shape, the second polygonal shapes, or the third polygonal shapes may be an octagon.

The first polygonal shape may be an octagon, and one of the second polygonal shapes and one of the third polygonal shapes may be a hexagon and a quadrilateral.

The first opening may include a plurality of first openings, and neighboring ones of the plurality of first openings may have symmetrical octagonal shapes.

Distances between the first opening and each of the second openings, and distances between the first opening and each of the third openings may be a same first length.

Distances between each of the second openings and each of the third openings may be a same second length, and distances between the neighboring ones of the plurality of first openings may be a same third length that is longer than each of the first length and the second length.

The OLED display may further include a first organic emission layer on the first electrode corresponding to the first opening, second organic emission layers on the second electrodes and corresponding to the second openings, and third organic emission layers on the third electrodes and corresponding to the third openings.

The first organic emission layer may be configured to emit a first color light, the second organic emission layers may be configured to emit a second color light different from the first color light, and the third organic emission layers may be configured to emit a third color light different from the first color light and the second color light.

The first color light may be green, and the second color light and the third color light may be blue and red.

According to one embodiment of the present invention, spacers are provided on a pixel defining layer of the OLED display in consideration of the shape of openings included in the pixel defining layer to reduce or minimize interference of a substrate with respect to an organic emission layer by increasing an area ratio of the spacers to the entire area.

#### BRIEF DESCRIPTION OF THE DRAWINGS

FIG. 1 partially shows a plane surface of an OLED display according to a first embodiment of the present invention.

FIG. 2 is a cross-sectional view of FIG. 1 taken along the line II-II.

FIG. 3 partially shows a plane surface of an OLED display according to a second embodiment of the present invention.

#### DETAILED DESCRIPTION

In the following detailed description, only certain embodiments of the present invention have been shown and described, simply by way of illustration. As those skilled in the art would realize, the described embodiments may be modified in various different ways, all without departing from the spirit or scope of the present invention. Accordingly, the drawings and description are to be regarded as illustrative in nature and not restrictive. Like reference numerals designate like elements throughout the specification. In addition, the size and thickness of each configuration shown in the drawings may be arbitrarily shown for better understanding and ease of description, but the present invention is not limited thereto.

In addition, unless explicitly described to the contrary, the word “comprise” and variations such as “comprises” or “comprising” will be understood to imply the inclusion of stated elements but not the exclusion of any other elements. Throughout, when a first element is described as being “coupled” to a second element, it may be directly coupled (e.g., connected) to the second element or indirectly coupled (e.g., electrically connected) to the second element via one or more third elements. Herein, the use of the term “may,” when describing embodiments of the present invention, refers to “one or more embodiments of the present invention.” In addition, the use of alternative language, such as “or,” when describing embodiments of the present invention, refers to “one or more embodiments of the present invention” for each corresponding item listed.

Hereinafter, an OLED display **1000** according to a first embodiment of the present invention will be described with reference to FIG. 1 and FIG. 2. FIG. 1 partially shows a plane surface of the OLED display **1000**. For convenience, a first electrode, a pixel defining layer, an organic emission layer, and a spacer are mainly illustrated in FIG. 1. FIG. 2 is a cross-sectional view of FIG. 1 taken along the line II-II.

As shown in FIG. 1 and FIG. 2, the OLED display **1000** includes a first substrate **SU1**, a circuit portion **PC**, a first electrode **E1**, a second electrode **E2**, a third electrode **E3**, a pixel defining layer **PDL**, a first organic emission layer **OL1**, a second organic emission layer **OL2**, a third organic emission layer **OL3**, a first spacer **SP1**, a second spacer **SP2**, a third spacer **SP3**, a fourth spacer **SP4**, a common electrode **CE**, and a second substrate **SU2**.

The first substrate **SU1** is formed of an insulating substrate made of glass, quartz, ceramic, metal, plastic, or the like. In addition, when the first substrate **SU1** is made of

plastic, the OLED display **1000** may have a flexible, stretchable, or rollable characteristic.

The circuit portion **PC** is disposed on the first substrate **SU1**, and may include wires including one or more scan lines, data lines, driving power lines, common power lines, pixel circuits, and the like. Each pixel circuit may correspond to one pixel and may include two or more thin film transistors (TFTs) coupled to the wires, one or more capacitors, and the like. The circuit portion **PC** may be formed to have various structures known to one of ordinary skill in the art.

The first electrode **E1** is positioned on the circuit part **PC**, and is coupled to one of the TFTs of the circuit part **PC**. A central area of the first electrode **E1** is positioned at a center point **CP** of a virtual tetragon, e.g., a virtual square **VS**.

Here, the virtual square **VS** includes the center point **CP**, a first vertex **P1**, a second vertex **P2**, a third vertex **P3**, a fourth vertex **P4**, a first side **V1**, a second side **V2**, a third side **V3**, and a fourth side **V4**. In further detail, the first side **V1** of the virtual square **VS** connects between the first vertex **P1** and the third vertex **P3**, the second side **V2** connects between the third vertex **P3** and the second vertex **P2**, the third side **V3** connects between the second vertex **P2** and the fourth vertex **P4**, and the fourth side **V4** connects between the fourth vertex **P4** and the first vertex **P1**. In addition, the first vertex **P1** and the second vertex **P2** of the virtual square **VS** are diagonal to each other (with the center point **CP** interposed therebetween), the third vertex **P3** and the fourth vertex **P4** are diagonal to each other (with the center point **CP** interposed therebetween), and both the third vertex **P3** and the fourth vertex **P4** neighbor both the first vertex **P1** and the second vertex **P2**.

The first side **V1**, the second side **V2**, the third side **V3**, and the fourth side **V4** have the same length such that the virtual square **VS** is formed. The first electrode **E1** may have various polygonal shapes, and a center area of the first electrode **E1** is exposed by a first opening portion (or first opening) **OM1** of the pixel defining layer **PDL**.

The second electrode **E2** is disposed on the circuit portion **PC** and is separated from the first electrode **E1**. The second electrode **E2** is coupled to a TFT of the circuit portion **PC**. Within and around the virtual square **VS**, the second electrode **E2** is provided as a pair of second electrodes **E2**, and the second electrodes **E2** are separated from each other, with the first electrode **E1** interposed therebetween. Respective center areas of the second electrodes **E2** are disposed around the first vertex **P1** and the second vertex **P2** of the virtual square **VS**. The second electrode **E2** may have various polygonal shapes, and the center area of the second electrode **E2** may be exposed by a second opening portion (or second opening) **OM2** of the pixel defining layer **PDL**.

The third electrode **E3** is separated from the first electrode **E1** and the second electrode **E2**, and is disposed on the circuit portion **PC**. The third electrode **E3** is coupled to one of the TFTs of the circuit portion **PC**. Within and around the virtual square **VS**, the third electrode **E3** is provided as a pair of third electrodes **E3**, and the third electrodes **E3** are separated from each other, with the first electrode **E1** interposed therebetween. Center regions of the respective third electrodes **E3** are disposed on the third vertex **P3** and the fourth vertex **P4** of the virtual square **VS**. The third electrode **E3** may have various polygonal shapes, and the center area of the third electrode **E3** is exposed by a third opening portion (or third opening) **OM3** of the pixel defining layer **PDL**.

The second electrodes **E2** and the third electrodes **E3** are disposed on and around the virtual square **VS**, with the first

electrode E1 interposed therebetween. That is, the second electrodes E2 and the third electrodes E3 surround the first electrode E1, centering the first electrode E1. The first electrode E1, the second electrodes E2, and the third electrodes E3 may be anodes or cathodes functioning as hole injection electrodes. The first electrode E1, the second electrodes E2, and the third electrodes E3 may be formed as light transmissive electrodes or light reflective electrodes.

The pixel defining layer PDL is disposed on the first electrode E1, the second electrode E2, and the third electrode E3, and covers the edge of each of the first electrode E1, the second electrode E2, and the third electrode E3. The pixel defining layer PDL includes the first opening portion OM1, the second opening portion OM2, and the third opening portion OM3, respectively exposing the first electrode E1, the second electrode E2, and the third electrode E3.

The first opening OM1 exposes the first electrode E1, and has a first polygonal shape, for example, an octagon. The first opening OM1 is separated from the third opening OM3 and the second opening OM2, and the center of the first opening OM1 coincides with the center point CP of the virtual square VS. The first opening OM1 has a smaller area compared to the second opening OM2 and the third opening OM3 that neighbor the first opening OM1. While the first opening OM1 in FIG. 1 is formed in the shape of an octagon, the shape of the first opening OM1 is not limited thereto. In other embodiments, the first opening OM1 may have various polygonal shapes such as a triangle, a quadrilateral, a pentagon, a hexagon, a heptagon, or the like.

While the above description focused on a single virtual square VS having a single first electrode E1, the OLED display 1000 has a plurality of virtual squares VS, each centered with a different one of a corresponding plurality of first electrodes E1 and first openings OM1. In the OLED display 1000 of FIG. 1, all neighboring (e.g., sharing a same row or column) first openings OM1 among the plurality of first openings OM1 have symmetric octagonal shapes (that are mirror images of each other), while all diagonal first openings OM1 have the same octagonal shape. In other embodiments, each of the plurality of first openings OM1 may have the same octagonal shape.

In the OLED display 1000 of FIG. 1, a first organic emission layer OL1 for emitting green light is disposed on each first electrode E1 that is exposed by its corresponding first opening OM1. In other embodiments, an organic emission layer for emitting light of various colors such as blue, red, or white may be disposed on each first electrode E1 that is exposed by its corresponding first opening OM1.

In and around the virtual square VS, the second openings OM2 expose the second electrodes E2, and have a second polygonal shape, for example, a hexagon. The second openings OM2 are separated from each of the third openings OM3 and the first opening OM1, and the centers of the second openings OM2 coincide with the first vertex P1 and the second vertex P2 of the virtual square VS. Each of the second openings OM2 has a larger area compared to each of the first opening OM1 and the third openings OM3. The second openings OM2 in FIG. 1 have a hexagonal shape, but the present invention is not limited thereto. In other embodiments, the second openings OM2 may have various polygonal shapes such as triangles, quadrilaterals, pentagons, hexagons, heptagons, octagons, or the like.

The OLED display 1000 of FIG. 1 has a plurality of second openings OM2 that have the same hexagonal shape. The plurality of second openings OM2 are separated from each other, with each pair of diagonal second openings OM2

sharing a first opening OM1 therebetween. In the OLED display 1000 of FIG. 1, second organic emission layers OL2 for emitting blue light are disposed on the second electrodes E2 that are exposed by the second openings OM2. In other embodiments, organic emission layers for emitting light of various colors such as green, red, or white may be disposed on the second electrodes E2 that are exposed by the second openings OM2.

In and around the virtual square VS, the third openings OM3 expose the third electrodes E3, and have a third polygonal shape, for example, a quadrilateral. The third openings OM3 are separated from each of the first opening OM1 and the second openings OM2, and the centers of the third openings OM3 coincide with the third vertex P3 and the fourth vertex P4 of the virtual square VS. Each of the third openings OM3 has a larger area compared to its neighboring first opening OM1 and has a smaller area compared to each of its neighboring second openings OM2. The third openings OM3 have a quadrilateral shape (in this case, a parallelogram shape), but the present invention is not limited thereto. In other embodiments, the third openings OM3 may have various polygonal shapes such as triangles, pentagons, hexagons, heptagons, octagons, or the like.

The OLED display 1000 has a plurality of third openings OM3 that have the same quadrilateral shape. The plurality of third openings OM3 are separated from each other, with each pair of diagonal third openings OM3 sharing a first opening OM1 therebetween. In the OLED display 1000 of FIG. 1, third organic emission layers OL3 for emitting red light are disposed on the third electrodes E3 exposed by the third openings OM3. In other embodiments, organic emission layers for emitting light of various colors such as blue, green, or white may be disposed on the third electrodes E3 that are exposed by the third openings OM3.

One of the shapes, such as the first polygon, the second polygon, or the third polygon of the first opening OM1, the second opening OM2, or the third opening OM3, respectively, may have an octagonal shape. In the OLED display 1000, the plurality of first openings OM1 are sequentially arranged along virtual first lines (e.g., rows or columns), and the plurality of second openings OM2 and the plurality of third openings OM3 are respectively alternately arranged on virtual second lines (e.g., rows or columns). The virtual first lines are offset by half a pixel from the virtual second lines such that within and around each virtual square VS, the second openings OM2 of which the centers coincide with the first vertex P1 and the second vertex P2 and the third openings OM3 of which the centers coincide with the third vertex P3 and the fourth vertex P4 surround the first opening OM1 of the virtual square VS.

As described, the center of the first opening OM1 coincides with the center point of the virtual square VS, the centers of the second openings OM2 coincide with the first vertex P1 and the second vertex P2, the centers of the third openings OM3 coincide with the third vertex P3 and the fourth vertex P4, and the second openings OM2 and the third openings OM3 surround the first opening OM1 of the virtual square VS. In the OLED display 1000 of FIG. 1, the first openings OM1, the second openings OM2, and the third openings OM3 respectively have the same polygonal (octagonal, hexagonal, and quadrilateral) shapes so that, within each virtual square VS, a distance between the first opening OM1 and each of the second openings OM2, and a distance between the first opening OM1 and each of the third opening OM3 is the same first length L1, and a distance between each of the second openings OM2 and each of the third openings OM3 is the same second length L2 that is different from the

first length L1. Furthermore, between neighboring virtual squares VS, a distance between respective first openings OM1 is the same third length L3 that is longer than each of the first length L1 and the second length L2.

The first organic emission layer OL1 is disposed on each of the first electrodes E1 corresponding to one of the first openings OM1. In the OLED display of FIG. 1, the first organic emission layer OL1 includes an organic material for emitting green light and thus, emits green light. In other embodiments, the first organic emission layer OL1 may include an organic material for emitting red, blue, or white light, and in this case, the first organic emission layer OL1 emits red light, blue light, or white light.

The second organic emission layer OL2 is disposed on each of the second electrodes E2 corresponding to one of the second openings OM2. In the OLED display of FIG. 1, the second organic emission layer OL2 includes an organic material for emitting blue light and thus, emits blue light. In other embodiments, the second organic emission layer OL2 may include an organic material for emitting red, green, or white light, and in this case, the second organic emission layer OL2 emits red light, green light, or white light.

The third organic emission layer OL3 is disposed on each of the third electrodes E3 corresponding to one of the third openings OM3. In the OLED display of FIG. 1, the third organic emission layer OL3 includes an organic material for emitting red light and thus, emits red light. In other embodiments, the third organic emission layer OL3 may include an organic material for emitting blue, green, or white light, and in this case, the third organic emission layer OL3 emits blue light, green light, or white light.

Thus, in the OLED display of FIG. 1, the first organic emission layer OL1, the second organic emission layer OL2, and the third organic emission layer OL3 respectively emit light of different colors (green, blue, and red, respectively). In other embodiments, the first organic emission layer OL1, the second organic emission layer OL2, and the third organic emission layer OL3 may emit light of the same color (such as white).

The first spacer SP1 is disposed between the first vertex P1 and the third vertex P3 corresponding to the first side V1 among the four sides of the virtual square VS. The first spacer SP1 is disposed as an island between the corresponding second opening OM2 and third opening OM3, and has a first center C1, which is the center of the first spacer SP1, that coincides with the first side V1. The first spacer SP1 is formed in the shape of a rectangle having long sides bisected by the first side V1 through the first center C1.

The second spacer SP2 is disposed between the third vertex P3 and the second vertex P2 corresponding to the second side V2 among the four sides of the virtual square VS. The second spacer SP2 is disposed as an island between the corresponding third opening OM3 and second opening OM2, and has a second center C2, which is the center of the second spacer SP2, that coincides with the second side V2 of the second center C2. The second spacer SP2 is formed in the shape of a rectangle having long sides bisected by the second side V2 through the second center C2.

The third spacer SP3 is disposed between the second vertex P2 and the fourth vertex P4 corresponding to the third side V3 among the four sides of the virtual square VS. The third spacer SP3 is disposed as an island between the corresponding second opening OM2 and third opening OM3, and has a third center C3, which is the center of the third spacer SP3, that coincides with the third side V3. The

third spacer SP3 is formed in the shape of a rectangle having long sides bisected by the third side V3 through the third center C3.

The fourth spacer SP4 is disposed between the fourth vertex P4 and the first vertex P1 corresponding to the fourth side V4 among the four sides of the virtual square VS. The fourth spacer SP4 is disposed as an island between the corresponding third opening OM3 and second opening OM2, and has a fourth center C4, which is the center of the fourth spacer SP4, that coincides with the fourth side V4. The fourth spacer SP4 is formed in the shape of a rectangle having long sides bisected by the fourth side V4 through the fourth center C4.

As described, the first spacer SP1, the second spacer SP2, the third spacer SP3, and the fourth spacer SP4 are respectively disposed as islands corresponding to the four sides, that is, the first side V1, the second side V2, the third side V3, and the fourth side V4 of the virtual square VS, and are also formed in the shape of rectangles respectively having long sides bisected respectively by the first side V1, the second side V2, the third side V3, and the fourth side V4 through the first center C1, the second center C2, the third center C3, and the fourth center C4, so that the area ratio occupied by the first spacers SP1, the second spacers SP2, the third spacers SP3, and the fourth spacers SP4 in the entire area of the OLED display 1000 can be increased without interfering with the distances respectively set between the first openings OM1, the second openings OM2, and the third openings OM3.

The first spacer SP1, the second spacer SP2, the third spacer SP3, and the fourth spacer SP4 may be formed of the same or different material of the pixel defining layer PDL, and may include at least one of an organic material, an inorganic material, a metal, glass, or the like.

As described, within each virtual square VS, the centers C1, C2, C3, and C4 of each of the first spacer SP1, the second spacer SP2, the third spacer SP3, and the fourth spacer SP4 that neighbor the center point CP of the virtual square VS coincide with a respective one of the first side V1, the second side V2, the third side V3, and the fourth side V4 so that distances between the respective centers C1, C2, C3, and C4 of the first spacer SP1, the second spacer SP2, the third spacer SP3, and the fourth spacer SP4, and the center point CP of the virtual square VS have the same length D.

In FIG. 1, the first spacer SP1, the second spacer SP2, the third spacer SP3, and the fourth spacer SP4 have rectangular shapes, but in other embodiments, they may have other polygonal shapes such as triangles, other quadrilaterals, pentagons, hexagons, heptagons, octagons, nonagons, or the like, or closed loop shapes formed by extension of a curved line.

The common electrode CE is disposed on the first organic emission layers OL1, the second organic emission layers OL2, and the third organic emission layers OL3 throughout the entire surface of the first substrate SU1, and may be a cathode functioning as an electron injection electrode, or an anode. The common electrode CE may be formed as a light transmissive electrode or a light reflective electrode.

In FIG. 2, the common electrode CE is disposed on the first spacer SP1. In another embodiment of the present invention, the common electrode CE may be disposed between the pixel defining layer PDL and the first spacer SP1.

The second substrate SU2 is formed of an insulating substrate made of glass, quartz, ceramic, metal, plastic, or the like. In addition, when the second substrate SU2 and the

first substrate SU1 are made of plastic, the OLED display may have a flexible, stretchable, or rollable characteristic.

As described above, in the OLED display 1000, within each virtual square VS, gaps of the first length L1 are formed between the first opening OM1 and each of the second openings OM2, and between the first opening OM1 and each of the third openings OM3. In addition, between neighboring virtual squares VS, gaps of the third length L3 that are longer than the first length L1 are formed between the neighboring first openings OM1 so that deposition reliability in a deposition process that uses fine metal masks that form the green organic emission layer, the blue organic emission layer, and the red organic emission layer respectively included in the first opening OM1, the second opening OM2, and the third opening OM3 can be improved. That is, deposition reliability of the OLED display 1000 can be improved.

In addition, in the OLED display 1000, within and around each virtual square VS, the second openings OM2 and the third openings OM3 are alternately arranged to surround the first opening OM1 so that an aperture ratio of each of the first opening OM1, the second openings OM2, and the third openings OM3 can be improved. Accordingly, manufacturing time and manufacturing cost of the OLED display can be reduced and quality of an image displayed by the OLED display can be improved. That is, image quality of the OLED display 1000 can be improved.

Further, in the OLED display 1000, the second openings OM2 for emitting blue light have corresponding second organic emission layers OL2 that have a shorter life span compared to those of other color pixels. Accordingly, each second opening OM2 has a larger area compared to those of the first opening OM1 and the third opening OM3 so that deterioration of the life span of the whole OLED display can be suppressed. That is, the life span of the OLED display 1000 can be improved.

As described above, in the OLED display 1000, the first opening OM1, the second opening OM2, and the third opening OM3 have polygonal shapes such as an octagon, a hexagon, a quadrilateral, or the like. Within or around each virtual square VS, the center of the first opening OM1 coincides with the center point CP of the virtual square VS, the centers of the second openings OM2 respectively coincide with the first vertex P1 and the second vertex P2, and the centers of the third openings OM3 respectively coincide with the third vertex P3 and the fourth vertex P4 to improve deposition reliability of the organic emission layer and also improve an aperture ratio of each of the first, second, and third openings OM1, OM2, and OM3 during the deposition process using the fine metal masks in consideration of a deposition process of the organic emission layer, which is another manufacturing feature of the OLED display 1000.

That is, the OLED display 1000 including the octagon-shaped first, hexagon-shaped second, and quadrilateral-shaped third openings OM1, OM2, and OM3 can be provided, and, in the OLED display 1000, deposition reliability of the organic emission layers can be improved, the life span of the organic emission layers can be improved, and the aperture ratio of each of the first openings OM1, the second openings OM2, and the third openings OM3 can be improved.

Further, in the OLED display 1000, within and around each virtual square VS, the first spacer SP1, the second spacer SP2, the third spacer SP3, and the fourth spacer SP4 are disposed as islands respectively corresponding to the first side V1, the second side V2, the third side V3, and the fourth side V4 in consideration of the shapes of the first,

second, and third openings OM1, OM2, and OM3 such that the first, second, third, and fourth spacers SP1, SP2, SP3, and SP4 of which centers have the same distance D to the center point CP to which the center of the first opening OM1 coincides. Thus, the first, second, third, and fourth spacers SP1, SP2, SP3, and SP4 do not interfere with distances set between the first, second, and third openings OM1, OM2, and OM3 and also maintain a consistent ratio of the area occupied by the first, second, third, and fourth spacers SP1, SP2, SP3, and SP4 when the entire area of the OLED display 1000 is increased. Accordingly, interference of the second substrate SU2 with respect to the first organic emission layers OL1, the second organic emission layers OL2, and the third organic emission layers OL3 can be reduced or minimized, regardless of how many virtual squares VS make up the OLED display 1000.

As described, the OLED display 1000 includes the octagonal-shaped first opening OM1, the hexagonal-shaped second opening OM2, and the quadrilateral-shaped third opening OM3 in consideration of improvement of deposition reliability of the organic emission layers, improvement of life span of the organic emission layers, and improvement of the aperture ratio of each of the first, second, and third openings OM1, OM2, and OM3, and also includes the first spacer SP1, the second spacer SP2, the third spacer SP3, and the fourth spacer SP4 in consideration of the shapes of the first opening OM1, the second opening OM2, and the third opening OM3 so that the deposition reliability and life span of the organic emission layers can be improved, the aperture ratio of each of the first, second, and third openings OM1, OM2, and OM3 can be improved, and the entire mechanical reliability can be improved.

Hereinafter, an OLED display 1002 according to a second embodiment of the present invention will be described with reference to FIG. 3. For convenience of description, only features distinguished from those of the first embodiment above may be extracted and described, and portions for which the description is omitted follow the first embodiment. In addition, the same constituent elements of both embodiments will be described by using the same reference numerals as the first embodiment.

FIG. 3 partially shows a plane surface of the OLED display 1002. As shown in FIG. 3, an OLED display 1002 includes a first spacer SP1, a second spacer SP2, a third spacer SP3, and a fourth spacer SP4, and they are respectively formed in the shape of a square.

The first spacer SP1, the second spacer SP2, the third spacer SP3, and the fourth spacer SP4 are respectively disposed as islands on a pixel defining layer PDL corresponding to four sides, namely a first side V1, a second side V2, a third side V3, and a fourth side V4, of a virtual square VS. In addition, the centers of the first to fourth spacers SP1 to SP4 respectively coincide with the first side V1, the second side V2, the third side V3, and the fourth side V4.

As described, the OLED display 1002 includes a first opening OM1, a second opening OM2, and a third opening OM3 respectively formed in the shape of an octagon, a hexagon, and a quadrilateral in consideration of improvement in deposition reliability of organic emission layers, improvement in life span of the organic emission layers, and improvement in aperture ratios of the first, second, and third openings OM1, OM2, and OM3, and also includes a first spacer SP1, a second spacer SP2, a third spacer SP3, and a fourth spacer SP4 in consideration of the shapes of the first, second, and third openings OM1, OM2, and OM3 such that the deposition reliability of the organic emission layers can be improved, the life span of the organic emission layers can

be improved, and the entire mechanical reliability of the OLED display 1002 can be improved.

While the present invention has been described in connection with what is presently considered to be practical embodiments, it is to be understood that the invention is not limited to the disclosed embodiments, but, on the contrary, is intended to cover various modifications and equivalent arrangements included within the spirit and scope of the appended claims, and their equivalents.

#### DESCRIPTION OF SOME SYMBOLS

first electrode E1  
second electrode E2  
third electrode E3  
pixel defining layer PDL  
spacer SP1, SP2, SP3, SP4

What is claimed is:

1. An organic light emitting diode (OLED) display comprising:

a first electrode around a center point of a virtual tetragon; four second electrodes each around a different one of four vertices of the virtual tetragon, the second electrodes being separated from each other and from the first electrode;

a pixel defining layer partially on the first electrode and the second electrodes, and including a first opening partially overlapping the first electrode and four second openings each partially overlapping a different one of the four second electrodes; and

four spacers on the pixel defining layer each corresponding to a different one of four sides of the virtual tetragon, the spacers being separated from each other, wherein two of the second openings are different from each other in area.

2. The OLED display of claim 1, wherein the first opening has a first polygon shape whose center coincides with the center point of the virtual tetragon, and

the second openings have polygonal shapes whose centers coincide with the vertices of the virtual tetragon.

3. The OLED display of claim 2, wherein the first opening has an octagonal shape.

4. The OLED display of claim 3, wherein a plane area of the first opening is smaller than a plane area of each of the second openings.

5. The OLED display of claim 2, wherein distances between the center point of the virtual tetragon and centers of the four spacers are the same.

6. The OLED display of claim 5, wherein each of the spacers has a quadrilateral shape.

7. The OLED display of claim 2, wherein the first polygonal shape is an octagon and the polygonal shapes of the second electrodes include a hexagon and a quadrilateral.

8. The OLED display of claim 7, wherein distances between the first opening and each of the four second openings are a same first length.

9. The OLED display of claim 8, wherein distances between each of adjacent ones of the four second openings are a same second length.

10. The OLED display of claim 2, further comprising:

a first organic emission layer on the first electrode corresponding to the first opening; and second organic emission layers on the second electrodes and corresponding to the second openings.

11. The OLED display of claim 10, wherein the first organic emission layer emits a first color light, and

the second organic emission layers emit a second color light different from the first color light, and a third color light different from the first color light and the second color light, and

wherein the first color light is green, and the second color light and the third color light are blue and red.

12. The OLED display of claim 1, wherein the first opening has an octagonal shape.

13. The OLED display of claim 12, wherein a plane area of the first opening is smaller than a plane area of each of the second openings.

14. The OLED display of claim 13, wherein each of the second electrodes has a hexagon or a quadrilateral.

15. The OLED display of claim 13, wherein distances between the center point of the virtual tetragon and centers of the four spacers are the same.

16. The OLED display of claim 1, wherein each of the spacers has a quadrilateral shape.

17. The OLED display of claim 16, wherein distances between the first opening and each of the four second openings are a same first length, and wherein distances between each of adjacent ones of the four second openings are a same second length.

18. The OLED display of claim 17, further comprising:

a first organic emission layer on the first electrode corresponding to the first opening; and second organic emission layers on the second electrodes and corresponding to the second openings, and

wherein the first organic emission layer is configured to emit a first color light, and the second organic emission layers are configured to emit a second color light different from the first color light, and a third color light different from the first color light and the second color light, and

wherein the first color light is green, and the second color light and the third color light are blue and red.

19. An organic light emitting diode (OLED) display comprising:

a first electrode around a center point of a virtual tetragon; four second electrodes each around a different one of four vertices of the virtual tetragon, the second electrodes being separated from each other and from the first electrode;

a pixel defining layer partially on the first electrode and the second electrodes, and including a first opening partially overlapping the first electrode and four second openings each partially overlapping a different one of the four second electrodes; and

four spacers on the pixel defining layer each corresponding to a different one of four sides of the virtual tetragon, the spacers being separated from each other, wherein a plane area of the first opening is smaller than a plane area of each of the second openings.

20. An organic light emitting diode (OLED) display comprising:

a first electrode around a center point of a virtual tetragon; four second electrodes each around a different one of four vertices of the virtual tetragon, the second electrodes being separated from each other and from the first electrode;

a pixel defining layer partially on the first electrode and the second electrodes, and including a first opening

partially overlapping the first electrode and four second openings each partially overlapping a different one of the four second electrodes; and  
four spacers on the pixel defining layer each corresponding to a different one of four sides of the virtual tetragon, the spacers being separated from each other, wherein the first opening has an octagonal shape.

\* \* \* \* \*

专利名称(译)	有机发光二极管显示器		
公开(公告)号	<a href="#">US10347703</a>	公开(公告)日	2019-07-09
申请号	US15/688760	申请日	2017-08-28
[标]申请(专利权)人(译)	三星显示有限公司		
申请(专利权)人(译)	三星DISPLAY CO. , LTD.		
当前申请(专利权)人(译)	三星DISPLAY CO. , LTD.		
[标]发明人	PARK OK KYUNG YUN SU YEON		
发明人	PARK, OK-KYUNG YUN, SU YEON		
IPC分类号	H01L27/32 H01L51/52 G02F1/1362		
CPC分类号	H01L27/3262 H01L27/3216 H01L27/3218 H01L27/3276 H01L51/525 H01L27/3246 G02F1/1362 G09G3/3208 G09G2300/0452 H01L51/5036 H01L51/504 H01L51/5203		
优先权	1020130046996 2013-04-26 KR		
其他公开文献	US20170358640A1		
外部链接	<a href="#">Espacenet</a>		

摘要(译)

有机发光二极管 ( OLED ) 显示器包括：围绕虚拟四边形的中心点的第一电极，例如虚拟方形；第二电极围绕第一顶点和与虚拟正方形的第一顶点对角的第二顶点，第二电极彼此分开并且虚拟正方形的中心点插入其间；第三电极围绕虚拟正方形的第三顶点和第四顶点，第三电极彼此分开并且虚拟正方形的中心点插入其间；像素限定层部分地位于第一电极，第二电极和第三电极上，并且部分地暴露第一电极，第二电极和第三电极；四个间隔物在像素限定层上设置为岛状，并对应于虚拟方形的四个边。

