

US010483336B2

(12) **United States Patent**
Lee et al.

(10) **Patent No.:** **US 10,483,336 B2**
(45) **Date of Patent:** **Nov. 19, 2019**

(54) **ORGANIC LIGHT EMITTING DISPLAY APPARATUS**

(71) Applicant: **LG Display Co., Ltd.**, Seoul (KR)

(72) Inventors: **Joonsuk Lee**, Seoul (KR); **Se June Kim**, Gyeonggi-do (KR)

(73) Assignee: **LG Display Co., Ltd.**, Seoul (KR)

(*) Notice: Subject to any disclaimer, the term of this patent is extended or adjusted under 35 U.S.C. 154(b) by 0 days.

(21) Appl. No.: **15/928,808**

(22) Filed: **Mar. 22, 2018**

(65) **Prior Publication Data**

US 2018/0212007 A1 Jul. 26, 2018

Related U.S. Application Data

(63) Continuation of application No. 14/983,899, filed on Dec. 30, 2015, now Pat. No. 9,960,216.

(30) **Foreign Application Priority Data**

May 29, 2015 (KR) 10-2015-0076678

(51) **Int. Cl.**
H01L 27/32 (2006.01)
H01L 51/52 (2006.01)

(52) **U.S. Cl.**
CPC **H01L 27/3246** (2013.01); **H01L 27/3276** (2013.01); **H01L 51/5212** (2013.01); **H01L 51/5228** (2013.01); **H01L 2251/5315** (2013.01)

(58) **Field of Classification Search**
CPC H01L 27/3246; H01L 51/5212; H01L 51/5228

See application file for complete search history.

(56) **References Cited**

U.S. PATENT DOCUMENTS

2003/0201716 A1* 10/2003 Yamazaki H01L 27/322 313/506

2004/0263056 A1* 12/2004 Seo G09G 3/3216 313/500

(Continued)

FOREIGN PATENT DOCUMENTS

CN 103066212 A 4/2013
CN 104124259 A 10/2014

(Continued)

OTHER PUBLICATIONS

First Notification of Office Action dated Jul. 9, 2018, from The State Intellectual Property Office of China in corresponding application No. 201510689725.0.

Primary Examiner — Kyoung Lee


Assistant Examiner — Christina A Sylvia

(74) *Attorney, Agent, or Firm* — Morgan, Lewis & Bockius LLP

(57) **ABSTRACT**

An organic light emitting display apparatus includes a substrate; an anode electrode on the substrate; an auxiliary electrode on the substrate; an organic emission layer on the anode electrode; a cathode electrode on the organic emission layer and on the auxiliary electrode; an insulating bank on the auxiliary electrode, the bank overlapping a first portion of the auxiliary electrode and exposing a second portion of the auxiliary electrode; a first partition wall on the auxiliary electrode; a second partition wall on the first partition wall and covering the exposed second portion of the auxiliary electrode in plan view. A separation space is between the second partition wall and the bank, the cathode electrode is electrically connected to the auxiliary electrode through the separation space between the second partition wall and the bank, and the second partition wall is supported by the first partition wall and the bank.

19 Claims, 6 Drawing Sheets



(56)

References Cited

U.S. PATENT DOCUMENTS

2007/0194307 A1 8/2007 Kim et al.
2009/0009069 A1 1/2009 Takata
2010/0232465 A1* 9/2010 Tsukiji H01S 5/0425
372/45.01
2013/0056784 A1 3/2013 Lee et al.
2013/0069067 A1 3/2013 Youn
2013/0099218 A1 4/2013 Lee et al.
2014/0183479 A1 7/2014 Park et al.
2014/0183501 A1* 7/2014 Kim H01L 27/3246
257/40
2014/0312323 A1 10/2014 Park et al.
2015/0001507 A1 1/2015 Kim et al.
2015/0188077 A1 7/2015 Kim et al.
2016/0149156 A1* 5/2016 Kim H01L 51/5228
257/40

FOREIGN PATENT DOCUMENTS

CN 104253144 A 12/2014
EP 2 827 371 A1 1/2015

* cited by examiner

FIG. 1
(RELATED ART)




FIG. 2




FIG. 3




FIG. 4




FIG. 5




FIG. 6A




FIG. 6B





FIG. 6C



ORGANIC LIGHT EMITTING DISPLAY APPARATUS

CROSS-REFERENCE TO RELATED APPLICATIONS

This is a continuation application of U.S. Application Ser. No. 14/983,899, filed Dec. 30, 2015, and also claims priority from Korean Patent Application No. 10-2015-0076678, filed on May 29, 2015, both of which are hereby incorporated by reference as if fully set forth herein.

BACKGROUND

Field of the Disclosure

The present disclosure relates to an organic light emitting display apparatus, and more particularly, to a top emission type organic light emitting display apparatus.

Discussion of the Related Art

Organic light emitting display apparatuses are self-emitting apparatuses and typically have low power consumption, a fast response time, high emission efficiency, high luminance, and a wide viewing angle.

The organic light emitting display apparatuses are typically classified into a top emission type and a bottom emission type, based on a transmission direction of light emitted from an organic light emitting device. In the bottom emission type, a circuit element is disposed between an emission layer and an image displaying surface, and for this reason, an aperture ratio is lowered. On the other hand, in the top emission type, the circuit element is not disposed between the emission layer and the image displaying surface, and thus, an aperture ratio is enhanced.

FIG. 1 is a cross-sectional view of a related art top emission type organic light emitting display apparatus.

As seen in FIG. 1, a thin film transistor (TFT) T, which includes an active layer 11, a gate insulation layer 12, a gate electrode 13, an interlayer dielectric 14, a source electrode 15, and a drain electrode 16, is formed on a substrate 10, and a passivation layer 20 and a planarization layer 30 are sequentially formed on the TFT T.

An anode electrode 40 and an auxiliary electrode 50 are formed on the planarization layer 30. The auxiliary electrode 50 decreases a resistance of a cathode electrode 80 as will be described below.

A bank 60 is formed on the anode electrode 40 and the auxiliary electrode 50 and defines a pixel area by its absence. An organic emission layer 70 is formed in the pixel area defined by the bank 60, and the cathode electrode 80 is formed on the organic emission layer 70.

In the top emission type, light emitted from the organic emission layer 70 passes through the cathode electrode 80 and travels. Therefore, the cathode electrode 80 is formed of a transparent conductive material, but for this reason, a resistance of the cathode electrode 80 typically is increased. To decrease the resistance of the cathode electrode 80, the cathode electrode 80 is connected to the auxiliary electrode 50.

The related art top emission type organic light emitting display apparatus may have at least the following problems.

The related art organic light emitting display apparatus is an organic light emitting display apparatus to which a top emission type is applied, and has a drawback where it is difficult to deposit the organic emission layer 70. For example, in the related art organic light emitting display apparatus, an additional process may be needed to deposit the organic emission layer 70 on only the anode electrode

40. Also, in a case of blanket-depositing the organic emission layer 70, the auxiliary electrode 50 cannot be connected to the cathode electrode 80. Furthermore, because the organic emission layer 70 is not patterned to be separated in each of a plurality of pixels, defective driving can occur.

SUMMARY

Accordingly, the present disclosure is directed to providing an organic light emitting display apparatus that substantially obviates one or more problems due to limitations and disadvantages of the related art.

To achieve these and other advantages and in accordance with the purpose of the invention, as embodied and broadly described herein, there is provided an organic light emitting display apparatus, comprising a substrate; an anode electrode on the substrate; an auxiliary electrode on the substrate; an organic emission layer on the anode electrode; a cathode electrode on the organic emission layer and on the auxiliary electrode; an insulating bank on the auxiliary electrode, the bank overlapping a first portion of the auxiliary electrode and exposing a second portion of the auxiliary electrode; a first partition wall on the auxiliary electrode; a second partition wall on the first partition wall and covering the exposed second portion of the auxiliary electrode in plan view, wherein a separation space is between the second partition wall and the bank; the cathode electrode is electrically connected to the auxiliary electrode through the separation space between the second partition wall and the bank; and the second partition wall is supported by the first partition wall and the bank.

Additional advantages and features of the invention will be set forth in part in the description which follows and in part will become apparent to those having ordinary skill in the art upon examination of the following or may be learned from practice of the invention. The objectives and other advantages of the invention may be realized and attained by the structure particularly pointed out in the written description and claims hereof as well as the appended drawings.

It is to be understood that both the foregoing general description and the following detailed description of the present disclosure are exemplary and explanatory and are intended to provide further explanation of the invention as claimed.

BRIEF DESCRIPTION OF THE DRAWINGS

The accompanying drawings, which are included to provide a further understanding of the invention and are incorporated in and constitute a part of this application, illustrate embodiments of the invention and together with the description serve to explain the principles of embodiments of the invention. In the drawings:

FIG. 1 is a cross-sectional view of a related art top emission type organic light emitting display apparatus;

FIG. 2 is a cross-sectional view of an organic light emitting display apparatus according to an example embodiment of the present invention;

FIG. 3 is a plan view of an organic light emitting display apparatus according to an example embodiment of the present invention;

FIG. 4 is a plan view of an organic light emitting display apparatus according to another example embodiment of the present invention;

FIG. 5 is a plan view of an organic light emitting display apparatus according to another example embodiment of the present invention;

FIGS. 6A to 6C are cross-sectional views of an organic light emitting display apparatus according to another example embodiment of the present invention;

FIG. 7 is a cross-sectional view of an organic light emitting display apparatus according to another example embodiment of the present invention; and

FIG. 8 is a cross-sectional view of an organic light emitting display apparatus according to another example embodiment of the present invention.

DETAILED DESCRIPTION OF THE ILLUSTRATED INVENTION

Reference will now be made in detail to example embodiments of the present invention, examples of which are illustrated in the accompanying drawings. Where possible, the same reference numbers may be used throughout the drawings to refer to the same or like parts.

Advantages and features of embodiments of the present invention, and implementation methods thereof, will be described through the following with reference to the accompanying drawings. The present invention may, however, be embodied in different forms and should not be construed as limited to the embodiments set forth herein. Rather, these embodiments are provided so that this disclosure will be thorough and complete, and will fully convey the scope of the present invention to those skilled in the art.

A shape, a size, a ratio, an angle, and a number disclosed in the drawings for describing embodiments of the present invention are merely an example, and thus, the present invention is not limited to the illustrated details. In the following description, when the detailed description of the relevant known function or configuration is determined to unnecessarily obscure the disclosure, detailed description may be omitted.

Features of various embodiments of the present invention may be partially or overall coupled to or combined with each other, and may be variously inter-operated with each other and driven technically as those skilled in the art can sufficiently understand. The embodiments of the present invention may be carried out independently from each other, or may be carried out together in co-dependent relationship.

Hereinafter, example embodiments of the present invention will be described in detail with reference to the accompanying drawings.

FIG. 2 is a cross-sectional view of an organic light emitting display apparatus according to an example embodiment of the present invention.

As seen in FIG. 2, a thin film transistor (TFT) T, an auxiliary line 300, a passivation layer 165, a planarization layer 170, an anode electrode 180, an auxiliary electrode 190, a bank 220, a partition wall 230, an organic emission layer 240, and a cathode electrode 250 may be formed on a substrate 100.

The TFT T may include an active layer 110, a gate insulation layer 120, a gate electrode 130, an interlayer dielectric 140, a source electrode 150, and a drain electrode 160.

The active layer 110 may be formed on the substrate 100. The active layer 110 may be formed of a silicon-based semiconductor material, or may be formed of an oxide-based semiconductor material. Although not shown, a light shielding layer may be further formed between the substrate 100 and the active layer 110, and in this case, external light incident through a bottom of the substrate 100 is blocked by the light shielding layer, thereby preventing the active layer 110 from being damaged by external light.

The gate insulation layer 120 may be formed on the active layer 110. The gate insulation layer 120 may insulate the active layer 110 from the gate electrode 130. The gate insulation layer 120 may be formed of an inorganic insulating material, for example, silicon oxide (SiO_x), silicon nitride (SiN_x), or a multilayer thereof, but is not limited thereto.

The gate electrode 130 may be formed on the gate insulation layer 120. The gate electrode 130 may be formed to overlap the active layer 110 with the gate insulation layer 120 therebetween. The gate electrode 130 may be formed of a single layer or a multilayer formed of one of molybdenum (Mo), aluminum (Al), chromium (Cr), gold (Au), titanium (Ti), nickel (Ni), neodymium (Nd), copper (Cu), or an alloy thereof, but is not limited thereto.

The interlayer dielectric 140 may be formed on the gate electrode 130. The interlayer dielectric 140 may be formed of the same inorganic insulating material as that of the gate insulation layer 120, for example, silicon oxide (SiO_x), silicon nitride (SiN_x), or a multilayer thereof, but is not limited thereto.

The source electrode 150 and the drain electrode 160 may be formed to face each other on the interlayer dielectric 140. A first contact hole CH1 exposing one end region of the active layer 110 and a second contact hole CH2 exposing the other end region of the active layer 110 may be included in the gate insulation layer 120 and the interlayer dielectric 140. The source electrode 150 may be connected to the other end region of the active layer 110 through the second contact hole CH2, and the drain electrode 160 may be connected to the one end region of the active layer 110 through the first contact hole CH1.

A structure of the TFT T is not limited to the illustrated structure, and may be variously modified to structures known to those skilled in the art. For example, a top gate structure where the gate electrode 130 is formed on the active layer 110 is illustrated in the drawing, but the TFT T may be formed in a bottom gate structure where the gate electrode 130 is formed under the active layer 110.

The auxiliary line 300 may be disposed on the same layer as a layer on which the source electrode 150 and the drain electrode 160 are disposed (e.g., on interlayer dielectric 140), and may be disposed to be separated from the source electrode 150 and the drain electrode 160. The auxiliary line 300 may be formed through the same process simultaneously with the source electrode 150 and the drain electrode 160, and may be formed of the same material as that of the source electrode 150 and the drain electrode 160. The auxiliary line 300 may be connected to the below-described auxiliary electrode 190 through a fourth contact hole CH4. Because the auxiliary line 300 is connected to the auxiliary electrode 190 through the fourth contact hole CH4, resistances of the auxiliary electrode 190 and the cathode electrode 250 may be lowered.

The passivation layer 165 may be formed on the TFT T, and in more detail, may be formed on tops of the source electrode 150, the drain electrode 160, and the auxiliary line 300. The passivation layer 165 protects the TFT T. The passivation layer 165 may be formed of an inorganic insulating material (for example, SiO_x and SiN_x), but is not limited thereto.

The planarization layer 170 may be formed on the passivation layer 165. The planarization layer 170 may planarize an upper surface of the substrate 100 including the TFT T. The planarization layer 170 may be formed of an

organic insulating material such as acryl resin, epoxy resin, phenolic resin, polyamide resin, polyimide resin, or the like, but is not limited thereto.

The anode electrode **180** and the auxiliary electrode **190** may be formed on the planarization layer **170**. That is, the anode electrode **180** and the auxiliary electrode **190** may be formed on the same layer. A third contact hole CH3 exposing the source electrode **150** may be included in the passivation layer **165** and the planarization layer **170**, and the source electrode **150** may be connected to the anode electrode **180** through the third contact hole CH3. Also, the fourth contact hole CH4 exposing the auxiliary line **300** may be included in the passivation layer **165** and the planarization layer **170**, and the auxiliary line **300** may be connected to the auxiliary electrode **190** through the fourth contact hole CH4.

The bank **220** may be formed on the anode electrode **180** and the auxiliary electrode **190**. The bank **220** may be formed on one side and the other side of the anode electrode **180** (e.g., opposite sides) to leave tops of the anode electrode **180** and the auxiliary electrode **190** exposed, and to cover side surfaces of the anode electrode **180** and the auxiliary electrode **190**. Because the bank **220** is formed to expose the top of the anode electrode **180**, an area where an image is displayed is secured. Also, because the bank **220** is formed to expose the tops of the anode electrode **180** and the auxiliary electrode **190**, an electrical connection space between the auxiliary electrode **190** and the cathode electrode **250** is made available.

Moreover, the bank **220** may be formed between the anode electrode **180** and the auxiliary electrode **190**, and may insulate the anode electrode **180** from the auxiliary electrode **190**. The bank **220** may be formed of an organic insulating material such as polyimide resin, acryl resin, benzocyclobutene (BCB), or the like, but is not limited thereto.

The partition wall **230** may be formed on the auxiliary electrode **190**. The partition wall **230** may be separated from the bank **220** by a certain distance, and the auxiliary electrode **190** may be electrically connected to the cathode electrode **250** through a separation space between the partition wall **230** and the bank **220**.

In a related art organic light emitting display apparatus, an auxiliary electrode is electrically connected to a cathode electrode without forming a partition wall. On the other hand, according to an example embodiment of the present invention, the partition wall **230** is formed, and thus, the organic emission layer **240** is more easily deposited. This will be described below in detail.

If the partition wall **230** is not formed, a mask pattern, which covers a top of the auxiliary electrode **190**, is needed in depositing the organic emission layer **240**, in order for the top of the auxiliary electrode **190** not to be covered by the organic emission layer **240**. However, if the partition wall **230** is formed, a top of the partition wall **230** may act as eaves in depositing the organic emission layer **240**. Thus, because the organic emission layer **240** is not deposited under the eaves, the mask pattern which covers the top of the auxiliary electrode **190** is not needed. That is, with respect to a case where the organic light emitting display apparatus is seen from the front thereof, when the top of the partition wall **230** that acts as eaves is formed to cover a separation space between the partition wall **230** and the bank **220**, the organic emission layer **240** may not penetrate into the separation space between the partition wall **230** and the bank **220**, and thus, the auxiliary electrode **190** may be exposed in the separation space between the partition wall **230** and the bank **220**. For example, the organic emission layer **240** may

be formed by a deposition process, such as an evaporation process, which is excellent in straightness of a deposited material, and thus, the organic emission layer **240** cannot be deposited in the separation space between the partition wall **230** and the bank **220**.

As described above, a width of the top of the partition wall **230** may be formed greater than that of a bottom of the partition wall **230**, in order for the top of the partition wall **230** to act as the eaves. The partition wall **230** may include a lower first partition wall **231** and an upper second partition wall **232**. The first partition wall **231** may be formed on a top of the auxiliary electrode **190** and may be formed of the same material as that of the bank **220** through the same process as that of the bank **220**. The second partition wall **232** may be formed on a top of the first partition wall **231**. A width of a top of the second partition wall **232** may be formed greater than that of a bottom of the second partition wall **232**, and particularly, the top of the second partition wall **232** may be formed to cover the separation space between the partition wall **230** and the bank **220** and may act as eaves.

In this case, the first partition wall **231** may be formed not to overlap the fourth contact hole CH4 that connects the auxiliary electrode **190** to the auxiliary line **300**. When the fourth contact hole CH4 and the first partition wall **231** are formed to overlap each other, the auxiliary electrode **190** formed under the first partition wall **231** may not uniformly be formed due to the fourth contact hole CH4, and for this reason, the first partition wall **231** may not be uniformly formed. When the first partition wall **231** is not uniformly formed, the second partition wall **232** formed on the first partition wall **231** may be inclined, and the organic emission layer **240** may be formed on the auxiliary electrode **190**, thereby causing a defect where the cathode electrode **250** may not be connected to the auxiliary electrode **190**.

The organic emission layer **240** may be formed on the anode electrode **180**. The organic emission layer **240** may include a hole injection layer, a hole transport layer, an emission layer, an electron transport layer, and an electron injection layer. The organic emission layer **240** may be modified to have various structures known to those skilled in the art.

The organic emission layer **240** may extend to the top of the bank **220**. However, the organic emission layer **240** may not extend to the top of the auxiliary electrode **190** and cover the top of the auxiliary electrode **190**. This is because when the organic emission layer **240** covers the top of the auxiliary electrode **190**, it may be difficult to electrically connect the auxiliary electrode **190** to the cathode electrode **250**. As described above, the organic emission layer **240** may be formed by a deposition process without a mask that covers the top of the auxiliary electrode **190**, and in this case, the organic emission layer **240** may be formed on the top of the partition wall **230**.

The cathode electrode **250** may be formed on the organic emission layer **240**. The cathode electrode **250** may be formed on a surface from which light is emitted, and thus may be formed of a transparent conductive material. Because the cathode electrode **250** is formed of a transparent conductive material, a resistance of the cathode electrode **250** is high, and for this reason, in order to lower the resistance of the cathode electrode **250**, the cathode electrode **250** may be connected to the auxiliary electrode **190**. That is, the cathode electrode **250** may be connected to the auxiliary electrode **190** through the separation space between the partition wall **230** and the bank **220**. The cathode electrode **250** may be formed by a deposition

process, such as a sputtering process, which is not good in straightness of a deposited material. Thus, the cathode electrode 250 may be deposited in the separation space between the partition wall 230 and the bank 220 in a process of depositing the cathode electrode 250.

Although not shown, an encapsulation layer may be further formed on the cathode electrode 250 and prevents penetration of water. The encapsulation layer may use various materials known to those skilled in the art. Also, although not shown, a color filter may be further formed for each pixel and on the cathode electrode 250, and in this case, white light may be emitted from the organic emission layer 240.

FIG. 3 is a plan view of an organic light emitting display apparatus according to an example embodiment of the present invention.

FIG. 3 illustrates a plan view of the above-described organic light emitting display apparatus of FIG. 2. Thus, like reference numerals refer to like elements, and in a material and a structure of each element, the same or similar descriptions are not repeated.

As seen in FIG. 3, the organic light emitting display apparatus according to an embodiment of the present invention may include an anode electrode 180, an auxiliary electrode 190, a bank 220, a first partition wall 231, a second partition wall 232, and an auxiliary line 300.

The anode electrode 180 may be formed in plurality on a substrate of the organic light emitting display apparatus. A plurality of the auxiliary lines 300 may be respectively formed between the plurality of anode electrodes 180 and arranged in one direction to have a stripe structure.

The auxiliary electrode 190 may be formed on the auxiliary line 300 in a rectangular shape. However, the present embodiment is not limited thereto.

The bank 220 may be formed to overlap a portion of the auxiliary electrode 190.

The first partition wall 231 may be formed at a center portion of the auxiliary electrode 190 to support the second partition wall 232. The first partition wall 231 and the second partition wall 232 may be formed in an island shape on the auxiliary electrode 190 to be separated from the other elements.

A fourth contact hole CH4 may be formed on the auxiliary electrode 190 and may be connected to the auxiliary line 300.

A cathode electrode may be formed without an organic emission layer being formed in a partial region (i.e., a portion of the auxiliary electrode 190 overlapping the second partition wall 232) other than a partial region where the first partition wall 231 is formed, in a region of the auxiliary electrode 190 corresponding to the second partition wall 232. Thus, the auxiliary electrode 190 may be electrically connected to the cathode electrode.

As described above, if the second partition wall 232 is formed, a top of the second partition wall 232 may act as eaves in depositing the organic emission layer, and thus, because the organic emission layer is not deposited under the eaves, a mask pattern which covers a top of the auxiliary electrode 190 is not needed.

However, a width of a top of the second partition wall 232 may be formed greater than that of a bottom of the second partition wall 232, and because the first partition wall 231 is formed under the second partition wall 232 according to a size of the bottom of the second partition wall 232, the first partition wall 231 may unstably support the second partition wall 232. Due to such a problem, if the first partition wall 231 cannot support the second partition wall 232, the top of

the second partition wall 232, acting as eaves, may not cover a separation space between the partition wall and the bank 220, and for this reason, the organic emission layer may penetrate into the separation space between the partition wall and the bank 220. Therefore, the auxiliary electrode 190 may not be exposed, causing a defect where the cathode electrode cannot be electrically connected to the auxiliary electrode 190. Also, when a total size of the auxiliary electrode 190 increases for forming the second partition wall 232 with a stable size, a size of the anode electrode 180 formed on the same layer as a layer on which the auxiliary electrode 190 is disposed may be reduced, causing a reduction in an aperture ratio.

FIG. 4 is a plan view of an organic light emitting display apparatus according to another example embodiment of the present invention.

FIG. 4 illustrates a plan view of the above-described organic light emitting display apparatus of FIG. 2. Thus, like reference numerals refer to like elements, and in a material and a structure of each element, the same or similar descriptions are not repeated.

As seen in FIG. 4, the organic light emitting display apparatus may include an anode electrode 180, an auxiliary electrode 190, a bank 220, a first partition wall 231, a second partition wall 232, and an auxiliary line 300. Elements other than the first partition wall 231 and the second partition wall 232 may be the same as those of the above-described organic light emitting display apparatus of FIG. 3, and thus, their detailed descriptions are not repeated.

The first partition wall 231 of the organic light emitting display apparatus of FIG. 3 is formed in an island shape on the auxiliary electrode 190 to be separated from the other elements. On the other hand, both ends of the first partition wall 231 of the organic light emitting display apparatus according to another example embodiment of the present invention may contact the bank 220. Therefore, according to another example embodiment, the first partition wall 231 may not be formed in an island shape on the auxiliary electrode 190 to be separated from the other elements, but may be formed to contact the bank 220, and thus, the first partition wall 231 may stably support the second partition wall 232.

Moreover, the second partition wall 232 of the organic light emitting display apparatus of FIG. 3 may be formed on a top of the first partition wall 231 to be supported by only the first partition wall 231. On the other hand, the second partition wall 232 of the organic light emitting display apparatus according to another example embodiment of the present invention may be formed to contact the bank 220, and the partition wall 231 may be formed on the same layer as a layer on which the bank 220 is disposed, whereby the second partition wall 232 is more stably supported by the first partition wall 231 and the bank 220. For this reason, a defect where the cathode electrode cannot electrically be connected to the auxiliary electrode 190 may be prevented. Also, the second partition wall 232 may be stably formed even without any increase in a total size of the auxiliary electrode 190, and thus may not affect a size of the anode electrode 180 which is formed on the same layer as a layer thereof, thereby preventing an aperture ratio from being reduced.

The first partition wall 231 may include a portion contacting the bank 220 and another portion which does not contact the bank 220. The auxiliary electrode 190 may be formed to be exposed in a region between the bank 220 and the other portion of the first partition wall 231 which does not contact the bank 220. Therefore, the exposed auxiliary

electrode **190** may be electrically connected to the cathode electrode, thereby lowering a resistance.

An organic emission layer may not be formed in an exposed region of the auxiliary electrode **190**, where the first partition wall **231** and the bank **220** are not formed. Accordingly, the cathode electrode may be electrically connected to the auxiliary electrode **190** in the exposed region of the auxiliary electrode **190**.

FIG. **5** is a plan view of an organic light emitting display apparatus according to another example embodiment of the present invention.

FIG. **5** illustrates a plan view of the above-described organic light emitting display apparatus of FIG. **2**. Thus, like reference numerals refer to like elements, and in a material and a structure of each element, the same or similar descriptions are not repeated.

As seen in FIG. **5**, the organic light emitting display apparatus may include an anode electrode **180**, an auxiliary electrode **190**, a bank **220**, a first partition wall **231**, a second partition wall **232**, and an auxiliary line **300**. Elements other than the auxiliary line **300** may be the same as those of the above-described organic light emitting display apparatus of FIG. **4**, and thus, their detailed descriptions are not repeated.

The auxiliary lines **300** of the organic light emitting display apparatus of FIG. **4** are respectively formed between the plurality of anode electrodes **180** and arranged in one direction to have the stripe structure. On the other hand, in the organic light emitting display apparatus according to the example embodiment of FIG. **5**, a plurality of the auxiliary lines **300** may be formed in a mesh structure where the plurality of auxiliary lines **300** are arranged to intersect each other between a plurality of the anode electrodes **180**. Therefore, an area of each of the auxiliary lines **300** is larger in a case where the auxiliary lines **300** are formed in the mesh structure, than in a case where the auxiliary lines **300** are formed in the stripe structure, and thus, a resistance of the organic light emitting display apparatus according to another example embodiment of the present invention may be further reduced.

The auxiliary electrode **190** may be formed at a portion where the auxiliary lines **300** intersect each other.

FIGS. **6A** to **6C** are cross-sectional views of an organic light emitting display apparatus according to another example embodiment of the present invention, and illustrate a cross-sectional view of the above-described auxiliary electrode of FIG. **5**. Thus, like reference numerals refer to like elements, and in a material and a structure of each element, the same or similar descriptions are not repeated.

FIG. **6A** illustrates a cross-sectional surface taken along line A-A of FIG. **5**. As seen in FIG. **6A**, the anode electrode **180** and the auxiliary electrode **190** may be formed on a planarization layer **170** to be separated from each other. The bank **220** may be formed between the anode electrode **180** and the auxiliary electrode **190**, and may insulate the anode electrode **180** from the auxiliary electrode **190**. The first partition wall **231** may be formed in an island shape on an exposed portion of a top of the auxiliary electrode **190**, and the second partition wall **232** may be formed on a top of the first partition wall **231**.

FIG. **6B** illustrates a cross-sectional surface taken along line B-B of FIG. **5**. As seen in FIG. **6B**, the anode electrode **180**, the auxiliary electrode **190**, and the bank **220** may be formed on the planarization layer **170**. Because line B-B is located in a region which is exposed without the first partition wall **231** being formed in the auxiliary electrode

190, the first partition wall **231** is not illustrated. Both ends of the second partition wall **232** may be formed to contact the bank **220**.

FIG. **6C** illustrates a cross-sectional surface taken along line C-C of FIG. **5**. As seen in FIG. **6C**, the anode electrode **180**, the auxiliary electrode **190**, and the bank **220** may be formed on the planarization layer **170**. The first partition wall **231** may extend and may be connected to the bank **220**, and the second partition wall **232** may be formed to be supported by the first partition wall **231** and the bank **220**.

FIG. **7** is a cross-sectional view of an organic light emitting display apparatus according to another example embodiment of the present invention.

Except for a first anode electrode **180**, a second anode electrode **200**, a first auxiliary electrode **190**, and a second auxiliary electrode **210**, the organic light emitting display apparatus of FIG. **7** may be the same as the above-described organic light emitting display apparatus of FIG. **2**, and thus, repetitive descriptions are not provided.

The first anode electrode **180** and the first auxiliary electrode **190** may be formed on the planarization layer **170**. That is, the first anode electrode **180** and the first auxiliary electrode **190** may be formed on the same layer. A third contact hole CH3 exposing the source electrode **150** may be included in the above-described passivation layer **165** and planarization layer **170**, and the source electrode **150** may be connected to the first anode electrode **180** through the third contact hole CH3.

The first anode electrode **180** may include a first lower anode electrode **181** and a first upper anode electrode **182**.

The first lower anode electrode **181** may be formed between the planarization layer **170** and the first upper anode electrode **182**, and may enhance an adhesive force between the planarization layer **170** and the first upper anode electrode **182**. Also, the first lower anode electrode **181** may protect a bottom of the first upper anode electrode **182**, thereby preventing the bottom of the first upper anode electrode **182** from being corroded.

The first upper anode electrode **182** may be formed on a top of the first lower anode electrode **181**. The first upper anode electrode **182** may be formed of metal which is relatively lower in resistance than the first lower anode electrode **181**.

Similarly to the above-described first anode electrode **180**, the first auxiliary electrode **190** may include a first lower auxiliary electrode **191** and a second upper auxiliary electrode **192**.

The first lower auxiliary electrode **191** may be formed between the planarization layer **170** and the first upper auxiliary electrode **192**. The first lower auxiliary electrode **191** may enhance an adhesive force between the planarization layer **170** and the first upper auxiliary electrode **192**, and may prevent a bottom of the first upper auxiliary electrode **192** from being corroded.

The first upper auxiliary electrode **192** may be formed of low-resistance metal on a top of the first lower auxiliary electrode **191**.

The second anode electrode **200** may be formed to cover a top and a side surface of the first anode electrode **180**, thereby preventing the top and side surfaces of the first anode electrode **180** from being corroded.

The second anode electrode **200** may include a second lower anode electrode **201**, a second center anode electrode **202**, and a second upper anode electrode **203**.

The second lower anode electrode **201** may be formed between the first anode electrode **180** and the second center anode electrode **202**. The second lower anode electrode **201**

may be formed to cover the top and side surface of the first anode electrode **180**, thereby preventing the first anode electrode **180** from being corroded.

The second center anode electrode **202** may be formed between the second lower anode electrode **201** and the second upper anode electrode **203**. The second center anode electrode **202** may be formed of a material which is lower in resistance than, and better in reflectivity than, the second lower anode electrode **201** and the second upper anode electrode **203**.

The second upper anode electrode **203** may be formed on a top of the second center anode electrode **202**, thereby preventing the top of the second center anode electrode **202** from being corroded.

The second auxiliary electrode **210** may be formed on a top of the first auxiliary electrode **190**. The second auxiliary electrode **210** may be formed on the same layer as a layer on which the second anode electrode **200** is disposed. The second auxiliary electrode **210** may be formed to cover a top and a side surface of the first auxiliary electrode **190**, thereby preventing the top and side surfaces of the first auxiliary electrode **190** from being corroded. The second auxiliary electrode **210** may lower a resistance of the cathode electrode **250** along with the first auxiliary electrode **190**.

The second auxiliary electrode **210** may include a second lower auxiliary electrode **211**, a second center auxiliary electrode **212**, and a second upper auxiliary electrode **213**.

The second lower auxiliary electrode **211** may be formed between the first auxiliary electrode **190** and the second center auxiliary electrode **212**. The second lower auxiliary electrode **211** may be formed to cover the top and side surfaces of the first auxiliary electrode **190**, thereby preventing the first auxiliary electrode **190** from being corroded.

The second center auxiliary electrode **212** may be formed between the second lower auxiliary electrode **211** and the second upper auxiliary electrode **213**. The second center auxiliary electrode **212** may be formed of a material that is lower in resistance than, and better in reflectivity than, the second lower auxiliary electrode **211** and the second upper auxiliary electrode **213**.

The second upper auxiliary electrode **213** may be formed on a top of the second center auxiliary electrode **212**, thereby preventing the top of the second center auxiliary electrode **212** from being corroded.

FIG. **8** is a cross-sectional view of an organic light emitting display apparatus according to another example embodiment of the present invention.

Except for a first connection line **185**, a second connection line **195**, and a second planarization layer **175**, the organic light emitting display apparatus of FIG. **8** may be the same as the above-described organic light emitting display apparatus of FIG. **2**, and thus, repetitive descriptions are not provided.

In the above-described organic light emitting display apparatus of FIG. **7**, the second anode electrode **200** and the second auxiliary electrode **210** are respectively formed on the first anode electrode **180** and the first auxiliary electrode **190**, and thus, resistances of the anode electrode **180** and the cathode electrode **250** may be lowered. However, because the auxiliary electrode **190** and the anode electrode **180** are formed on the same layer, a space for forming the anode electrode **180** and the auxiliary electrode **190** may be limited. In contrast, in the organic light emitting display apparatus of FIG. **8** according to another example embodiment, the first connection line **185** connected to the anode electrode **180** may be formed under the anode electrode **180**, and the second connection line **195** connected to the auxil-

iliary electrode **190** may be formed under the auxiliary electrode **190**. The anode electrode **180** and the auxiliary electrode **190** are respectively connected to the first connection line **185** and the second connection line **195**, and thus may be broad in area. Accordingly, resistances of the anode electrode **180** and the cathode electrode **250** may be further reduced.

The first connection line **185** and the second connection line **195** may be formed on the first planarization layer **170**. That is, the first connection line **185** and the second connection line **195** may be formed on the same layer to be separated from each other. A third contact hole CH3 exposing the source electrode **150** may be included in the passivation layer **165** and the first planarization layer **170**, and the source electrode **150** may be connected to the first connection line **185** through the third contact hole CH3. Also, a fourth contact hole CH4 exposing the auxiliary line **300** may be included in the passivation layer **165** and the first planarization layer **170**, and the auxiliary line **300** may be connected to the second connection line **195** through the fourth contact hole CH4.

The second planarization layer **175** may be formed on the first and second connection lines **185** and **195**. The anode electrode **180** and the auxiliary electrode **190** may be formed on the second planarization layer **175**. A fifth contact hole CH5 exposing the first connection line **185** may be included in the second planarization layer **175**, and the first connection line **185** may be connected to the anode electrode **180** through the fifth contact hole CH5. That is, the anode electrode **180** may be connected to the source electrode **150** through the first connection line **185**. Also, a sixth contact hole CH6 exposing the second connection line **195** may be included in the second planarization layer **175**, and the second connection line **195** may be connected to the auxiliary electrode **190** through the sixth contact hole CH6. That is, the auxiliary electrode **190** may be connected to the auxiliary line **300** through the second connection line **195**.

As described above, according to example embodiments of the present invention, the partition wall may be stably formed in the existing size of the auxiliary electrode without reduction in an aperture ratio.

Moreover, according to example embodiments of the present invention, the organic emission layer may be formed without a mask pattern covering a top of the auxiliary electrode, and thus, an increase in the complexity or time for the mask process may be prevented.

Moreover, according to example embodiments of the present invention, the first partition wall may stably support the second partition wall, thereby preventing a defect.

Moreover, according to example embodiments of the present invention, two anode electrodes (for example, the first and second anode electrodes) may be stack-formed for lowering the resistance of the anode electrode, and thus, the desired resistance characteristic of the anode electrode may be more easily obtained.

Moreover, according to example embodiments of the present invention, two auxiliary electrodes (for example, the first and second auxiliary electrodes) may be stack-formed for lowering the resistance of the cathode electrode, and thus, the desired resistance characteristic of the auxiliary electrode may be more easily obtained.

Moreover, according to example embodiments of the present invention, the auxiliary line may be connected to the auxiliary electrode by the connection line, and thus, the desired resistance characteristic of the auxiliary electrode may be more easily obtained.

It will be apparent to those skilled in the art that various modifications and variations can be made in the present invention without departing from the spirit or scope of the inventions. Thus, it is intended that the present invention covers the modifications and variations of this invention provided they come within the scope of the appended claims and their equivalents.

The invention claimed is:

1. An organic light emitting display apparatus, comprising:

- a substrate;
 - an auxiliary line on the substrate;
 - an anode electrode on the substrate;
 - an auxiliary electrode on the substrate;
 - an organic emission layer on the anode electrode;
 - a cathode electrode on the organic emission layer and on the auxiliary electrode;
 - a bank overlapping with a first portion of the auxiliary electrode and exposing a second portion of the auxiliary electrode;
 - a partition wall on the second portion of the auxiliary electrode; and
 - a separation space between the partition wall and the bank, the cathode electrode being electrically connected to the auxiliary electrode through the separation space,
- wherein the auxiliary line is connected to the second portion of the auxiliary electrode through a contact hole, and
- wherein the auxiliary line is disposed between a plurality of the anode electrodes.

2. The organic light emitting display apparatus according to claim 1, wherein:

- the partition wall includes eaves covering the separation space, and
- a first portion of the eaves in a first direction is separated from the bank by a certain distance, and a second portion of the eaves in a second direction intersecting the first direction is supported by the bank.

3. The organic light emitting display apparatus according to claim 2, wherein the partition wall includes:

- a first partition wall on the second portion of the auxiliary electrode; and
- a second partition wall on the first partition wall to act as the eaves.

4. The organic light emitting display apparatus according to claim 3, wherein the contact hole which connects the auxiliary electrode to the auxiliary line does not overlap the first partition wall.

5. The organic light emitting display apparatus according to claim 3, wherein:

- a first portion of the first partition wall in the first direction is separated from the bank by the certain distance, and
- a second portion of the first partition wall in the second direction is connected to the bank on the auxiliary electrode.

6. The organic light emitting display apparatus according to claim 3, wherein the first partition wall is on the same layer as the bank.

7. The organic light emitting display apparatus according to claim 5, wherein the second partition wall in the second direction is supported by the second portion of the first partition wall and the bank.

8. The organic light emitting display apparatus according to claim 5, wherein a width of a top of the second partition

wall is greater than a width of a bottom of the second partition wall on the first partition wall.

9. The organic light emitting display apparatus according to claim 5, wherein the second portion of the auxiliary electrode is exposed in a region between the second portion of the first partition wall and the bank.

10. The organic light emitting display apparatus of claim 5, wherein the cathode electrode is connected to the second portion of the auxiliary electrode through the region between the second portion of the first partition wall and the bank.

11. The organic light emitting display apparatus according to claim 2, wherein the cathode electrode is connected to the second portion of the auxiliary electrode under the first portion of the eaves.

12. The organic light emitting display apparatus according to claim 1, wherein:

- the auxiliary line has a stripe structure wherein a plurality of the auxiliary lines are arranged in one direction, or
- a mesh structure wherein a plurality of auxiliary lines are arranged in two directions to intersect each other.

13. The organic light emitting display apparatus according to claim 1, further comprising a thin film transistor on the substrate, the thin film transistor including a source electrode,

- wherein the auxiliary line is on the same layer as the source electrode.

14. The organic light emitting display apparatus according to claim 1, wherein:

- the anode electrode includes a first anode electrode and a second anode electrode, the second anode electrode covering a top surface and a side surface of the first anode electrode; and
- the auxiliary electrode includes a first auxiliary electrode and a second auxiliary electrode, the second auxiliary electrode covering a top surface and a side surface of the first auxiliary electrode.

15. The organic light emitting display apparatus according to claim 1, wherein the auxiliary electrode is on the same layer as the anode electrode.

16. The organic light emitting display apparatus according to claim 1, further comprising

- a connection line on the auxiliary line and connected to the auxiliary line, the connection line connected to the auxiliary electrode.

17. The organic light emitting display apparatus according to claim 16, wherein the connection line is connected to the auxiliary electrode through the contact hole.

18. The organic light emitting display apparatus according to claim 17, wherein the partition wall includes:

- a first partition wall on the second portion of the auxiliary electrode; and
 - a second partition wall on the first partition wall to act as the eaves,
- wherein the contact hole which connects the auxiliary electrode to the auxiliary line does not overlap the first partition wall.

19. The organic light emitting display apparatus according to claim 16, further comprising a thin film transistor on the substrate, the thin film transistor including a source electrode,

- wherein the auxiliary line is on the same layer as the source electrode.

