



US010644079B2

(12) **United States Patent**
Hong et al.

(10) **Patent No.:** **US 10,644,079 B2**
(45) **Date of Patent:** **May 5, 2020**

(54) **ORGANIC LIGHT EMITTING DIODE DISPLAY**

(52) **U.S. Cl.**
CPC **H01L 27/3218** (2013.01); **H01L 27/326** (2013.01); **H01L 27/3223** (2013.01);
(Continued)

(71) Applicant: **SAMSUNG DISPLAY CO., LTD.**,
Yongin-si, Gyeonggi-do (KR)

(58) **Field of Classification Search**
CPC H01L 27/3218; H01L 27/326; H01L 27/3276; H01L 51/0097; H01L 27/3223;
(Continued)

(72) Inventors: **Jong Ho Hong**, Yongin-si (KR); **Won Il Choi**, Yongin-si (KR); **Hye Jin Joo**, Yongin-si (KR); **Won Sang Park**, Yongin-si (KR); **Mu Gyeom Kim**, Yongin-si (KR); **Man Sik Myeong**, Yongin-si (KR); **Hyo Yul Yoon**, Yongin-si (KR)

(56) **References Cited**

(73) Assignee: **SAMSUNG DISPLAY CO., LTD.**,
Yongin-si, Gyeonggi-Do (KR)

U.S. PATENT DOCUMENTS
8,084,117 B2 12/2011 Lalvani
8,207,473 B2 6/2012 Axisa et al.
(Continued)

(*) Notice: Subject to any disclaimer, the term of this patent is extended or adjusted under 35 U.S.C. 154(b) by 0 days.

FOREIGN PATENT DOCUMENTS

(21) Appl. No.: **16/105,361**

JP 2008-542834 A 11/2008
WO WO 2006/129232 A2 12/2006
WO WO 2011/008459 A2 1/2011

(22) Filed: **Aug. 20, 2018**

Primary Examiner — Think T Nguyen

(65) **Prior Publication Data**

US 2018/0358418 A1 Dec. 13, 2018

(74) *Attorney, Agent, or Firm* — Kile Park Reed & Houtteman PLLC

Related U.S. Application Data

(57) **ABSTRACT**

(63) Continuation of application No. 15/786,819, filed on Oct. 18, 2017, now Pat. No. 10,056,435, which is a
(Continued)


An organic light emitting diode display includes a stretchable substrate, a plurality of pixel forming plates, first and second pixels, and a cut-out groove. The pixel forming plates are on the substrate and spaced apart from each other. The first and second pixels are on respective first and second pixel forming plates of the plurality of the pixel forming plates adjacent in a first direction. The first and second pixel forming plates are connected by a first bridge. The cut-out groove are in the first and second pixel forming plates and adjacent to an area connected to the first bridge.

(30) **Foreign Application Priority Data**

Mar. 10, 2015 (KR) 10-2015-0033419

20 Claims, 25 Drawing Sheets

(51) **Int. Cl.**
H01L 27/32 (2006.01)
H01L 51/00 (2006.01)
H01L 29/08 (2006.01)



Related U.S. Application Data

continuation of application No. 15/064,917, filed on Mar. 9, 2016, now Pat. No. 9,799,708.

- (52) **U.S. Cl.**
 CPC *H01L 27/3276* (2013.01); *H01L 51/0097* (2013.01); *H01L 29/08* (2013.01); *H01L 2251/5338* (2013.01); *Y02E 10/549* (2013.01)

- (58) **Field of Classification Search**
 CPC .. H01L 2251/5838; H01L 29/08; H01L 33/40
 USPC 257/40, 59, 72, 88, 99; 438/21, 26, 88, 438/89

See application file for complete search history.

- (56) **References Cited**

U.S. PATENT DOCUMENTS

8,217,381	B2	7/2012	Rogers et al.	
8,389,862	B2	3/2013	Arora et al.	
8,536,667	B2	9/2013	De Graff et al.	
9,391,286	B1	7/2016	Kwon et al.	
2007/0122590	A1	5/2007	Lalvani	
2008/0218369	A1	9/2008	Krans et al.	
2010/0002402	A1	1/2010	Rogers et al.	
2010/0330338	A1	12/2010	Boyce et al.	
2012/0052268	A1	3/2012	Axisa et al.	
2014/0138637	A1	5/2014	Yang et al.	
2014/0299362	A1*	10/2014	Park et al.	H05K 1/028 174/254

* cited by examiner

FIG. 1




FIG. 2




FIG. 3





FIG. 4





FIG. 5




FIG. 6




FIG. 7




FIG. 8




FIG. 10




FIG. 11




FIG. 12




FIG. 13




FIG. 14




FIG. 15




FIG. 16




FIG. 17




FIG. 18




FIG. 19






FIG. 20



Second direction



First direction



FIG. 21




FIG. 22





FIG. 23





FIG. 24






FIG. 25



ORGANIC LIGHT EMITTING DIODE DISPLAY

CROSS-REFERENCE TO RELATED APPLICATIONS

This is a continuation application based on pending application Ser. No. 15/786,819, filed Oct. 18, 2017, which in turn is a continuation of Ser. No. 15/064,917, filed Mar. 9, 2016, now U.S. Pat. No. 9,799,708 B2 issued Oct. 24, 2017, the entire contents of which is hereby incorporated by reference.

Korean Patent Application No. 10-2015-0033419, filed on Mar. 10, 2015, and entitled, "Organic Light Emitting Diode Display," is incorporated by reference herein in its entirety.

BACKGROUND

1. Field

One or more embodiments described herein relate to an organic light emitting diode display.

2. Description of the Related Art

A variety of flat panel displays have been developed. Examples include a liquid crystal display, a plasma display panel, an organic light emitting diode (OLED) display, a field effect display, and an electrophoretic display. Each pixel of an OLED display has an organic emission layer between two electrodes. Electrons injected from one electrode and holes injected from another electrode combine in the organic emission layer to generate excitons. Light is emitted when excitons change state.

An OLED display has self-luminance characteristics which allow it to achieve improved performance and efficiency, e.g., low power consumption, high luminance, and high response speed. Also, because an OLED display does not require an additional light source (e.g., a backlight), it is also able to be thinner and lighter than other displays.

Recently, a bendable, foldable, stretchable, or extensible display device has been developed. In a stretchable display device, light-emitting devices may be formed on a stretchable substrate. When the stretchable substrate is stretched, the light-emitting devices or wires laminated on an upper portion of the stretchable substrate may be damaged.

SUMMARY

In accordance with one or more embodiments, an organic light emitting diode display includes a stretchable substrate; a plurality of pixel forming plates on the substrate and spaced apart from each other; and first and second pixels on respective first and second pixel forming plates of the plurality of the pixel forming plates adjacent in a first direction, the first and second pixel forming plates connected by a first bridge, and a cut-out groove in the first and second pixel forming plates and adjacent to an area connected to the first bridge.

The first bridge may be curved in a second direction crossing the first direction. The first bridge may have a predetermined width. The first bridge may have a predetermined radius of curvature. The first bridge may be upwardly curved along the second direction.

The first pixel forming plate may include a first main supporting plate; a first wing plate on one lateral surface of the first main supporting plate, wherein one side end portion

of the first wing plate is connected to the first bridge; a second wing plate on another lateral surface of the first main supporting plate and adjacent to the one side end portion of the first wing plate; and a first cut-out groove between one side end portion of the second wing plate and the first bridge.

The second pixel forming plate may include a second main supporting plate; a third wing plate on one lateral surface of the second main supporting plate to face the first wing plate of the first pixel forming plate, one side end portion of the third wing plate connected to the first bridge; a fourth wing plate on another lateral surface of the second main supporting plate and adjacent to the one side end portion of the third wing plate; and a second cut-out groove between one side end portion of the fourth wing plate and the first bridge.

The base layer may include a third pixel forming plate adjacent to the first pixel forming plate in the second direction; a third pixel on the third pixel forming plate; and a second bridge connecting the first and third pixel forming plates.

The third pixel forming plate may include a third main supporting plate; a fifth wing plate on one lateral surface of the third main supporting plate to face the second wing plate of the first pixel forming plate, one side end portion of the fifth wing plate connected to the second bridge; and a sixth wing plate on another lateral surface of the third main supporting plate to be adjacent to the one side end portion of the fifth wing plate, wherein the second bridge is connected to the another end portion of the second wing plate of the first pixel forming plate, and a third cut-out groove between one side end portion of the sixth wing plate and the second bridge.

The display may include a plurality of first to third wires on the first pixel forming plate connected to the first pixel, and the first wires may be connected to a second pixel of the second pixel forming plate through an upper side of the first bridge. The first wires may extend in a length direction of the first bridge and may be disposed in an outer side of a center line of the first bridge passing through a center of the first bridge.

The display may include a plurality of dummy wires on the first bridge and disposed above and below the first wires to overlap a portion of the first wires, wherein strain on the dummy wires is greater than that on the first wires. The dummy wires may extend in a length direction of the first bridge and may be disposed in an inner side of a center line of the first bridge passing through a center of the first bridge. The lengths of the dummy wires may decrease from the inner side of the first bridge toward an outer side thereof.

The display may include a sensing thin film transistor on the respective pixel forming plates and connected to at least one of the first to third wires to measure strain on the at least one of the first to third wires. The first wires may include a plurality of gate lines. The second bridge may be curved in the first direction. The second bridge may have a predetermined width. The second bridge may have a predetermined radius of curvature.

The second and third wires may be connected to a third pixel on the third pixel forming plate through an upper side of the second bridge. Based on a center line of the second bridge extending in a length direction of the second bridge and passing through a center of the second bridge, a portion of the second and third wires that have strain in a first range may be disposed in an outer side of the center line, and another portion of the second and third wires that have strain in a second range may be disposed in an inner side of the center line, the second range greater than the first range. The

second wires may include a plurality of data lines and the third wires include a plurality of driving voltage lines. The first bridge may be downwardly curved along the second direction.

The first pixel forming plate may include a first main supporting plate; a first wing plate on one lateral surface of the first main supporting plate; and a second wing plate on another lateral surface of the first main supporting plate, wherein one side end portion of the second wing plate is connected to the first bridge, and wherein a first cut-out groove is between one side end portion of the first wing plate adjacent to the one side end portion of the second wing plate and the first bridge.

The second pixel forming plate may include a second main supporting plate; a third wing plate formed on one lateral surface of the second main supporting plate to face the first wing plate of the first pixel forming plate; and a fourth wing plate formed on another lateral surface of the second main supporting plate, wherein one side end portion of the fourth wing plate is connected to the first bridge, and wherein a second cut-out groove is between one side end portion of the third wing plate adjacent to the one side end portion of the fourth wing plate and the first bridge.

The display may include a plurality of the first pixels, and a plurality of the second pixels. Each of the first pixels and the second pixels may include at least one pixel circuit. Each of the first pixels and the second pixels may include a plurality of subpixels. Each of the pixel forming plates may have substantially a polygonal shape.

In accordance with one or more other embodiments, an organic light emitting diode display includes a stretchable substrate; a plurality of pixel forming plates on the substrate and spaced apart from each other; and first and second pixels on respective first and second pixel forming plates of the plurality of the pixel forming plates adjacent in a first direction; and first to third wires on the first pixel forming plate connected to the first pixels, wherein the first and second pixel forming plates are connected by the first bridge, and wherein the first wires are connected to the second pixels of the second pixel forming plate through an upper side of the first bridge.

The first bridge may have a predetermined width and may be curved in a second direction crossing the first direction. The first bridge may have a predetermined radius of curvature. The first wires may extend in a length direction of the first bridge and may be disposed in an outer side of a center line of the first bridge passing through a center of the first bridge.

The display may include a plurality of dummy wires on the first bridge and above and below the first wires overlapping a portion of the first wires, wherein the dummy wires extend in a length direction of the first bridge and are disposed in an inner side of a center line of the first bridge passing through a center of the first bridge, and wherein strain on the dummy wires is greater than strain on the first wires.

The base layer may include a third pixel forming plate adjacent to the first pixel forming plate in the second direction crossing the first direction, and a second bridge connecting the first and third pixel forming plates, wherein the second and third wires are connected to third pixels on the third pixel forming plate through an upper side of the second bridge. The second bridge may have a predetermined width and is curved in the first direction. The second bridge may have a predetermined radius of curvature.

Based on a center line of the second bridge extending in a length direction of the second bridge and passing through

a center of the second bridge, a portion of the second and third wires may have strain in a first range and may be disposed in an outer side of the center line, and another portion of the second and third wires may have strain in a second range and may be disposed in an inner side of the center line, the second range greater than the first range.

BRIEF DESCRIPTION OF THE DRAWINGS

Features will become apparent to those of skill in the art by describing in detail exemplary embodiments with reference to the attached drawings in which:

FIG. 1 illustrates an embodiment of an OLED display;

FIG. 2 illustrates an embodiment of a pixel;

FIG. 3 illustrates a base layer according to the first embodiment;

FIG. 4 illustrates an enlarged view of area A in FIG. 3;

FIG. 5 illustrates an example of first to a third wires connected to the pixel;

FIG. 6 illustrates an example for expanding the base layer; FIG. 7 illustrates an example of strain in area B of FIG. 6;

FIG. 8 illustrates an example of variation of strain based on position;

FIG. 9 illustrates an example of a pixel circuit;

FIG. 10 illustrates a layout embodiment of a pixel;

FIG. 11 illustrates a view along section line XI-XI in FIG. 10;

FIG. 12 illustrates a view along section line XII-XII in FIG. 10;

FIGS. 13 to 17 illustrate layout embodiments of wires in a bridge area;

FIG. 18 illustrates an example of a connection structure between a wire and a sensing transistor for measuring strain on the wire;

FIGS. 19 to 21 illustrate layout embodiments of subpixels;

FIG. 22 illustrates a top plan view of a base layer of a second embodiment;

FIG. 23 illustrates a top plan view of a base layer of a third embodiment;

FIG. 24 illustrates an enlarged view of area C in FIG. 23;

FIG. 25 illustrates an example of first to third wires connected to respective pixels on the base layer in FIG. 24.

DETAILED DESCRIPTION

Example embodiments are described more fully hereinafter with reference to the accompanying drawings; however, they may be embodied in different forms and should not be construed as limited to the embodiments set forth herein. Rather, these embodiments are provided so that this disclosure will be thorough and complete, and will fully convey exemplary implementations to those skilled in the art. The embodiments may be combined to form additional embodiments.

It will also be understood that when a layer or element is referred to as being “on” another layer or substrate, it can be directly on the other layer or substrate, or intervening layers may also be present. Further, it will be understood that when a layer is referred to as being “under” another layer, it can be directly under, and one or more intervening layers may also be present. In addition, it will also be understood that when a layer is referred to as being “between” two layers, it can be the only layer between the two layers, or one or more intervening layers may also be present. Like reference numerals refer to like elements throughout.

FIG. 1 illustrates an embodiment of an OLED display, FIG. 2 illustrates a cross-sectional view of an embodiment of a pixel (PX) structure, FIG. 3 is a top plan view of an embodiment of a base layer of the OLED display, FIG. 4 illustrates an enlarged view of area A in FIG. 3, and FIG. 5 illustrates an example of first to a third wires connected to pixels on a base layer in FIG. 4.

In FIGS. 1 and 2, the OLED display includes a stretchable substrate 100 having an island (IS) shape, and a pixel (PX) structure on the stretchable substrate 100. The pixel (PX) structure represents a remaining configuration of the OLED display, except for the substrate 100.

Referring to FIG. 1, the substrate 100 has a structure for supporting pixel. As a stretchable substrate, the substrate 100 may be extended or contract in at least one direction. The substrate 100 has an island shape, where, for example, plurality of islands (IS) are spaced apart from each other at a predetermined distance P. When the substrate 100 is stretched, the distance P between the islands IS increases or decreases. However, even though the substrate 100 is stretched, each of the islands (IS) is not modified, e.g., a width and/or height of each of the islands IS does not increase or decrease.

In addition, even though the substrate 100 is stretched, the pixel PX structures on the islands IS are not modified. However, bridges BR connecting the pixel PX structures to each other, and areas CN in which the bridges and the pixels PX are connected, may be modified.

Referring to FIG. 2, the pixel PX on the substrate 100 includes a base layer 110, a thin film transistor, a first electrode, an emission layer, a second electrode, and the like. The base layer 110 is on the substrate 100. For example, the base layer 110 is on each of the islands on the substrate 100. In this case, the base layer 110 is formed is stretchable together with the substrate 100 when the substrate 100 is stretched.

Referring to FIG. 3, the base layer 110 includes a plurality of pixel forming plates 1110 and bridges 1130. The pixel forming plates 1110 are respectively disposed on the islands IS of the substrate 100. The pixel forming plates 1110 may be disposed in a lattice shape. Each of pixels PX may be formed on each of the pixel forming plates 1110. The bridges 1130 connect the pixel forming plates 1110 to each other. In this case, a plurality of pixels may be formed on each of the pixel forming plates 1110.

Each of the pixels may include a pixel circuit for driving an organic light emitting element. The pixel circuit may include, for example, a thin film transistor and a storage capacitor Cst for driving a pixel.

Each of the pixel forming plates 1110 may have a shape corresponding to a sectional shape of the island IS of the substrate 100. In one embodiment, the pixel forming plate 1110 may have substantially a quadrangular shape. The pixel forming plate 1110 may have a different shape in another embodiment, e.g., polygonal shape, such as a circular, triangular, or pentagonal shape corresponding to a sectional shape of the island IS of the substrate 100.

Referring to FIG. 4, an enlarged view of area A in FIG. 3 includes first and second pixel forming plates 1111 and 1113 of the pixel forming plate 1110 arranged in a first direction. First and third pixel forming plates 1111 and 1115 are arranged in a second direction perpendicular to the first direction. The first and second pixel forming plates 1111 and 1113 are connected by a first bridge 1131, and the first and third pixel forming plates 1111 and 1115 are connected by a second bridge 1133.

The first pixel forming plate 1111 includes a first main supporting plate 1111a, and first and second wing plates 1111b and 1111c. The first main supporting plate 1111a is in a center area of the first pixel forming plate 1111. A thin film transistor, an organic light emitting element are formed on the first main supporting plate 1111a. The first main supporting plate 1111a may have substantially a quadrangular shape.

The first and second wing plates 1111b and 1111c are formed on lateral surfaces of the first pixel forming plate 1111, and are combined with bridges connecting pixel forming plates to each other. The second wing plate 1111c is on the first main supporting plate 1111a and adjacent to the first wing plate 1111b. In FIG. 4, a dotted line between the first main supporting plate 1111a and the first and second wing plates 1111b and 1111c is a virtual line distinguishing the main supporting plate and the wing plate.

In addition to the first and second wing plates 1111b and 1111c, an additional wing plate may be formed on a lateral surface of the first main supporting plate 1111a. As shown in FIG. 4, wing plates may be formed at right and left sides and upper and lower sides of the first main supporting plate 1111a. Four wing plates may be formed on the first main supporting plate 1111a. In this case, the four wing plates are respectively disposed on respective lateral surfaces of the quadrangular first main supporting plate 1111a. The wing plate formed on the pixel forming plate may have substantially a quadrangular shape.

In addition, the second pixel forming plate 1113 includes a second main supporting plate 1113a, and third and fourth wing plates 1113b and 1113c. Like the first main supporting plate 1111a, the second main supporting plate 1113a is in a center area of the second pixel forming plate 1113. A thin film transistor, an organic light emitting element, and the like, are formed on the second main supporting plate 1113a. The second main supporting plate 1113a have substantially a quadrangular shape.

The third and fourth wing plates 1113b and 1113c are on lateral surfaces of the second pixel forming plate 1113, and are combined with bridges connecting pixel forming plates to each other. The third wing plate 1113b is on a lateral surface of the second main supporting plate 1113a to face the first wing plate 1111b of the first pixel forming plate 1111. The fourth wing plate 1113c is on the second main supporting plate 1113a and adjacent to the third wing plate 1113b.

In addition to the third and fourth wing plates 1113b and 1113c, an additional wing plate may be formed on the lateral surface of the second main supporting plate 1113a. As shown in FIG. 4, similar to the first main supporting plate 1111a, wing plates may be formed at right and left sides and upper and lower sides of the second main supporting plate 1113a. Four wing plates may be formed on the second main supporting plate 1113a. In this case, the four wing plates are disposed on respective lateral surfaces of the quadrangular second main supporting plate 1113a. The wing plate formed on the pixel forming plate may have substantially a quadrangular shape.

The third pixel forming plate 1115 include a third main supporting plate 1115a, and fifth and sixth wing plates 1115b and 1115c. Like the first main supporting plate 1111a, the third main supporting plate 1115a is in a center area of the third pixel forming plate 1115, and a thin film transistor, an organic light emitting element, and the like, are on the third main supporting plate 1115a. The third main supporting plate 1115a may have substantially a quadrangular shape.

The fifth and sixth wing plates 1115b and 1115c are on lateral surfaces of the third pixel forming plate 1115, and are

combined with bridges connecting pixel forming plates to each other. The fifth wing plate **1115b** is on a lateral surface of the third main supporting plate **1115a** to face the second wing plate **1111c** of the first pixel forming plate **1111**. The sixth wing plate **1115c** is on the third main supporting plate **1115a** and adjacent to the fifth wing plate **1115b**.

In addition to the fifth and sixth wing plates **1115b** and **1115c**, an additional wing plate may be formed on the lateral surface of the third main supporting plate **1115a**. As shown in FIG. 4, similar to the first main supporting plate **1111a**, wing plates may be formed at right and left sides and upper and lower sides of the third main supporting plate **1115a**. Four wing plates may be formed on the third main supporting plate **1115a**. In this case, the four wing plates are disposed on respective lateral surfaces of the quadrangular third main supporting plate **1115a**.

In one embodiment, the first wing plate **1111b** of the first pixel forming plate **1111** and the third wing plate **1113b** of the second pixel forming plate **1113** are connected by the first bridge **1131**. The first bridge **1131** is combined with the same side end portions of the first wing plate **1111b** and the third wing plate **1113b**.

The first bridge **1131** may have a curved shape, e.g., a bent shape. The first bridge **1131** may have a predetermined constant width. In one embodiment the first bridge **1131** may have a predetermined radius of curvature. In this case, the shape of the first bridge **1131** is modified when the substrate **100**, that is disposed below the first bridge **1131**, is stretched.

Referring to FIG. 6, when the substrate **100** is stretched, each of the pixel forming plates on the island IS of the substrate **100** is moved in one direction, and a shape of the first bridge **1131** connecting the first and second pixel forming plates **1111** and **1113** is modified. In this case, the radius of curvature of the first bridge **1131** increases so that the area of the base layer **110** may be expanded or a length thereof may extend in one direction.

Referring again to FIG. 4, the second wing plate **1111c** of the first pixel forming plate **1111** and the fifth wing plate **1115b** of the third pixel forming plate **1115** are connected by the second bridge **1133**. The second bridge **1133** is combined with the same side end portions of the second wing plate **1111c** and the fifth wing plate **1115b**.

Like the first bridge **1131**, the second bridge **1133** may be curved. In this case, the second bridge **1133** may have a predetermined width. In one embodiment, the second bridge **1133** may have a predetermined radius of curvature.

Like the first bridge **1131**, the shape of the second bridge **1133** is modified when the substrate **100**, that is disposed below the second bridge **1133**, is stretched. When the substrate **100** is stretched, the shape of the second bridge **1133** connecting the first and third pixel forming plates **1111** and **1115** is modified. In this case, the radius of curvature of the second bridge **1133** increases, so that the area of the base layer **110** may be expanded or the length thereof may extend in one direction.

In one embodiment, a first cut-out groove **30a** is formed in the first pixel forming plate **1111** to be adjacent to an area connected with the first bridge **1131**. For example, the first cut-out groove **30a** may be formed between the first pixel forming plate **1111** and the first bridge **1131**.

More specifically, the first cut-out groove **30a** may be formed between one side end portion of the second wing plate **1111c** of the first pixel forming plate **1111** and the first bridge **1131**. The first cut-out groove **30a** may prevent the base layer from being broken due to stress occurring between one side end portion of the second wing plate **1111c** and the first bridge **1131**.

In FIG. 4, if the first cut-out groove **30a** is not formed between the second wing plate **1111c** of the first pixel forming plate **1111** and the first bridge **1131**, and the same material as the second wing plate **1111c** and the first bridge **1131** is filled in a region of the first cut-out groove **30a**, the first bridge **1131** may be modified so that stress may be concentrated on the region. Accordingly, a crack may occur in the region. Further, a pixel laminated on the first pixel forming plate **1111** may be damaged.

In addition, a second cut-out groove **30b** is formed in the second pixel forming plate **1113** to be adjacent to an area connected with the first bridge **1131**. For example, the second cut-out groove **30b** may be formed between the second pixel forming plate **1113** and the first bridge **1131**.

More specifically, the second cut-out groove **30b** may be formed between one side end portion of the fourth wing plate **1113c** of the second pixel forming plate **1113** and the first bridge **1131**. Similar to the first cut-out groove **30a**, the second cut-out groove **30b** may prevent the base layer from being broken due to stress occurring between one side end portion of the fourth wing plate **1113c** and the first bridge **1131**.

In addition, similar to the first and second cut-out grooves **30a** and **30b** described above, a fourth cut-out groove **50b** may be formed in the first pixel forming plate **1111** to be adjacent to an area connected with the second bridge **1133**. Further, a third cut-out groove **50a** may be formed in the third pixel forming plate **1115** to be adjacent to an area connected with the second bridge **1133**.

Referring to FIG. 5, one pixel PX1, PX2, PX3, or PX4 may be formed on each of the pixel forming plates **1110** of the base layer. Each pixel PX1, PX2, PX3, or PX4 may include a plurality of subpixels, e.g., a red subpixel (R), a green subpixel (G), and blue subpixel (B).

FIG. 9 illustrates an embodiment of a pixel, or subpixel, in the OLED display.

FIG. 10 illustrates a layout embodiment of the pixel. FIG. 11 is a cross-sectional view of FIG. 10 taken along line XI-XI. FIG. 12 is a cross-sectional view of FIG. 10 taken along line XII-XII.

An equivalent circuit diagram of one pixel or subpixel, on each of the pixel forming plates **1110** will be described with reference to FIG. 9. The OLED display includes a plurality of signal lines **121**, **171**, and **172**, and subpixels connected thereto. In this case, the subpixels may be any one of a red pixel R, a green pixel G, and a blue pixel B. As described above, the pixel PX1, PX2, PX3, or PX4 each of the pixel forming plates **1110** may include a plurality of subpixels.

The signal lines include gate lines **121** for transmitting a scanning signal, data lines **171** for transmitting a data signal, a driving voltage line **172** for transmitting a driving voltage. The gate lines **121** substantially extend in a row direction and are nearly parallel to each other. The data lines **171** substantially extend in a column direction and are nearly parallel to each other. The driving voltage lines **172** are illustrated to substantially extend in the column direction, but may extend in the row or column direction or have a net-like shape.

A single subpixel includes a thin film transistor including a switching transistor T1 and a driving transistor T2, a storage capacitor Cst, and an organic light emitting element LD. One pixel PX, or subpixel, may include a thin film transistor and a capacitor to compensate a current supplied to the organic light emitting element LD.

The switching transistor T1 includes a control terminal N1, an input terminal N2, and an output terminal N3. The control terminal N1 is connected to the gate line **121**, the

input terminal N2 is connected to the data line 171, and the output terminal N3 is connected to the driving transistor T2.

The switching transistor T1 transmits the data signal from the data line 171 to the driving transistor T2 based on the scanning signal transmitted via the gate line 121.

The driving transistor T2 includes a control terminal N3, an input terminal N4, and an output terminal N5. The control terminal N3 is connected to the switching transistor T1, the input terminal N4 is connected to the driving voltage line 172, and the output terminal N5 is connected to the organic light emitting element LD. The driving transistor T2 outputs an output current I_d in an amount which varies according to a voltage applied between the control terminal N3 and the output terminal N5.

In this case, the capacitor Cst is connected between the control terminal N3 and the input terminal N4 of the driving transistor T2. The capacitor Cst is charged with a data signal applied to the control terminal N3 of the driving transistor T2, and maintains the data signal even after the switching transistor T1 is turned off.

For example, as an organic light emitting diode (OLED), the organic light emitting element LD has an anode connected to the output terminal N5 of the driving transistor T2 and a cathode connected to a common voltage Vss. The organic light emitting element LD emits light of varying intensities according to the output current I_d of the driving transistor T2.

The organic light emitting element LD may include an organic material that represents one or more primary colors, e.g., red, green, and blue. The OLED display displays a desired image with a spatial sum of these colors.

The switching transistor T1 and the driving transistor T2 are n-channel electric effect transistors (FETs), but at least one of them may be a p-channel FET. In addition, a connection relationship between the transistors T1 and T2, the capacitor Cst, and the organic light emitting element LD may be different in another embodiment.

The OLED display formed on each of the pixel forming plates 1110 will be described more fully with reference to FIGS. 10 to 12. As described above, the base layer 110 is on the substrate 100 and may include, for example, polyamide, polyamide, polyacrylates, or the like.

A buffer layer 120 is formed on the base layer 110. The buffer layer 120 may be formed as a single layer of a silicon nitride (SiN_x) or as a dual-layer in which a silicon nitride (SiN_x) and a silicon oxide (SiO_x) are laminated. The buffer layer 120 serves to flatten a surface while preventing permeation of unnecessary materials such as impurities or moisture.

A switching semiconductor layer 135a and a driving semiconductor layer 135b are formed on the buffer layer 120 and separated from each other. These semiconductor layers 135a and 135b may include, for example, polysilicon or an oxide semiconductor. The oxide semiconductor may include, for example, an oxide based on titanium (Ti), hafnium (Hf), zirconium (Zr), aluminum (Al), tantalum (Ta), germanium (Ge), zinc (Zn), gallium (Ga), tin (Sn), or indium (In), and complex oxides thereof such as zinc oxide (ZnO), indium-gallium-zinc oxide (InGaZnO_4), indium-zinc oxide (Zn—In—O), zinc-tin oxide (Zn—Sn—O), indium-gallium oxide (In—Ga—O), indium-tin oxide (In—Sn—O), indium-zirconium oxide (In—Zr—O), indium-zirconium-zinc oxide (In—Zr—Zn—O), indium-zirconium-tin oxide (In—Zr—Sn—O), indium-zirconium-gallium oxide (In—Zr—Ga—O), indium-aluminum oxide (In—Al—O), indium-zinc-aluminum oxide (In—Zn—Al—O), indium-tin-aluminum oxide (In—Sn—Al—O), indium-aluminum-gallium oxide

(In—Al—Ga—O), indium-tantalum oxide (In—Ta—O), indium-tantalum-zinc oxide (In—Ta—Zn—O), indium-tantalum-tin oxide (In—Ta—Sn—O), indium-tantalum-gallium oxide (In—Ta—Ga—O), indium-germanium oxide (In—Ge—O), indium-germanium-zinc oxide (In—Ge—Zn—O), indium-germanium-tin oxide (In—Ge—Sn—O), indium-germanium-gallium oxide (In—Ge—Ga—O), titanium-indium-zinc oxide (Ti—In—Zn—O), and hafnium-indium-zinc oxide (Hf—In—Zn—O).

When the semiconductor layers 135a and 135b include an oxide semiconductor material, a separate passivation layer may be added to protect the oxide semiconductor from environmental influences, e.g., high temperature or the like.

The semiconductor layers 135a and 135b include a channel region where impurities are not doped. Source and drain regions are at opposite sides of the channel region where the impurities are doped. The doped impurities may be different depending on the type of the thin film transistor and may, for example, include n-type or p-type impurities.

The switching semiconductor layer 135a and the driving semiconductor layer 135b are divided into channel regions 1355 and source and drain regions 1356 and 1357 respectively formed at opposite sides of the channel region 1355. The channel regions 1355 of the switching semiconductor layer 135a and the driving semiconductor layer 135b may include polysilicon that is not doped with the impurities, e.g., may be an intrinsic semiconductor.

The source and drain regions 1356 and 1357 of the switching semiconductor layer 135a and the driving semiconductor layer 135b may include polysilicon doped with conductive impurities, e.g., may be an impurity semiconductor.

A gate insulating layer 140 is on the switching semiconductor layer 135a and the driving semiconductor layer 135b. The gate insulating layer 140 may be a single layer or multiple layers including, for example, at least one of a silicon nitride or a silicon oxide.

A gate line 121, a driving gate electrode 125b, and a first capacitor electrode 128 are on the gate insulating layer 140. The gate line 121 extends in a horizontal direction and transmits a scan signal to a switching transistor T1. The gate line 121 includes a switching gate electrode 125a that protrudes toward switching semiconductor layer 135a.

The driving gate electrode 125b protrudes toward the driving semiconductor layer 135b from the first capacitor electrode 128. Each of the switching gate electrode 125a and the driving gate electrode 125b overlap the channel region 1355.

An interlayer insulating layer 160 is on the gate line 121, the driving gate electrode 125b, and the first capacitor electrode 128. The interlayer insulating layer 160 may include, for example, a silicon nitride, a silicon oxide, or the like, as is the gate insulating layer 140.

In the interlayer insulating layer 160 and the gate insulating layer 140, a source contact hole 61 and a drain contact hole 62 are formed to respectively expose the source region 1356 and the drain region 1357. A storage contact hole 63 is formed to expose some of the first capacitor electrode 128.

A data line 171 having a switching source electrode 176a, a driving voltage line 172 having a driving source electrode 176b and a second capacitor electrode 178, and a switching drain electrode 177a and a driving drain electrode 177b connected to the first capacitor electrode 128 are formed on the interlayer insulating layer 160.

The data line 171 transmits a data signal and extends to cross the gate line 121.

The driving voltage line **172** transmits a driving voltage and is separated from the data line to extend in the same direction as the data line **171**.

The switching source electrode **176a** protrudes toward the switching semiconductor layer **135a** from the data line **171**. The driving source electrode **176b** protrudes toward the driving semiconductor layer **135b** from driving voltage line **172**. Each of the switching source electrode **176a** and the driving source electrode **176b** is connected to the source region **1356** through the source contact hole **61**. The switching drain electrode **177a** faces the switching source electrode **176a**, and the driving drain electrode **177b** faces the driving source electrode **176b**.

Each of the switching drain electrode **177a** and the driving drain electrode **177b** is connected to the drain region **1357** through the drain contact hole **62**. The switching drain electrode **177a** is extended to be electrically connected to the first capacitor electrode **128** and the driving gate electrode **125b** through the contact hole **63** in the interlayer insulating layer **160**.

The second capacitor electrode **178** protrudes from the driving voltage line **172** to overlap the first capacitor electrode **128**. Accordingly, the first capacitor electrode **128** and the second capacitor electrode **178** form the storage capacitor **Cst1**, with the interlayer insulating layer **160** serving as a dielectric material.

The switching semiconductor layer **135a**, the switching gate electrode **125a**, the switching source electrode **176a**, and the switching drain electrode **177a** form a switching thin film transistor **T1**. Meanwhile, the driving semiconductor layer **135b**, the driving gate electrode **125b**, the driving source electrode **176b**, and the driving drain electrode **177b** form a driving thin film transistor **T2**. The switching thin film transistor **T1** and the driving thin film transistor **T2** correspond to switching elements.

A passivation layer **180** is formed on the switching source electrode **176a**, the driving source electrode **176b**, the switching drain electrode **177a**, and the driving drain electrode **177b**.

A pixel electrode **710** is formed on the passivation layer **180**. The pixel electrode **710** may include, for example, a transparent conductive material such as indium tin oxide (ITO), indium zinc oxide (IZO), zinc oxide (ZnO), indium oxide (In₂O₃), etc., or a reflective metal such as lithium, calcium, lithium fluoride/calcium, lithium fluoride/aluminum, aluminum, silver, magnesium, gold, etc.

The pixel electrode **710** is electrically connected to the driving drain electrode **177b** of the driving thin film transistor **T2** through a contact hole **181** in the interlayer insulating layer **160**, and becomes an anode of the organic light emitting element **70**.

A pixel definition layer **350** is formed on edge portions of the passivation layer **180** and the pixel electrode **710**. The pixel definition layer **350** includes an opening that exposes the pixel electrode **710**. The pixel definition layer **350** include a resin based on, for example, polyacrylates or polyimides, or a silica-based inorganic material.

An organic emission layer **720** is formed in the opening of the pixel definition layer **350**. The organic emission layer **720** may be formed with multiple layers including a hole-injection layer (HIL), a hole-transporting layer (HTL), an electron-transporting layer (ETL), and/or an an electron-injection layer. When all of the above layers are included, the HIL may be disposed on the pixel electrode **710** serving as the anode, and the HTL, the emission layer, the ETL, and the EIL may be sequentially laminated thereon.

The organic emission layer **720** may include a red organic emission layer emitting red light, a green organic emission layer emitting green light, and/or a blue organic emission layer emitting blue light. The red organic emission layer, the green organic emission layer, and the blue organic emission layer are respectively formed on a red pixel, a green pixel, and a blue pixel to implement a color image.

The red organic emission layer, the green organic emission layer, and the blue organic emission layer may be integrally laminated on the organic emission layer **720** together with the red pixel, the green pixel, and the blue pixel to respectively form a red color filter, a green color filter, and a blue color filter in each pixel, to thereby implement a color image.

In another embodiment, a white organic emission layer emitting white light is formed on all of the red pixel, the green pixel, and the blue pixel. A red color filter, a green color filter, and a blue color filter may be respectively formed for these pixels to implement a color image. When the color image is implemented using the white organic emission layer and the color filter, a deposition mask for depositing the red organic emission layer, the green organic emission layer, and the blue organic emission layer on individual pixels, that is, the red pixel, the green pixel, and the blue pixel, is not required.

In another embodiment, the white organic emission layer may be formed to have a single organic emission layer, and may further include a configuration in which a plurality of organic emission layers are laminated to emit white light. For example, a configuration in which at least one yellow organic emission layer and at least one blue organic emission layer are combined to emit white light, a configuration in which at least one cyan organic emission layer and at least one red organic emission layer are combined to emit white light, and a configuration in which at least one magenta organic emission layer and at least one green organic emission layer are combined to emit white light, may be further included.

A common electrode **730** is formed on the pixel definition layer **350** and the organic emission layer **720**. The common electrode **730** may include, for example, a transparent conductive material such as indium tin oxide (ITO), indium zinc oxide (IZO), zinc oxide (ZnO), indium oxide (In₂O₃), etc., or a reflective metal such as lithium, calcium, lithium fluoride/calcium, lithium fluoride/aluminum, aluminum, silver, magnesium, gold, etc. The common electrode **730** may be a cathode of the organic light emitting element **70**. The pixel electrode **710**, the organic emission layer **720**, and the common electrode **730** form the organic light emitting element **70**. An overcoat may be formed on the common electrode **730** to protect the organic light emitting element **70**.

In one embodiment, first to third wires **121**, **171**, and **172** are connected to the pixel **PX1**, **PX2**, **PX3**, and **PX4** on the pixel forming plates **1110**, and may be formed on the bridge **1130**. For example, a plurality of wires connected to the pixel **PX1**, **PX2**, **PX3**, and **PX4** may respectively extend to the pixel forming plates through the bridge.

Referring again to FIG. 5, the first wire **121** extends in the first direction through the pixel **PX1** on the first pixel forming plate **1111**. The first wire **121** is formed on the first bridge **1131** and may be connected to the pixel **PX2** of the second pixel forming plate **1113**. For example, the first wire **121** extends in the first direction through the first pixel forming plate **1111**, the first bridge **1131**, and the second pixel forming plate **1113**.

In one embodiment, the first wire **121** may correspond to the aforementioned gate line **121** for transmitting the scanning signal. In FIG. **10**, the gate line **121** substantially extends in the row direction and may correspond to the first wire **121**. For example, the gate lines **121** may be respectively connected to the pixels through the bridges connecting the pixel forming plates.

The second and third wires **171** and **172** extend in the second direction through the pixel **PX1** on the first pixel forming plate **1111** and may be formed on the second bridge **1133**. The second and third wires **171** and **172** may be connected to the pixel **PX3** of the third pixel forming plate **1115**. For example, the second and third wires **171** and **172** extend through the first pixel forming plate **1111**, the second bridge **1133**, and the third pixel forming plate **1115**.

In one embodiment, the second and third wires **171** and **172** may correspond to the aforementioned data line **171** for transmitting the data signal and the aforementioned driving voltage line **172** for transmitting the driving voltage, respectively. In FIG. **10**, the data line **171** and the driving voltage line **172** substantially extend in the column direction and may correspond to the second and third wires **171** and **172**, respectively. For example, the data line **171** and the driving voltage line **172** may be respectively connected to the pixels through the bridges connecting the pixel forming plates.

FIG. **7** illustrates an example of strain in area B of FIG. **6**, and FIG. **8** is a graph illustrating an example of a variation of strain according to positions of a bridge. More specifically, FIG. **7** sets forth an example results for measuring strain occurring in a region of the first bridge **1131** when the first and second pixel forming plates **1111** and **1113** move in opposite side directions. FIG. **8** sets forth results for measuring the strain on the first bridge **1131** along a d-axis corresponding to an external circumference direction based on a reference point S.

Referring to FIG. **7**, when the first and second pixel forming plates **1111** and **1113** move in opposite side directions, the strain occurring in the first bridge **1131** varies depending on position. The strain is a measure of the rate (%) of length variation per unit length. For example, respective areas a, b, c, and d in FIG. **7** are those where the strain is equal, and strain decreases from the area a toward the area b, the area c, and the area d.

The strain on the first bridge **1131** increases closer to the reference point S. That is, the strain increases closer to a center of the first bridge **1131** based on a predetermined radius of curvature. For example, based on a center line through a center of width of the first bridge **1131**, strain on an inner side of the center line is greater than on an outer side thereof.

Referring to FIG. **8**, the strain rapidly decreases closer to the outer side along the d-axis based on the reference point S in FIG. **7**.

Based on the measured results in FIGS. **7** and **8**, when the first and second pixel forming plates **1111** and **1113** move in opposite side directions, greater modification occurs in the inner side than the outer side in the first bridge **1131**. Accordingly, the first wire **121** formed on the bridge **1130** may be disposed at the outer side of the bridge **1130** based on the center line.

Referring to FIG. **13**, the first wires **121** may be disposed at the outer side of a center line CL based on the center line CL through the center of the width of the first bridge **1131**. As described above, since the first wires **121** are disposed at the outer side in which strain is relatively small, the first wire

121 may be prevented from being cut or cracked due to repetitive moving of the first and second pixel forming plates **1111** and **1113**.

In one embodiment, the first wires **121** may be uniformly disposed in the bridge **1130**. However, dummy wires **800** may be in the inner side of the center line CL. In this case, strain on the dummy wire **800** may be greater than that on the first wire **121**.

Referring to FIGS. **14** and **15**, the dummy wires **800** may be above or below of the first wires **121** in the inner side of the center line CL. For example, as shown in FIG. **14**, the first wires **121** may be uniformly laminated, and a dummy wire **800** may be additionally laminated on the first wires **121** in the inner side of the center line CL. Further, as shown in FIG. **15**, the dummy wires **800** are laminated in the inner side of the center line CL, and the first wires **121** may be uniformly laminated above the dummy wires **800**.

In one embodiment, the first wires **121** may be uniformly above the bridge **1130**. However, as shown in FIG. **16**, dummy wires **800** may be additionally disposed in center areas of the bridge **1130**. Length of the dummy wires **800** become shorter from the inner side of the bridge **1130** toward the outer side thereof. Further, strain on the dummy wire **800** is greater than that on the first wire **121**. The inner side of the bridge **1130** is an area in which a center of a curvature radius of a curved bridge **1130** is positioned, and the outer side of the bridge **1130** is a remaining area except for the center area.

In one embodiment, among the second and third wires **171** and **172** on the bridge **1130**, a wire that has relatively small strain is in the outer side of the center line CL. Further, among the second and third wires **171** and **172**, a wire that has relatively greater strain is in the inner side of the center line CL. Accordingly, since the wire with the relatively greater strain is disposed in the inner side of the center line CL and the wire with the relatively small strain is disposed in the outer side of the center line CL, the second and third wires **171** and **172** may be prevented from being cut or cracked due to repetitive moving of the first and second pixel forming plates **1111** and **1113**.

For example, referring to FIG. **17**, the second wires **171** may be disposed in the inner side of the center line CL, and the third wire **172** may be disposed in the outer side of the center line CL. In one embodiment, the second and third wires **171** and **172** respectively correspond to the data line **171** and the driving voltage line **172**. The second wire **171** may include a metal with strain greater than that of the third wire **172**.

In one embodiment, a sensing thin film transistor **900** for measuring strain of the first to third wires **121**, **171**, and **172** on the bridge **1130** may be disposed on the pixel forming plates **1110**. For example, referring to FIG. **18**, the sensing thin film transistor **900** may be connected to the second wire **171** to measure resistance of the second wire **171**, in order to detect strain on second wire **171**. The sensing thin film transistor **900** may be, for example, a sensing thin film transistor for measuring resistance of metal.

FIGS. **19**, **20**, and **21** are examples of layout views of subpixels on pixel forming plates. As described above, the pixel PX on each of the pixel forming plates **1110** may include a plurality of subpixels. In this case, a red subpixel (R), a green subpixel (G), and a blue subpixel (B) may be disposed in various forms in each pixel PX. In another embodiment, at least one pixel PX may be formed on each of the pixel forming plates, e.g., a plurality of pixels PX including red, green, and blue subpixels may be formed on each of the pixel forming plates.

Referring to FIG. 19, the green subpixel (G) is at the center of the pixel forming plate 1110 and extends in the second direction. The blue and red subpixels B and R may be disposed at opposite sides of the green subpixel (G).

Referring to FIG. 20, a pair of green subpixels G may be spaced apart from each other at a predetermined angle with the first direction. The blue and red subpixels B and R may be symmetrical to the pair of green subpixels G based on the second direction.

Referring to FIG. 21, the first blue and red subpixels B1 and R may be spaced apart from each other in the first direction. The green and second blue subpixels G and B2 may be spaced apart from each other in the second direction. In one embodiment, the first and second blue subpixels B1 and B2 may emit light having different wavelengths.

FIG. 22 is a top plan view of a base layer of another embodiment of an OLED display. Referring to FIG. 22, the OLED display is different from the OLED display of the aforementioned embodiment in terms of the structure of the base layer.

As shown in FIG. 4, the first bridge 1131 is upwardly curved along the second direction in the OLED display of the aforementioned embodiment. Further, the first bridge 1131 connecting the first pixel forming plate 1111 and the second pixel forming plate 1113 are connected to the first wing plate 1111b and the third wing plate 1113b.

However, as shown in FIG. 22, in present embodiment, a first bridge 1131" is downwardly curved along the second direction. Here, the upward and downward curves of the second direction are conceptual positions applied to FIGS. 4 and 22 to differentiate between curved shapes of the first bridge. In this case, the upward curve of the second direction represents a direction from first pixel forming plates 1111 and 1111" toward third pixel forming plates 1115 and 1115". The downward curve of the second direction represents a direction from the third pixel forming plates 1115 and 1115" toward the first pixel forming plates 1111 and 1111".

Configurations of the first to third pixel forming plates 1111", 1113", and 1115" may be the same as those of the first to third pixel forming plates 1111, 1113, and 1115 of the aforementioned embodiment. Also, like the aforementioned embodiment, the first bridge 1131" may have a predetermined width. Further, the first bridge 1131" may be bent to a predetermined curvature radius.

Referring to FIG. 22, the first bridge 1131" is connected to the second wing plate 1111c" of the first pixel forming plate 1111" and the fourth wing plate 1113c" of the second pixel forming plate 1113". The first bridge 1131c" is combined with end portions of the second wing plates 1111c" and the fourth wing plate (1113c") facing each other. For example, the second wing plate 1111c" is on an upper portion of a quadrangular first main supporting plate 1111a", and the fourth wing plate 1113c" is on an upper portion of a quadrangular second main supporting plate 1113a". The first bridge 1131c" downwardly curved along the second direction is combined with each of the end portions of the second wing plate 1111c" and the fourth wing plate 1113c" facing each other.

In this embodiment, a first cut-out groove 30a" is formed in the first pixel forming plate 1111" to be adjacent to an area connected with the first bridge 1131". For example, the first cut-out groove 30a" may be between the first pixel forming plate 1111" and the first bridge 1131". For example, the first cut-out groove 30a" is between one side end portion of the second wing plate 1111c" of the first pixel forming plate 1111" and the first bridge 1131". The first cut-out groove 30a" may prevent the base layer from being broken due to

stress occurring between one side end portion of the first wing plate 1111b" and the first bridge 1131".

In FIG. 22, if the first cut-out groove 30a" is not formed between the first wing plate 1111b" of the first pixel forming plate 1111" and the first bridge 1131", and the same material as the first wing plate 1111b" and the first bridge 1131" is filled in a region of the first cut-out groove 30a", the first bridge 1131" may be modified so that stress may be concentrated on the region. Accordingly, a crack may occur in the region. Further, a pixel laminated on the first pixel forming plate 1111" may be damaged.

In addition, a second cut-out groove 30b" is formed in the second pixel forming plate 1113" to be adjacent to an area connected with the first bridge 1131". For example, the second cut-out groove 30b" may be between the second pixel forming plate 1113" and the first bridge 1131". For example, the second cut-out groove 30b" is between one side end portion of the third wing plate 1113b" of the second pixel forming plate 1113" and the first bridge 1131". Similar to the first cut-out groove 30a", the second cut-out groove 30b" may prevent the base layer from being broken due to stress occurring between one side end portion of the third wing plate 1113c" and the first bridge 1131".

In addition, similar to the first and second cut-out grooves 30a" and 30b" described above, a fourth cut-out groove 50b" may be formed in the first pixel forming plate 1111" to be adjacent to an area connected with the second bridge 1133". Further, a third cut-out groove 50a" may be formed in the third pixel forming plate 1115" to be adjacent to an area connected with the second bridge 1133".

FIG. 23 is a top plan view of a base layer of another embodiment of an OLED display. FIG. 24 illustrates an enlarged view of area C in FIG. 23. FIG. 25 illustrates an example of first to third wires connected to respective pixels on the base layer in FIG. 24. In FIGS. 23 to 25, the OLED display is different from the OLED display of the aforementioned initial embodiment in terms of the structure of the base layer.

As shown in FIG. 4, in the OLED display of the aforementioned initial embodiment, the cut-out grooves 30a, 30b, 50a, 50b are formed in the pixel forming plates 1111, 1113, and 1115 to be adjacent to an area connected with the bridge 1131 and 1133. However, in the OLED display of the present embodiment, as shown in FIGS. 23 and 24, a cut-out groove is not formed in the pixel forming plates 1111', 1113', 1115' to be adjacent to the area connected to the bridge 1131' and 1133'. That is, the OLED display of this embodiment is different in terms of whether the cut-out groove is formed in the base layer or not.

According to the second embodiment described above, the first and second pixel forming plates 1111' and 1113' are arranged in the first direction. Further, the first and third pixel forming plates 1111' and 1115' are arranged in the second direction. In this case, the first and second pixel forming plates 1111' and 1113' are connected by the first bridge 1131', and the first and third pixel forming plates 1111', 1115' are connected by the second bridge 1133'.

For example, the first pixel forming plate 1111' includes a first main supporting plate 1111a', and first and second wing plates 1111b' and 1111c'.

The first main supporting plate 1111a' may have a substantially quadrangular shape in a center area of the first pixel forming plate 1111'. Further, the first and second wing plates 1111b' and 1111c' are formed in a lateral surface of the first pixel forming plate 1111', and are combined with the bridge connecting the pixel forming plates to each other. The second wing plate 1111c' is disposed in the first main

supporting plate **1111a'** to be adjacent to the first wing plate **1111b'**. In FIG. 24, a dotted line shown between the first main supporting plate **1111a''** and the first and second wing plates **1111b''** and **1111c''** is a virtual line to distinguish between the main supporting plate and the wing plate.

In this case, the first and second wing plates **1111b'** and **1111c'** disposed in the lateral surface of the first pixel forming plate **1111'** may be formed to have a substantially triangular shape. As shown in FIG. 24, since the first and second wing plates **1111b'** and **1111c'** are formed to have a triangular shape, a cut-out groove is not formed between the first bridge **1131'** and the second wing plate (**1111c'**).

Similar to the aforementioned first pixel forming plate **1111'**, the wing plates of the second and third pixel forming plates **1113'** and **1115'** are also formed to have a triangular shape, and a cut-out groove is not formed between the second and third pixel forming plates **1113'** and **1115'** and the bridge.

Referring to FIG. 25, in the present embodiment, first to third wires **121'**, **171'**, and **172'** connected to pixels **PX1'**, **PX2'**, **PX3'**, and **PX4'** formed on the pixel forming plates **1110'** may be formed on bridges **1131'**, **1133'**, and **1135'**. For example, in the same way as the first embodiment, a plurality of wires connected to the pixels **PX1'**, **PX2'**, **PX3'**, and **PX4'** may extend to the pixel forming plates through the bridges **1131'**, **1133'**, and **1135'**, respectively.

For example, first wires **121'**, extended in the first direction through the pixel **PX1'** formed on the first pixel forming plate **1111'**, are formed on the first bridge **1131'**. Further, the first wires **121'** may be connected to the pixel **PX2'** of the second pixel forming plate **1113'**. For example, the first wires **121'** are formed to extend in the first direction through the first pixel forming plate **1111'**, the first bridge **1131'**, and the second pixel forming plate **1113'**.

Second and third wires **171'** and **172'**, extended in the second direction through the pixel **PX1'** formed on the first pixel forming plate **1111'**, are formed on the second bridge **1133'**. Further, the second and third wires **171'** and **172'** may be connected to the pixel **PX3'** of the third pixel forming plate **1115'**. For example, the second and third wires **171'** and **172'** are formed to extend through the first pixel forming plate **1111'**, the second bridge **1133'**, and the third pixel forming plate **1115'**.

In the present embodiment, the first to third wires **121'**, **171'**, and **172'** through the first or second bridge **1131'** or **1133'** may be disposed in the first or second bridge **1131'** or **1133'** in the same way as the embodiment in FIG. 13 to FIG. 17. Since the first to third wires **121'**, **171'**, and **172'** are disposed in the aforementioned structure, the first to third wires **121'**, **171'**, and **172'** may be prevented from being cut or cracked due to repetitive moving of the first to third pixel forming plates **1111'**, **1113'**, and **1115'**.

Example embodiments have been disclosed herein, and although specific terms are employed, they are used and are to be interpreted in a generic and descriptive sense only and not for purpose of limitation. In some instances, as would be apparent to one of skill in the art as of the filing of the present application, features, characteristics, and/or elements described in connection with a particular embodiment may be used singly or in combination with features, characteristics, and/or elements described in connection with other embodiments unless otherwise indicated. Accordingly, it will be understood by those of skill in the art that various changes in form and details may be made without departing from the spirit and scope of the invention as set forth in the following claims.

What is claimed is:

1. A display device, comprising:

a plurality of pixel forming plates spaced apart from each other; and

first and second pixels on respective first and second pixel forming plates of the plurality of pixel forming plates adjacent in a first direction, the first and second pixel forming plates connected by a first bridge, wherein a portion of the first pixel forming plate adjacent to the first bridge has a curved side.

2. The display device as claimed in claim 1, wherein a portion of the second pixel forming plate adjacent to the first bridge has a curved side.

3. The display device as claimed in claim 1, wherein each of the first pixels and the second pixels includes a plurality of subpixels.

4. The display device as claimed in claim 3, wherein at least one of the plurality of subpixels has a rhombus shape.

5. The display device as claimed in claim 1, wherein each of the first pixels and the second pixels includes a plurality of subpixels having different sizes.

6. The display device as claimed in claim 1, wherein each of the first pixels and the second pixels includes three subpixels, two of which have a same size and the other of which has a size different from the two subpixels.

7. The display device as claimed in claim 6, wherein the two subpixels have a square shape and the other subpixel has a rectangular shape.

8. The display device as claimed in claim 1, wherein the first bridge is upwardly or downwardly curved along the second direction.

9. The display device as claimed in claim 1, wherein the first pixel forming plate includes:

a first main supporting plate;

a first wing plate at one lateral surface of the first main supporting plate, wherein one side end portion of the first wing plate is connected to the first bridge;

a second wing plate at another lateral surface of the first main supporting plate and adjacent to the one side end portion of the first wing plate; and

a first cut-out groove between one side end portion of the second wing plate and the first bridge.

10. The display device as claimed in claim 9, wherein the second pixel forming plate includes:

a second main supporting plate;

a third wing plate at one lateral surface of the second main supporting plate to face the first wing plate of the first pixel forming plate, one side end portion of the third wing plate connected to the first bridge;

a fourth wing plate at another lateral surface of the second main supporting plate and adjacent to the one side end portion of the third wing plate; and

a second cut-out groove between one side end portion of the fourth wing plate and the first bridge.

11. The display device as claimed in claim 1, further comprising:

a base layer including:

a third pixel forming plate adjacent to the first pixel forming plate in the second direction;

a third pixel on the third pixel forming plate; and

a second bridge connecting the first and third pixel forming plates.

12. The display device as claimed in claim 11, further comprising:

a plurality of first to third wires on the first pixel forming plate and connected to the first pixel, wherein the first

19

wires are connected to a second pixel of the second pixel forming plate through an upper side of the first bridge.

13. The display device as claimed in claim 12, wherein the first wires extend in a length direction of the first bridge and are disposed in an outer side of a center line of the first bridge passing through a center of the first bridge.

14. The display device as claimed in claim 12, further comprising:

a plurality of dummy wires on the first bridge and disposed above or below the first wires to overlap a portion of the first wires, wherein strain on the dummy wires is greater than that on the first wires.

15. The display device as claimed in claim 14, wherein the dummy wires extend in a length direction of the first bridge and are disposed in an inner side of a center line of the first bridge passing through a center of the first bridge.

20

16. The display device as claimed in claim 15, wherein lengths of the dummy wires decrease from an inner side of the first bridge toward an outer side thereof.

17. The display device as claimed in claim 12, further comprising:

a sensing thin film transistor on the respective pixel forming plates and connected to at least one of the first to third wires to measure strain on the at least one of the first to third wires.

18. The display device as claimed in claim 12, wherein the first wires include a plurality of gate lines.

19. The display device as claimed in claim 12, wherein the second wires include a plurality of data lines and the third wires include a plurality of driving voltage lines.

20. The display device as claimed in claim 1, wherein each of the pixel forming plates has substantially a polygonal shape.

* * * * *

专利名称(译)	有机发光二极管显示器		
公开(公告)号	US10644079	公开(公告)日	2020-05-05
申请号	US16/105361	申请日	2018-08-20
[标]申请(专利权)人(译)	三星显示有限公司		
申请(专利权)人(译)	三星DISPLAY CO. , LTD.		
当前申请(专利权)人(译)	三星DISPLAY CO. , LTD.		
[标]发明人	HONG JONG HO CHOI WON IL JOO HYE JIN PARK WON SANG KIM MU GYEOM MYEONG MAN SIK YOON HYO YUL		
发明人	HONG, JONG HO CHOI, WON IL JOO, HYE JIN PARK, WON SANG KIM, MU GYEOM MYEONG, MAN SIK YOON, HYO YUL		
IPC分类号	H01L27/32 H01L51/00 H01L29/08		
CPC分类号	H01L27/3218 H01L27/326 H01L27/3223 H01L27/3276 H01L51/0097 Y02E10/549 H01L2251/5338 H01L29/08 G09F9/33 G09G3/3208 G09G3/3225 H01L27/32 H01L27/3246 H01L2227/32		
审查员(译)	NGUYEN , THINH T		
优先权	1020150033419 2015-03-10 KR 15/064917 2017-10-24 US		
其他公开文献	US20180358418A1		
外部链接	Espacenet		

摘要(译)

有机发光二极管显示器包括可拉伸基板，多个像素形成板，第一和第二像素以及切出凹槽。像素形成板在基板上并且彼此间隔开。第一和第二像素在沿第一方向相邻的多个像素形成板中的相应的第一和第二像素形成板上。第一和第二像素形成板通过第一桥连接。切口槽在第一像素形成板和第二像素形成板中并且邻近连接到第一桥的区域。

