



US008735900B2

(12) **United States Patent**
Yamazaki et al.

(10) **Patent No.:** **US 8,735,900 B2**
(45) **Date of Patent:** **May 27, 2014**

(54) **EL DISPLAY DEVICE**

Nov. 26, 1999 (JP) 11-336247
Nov. 26, 1999 (JP) 11-336248

(71) Applicant: **Semiconductor Energy Laboratory Co., Ltd.**, Kanagawa-ken (JP)

(51) **Int. Cl.**
H01L 29/04 (2006.01)

(72) Inventors: **Shunpei Yamazaki**, Tokyo (JP);
Mayumi Mizutami, Kanagawa (JP);
Toshimitsu Konuma, Kanagawa (JP)

(52) **U.S. Cl.**
USPC **257/72**; 257/59; 257/E21.141; 257/E21.143;
257/E51.022

(73) Assignee: **Semiconductor Energy Laboratory Co., Ltd.** (JP)

(58) **Field of Classification Search**
USPC 257/59, 72, E21.141, E21.143, E51.022
See application file for complete search history.

(*) Notice: Subject to any disclaimer, the term of this patent is extended or adjusted under 35 U.S.C. 154(b) by 0 days.

(56) **References Cited**

U.S. PATENT DOCUMENTS

4,357,557 A 11/1982 Inohara et al.
5,072,263 A 12/1991 Watanabe et al.

(Continued)

(21) Appl. No.: **13/899,893**

(22) Filed: **May 22, 2013**

FOREIGN PATENT DOCUMENTS

(65) **Prior Publication Data**
US 2013/0313558 A1 Nov. 28, 2013

EP 0 776 147 A1 5/1997
EP 0 809 420 A1 11/1997

(Continued)

Related U.S. Application Data

(63) Continuation of application No. 13/475,523, filed on May 18, 2012, now Pat. No. 8,450,745, which is a continuation of application No. 13/117,319, filed on May 27, 2011, now Pat. No. 8,183,571, which is a continuation of application No. 12/418,749, filed on Apr. 6, 2009, now Pat. No. 7,952,103, which is a continuation of application No. 11/070,121, filed on Mar. 1, 2005, now Pat. No. 7,518,146, which is a continuation of application No. 10/206,018, filed on Jul. 26, 2002, now Pat. No. 6,894,312, which is a continuation of application No. 09/661,022, filed on Sep. 13, 2000, now Pat. No. 6,445,005.

European Search Report re application No. EP 00119584.1, dated Mar. 12, 2004.

(Continued)

Primary Examiner — Andy Huynh

(74) *Attorney, Agent, or Firm* — Husch Blackwell LLP


(30) **Foreign Application Priority Data**

Sep. 17, 1999 (JP) 11-264672
Sep. 17, 1999 (JP) 11-264680

(57) **ABSTRACT**

A plurality of pixels are arranged on the substrate. Each of the pixels is provided with an EL element which utilizes as a cathode a pixel electrode connected to a current control TFT. On a counter substrate, a light shielding film, a first color filter having a first color and a second color filter having a second color are provided. The second color is different from the first color.

18 Claims, 13 Drawing Sheets



(56)

References Cited

U.S. PATENT DOCUMENTS

5,107,175 A 4/1992 Hirano et al.
 5,124,204 A 6/1992 Yamashita et al.
 5,189,405 A 2/1993 Yamashita et al.
 5,190,794 A 3/1993 Yoshino et al.
 5,206,749 A 4/1993 Zavracky et al.
 5,317,236 A 5/1994 Zavracky et al.
 5,518,940 A 5/1996 Hodate et al.
 5,541,119 A 7/1996 Kodama
 5,610,738 A 3/1997 Sasano et al.
 5,617,228 A 4/1997 Watanabe et al.
 5,643,826 A 7/1997 Ohtani et al.
 5,654,811 A 8/1997 Spitzer et al.
 5,670,205 A 9/1997 Miyazaki et al.
 5,686,360 A 11/1997 Harvey, III et al.
 5,693,956 A 12/1997 Shi et al.
 5,708,484 A 1/1998 Someya et al.
 5,729,308 A 3/1998 Yamazaki et al.
 5,757,126 A 5/1998 Harvey, III et al.
 5,763,899 A 6/1998 Yamazaki et al.
 5,771,562 A 6/1998 Harvey, III et al.
 5,798,744 A 8/1998 Tanaka et al.
 5,811,177 A 9/1998 Shi et al.
 5,828,429 A 10/1998 Takemura
 5,859,627 A 1/1999 Hoshiya et al.
 5,869,929 A 2/1999 Eida et al.
 5,882,761 A 3/1999 Kawami et al.
 5,909,081 A 6/1999 Eida et al.
 5,920,080 A 7/1999 Jones
 5,923,962 A 7/1999 Ohtani et al.
 5,929,948 A 7/1999 Ohori et al.
 5,943,107 A 8/1999 Kadota et al.
 5,952,778 A 9/1999 Haskal et al.
 5,956,063 A 9/1999 Yokoi et al.
 5,962,962 A 10/1999 Fujita et al.
 6,049,167 A 4/2000 Onitsuka et al.
 6,072,450 A 6/2000 Yamada et al.
 6,104,137 A 8/2000 Abiko et al.
 6,111,355 A 8/2000 Inoue et al.
 6,114,183 A 9/2000 Hamada et al.
 6,114,715 A 9/2000 Hamada
 6,128,060 A 10/2000 Shimada et al.
 6,146,225 A 11/2000 Sheats et al.
 6,150,187 A 11/2000 Zyung et al.
 6,175,186 B1 1/2001 Matsuura et al.
 6,177,965 B1 1/2001 Takahara et al.
 6,181,062 B1 1/2001 Hiraishi et al.
 6,198,217 B1 3/2001 Suzuki et al.
 6,198,220 B1 3/2001 Jones et al.
 6,198,517 B1 3/2001 Ohori et al.
 6,268,071 B1 7/2001 Yasukawa et al.
 6,274,887 B1 8/2001 Yamazaki et al.
 6,284,342 B1 9/2001 Ebisawa et al.
 6,344,712 B1 2/2002 Eida et al.
 6,362,030 B1 3/2002 Nagayama et al.
 6,373,453 B1 4/2002 Yudasaka
 6,384,528 B1 5/2002 Friend et al.
 6,392,340 B2 5/2002 Yoneda et al.
 6,413,645 B1 7/2002 Graff et al.
 6,417,896 B1 7/2002 Yamazaki et al.
 6,417,898 B1 7/2002 Izumi
 6,466,281 B1 10/2002 Huang et al.
 6,498,428 B1 12/2002 Matsuura et al.
 6,525,791 B1 2/2003 Tsuda et al.
 6,577,375 B1 6/2003 Umehara et al.
 6,580,214 B2 6/2003 Yoneda et al.
 6,593,691 B2 7/2003 Nishi et al.
 6,642,989 B2 11/2003 Umehara et al.
 6,914,642 B2 7/2005 Yamazaki et al.
 6,977,394 B2 12/2005 Yamazaki et al.
 6,982,768 B2 1/2006 Ohori et al.
 7,952,103 B2 5/2011 Yamazaki et al.
 2001/0004190 A1 6/2001 Nishi et al.

2001/0026127 A1 10/2001 Yoneda et al.
 2002/0021087 A1 2/2002 Eida et al.
 2002/0036463 A1 3/2002 Yoneda et al.
 2002/0075207 A1 6/2002 Yudasaka
 2002/0125817 A1 9/2002 Yamazaki et al.
 2003/0155573 A1 8/2003 Yamazaki et al.
 2003/0206144 A1 11/2003 Yudasaka
 2008/0036699 A1 2/2008 Yudasaka
 2009/0303165 A1 12/2009 Yudasaka
 2010/0045577 A1 2/2010 Yudasaka

FOREIGN PATENT DOCUMENTS

EP 0 845 770 A1 6/1998
 EP 0 845 812 A2 6/1998
 EP 0 884 930 A1 12/1998
 EP 0 892 589 A1 1/1999
 EP 0 940 796 A1 9/1999
 EP 0 999 595 A2 5/2000
 EP 1 524 696 A2 4/2005
 EP 1 773 103 A2 4/2007
 JP 59-055487 A 3/1984
 JP 61-96695 5/1986
 JP 62-90260 4/1987
 JP 62-290096 A 12/1987
 JP 3-2592 U 1/1991
 JP 5-241201 9/1993
 JP 7-28092 1/1995
 JP 7-130652 5/1995
 JP 7-220871 8/1995
 JP 8-75908 3/1996
 JP 8-96959 4/1996
 JP 8-222369 8/1996
 JP 8-234018 9/1996
 JP 8-321380 12/1996
 JP 8-330602 12/1996
 JP 9-63770 3/1997
 JP 9-134781 5/1997
 JP 9-148066 6/1997
 JP 9-230362 9/1997
 JP 10-107266 4/1998
 JP 10-116687 5/1998
 JP 10-161563 6/1998
 JP 10-161564 6/1998
 JP 10-162952 6/1998
 JP 10-162958 6/1998
 JP 10-189252 7/1998
 JP 10-214043 8/1998
 JP 10-241857 9/1998
 JP 10-247587 9/1998
 JP 10-270363 10/1998
 JP 10-289784 10/1998
 JP 10-319910 A 12/1998
 JP 11-26156 1/1999
 JP 11-54273 2/1999
 JP 11-65487 3/1999
 JP 11-76967 3/1999
 JP 11-121763 4/1999
 JP 11-231805 8/1999
 JP 11-251059 9/1999
 JP 2000-77191 3/2000
 JP 2000-173766 6/2000
 WO WO 96/34514 A1 10/1996
 WO WO 97/31508 A1 8/1997
 WO WO 98/59528 A1 12/1998
 WO WO 99/42983 A1 8/1999

OTHER PUBLICATIONS

European Examination Report re application No. EP 00119584.1, dated Mar. 2, 2006.
 Office Action re U.S. Appl. No. 10/337,886, dated Dec. 4, 2003.
 Office Action re Japanese application No. JP 2000-281054, dated Nov. 24, 2010 (with English translation).
 European Search Report re application No. EP 10177425.5, dated Feb. 28, 2012.




Fig. 1







Fig.2





300: glass substrate 301: base film 302: crystalline silicon film 303: protecting film 304a-304b: resist mask
 305, 306: n-type impurity regions (b) 307-310: active layers 311: gate insulating film 312-316: gate electrodes




Fig. 5A




Fig. 5B




Fig. 5C




Fig. 5D

317-323:n-type impurity regions(c) 324a-324d,332:resist mask 325-331:n-type impurity regions(a)
333,334:p-type i(a) 335:gate wiring




Fig. 6A




Fig. 6B




Fig. 6C

p-channel type TFT n-channel type TFT 205

336: first interlayer insulating film 337-340: source wiring lines 341-343: drain wiring lines
344: first passivation film 345: second interlayer insulating film 346, 347: pixel electrodes
348: alkaline compound 349: EL layer 350: anode 351: second passivation film

Fig.7




Fig.8




Fig.9




Fig.10




Fig.11A





Fig.11B

Fig.12




Fig.13




Fig.14A




Fig.14B




Fig.14C




Fig.14D




Fig.14E




Fig.14F




Fig.15A




Fig.15B




Fig.16A





Fig.16B



1

EL DISPLAY DEVICE

This application is a continuation of U.S. application Ser. No. 13/475,523, filed on May 18, 2012 which is a continuation of U.S. application Ser. No. 13/117,319, filed on May 27, 2011 (now U.S. Pat. No. 8,183,571 issued May 22, 2012) which is a continuation of U.S. application Ser. No. 12/418,749, filed on Apr. 6, 2009 (now U.S. Pat. No. 7,952,103 issued May 31, 2011) which is a continuation of U.S. application Ser. No. 11/070,121, filed on Mar. 1, 2005 (now U.S. Pat. No. 7,518,146 issued Apr. 14, 2009) which is a continuation of U.S. application Ser. No. 10/206,018, filed on Jul. 26, 2002 (now U.S. Pat. No. 6,894,312 issued May 17, 2005) which is a continuation of U.S. application Ser. No. 09/661,022 filed on Sep. 13, 2000 (now U.S. Pat. No. 6,445,005 issued Sep. 3, 2002), all of which are incorporated herein by reference.

BACKGROUND OF THE INVENTION

1. Field of the Invention

The present invention relates to an EL (Electro-luminescence) display device formed by fabricating a semiconductor device (a device utilizing a semiconductor thin film; typically a thin film transistor) on a substrate, and an electronic device having such an EL display device as a display portion.

2. Description of the Related Art

A technique for forming a thin film transistor (hereinafter referred to as the TFT) on a substrate has been significantly improved in these days, and development for application thereof to an active matrix type display device has continued. In particular, a TFT utilizing a polysilicon film has a field effect mobility higher than that obtainable in a TFT utilizing a conventional amorphous silicon film, thereby realizing an operation at higher speed. Thus, it becomes possible to control pixels by a driving circuit formed on the identical substrate on which the pixels are formed, which is different from the conventional case in which the pixels are controlled by a driving circuit formed in the outside of the substrate.

Such an active matrix type display device has drawn much attention thereto since the device can realize various advantages, such as reduction in manufacturing cost, down-sizing of a display device, an improved yield, a reduced throughput or the like, by fabricating various circuits and devices on one and the same substrate.

In an active matrix EL display device, each pixel is provided with a switching device made of a TFT, and a driving device for controlling a current is activated by the switching device to cause an EL layer (more strictly speaking, a light emitting layer) to emit light. The EL display device is disclosed, for example, in Japanese Laid-open Patent Publication No. Hei 10-189252.

Thus, the present invention is intended to provide an inexpensive EL display device capable of displaying an image with high definition. Furthermore, the present invention is also intended to provide an electronic device having a high recognizability of a display portion by utilizing such an EL display device as the display portion.

SUMMARY OF THE INVENTION

The present invention will be described with reference to FIG. 1. In FIG. 1, reference numeral 101 denotes a substrate having an insulating surface. As the substrate 101, an insulating substrate such as a quartz substrate can be used. Alternatively, various kinds of substrate, such as a glass substrate, a semiconductor substrate, a ceramic substrate, a crystallized

2

substrate, a metal substrate, or a plastic substrate, can be used by providing an insulating film on a surface thereof.

On the substrate 101, pixels 102 are formed. Although only three of the pixels are illustrated in FIG. 1, a higher number of pixels are actually formed in matrix. In addition, although one of these three pixels will be described below, the other pixels have the same structure.

In each of the pixels 102, two TFTs are formed; one of them is a switching TFT 103, and the other is a current control TFT 104. A drain of the switching TFT 103 is electrically connected to a gate of the current control TFT 104. Furthermore, a drain of the current control TFT 104 is electrically connected to a pixel electrode 105 (which in this case, also functions as a cathode of an EL element). The pixel 102 is thus formed.

Various wirings of the TFT as well as the pixel electrode can be formed of a metal film having a low resistivity. For example, an aluminum alloy film may be used for this purpose.

Following the fabrication of the pixel electrode 105, an insulating compound 106 (hereinbelow, referred to as the alkaline compound) including an alkali metal or an alkaline-earth metal over all of the pixel electrodes. Note that the outline of the alkaline compound is indicated by a dotted line in FIG. 1. This is because the alkaline compound 106 has a thickness which is as thin as several nm, and it is not known whether the compound 106 is formed as a layer or in an island-shape.

As the alkaline compound, lithium fluoride (LiF), lithium oxide (Li₂O), barium fluoride (BaF₂), barium oxide (BaO), calcium fluoride (CaF₂), calcium oxide (CaO), strontium oxide (SrO), or cesium oxide (Cs₂O) can be used. Since these are insulating materials, short-circuiting between the pixel electrodes does not occur even when the alkaline compound 106 is formed as a layer.

It is of course possible to use as a cathode a known conductive material as an MgAg electrode. However, in this case, the cathode itself has to be selectively formed or patterned into a certain shape in order to avoid short-circuiting between the pixel electrodes.

After the alkaline compound 106 is formed, an EL layer (Electro-luminescence layer) 107 is formed thereover. Although any known material and/or structure can be employed for the EL layer 107, a material capable of emitting white light is used in the present invention. As the structure, only a light emitting layer providing a field for recombination may be employed for the EL layer. If necessary, an electron injection layer, an electron transport layer, a hole transport layer, an electron blocking layer, a hole device layer, or a hole injection layer may be further layered. In the present specification, all of those layered intended to realize injection, transport or recombination of carriers are collectively referred to as the EL layer.

As an organic material to be used as the EL layer 107, either a low-molecule type organic material or a polymer type (high-molecule type) organic material can be used. However, it is desirable to use a polymer type organic material that can be formed by an easy formation technique such as a spin coat technique, a printing technique or the like. The structure illustrated in FIG. 1 is of the color display scheme in which an EL layer for emitting white light is combined with a color filter.

Alternatively, a color display scheme in which an EL layer for emitting blue or blue-green light is combined with fluorescent material (fluorescent color conversion layer; CCM), or another color display scheme in which EL layers respect-

tively corresponding to RGB are overlaid one upon another to provide color display, can also be employed.

Over the EL layer **107**, a transparent conductive film is formed as an anode **108**. As the transparent conductive film, a compound of indium oxide and tin oxide (referred to as ITO), a compound of indium oxide and zinc oxide, tin oxide or zinc oxide can be used.

Over the anode **108**, an insulating film as a passivation film **109** is provided. As the passivation film **109**, a silicon nitride film or a silicon oxynitride film (represented as SiOxNy) is preferably used. Although a silicon oxide film may be used, an insulating film with as low an oxygen content as possible is preferred.

The substrate fabricated up to this stage is referred to as an active matrix substrate in the present application. More specifically, the substrate on which a TFT, a pixel electrode electrically connected to the TFT, and an EL element (a capacitor made of a cathode, an EL layer, and an anode) utilizing the pixel electrode as the cathode are formed is referred to as the active matrix substrate.

Furthermore, a counter substrate **110** is attached to the active matrix substrate with the EL element being interposed therebetween. The counter substrate **110** is provided with a light shielding film **112** and color filters **113a** to **113c**.

At this situation, the light shielding film **112** is provided so that a gap **111** formed between the pixel electrodes **105** is unseen from the viewing direction of an observer (i.e.

from a direction normal to the counter substrate.) More specifically, the light shielding film **112** is provided to overlap (align with) the periphery of the pixel when viewed from the direction normal to the counter substrate. This is because this portion is non-emitting portion, and furthermore, electric field becomes complicated at the edge portion of the pixel electrode and thus light cannot be emitted with a desired luminance or chromaticity.

More specifically, by providing the light shielding film **112** at the position corresponding to the periphery (edge portion) of the pixel electrode **105** and the gap **111**, contour between the pixels can be made clear. It can be also said that in the present invention, the light shielding film **112** is provided at the position corresponding to the periphery (edge portion) of the pixel because the contour of the pixel electrode corresponds to the contour of the pixel. Note that the position corresponding to the periphery of the pixel refers to the position aligned with the periphery of the pixel when viewed from the aforementioned direction which is normal to the counter substrate.

Among the color filters **113a** to **113c**, the color filter **113a** is the one for obtaining red light, the color filter **113b** is the one for obtaining green light, and the color filter **113c** is the one for obtaining blue light. These color filters are formed at positions respectively corresponding to the different pixels **102**, and thus, different color of light can be obtained for the respective pixels. In theory, this is the same as the color display scheme in a liquid crystal display device which uses color filters. Note that the position corresponding to the pixel refers to the position overlapped (aligned) with the pixel when viewed from the aforementioned direction which is normal to the counter substrate. More specifically, the color filters **113a** to **113c** are provided so as to overlap the pixels respectively corresponding thereto when viewed from the direction normal to the counter substrate.

Note that the color filter is a filter for improving the color purity of light which has passed therethrough by extracting light of a specific wavelength. Accordingly, in the case where the light component of the wavelength to be extracted is small, there may be disadvantages in which the light of that

wavelength has extremely small luminance or deteriorated color purity. Thus, although no limitation is imposed to an EL layer for emitting white light which can be used in the present invention, it is preferable that the spectrum of the emitted white light includes emission spectrums of red, green and blue light components having as high purity as possible.

FIGS. **16A** and **16B** show typical x-y chromaticity diagrams of an EL layer to be used in the present invention. More specifically, FIG. **16A** shows the chromaticity coordinate of light emitted from a known polymer type organic material for emitting white light. In the known material, the red color emission with high color purity cannot be realized. Therefore, yellow light or orange light is used instead of red light. Accordingly, white color obtained by adhesive color mixing seems to slightly include green color or yellow color. In addition, the respective emission spectrums of red light, green light, and blue light are so broad that it also becomes difficult to obtain monochromatic light having high purity when these light are mixed.

Accordingly, although sufficient color display can be realized even when an organic material as represented in the chromaticity diagram in FIG. **16A** is used as an EL layer, it is now preferable to use as an EL layer an organic material as represented in the chromaticity diagram in FIG. **16B** in order to realize brighter color display with higher purity.

The organic material as represented in the chromaticity diagram in FIG. **16B** is an example in which an EL layer for emitting white light is formed by mixing organic materials capable of providing monochromatic light with high purity. In order to obtain light emission spectrums of red, green and blue colors having high color purity from a color filter, it is necessary to form an EL layer for emitting white light by mixing organic materials respectively exhibiting light emission spectrums of red, green and blue colors with high color purity. In addition, by using materials capable of providing a spectrum not only with high color purity but also with a narrow half-peak width, white color with a sharp spectrum can be reproduced. With this kind of the EL layer for emitting white light, the present invention can display a further brighter color image.

Furthermore, the color filters **113a** to **113c** can contain, as a drying agent, an oxide of an element in group I or II in periodic table, e.g., barium oxide, calcium oxide, lithium oxide or the like. In this case, a resin film containing a drying agent and a pigment of red, green or blue color may be used as a color filter.

Note that although not illustrated herein, the counter substrate **110** is adhered to the active matrix substrate by means of a sealing agent, so that a space designated with reference numeral **114** is a closed space.

As the counter substrate **110**, it is necessary to use a transparent substrate so as not to prevent light from traveling. For example, a glass substrate, a quartz substrate, or a plastic substrate is preferably used. In addition, as the light shielding film **112**, a thin film capable of satisfactorily shielding light, e.g., a titanium film, a resin film including a black-colored pigment or carbon. Similarly to the case of the above-mentioned color filters **113a** to **113c**, it is advantageous to provide the light shielding film **112** containing, as a drying agent, an oxide of an element in group I or II in periodic table, e.g., barium oxide, calcium oxide, lithium oxide or the like.

The closed space **114** may be filled with inert gas (noble gas or nitrogen gas), or with inert liquid. Alternatively, the closed space **114** may be filled with a transparent adhesive so as to adhere the whole surface of the substrate. Moreover, it is preferable to dispose a drying agent such as barium oxide in the closed space **114**. Since the EL layer **107** is very vulner-

able to water, it is highly desirable to prevent water from entering the closed space 114.

In the EL display device having the above-mentioned construction in accordance with the present invention, light emitted from the EL element passes through the counter substrate to be emitted toward an observer's eyes. Accordingly, the observer can recognize an image through the counter substrate. In this situation, one of the features of the EL display device in accordance with the present invention is that the light shielding film 112 is disposed between the EL element and the observer so as to conceal the gap 111 between the pixel electrodes 105. Thus, the contour between the pixels can be made clear, thereby resulting in an image display with high definition. This advantage can be obtained due to the light shielding film 112 provided at the counter substrate 110. When at least the light shielding film 112 is provided, this advantage can be obtained.

Furthermore, the light shielding film 112 and the color filters 113a to 113c are disposed at the counter substrate 110, and the counter substrate 110 also functions as a ceiling substrate for suppressing deterioration of the EL element. When the light shielding film 112 and the color filters 113a to 113c are disposed at the active matrix substrate, additional film-formation and patterning steps are required, whereas the number of fabrication steps for the active matrix substrate can be suppressed in the case where they are provided at the counter substrate, although additional film-formation and patterning steps are required.

Furthermore, the structure in accordance with the present invention in which the counter substrate 110 is provided with the light shielding film 112 and the color filters 113a to 113c and adhered to the active matrix substrate by means of the sealing agent has features common to the structure of a liquid crystal display device. Accordingly, it is possible to fabricate the EL display device of the present invention with most of an existing manufacturing line for liquid crystal display devices. Thus, an amount of equipment investment can be significantly reduced, thereby resulting in a reduction in the total manufacturing cost.

Thus, in accordance with the present invention, an inexpensive EL display device capable of displaying an image with high definition can be obtained. Furthermore, the present invention can also provide an electronic device having a high recognizability of a display portion by utilizing such an EL display device as the display portion.

BRIEF DESCRIPTION OF THE DRAWINGS

FIG. 1 is a view for illustrating a pixel portion of an EL display device.

FIG. 2 is a view for illustrating the cross-sectional structure of a pixel of an EL display device.

FIG. 3A is a view for illustrating the top structure of a pixel portion of an EL display device.

FIG. 3B is a view for illustrating the configuration of a pixel portion of an EL display device.

FIGS. 4A through 4E are views for illustrating the fabricating steps of an active matrix type EL display device.

FIGS. 5A through 5D are views for illustrating the fabricating steps of an active matrix type EL display device.

FIGS. 6A through 6C are views for illustrating the fabricating steps of an active matrix type EL display device.

FIG. 7 is a view for illustrating the perspective appearance of an EL display device.

FIG. 8 is a view for illustrating the circuit block configuration of an EL display device.

FIG. 9 is an enlarged view of a pixel of an EL display device.

FIG. 10 is a view of the structure of a sampling circuit of an EL display device.

FIG. 11A is a top view for illustrating the appearance of an EL display device:

FIG. 11B is a cross-sectional view for illustrating the appearance of an EL display device.

FIG. 12 is a view for illustrating the pixel structure of an EL display device.

FIG. 13 is a view for illustrating the cross-sectional structure of a pixel of an EL display device.

FIGS. 14A to 14F are views for respectively illustrating specific examples of an electronic device.

FIGS. 15A and 15B are views for respectively illustrating specific examples of an electronic device.

FIGS. 16A and 16B are diagrams for respectively showing the chromaticity coordinates of organic materials.

DETAILED DESCRIPTION OF THE PREFERRED EMBODIMENTS

Some embodiments of the present invention will be described with reference to FIGS. 2, 3A and 3B. FIG. 2 shows a cross-sectional view of a pixel portion in an EL display device in accordance with the present invention. FIG. 3A shows a top view of the pixel portion, and FIG. 3B shows the circuit configuration thereof. In an actual structure, pixels are arranged in a plurality of lines to be in matrix, thereby forming a pixel portion (image display portion). FIG. 2 illustrates a cross-sectional view taken along the line A-A' in FIG. 3A. Accordingly, the same components are commonly designated by the same reference numerals in both of the figures, and it will be advantageous for understanding the structure to make reference to both of the figures. In addition, the two pixels illustrated in the top view of FIG. 3A have the same structure.

In FIG. 2, reference numeral 11 denotes a substrate, and 12 denotes a base insulating film (hereinafter referred to as the base film). As the substrate 11, a glass substrate, a glass ceramic substrate, a quartz substrate, a silicon substrate, a ceramic substrate, a metal substrate, or a plastic substrate (including a plastic film) can be used.

In addition, the base film 12 is especially advantageous for a substrate including mobile ions or a substrate having conductivity, but does not necessarily have to be provided for a quartz substrate. As the base film 12, an insulating film containing silicon may be used. In the present specification, the "insulating film containing silicon" refers to an insulating film containing silicon and oxygen or nitrogen at a predetermined ratio, and more specifically, a silicon oxide film, a silicon nitride film, or a silicon oxynitride film (represented as SiOxNy.)

It is advantageous to provide the base film 12 with a heat radiation function to dissipate heat generated in a TFT in order to prevent a TFT or an EL element from deteriorating. The heat radiation function can be provided by any known material.

In this example, two TFTs are provided in one pixel. A TFT 201 functions as a switching device (hereinafter referred to as the switching TFT), and a TFT 202 functions as a current controlling device for controlling an amount of current to flow through the EL element (hereinafter referred to as the current control TFT.) Both of the TFTs 201 and 202 are made of the n-channel type TFT.

Since the n-channel type TFT has a field effect mobility higher than that of the p-channel type TFT, the n-channel type TFT can operate at higher speed and accept a large amount of

current. Furthermore, a current of the same amount can flow through the n-channel type TFT of smaller size as compared to the p-channel type TFT. Accordingly, it is preferable to use the n-channel type TFT as the current control TFT since this results in an increased effective area of the display portion.

The p-channel type TFT has advantages, e.g., in which the injection of hot carriers becomes hardly a problem and an OFF current value is small. Thus, it has been already reported the structures in which the p-channel type TFT is used as the switching TFT or the current control TFT. However, in the present invention, the disadvantages in connection with the injection of hot carriers and a small OFF current value can be overcome even in the n-channel type TFT by providing the structure with shifted LDD regions. Thus, it is another feature of the present invention in which all of the TFTs in the pixel are made of the n-channel type TFTs.

However, the present invention is not limited to the case where the switching TFT and the current control TFT are made of the n-channel type TFTs. It is possible to use the p-channel type TFT as both or either of the switching TFT and the current control TFT.

The switching TFT **201** is formed to have a source region **13**, a drain region **14**, an active layer including LDD regions **15a** to **15d** and a high concentration impurities region **16** and channel forming regions **17a** and **17b**, a gate insulating film **18**, gate electrodes **19a** and **19b**, a first interlayer insulating film **20**, a source wiring **21**, and a drain wiring **22**.

In addition, as shown in FIGS. 3A and 3B, the gate electrodes **19a** and **19b** are electrically connected to each other by means of a gate wiring **211** which is made of a different material (that has a lower resistivity than the gate electrodes **19a** and **19b**), thereby forming a double-gate structure. It is of course possible to employ, not only the double-gate structure, but also the so-called multigate structure (a structure including an active layer which contains two or more channel forming regions connected in series) such as a triple-gate structure. The multigate structure is significantly advantageous for decreasing of OFF current value. In accordance with the present invention, a switching device having a low OFF current value can be realized by providing the switching device **201** in the pixel with the multigate structure.

In addition, the active layer is formed of a semiconductor film that includes a crystalline structure. This may be a single crystalline semiconductor film, a polycrystalline semiconductor film, or a microcrystalline semiconductor film. The gate insulating film **18** may be formed of an insulating film containing silicon. Furthermore, any kind of conductive films can be used as the gate electrode, the source wiring, or the drain wiring.

Furthermore, in the switching TFT **201**, the LDD regions **15a** to **15d** are disposed so as not overlap the gate electrodes **19a** and **19b**. Such a structure is significantly advantageous for reducing an OFF current value.

For reducing the OFF current value, it is further preferable to provide an offset region (which is made of a semiconductor layer having the same composition as the channel forming regions and a gate voltage is not applied thereto) between the channel forming regions and the LDD regions. In addition, in the case of the multigate structure having two or more gate electrodes, the high concentration impurities region disposed between the channel forming regions is effective for reducing the OFF current value.

As set forth above, by employing the TFT having the multigate structure as the switching device **201** in the pixel, a switching device having a sufficiently low OFF current value can be realized. Thus, a gate voltage of the current control TFT can be maintained for a sufficient period of time (from

the timing selected until the next timing selected) without providing a capacitor as shown in FIG. 2 of Japanese Laid-Open Patent Publication No. Hei 10-189252.

Then, the current control TFT **202** is formed to have a source region **31**, a drain region **32**, an active layer including an LDD region **33** and a channel forming region **34**, a gate insulating film **18**, a gate electrode **35**, a first interlayer insulating film **20**, a source wiring **36**, and a drain wiring **37**. Although the illustrated gate electrode **35** has the single gate structure, it may have the multi-gate structure.

As shown in FIG. 2, a drain of the switching TFT is connected to a gate of the current control TFT. More specifically, the gate electrode **35** is electrically connected to the drain region **14** of the switching TFT **201** through the drain wiring **22** (also referred to as the connecting wiring). Furthermore, the source wiring **36** is connected to a power supply line **212**.

The current control TFT **202** is a device intended to control an amount of current to be injected into the EL element **203**. However, considering possible deterioration of the EL element, it is not preferable to allow a large amount of current to flow. Accordingly, in order to prevent excessive current from flowing through the current control TFT **202**, the channel length (L) thereof is preferably designed to be long. Desirably, the channel length (L) is design to be 0.5 to 2 μm (preferably, 1 to 1.5 μm) long per pixel.

In view of the above-mentioned description, as shown in FIG. 9, the channel length L1 (where $L1=L1a+L1b$) and the channel width W1 of the switching TFT, and the channel length L2 and the channel width W2 of the current control TFT are preferably set as follows: W1 is in the range from 0.1 to 5 μm (typically, 0.5 to 2 μm); W2 is in the range from 0.5 to 10 μm (typically, 2 to 5 μm); L1 is in the range from 0.2 to 18 μm (typically, 2 to 15 μm); and L2 is in the range from 1 to 50 μm (typically, 10 to 30 μm). However, the present invention is not limited to the above-mentioned values.

The length (width) of the LDD regions to be formed in the switching TFT **201** is set in the range from 0.5 to 3.5 μm , typically in the range from 2.0 to 2.5 μm .

The EL display device as shown in FIG. 2 has features in which the LDD region **33** is provided between the drain region **32** and the channel forming region **34** in the current control TFT **202**, and part of the LDD region **33** overlaps the gate electrode **35** through the gate insulating film **18** while the remaining portion does not.

The current control TFT **202** supplies a current to the EL element **203** for causing it to emit light, and at the same time controls the supplied amount of the current to realize gray scale display. For that purpose, it is necessary to implement countermeasure against deterioration due to the injection of hot carriers so as not to deterioration when the current flows. Further, in the case where black color is displayed by turning off the current control TFT **202**, a high OFF current value prevents black color from being displayed in satisfactory condition, resulting in disadvantages such as reduced contrast. Accordingly, it is also necessary suppress the OFF current value.

With respect to the deterioration due to the injection of hot carriers, it has been known that the structure with the LDD region overlapping the gate electrode is very effective. However, when the whole LDD region overlaps the gate electrode, the OFF current value increases. Thus, the present inventors overcome both the disadvantage related to the hot carriers and the disadvantage related to the OFF current value by providing a novel structure with the LDD regions being disposed in series so as not to overlap the gate electrode.

In this case, the length of the LDD region overlapping the gate electrode may be set to be in the range from 0.1 to 3 μm

(preferably in the range of 0.3 to 13 μm). If the overlap length is too long, parasitic capacitance is increased, whereas when the overlap length is too short, hot carriers cannot be sufficiently suppressed. Furthermore, a region of the LDD not overlapping the gate electrode may be set to be in the range from 1.0 to 3.5 μm (preferably in the range of 1.3 to 2.0 μm). If this length is too long, a sufficient current cannot flow, whereas when this length is too short, the OFF current value cannot be sufficiently reduced.

Furthermore, in the above structure, a parasitic capacitance is generated in the region where the gate electrode overlaps the LDD region, and therefore, such an overlap region should not be provided between the source region **31** and the channel forming region **34**. Since carriers (electrons) always travel in the same direction in the current control TFT, it is sufficient to provide the LDD region only on the side closer to the drain region.

From the view point of increasing a possible amount of current to flow, it is also effective to increase film thickness of the active layer (in particular, a thickness at the channel forming region) of the current control TFT **202** (preferably in the range from 50 to 100 nm, and more preferably in the range from 60 to 80 nm). On the other hand, in the case of the switching TFT **201**, from the view point of reducing an OFF current value, it is also effective to decrease film thickness of the active layer (in particular, a thickness at the channel forming region) of the current control TFT **202** (preferably in the range from 20 to 50 nm, and more preferably in the range from 25 to 40 nm.)

Then, reference numeral **41** denotes the first passivation film, which may have a thickness of 10 nm to 1 μm (preferably 200 to 500 nm). As the constituent material thereof, an insulating film containing silicon can be used (particularly, a silicon oxynitride film or a silicon nitride film is preferred). It is effective to provide this passivation film **41** with the heat radiation effect for preventing the EL layer from thermal degradation. A thin film exhibiting the heat radiation effect includes an insulating film containing at least one element selected from B (boron), C (carbon), and N (nitrogen), as well as at least one element selected from Al (aluminum), Si (silicon), and P (phosphorous). For example, it is possible to use a nitride of aluminum, typically aluminum nitride (AlxNy); a carbide of silicon, typically silicon carbide (SixCy); a nitride of silicon, typically silicon nitride (SixNy); a nitride of boron, typically boron nitride (BxNy); and a phosphide of boron, typically boron phosphide (BxPy). Furthermore, an oxide of aluminum, typically aluminum oxide (AlxOy) has a thermal conductivity of $20 \text{ Wm}^{-1}\text{K}^{-1}$, and can be one of preferable materials. In the above-mentioned transparent materials, x and y can be any integer.

Note that it is also possible to combine the above compound with another element. For example, it is also possible to use aluminum nitride oxide indicated by AlNxOy by adding nitrogen to the aluminum oxide. Note that in the above aluminum nitride oxide, x and y are respectively arbitrary integers.

Besides, it is possible to use materials disclosed in Japanese Laid-open Patent Publication No. Sho 62-90260. That is, it is also possible to use an insulating film containing Si, Al, N, O, or M (M is at least one kind of rare-earth element, preferably at least one element selected from Ce (cerium), Yb (ytterbium), Sm (samarium), Er (erbium), Y (yttrium), La (lanthan), Gd (gadolinium), Dy (dysprosium), and Nd (neodymium)).

Besides, it is also possible to use a carbon film such as a diamond thin film or an amorphous carbon film (especially a film having characteristics close to diamond, called diamond-

like carbon or the like). These have very high thermal conductivity and are very effective as a heat radiating layer.

Thus, although a thin film made of the material having the foregoing heat radiating effect can be used alone, it is effective to stack these thin films and a silicon nitride film (SixNy) or silicon nitride oxide film (SiOxNy). Note that in the silicon nitride film or silicon nitride oxide film, x and y are respectively arbitrary integers.

Over the first passivation film **41**, a second interlayer insulating film **42** (also referred to as a planarizing film) is formed to cover the respective TFTs, and thus steps caused by the TFTs are planarized. As the second interlayer insulating film **42**, an organic resin film is preferred, and polyimide, polyamide, acrylic, BCB (benzocyclobutane), or the like can be used. An inorganic film can be also used of course, so long as sufficient planarization is realized.

The planarization of the steps caused by the TFTs by means of the second interlayer insulating film **42** is very important. The EL layer to be formed in the subsequent step is so thin that the steps may cause to defect in light emission. Accordingly, in order to form the EL layer on a flat surface as much as possible, it is preferable to perform a planarization process prior to the formation of the pixel electrode.

Reference numeral **43** denotes the pixel electrode (corresponding to the cathode of the EL element) made of a conductive film having a function to shield light. The pixel electrode **43** is formed, after contact holes (openings) are provided in the second interlayer insulating film **42** and the first passivation film **41**, to be connected the drain wiring **37** of the current control TFT **202** in the thus formed opening portion. A lithium fluoride film having a thickness of 5 to 10 nm is formed by a vapor deposition method as the alkaline compound **44** on the pixel electrode **43**. The lithium fluoride film is an insulating film, and thus, when the thickness thereof is too large, a current cannot flow to the EL layer. No adverse effect is generated even when the lithium fluoride film is formed in an island-like pattern, not in a layer.

The EL layer **45** is then formed. In the present embodiment, a polymer type organic material is formed through a spin coat technique. Any known material can be used as the polymer type organic material. Although a single layer of the light emitting layer is used as the EL layer **45** in the present embodiment, the laminated structure in which the light emitting layer is combined with a hole transport layer, or an electron transport layer provides a higher light emission efficiency. When the polymer type organic material is to be laminated, it is preferable to be combined with a low molecule organic material formed by a vapor deposition technique. With the spin coat technique, if there is the base organic material, it may re-melt since the organic material to form the EL layer is mixed with an organic solvent and coated.

A typical polymer type organic material that can be used in the present embodiment includes high molecule material such as polyparaphenylene vinylene (PPV) type, polyvinyl carbazole (PVK) type, polyfluorene type, or the like. In order to form an electron transport layer, a light emitting layer, a hole transport layer or a hole injection layer with these polymer type organic materials, the organic material may be coated in the form of polymer precursor, and then heated (baked) in vacuum to be converted into the polymer type organic material.

More specifically, as the polymer type organic material for providing light of white color to be a light emitting layer, the materials disclosed in Japanese Laid-Open Patent Publication No. Hei 8-96959 or No. Hei 9-63770 can be used. For example, the material obtained by solving PVK (polyvinyl carbazole), Bu-PBD (2-(4'-tert-butylphenyl)-5-(4"-biphen

yl)-1,3,4-oxydiazole), coumarin 6, DCM 1 (4-dicyanomethylene-2-methyl-6-p-dimethyl-4H-pyran), TPB (tetra phenyl butadiene), and Nile Red into 1,2-dichloromethane can be used. The thickness of the above material can be set to be in the range from 30 to 150 nm (preferably 40 to 100 nm). As the hole transport layer, polytetrahydrothiophenyl phenylene that is the polymer precursor, is used, which is heated to be converted into polyphenylene vinylene. The thickness thereof can be set to be in the range from 30 to 100 nm (preferably 40 to 80 nm).

Thus, the polymer type organic material is advantageous especially for emitting white light since color adjustment can be easily performed by adding a fluorescent pigment into a solution in which a host material is solved. Although the EL element is formed by using the polymer type organic material in the above description, any low molecule type organic material can be used. Moreover, the EL layer can be formed with an inorganic material. The above-mentioned organic materials are only examples that can be used for the EL layer in accordance with the present invention. Note that the present invention is not limited thereto.

When the EL layer **45** is formed, it is desirable that the process is proceeded in a dry inert gas atmosphere containing water as less as possible. The EL layer is likely to easily deteriorate due to water or oxygen existing in the surrounding atmosphere, and therefore, those factors should be eliminated as much as possible in the formation of the EL layer. For example, a dry nitrogen atmosphere, a dry argon atmosphere, or the like is preferred. For that purpose, it is preferable to place a coating process chamber and a baking process chamber in a clean booth filled with inert gas and the process is proceeded in the above-mentioned atmosphere.

After the EL layer **45** is formed in the above-mentioned manner, the anode **46** made of a transparent conductive film, as well as the second passivation film **47**, are formed. In the present embodiment, the anode **46** is formed of a conductive film made of a compound of indium oxide and zinc oxide. A small amount of gallium may be added thereto. As the second passivation film **47**, a silicon nitride film having a thickness of 10 nm to 1 μ m (preferably 200 to 500 nm) can be used.

Since the EL layer is vulnerable to heat as explained above, it is desirable to deposit the anode **46** and the second passivation film **47** at a temperature of as low as possible (preferably in the range from room temperature to 120° C.). Accordingly, it can be said that a plasma CVD technique, a vacuum vapor deposition technique, or a solution coating (spin coat) technique is a preferred technique for the film formation.

The counter substrate **48** is disposed to face the active matrix substrate thus completed. In the present embodiment, a glass substrate is used as the counter substrate **48**. Furthermore, the counter substrate **48** is provided with light shielding films **49a** and **49b** made of resin with a black-colored pigment being dispersed therein, and a color filter **50** made of resin with a red-colored, green-colored, or blue-colored pigment being dispersed therein. These light shielding films **49a** and **49b** are disposed so as to conceal a gap between the pixel electrode **43** and its adjacent pixel electrode. At this time, it is advantageous that the light shielding films **49a** and **49b** contain a drying agent such as barium oxide or the like. Other material such as those disclosed in Japanese Laid-Open Patent Publication No. Hei 9-148066 can be used as the drying agent. Furthermore, the color filter **50** is formed at the position corresponding to the pixel **102**.

The active matrix substrate is adhered to the counter substrate **48** by means of a sealing agent (not illustrated) to form a closed space **51**. In the present embodiment, the closed space is filled with argon gas. It is of course possible to place

the above-mentioned drying agent in the closed space **51**. The EL display device in accordance with the present embodiment includes a pixel portion composed of pixels each having the structure as shown in FIG. 2, in which the TFTs having the different structures in accordance with their functions in pixels are arranged. More specifically, the switching TFT having a sufficiently low OFF current value and the current control TFT which is not vulnerable to the injection of hot carriers are formed in the same pixel. Thus, the EL display device with high reliability capable of displaying an image with high definition can be obtained.

[Embodiment 1]

The embodiments of the present invention are explained using FIGS. 4A to 6C. A method of simultaneous manufacture of a pixel portion, and TFTs of a driving circuit portion formed in the periphery of the pixel portion, is explained here. Note that in order to simplify the explanation, a CMOS circuit is shown as a basic circuit for the driving circuits.

First, as shown in FIG. 4A, a base film **301** is formed with a 300 nm thickness on a glass substrate **300**. Oxidized silicon nitride films are laminated as the base film **301** in embodiment 1. It is good to set the nitrogen concentration at between 10 and 25 wt % in the film contacting the glass substrate **300**.

Besides, as a part of the base film **301**, it is effective to provide an insulating film made of a material similar to the first passivation film **41** shown in FIG. 2. The current controlling TFT is apt to generate heat since a large current is made to flow, and it is effective to provide an insulating film having a heat radiating effect at a place as close as possible.

Next, an amorphous silicon film (not shown in the figures) is formed with a thickness of 50 nm on the base film **301** by a known deposition method. Note that it is not necessary to limit this to the amorphous silicon film, and another film may be formed provided that it is a semiconductor film containing an amorphous structure (including a microcrystalline semiconductor film). In addition, a compound semiconductor film containing an amorphous structure, such as an amorphous silicon germanium film, may also be used. Further, the film thickness may be made from 20 to 100 nm.

The amorphous silicon film is then crystallized by a known method, forming a crystalline silicon film (also referred to as a polycrystalline silicon film or a polysilicon film) **302**. Thermal crystallization using an electric furnace, laser annealing crystallization using a laser, and lamp annealing crystallization using an infrared lamp exist as known crystallization methods. Crystallization is performed in embodiment 1 using an excimer laser light which uses XeCl gas.

Note that pulse emission type excimer laser light formed into a linear shape is used in embodiment 1, but a rectangular shape may also be used, and continuous emission argon laser light and continuous emission excimer laser light can also be used.

In this embodiment, although the crystalline silicon film is used as the active layer of the TFT, it is also possible to use an amorphous silicon film. Further, it is possible to form the active layer of the switching TFT, in which there is a necessity to reduce the off current, by the amorphous silicon film, and to form the active layer of the current control TFT by the crystalline silicon film. Electric current flows with difficulty in the amorphous silicon film because the carrier mobility is low, and the off current does not easily flow. In other words, the most can be made of the advantages of both the amorphous silicon film, through which current does not flow easily, and the crystalline silicon film, through which current easily flows.

Next, as shown in FIG. 4B, a protecting film **303** is formed on the crystalline silicon film **302** with a silicon oxide film

having a thickness of 130 nm. This thickness may be chosen within the range of 100 to 200 nm (preferably between 130 and 170 nm).

Furthermore, other films may also be used providing that they are insulating films containing silicon. The protecting film **303** is formed so that the crystalline silicon film is not directly exposed to plasma during addition of an impurity, and so that it is possible to have delicate concentration control of the impurity.

Resist masks **304a** and **304b** are then formed on the protecting film **303**, and an impurity element which imparts n-type conductivity (hereafter referred to as an n-type impurity element) is added. Note that elements residing in periodic table group **15** are generally used as the n-type impurity element, and typically phosphorous or arsenic can be used. Note that a plasma doping method is used, in which phosphine (PH_3) is plasma activated without separation of mass, and phosphorous is added at a concentration of 1×10^{18} atoms/cm³ in embodiment 1. An ion implantation method, in which separation of mass is performed, may also be used, of course.

The dose amount is regulated so that the n-type impurity element is contained in n-type impurity regions **305** and **306**, thus formed by this process, at a concentration of 2×10^{16} to 5×10^{19} atoms/cm³ (typically between 5×10^{17} and 5×10^{18} atoms/cm³).

Next, as shown in FIG. 4C, the protecting film **303** is removed, and an activation of the added periodic table group **15** elements is performed. A known technique of activation may be used as the means of activation, but activation is done in embodiment 1 by irradiation of excimer laser light. Of course, a pulse emission type excimer laser and a continuous emission type excimer laser may both be used, and it is not necessary to place any limits on the use of excimer laser light. The goal is the activation of the added impurity element, and it is preferable that irradiation is performed at an energy level at which the crystalline silicon film does not melt. Note that the laser irradiation may also be performed with the protecting film **303** in place.

The activation by heat treatment may also be performed along with activation of the impurity element by laser light. When activation is performed by heat treatment, considering the heat resistance of the substrate, it is good to perform heat treatment on the order of 450 to 550° C.

A boundary portion (connecting portion) with end portions of the n-type impurity regions **305** and **306**, namely regions, in which the n-type impurity element is not added, on the periphery of the n-type impurity regions **305** and **306**, is not added, is delineated by this process. This means that, at the point when the TFTs are later completed, extremely good connections can be formed between LDD regions and channel forming regions.

Unnecessary portions of the crystalline silicon film are removed next, as shown in FIG. 4D, and island shape semiconductor films (hereafter referred to as active layers) **307** to **310** are formed. Then, as shown in FIG. 4E, a gate insulating film **311** is formed, covering the active layers **307** to **310**. An insulating film containing silicon and with a thickness of 10 to 200 nm, preferably between 50 and 150 nm, may be used as the gate insulating film **311**. A single layer structure or a lamination structure may be used. A 110 nm thick oxidized silicon nitride film is used in embodiment 1.

Thereafter, a conductive film having a thickness of 200 to 400 nm is formed and patterned to form gate electrodes **312** to **316**. Respective end portions of these gate electrodes **312** to **316** may be tapered. In the present embodiment, the gate electrodes and wirings (hereinafter referred to as the gate wirings) electrically connected to the gate electrodes for pro-

viding conducting paths are formed of different materials from each other. More specifically, the gate wirings are made of a material having a lower resistivity than the gate electrodes. Thus, a material enabling fine processing is used for the gate electrodes, while the gate wirings are formed of a material that can provide a smaller wiring resistance but is not suitable for fine processing. It is of course possible to form the gate electrodes and the gate wirings with the same material.

Although the gate electrode can be made of a single-layered conductive film, it is preferable to form a lamination film with two, three or more layers for the gate electrode if necessary. Any known conductive materials can be used for the gate electrode. It should be noted, however, that it is preferable to use such a material that enables fine processing, and more specifically, a material that can be patterned with a line width of 2 μm or less.

Typically, it is possible to use a film made of an element selected from tantalum (Ta), titanium (Ti), molybdenum (Mo), tungsten (W), chromium (Cr), and silicon (Si), a film of nitride of the above element (typically a tantalum nitride film, tungsten nitride film, or titanium nitride film), an alloy film of combination of the above elements (typically Mo-W alloy, Mo-Ta alloy), or a silicide film of the above element (typically a tungsten silicide film or titanium silicide film). Of course, the films may be used as a single layer or a laminate layer.

In this embodiment, a laminate film of a tungsten nitride (WN) film having a thickness of 50 nm and a tungsten (W) film having a thickness of 350 nm is used. This may be formed by a sputtering method. When an inert gas of Xe, Ne or the like is added as a sputtering gas, film peeling due to stress can be prevented.

The gate electrodes **313** and **316** are formed at this time so as to overlap a portion of the n-type impurity regions **305** and **306**, respectively, sandwiching the gate insulating film **311**. This overlapping portion later becomes an LDD region overlapping the gate electrode.

Next, an n-type impurity element (phosphorous is used in embodiment 1) is added in a self-aligning manner with the gate electrodes **312** to **316** as masks, as shown in FIG. 5A. The addition is regulated so that phosphorous is added to impurity regions **317** to **323** thus formed at a concentration of $1/10$ to $1/2$ that of the impurity regions **305** and **306** (typically between $1/4$ and $1/3$). Specifically, a concentration of 1×10^{16} to 5×10^{18} atoms/cm³ (typically 3×10^{17} to 3×10^{18} atoms/cm³) is preferable.

Resist masks **324a** to **324c** are formed next, with a shape covering the gate electrodes etc., as shown in FIG. 5B, and an n-type impurity element (phosphorous is used in embodiment 1) is added, forming impurity regions **325** to **331** containing phosphorous at high concentration of phosphorous. Ion doping using phosphine (PH_3) is also performed here, and is regulated so that the phosphorous concentration of these regions is from 1×10^{20} to 1×10^{21} atoms/cm³ (typically between 2×10^{20} and 5×10^{21} atoms/cm³).

A source region or a drain region of the n-channel type TFT is formed by this process, and in the switching TFT, a portion of the n-type impurity regions **320** to **322** formed by the process of FIG. 5A are remained. These remaining regions correspond to the LDD regions **15a** to **15d** of the switching TFT in FIG. 2.

Next, as shown in FIG. 5C, the resist masks **324a** to **324c** are removed, and a new resist mask **332** is formed. A p-type impurity element (boron is used in embodiment 1) is then added, forming impurity regions **333** and **334** containing boron at high concentration. Boron is added here to form impurity regions **333** and **334** at a concentration of 3×10^{20} to

3×10^{21} atoms/cm³ (typically between 5×10^{20} and 1×10^{21} atoms/cm³) by ion doping using diborane (B₂H₆).

Note that phosphorous has already been added to the impurity regions **333** and **334** at a concentration of 1×10^{20} to 1×10^{21} atoms/cm³, but boron is added here at a concentration of at least 3 times that of the phosphorous. Therefore, the n-type impurity regions already formed completely invert to p-type, and function as p-type impurity regions.

Next, after removing the resist mask **332**, the n-type and p-type impurity elements added to the active layer at respective concentrations are activated. Furnace annealing, laser annealing or lamp annealing can be used as a means of activation. In embodiment 1, heat treatment is performed for 4 hours at 550° C. in a nitrogen atmosphere in an electric furnace.

At this time, it is critical to eliminate oxygen from the surrounding atmosphere as much as possible. This is because when even only a small amount of oxygen exists, an exposed surface of the gate electrode is oxidized, which results in an increased resistance and later makes it difficult to form an ohmic contact with the gate electrode. Accordingly, the oxygen concentration in the surrounding atmosphere for the activation process is set at 1 ppm or less, preferably at 0.1 ppm or less.

After the activation process is completed, the gate wiring **335** having a thickness of 300 nm is formed. As a material for the gate wiring **335**, a metal film containing aluminum (Al) or copper (Cu) as its main component (occupied 50 to 100% in the composition) can be used. The gate wiring **335** is arranged, as the gate wiring **211** shown in FIG. 3A, so as to provide electrical connection for the gate electrodes **314** and **315** (corresponding to the gate electrodes **19a** and **19b** in FIG. 3A) of the switching TFT (see FIG. 5D).

The above-described structure can allow the wiring resistance of the gate wiring to be significantly reduced, and therefore, an image display region (pixel portion) with a large area can be formed. More specifically, the pixel structure in accordance with the present embodiment is advantageous for realizing an EL display device having a display screen with a diagonal size of 10 inches or larger (or 30 inches or larger.)

A first interlayer insulating film **336** is formed next, as shown in FIG. 6A. A single layer insulating film containing silicon is used as the first interlayer insulating film **336**, while a lamination film may be used. Further, a film thickness of between 400 nm and 1.5 μm may be used. A lamination structure of an 800 nm thick silicon oxide film on a 200 nm thick oxidized silicon nitride film is used in embodiment 1.

In addition, heat treatment is performed for 1 to 12 hours at 300 to 450° C in an atmosphere containing between 3 and 100% hydrogen, performing hydrogenation. This process is one of hydrogen termination of dangling bonds in the semiconductor film by hydrogen which is thermally activated. Plasma hydrogenation (using hydrogen activated by a plasma) may also be performed as another means of hydrogenation.

Note that the hydrogenation processing may also be inserted during the formation of the first interlayer insulating film **336**. Namely, hydrogen processing may be performed as above after forming the 200 nm thick oxidized silicon nitride film, and then the remaining 800 nm thick silicon oxide film may be formed.

Next, a contact hole is formed in the first interlayer insulating film **336**, and source wiring lines **337** to **340** and drain wiring lines **341** to **343** are formed. In this embodiment, this electrode is made of a laminate film of three-layer structure in which a titanium film having a thickness of 100 nm, an aluminum film containing titanium and having a thickness of

300 nm, and a titanium film having a thickness of 150 nm are continuously formed by a sputtering method. Of course, other conductive films may be used.

A first passivation film **344** is formed next with a thickness of 50 to 500 nm (typically between 200 and 300 nm). A 300 nm thick oxidized silicon nitride film is used as the first passivation film **344** in embodiment 1. This may also be substituted by a silicon nitride film. It is of course possible to use the same materials as those of the first passivation film **41** of FIG. 2.

Note that it is effective to perform plasma processing using a gas containing hydrogen such as H₂ or NH₃ etc. before the formation of the oxidized silicon nitride film. Hydrogen activated by this preprocess is supplied to the first interlayer insulating film **336**, and the film quality of the first passivation film **344** is improved by performing heat treatment. At the same time, the hydrogen added to the first interlayer insulating film **336** diffuses to the lower side, and the active layers can be hydrogenated effectively.

Next, as shown in FIG. 6B, a second interlayer insulating film **345** made of organic resin is formed. As the organic resin, it is possible to use polyimide, polyamide, acryl, BCB (benzocyclobutene) or the like. Especially, since the second interlayer insulating film **345** is primarily used for flattening, acryl excellent in flattening properties is preferable. In this embodiment, an acrylic film is formed to a thickness sufficient to flatten a stepped portion formed by TFTs. It is appropriate that the thickness is made 1 to 5 μm (more preferably, 2 to 4 μm).

Thereafter, a contact hole is formed in the second interlayer insulating film **345** and the first passivation film **344** to reach the drain wiring **343**, and then the pixel electrode **346** is formed. In the present embodiment, an aluminum alloy film (an aluminum film containing titanium of 1 wt %) having a thickness of 300 nm is formed as the pixel electrode **346**. Reference numeral **347** denotes an end portion of the adjacent pixel electrode.

Then, the alkaline compound **348** is formed, as shown in FIG. 6C. In the present embodiment, a lithium fluoride film is formed by a vapor deposition method so as to have a film thickness of 5 nm. Thereafter, the EL layer **349** having a thickness of 100 nm is formed by spin coating.

In the present embodiment, as the polymer type organic material for providing light of white color, the materials disclosed in Japanese Laid-Open Patent Publication No. Hei 8-96959 or No. Hei 9-63770 can be used. For example, the material obtained by solving PVK (polyvinyl carbazole), Bu-PBD (2-(4'-tert-butylphenyl)-5-(4"-biphenyl)-1,3,4-oxadiazole), coumarin 6, DCM 1 (4-dicyanomethylene-2-methyl-6-p-dimethyl aminostyryl-4H-pyran), TPB (tetra phenyl butadiene), and Nile Red into 1,2-dichloromethane can be used.

In the present embodiment, the EL layer **349** has a single layer structure including only the above-mentioned light emitting layer. Alternatively, an electron injection layer, an electron transport layer, a hole transport layer, a hole injection layer, an electron blocking layer, or a hole element layer can be further formed, if necessary.

Then, the anode **350** made of a transparent conductive film having a thickness of 200 nm is formed to cover the EL layer **349**. In this embodiment, a film made of a compound of indium oxide and zinc oxide is formed by a vapor deposition and then patterned to obtain the anode.

Finally, the second passivation film **351** made of a silicon nitride film is formed by a plasma CVD to have a thickness of 100 nm. This second passivation film **351** is intended to provide protection for the EL layer **349** against water or the like, and also function to release heat generated in the EL

layer **349**. In order to further enhance the heat radiation effect, it is advantageous to form the second passivation film by forming a silicon nitride film and a carbon film (preferably a diamond-like carbon film) into the lamination structure.

In this way, an active matrix EL display device having a structure as shown in FIG. 6C is completed. In the active matrix EL display device of this embodiment, a TFT having an optimum structure is disposed in not only the pixel portion but also the driving circuit portion, so that very high reliability is obtained and operation characteristics can also be improved. First, a TFT having a structure to decrease hot carrier injection so as not to drop the operation speed thereof as much as possible is used as an n-channel type TFT **205** of a CMOS circuit forming a driving circuit. Note that the driving circuit here includes a shift register, a buffer, a level shifter, a sampling circuit (sample and hold circuit) and the like. In the case where digital driving is made, a signal conversion circuit such as a D/A converter can also be included.

In the case of this embodiment, as shown in FIG. 6C, the active layer of the n-channel TFT **205** includes a source region **355**, a drain region **356**, an LDD region **357** and a channel forming region **358**, and the LDD region **357** overlaps with the gate electrode **313** through the gate insulating film **311**.

Consideration not to drop the operation speed is the reason why the LDD region is formed at only the drain region side. In this n-channel type TFT **205**, it is not necessary to pay attention to an off current value very much, rather, it is better to give importance to an operation speed. Thus, it is desirable that the LDD region **357** is made to completely overlap with the gate electrode to decrease a resistance component to a minimum. That is, it is preferable to remove the so-called offset.

Furthermore, deterioration of the p-channel type TFT **206** in the CMOS circuit due to the injection of hot carriers is almost negligible, and thus, it is not necessary to provide any LDD region for the p-channel type TFT **206**. It is of course possible to provide the LDD region for the p-channel type TFT **206**, similarly for the n-channel type TFT **205**, to exhibit countermeasure against the hot carriers.

Note that, among the driving circuits, the sampling circuit is somewhat unique compared to the other circuits, in that a large electric current flows in both directions in the channel forming region. Namely, the roles of the source region and the drain region are interchanged. In addition, it is necessary to control the value of the off current to be as small as possible, and with that in mind, it is preferable to use a TFT having functions which are on an intermediate level between the switching **1** and the current control TFT in the sampling circuit. A combination of an n-channel type TFT **207** and a p-channel type TFT **208** as shown in FIG. 10 is used as the sampling circuit in embodiment 1.

Accordingly, in the n-channel type TFT for forming the sampling circuit, it is desirable to arrange the TFTs having the structure as shown in FIG. 10. As illustrated in FIG. 10, portions of the LDD regions **901a** and **901b** overlap the gate electrode **903** through the gate insulating film **902**. The advantages obtainable by this structure have been already described with respect to the current control TFT **202**. In the case where the TFT is used for the sampling circuit, the LDD regions are disposed to interpose the channel forming region **904** therebetween, which is different from the case of the current control TFT.

In the actual process, after the structure shown in FIG. 6C is completed, the EL layer is sealed in the closed space by using the counter substrate provided with the light shielding film, as previously described with reference to FIGS. 1 and 2.

At this time, the reliability (lifetime) of the EL layer can be improved by setting an inert atmosphere within the closed space or disposing a moisture absorbing material (e.g., barium oxide) in the closed space. Such a sealing process of the EL layer can be performed by using the technique to be used in the cell assembly step for liquid crystal display devices.

After the sealing process of the EL layer is completed, a connector (flexible print circuit: FPC) is attached for connecting the terminals extended from the elements or circuits formed on the substrate to external signal terminals, thereby completing a final product.

Here, the structure of the active matrix EL display device of this embodiment will be described with reference to a perspective view of FIG. 7. The active matrix EL display device of this embodiment is constituted by a pixel portion **602**, a gate side driving circuit **603**, and a source side driving circuit **604** formed on a glass substrate **601**. A switching TFT **605** of a pixel portion is an n-channel type TFT, and is disposed at an intersection point of a gate wiring line **606** connected to the gate side driving circuit **603** and a source wiring line **607** connected to the source side driving circuit **604**. The drain of the switching TFT **605** is connected to the gate of a current control TFT **608**.

Furthermore, the source side of the current control TFT **608** is connected to the power supply line **609**. In the structure in accordance with the present embodiment, the power supply line **609** is connected to the source of the EL element **610**, and the drain of the current control TFT **608** is connected to the EL element **610**.

If the current control TFT **608** is an n-channel type TFT, then a cathode of the EL element **610** is electrically connected to the drain. Further, in a case of using a p-channel type TFT for the current control TFT **608**, an anode of the EL element **610** is electrically connected to the drain.

Input/output wiring lines (connection wiring lines) **612** and **613** for transmitting signals to the driving circuits and a connection wiring line **614** connected to the current supply line **609** are provided in an FPC **611** as an external input/output terminal.

An example of circuit structure of the EL display device shown in FIG. 7 is shown in FIG. 8. The EL display device of this embodiment includes a source side driving circuit **701**, a gate side driving circuit (A) **707**, a gate side driving circuit (B) **711**, and a pixel portion **706**. Note that in the present specification, the term driving circuit is a general term including the source side driving circuit and the gate side driving circuit.

The source side driving circuit **701** is provided with a shift register **702**, a level shifter **703**, a buffer **704**, and a sampling circuit (sample and hold circuit) **705**. The gate side driving circuit (A) **707** is provided with a shift register **708**, a level shifter **709**, and a buffer **710**. The gate side driving circuit (B) **711** also has the same structure.

Here, the shift registers **702** and **708** have driving voltages of 5 to 16 V (typically 10 V) respectively, and the structure indicated by **205** in FIG. 6C is suitable for an n-channel type TFT used in a CMOS circuit forming the circuit.

Besides, for each of the level shifters **703** and **709** and the buffers **704** and **710**, similarly to the shift register, the CMOS circuit including the n-channel type TFT **205** of FIG. 6C is suitable. Note that it is effective to make a gate wiring line a multi-gate structure such as a double gate structure or a triple gate structure in improving reliability of each circuit.

Besides, since the source region and the drain region are inverted and it is necessary to decrease an off current value, a CMOS circuit including the n-channel type TFT **208** of FIG. 10 is suitable for the sampling circuit **705**.

The pixel portion **706** is disposed with pixels having the structure shown in FIG. **2**.

The foregoing structure can be easily realized by manufacturing TFTs in accordance with the manufacturing steps shown in FIGS. **4A** to **6C**. In this embodiment, although only the structure of the pixel portion and the driving circuit is shown, if the manufacturing steps of this embodiment are used, it is possible to form a logical circuit other than the driving circuit, such as a signal dividing circuit, a D/A converter circuit, an operational amplifier circuit, a α -correction circuit, or the like on the same substrate, and further, it is considered that a memory portion, a microprocessor, or the like can be formed.

Furthermore, the EL display device in accordance with the present embodiment will be described with reference to FIGS. **11A** and **11B**. The reference signs used in FIGS. **7** and **8** are referred if necessary.

A substrate **1000** (including an base film beneath TFTs) is an active matrix substrate. On the substrate, a pixel portion **1001**, a source side driving circuit **1002**, and a gate side driving circuit **1003** are formed. Various wirings from the respective driving circuits are extended through connection wirings **612** to **614** to reach an FPC **611** and be connected to an external device.

At this time, a counter substrate **1004** is provided to surround at least the pixel portion, and more preferably, the driving circuits and the pixel portion. The counter substrate **1004** is adhered to the active matrix substrate **1000** by means of an adhesive (sealing agent) **1005** to form a closed space **1006**. Thus, the EL element is completely sealed in the closed space **1006** and shut out from the external air.

In the present embodiment, a photocurable epoxy resin is used as the adhesive **1005**. Alternatively, other adhesives such as an acrylate type resin can also be used. A thermosetting resin can be also used if acceptable in view of heat-resistance of the EL element. Note that the material is required to prevent oxygen and water from passing therethrough as much as possible. The adhesive **1005** can be applied by a coating device such as a dispenser.

Furthermore, in the present embodiment, the closed space **1006** between the counter substrate **1004** and the active matrix substrate **1000** is filed with nitrogen gas. Moreover, the counter substrate **1004** is provided on its inner side (on the side closer to the closed space) with a light shielding film **1007** and a color filter **1008**, as described with reference to FIGS. **1** and **2**. In the present embodiment, a resin film containing barium oxide and a black-colored pigment is used as the light shielding film **1007**, and a resin film containing a red-colored, green-colored, or blue-colored pigment can be used as the color filter **1008**.

Furthermore, as shown in FIG. **11B**, the pixel portion is provided with a plurality of pixels each including an individually separated EL element. All of these EL elements share an anode **1009** as a common electrode. The EL layer may be provided only in the pixel portion, but is not required to be disposed over the driving circuits. In order to selectively provide the EL layer, a vapor deposition method employing a shadow mask, a lift-off method, a dry etching method, or a laser scribing method can be used.

The anode **1009** is electrically connected to a connection wiring **1010**. The connection wiring **1010** is a power supply line to be used for supplying a predetermined voltage to the anode **1009**, and is connected to the FPC **611** through a conductive paste material **1011**. Although only the connection wiring **1010** is described herein, the other connection wirings **612** to **614** are also electrically connected to the FPC **611** in the similar manner.

As described above, the structure as shown in FIGS. **11A** and **11B** can display an image on its pixel portion by connecting the FPC **611** to a terminal of an external device. In the present specification, the EL display device is defined as a product in which an image display becomes possible when an FPC is attached thereto, in other words, a product obtained by attaching an active matrix substrate to a counter substrate (including the one provided with an FPC attached thereto.) [Embodiment 2]

In this embodiment, an example in which a structure of a pixel is made different from the structure shown in FIG. **3B** will be described with reference to FIG. **12**. In this embodiment, two pixels shown in FIG. **3B** are arranged to become symmetrical with respect to a current supply line **212** which applies ground electric potential. That is, as shown in FIG. **12**, a current supply line **213** is made common to two adjacent pixels, so that the number of necessary wiring lines can be reduced. Incidentally, a TFT structure or the like arranged in the pixel may remain the same.

If such structure is adopted, it becomes possible to manufacture a more minute pixel portion, and the quality of an image is improved.

Incidentally, the structure of this embodiment can be easily realized in accordance with the manufacturing steps of the embodiment 1, and with respect to the TFT structure or the like, the description of the embodiment 1 or FIG. **2** may be referred to.

[Embodiment 3]

Although the description has been made on the case of the top gate type TFT in the embodiments 1 and 2, the present invention is not limited to the TFT structure, and may be applied to a bottom gate type TFT (typically, inverted stagger type TFT). Besides, the inverted stagger type TFT may be formed by any means. Since the inverted stagger type TFT has such a structure that the number of steps can be easily made smaller than the top gate type TFT, it is very advantageous in reducing the manufacturing cost, which is the object of the present invention. Incidentally, the structure of this embodiment can be freely combined with any structure of the embodiments 2 and 3.

[Embodiment 4]

FIG. **3B** shows that the amount of the off current value in the switching TFT in the pixel of the EL display device is reduced by using a multi-gate structure for the switching TFT, and the need for a storage capacitor is eliminated. However, it is also acceptable to make a structure of disposing a storage capacitor as is done conventionally. In this case, as shown in FIG. **14**, a storage capacitor **1301** is formed in parallel to the gate of the current control TFT **202** with respect to the drain of the switching TFT **201**.

Note that the constitution of embodiment 4 can be freely combined with any constitution of embodiments 1 to 3. Namely, a storage capacitor is merely formed within a pixel and it is not to limit the TFT structure, materials of EL layer, etc.

[Embodiment 5]

Laser crystallization is used as the means of forming the crystalline silicon film **302** in embodiment 1, and a case of using a different means of crystallization is explained in embodiment 5.

After forming an amorphous silicon film in embodiment 5, crystallization is performed using the technique recorded in Japanese Patent Application Laid-open No. Hei 7-130652. The technique recorded in the above patent application is one of obtaining a crystalline silicon film having good crystallinity by using an element such as nickel as a catalyst for promoting crystallization.

Further, after the crystallization process is completed, a process of removing the catalyst used in the crystallization may be performed. In this case, the catalyst may be gettered using the technique recorded in Japanese Patent Application Laid-open No. Hei 10-270363 or Japanese Patent Application Laid-open No. Hei 8-330602.

In addition, a TFT may be formed using the technique recorded in the specification of Japanese Patent Application No. Hei 11-076967 by the applicant of the present invention.

The processes of manufacturing shown in embodiment 1 are one embodiment of the present invention, and provided that the structure of FIG. 1 or of FIG. 6C of embodiment 1 can be realized, then other manufacturing process may also be used without any problems, as above.

Note that it is possible to freely combine the constitution of embodiment 5 with the constitution of any of embodiments 1 to 4.

[Embodiment 6]

In driving the EL display device of the present invention, analog driving can be performed using an analog signal as an image signal, and digital driving can be performed using a digital signal.

When analog driving is performed, the analog signal is sent to a source wiring of a switching TFT, and the analog signal, which contains gray scale information, becomes the gate voltage of a current control TFT. The current flowing in an EL element is then controlled by the current control TFT, the EL element emitting intensity is controlled, and gray scale display is performed.

On the other hand, when digital driving is performed, it differs from the analog type gray scale display, and gray scale display is performed by time division driving.

The EL element has an extremely fast response speed in comparison to a liquid crystal element, and therefore it is possible to have high speed driving. Therefore, the EL element is one, which is suitable for time ratio gray scale driving, in which one frame is partitioned into a plural number of subframes and then gray scale display is performed.

The present invention is a technique related to the element structure, and therefore any method of driving it may thus be used.

[Embodiment 7]

The EL display device uses light emitted from itself, and thus, does not require any back light. A reflection type liquid crystal display device requires a back light in a dark place where sufficient light is not available, although it has a feature in that an image can be displayed with outdoor light. On the other hand, the EL display device is not suffered from such a disadvantage in a dark place, since it is of the self-emission type.

However, when an electronic device including the EL display device as its display portion is actually used outdoors, it may be of course used both in a light place and in a dark place. In such a situation, an image can be sufficiently recognized in a dark place even when the luminance is not so high, while an image may not be recognized in a light place if the luminance is not sufficiently high.

An amount of light emitted from the EL layer varies depending on an amount of current to flow. Thus, a larger amount of current to flow requires the higher luminance, resulting in an increased power consumption. However, when the luminance of emitted light is set at such a high level, too brighter image than necessary with too large power consumption will be displayed in a dark place.

In order to overcome the above-mentioned disadvantage, the EL display device in accordance with the present invention preferably has a function to detect the lightness in the

surrounding atmosphere by means of a sensor, and adjust the luminance of the light emitted from the EL layer in accordance with the sensed lightness. More specifically, the luminance of the emitted light is set at a high level in a light place, while at a low level in a dark place, so that an increase in power consumption is avoided. Thus, the EL display device in accordance with the present invention can realize reduction in power consumption.

As a sensor to be used for detecting lightness in the surrounding atmosphere, a CMOS sensor, a CCD or the like can be used. A CMOS sensor can be formed with any known technique on the identical substrate with driving circuits and a pixel portion of the EL display device. A semiconductor chip on which a CCD is formed can be attached onto the EL display device. Alternatively, a CCD or a CMOS sensor may be provided as a portion of an electronic device including the EL display device as its display portion.

A circuit for adjusting a current to flow into the EL layer based on a signal obtained by the sensor for detecting the lightness in the surrounding atmosphere is provided. Thus, the luminance of the light emitted from the EL layer can be adjusted in accordance with the lightness in the surrounding atmosphere.

The structure in the present embodiment is applicable in combination with any structure in Embodiment 1 through 6.

Although the preferred embodiments of the present invention utilize thin film transistors as switching elements formed over an insulating substrate, it is possible to utilize a silicon substrate. In this case, insulated gate field effect transistors formed with the silicon substrate can be used as switching elements.

[Embodiment 8]

The EL display device fabricated in accordance with the present invention is of the self-emission type, and thus exhibits more excellent recognizability of the displayed image in a light place as compared to the liquid crystal display device. Furthermore, the EL display device has a wider viewing angle. Accordingly, the EL display device can be applied to a display portion in various electronic devices. For example, in order to view a TV program or the like on a large-sized screen, the EL display device in accordance with the present invention can be used as a display portion of an EL display (i.e., a display in which an EL display device is installed into a frame) having a diagonal size of 30 inches or larger (typically 40 inches or larger.)

The EL display includes all kinds of displays to be used for displaying information, such as a display for a personal computer, a display for receiving a TV broadcasting program, a display for advertisement display. Moreover, the EL display device in accordance with the present invention can be used as a display portion of other various electric devices.

Such electronic devices include a video camera, a digital camera, a goggles-type display (head mount display), a car navigation system, a car audio equipment, note-size personal computer, a game machine, a portable information terminal (a mobile computer, a portable telephone, a portable game machine, an electronic book, or the like), an image reproduction apparatus including a recording medium (more specifically, an apparatus which can reproduce a recording medium such as a compact disc (CD), a laser disc (LD), a digital video disc (DVD), and includes a display for displaying the reproduced image), or the like. In particular, in the case of the portable information terminal, use of the EL display device is preferable, since the portable information terminal that is likely to be viewed from a tilted direction is often required to have a wide viewing angle. FIGS. 14A to 14F respectively show various specific examples of such electronic devices.

FIG. 14A illustrates an EL display which includes a frame 2001, a support table 2002, a display portion 2003, or the like. The present invention is applicable to the display portion 2003. The EL display is of the self-emission type and therefore requires no back light. Thus, the display portion thereof can have a thickness thinner than that of the liquid crystal display device.

FIG. 14B illustrates a video camera which includes a main body 2101, a display portion 2102, an audio input portion 2103, operation switches 2104, a battery 2105, an image receiving portion 2106, or the like. The EL display device in accordance with the present invention can be used as the display portion 2102.

FIG. 14C illustrates a portion (the right-half piece) of an EL display of head mount type, which includes a main body 2201, signal cables 2202, a head mount band 2203, a display portion 2204, an optical system 2205, an EL display device 2206, or the like. The present invention is applicable to the EL display device 2206.

FIG. 14D illustrates an image reproduction apparatus including a recording medium (more specifically, a DVD reproduction apparatus), which includes a main body 2301, a recording medium (a CD, an LD, a DVD or the like) 2302, operation switches 2303, a display portion (a) 2304, another display portion (b) 2305, or the like. The display portion (a) is used mainly for displaying image information, while the display portion (b) is used mainly for displaying character information. The EL display device in accordance with the present invention can be used as these display portions (a) and (b). The image reproduction apparatus including a recording medium further includes a CD reproduction apparatus, a game machine or the like.

FIG. 14E illustrates a portable (mobile) computer which includes a main body 2401, a camera portion 2402, an image receiving portion 2403, operation switches 2404, a display portion 2405, or the like. The EL display device in accordance with the present invention can be used as the display portion 2405.

FIG. 14F illustrates a personal computer which includes a main body 2501, a frame 2502, a display portion 2503, a key board 2504, or the like. The EL display device in accordance with the present invention can be used as the display portion 2503.

When the brighter luminance of light emitted from the EL material becomes available. In the future, the EL display device in accordance with the present invention will be applicable to a front-type or rear-type projector in which light including output image information is enlarged by means of lenses or the like to be projected.

The aforementioned electronic devices are more likely to be used for display information distributed through a telecommunication path such as Internet, a CATV (cable television system), and in particular likely to display moving picture information. The EL display device is suitable for displaying moving pictures since the EL material can exhibit high response speed. However, if the contour between the pixels becomes unclear, the moving pictures as a whole cannot be clearly displayed. Since the EL display device in accordance with the present invention can make the contour between the pixels clear, it is significantly advantageous to apply the EL display device of the present invention to a display portion of the electronic devices.

A portion of the EL display device that is emitting light consumes power, so it is desirable to display information in such a manner that the light emitting portion therein becomes as small as possible. Accordingly, when the EL display device is applied to a display portion which mainly displays charac-

ter information, e.g., a display portion of a portable information terminal, and more particularly, a portable telephone or a car audio equipment, it is desirable to drive the EL display device so that the character information is formed by a light-emitting portion while a non-emission portion corresponds to the background.

With now reference to FIG. 15A, a portable telephone is illustrated, which includes a main body 2601, an audio output portion 2602, an audio input portion 2603, a display portion 2604, operation switches 2605, and an antenna 2606. The EL display device in accordance with the present invention can be used as the display portion 2604. The display portion 2604 can reduce power consumption of the portable telephone by displaying white-colored characters on a black-colored background.

FIG. 15B illustrates a car audio equipment which includes a main body 2701, a display portion 2702, and operation switches 2703 and 2704. The EL display device in accordance with the present invention can be used as the display portion 2702. Although the car audio equipment of the mount type is shown in the present embodiment, the present invention is also applicable to a car audio of the set type. The display portion 2702 can reduce power consumption by displaying white-colored characters on a black-colored background, which is particularly advantageous for the car audio of the set type.

As set forth above, the present invention can be applied variously to a wide range of electronic devices in all fields. The electronic device in the present embodiment can be obtained by utilizing an EL display device having the configuration in which the structures in Embodiments 1 through 7 are freely combined.

In accordance with the present invention, in the pixel portion of the EL display device, the contour between the pixels can be made clear, and the EL display device capable of displaying an image with high definition can be provided. Moreover, in the present invention the light shielding film to be used for concealing the gaps between the pixels is provided on the counter substrate, thereby preventing yield from decreasing. Furthermore, the EL display device in accordance with the present invention can be fabricated by using a manufacturing line for liquid crystal display devices, and thus, equipment investment can be suppressed to a small level.

Accordingly, in accordance with the present invention, an inexpensive EL display device capable of displaying an image with high definition can be obtained. Furthermore, the present invention can also provide an electronic device having a display portion with a high recognizability by utilizing such an EL display device as the display portion.

What is claimed is:

1. A display device comprising:

a first pixel over a first substrate;

a second pixel over the first substrate, the second pixel being adjacent to the first pixel;

a first line;

a second line;

a third line;

a fourth line;

a second substrate;

a first color filter between the first substrate and the second substrate; and

a second color filter between the first substrate and the second substrate;

wherein the first pixel comprises a first transistor, a second transistor and a first electroluminescence element,

25

wherein the second pixel comprises a third transistor, a fourth transistor and a second electroluminescence element,
 wherein one of a source and a drain of the first transistor is electrically connected to the first line,
 wherein one of a source and a drain of the second transistor is electrically connected to a gate of the first transistor,
 wherein the other of the source and the drain of the second transistor is electrically connected to the second line,
 wherein a gate of the second transistor is electrically connected to the fourth line,
 wherein the first electroluminescence element is electrically connected to the other of the source and the drain of the first transistor,
 wherein one of a source and a drain of the third transistor is electrically connected to the first line,
 wherein one of a source and a drain of the fourth transistor is electrically connected to a gate of the third transistor,
 wherein the other of the source and the drain of the fourth transistor is electrically connected to the third line,
 wherein a gate of the fourth transistor is electrically connected to the fourth line,
 wherein the second electroluminescence element is electrically connected to the other of the source and the drain of the third transistor,
 wherein the first color filter comprises a first region that overlaps with the first electroluminescence element,
 wherein the second color filter comprises a second region that overlaps with the second electroluminescence element,
 wherein the first color filter has a first color,
 wherein the second color filter has a second color different from the first color,
 wherein the first color filter overlaps with the second transistor, and
 wherein the first color is red.

2. The display device according to claim 1, wherein each of the first transistor, the second transistor, the third transistor and the fourth transistor is a top gate type transistor.

3. The display device according to claim 1, wherein each of the second transistor and the fourth transistor is a multi gate transistor.

4. The display device according to claim 1, wherein each of the first color filter and the second color filter is in contact with the second substrate.

5. The display device according to claim 1,
 wherein the first electroluminescence element has a top emission structure, and
 wherein the second electroluminescence element has a top emission structure.

6. The display device according to claim 1,
 wherein the first electroluminescence element comprises a third region that overlaps with one of the first transistor and the second transistor, and
 wherein the second electroluminescence element comprises a fourth region that overlaps with one of the third transistor and the fourth transistor.

7. The display device according to claim 1,
 wherein the first line is a power supply line,
 wherein the second line is a first source line,
 wherein the third line is a second source line, and
 wherein the fourth line is a gate line.

8. A display module comprises the display device according to claim 1 and a flexible print circuit.

9. An electronic device comprises the display module according to claim 8 and at least one of a battery, an audio

26

output portion, an audio input portion, an antenna, an operation switch and a recording medium.

10. A display device comprising:

a first pixel over a first substrate;
 a second pixel over the first substrate, the second pixel being adjacent to the first pixel;
 a first line;
 a second line;
 a third line;
 a fourth line;
 a second substrate;
 a first color filter between the first substrate and the second substrate; and
 a second color filter between the first substrate and the second substrate;
 wherein the first pixel comprises a first transistor, a second transistor and a first electroluminescence element,
 wherein the second pixel comprises a third transistor, a fourth transistor and a second electroluminescence element,
 wherein one of a source and a drain of the first transistor is electrically connected to the first line,
 wherein one of a source and a drain of the second transistor is electrically connected to a gate of the first transistor,
 wherein the other of the source and the drain of the second transistor is electrically connected to the second line,
 wherein a gate of the second transistor is electrically connected to the fourth line,
 wherein the first electroluminescence element is electrically connected to the other of the source and the drain of the first transistor,
 wherein one of a source and a drain of the third transistor is electrically connected to the first line,
 wherein one of a source and a drain of the fourth transistor is electrically connected to a gate of the third transistor,
 wherein the other of the source and the drain of the fourth transistor is electrically connected to the third line,
 wherein a gate of the fourth transistor is electrically connected to the fourth line,
 wherein the second electroluminescence element is electrically connected to the other of the source and the drain of the third transistor,
 wherein the first color filter comprises a first region that overlaps with the first electroluminescence element,
 wherein the second color filter comprises a second region that overlaps with the second electroluminescence element,
 wherein an insulating layer is positioned over the first electroluminescence element and the second electroluminescence element,
 wherein the insulating layer comprises silicon, nitride and oxygen,
 wherein the first color filter has a first color,
 wherein the second color filter has a second color different from the first color,
 wherein the first color filter overlaps with the second transistor, and
 wherein the first color is red.

11. The display device according to claim 10, wherein each of the first transistor, the second transistor, the third transistor and the fourth transistor is a top gate type transistor.

12. The display device according to claim 10, wherein each of the second transistor and the fourth transistor is a multi gate transistor.

13. The display device according to claim 10, wherein each of the first color filter and the second color filter is in contact with the second substrate.

27

14. The display device according to claim 10,
wherein the first electroluminescence element has a top
emission structure, and
wherein the second electroluminescence element has a top
emission structure. 5

15. The display device according to claim 10,
wherein the first electroluminescence element comprises a
third region that overlaps with one of the first transistor
and the second transistor, and
wherein the second electroluminescence element com- 10
prises a fourth region that overlaps with one of the third
transistor and the fourth transistor.

16. The display device according to claim 10,
wherein the first line is a power supply line,
wherein the second line is a first source line, 15
wherein the third line is a second source line, and
wherein the fourth line is a gate line.

17. A display module comprises the display device accord-
ing to claim 10 and a flexible print circuit.

18. An electronic device comprises the display module 20
according to claim 17 and at least one of a battery, an audio
output portion, an audio input portion, an antenna, an opera-
tion switch and a recording medium.

* * * * *

28

UNITED STATES PATENT AND TRADEMARK OFFICE
CERTIFICATE OF CORRECTION

PATENT NO. : 8,735,900 B2
APPLICATION NO. : 13/899893
DATED : May 27, 2014
INVENTOR(S) : Shunpei Yamazaki et al.

Page 1 of 1

It is certified that error appears in the above-identified patent and that said Letters Patent is hereby corrected as shown below:

In the Specification:

Column 3, Line 27; Change "(i.e.," to --(i.e.--.
Column 6, Line 6; Change "device:" to --device--.
Column 6, Line 16; Change "an . electronic" to --an electronic--.
Column 9, Line 1; Change "13" to --1.5--.
Column 9, Line 6; Change "13" to --1.5--.
Column 9, Line 12; Change "Should" to --should--.
Column 10, Line 29; Change "pasivation" to --passivation--.
Column 11, Line 66; Change "in" to --In--.
Column 14, Line 9; Change "he made" to --be made--.
Column 14, Line 57; Change "process. and" to --process, and--.
Column 15, Line 49; Change "450'C" to --450°C--.
Column 16, Line 2; Change "a to sputtering" to --a sputtering--.
Column 16, Lines 31 to 32; Change "is : formed." to --is formed--.
Column 17, Line 49; Change "switching 1 and" to --switching TFT and--.
Column 23, Line 45; Change "available In the" to --available in the--.
Column 24, Line 42; Change "liquid :crystal" to --liquide crystal--.

Signed and Sealed this
Seventh Day of October, 2014



Michelle K. Lee
Deputy Director of the United States Patent and Trademark Office

专利名称(译)	显示设备		
公开(公告)号	US8735900	公开(公告)日	2014-05-27
申请号	US13/899893	申请日	2013-05-22
[标]申请(专利权)人(译)	株式会社半导体能源研究所		
申请(专利权)人(译)	半导体能源研究所有限公司.		
当前申请(专利权)人(译)	半导体能源研究所有限公司.		
[标]发明人	YAMAZAKI SHUNPEI MIZUTAMI MAYUMI KONUMA TOSHIMITSU		
发明人	YAMAZAKI, SHUNPEI MIZUTAMI, MAYUMI KONUMA, TOSHIMITSU		
IPC分类号	H05B33/04 H05B33/10 G09G3/30 H01L27/32 H01L29/04 H01L31/12 H05B33/22 H01L51/52		
CPC分类号	H01L2251/5315 H01L51/5284 H01L27/1218 H01L27/322 H01L27/124 H01L51/5253 H01L51/524 H01L51/5259 H01L27/3244 H01L51/5246		
代理机构(译)	HUSCH BLACKWELL LLP		
审查员(译)	HUYNH , ANDY		
优先权	1999264672 1999-09-17 JP 1999264680 1999-09-17 JP 1999336247 1999-11-26 JP 1999336248 1999-11-26 JP 13/117319 2012-05-22 US		
其他公开文献	US20130313558A1		
外部链接	Espacenet USPTO		

摘要(译)

多个像素布置在基板上。每个像素设置有EL元件，该EL元件利用连接到电流控制TFT的像素电极作为阴极。在对向基板上，提供遮光膜，具有第一颜色的第一滤色器和具有第二颜色的第二滤色器。第二种颜色与第一种颜色不同。

