



US 20180040671A1

(19) **United States**

(12) **Patent Application Publication**  
Miyake et al.

(10) **Pub. No.: US 2018/0040671 A1**  
(43) **Pub. Date: Feb. 8, 2018**

(54) **DISPLAY DEVICE**

(71) Applicant: **Japan Display Inc.**, Tokyo (JP)

(72) Inventors: **Hidekazu Miyake**, Tokyo (JP);  
**Kazufumi Watabe**, Tokyo (JP);  
**Yoshinori Ishii**, Tokyo (JP)

(21) Appl. No.: **15/660,276**

(22) Filed: **Jul. 26, 2017**

(30) **Foreign Application Priority Data**

Aug. 3, 2016 (JP) ..... 2016-152758

**Publication Classification**

(51) **Int. Cl.**  
**H01L 27/32** (2006.01)  
**G06F 3/041** (2006.01)

(52) **U.S. Cl.**

CPC ..... **H01L 27/323** (2013.01); **G06F 3/0412**  
(2013.01); **H01L 27/3276** (2013.01); **G06F**  
**3/044** (2013.01)

(57) **ABSTRACT**

The organic EL display device includes a TFT substrate on which a scanning line extends in a first direction, a video signal line extends in a second direction, and a pixel having an anode, an organic EL layer, and a cathode is formed on a region enclosed with the scanning line and the video signal line. A first detection electrode extends in the first direction above the pixel via insulation films. A counter substrate is disposed while covering the first detection electrode via an adhesive. A second detection electrode extends in the second direction at the outer side of the counter substrate.




FIG. 1




FIG. 2




FIG. 3




FIG. 4




FIG. 5




FIG. 6




FIG. 7




FIG. 8




FIG. 9




FIG. 10




FIG. 11




FIG. 12




FIG. 13




FIG. 14




FIG. 15




FIG. 16




FIG. 17




FIG. 18




FIG. 19





FIG. 20



**DISPLAY DEVICE****CLAIM OF PRIORITY**

**[0001]** The present application claims priority from Japanese Patent Application JP 2016-152758 filed on Aug. 3, 2016, the content of which is hereby incorporated by reference into this application.

**BACKGROUND**

**[0002]** The present invention relates to a display device, and more particularly, to a display section having a touch panel built in an organic EL display device.

**[0003]** Touching the surface of the display device with the user's finger has become common input process for the display device of the smart phone or the tablet. Generally, the touch panel is disposed on the display region. The liquid crystal display panel with built-in touch panel function has been developed for adaption to the liquid crystal display device.

**[0004]** Japanese Unexamined Patent Application Publication No. 2016-1233 discloses the liquid crystal display panel with built-in touch panel function. The disclosed liquid crystal display panel is configured to dispose one of electrodes of the touch panel at the outer side of the counter substrate, and to allow the common electrode inside the liquid crystal display panel to be used as the other electrode of the touch panel.

**SUMMARY**

**[0005]** The organic EL display device of self-luminous type is capable of generating the high contrast image. The device requires no backlight, which is advantageous in thinning the display device as a whole. Meanwhile, the use of the touch panel for the organic EL display device has also been demanded.

**[0006]** Mounting the touch panel onto the organic EL display device may increase its thickness by the amount corresponding to that of the touch panel, thus lessening the advantageous feature of the organic EL display device providing the thinning effect. The present invention provides the organic EL display device with built-in touch panel function.

**[0007]** The present invention has been made to overcome the aforementioned problem, which is configured as below.

(1) An organic EL display device includes a TFT substrate on which a scanning line extends in a first direction, a video signal line extends in a second direction, and a pixel having an anode, an organic EL layer and a cathode is formed on a region enclosed with the scanning line and the video signal line. A first electrode of a touch panel extends above the pixel in the first direction via an insulation film. A counter substrate is disposed while covering the first electrode of the touch panel. A second electrode of the touch panel extends in the second direction at an outer side of the counter substrate.

(2) According to the description (1), the second electrode is formed at the outer side of the counter substrate.

(3) According to the description (1), the second electrode is formed at the inner side of the counter substrate.

**BRIEF DESCRIPTION OF THE DRAWINGS**

**[0008]** FIG. 1 is a perspective view of an organic EL display device;

**[0009]** FIG. 2 is a plan view of a TFT substrate according to the present invention;

**[0010]** FIG. 3 is a plan view of a counter substrate according to the present invention;

**[0011]** FIG. 4 is a plan view showing an example of a detection electrode Y (Rx);

**[0012]** FIG. 5 is a plan view showing another example of the detection electrode Y (Rx);

**[0013]** FIG. 6 is a plan view showing an example of a detection electrode X (Tx);

**[0014]** FIG. 7 is a sectional view representing the principle of a touch panel of electrostatic capacity type;

**[0015]** FIG. 8 is a sectional view of a structure according to a first embodiment;

**[0016]** FIG. 9 is a sectional view of a TFT substrate according to the first embodiment;

**[0017]** FIG. 10 is a sectional view representing the state that the counter substrate is bonded to the TFT substrate;

**[0018]** FIG. 11 is a sectional view representing the state that the counter substrate is thinned through polishing;

**[0019]** FIG. 12 is a sectional view representing the state that an overcoat film is applied to cover the detection electrode Y (Rx) formed on the polished counter substrate;

**[0020]** FIG. 13 is an equivalent circuit diagram of a pixel;

**[0021]** FIG. 14 is a plan view representing a pixel layer structure corresponding to FIG. 13;

**[0022]** FIG. 15 is a plan view representing a first example of the detection electrode X (Tx);

**[0023]** FIG. 16 is a plan view representing a second example of the detection electrode X (Tx);

**[0024]** FIG. 17 is a sectional view representing a structure according to a second embodiment;

**[0025]** FIG. 18 is a sectional view representing the state that the counter substrate is disposed according to the second embodiment;

**[0026]** FIG. 19 is a sectional view representing the state that the counter substrate is thinned through polishing; and

**[0027]** FIG. 20 is a sectional view representing the structure according to a third embodiment.

**DETAILED DESCRIPTION**

**[0028]** The present invention will be described in detail referring to embodiments.

**First Embodiment**

**[0029]** FIG. 1 is a perspective view of an organic EL display device having built-in touch panel according to the present invention. Referring to FIG. 1, a counter substrate **200** is disposed on a TFT substrate **100** on which an organic EL device, a power source line, a scanning line, a video signal line and the like are formed. The counter substrate **200** is made of glass for protecting the organic EL device from external penetration of moisture. A flexible wiring substrate **60** for touch panel is connected to the counter substrate **200**.

**[0030]** A driver IC **40** for driving the video signal line and the like is disposed on the TFT substrate **100**, to which a flexible wiring substrate **50** is connected. The flexible wiring substrate **50** supplies power, video signals, clock signals and the like. As FIG. 1 shows, the code Rx denotes a touch panel detection electrode Y formed at the outer side of the counter substrate **200**. The Rx may be formed at the inner side of the counter substrate. The code Tx denotes a touch panel detection electrode X formed on the TFT substrate **100**. The Tx

intersects the Rx in planar view. According to the present invention, the touch panel is built in the organic EL display device as shown in FIG. 1.

**[0031]** FIG. 2 is a plan view schematically showing the TFT substrate **100** of the organic EL display device. Referring to FIG. 2, scanning line drive circuits **20** are formed at both sides of the TFT substrate **100**. Scanning lines from the scanning line drive circuits **20** extends transversely. Tx drive circuits **30** for driving the touch panel detection electrodes X (hereinafter referred to as detection electrode X or Tx) are disposed at the outer side of the respective scanning line drive circuits **20**. The n transversely extending detection electrodes Tx are arranged in the longitudinal direction.

**[0032]** The driver IC **40** is disposed at the lower side as shown in FIG. 2, from which the video signal lines extend longitudinally. As shown in FIG. 2, the flexible wiring substrate **50** is connected to the TFT substrate **100**. The flexible wiring substrate **50** supplies the video signals, the clock signals, power, and the like to the driver IC **40**.

**[0033]** Pixels are arranged in a matrix on the TFT substrate **100**. FIG. 2 represents the pixel array structure Pix having the pixels arranged in the same direction as the extending direction of the scanning line. In other words, each of the pixel arrays Pix may be collectively selected by the scanning line. The term "Pix 1 to Pix n" represents the array of n pixel rows. As FIG. 2 shows, the detection electrode X (Tx) receives a signal supplied from the Tx drive circuit. The term "Tx 1 to Tx n" represents the array of n Tx rows.

**[0034]** FIG. 2 shows that arrays of Tx and Pix arranged in parallel one another. Actually, however, those Tx and Pix are formed while being overlapped one another in planar view. FIG. 2 shows that the number of electrodes Tx is the same as that of the pixels Pix. However, those numbers do not necessarily have to be the same.

**[0035]** FIG. 3 is a plan view of the counter substrate **200**. Referring to FIG. 3, m longitudinally extending touch panel detection electrodes Y (hereinafter referred to as detection electrode Y or Rx) are arrayed in the transverse direction. The flexible wiring substrate **60** for touch panel supplies the signal for driving the Rx. The capacitance generated between the Tx as shown in FIG. 2 and the Rx as shown in FIG. 3 changes its value in response to touching on the screen with the user's finger. The touched position is detected by sensing the capacitance change.

**[0036]** FIG. 4 represents an example of the detection electrode Rx. As FIG. 4 shows, thin stripe-like electrodes Rx are arrayed at predetermined pitches on the counter substrate **200**. The Rx is made of a transparent conductive film such as ITO (Indium Tin Oxide), ZnO (Zinc Oxide), or the metal film. The Rx does not have to be linearly formed. Specifically, in order to lessen moire caused by interference with the video signal lines and the power source lines formed on the TFT substrate **100**, the planar shape of the Rx may be formed into the zigzag, or the wave-like shape as shown in FIG. 5. The extending direction of the Rx as shown in FIG. 4 is the same as the one as shown in FIG. 5.

**[0037]** FIG. 6 is a plan view representing an example of the Tx. As FIG. 6 shows, the transversely extending scanning lines **10** are arrayed in the longitudinal direction. The longitudinally extending video signal lines **11** are arrayed in the transverse direction. The longitudinally extending power source lines **12** parallel to the video signal lines **11** are arrayed in the transverse direction. The pixel is formed on the region enclosed with the video signal line **11**, the power

source line **12**, and the scanning line **10**. In other words, a pixel **14** exists as the region enclosed with the scanning line **10** and the video signal line **11**. The Tx is formed as the part overlapped with the pixel in planar view. The Tx transversely extends between the scanning lines **10** to constitute the detection electrode X. The Tx is made of the transparent conductive film such as ITO (Indium Tin Oxide) and ZnO (Zinc Oxide), or the metal film.

**[0038]** FIG. 7 is a sectional view representing the principles of electrostatic type touch panel according to the present invention. As FIG. 7 shows, the Tx transversely extends on the TFT substrate **100**. The counter substrate **200** is disposed on the TFT substrate **100** via an adhesive **201**. The electrodes Rx which extend on the counter substrate **200** in the direction orthogonal to the drawing are arrayed at predetermined pitches. As FIG. 7 shows, the capacitance Ct is generated at the intersection area between the Rx as shown in FIG. 4 and the Tx as shown in FIG. 6. The capacitance Ct changes its value in response to touching on the screen by the user's finger. The touched position is detected by sensing the capacitance change.

**[0039]** FIG. 8 is a sectional view of the organic EL display device. The left part of FIG. 8 is the sectional view of the pixel part, and the right part is the sectional view of the part for supplying the signal to the Tx. As FIG. 8 shows, the TFT substrate **100** is made of such resin as polyimide, polyethylene terephthalate, and polyethylene naphthalate. Especially, the use of polyimide is preferable as it exhibits excellent properties of mechanical strength and thermal resistance. The thickness of the TFT substrate **100** ranges from 10  $\mu\text{m}$  to 20  $\mu\text{m}$ , serving as the flexible substrate. It is very difficult to subject the above-described thin substrate to the manufacturing process. Therefore, as described later, the TFT substrate **100** made of resin is formed on the glass substrate. The glass substrate will be removed later.

**[0040]** A base film **101** is formed on the TFT substrate **100**. The base film **101** is made of the laminated film, for example, SiO film, SiN film, and the like so as to prevent impurities from the TFT substrate **100** from contaminating a semiconductor layer **102**. For the purpose of ensuring barrier property against penetration of moisture, the aluminium oxide (AlO) film may be prepared as the base film.

**[0041]** The term AB (for example, SiO) as described herein represents the compound having constituent elements A and B. However, it does not mean that each element has the same composition ratio. The basic composition ratio is specified, but there may often be the case that such ratio deviates from the value of the basic composition ratio, in general, depending on manufacturing conditions.

**[0042]** The semiconductor layer **102** constituting the TFT (Thin Film Transistor) is formed on the base film **101**. Initially, the semiconductor layer **102** is formed by producing a-Si (amorphous silicon) through CVD, and then converting the a-Si into Poly-Si (polycrystal silicon) through excimer laser. Gate insulation film **103** is formed by using SiO made from TEOS (Tetraethyl orthosilicate), which covers the semiconductor layer **102**. Then a gate electrode **104** is formed on the gate insulation film **103**. Thereafter, ion implantation of phosphorus or boron is conducted so that conductivity is imparted to the part of the semiconductor layer **102**, which is not covered with the gate electrode **104** for forming a drain **1021** and a source **1022**.

**[0043]** An interlayer insulation film **105** is formed from SiN while covering the gate electrode **104**. A through hole

is formed in the interlayer insulation film **105** and the gate insulation film **103** for connection of a drain electrode **106** and a source electrode **107**. An organic passivation film **108** is formed while covering the drain electrode **106** and the source electrode **107**. As the material for forming the organic passivation film **108**, polyimide, acryl and the like may be used. The organic passivation film **108** is made of a photo-sensitive resin. The exposed portion of the photosensitive resin dissolves in developing fluid so that the through hole is made without using the resist.

[0044] Then a reflection electrode **109** is formed on the organic passivation film **108**. The reflection electrode **109** is connected to the source electrode **107** via the through hole formed in the organic passivation film **108**. The reflection electrode **109** is made of an Al alloy.

[0045] An anode **110** is formed on the reflection electrode **109** through ITO. Then a bank **111** is formed from an organic material such as acryl. The bank **111** serves to prevent step-out of an organic EL layer **112** to be formed later. Alternatively, the bank may serve as the partition between the respective pixels. The organic EL layer **112** is applied to the inside of the through hole formed in the bank **111**. The organic EL layer **112** is constituted by a plurality of layers including a hole injection layer, hole transport layer, luminous layer, electron transport layer, electron injection layer, and the like.

[0046] A cathode **113** is made of the transparent conductive film selected from any one of ITO, IZO (Indium Zinc Oxide), and AZO (Antimony Zinc Oxide). The cathode **113** is applied onto the entire surface of the display region. The cathode may be made of the metal thin film. The material for forming the cathode may be determined depending on the balance between the light transmittance and electric resistance.

[0047] A protective film **114** is formed from SiN, SiO, and the like through CVD while covering the cathode **113**. The AIO film may be formed to further ensure the barrier property. The AIO film is formed through sputtering. That is, the protective film may be formed as the laminated film constituted by SiN, SiO, and AIO.

[0048] As FIG. **8** shows, a flattening film **115** made of polyimide or acryl is applied onto the protective film. The touch panel detection electrode X (Tx) is formed on the flattening film **115**. The Tx may be made of the transparent conductive film such as ITO and ZnO, or the metal film.

[0049] Referring to the right part of FIG. **8**, the Tx extends to the periphery of the display region, and is connected to a Tx wiring **120** at the periphery via the through hole. The Tx wiring **120** is formed as the layer corresponding to those of the drain electrode **106**, the source electrode **107**, and the video signal line **11**, and made of the same material as the one for forming those elements. A signal for Tx is supplied via the Tx wiring **120**. The TFT substrate **100**, thus, is completed.

[0050] Referring to FIG. **8**, the counter substrate **200** on which the touch panel detection electrode Y (Rx) is formed is bonded via the adhesive **201**. The counter substrate **200** is made of glass, and has thickness ranging from 20  $\mu\text{m}$  to 150  $\mu\text{m}$ . The touch panel detection electrodes Y (Rx) at the outer side of the counter substrate **200** are arranged at predetermined pitches, and extend in the direction orthogonal to the drawing.

[0051] The pitch of the Rx may be determined in accordance with resolution of the touch panel. Therefore, the pitch

does not have to be finely set as shown in FIG. **8**. An overcoat film **202** made of resin such as acryl and epoxy is formed to cover the Rx for protective purpose. If humidity resistance is demanded, the overcoat film **202** may be made of the inorganic film such as SiO. The overcoat film **202** may be formed into the laminated structure constituted by the inorganic film and the organic film.

[0052] The overcoat film **202** is formed while being kept away from the terminal part of the counter substrate **200**. The flexible wiring substrate **60** for touch panel is connected to the terminal part of the counter substrate **200**, and outputs Rx signals. The touched position is detected by sensing change in the detection capacitance  $C_t$  formed between the Rx and Tx as shown in FIG. **8**.

[0053] The structure as shown in FIG. **8** is configured to have the counter substrate **200** made of glass, exhibiting significantly excellent property as the protective film for protecting the organic EL layer from penetration of moisture. Referring to the structure as shown in FIG. **8**, the counter substrate made of glass has its thickness ranging from 20  $\mu\text{m}$  to 150  $\mu\text{m}$ , which allows the organic EL display device to be formed into remarkably thin structure as a whole. This makes it possible to impart flexibility to the organic EL display device.

[0054] FIGS. **9** to **12** are sectional views representing the process of forming the organic EL display device with built-in touch panel according to a first embodiment. FIG. **9** shows the completed TFT substrate **100**. Specifically, the detection electrode X (Tx) is formed on the flattening film made of polyimide or acryl. The Tx is connected to the Tx wiring via the through hole formed in the flattening film **115**, the protective film **114**, the bank **111**, and the organic passivation film **108**.

[0055] FIG. **10** shows the state that the glass substrate to be formed as the counter substrate **200** is bonded to the TFT substrate **100** via the adhesive **201**. Referring to the state as shown in FIG. **10**, the TFT substrate **100** made of resin such as polyimide is formed on a glass substrate **99**. In the state as shown in FIG. **10**, the glass substrate to be formed as the counter substrate **200** is readily available on the market. The glass substrate has its thickness of approximately 0.5 mm, which may be easily handled.

[0056] Then the glass substrate to be formed as the counter substrate **200** is polished through the mechanical-chemical polishing process for thinning to have the thickness ranging from 20  $\mu\text{m}$  to 150  $\mu\text{m}$  as FIG. **11** shows.

[0057] Thereafter, as FIG. **12** shows, the detection electrode Y (Rx) is formed on the thus thinned counter substrate **200**. The Rx is formed of the transparent conductive film such as ITO and ZnO, or the metal film. The Rx is covered with the overcoat film **202** made of such resin as epoxy and acryl, or such inorganic film as SiO and SiN for the protective purpose.

[0058] Then, the glass substrate **99** is separated from the TFT substrate **100** made of resin through the laser abrasion process, resulting in the organic EL display device with built-in touch panel as shown in FIG. **8**. This makes it possible to actualize the organic EL display device with built-in touch panel, which is thin sufficient to impart flexibility to the device.

[0059] FIG. **13** shows an equivalent circuit diagram of the pixel structure. Referring to FIG. **13**, the pixel is formed on the region enclosed with the scanning line **10**, the video signal line **11**, and the power source line **12**. In the pixel, an

organic EL element EL formed of the organic EL layer **112** is connected to a drive TFT (T2) for driving the organic EL element EL in series. A storage capacitance Cs is positioned between the gate and the drain of the drive TFT (T2). The current is applied from the drive TFT (T2) to the EL in accordance with potential of the storage capacitance Cs.

[0060] As FIG. 13 shows, the scanning line **10** is connected to the gate of the selected TFT (T1). The T1 is opened or closed in accordance with the ON or OFF signal of the scanning line **10**. When the T1 is turned ON, the video signal is supplied from the video signal line **11** so that charge is accumulated in the storage capacitance Cs by the video signal. The potential of the storage capacitance Cs serves to drive the drive TFT (T2) so that the current is applied to the organic EL (EL).

[0061] FIG. 14 is a plan view of the pixel part corresponding to the circuit as shown in FIG. 13. Referring to FIG. 14, the scanning lines **10** extend transversely. The video signal lines **11** and the power source lines **12** longitudinally extend, respectively. The pixel is formed on the region enclosed with the scanning line **10**, the video signal line **11**, and the power source line **12**. In other words, the pixel may be the region enclosed with the scanning line **10** and the video signal line **11**. The selected TFT (T1) is formed at a part where the semiconductor layer **102** connected to the video signal line **11** intersects the scanning line **10**.

[0062] The drive TFT (T2) is formed at a part where the semiconductor layer **102** connected to the power source line **12** intersects one of electrodes constituting the storage capacitance Cs. The other electrode of the storage capacitance Cs, that is, the semiconductor layer to which conductivity is imparted is connected to the anode in a through hole **15**. FIG. 14 does not show the cathode which is formed over all the surfaces of the pixels.

[0063] FIG. 15 is a plan view showing the state that the detection electrode X (Tx) transversely extends while covering the respective pixels. Referring to FIG. 15, the Tx drive circuit **30** located at the left side of the drawing supplies detection signals to the detection electrode X (Tx) via the Tx wiring **120**. The Tx extends rightward while covering the pixels in planar view. The scanning line drive circuit **20** located closer to the display region than the Tx drive circuit **30** extend longitudinally.

[0064] As FIG. 15 shows, the Tx is formed corresponding to each of the respective pixel arrays. However, it does not have to be formed for each of the pixel arrays. It is possible to form the Tx for every two pixel arrays or more because the touch panel resolution is not considered as necessary as the video resolution.

[0065] FIG. 16 shows an opening **70** that is formed in the Tx as a Tx-free region. In other words, the Tx is made of the conductive transparent electrode or the metal thin film, which may deteriorate transmittance to a slight degree. In order to prevent such deterioration, the opening **70** is formed in the pixel at the region where light is actually emitted so as to prevent the luminance deterioration owing to the Tx.

#### Second Embodiment

[0066] FIG. 17 is a sectional view of a second embodiment according to the present invention. FIG. 17 shows the feature of the detection electrode Y (Rx) formed at the inner side of the counter substrate **200**. In other words, the counter substrate **200** having the detection electrodes Y (Rx) formed

at the inner side is bonded to the flattening film **115** and the detection electrode X (Tx) of the TFT substrate **100** via the adhesive **201**.

[0067] The structure as shown in FIG. 17 has the Rx formed at the inner side of the counter substrate **200**. Therefore, the distance between the Rx and Tx is reduced, allowing increase in the capacitance. This makes it possible to improve the touch panel sensitivity. Furthermore, as the Rx is formed at the inner side of the counter substrate **200**, the overcoat film for protecting the Rx is no longer necessary.

[0068] Furthermore, the Rx formed at the inner side of the counter substrate **200** does not have to be connected to the flexible wiring substrate for touch panel. In other words, as FIG. 17 shows, the through hole is formed in the flattening film **115**, the protective film **114**, the bank **111**, the organic passivation film **108** and the like at the region around the substrate so as to generate a conductive paste **150** with a conductive particle **140** in the through hole. This makes it possible to supply the signal from the TFT substrate **100** to the Rx via an Rx wiring **130**.

[0069] FIG. 17 shows cross section of the conductive particle **140**, which is formed into a vertically long elliptic shape. It is schematically shown, and actually, the conductive particle **140** is spherical, or formed by laminating a plurality of spherical conductive particles. The resin medium of the conductive paste **150** is formed by using epoxy resin. Any other structures of the TFT substrate **100** as shown in FIG. 17 are similar to those shown in FIG. 8.

[0070] FIGS. 18 and 19 are sectional views showing the process of manufacturing the organic EL display device with built-in touch panel as shown in FIG. 17. FIG. 18 is a sectional view representing the state that the counter substrate **200** having the Rx formed at its inner side is bonded to the TFT substrate **100** with the adhesive **201**. The aforementioned state shows sufficient strength because of the thickness of the counter substrate **200** set to approximately 0.5 mm. This makes it possible to allow execution of the Rx-forming process.

[0071] Unlike the first embodiment, this embodiment has an advantage that allows bonding of the counter substrate having the Rx formed thereon to the TFT substrate. In the state as shown in FIG. 18, the TFT substrate **100** made of resin is disposed on the glass substrate **99**.

[0072] FIG. 19 is a sectional view representing the state that the counter substrate is thinned to have the thickness ranging from 20  $\mu\text{m}$  to 150  $\mu\text{m}$  through the mechanical-chemical polishing process. FIG. 19 shows the state that the TFT substrate **100** is still placed on the glass substrate **99**. Thereafter, the TFT substrate **100** made of resin is separated from the glass substrate **99** through the laser abrasion process, resulting in the organic EL display device with built-in touch panel as shown in FIG. 17.

#### Third Embodiment

[0073] FIG. 20 is a sectional view of a third embodiment of the organic EL display device according to the present invention. The structure as shown in FIG. 20 is different from the one according to the first embodiment as shown in FIG. 8 in that there is no flattening film between the detection electrode X (Tx) and the counter substrate **200**. The absence of the flattening film contributes to direct formation of the detection electrode X (Tx) on the protective

film 114. A large stepped portion on the protective film surface may cause the problem of disconnection of the detection electrode X (Tx).

[0074] Any one of the SiN film, the SiO film, the AlO film, or the laminated film thereof may be used for forming the protective film 114. The concavo-convex surface of the protective film 114 is influenced by the film thickness, or the film forming process such as CVD and sputtering.

[0075] Therefore, the employment of the flattening film 115 may be determined depending on the surface shape of the protective film 114, and the planar shape of the Tx. Specifically, whether or not the flattening film is employed may be determined in consideration of the shape which is unlikely to cause disconnection as shown in FIG. 15, or in consideration of the shape having emphasis placing on brightness as shown in FIG. 16.

[0076] FIG. 20 schematically shows that the side wall of the through hole for connection of the Tx and the Tx wiring 120 is steeply tapered. Actually, the side wall of the through hole may be tapered far gentler than the one as shown in the drawing. As the through hole for connection of the Tx and the Tx wiring 120 may be formed outside the display region, the through hole may be formed in the region with relatively large area.

[0077] FIG. 20 shows the structure applied to the cross sectional shape according to the first embodiment. It is also possible to apply the structure to the cross sectional shape according to the second embodiment.

[0078] Even the above explanation has been described with respect to the TFT which employs Poly-Si, it is possible to employ the oxide semiconductor such as IGZO (Indium Gallium Zinc Oxide) for the TFT. In the above description, the TFT of top gate type has been explained as an example. It is also possible to use the TFT of bottom gate type as well.

What is claimed is:

1. An organic EL display device which includes a TFT substrate on which a scanning line extends in a first direction, a video signal line extends in a second direction, and a pixel having an anode, an organic EL layer and a cathode is formed on a region enclosed with the scanning line and the video signal line, wherein:

- a first electrode of a touch panel extends above the pixel in the first direction via an insulation film;
- a counter substrate is disposed while covering the first electrode of the touch panel; and
- a second electrode of the touch panel extends in the second direction at an outer side of the counter substrate.

2. The organic EL display device according to claim 1, wherein the first electrode of the touch panel extends between the scanning lines in the first direction in planar view.

3. The organic EL display device according to claim 2, wherein the first electrode of the touch panel has an opening formed in a part corresponding to the organic EL layer.

4. The organic EL display device according to claim 1, wherein the first electrode of the touch panel is formed on a

flattening film which covers a protective film made of an inorganic insulation film for covering the cathode.

5. The organic EL display device according to claim 1, wherein the first electrode of the touch panel is formed on a protective film made of an inorganic insulation film for covering the cathode.

6. The organic EL display device according to claim 1, wherein the second electrode of the touch panel is covered with an overcoat film.

7. The organic EL display device according to claim 6, wherein the overcoat film is made of a resin.

8. The organic EL display device according to claim 6, wherein the overcoat film is made of an organic film.

9. An organic EL display device which includes a TFT substrate on which a scanning line extends in a first direction, a video signal line extends in a second direction, and a pixel having an anode, an organic EL layer and a cathode is formed on a region enclosed with the scanning line and the video signal line, wherein:

- a first electrode of a touch panel extends above the pixel in the first direction via an insulation film;
- a counter substrate is disposed while covering the first electrode of the touch panel; and
- a second electrode of the touch panel extends in the second direction at an inner side of the counter substrate.

10. The organic EL display device according to claim 9, wherein the first electrode of the touch panel extends between the scanning lines in the first direction in planar view.

11. The organic EL display device according to claim 9, wherein the first electrode of the touch panel has an opening formed in a part corresponding to the organic EL layer.

12. The organic EL display device according to claim 9, wherein the first electrode of the touch panel is formed on a flattening film which covers a protective film made of an inorganic insulation film for covering the cathode.

13. The organic EL display device according to claim 9, wherein the first electrode of the touch panel is formed on a protective film made of an inorganic insulation film for covering the cathode.

14. The organic EL display device according to claim 9, wherein the second electrode of the touch panel faces the first electrode of the touch panel via an adhesive.

15. The organic EL display device according to claim 9, wherein the second electrode of the touch panel receives a detection signal supplied from the TFT substrate.

16. The organic EL display device according to claim 1, wherein the TFT substrate is made of polyimide.

17. The organic EL display device according to claim 9, wherein the TFT substrate is made of polyimide.

18. The organic EL display device according to claim 1, wherein the counter substrate is made of glass.

19. The organic EL display device according to claim 9, wherein the counter substrate is made of glass.

\* \* \* \* \*

专利名称(译)	显示设备		
公开(公告)号	<a href="#">US20180040671A1</a>	公开(公告)日	2018-02-08
申请号	US15/660276	申请日	2017-07-26
[标]申请(专利权)人(译)	株式会社日本显示器		
申请(专利权)人(译)	日本展示INC.		
当前申请(专利权)人(译)	日本展示INC.		
[标]发明人	MIYAKE HIDEKAZU WATABE KAZUFUMI ISHII YOSHINORI		
发明人	MIYAKE, HIDEKAZU WATABE, KAZUFUMI ISHII, YOSHINORI		
IPC分类号	H01L27/32 G06F3/041		
CPC分类号	H01L27/323 G06F3/044 H01L27/3276 G06F3/0412		
优先权	2016152758 2016-08-03 JP		
其他公开文献	US10541278		
外部链接	<a href="#">Espacenet</a> <a href="#">USPTO</a>		

摘要(译)

有机EL显示装置具有：扫描线在第一方向上延伸的TFT基板，在第二方向上延伸的视频信号线，在区域上形成有具有阳极，有机EL层和阴极的像素与扫描线和视频信号线一起封闭。第一检测电极经由绝缘膜在像素上方沿第一方向延伸。在通过粘合剂覆盖第一检测电极的同时设置对置基板。第二检测电极在对置基板的外侧沿第二方向延伸。

