



US009793508B2

(12) **United States Patent**
Wang

(10) **Patent No.:** **US 9,793,508 B2**
(45) **Date of Patent:** **Oct. 17, 2017**

(54) **OLED DISPLAY PANEL AND OLED DISPLAY DEVICE APPLYING IT**

(58) **Field of Classification Search**
CPC H01L 51/525
See application file for complete search history.

(71) Applicant: **BOE TECHNOLOGY GROUP CO., LTD.**, Beijing (CN)

(56) **References Cited**

(72) Inventor: **Huifeng Wang**, Beijing (CN)

U.S. PATENT DOCUMENTS

(73) Assignee: **BOE Technology Group Co., Ltd.**, Beijing (CN)

2007/0013293 A1 1/2007 Cok
2008/0143255 A1 6/2008 Lee et al.
(Continued)

(*) Notice: Subject to any disclaimer, the term of this patent is extended or adjusted under 35 U.S.C. 154(b) by 0 days.

FOREIGN PATENT DOCUMENTS

CN 103325812 A 9/2013
CN 103545345 A 1/2014
(Continued)

(21) Appl. No.: **14/435,970**

(22) PCT Filed: **Oct. 1, 2014**

OTHER PUBLICATIONS

(86) PCT No.: **PCT/CN2014/088076**

International Search Report of PCT/CN2014/088076 in Chinese with English translation, dated Feb. 9, 2015.

§ 371 (c)(1),

(2) Date: **Apr. 15, 2015**

(Continued)

(87) PCT Pub. No.: **WO2015/169047**

Primary Examiner — Benjamin Sandvik

(74) *Attorney, Agent, or Firm* — Collard & Roe, P.C.

PCT Pub. Date: **Nov. 12, 2015**

(57) **ABSTRACT**

(65) **Prior Publication Data**

US 2016/0181566 A1 Jun. 23, 2016

Disclosed are an OLED display panel and an OLED display device. The OLED display panel includes an array substrate (21) which is covered by a cathode (211) and a color filter substrate (22) on which an auxiliary electrode (221) is formed. A contact structure is disposed between the color filter substrate (22) and the array substrate (21) to electrically connect the cathode (211) and the auxiliary electrode (221), and the contacting area between the contact structure and the array substrate (21) is greater than or equal to that between auxiliary electrode (221) and the contact structure. The OLED display panel avoids broken circuit between the auxiliary electrode and the cathode that tends to occur due to excessive pressure upon cell-assembling a top-emitting OLED display panel.

(30) **Foreign Application Priority Data**

May 9, 2014 (CN) 2014 1 0194343

13 Claims, 3 Drawing Sheets

(51) **Int. Cl.**


H01L 51/52 (2006.01)

H01L 27/32 (2006.01)

(52) **U.S. Cl.**

CPC **H01L 51/525** (2013.01); **H01L 27/3246** (2013.01); **H01L 51/5228** (2013.01);

(Continued)



(52) **U.S. Cl.**
 CPC H01L 27/322 (2013.01); H01L 51/5243
 (2013.01); H01L 51/5246 (2013.01); H01L
 2251/5315 (2013.01)

CN 203812883 U 9/2014
 JP 2009-295447 A 12/2009

OTHER PUBLICATIONS

(56) **References Cited**

U.S. PATENT DOCUMENTS

2010/0097295 A1* 4/2010 Kwak H01L 27/322
 345/32
 2013/0069085 A1* 3/2013 Kang H01L 51/56
 257/88
 2014/0077171 A1 3/2014 Yamakita et al.
 2015/0162387 A1* 6/2015 Gu G06F 3/0412
 345/174
 2016/0035980 A1 2/2016 Kong et al.

FOREIGN PATENT DOCUMENTS

CN 103715231 A 4/2014
 CN 103972270 A 8/2014

Notice of Transmittal of the International Search Report of PCT/
 CN2014/088076 in Chinese, dated Feb. 9, 2015.
 Written Opinion of the International Searching Authority of PCT/
 CN2014/088076 in Chinese with English translation dated Feb. 9,
 2015.
 First Chinese Office Action in Chinese Application No.
 201410194343.6 dated Feb. 28, 2015 with English translation.
 Second Chinese Office Action in Chinese Application No.
 201410194343.6 dated Jun. 3, 2015 with English translation.
 Notification to Grant the Patent Right (Notice of Allowance) in
 Chinese Application No. 201410194343.6 dated Jan. 29, 2016 with
 English translation.
 Issued Patent for Chinese Application No. 201410194343.6 (CN
 103972270 B) dated Mar. 2, 2016 in Chinese with the Chinese
 granted claims with an English translation.

* cited by examiner




Figure 1 Prior Art




Figure 2




Figure 3




Figure 4




Figure 5




Figure 6

OLED DISPLAY PANEL AND OLED DISPLAY DEVICE APPLYING IT

CROSS REFERENCE TO RELATED APPLICATIONS

This application is the National Stage of PCT/CN2014/088076 filed on Oct. 1, 2014, which claims priority under 35 U.S.C. §119 of Chinese Application No. 201410194343.6 filed on May 9, 2014, the disclosure of which is incorporated by reference.

FIELD OF THE INVENTION

Embodiments of the present invention relate to an OLED display panel and an OLED display device applying it.

BACKGROUND

In flat display panels, organic light emitting diode (OLED) display panels have received people's attention widely due to their advantages such as self luminescence, fast response, wide viewing angle, high luminance, fresh colors and being light and thin.

The structure of an OLED usually includes an anode layer, a cathode layer and a luminescent layer disposed between the anode layer and the cathode layer. The luminescence principle of an OLED is as follows. When a voltage is applied between the anode layer and the cathode layer, under the driving of the external voltage, holes injected from the anode layer overcome the interfacial barrier and are transported into the luminescent layer, and electrons injected from the cathode layer overcome the interfacial barrier and are transported into the luminescent layer. Holes and electrons arriving in the luminescent layer recombine to form excitons that experience radiative transitions to bring about luminescence, namely electroluminescence. According to different light emitting surfaces, OLED display panels may be classified into top emitting and bottom emitting types. An OLED display panel includes a pixel array.

In order to increase light transmittance, thin transparent conducting materials are required for the cathode. However, a thin transparent cathode has a high sheet resistance, and a large voltage drop would occur when a current flows through the cathode. Therefore, the farther a pixel is from the power supply point, the smaller cathode voltage it obtains, which leads to a lower display luminance of the pixel than a pixel closer to the power supply point, thereby deteriorating the luminance uniformity of the OLED display device.

SUMMARY

At least one embodiment of the present invention provides an OLED display panel and an OLED display device applying it to avoid broken circuit between the auxiliary electrode and the cathode that tends to occur due to excessive pressure upon cell-assembling a top emitting OLED display panel.

At least one embodiment of the present invention provides an OLED display panel comprising: an array substrate which is covered by a cathode; a color filter substrate on which an auxiliary electrode is formed; and a contact structure provided between the color filter substrate and the array substrate. The contact structure is configured to electrically connect the cathode and the auxiliary electrode, and the contacting area between the contact structure and the

array substrate is greater than or equal to that between the auxiliary electrode and the contact structure.

For example, in one embodiment, the contact structure comprises a spacer and a transparent conductive film on the color filter substrate, the spacer is formed on the auxiliary electrode, the transparent conductive film covers a surface of the color filter substrate and covers at least a surface of the spacer and the auxiliary electrode not blocked by the spacer; a pixel defining layer of the array substrate has a depressed section at a location corresponding to the spacer; the cathode further covers the surface in the depressed section; the spacer on the color filter substrate, whose surface is covered with the transparent conductive film, is inserted into the depressed section of the array substrate whose surface is covered with the cathode.

For example, in one embodiment, a surface shape of the depressed section after being covered by the cathode on the surface matches a surface shape of the spacer contained in the depressed section after being covered by the transparent conductive film on its surface.

For example, conducting glue is placed between the spacer, the surface of which is covered by the transparent conductive film, contained in the depressed section and the cathode in the depressed section.

For example, in one embodiment, the contact structure comprises a spacer formed on a planarization layer of the color filter substrate, and the auxiliary electrode is on top of the spacer; a pixel defining layer of the array substrate has a depressed section at a location corresponding to the spacer; the cathode further covers the surface in the depressed section; the spacer on the color filter substrate with the auxiliary electrode formed on its top is inserted into the depressed section of the array substrate whose surface is covered with the cathode.

For example, a surface shape of the depressed section of the array substrate after being covered by the cathode on the surface matches a surface shape of the spacer contained in the depressed section which is formed on the color filter substrate with the auxiliary electrode on its top.

For example, conducting glue is placed between the spacer, which has the auxiliary electrode on its top, contained in the depressed section and the cathode in the depressed section.

For example, in one embodiment, transparent conducting glue is placed in a gap between the array substrate and the color filter substrate, and the transparent conducting glue is placed at least between the auxiliary electrode and the cathode to form the contact structure.

At least one embodiment of the present invention provides an OLED display device including the above-mentioned OLED display panel.

BRIEF DESCRIPTION OF DRAWINGS

In order to explain the technical solution of embodiments of the present invention more clearly, accompanying drawings of the embodiments will be introduced briefly below. Obviously, the accompanying drawings in the following description only relate to some embodiments of the present invention rather than limiting the present invention.

FIG. 1 is a structure diagram of an OLED display panel;

FIG. 2 is a structure diagram of an OLED display panel provided in an embodiment of the present invention;

FIG. 3 is a structure diagram of the OLED display panel shown in FIG. 2 after cell-assembling;

FIG. 4 is a structure diagram of an OLED display panel provided in another embodiment of the present invention;

FIG. 5 is a structure diagram of the OLED display panel shown in FIG. 4 after cell-assembling;

FIG. 6 is a structure diagram of an OLED display panel provided in yet another embodiment of the present invention.

DETAIL DESCRIPTION

In order to make objects, technical details and advantages of the embodiments of the invention apparent, the technical solutions of the embodiments will be described in a clearly and fully understandable way in connection with the drawings related to the embodiments of the invention. Apparently, the described embodiments are just a part but not all of the embodiments of the invention. Based on the described embodiments herein, those skilled in the art can obtain other embodiments, without any inventive work, which should be within the scope of the invention.

FIG. 1 shows a structure of a pixel in a top emitting OLED display panel, which includes an array substrate and a color filter substrate. The array substrate includes a thin film transistor device layer (not shown in FIG. 1), an anode **103**, a pixel defining layer **104**, a luminescent layer **105** and a cathode **106** formed on a first substrate **101**; and the color filter substrate includes a black matrix **108**, a color filter **109** and a planarization layer **110** formed on a second substrate **107**. The pixel defining layer **104** corresponds to the black matrix **108** in their locations. In operation of the OLED display panel, light is emitted from the luminescent layer **105** by applying a voltage between the anode **103** and the cathode **106**, and light (as shown in FIG. 1 by the hollow arrowhead) transmits through the transparent cathode **106** and the color filter substrate on the top, realizing top emission.

The OLED display panel includes a pixel array consisting of a plurality of pixels shown in FIG. 1. Anodes **103** of the pixels are separated by the pixel defining layer **104** for mutual electrical insulation, and the anode of each pixel obtains electrical signals from the thin film transistor connected therewith. The luminescent layer **105** and the cathode **106** cover the entire pixel array, and the cathodes are supplied with power by a power supply on a side of the pixel array.

In order to solve deterioration of the luminance uniformity, it is possible to provide an auxiliary electrode **111** with small resistance on the planarization layer of the color filter substrate to reduce the resistance of the cathode **106**, as shown in FIG. 1. A spacer **112** is formed on the auxiliary electrode **111** to prevent the substrate surface from damage caused by hard contact between the substrates while cell-assembling the color filter substrate and the array substrate. A transparent conductive layer **113** is further placed on the surface of the color filter substrate to realize electrical connection between the auxiliary electrode **111** and the cathode **106** after cell-assembling the color filter substrate and the array substrate.

The inventors found out that when the OLED display panel shown in FIG. 1 is manufactured, the spacer **112** formed on the auxiliary electrode **111** has an elongated conical structure with a small area at the top, and while cell-assembling the color filter substrate and the array substrate, the transparency conductive layer covering the top of the spacer contacts the array substrate. Due to a small area of the top of the spacer, the contacting area is significantly smaller than the surface area of the auxiliary electrode that faces the array substrate, and a large force is exerted on the spacer **112**, which makes the top of the spacer **112** experi-

ence a large pressure, and the transparent conductive layer **113** on the top of the spacer **112** is subjected to a large pressure and tends to break, thereby causing broken circuit between the cathode and the auxiliary electrode.

At least one embodiment of the present invention provides an OLED display panel. As shown in FIG. 2, the OLED display panel includes an array substrate **21** which is covered by a cathode **211** and a color filter substrate **22** on which an auxiliary electrode **221** is formed. The OLED display panel further includes a contact structure disposed between the color filter substrate **22** and the array substrate **21** to electrically connect the cathode **211** and the auxiliary electrode **221**, and the contacting area between the contact structure and the array substrate **21** is greater than that between auxiliary electrodes **221** and the contact structure.

In the OLED display panel provided in at least one embodiment of the present invention, the contact structure can electrically connect the auxiliary electrode and the cathode, and the contacting area between the contact structure and the array substrate is larger than that between the auxiliary electrode and the contact structure, thereby increasing the contacting area between the contact structure and the cathode covering the array substrate. Even if the contact structure is subjected to a large force, the contacting region thereof experiences a small pressure, which may significantly reduce the risk of broken circuit between the auxiliary electrode and the cathode due to large pressure upon cell-assembling.

In the OLED display panel provided in the above-mentioned embodiment, as shown in FIG. 2, the contact structure may include a spacer **23** and a transparent conductive film **24** formed on the color filter substrate **22**, in which the spacer **23** is formed on the auxiliary electrode **221**, and the transparent conductive film **24** covers a surface of the color filter substrate **22** and covers at least a surface of the spacer **23** and the auxiliary electrode **221** not blocked by the spacer **23**. The pixel defining layer **212** of the array substrate **21** has a depressed section D at a location corresponding to the spacer **23**; and the cathode **211** further covers the surface inside the depressed section D. After disposing the array substrate and the color filter substrate oppositely, the spacer **23** covered by the transparent conductive film **24** on the surface is inserted into the depressed section D covered with the cathode **211** on its surface.

It is to be noted that, in order to make the contact structure more clear, FIG. 2 shows the structures of the array substrate **21**, the color filter substrate **22** and the contact structure before cell-assembling. Therefore, in FIG. 2, the spacer **23** covered by the transparent conductive film **24** on the surface has not been inserted into the depressed section D covered by the cathode **211** on its surface yet. Whereas the structure of the OLED display panel described in the present embodiment is the structure after cell-assembling, as shown in FIG. 3.

The contacting region between the transparent conductive film **24** inside the depressed section D and the cathode **211** is the contacting region between the above-mentioned contact structure and the array substrate. Since the contacting region includes not only the surface of the transparent conductive layer **24** covering the top of the spacer **23**, but also includes the surface of the transparent conductive layer **24** covering partial side walls of the spacer **23**, the area of the contacting region increases significantly to be greater than the area of the contacting region between the auxiliary electrode **221** and the spacer **23** (namely contacting region between the auxiliary electrode and the contact structure). While the spacer **23** is exerted with a force, the pressure

exerted on the transparent conductive layer 24 would decrease significantly, thereby reducing the risk of broken circuit between the auxiliary electrode 221 and the cathode 211 caused by break of the transparent conductive layer 24.

In the OLED display panel shown in FIG. 3, a surface shape of the depressed section D after being covered by the cathode 211 on the surface matches for example a surface shape of the spacer 23 contained therein after being covered by the transparent conductive film 24. This allows the transparent conductive film 24 and the cathode to contact closely without any gap, thereby avoiding increased contacting resistance.

In addition, in the OLED display panel shown in FIG. 2, conducting glue 25 may be placed between the spacer 23 contained in depressed section D after being covered by the transparent conductive film 24 on the surface and the cathode 211 in the depressed section D. Therefore, when any gap exists between the transparent conductive film 24 and the cathode 211 such that they can not contact closely, conducting glue 25 is placed in the gap to prevent contacting resistance from increasing.

In another embodiment of the present invention, as shown in FIG. 4, the contact structure may include a spacer 23 formed on the planarization layer 222 of the color filter substrate 22 with an auxiliary electrode 221 on top of the spacer 23; and the pixel defining layer 212 of the array substrate 21 has a depressed section D at a location corresponding to the spacer 23, and the cathode 211 further covers the surface inside the depressed section D. After disposing the array substrate and the color filter substrate oppositely, the spacer 23 with the auxiliary electrode 221 formed on its top is inserted into the depressed section D covered with the cathode 211 on the surface.

It is to be noted that, in order to make the contact structure more clear, FIG. 4 shows a specific structure of the array substrate 21, the color filter substrate 22 and the contact structure before cell-assembling. Therefore, in FIG. 4, the spacer 23 formed with the auxiliary electrode 221 on its top has not been inserted into the depressed section D covered by the cathode 211 on the surface yet. The structure of the OLED display panel described in the present embodiment is the structure after cell-assembling, as shown in FIG. 5.

The contacting region between the spacer 23 inside the depressed section D and the cathode 211 is the contacting region between the above-mentioned contact structure and the array substrate. Since the contacting region includes partial side wall surfaces of the spacer 23, the area of contacting region is increased significantly to be greater than the area of contacting region between the auxiliary electrode 221 and the spacer 23 (namely contacting region between the auxiliary electrode and the contact structure).

In the implementations shown in FIGS. 4 and 5, since the auxiliary electrode 221 on top of the spacer 23 can electrically contact the cathode inside the depressed section D directly, it is unnecessary to provide the transparent conductive layer between the spacer 23 inside the depressed section D and the cathode 211, which eliminates the problem of breaking of transparent conductive layer while the spacer 23 is exerted with a force, thereby avoiding broken circuit problem between the auxiliary electrode 221 and the cathode 211 caused by excessive pressure upon cell-assembling.

In the OLED display panel shown in FIG. 5, a surface shape of the depressed section D after being covered by the cathode 211 on the surface matches, for example, a surface shape of the spacer 23 contained therein which is formed with auxiliary electrodes 221 on its top. This allows the auxiliary electrode 221 and the spacer 23 contact the cathode

211 closely without any gap, thereby preventing the contacting resistance between the auxiliary electrode 221 and the cathode 211 from increasing.

In addition, in the OLED display panel shown in FIG. 4, conducting glue 25 may be placed between the spacer 23 with the auxiliary electrode 221 on its top which is contained in the depressed section D and the cathode 211 inside depressed sections D. Therefore, when any gap exists between the auxiliary electrode 221 and the cathode 211 such that they can not contact closely, conducting glue 25 is placed in the gap to prevent contacting resistance from increasing.

In yet another embodiment of the present invention, as shown in FIG. 6, transparent conducting glue 25 is placed in the gap between the array substrate 21 and the color filter substrate 22, which is placed at least between the auxiliary electrode 221 and the cathode 211 to form a contact structure.

When the transparent conducting glue 25 is only placed between the auxiliary electrode 221 and the cathode 211, the area of contacting region between the contact structure formed of the transparent conducting glue 25 and the auxiliary electrode 221. When the transparent conducting glue 25 is placed in the entire gap between the array substrate 21 and the color filter substrate 22, the area of contacting region between the contact structure formed of the transparent conducting glue 25 and the array substrate 21 is greater than the area of contacting region between the contact structure formed of the transparent conducting glue 25 and the auxiliary electrode 221.

In the implementation shown in FIG. 6, since the auxiliary electrode 221 on the color filter substrate 22 may electrically contact the cathode 211 via the transparent conducting glue 25, it is not necessary to provide the transparent conductive layer between the auxiliary electrode 221 and the cathode 211. And since the transparent conducting glue 25 has strong deformability, even if the transparent conducting glue 25 experiences a large pressure while cell-assembling, it would not be broken, thereby avoiding broken circuit problem between the auxiliary electrode 221 and the cathode 211 caused by excessive pressure upon cell-assembling.

At least one embodiment of the present invention further provides an OLED display device including the OLED display panel described in any one embodiment of the present invention. Since the probability of broken circuit between the auxiliary electrode and the cathode in the OLED display panel decreases significantly, the OLED display device may have significantly enhanced display performance.

What are described above is related to the illustrative embodiments of the disclosure only and not limitative to the scope of the disclosure; the scopes of the disclosure are defined by the accompanying claims.

The present application claims priority of a Chinese patent application No. 201410194343.6 filed on May 9, 2014, which is incorporated in its entirety herein by reference as part of the present application.

What is claimed is:

1. An OLED display panel, comprising: an array substrate which is covered by a cathode, a color filter substrate on which an auxiliary electrode is formed, a contact structure provided between the color filter substrate and the array substrate,

7

wherein the contact structure is configured to electrically connect the cathode and the auxiliary electrode, and the contacting area between the contact structure and the array substrate is greater than or equal to that between the auxiliary electrode and the contact structure, and the contact structure is in contact with the auxiliary electrode and does not include the cathode, wherein the contact structure comprises a spacer and a transparent conductive film on the color filter substrate; the spacer is formed on the auxiliary electrode; and the transparent conductive film covers a surface of the color filter substrate and covers at least a surface of the spacer and the auxiliary electrode not blocked by the spacer;

a pixel defining layer of the array substrate has a depressed section at a location corresponding to the spacer;

the cathode further covers the surface inside the depressed section; and

the spacer on the color filter substrate, whose surface is covered with the transparent conductive film, is inserted into the depressed section of the array substrate whose surface is covered with the cathode.

2. The OLED display panel of claim 1, wherein a surface shape of the depressed section of the array substrate after being covered by the cathode on the surface matches a surface shape of the spacer on the color filter substrate contained in the depressed section after being covered by the transparent conductive film on its surface.

3. The OLED display panel of claim 1, wherein conducting glue is placed between the spacer, whose surface is covered by the transparent conductive film, contained in the depressed section and the cathode in the depressed section.

4. The OLED display panel of claim 2, wherein conducting glue is placed between the spacer, whose surface is covered by the transparent conductive film, contained in the depressed section and the cathode in the depressed section.

5. An OLED display device comprising an OLED display panel of claim 1.

6. An OLED display device comprising an OLED display panel of claim 2.

7. An OLED display device comprising an OLED display panel of claim 3.

8

8. An OLED display panel, comprising:
 an array substrate which is covered by a cathode,
 a color filter substrate on which an auxiliary electrode is formed,
 a contact structure provided between the color filter substrate and the array substrate,
 wherein the contact structure is configured to electrically connect the cathode and the auxiliary electrode, and the contacting area between the contact structure and the array substrate is greater than or equal to that between the auxiliary electrode and the contact structure, and the contact structure is in contact with the auxiliary electrode and does not include the cathode,
 wherein the contact structure comprises a spacer formed on a planarization layer of the color filter substrate, and the auxiliary electrode is on top of the spacer;
 a pixel defining layer of the array substrate has a depressed section at a location corresponding to the spacer;
 the cathode further covers the surface inside the depressed section;

the spacer on the color filter substrate with the auxiliary electrode formed on its top is inserted into the depressed section of the array substrate whose surface is covered with the cathode.

9. The OLED display panel of claim 8, wherein a surface shape of the depressed section of the array substrate after being covered by the cathode on the surface matches a surface shape of the spacer contained in the depressed section which is formed on the color filter substrate with the auxiliary electrode on its top.

10. The OLED display panel of claim 8, wherein conducting glue is placed between the spacer, which has the auxiliary electrode on its top, contained in the depressed section and the cathode in the depressed section.

11. The OLED display panel of claim 9, wherein conducting glue is placed between the spacer, which has the auxiliary electrode on its top, contained in the depressed section and the cathode in the depressed section.

12. An OLED display device comprising an OLED display panel of claim 8.

13. An OLED display device comprising an OLED display panel of claim 9.

* * * * *

专利名称(译)	OLED显示面板和应用它的OLED显示设备		
公开(公告)号	US9793508	公开(公告)日	2017-10-17
申请号	US14/435970	申请日	2014-10-01
[标]申请(专利权)人(译)	京东方科技集团股份有限公司		
申请(专利权)人(译)	京东方科技集团股份有限公司.		
当前申请(专利权)人(译)	京东方科技集团股份有限公司.		
[标]发明人	WANG HUIFENG		
发明人	WANG, HUIFENG		
IPC分类号	H01L51/52 H01L27/32		
CPC分类号	H01L51/525 H01L27/3246 H01L51/5228 H01L27/322 H01L51/5243 H01L51/5246 H01L2251/5315		
优先权	201410194343.6 2014-05-09 CN		
其他公开文献	US20160181566A1		
外部链接	Espacenet	USPTO	

摘要(译)

公开了一种OLED显示面板和OLED显示装置。OLED显示面板包括阵列基板(21)，其被阴极(211)和滤色器基板(22)覆盖。其中形成辅助电极(221)。接触结构设置在滤色器基板(22)和阵列基板(21)之间，以电连接阴极(211)和辅助电极(221)，接触结构与阵列基板之间的接触面积(21)大于或等于辅助电极之间的接触面积(221)和接触结构。OLED显示面板避免了在电池组装顶部发光OLED显示面板时由于过大的压力而易于发生的辅助电极和阴极之间的断开电路。

