




US 20190173041A1

(19) **United States**(12) **Patent Application Publication**
Large et al.(10) **Pub. No.: US 2019/0173041 A1**(43) **Pub. Date: Jun. 6, 2019**(54) **MOVEABLE DISPLAY SUPPORTS,
COMPUTING DEVICES USING SAME, AND
METHODS OF USE**(71) Applicant: **Microsoft Technology Licensing, LLC,**
Redmond, WA (US)(72) Inventors: **Timothy Andrew Large**, Bellevue, WA
(US); **Lincoln Matthew Ghioni**,
Redmond, WA (US); **Sarat Babu**,
London (GB); **Matthew James**
Longbottom, London (GB); **Duncan**
Alexander Wallis Carter, London
(GB)(21) Appl. No.: **15/832,639**(22) Filed: **Dec. 5, 2017****Publication Classification**(51) **Int. Cl.**
H01L 51/52 (2006.01)
H01L 51/00 (2006.01)
H01L 51/56 (2006.01)
(52) **U.S. Cl.**
CPC **H01L 51/524** (2013.01); **H01L 2251/5338**
(2013.01); **H01L 51/56** (2013.01); **H01L**
51/0097 (2013.01)(57) **ABSTRACT**

A computing device is disclosed that includes an organic light-emitting diode (OLED) display. The OLED display has a front surface and a back surface. The computing device includes a moveable display support connected to the back surface of the display. In some implementations, the moveable display support is configured to limit bending in one direction to a first bend radius and to limit bending in another direction to a second bend radius. In some implementations, the moveable display support is formed by a plurality of unit cells.






FIG. 1




FIG. 2




FIG. 3




FIG. 6




FIG. 4




FIG. 5




FIG. 7




FIG. 8






FIG. 13




FIG. 14




FIG. 15

FIG. 16





FIG. 17






FIG. 18




FIG. 19




FIG. 20




FIG. 21




FIG. 22




FIG. 23




FIG. 24




FIG. 25




FIG. 26




FIG. 27




FIG. 28




FIG. 29

FIG. 30




FIG. 31




FIG. 32





FIG. 33



MOVEABLE DISPLAY SUPPORTS, COMPUTING DEVICES USING SAME, AND METHODS OF USE

BACKGROUND

Background and Relevant Art

[0001] Use of computing devices is becoming more ubiquitous by the day. Computing devices range from standard desktop computers to wearable computing technology and beyond. One area of computing devices that has grown in recent years is flexible displays. Flexible displays may be moved to a bent configuration. Flexible screens may be fragile.

[0002] The subject matter claimed herein is not limited to implementations that solve any disadvantages or that operate only in environments such as those described above. Rather, this background is only provided to illustrate one exemplary technology area where some implementations described herein may be practiced.

BRIEF SUMMARY

[0003] In one implementation, a computing device is described. The computing device includes a flexible display including a thin film transistor matrix having a front surface and a back surface. A moveable display support is included and is connected to the back surface of the display and is configured to limit bending in one direction to a first bend radius while maintaining strain on the thin film transistor matrix below a predetermined amount of strain by elongating the moveable display support during bending.

[0004] In another implementation, a computing device is described. The computing device includes a flexible display having a front surface and a back surface. The computing device includes a moveable display support connected to the back surface of the display. The moveable display support is formed by a plurality of unit cells.

[0005] This Summary is provided to introduce a selection of concepts in a simplified form that are further described below in the Detailed Description. This Summary is not intended to identify key features or essential features of the claimed subject matter, nor is it intended to be used as an aid in determining the scope of the claimed subject matter.

[0006] Additional features and advantages will be set forth in the description which follows, and in part will be obvious from the description, or may be learned by the practice of the teachings herein. Features and advantages of the disclosure may be realized and obtained by means of the instruments and combinations particularly pointed out in the appended claims. Features of the present disclosure will become more fully apparent from the following description and appended claims, or may be learned by the practice of the disclosure as set forth hereinafter.

BRIEF DESCRIPTION OF THE DRAWINGS

[0007] To describe the way the above-recited and other features of the disclosure can be obtained, a more particular description will be rendered by reference to specific implementations thereof which are illustrated in the appended drawings. For better understanding, the like elements have been designated by like reference numbers throughout the various accompanying figures. While some of the drawings may be schematic or exaggerated representations of con-

cepts, at least some of the drawings may be drawn to scale. Understanding that the drawings depict some example implementations, the implementations will be described and explained with additional specificity and detail through the use of the accompanying drawings in which:

[0008] FIG. 1 is a perspective top view of an implementation of a computing device in a planar configuration;

[0009] FIG. 2 is perspective top view of the computing device of FIG. 1 in a bent configuration;

[0010] FIG. 3 is a cutaway side view of the computing device of FIG. 1;

[0011] FIG. 4 is an isometric view of another implementation of a computing device in a bent configuration;

[0012] FIG. 5 is a side view of the computing device of FIG. 4 in a bent configuration;

[0013] FIG. 6 is a side view of the computing device of FIG. 4 in a planar configuration;

[0014] FIG. 7 is a partial side view of an implementation of a moveable display support in a planar configuration;

[0015] FIG. 8 is a side view of an implementation of an interlocking element of FIG. 7;

[0016] FIG. 9 is a partial side view of the moveable display support of FIG. 7 in a bent configuration;

[0017] FIG. 10 is a perspective side view of the moveable display support of FIG. 7 in the planar configuration;

[0018] FIG. 11 is a perspective side view of the moveable display support of FIG. 7 in the bent configuration;

[0019] FIG. 12 is a cutaway side view of an implementation of a plurality of support elements in a planar configuration;

[0020] FIG. 13 is a cutaway side view of the plurality of support elements in a bent configuration;

[0021] FIG. 14 is a side view of an implementation of a moveable display support incorporating the plurality of support elements of FIG. 12 in a planar configuration;

[0022] FIG. 15 is a perspective side view of the moveable display support of FIG. 14 in the planar configuration;

[0023] FIG. 16 is a side view of the moveable display support of FIG. 14 in a bent configuration;

[0024] FIG. 17 is a perspective side view of the moveable display support of FIG. 14 in the bent configuration;

[0025] FIG. 18 is a front view of an implementation of a plurality of unit cells in a planar configuration;

[0026] FIG. 19 is a perspective top view of a plurality of rows incorporating the plurality of unit cells of FIG. 18 in the planar configuration;

[0027] FIG. 20 is a top view of a plurality of separated rows of unit cells in the planar configuration;

[0028] FIG. 21 is a top view of a plurality of interconnected rows of unit cells in the planar configuration;

[0029] FIG. 22 is a perspective top view of an implementation of a moveable display support incorporating the plurality of interconnected rows of unit cells of FIG. 21 in the planar configuration;

[0030] FIG. 23 is a perspective bottom view of the moveable display support of FIG. 21 in the planar configuration;

[0031] FIG. 24 is a perspective top view of the moveable display support of FIG. 21 in a bent configuration;

[0032] FIG. 25 is a perspective bottom view of the moveable display support of FIG. 21 in the bent configuration;

[0033] FIG. 26 is a front view of an implementation of a plurality of unit cells in a planar configuration;

[0034] FIG. 27 is a perspective top view of a plurality of rows incorporating the plurality of unit cells of FIG. 26 in the planar configuration;

[0035] FIG. 28 is a top view of a plurality of separated rows of unit cells in the planar configuration;

[0036] FIG. 29 is a top view of a plurality of interconnected rows of unit cells in the planar configuration;

[0037] FIG. 30 is a perspective top view of an implementation of a moveable display support incorporating the plurality of interconnected rows of unit cells of FIG. 29 in the planar configuration;

[0038] FIG. 31 is a perspective bottom view of the moveable display support of FIG. 29 in the planar configuration;

[0039] FIG. 32 is a perspective top view of the moveable display support of FIG. 29 in a bent configuration; and

[0040] FIG. 33 is a perspective bottom view of the moveable display support of FIG. 28 in the bent configuration.

DETAILED DESCRIPTION

[0041] This disclosure generally relates to moveable display supports, computing devices using the same, and methods of use. More particularly, this disclosure generally relates to moveable display supports that are connected to a back surface of flexible light emitting displays such as organic light-emitting diode (OLED) displays or micro-LED displays.

[0042] As displays continue to get thinner, the risk of damaging the display increases. For example, the outer surface of a display may be soft, which may increase the risk of scratches. In another example, a display may not completely support the display and softer materials, such as foams, may be used to provide some support. However, these softer materials, may still allow for damage from bending beyond a minimum bend radius and/or normal loads. This often results in layers that are compressible which may make the display susceptible to point loads (e.g., finger-nails, digitizer pen tips, particles of dust) that may locally exceed a minimum bend radius of the display, which may result in the destruction of small areas of pixels. A minimum bend radius may include the minimum radius to which a display may be bent without destroying pixels.

[0043] Folding displays may also include the risk of damaging the display. Typically, foldable displays have a complex structure of (mostly plastic) layers. An electrode structure may be included in and/or near the middle and may include a water barrier layer on either side. The electrode structure and/or water barrier layers are typically inorganic and may crack when an applied stress (e.g., pressure or tension exerted on a material object) places the electrode structure and/or water barrier layers under strain (e.g., distortion of a material object caused by application of stress). The layers of a foldable display may form a stack. In at least some implementations, it may be desirable that the electrode structure should have as close to zero strain as possible. For example, when a display is folded beyond a minimum bend radius, plasticity (e.g., tendency to retain permanent deformation after application of stress) in the layers tends to retain the fold, which may result in buckling and/or creasing of the display surface. In some instances, this buckling and/or creasing may cause the display to extend above a chassis of the display. It may therefore be desirable to affix the display to a structure, to limit long term plastic deformation.

[0044] Fixing a display to a hard backing surface (e.g., a planar hard piece of plastic) may reduce risk of damage to the display until stress applied to the display exceeds the strain tolerance of the hard surface. However, for a foldable display, the hard backing surface may limit the ability of the display to fold. For example, a hard and thick sheet of plastic attached to a back surface of a foldable display may have a very large bend radius, which may significantly limit the bendability of the foldable display. Furthermore, such a large and thick sheet will have a neutral plane (zero strain layer) inside the sheet, so that when the assembly is folded, the display affixed to the external surface will suffer severe strain.

[0045] In at least one implementation, a moveable display support affixed to a display may be capable of supporting high normal loads while allowing the display to globally fold along a pre-determined path with low internal strain in the display. In at least one implementation, a moveable display support may facilitate curvature over a pre-defined radius without exceeding the pre-defined radius and/or providing support against point loads.

[0046] In at least one implementation, the moveable display support may provide added stiffness to resist normal forces. In at least one implementation, the moveable display support expands along its length when rolled to maintain the zero-strain condition of the display. In at least one implementation, a computing device may be capable of resisting point loads of less than 500 grams over a 0.39 mm² area. In at least one implementation, the moveable display support includes elements that are linked like chain mail with particular bends to limit motion in two directions.

[0047] A display may have a theoretical zero-strain plane that extends through the transistor layer of the display. The zero-strain plane has a theoretical thickness of zero. In the real world, maintaining the display with near zero-strain may include preventing the application of more than a predetermined amount of strain. In at least one implementation, a moveable display support may prevent the display from experiencing more than a predetermined amount of strain. In some implementations, the predetermined amount of strain may be in a range having an upper value, a lower value, or upper and lower values including any of less than 2.0%, less than 1.5%, less than 1.0%, less than 0.75%, less than 0.50%, less than 0.25%, less than 0.10%, less than 0.05%, or any value therebetween. For example, the predetermined amount of strain may be less than 2.0%. In other examples, the predetermined amount of strain may be less than 1.0%. In further examples, the predetermined amount of strain may be less than 0.50%. In yet other examples, the predetermined amount of strain may be in a range of 0.05% to 2.0%. In yet further examples, the predetermined amount of strain may be in a range of 0.05% to 1.5%.

[0048] FIG. 1 is a perspective top view of an implementation of a computing device 100 in a planar configuration. FIG. 2 is perspective top view of the computing device 100 of FIG. 1 in a bent configuration. Referring generally now to FIGS. 1 and 2 (and specifically as indicated). The computing device 100 may be a laptop, a smartphone, a monitor (e.g., a television, desktop computer monitor, an interactive white board, or other display), a watch display, an electronic reading device, or other computing devices with a display.

[0049] The computing device 100 may include a flexible display 110 and a moveable display support 120. The display 110 may be an OLED display that may include a thin film

transistor matrix. In other examples, the flexible display **110** may include a micro LED display, a LCD display, an electrophoretic display, other flexible displays, or combinations thereof. The display **110** may have a minimum bend radius without additional support.

[0050] The display **110** is flexible and may be biased toward the planar configuration shown in FIG. 1. The display **110** may be bent from the planar configuration of FIG. 1 to a bent configuration, such as the bent configuration shown in FIG. 2. As described above, bending a display **110** beyond a predetermined minimum bend radius may damage the display **110**. The moveable display support **120** may limit the amount that the display **110** may bend. For example, as shown in FIG. 2, the moveable display support **120** limits the moveable display support **120** to a radius of, for example, 3 millimeters (mm).

[0051] The display **110** may include a front surface **112** and a back surface (not shown). The moveable display support **120** may be connected to the back surface of the display **110**. For example, the moveable display support **120** may be attached (e.g., adhered, affixed, mechanically connected) to the back surface of the display **110**. In some implementations, the moveable display support **120** may be attached to the entire back surface of the display **110**. In other implementations, the moveable display support **120** may include attachment points that are spaced about the back surface of the display **110**. For example, the attachment points may be spaced such that the display **110** is capable of withstanding applied normal forces above a predetermined amount. Supporting the display **110** may provide the support necessary to prevent point load damage to the display **110**.

[0052] In some implementations, the moveable display support **120** may limit motion (e.g., bending) in one direction to a first bend radius and/or may limit bending in another direction to a second bend radius. For example, in the implementation of FIGS. 1 and 2, the moveable display support **120** may limit bending about the back surface of the display **110** to a first bend radius of infinity and may limit bending about the front surface **112** of the display **110** to a second bend radius of 3 mm. In other words, the moveable display support **120** may limit bending about the back surface **114** of the display **110** such that the back surface **114** remains planar (e.g., does not bend to a concave shape) in a first configuration and may bend to the second bend radius of 3 mm (e.g., bent to a concave shape having a bend radius of 3 mm).

[0053] In other implementations, the first bend radius may be in a range having an upper value, a lower value, or upper and lower values including any of infinity, 10 mm, 5 mm, 4.5 mm, 4 mm, 3.5 mm, 3 mm, 2.5 mm, 2 mm, 1.5 mm, 1 mm, 0.5 mm, or any value therebetween. For example, the first bend radius may be infinity (e.g., may remain flat). In other examples, the first bend radius may be less than 10 mm. In further examples, the first bend radius may be greater than 0.5 mm.

[0054] In yet other examples, the first bend radius may be in a range of 0.5 mm to 10 mm. In yet further examples, the first bend radius may be in a range of 0.5 mm to 10 mm and/or infinity.

[0055] In other implementations, the second bend radius may be in a range having an upper value, a lower value, or upper and lower values including any of infinity, 2,000 mm, 1,500 mm, 1,000 mm, 500 mm, 250 mm, 100 mm, 50 mm, 25 mm, 10 mm, 5 mm, 4.5 mm, 4 mm, 3.5 mm, 3 mm, 2.5

mm, 2 mm, 1.5 mm, 1 mm, 0.5 mm, or any value therebetween. For example, the second bend radius may be infinity (e.g., may remain flat). In other examples, the second bend radius may be less than 5 mm. In further examples, the second bend radius may be greater than 0.5 mm. In yet other examples, the second bend radius may be in a range of 0.5 mm to 4 mm. In yet further examples, the second bend radius may be in a range of 1,000 mm to infinity.

[0056] Therefore, the first bend radius and the second bend radius may be selected to determine a first configuration and a second configuration. For example, the first configuration may be planar (e.g., with an infinite first bend radius) and the second configuration may be curved with, in some implementations, a second bend radius of less than 4 mm. In another example, the first configuration may be curved such that the front surface **112** is concave and may have a first bend radius of less than 4 mm and the second configuration may be curved such that the back surface is concave and may have a second bend radius of less than 4 mm.

[0057] The first and/or second bend radius may be selected to prevent bending of the display **110** beyond a first and/or second maximum bend radius. For example, the maximum bend radius of a display **110** may be 3 mm and the first and/or second bend radius of the moveable display support **120** may be greater than the maximum bend radius of the display (e.g., greater than 3 mm). Example moveable display supports are provided below.

[0058] Although bend radii are described above as applying to the bending of the entire display **110**, bend radii are also applicable for point or other normal loads applied to a surface of the display **110**. For example, if a stylus (not shown) were pressed against the display, the moveable display support **120** may provide support to the display **110** to prevent the transistor layer exceeding a minimum bend radius (e.g., preventing the stylus from puncturing the display **110**). This support may be provided in a planar state, a bent state, an intermediate state, or combinations thereof.

[0059] The display **110** may have a dimension **111**. As shown, the dimension **111** is a width. In other implementations, the dimension **111** may be a length, a diagonal, a perimeter, a radius, a diameter, or other major dimension. The dimension **111** may extend from a first edge **116** to a second edge **118** of the display **110**. The moveable display support **120** may extend between the first edge **116** and the second edge **118** of the display **110**.

[0060] The moveable display support **120** may have a dimension (not labeled) that corresponds with the dimension **111** of the display **110**. As shown, the dimension of the moveable display support **120** is the width of the moveable display support **120**. In another example, if the dimension **111** of the display **110** is the length, then the dimension of the moveable display support **120** is also the length, etc. The dimension of the moveable display support **120** (e.g., width), in the present implementation, is the same as the dimension **111** of the display **110**. In other words, the width of the display **110** and the width of the moveable display support **120** are the same. In other implementations, the dimension of the moveable display support **120** may be smaller than the dimension **111** of the display **110**.

[0061] For example, the dimension of the moveable display support **120** may be a portion of the dimension **111**. In other implementations, the dimension of the moveable display support **120** may be a percentage of the dimension **111**

in a range having an upper value, a lower value, or upper and lower values including any of within 75%, 80%, 85%, 90%, 95%, 97.5%, 98%, 98.5%, 99%, 99.5%, 99.75%, 99.9%, 99.95% of the dimension 111 of the display 110, or any value therebetween. For example, the distance may be less than 99.95% of the dimension. In other examples, the distance may be greater than 0.05% of the dimension 111. In yet other examples, the distance may be in a range of 25% to 0.05% of the dimension 111.

[0062] In implementations where the dimension of the moveable display support 120 is smaller than the dimension 111 of the display 110, the moveable display support 120 may extend within 5% of the dimension 111 to the first edge 116 and/or the second edge 118 of the display 110. In other words, the distance between an edge (not shown) of the moveable display support 120 and the first edge 116 and/or second edge 118 of the display may be less than 5% of the dimension 111 of the display. In other implementations, the distance may be in a range having an upper value, a lower value, or upper and lower values including any of within 25%, 20%, 15%, 10%, 7.5%, 5%, 3%, 2%, 1%, 0.5%, 0.25%, 0.1%, 0.05% of the dimension 111 of the display 110, or any value therebetween. For example, the distance may be less than 25% of the dimension. In other examples, the distance may be greater than 0.05% of the dimension 111. In yet other examples, the distance may be in a range of 25% to 0.05% of the dimension 111.

[0063] As shown, the front surface 112 of the display 110 may be entirely unobstructed. In other words, the front surface 112 is the outermost surface on the front side of the display 110. In other implementations, a portion of the front surface 112 may be obstructed. For instance, a cover (not shown) may extend partially around the front surface 112. In some implementations, a majority of the front surface 112 may be unobstructed.

[0064] FIG. 3 is a cutaway side view of the computing device of FIG. 1 illustrating a display stack 140. The stack 140 may include the front surface 112 and the back surface 114 of the display 110. The stack 140 may include a display layer 130. The display layer 130 may be surrounded by one or more front layers (including the front surface 112) and is shown with the front layer (the frontmost layer including the front surface 112) and a second front layer 112-1 and/or one or more back layers (including the back surface 114) and is shown with the back layer (the backmost layer including the back surface 114) and a second back layer 114-1.

[0065] In some implementations, the display layer 130 may be an OLED layer and may include a thin film transistor matrix. The second front layer 112-1 and/or the second back layer 114-1 may be barrier layer(s).

[0066] FIG. 4 is an isometric view of another implementation of a computing device 200 in a bent configuration; FIG. 5 is a side view of the computing device 200 of FIG. 4 in the bent configuration; and FIG. 6 is a side view of the computing device 200 of FIG. 4 in a planar configuration. Referring generally to FIGS. 4-6, unless otherwise specified, the computing device 200 includes a display 210 and a moveable display support 220. The display 210 includes a front surface 212 and a back surface 214. The moveable display support 220 may be connected to the back surface 214 of the display 210. The moveable display support 220 is shown extending a full length (e.g., from the first edge 216 to the second edge 218) of the display 210.

[0067] As shown in FIG. 6, the front surface 212 of the display 210 is unobstructed and as shown in FIG. 4, the front surface 212 is only obstructed by another portion of the front surface 212.

[0068] The moveable display support 220 may include a plurality of support elements 260. As shown, the moveable display support 220 includes five support elements 260-1, 260-2, 260-3, 260-4, 260-5. The support elements 260 may cooperate to limit bending about the back surface 214 of the display 210.

[0069] As shown, the support elements 260 limit bending about the back surface 214 of the display 210 to an infinite bend radius (e.g., planar). However, the support elements 260 are not capable of limiting movement of the display 210 beyond a radius of curvature 221, as shown in FIG. 4. Specifically, as the display 210 bends, the portions of the support elements 260 that contact, in some implementations are attached to, the display 210, retain their same individual geometry in both the planar and bent configurations. In other words, the first support element 260-1 (and/or any other support elements 260) does not change in length (in the direction of the bending). Thus, while capable of limiting motion of the display 210 to prevent exceeding a first bend radius (e.g., the infinite bend radius of FIG. 6), the implementation of a moveable display support 220 in FIGS. 4-6 is not capable of limiting motion of the display 210 to prevent exceeding a second bend radius (e.g., bend radius 221 of FIGS. 4-5).

[0070] FIG. 7 is a partial side view of an implementation of a moveable display support 320 in a planar configuration and FIG. 9 is a partial side view of the moveable display support 320 of FIG. 7 in a bent configuration. Referring generally to FIGS. 7 and 9, the moveable display support 320 may move between and/or to the planar configuration of FIG. 7 and the bent configuration of FIG. 9.

[0071] The moveable display support 320 includes a plurality of support elements 360. The support elements 360 may interlock. The plurality of support elements 360 may cooperate to form interlocking unit cells 350. The support elements 360 may include a plurality of pivots 352 and a plurality of links 354.

[0072] As shown, the moveable display support 320 includes three interlocking unit cells 350-1, 350-2, 350-3. The first unit cell 350-1 may be connected to the second unit cell 350-2 by the third link 352-3. The second unit cell 350-2 may be connected to the third unit cell 350-3 by the first link 352-1.

[0073] The first unit cell 350-1 is formed by ninth link 354-9, tenth link 354-10, eleventh link 354-11, and twelfth link 354-12. Ninth link 354-9 is connected to tenth link 354-10 by eighth pivot 352-8, tenth link 354-10 is connected to eleventh link 354-11 by ninth pivot 352-9, eleventh link 354-11 is connected to twelfth link 354-12 by tenth pivot 352-10, and twelfth link 354-12 is connected to ninth link 354-9 by third pivot 352-3.

[0074] The second unit cell 350-2 is formed by first link 354-1, second link 354-2, third link 354-3, and fourth link 354-4. First link 354-1 is connected to second link 354-2 by second pivot 352-2, second link 354-2 is connected to third link 354-3 by third pivot 352-3, third link 354-3 is connected to fourth link 354-4 by fourth pivot 352-4, and fourth link 354-4 is connected to first link 354-1 by first pivot 352-1.

[0075] The third unit cell 350-3 is formed by fifth link 354-5, sixth link 354-6, seventh link 354-7, and eighth link

354-8. Fifth link **354-5** is connected to sixth link **354-6** by fifth pivot **352-5**, sixth link **354-6** is connected to seventh link **354-7** by sixth pivot **352-6**, seventh link **354-7** is connected to eighth link **354-8** by seventh pivot **352-7**, and eighth link **354-8** is connected to fifth link **354-5** by first pivot **352-1**.

[0076] FIG. 8 is a side view of an implementation of a support element **360-1** of FIG. 7. The support element **360-1** may include the first pivot **352-1**, the fourth pivot **352-4**, and the seventh pivot **352-7**. The support element **360-1** includes the fourth link **354-4** and the eighth link **354-8**. The fourth link **354-4** extends from a first end **355-4-1** to a second end **355-4-2**. The eighth link **354-8** extends from a first end **355-8-1** to a second end **355-8-2**.

[0077] The fourth link **354-4** and the eighth link **354-8** are directly connected to each other such that the angle **351-1** between the fourth and eighth links **354-4**, **354-8** does not change. The angle **351-1** may be determined to control angles **361**, **363** (shown in FIGS. 7 and 9) between unit cells **350**.

[0078] As shown in FIG. 9, the unit cells **350** create a radius of curvature **321** in the bent configuration. The angles **351**, **361**, **363** may vary. In at least one implementation, in the planar configuration, the angle **351** may be 150 degrees, the angle **361** may be 90 degrees, and the angle **363** may be 81 degrees. As shown in FIG. 7, in the planar configuration, the angle **361-1** between the second unit cell **350-2** and the third unit cell **350-3** is larger than the angle **363-3** between the second unit cell **350-2** and the third unit cell **350-3**.

[0079] Unlike the moveable display support **220** of the implementation of FIGS. 4-6, the implementation of the moveable display support **320** of FIGS. 7 and 9 (and FIGS. 10 and 11) may be capable of limiting motion of the display **310** (shown in FIGS. 10 and 11) to prevent exceeding a first bend radius (e.g., the infinite bend radius of FIGS. 7 and 10), and may be capable of limiting motion of the display **310** to prevent exceeding a second bend radius (e.g., bend radius **321** shown in the bent configurations of FIGS. 9 and 11). The ability to limit motion of the display **310** in two directions without exceeding one or more bend radii of the display may be accomplished by using support elements (e.g., support elements **360**) and/or unit cells (e.g., unit cells **350**) that elongate during the bending process. In other words, a distance **365-1** between the second pivot **352-2** and the seventh pivot **452-7** may elongate from the first (e.g., planar) configuration to the second (e.g., bent configuration). In another example, as the moveable display support **320** transitions from the planar configuration of FIG. 7 to the bent configuration of FIG. 9, the angles **361-1** and **363-1** between the second and third unit cell **350-2**, **350-3** may increase.

[0080] FIG. 10 is a perspective side view of the moveable display support **320** of FIG. 7 in the planar configuration and FIG. 11 is a perspective side view of the moveable display support **320** of FIG. 7 in the bent configuration. As shown, the moveable display support **320** may be connected (e.g., adhered, affixed, mechanically connected) to the back surface of the display **310**.

[0081] As shown in FIGS. 10 and 11, unit cells **350** may form rows **362** and columns **364**. For example, unit cells **350-1**, **350-2**, **350-3** form column **364-1** and unit cells **350-2**, **350-5**, **350-8** form row **362-1**. The rows **362** may move together between configurations. For example, a pin may

extend through multiple pivots **352** in a row **362**. In another example, flexures may act as pivots **352**.

[0082] The moveable display support **320** may bend parallel to one or more rows **362**. In other words, the moveable display support **320** may act as a hinge. In some implementations, the moveable display support **320** may only bend parallel to one or more rows **362**. In other implementations, the moveable display support **320** may bend transversely to one or more rows **362**. For instance, the moveable display support **320** may bend about lines and/or curves that are not parallel to one or more rows **362**.

[0083] FIG. 12 is a cutaway side view of an implementation of a plurality of support elements **460** in a planar configuration and FIG. 13 is a cutaway side view of the plurality of support elements **460** in a bent configuration. The plurality of support elements **460** may be similar to other implementations of support elements described herein (e.g., support elements **260**, **360**). One or more components of other support elements described herein may be incorporated into the present implementation.

[0084] The plurality of support elements **460** include a first support element **460-1**, a second support element **460-2**, a third support element **460-3**, and a fourth support element **460-4**. The plurality of support elements **460** may be interconnected by pivots **452**. Links (not labeled) may extend between pivots **452**. Pivots **452** may include pins, flexures, or other pivots. Support elements **460** may cooperate to form unit cells. For example, the first support element **460-1**, the second support element **460-2**, the third support element **460-3**, and the fourth support element **460-4** may cooperate to form a first unit cell **450-1**.

[0085] The first support element **460-1** is connected to the second support element **460-2** by a first pivot **452-1**. The first support element **460-1** is connected to the fourth support element **460-4** by a second pivot **452-2**. The third support element **460-3** is connected to the fourth support element **460-4** by a third pivot **452-3**. The second support element **460-2** is connected to the third support element **460-3** by a fourth pivot **452-4**.

[0086] The pivots **452** may be separated by distances (e.g., distances **465**, **467**) and/or angles (e.g., angle **461**). A first angle **461-1** may be formed between the first support element **460-1** and the second support element **460-2** about the first pivot **452-1**.

[0087] The first angle **461-1** may increase from the planar configuration of FIG. 12 and the bent configuration of FIG. 13. A first distance **465-1** may be formed between the second pivot **452-2** and a seventh pivot **452-7**. A first distance **467-1** may be formed between the fourth pivot **452-4** and the fifth pivot **452-5**.

[0088] Similar to the implementation of a moveable display support **320** of FIGS. 7-11, the implementation of the moveable display support **420** of FIGS. 12-17 may be capable of limiting motion of display (e.g., displays **110**, **210**, **310**) attached to the moveable display support **420** to prevent exceeding a first bend radius (e.g., the infinite bend radius of FIGS. 12 and 14-15), and may be capable of limiting motion of the display to prevent exceeding a second bend radius (e.g., the bend radius shown in the bent configurations of FIGS. 13 and 16-17). The ability to limit motion of the display in two directions without exceeding one or more bend radii of the display may be accomplished by using support elements (e.g., support elements **460**) and/or unit cells (e.g., unit cells **450**) that elongate during the

bending process. In other words, a distance 465-1 between the second pivot 452-2 and the seventh pivot 452-7 may elongate from the first (e.g., planar) configuration to the second (e.g., bent configuration). In another example, as the moveable display support 420 transitions from the planar configuration of FIG. 7 to the bent configuration of FIG. 9, the angles (e.g., angle 461-1) between unit cells 450 may increase.

[0089] Support elements 460 may include stop surfaces 456, 457, 458, 459. Stop surfaces 456, 457, 458, 459 may cooperate to limit the motion (e.g., bending) of a moveable display support (e.g., moveable display support 420).

[0090] For example, in the planar configuration of FIG. 12, the stop surface 456-3 of the third support element 460-3 may abut the stop surface 457-1 of the first support element 460-1. In another example, in the bent configuration of FIG. 13, the stop surface 458-3 of the third support element 460-3 may abut the stop surface 459-1 of the first support element 460-1.

[0091] FIG. 14 is a side view of an implementation of a moveable display support 420 incorporating the plurality of support elements 460 of FIG. 12 in a planar configuration and FIG. 15 is a perspective side view of the moveable display support 420 of FIG. 14 in the planar configuration. Referring generally to FIGS. 14 and 15, the moveable display support 420 may include one or more rows 462 and/or one or more columns 464 of support elements 460. For example, the first row 462-1 may be formed through the first pivot 452-1 and may include the first support element 460-1 and the second support element 460-2. The moveable display support 420 may include eight rows 462-1, 462-2, 462-3, 462-4, 462-5, 462-6, 462-7, 462-8. In another example, the first column 464-1 may include the first support element 460-1, the third support element 460-3, the fifth support element 460-5, the seventh support element 460-7, the ninth support element 460-9, the eleventh support element 460-11, the thirteenth support element 460-13, and the fifteenth support element 460-15.

[0092] The moveable display support 420 may bend parallel to one or more rows 462. In other words, the moveable display support 420 may act as a hinge. In some implementations, the moveable display support 420 may only bend parallel to one or more rows 462. In other implementations, the moveable display support 420 may bend transversely to one or more rows 462. For instance, the moveable display support 420 may bend about lines and/or curves that are not parallel to one or more rows 462.

[0093] FIG. 16 is a side view of the moveable display support 420 of FIG. 14 in a bent configuration and FIG. 17 is a perspective side view of the moveable display support 420 of FIG. 14 in the bent configuration. In the planar configurations shown in FIGS. 14-15, the stop surfaces 456 may abut the stop surfaces 457. In the bent configurations of FIGS. 16-17, the stop surfaces 458 may abut the stop surfaces 459.

[0094] FIG. 18 is a front view of an implementation of a plurality of unit cells 550 in a planar configuration. The unit cells 550 may include one or more support elements 560. The unit cells 550 may be interconnected. As shown in FIG. 18, a first support element 560-1 of the first unit cell 550-1 and a second support element 560-2 of the second unit cell 550-2 may be linked. In other words, a portion of the first support element 560-1 the first unit cell 550-1 may extend through a portion of the second support element 560-2 of the

second unit cell 550-2. In another example, the first unit cell 550-1 may be linked to the second unit cell 550-2 in a manner similar to links of a chain. In other words, a first unit cell 550-1 may pivot relative to a second unit cell 550-2.

[0095] Linking unit cells 550 may allow for movement of between unit cells 550. The unit cells 550 may include stop surfaces 556, 557. As shown in FIG. 18, the stop surface 557-1 of the first unit cell 550-1 and the stop surface 557-2 of the second unit cell 550-1 may abut in a planar configuration. The stop surfaces 557 may limit movement of the unit cells 550. For example, the stop surfaces 557 may limit movement of the unit cells 550 from leaving the planar configuration.

[0096] Referring briefly to FIG. 25, which will be described further below, which illustrates a first stop surface 556-1 of the first unit cell 550-1 abutting a second stop surface 556-2 of the second unit cell 550-2. This abutting relationship may limit movement of the first and second unit cells 550-1, 550-2. For example, as shown, the stop surfaces 556 may limit movement of the unit cells 550 to the second configuration (e.g., a bent configuration).

[0097] FIG. 19 is a perspective top view of a plurality of rows 562 incorporating the plurality of unit cells 550 of FIG. 18 in the planar configuration. As shown, the unit cells 550 are linked and stop surfaces (e.g., stop surfaces 557 shown in FIG. 18) abut to limit movement of the unit cells 550.

[0098] The first unit cell 550-1 is in a first row 562-1 (with unit cells 550-3, 550-5, 550-7, 550-9, 550-11, 550-13, 550-15) and the second unit cell 550-2 is in a second row 562-2 (with unit cells 550-2, 550-4, 550-6, 550-8, 550-10, 550-12, 550-14, 550-16). The first unit cell 550-1 and the second unit cell 550-2 are in a first column 564-1 (with additional unit cells 550 as shown in FIG. 22). Additional unit cells 550 may be located in columns 564 (e.g., columns 564-1, 564-2, 564-3, 564-4, 564-5, 564-6, 564-7, 564-8).

[0099] The moveable display support 520 may bend parallel to one or more rows 562. In other words, the moveable display support 520 may act as a hinge. In some implementations, the moveable display support 520 may only bend parallel to one or more rows 562. In other implementations, the moveable display support 520 may bend transversely to one or more rows 562. For instance, the moveable display support 520 may bend about lines and/or curves that are not parallel to one or more rows 562.

[0100] FIG. 20 is a top view of a plurality of separated rows 562 of unit cells 550 in the planar configuration. In the present implementation, the unit cells 550 in each row 562 may be interconnected. In other words, the first unit cell 550-1 and the third unit cell 550-3 may be directly connected, integrally formed, unitarily constructed, or otherwise interconnected. The fifth unit cell 550-5, the seventh unit cell 550-7, the ninth unit cell 550-9, the eleventh unit cell 550-11, the thirteenth unit cell 550-13, and the fifteenth unit cell 550-15 may also be interconnected. The unit cells 550-2, 550-4, 550-6, 550-8, 550-10, 550-12, 550-14, 550-16 may also be interconnected.

[0101] In other implementations, fewer than all unit cells 550 in a row may be interconnected. For instance, first unit cell 550-1 and third unit cell 550-3 may be interconnected while third unit cell 550-3 is not interconnected with the fifth unit cell 550-5.

[0102] Similar to the implementations of a moveable display support 320, 420 of FIGS. 7-11 and 12-17, the implementation of the moveable display support 520 of

FIGS. 18-25 may be capable of limiting motion of display (e.g., displays 110, 210, 310) attached to the moveable display support 520 to prevent exceeding a first bend radius (e.g., the infinite bend radius of FIGS. 22-23), and may be capable of limiting motion of the display to prevent exceeding a second bend radius (e.g., the bend radius shown in the bent configurations of FIGS. 24-25). The ability to limit motion of the display in two directions without exceeding one or more bend radii of the display may be accomplished by using support elements (e.g., support elements 560) and/or unit cells (e.g., unit cells 550) that elongate during the bending process. In other words, a distance (not labeled) between the first stop surface 557-1 and the second stop surface 557-2 may elongate from the first (e.g., planar) configuration (where the distance is zero) to the second (e.g., bent configuration). In another example, as the moveable display support 520 transitions from the planar configuration of FIGS. 22-23 to the bent configuration of FIGS. 24-25, the angles (not labeled) between unit cells 550 may increase.

[0103] FIG. 21 is a top view of the plurality of interconnected rows 562 of unit cells 550 of FIG. 20 in the planar configuration. The first row 562-1 and the second row 562-2 may also be interconnected. The unit cells 550 of the first row 562-1 may be interconnected both to each other and to the unit cells 550 of the second row 562-2. For example, the unit cells 550 of the first row 562-1 may be directly connected together, as described herein, while the unit cells 550 of the first row 562-1 may be linked to the unit cells 550 of the second row 562-2. In another example, the unit cells 550 of the rows 562 may not be directly connected together, but may interconnect with the unit cells 550 of one or more other rows 562.

[0104] FIG. 22 is a perspective top view of an implementation of a moveable display support 520 incorporating the plurality of interconnected rows 562 and columns 564 of unit cells 550 of FIG. 21 in the planar configuration and FIG. 23 is a perspective bottom view of the moveable display support 520 of FIG. 21 in the planar configuration. As shown, the unit cells 550 in rows 562 and columns 564 are linked.

[0105] The unit cells 550 may include stop surfaces (e.g., stop surfaces 556, 557). One or more stop surfaces may limit movement of the moveable display support 520 beyond the planar configuration. In other words, as shown in FIG. 23, the stop surfaces may prevent bending of the bottom surface (not labeled) of the moveable display support 520 beyond the planar configuration. In other implementations, the unit cells 550 may be designed for a different bend radius (e.g., other than an infinite bend radius in the first, planar configuration).

[0106] FIG. 24 is a perspective top view and FIG. 25 is a perspective bottom view of the moveable display support 520 of FIG. 21 in the bent configuration. As shown, the unit cells 550 in rows 562 and columns 564 remain linked.

[0107] The unit cells 550 may include stop surfaces (e.g., stop surfaces 556, 557). One or more stop surfaces may limit movement of the moveable display support 520 beyond the bent configuration. In other words, as shown in FIG. 24, the stop surfaces may prevent bending of the top surface (not labeled) of the moveable display support 520 beyond the bent configuration. In other words, the stop surfaces may limit bending of the top surface to a predetermined bend radius. In other implementations, the unit cells 550 may be

designed for a different bend radius (e.g., an infinite bend radius like the first, planar configuration).

[0108] FIG. 26 is a front view of an implementation of a plurality of unit cells 650 in a planar configuration. The unit cells 650 may include one or more support elements 660. The unit cells 650 may be interconnected. As shown in FIG. 26, a first support element 660-1 of the first unit cell 650-1 and a second support element 660-2 of the second unit cell 650-2 may be linked. In other words, a first unit cell 650-1 may pivot relative to a second unit cell 650-2.

[0109] Similar to the implementations of a moveable display support 320, 420, 520, of FIGS. 7-11, 12-17, and 18-25, the implementation of the moveable display support 620 of FIGS. 26-33 may be capable of limiting motion of display (e.g., displays 110, 210, 310) attached to the moveable display support 620 to prevent exceeding a first bend radius (e.g., the infinite bend radius of FIGS. 30-31), and may be capable of limiting motion of the display to prevent exceeding a second bend radius (e.g., the bend radius shown in the bent configurations of FIGS. 32-33). The ability to limit motion of the display in two directions without exceeding one or more bend radii of the display may be accomplished by using support elements (e.g., support elements 660) and/or unit cells (e.g., unit cells 650) that elongate during the bending process. In other words, a distance (not labeled) between the first stop surface 657-1 and the second stop surface 656-2 may elongate from the first (e.g., planar) configuration (where the distance is zero) to the second (e.g., bent configuration). In another example, as the moveable display support 620 transitions from the planar configuration of FIGS. 30-31 to the bent configuration of FIGS. 32-33, the angles (not labeled) between unit cells 650 may increase.

[0110] The unit cells 650 may include stop surfaces 656, 657. As shown in FIG. 26, the stop surface 656-1 of the first unit cell 650-1 and the stop surface 656-2 of the second unit cell 650-1 may abut in a planar configuration.

[0111] Referring briefly to FIG. 21, which will be described further below, which illustrates abutting relationships between unit cells 650. These abutting relationships may limit movement of the unit cells 650.

[0112] FIG. 27 is a perspective top view of a plurality of rows 662 incorporating the plurality of unit cells 650 of FIG. 26 in the planar configuration. As shown, the unit cells 650 are linked and stop surfaces (e.g., stop surfaces 657 shown in FIG. 26) abut to limit movement of the unit cells 650.

[0113] The first unit cell 650-1 is in a first row 662-1 (with unit cells 650-3, 650-5, 650-7, 650-9, 650-11, 650-13, 650-15, 650-17, 650-19, 650-21) and the second unit cell 650-2 is in a second row 662-2 (with unit cells 650-2, 650-4, 650-6, 650-8, 650-10, 650-12, 650-14, 650-16, 650-18, 650-20, 650-22). The first unit cell 650-1 and the second unit cell 650-2 are in a first column 664-1 (with additional unit cells 650 as shown in FIG. 30). Additional unit cells 650 may be located in columns 664 (e.g., columns 664-1, 664-2, 664-3, 664-4, 664-5, 664-6, 664-7, 664-8).

[0114] The moveable display support 620 may bend parallel to one or more rows 662. In other words, the moveable display support 620 may act as a hinge. In some implementations, the moveable display support 620 may only bend parallel to one or more rows 662. In other implementations, the moveable display support 620 may bend transversely to one or more rows 662. For instance, the moveable display support 620 may bend about lines and/or curves that are not parallel to one or more rows 662.

[0115] FIG. 28 is a top view of a plurality of separated rows 662 of unit cells 650 in the planar configuration. In the present implementation, the unit cells 650 in each row 662 may be interconnected. In other words, the first unit cell 650-1 and the third unit cell 650-3 may be directly connected, integrally formed, unitarily constructed, or otherwise interconnected. The fifth unit cell 650-5, the seventh unit cell 650-7, the ninth unit cell 650-9, the eleventh unit cell 650-11, the thirteenth unit cell 650-13, the fifteenth unit cell 650-15, the seventeenth unit cell 650-17, the nineteenth unit cell 650-19, and the twenty-first unit cell 650-21 may also be interconnected. The unit cells 650-2, 650-4, 650-6, 650-8, 650-10, 650-12, 650-14, 650-16, 650-18, 650-20 may also be interconnected.

[0116] In other implementations, fewer than all unit cells 650 in a row may be interconnected. For instance, first unit cell 650-1 and third unit cell 650-3 may be interconnected while third unit cell 650-3 is not interconnected with the fifth unit cell 650-5.

[0117] FIG. 29 is a top view of a plurality of interconnected rows 662 of unit cells 650 in the planar configuration. The first row 662-1 and the second row 662-2 may also be interconnected. The unit cells 650 of the first row 662-1 may be interconnected both to each other and to the unit cells 650 of the second row 662-2.

[0118] FIG. 30 is a perspective top view of an implementation of a moveable display support 620 incorporating the plurality of interconnected rows 662 of unit cells 650 of FIG. 29 in the planar configuration and FIG. 31 is a perspective bottom view of the moveable display support 620 of FIG. 29 in the planar configuration. As shown, the unit cells 650 in rows 662 and columns 664 are linked.

[0119] The unit cells 650 may include stop surfaces (e.g., stop surfaces 656, 657). One or more stop surfaces may limit movement of the moveable display support 620 beyond the planar configuration. In other words, as shown in FIG. 30, the stop surfaces may prevent bending of the top surface (not labeled) of the moveable display support 620 beyond the planar configuration. In other implementations, the unit cells 650 may be designed for a different bend radius (e.g., other than an infinite bend radius in the first, planar configuration).

[0120] FIG. 32 is a perspective top view and FIG. 33 is a perspective bottom view of the moveable display support 620 of FIG. 28 in the bent configuration. As shown, the unit cells 650 in rows 662 and columns 664 remain linked.

[0121] The unit cells 650 may include stop surfaces (e.g., stop surfaces 656, 657). One or more stop surfaces may limit movement of the moveable display support 620 beyond the bent configuration. In other implementations, the unit cells 650 may be designed for a different bend radius (e.g., an infinite bend radius like the first, planar configuration).

[0122] The articles “a,” “an,” and “the” are intended to mean that there are one or more of the elements in the preceding descriptions. The terms “comprising,” “including,” and “having” are intended to be inclusive and mean that there may be additional elements other than the listed elements. Additionally, it should be understood that references to “one implementation” or “an implementation” of the present disclosure are not intended to be interpreted as excluding the existence of additional implementations that also incorporate the recited features. For example, any element described in relation to an implementation herein may be combinable with any element of any other implementation described herein. Numbers, percentages, ratios, or

other values stated herein are intended to include that value, and also other values that are “about” or “approximately” the stated value, as would be appreciated by one of ordinary skill in the art encompassed by implementations of the present disclosure. A stated value should therefore be interpreted broadly enough to encompass values that are at least close enough to the stated value to perform a desired function or achieve a desired result. The stated values include at least the variation to be expected in a suitable manufacturing or production process, and may include values that are within 5%, within 1%, within 0.1%, or within 0.01% of a stated value.

[0123] A person having ordinary skill in the art should realize in view of the present disclosure that equivalent constructions do not depart from the spirit and scope of the present disclosure, and that various changes, substitutions, and alterations may be made to implementations disclosed herein without departing from the spirit and scope of the present disclosure. Equivalent constructions, including functional “means-plus-function” clauses are intended to cover the structures described herein as performing the recited function, including both structural equivalents that operate in the same manner, and equivalent structures that provide the same function. It is the express intention of the applicant not to invoke means-plus-function or other functional claiming for any claim except for those in which the words “means for” appear together with an associated function. Each addition, deletion, and modification to the implementations that falls within the meaning and scope of the claims is to be embraced by the claims.

[0124] It should be understood that any directions or reference frames in the preceding description are merely relative directions or movements. For example, any references to “front” and “back” or “top” and “bottom” or “left” and “right” are merely descriptive of the relative position or movement of the related elements.

[0125] The present disclosure may be embodied in other specific forms without departing from its spirit or characteristics. The described implementations are to be considered as illustrative and not restrictive. The scope of the disclosure is, therefore, indicated by the appended claims rather than by the foregoing description. Changes that come within the meaning and range of equivalency of the claims are to be embraced within their scope.

What is claimed is:

1. A computing device, comprising:

a flexible display including a thin film transistor matrix having a front surface and a back surface; and

a moveable display support connected to the back surface of the display and configured to limit bending in one direction to a first bend radius while maintaining strain on the thin film transistor matrix below a predetermined amount of strain by elongating the moveable display support during bending.

2. The computing device of claim 1, wherein the moveable display support includes a plurality of interlocking elements.

3. The computing device of claim 1, wherein the moveable display support extends between a first edge of the flexible display and a second edge of the flexible display.

4. The computing device of claim 1, wherein the flexible display has a dimension from a first edge to a second edge and wherein the moveable display support extends from within five percent of the dimension of the first edge of the

flexible display to within five percent of the dimension of the second edge of the flexible display.

5. The computing device of claim 1, wherein the moveable display support extends from a first edge of the flexible display to a second edge of the flexible display.

6. The computing device of claim 1, wherein the moveable display support is attached to the back surface of the flexible display.

7. The computing device of claim 1, wherein the flexible display includes a layer adjacent one or more front layers, and one or more back layers, to form a stack.

8. The computing device of claim 7, wherein the stack is foldable between infinite radius to a radius of 2 mm without additional support.

9. The computing device of claim 8, wherein the moveable display support and the flexible display cooperate to reduce the radius to which the stack is foldable by 1 mm.

10. The computing device of claim 1, wherein the moveable display support is formed of a material having sufficient hardness to prevent strain above 0.5% of the predetermined amount of strain.

11. The computing device of claim 1, wherein the moveable display support is formed by additive manufacturing.

12. A computing device, comprising:

a flexible display having a front surface and a back surface; and

a moveable display support connected to the back surface of the display, the moveable display support formed by a plurality of unit cells.

13. The computing device of claim 12, wherein the moveable display support includes a second unit cell.

14. The computing device of claim 13, wherein the second unit cell is connected to the first unit cell.

15. The computing device of claim 12, the plurality of unit cells extends in rows and columns.

16. The computing device of claim 15, wherein a first row of unit cells of the plurality of unit cells and a second row of unit cells of the plurality of unit cells are interconnected.

17. The computing device of claim 15, wherein a first row of unit cells of the plurality of unit cells and a second row of unit cells of the plurality of unit cells are linked.

18. The computing device of claim 15, wherein a first row of unit cells of the plurality of unit cells and a second row of unit cells of the plurality of unit cells are pinned.

19. The computing device of claim 15, wherein a first row of unit cells of the plurality of unit cells and a second row of unit cells of the plurality of unit cells are directly connected.

20. A computing device, comprising:

an organic light-emitting diode (OLED) display including a thin film transistor matrix having a front surface and a back surface; and

a moveable display support connected to the back surface of the display and configured to limit bending in one direction to a first bend radius and to limit bending in another direction to a second bend radius, the moveable display support formed by a plurality of unit cells, the moveable display support including a plurality of interlocking elements, wherein the OLED display has a dimension from a first edge to a second edge and wherein the moveable display support extends from within five percent of the dimension of the first edge of the OLED display to within five percent of the dimension of the second edge of the OLED display, wherein the moveable display support is attached to the back surface of the OLED display.

* * * * *

专利名称(译)	可移动显示器支持，使用它的计算设备和使用方法		
公开(公告)号	US20190173041A1	公开(公告)日	2019-06-06
申请号	US15/832639	申请日	2017-12-05
[标]申请(专利权)人(译)	微软技术许可有限责任公司		
申请(专利权)人(译)	微软技术Licensing，LLC公司		
当前申请(专利权)人(译)	微软技术Licensing，LLC公司		
[标]发明人	LARGE TIMOTHY ANDREW GHIONI LINCOLN MATTHEW BABU SARAT LONGBOTTOM MATTHEW JAMES		
发明人	LARGE, TIMOTHY ANDREW GHIONI, LINCOLN MATTHEW BABU, SARAT LONGBOTTOM, MATTHEW JAMES CARTER, DUNCAN ALEXANDER WALLIS		
IPC分类号	H01L51/52 H01L51/00 H01L51/56		
CPC分类号	H01L51/524 H01L51/0097 H01L51/56 H01L2251/5338 G06F1/1652 G06F1/1681 H04M1/0216 H04M1/0268		
外部链接	Espacenet USPTO		

摘要(译)

公开了一种包括有机发光二极管 (OLED) 显示器的计算设备。OLED显示器具有前表面和后表面。计算设备包括连接到显示器的后表面的可移动显示器支撑件。在一些实施方案中，可移动显示器支撑件经配置以将沿一个方向的弯曲限制到第一弯曲半径并将另一方向上的弯曲限制到第二弯曲半径。在一些实施方式中，可移动显示器支撑件由多个单元电池形成。

