



US010516112B2

(12) **United States Patent**
Kato et al.

(10) **Patent No.:** **US 10,516,112 B2**
(45) **Date of Patent:** **Dec. 24, 2019**

(54) **COMPOUND, ORGANIC ELECTROLUMINESCENT ELEMENT MATERIAL, ORGANIC ELECTROLUMINESCENT ELEMENT, AND ELECTRONIC DEVICE**

(71) Applicant: **IDEMITSU KOSAN CO., LTD.**, Chiyoda-ku (JP)

(72) Inventors: **Tomoki Kato**, Ichihara (JP); **Nobuhiro Yabunouchi**, Sodegaura (JP); **Masakazu Funahashi**, Chiba (JP); **Takahiro Fujiyama**, Kisarazu (JP)

(73) Assignee: **IDEMITSU KOSAN CO., LTD.**, Chiyoda-ku (JP)

(*) Notice: Subject to any disclaimer, the term of this patent is extended or adjusted under 35 U.S.C. 154(b) by 6 days.

(21) Appl. No.: **14/910,156**

(22) PCT Filed: **Jul. 13, 2015**

(86) PCT No.: **PCT/JP2015/070047**

§ 371 (c)(1),
(2) Date: **Feb. 4, 2016**

(87) PCT Pub. No.: **WO2016/006711**

PCT Pub. Date: **Jan. 14, 2016**

(65) **Prior Publication Data**

US 2016/0181525 A1 Jun. 23, 2016

(30) **Foreign Application Priority Data**

Jul. 11, 2014 (JP) 2014-143248

Jul. 11, 2014 (JP) 2014-143249

(Continued)

(51) **Int. Cl.**

H01L 51/00 (2006.01)

C07D 333/76 (2006.01)

(Continued)

(52) **U.S. Cl.**

CPC **H01L 51/006** (2013.01); **C07C 211/61** (2013.01); **C07D 209/82** (2013.01);
(Continued)

(58) **Field of Classification Search**

CPC **C07D 405/12**; **C07D 405/04**; **C09K 11/06**; **H01L 51/06**; **H01L 51/0061**;
(Continued)

(56) **References Cited**

U.S. PATENT DOCUMENTS

2011/0215308 A1 9/2011 Im et al.
2015/0179940 A1* 6/2015 Mujica-Fernaud
H01L 51/0052
252/519.21
2015/0243891 A1 8/2015 Kato et al.

FOREIGN PATENT DOCUMENTS

CN 101341115 1/2009
EP 2 891 648 A1 7/2015
(Continued)

OTHER PUBLICATIONS

Extended European Search Report dated Nov. 24, 2016 in Patent Application No. 15819013.2.

(Continued)


Primary Examiner — Ruiyun Zhang



(74) *Attorney, Agent, or Firm* — Oblon, McClelland, Maier & Neustadt, L.L.P.

(57) **ABSTRACT**

A compound represented by formula (A-0) or (B-0) is useful as a material for organic EL devices which realizes an organic EL device exhibiting high emission efficiency even when driving at a low voltage and has a long lifetime:

(Continued)





wherein R¹ to R⁴, n₁, m₂, k₃, k₄, L⁰ to L², Ar¹, and Ar² are as defined in the description.

17 Claims, 1 Drawing Sheet

(30) Foreign Application Priority Data

Dec. 17, 2014	(JP)	2014-255559
Dec. 17, 2014	(JP)	2014-255562
Dec. 17, 2014	(JP)	2014-255565

(51) Int. Cl.

C07C 211/61	(2006.01)
C07D 307/91	(2006.01)
C09K 11/06	(2006.01)
H01L 51/50	(2006.01)
C07D 209/82	(2006.01)
C07D 405/12	(2006.01)
C07D 209/86	(2006.01)

(52) U.S. Cl.

CPC **C07D 209/86** (2013.01); **C07D 307/91** (2013.01); **C07D 333/76** (2013.01); **C07D 405/12** (2013.01); **C09K 11/06** (2013.01); **H01L 51/0061** (2013.01); **H01L 51/0072** (2013.01); **H01L 51/0073** (2013.01); **H01L 51/0074** (2013.01); **H01L 51/50** (2013.01); **H01L 51/5012** (2013.01); **C07C 2603/18** (2017.05); **C07C 2603/42** (2017.05); **C09K 2211/1007** (2013.01); **C09K 2211/1011** (2013.01); **C09K 2211/1014** (2013.01); **C09K 2211/1018** (2013.01); **H01L 51/0052** (2013.01); **H01L 51/0054** (2013.01); **H01L 51/0058** (2013.01); **H01L 51/5016** (2013.01); **H01L 51/5056** (2013.01); **H01L 51/5064**

(2013.01); **H01L 51/5072** (2013.01); **H01L 51/5088** (2013.01); **H01L 51/5092** (2013.01)

(58) Field of Classification Search

CPC ... **H01L 51/0062**; **H01L 51/0071-0074**; **H01L 51/50**; **H01L 51/5012**; **H01L 51/5052**; **H01L 51/5056**
 USPC 428/690, 917; 257/40, E51.027, E51.032, 257/E51.035; 549/43, 460; 564/308
 See application file for complete search history.

(56) References Cited


FOREIGN PATENT DOCUMENTS

JP	11-144875	A	5/1999
JP	2008-300503		12/2008
JP	2009-010364		1/2009
JP	2011-187959	A	9/2011
JP	2013-539205	A	10/2013
KR	2013-0121597		11/2013
KR	10-2014-0024734	A	3/2014
KR	10-2014-0098502	A	8/2014
KR	10-2015-0007476	A	1/2015
WO	2011/021520	A1	2/2011
WO	2012/011642		1/2012
WO	2013/182263	A1	12/2013
WO	2014/015935	A2	1/2014
WO	2014/015937	A1	1/2014
WO	2014/034795		3/2014
WO	2014/034795	A1	3/2014
WO	WO 2014/088285	A1	6/2014
WO	WO 2015/041428	A1	3/2015
WO	2015-082056		6/2015
WO	WO 2015/162912	A1	10/2015
WO	WO 2016/122150	A2	8/2016

OTHER PUBLICATIONS

International Search Report dated Oct. 13, 2015 in PCT/JP2015/070047 filed Jul. 13, 2015.
 Official Action dated Sep. 28, 2018, in connection with a corresponding Chinese patent application No. 2015/80001555.0.
 Office Action as received in the corresponding European Patent Application No. 15 818 619.7-110 dated Nov. 16, 2018.
 Office Action as received in the corresponding Chinese Patent Application No. 201580001554.6 dated May 21, 2018 w/English Translation.
 Office Action dated Aug. 28, 2018 in the corresponding Japanese patent application with machine English translation (JP-OA 2016-504820).
 Office Action dated Aug. 28, 2018 in the corresponding Japanese patent application with machine English translation (JP-2015-560883).
 European Office Action dated Nov. 8, 2018 in European Patent Application No. 15 818 448.1, citing documents AO and AP therein, 6 pages.
 Japanese Office Action dated Feb. 5, 2019 in Japanese Patent Application No. 2015-560883 (with English translation), 6 pages.
 Japanese Office Action dated Feb. 5, 2019 in Japanese Patent Application No. 2016-504820 (with English translation), 6 pages.
 Chinese Office Action dated Feb. 22, 2019 in Patent Application No. 201580001549.5 (with English translation), 10 pages.
 Japanese Office Action dated Mar. 5, 2019 in Patent Application No. 2016-504413 (with English translation), citing document AO therein, 9 pages.
 Office Action issued in EP Application No. 15 818 448.1, dated Jun. 21, 2019.
 Office Action as received in the corresponding Chinese Patent Application No. 201580001555.0 dated Jun. 17, 2019 w/English Translation.
 Office Action as received in the corresponding Chinese Patent Application No. 201580001549.5 dated Nov. 4, 2019 / English Translation not available.

* cited by examiner



1
**COMPOUND, ORGANIC
 ELECTROLUMINESCENT ELEMENT
 MATERIAL, ORGANIC
 ELECTROLUMINESCENT ELEMENT, AND
 ELECTRONIC DEVICE**

TECHNICAL FIELD

The present invention relates to compounds, materials for organic electroluminescence devices comprising the compounds, organic electroluminescence devices comprising the compounds, and electronic equipment comprising the organic electroluminescence devices.

BACKGROUND ART

An organic electroluminescence device (also referred to as "organic EL device") is generally composed of an anode, a cathode, and one or more organic thin film layers which comprise a light emitting layer and are sandwiched between the anode and the cathode. When a voltage is applied between the electrodes, electrons are injected from the cathode and holes are injected from the anode into a light emitting region. The injected electrons recombine with the injected holes in the light emitting region to form excited states. When the excited states return to the ground state, the energy is released as light. Therefore, it is important for increasing the efficiency of an organic EL device to develop a compound which transports electrons or holes into a light emitting region efficiently and facilitates the recombination of electrons and holes.

The lower voltage drive of an organic EL device is effective for reducing the power consumption and also effective for improving the emission efficiency and the device lifetime. To reduce the driving voltage, a charge transporting material having a high electron mobility and/or a high hole mobility is required, and many proposals have been made on such a charge transporting material.

CITATION LIST

Patent Literature

Patent Literature 1: WO 2013/182263

Patent Literature 2: WO 2014/015935

Patent Literature 3: WO 2014/015937

Patent Literature 4: WO 2011/021520

SUMMARY OF INVENTION

Technical Problem

An object of the present invention is to provide an organic EL device which exhibits high emission efficiency even when driving at a lower voltage and has long lifetime and also provide a material for organic EL devices which realizes such an organic EL device.



Solution to Problem

As a result of extensive research in view of achieving the above object, the inventors have found that a compound represented by formula (A-0) or (B-0) has a high hole mobility, and further found that an organic EL device which is capable of driving at a lower voltage and has high emission efficiency and long lifetime is obtained by using the compound.

2

In an aspect of the invention, the following (1) to (4) are provided:

(1) a compound represented by formula (A-0) or (B-0):




wherein R^1 to R^4 each independently represent, a substituted or unsubstituted alkyl group having 1 to 20 carbon atoms, a substituted or unsubstituted aryl group having 6 to 50 ring carbon atoms, a substituted or unsubstituted heteroaryl group having 5 to 50 ring atoms, a halogen atom, a substituted or unsubstituted fluoroalkyl group having 1 to 20 carbon atoms, a substituted or unsubstituted alkoxy group having 1 to 20 carbon atoms, a substituted or unsubstituted fluoroalkoxy group having 1 to 20 carbon atoms, a substituted or unsubstituted aryloxy group having 6 to 50 ring carbon atoms, or a cyano group, and when R^1 to R^4 are each plurality in number, groups R^1 to groups R^4 may be the same or different;

k_3 and k_4 each independently represent an integer of 0 to 5, m_2 represents an integer of 0 to 4, and n_1 represents an integer of 0 to 3;


L^0 to L^2 each independently represent a single bond, a substituted or unsubstituted arylene group having 6 to 50 ring carbon atoms, or a substituted or unsubstituted heteroarylene group having 5 to 50 ring atoms;

Ar^1 and Ar^2 each independently represent a group represented by any of formulae (a) to (c):



3

-continued



wherein R^5 and R^6 are each independently the same as defined with respect to R^1 , when R^5 and R^6 are each plurality in number, groups R^5 and groups R^6 may be the same or different, and R^5 and R^6 may be bonded to each other to form a ring structure;

$m5$ and $m6$ each independently represent an integer of 0 to 4, and each $n5$ independently represents an integer of 0 to 3; and

* represents a bonding site to the nitrogen atom, L^1 , or L^2 in formula (A-0) or (B-0);

(2) a material for organic electroluminescence devices comprising the compound according to (1);

(3) an organic electroluminescence device which comprises a cathode, an anode, and at least one organic thin film layer disposed between the cathode and the anode, wherein the at least one organic thin film layer comprises a light emitting layer and at least one layer of the at least one organic thin film layer comprises the compound according to (1); and

(4) an electronic equipment comprising the organic electroluminescence device according to (3).

Advantageous Effects of Invention

An organic EL device which exhibits high emission efficiency even when driving at a lower voltage and has a long lifetime is obtained by using the compound represented by formula (A-0) or (B-0) as the material for organic EL devices.

BRIEF DESCRIPTION OF DRAWINGS

FIG. 1 is a schematic illustration of the structure of an organic EL device in an aspect of the present invention.

DESCRIPTION OF EMBODIMENTS

The term of “XX to YY carbon atoms” referred to by “a substituted or unsubstituted group ZZ having XX to YY carbon atoms” used herein is the number of carbon atoms of the unsubstituted group ZZ and does not include any carbon atom in the substituent of the substituted group ZZ.

The term of “XX to YY atoms” referred to by “a substituted or unsubstituted group ZZ having XX to YY atoms” used herein is the number of atoms of the unsubstituted group ZZ and does not include any atom in the substituent of the substituted group ZZ.

The number of “ring carbon atoms” referred to herein means the number of the carbon atoms included in the atoms which are members forming the ring itself of a compound in which a series of atoms is bonded to form a ring (for

4

example, a monocyclic compound, a fused ring compound, a cross-linked compound, a carbocyclic compound, and a heterocyclic compound). If the ring has a substituent, the carbon atom in the substituent is not included in the ring carbon atom. The same applies to the number of “ring carbon atom” described below, unless otherwise noted. For example, a benzene ring has 6 ring carbon atoms, a naphthalene ring has 10 ring carbon atoms, a pyridinyl group has 5 ring carbon atoms, and a furanyl group has 4 ring carbon atoms. If a benzene ring or a naphthalene ring has, for example, an alkyl substituent, the carbon atom in the alkyl substituent is not counted as the ring carbon atom of the benzene or naphthalene ring. In case of a fluorene ring to which a fluorene substituent is bonded (inclusive of a spirofluorene ring), the carbon atom in the fluorene substituent is not counted as the ring carbon atom of the fluorene ring.

The number of “ring atom” referred to herein means the number of the atoms which are members forming the ring itself (for example, a monocyclic ring, a fused ring, and a ring assembly) of a compound in which a series of atoms is bonded to form the ring (for example, a monocyclic compound, a fused ring compound, a cross-linked compound, a carbocyclic compound, and a heterocyclic compound). The atom not forming the ring (for example, hydrogen atom(s) for saturating the valence of the atom which forms the ring) and the atom in a substituent, if the ring is substituted, are not counted as the ring atom. The same applies to the number of “ring atoms” described below, unless otherwise noted. For example, a pyridine ring has 6 ring atoms, a quinazoline ring has 10 ring atoms, and a furan ring has 5 ring atoms. The hydrogen atom on the ring carbon atom of a pyridine ring or a quinazoline ring and the atom in a substituent are not counted as the ring atom. In case of a fluorene ring to which a fluorene substituent is bonded (inclusive of a spirofluorene ring), the atom in the fluorene substituent is not counted as the ring atom of the fluorene ring.

The definition of “hydrogen atom” used herein includes isotopes different in the neutron numbers, i.e., light hydrogen (protium), heavy hydrogen (deuterium), and tritium.

The terms of “heteroaryl group” and “heteroarylene group” used herein means a group having at least one hetero atom as a ring atom. The hetero atom is preferably at least one selected from a nitrogen atom, an oxygen atom, a sulfur atom, a silicon atom, and a selenium atom.

The optimal substituent referred to by “substituted or unsubstituted” used herein is preferably selected from the group consisting of an alkyl group having 1 to 50, preferably 1 to 18, more preferably 1 to 8 carbon atoms; a cycloalkyl group having 3 to 50, preferably 3 to 10, more preferably 3 to 8, still more preferably 5 or 6 ring carbon atoms; an aryl group having 6 to 50, preferably 6 to 25, more preferably 6 to 18 ring carbon atoms; an aralkyl group having 7 to 51, preferably 7 to 30, more preferably 7 to 20 carbon atoms which includes an aryl group having 6 to 50, preferably 6 to 25, more preferably 6 to 18 ring carbon atoms; an amino group; an alkoxy group having an alkyl group having 1 to 50, preferably 1 to 18, more preferably 1 to 8 carbon atoms; an aryloxy group having an aryl group having 6 to 50, preferably 6 to 25, more preferably 6 to 18 ring carbon atoms; a mono-, di- or tri-substituted silyl group, wherein the substituent is selected from an alkyl group having 1 to 50, preferably 1 to 18, more preferably 1 to 8 carbon atoms and an aryl group having 6 to 50, preferably 6 to 25, more preferably 6 to 18 ring carbon atoms; a heteroaryl group having 5 to 50, preferably 5 to 24, more preferably 5 to 13

5

ring atoms; a haloalkyl group having 1 to 50, preferably 1 to 18, more preferably 1 to 8 carbon atoms; a halogen atom selected from a fluorine atom, a chlorine atom, a bromine atom and an iodine atom; a cyano group; a nitro group; a substituted sulfonyl group, wherein the substituent is selected from an alkyl group having 1 to 50, preferably 1 to 18, more preferably 1 to 8 carbon atoms and an aryl group having 6 to 50, preferably 6 to 25, more preferably 6 to 18 ring carbon atoms; a di-substituted phosphoryl group, wherein the substituent is selected from an alkyl group having 1 to 50, preferably 1 to 18, more preferably 1 to 8 carbon atoms and an aryl group having 6 to 50, preferably 6 to 25, more preferably 6 to 18 ring carbon atoms; an alkylsulfonyloxy group; an arylsulfonyloxy group; an alkylcarbonyloxy group; an arylcarbonyloxy group; a boron-containing group; a zinc-containing group; a tin-containing group; a silicon-containing group; a magnesium-containing group; a lithium-containing group; a hydroxyl group; an alkyl-substituted or aryl-substituted carbonyl group; a carboxyl group; a vinyl group; a (meth)acryloyl group; an epoxy group; and an oxetanyl group.

The optional substituent may further has the substituent mentioned above. The optional substituents may be bonded to each other to form a ring.


The term of "unsubstituted" referred to by "substituted or unsubstituted" used herein means that no hydrogen atom in a group is substituted by a substituent.

Of the above substituents, more preferred are an alkyl group having 1 to 50, preferably 1 to 18, more preferably 1 to 8 carbon atoms; a cycloalkyl group having 3 to 50, preferably 3 to 10, more preferably 3 to 8, still more preferably 5 or 6 ring carbon atoms; an aryl group having 6 to 50, preferably 6 to 25, more preferably 6 to 18 ring carbon atoms; a heteroaryl group having 5 to 50, preferably 5 to 24, more preferably 5 to 13 ring atoms; a halogen atom; and a cyano group.

In the present invention, those which are defined as being preferred can be selected arbitrarily and a combination thereof is a more preferred embodiment.

Compound

In an aspect of the invention, a compound represented by formula (A-0) (also referred to as "compound (A)") and a compound represented by formula (B-0) (also referred to as "compound (B)") are provided. The compound (A) and the compound (B) are useful as a material for organic electroluminescence devices.




(A-0)

6

-continued

(B-0)



R¹ to R⁴ in formulae (A-0) and (B-0)

In formulae (A-0) and (B-0), R¹ to R⁴ each represent a substituent which is bonded to a carbon atom of each benzene ring in each formula.

R¹ to R⁴ each independently represent a substituted or unsubstituted alkyl group having 1 to 20, preferably 1 to 8, and more preferably 1 to 3 carbon atoms; a substituted or unsubstituted aryl group having 6 to 50, preferably 6 to 25, more preferably 6 to 18, and still more preferably 6 to 12 ring carbon atoms; a substituted or unsubstituted heteroaryl group having 5 to 50, preferably 5 to 10, more preferably 5 to 8, and still more preferably 5 or 6 ring atoms; a halogen atom, a substituted or unsubstituted fluoroalkyl group having 1 to 20, preferably 1 to 5, and more preferably 1 to 4 carbon atoms; a substituted or unsubstituted alkoxy group having 1 to 20, preferably 1 to 5, and more preferably 1 to 4 carbon atoms; a substituted or unsubstituted fluoroalkoxy group having 1 to 20, preferably 1 to 5, and more preferably 1 to 4 carbon atoms; a substituted or unsubstituted aryloxy group having 6 to 50, preferably 6 to 25, more preferably 6 to 18, and still more preferably 6 to 12 ring carbon atoms; or a cyano group.

Preferably, R¹ to R⁴ in formulae (A-0) and (B-0) each independently represent a group selected from the group consisting of a substituted or unsubstituted alkyl group having 1 to 20 carbon atoms, a substituted or unsubstituted heteroaryl group having 5 to 50 ring atoms, and a halogen atom, with a substituted or unsubstituted alkyl group having 1 to 20 carbon atoms being more preferred.

The subscripts k₃ and k₄ each independently represent an integer of 0 to 5, preferably an integer of 0 to 2, more preferably 0 or 1, and still more preferably 0;

m₂ represents an integer of 0 to 4, preferably an integer of 0 to 2, more preferably 0 or 1, and still more preferably 0; and

n₁ represents an integer of 0 to 3, preferably an integer of 0 to 2, more preferably 0 or 1, and still more preferably 0.

When k₃, k₄, m₂, and n₁ are each 0, each benzene ring has no substituent.

When R¹ to R⁴ are each plurality in number, groups R¹ to groups R⁴ may be the same or different.

In an embodiment of the invention, two selected from R¹ to R⁴ are not bonded to each other, thereby failing to form a ring structure.

Examples of the alkyl group having 1 to 20 carbon atoms include a methyl group, an ethyl group, a n-propyl group, an isopropyl group, a n-butyl group, an isobutyl group, a s-butyl group, a t-butyl group, a pentyl group (inclusive of isomeric groups), a hexyl group (inclusive of isomeric groups), a heptyl group (inclusive of isomeric groups), an octyl group (inclusive of isomeric groups), a nonyl group

(inclusive of isomeric groups), a decyl group (inclusive of isomeric groups), an undecyl group (inclusive of isomeric groups), and a dodecyl group (inclusive of isomeric groups).

Of the above, preferred are a methyl group, an ethyl group, a n-propyl group, an isopropyl group, a n-butyl group, an isobutyl group, a s-butyl group, a t-butyl group, and a pentyl group (inclusive of isomeric groups), with a methyl group, an ethyl group, a n-propyl group, an isopropyl group, a n-butyl group, an isobutyl group, a s-butyl group, and a t-butyl group being more preferred, and a methyl group and a t-butyl group being still more preferred.

Examples of the aryl group having 6 to 50 ring carbon atoms include a phenyl group, a naphthylphenyl group, a biphenyl group, a terphenyl group, a biphenylenyl group, a naphthyl group, a phenylnaphthyl group, an ace-naphthylenyl, an anthryl group, a benzanthryl group, an aceanthryl group, a phenanthryl group, a benzophenanthryl group, a phenalenyl group, a fluorenyl group, a 9,9-dimethylfluorenyl group, a 7-phenyl-9,9-dimethylfluorenyl group, a pentaceny group, a picenyl group, a pentaphenyl group, a pyrenyl group, a chrysenyl group, a benzochrysenyl group, a s-indacenyl group, an as-indacenyl group, a fluoranthenyl group, and a perylenyl group.

Of the above, preferred are a phenyl group, a naphthylphenyl group, a biphenyl group, a terphenyl group, a naphthyl group, and a 9,9-dimethylfluorenyl group, with a phenyl group, a biphenyl group, a naphthyl group, and a 9,9-dimethylfluorenyl group being more preferred, and a phenyl group being still more preferred.

The heterocyclic group having 5 to 50 ring atoms comprises at least one, preferably 1 to 3 hetero atoms which may be the same or different, such as a nitrogen atom, a sulfur atom and an oxygen atom.

Examples of the heterocyclic group include a pyrrolyl group, a furyl group, a thienyl group, a pyridyl group, a pyridazinyl group, a pyrimidinyl group, a pyrazinyl group, a triazinyl group, an imidazolyl group, an oxazolyl group, a thiazolyl group, a pyrazolyl group, an isoxazolyl group, an isothiazolyl group, an oxadiazolyl group, a thiadiazolyl group, a triazolyl group, an indolyl group, an isoindolyl group, a benzofuranyl group, an isobenzofuranyl group, a benzothiofenyl group, an isobenzothiofenyl group, an indoliziny group, a quinoliziny group, a quinolyl group, an isoquinolyl group, a cinnoyl group, a phthalaziny group, a quinazoliny group, a quinoxaliny group, a benzimidazolyl group, a benzoxazolyl group, a benzothiazolyl group, an indazolyl group, a benzisoxazolyl group, a benzisothiazolyl group, a dibenzofuranyl group, a dibenzothiofenyl group, a phenanthridinyl group, an acridinyl group, a phenanthroli-nyl group, a phenaziny group, a phenothiaziny group, a phenoxaziny group, and a xanthenyl group.

Of the above, preferred are a furyl group, a thienyl group, a pyridyl group, a pyridazinyl group, a pyrimidinyl group, a pyrazinyl group, a triazinyl group, a benzofuranyl group, a benzothiofenyl group, a dibenzofuranyl group, and a dibenzothiofenyl group, with a benzofuranyl group, a benzothiofenyl group, a dibenzofuranyl group, and a dibenzothiofenyl group being more preferred.

Examples of the halogen atom include a fluorine atom, a chlorine atom, a bromine atom, and a iodine atom, with a fluorine atom being preferred.

Examples of the fluoroalkyl group having 1 to 20 carbon atoms include, for example, those derived from the above alkyl group having 1 to 20 carbon atoms by replacing at least one hydrogen atom, preferably 1 to 7 hydrogen atoms or all hydrogen atoms with a fluorine atom or fluorine atoms.

Preferred examples thereof are a heptafluoropropyl group, a pentafluoroethyl group, a 2,2,2-trifluoroethyl group, and a trifluoromethyl group, with a pentafluoroethyl group, a 2,2,2-trifluoroethyl group, and a trifluoromethyl group being more preferred, and a trifluoromethyl group being still more preferred.

The alkoxy group having 1 to 20 carbon atoms is represented by $—OR^X$, wherein R^X is the above alkyl group having 1 to 20 carbon atoms.

Preferred examples thereof include a t-butoxy group, a propoxy group, an ethoxy group, and a methoxy group, with an ethoxy group and a methoxy group being more preferred, and a methoxy group being still more preferred.

The fluoroalkoxy group having 1 to 20 carbon atoms is represented by $—OR^Y$, wherein R^Y is the above fluoroalkyl group having 1 to 20 carbon atoms.

Preferred examples thereof include a heptafluoropropoxy group, a pentafluoroethoxy group, a 2,2,2-trifluoroethoxy group, and a trifluoromethoxy group, with a pentafluoroethoxy group, a 2,2,2-trifluoroethoxy group, and a trifluoromethoxy group being more preferred, and a trifluoromethoxy group being still more preferred.

The aryloxy group having 6 to 50 ring carbon atoms is represented by $—OR^Z$, wherein R^Z is the above aryl group having 6 to 50 ring carbon atoms.

Preferred examples thereof include a phenyloxy group, a 1-naphthyloxy group, a 2-naphthyloxy group, a 4-biphenylyloxy group, a p-terphenyl-4-yloxy group, and a p-tolyloxy group, with a phenyloxy group and a 2-naphthyloxy group being more preferred and a phenyloxy group being still more preferred.

L^0 to L^2 in Formulae (A-0) and (B-0)

In formulae (A-0) and (B-0), L^0 to L^2 each independently represent a single bond, a substituted or unsubstituted arylene group having 6 to 50, preferably 6 to 24, and more preferably 6 to 12 ring carbon atoms, or a substituted or unsubstituted heteroarylene group having 5 to 50, preferably 5 to 10, more preferably 5 to 8, and still more preferably 5 or 6 ring atoms.

Examples of the arylene group having 6 to 50 ring carbon atoms include divalent groups derived from the aryl group having 6 to 50 ring carbon atoms mentioned above with respect to R^1 to R^4 of formulae (A-0) and (B-0) by removing one hydrogen atom.

Preferred examples thereof include a terphenyldiyl group (inclusive of isomeric groups), a biphenyldiyl group (inclusive of isomeric groups), and a phenylene group (inclusive of isomeric groups), with a biphenyldiyl group (inclusive of isomeric groups) and a phenylene group (inclusive of isomeric groups) being more preferred, an o-phenylene group, a m-phenylene group, and a p-phenylene group being still more preferred, and a p-phenylene group being further preferred.

The substituted or unsubstituted heteroarylene group having 5 to 50 ring atoms comprises at least one, preferably 1 to 3 hetero atoms which may be the same or different, such as a nitrogen atom, a sulfur atom and an oxygen atom.

Examples the heteroarylene group include divalent groups derived from the heteroaryl group having 5 to 50 ring atoms mentioned above with respect to R^1 to R^4 of formulae (A-0) and (B-0) by removing one hydrogen atom.


Preferred examples thereof include a furylene group, a thienylene group, a pyridylene group, a pyridazinylene group, a pyrimidinylene group, a pyrazinylene group, a triazinylene group, a benzofuranylene group, a benzothio-phenylene group, a dibenzofuranylene group, and a dibenzothiofenylene group, with a benzofuranylene group, a

9

benzothiophenylene group, a dibenzofuranylene group, and a dibenzothiophenylene group being more preferred.

L⁰ in formula (A-0) or (B-0) is preferably a single bond or a substituted or unsubstituted arylene group having 6 to 50 ring carbon atoms, more preferably a single bond or a group represented by any of formulae (i) and (ii), still more preferably a single bond or a group represented by formula (i). In view of obtaining a hole transporting material capable of improving emission efficiency of an organic EL device, L⁰ is further preferably a single bond. In view of obtaining a hole transporting material capable of improving lifetime of an organic EL device, L⁰ is further preferably a group represented by formula (i).

L¹ and L² in formula (A-0) or (B-0) are each preferably a single bond or a substituted or unsubstituted arylene group having 6 to 50 ring carbon atoms and more preferably a single bond or a group represented by any of formulae (i) and (ii):




In formulae (i) and (ii), * and ** each represent a bonding site.

One of * and ** is the bonding site to the nitrogen atom in formula (A-0) or (B-0) and the other is the bonding site to Ar¹, Ar², or the carbon atom of the benzene ring in the 9,9-diphenyl-9H-fluorene skeleton in formula (A-0) or (B-0).

In formulae (i) and (ii), each R and preferred examples thereof are independently the same as those described with respect to R¹ in formulae (A-0) and (B-0). Each R is a substituent which is bonded to the carbon atom of each benzene ring in formulae (i) and (ii).

In an embodiment of the invention, when more than one R occurs, groups R may be the same or different. In another embodiment of the invention, when more than one R occurs, two selected from groups R may be bonded to each other to form a ring structure.


Examples of formula (i) wherein a ring structure is formed are shown below:



wherein * and ** are as defined in formula W.

Examples of formula (ii) wherein a ring structure is formed are shown below:

10






wherein * and ** are as defined in formula).

In formulae (i) and (ii), each m independently represents an integer of 0 to 4, preferably an integer of 0 to 2, more preferably 0 or 1, and still more preferably 0.


(i) When m is 0, each benzene ring has no substituent.

(ii) The group represented by formula (i) is preferably represented by formula (i-a), and the group represented by formula (ii) is preferably represented by formula (ii-a) or (ii-b);





wherein R, m, *, and ** as defined in formulae (i) and (ii). Ar¹ and Ar² in Formulae (A-0) and (B-0)

In formulae (A-0) and (B-0), Ar¹ and Ar² each independently represent a group represented by any of formulae (a) to (c):



11

-continued



In formulae (a) to (c), examples of R^5 and R^6 and preferred examples thereof are each independently the same as those described with respect to R^1 in formulae (A-0) and (B-0). R^5 and R^6 each represent a substituent which is bonded to a carbon atom of each benzene ring in formulae (a) to (c).

When R^5 and R^6 are each plurality in number, groups R^5 and groups R^6 may be the same or different, and R^5 and R^6 may be bonded to each other to form a ring structure.



In formulae (a) to (c), m_5 and m_6 each independently represent an integer of 0 to 4, preferably an integer of 0 to 2, more preferably 0 or 1, and still more preferably 0; and

n_5 each independently represents an integer of 0 to 3, preferably an integer of 0 to 2, more preferably 0 or 1, and still more preferably 0.

When m_5 , m_6 , and n_5 are each 0, each benzene ring has no substituent.

In formulae (a) to (c), * represents a bonding site to the nitrogen atom, L^1 , or L^2 in formulae (A-0) and (B-0).

In formulae (b) and (c), one of the carbon atoms *1, *2, *3, and *4 in the following formula, i.e., one of carbon atoms at 1-, 2-, 3-, and 4-positions of the dibenzofuran group and the dibenzothiophenyl group, is bonded to the nitrogen atom, L^1 , or L^2 in formula (A-0) or (B-0).



In an embodiment of the invention, at least one selected from Ar^1 and Ar^2 is preferably a group represented by formula (b) or (c) and more preferably at least one selected from Ar^1 and Ar^2 is a group represented by any of formulae (b-1), (b-2), (c-1), and (c-2):

12

(b)

5

(c)

10

15

20

25

30

35

40

45

(b)


50

(c)


55

60


65




(b-1)



(b-2)



(c-1)




(c-2)

wherein R^5 , R^6 , n_5 , and m_6 are as defined in formulae (a) to (c); and







* represents a bonding site to the nitrogen atom, L^1 , or L^2 in formula (A-0) or (B-0).

In an embodiment of the invention, at least one selected from $-L^1-Ar^1$ and $-L^2-Ar^2$ in formulae (A-0) and (B-0) is preferably a group represented by any of formulae (a-11), (a-12), (b-11) to (b-14), and (c-11) to (c-14):






(a-11)

13
-continued



14
-continued



30 wherein R⁵, R⁶, m₅, n₅, and m₆ are as defined in formulae (a) to (c);


35 R⁷ and R⁸ are independently the same as defined with respect to R¹ in formulae (A-0) and (B-0), when R⁷ and R⁸ are each plurality in number, groups R⁷ and groups R⁸ may be the same or different, and two selected from groups R⁷ and two selected from groups R⁸ may be bonded to each other to form a ring structure;

40 m₇ and m₈ each independently represent an integer of 0 to 4, preferably an integer of 0 to 2, more preferably 0 or 1, and still more preferably 0; and

* represents a bonding site to the nitrogen atom in formula (A-0) or (B-0).

Compound (A) in an Aspect of the Invention


45 The compound (A) in an aspect of the invention is preferably a compound represented by formula (A-1) (also referred to as "compound (A-1)");



50 wherein R¹ to R⁴, n₁, m₂, k₃, k₄, L¹, L², Ar¹, and Ar² are as defined in formula (A-0).


55 In another embodiment, the compound (A) is preferably a compound represented by formula (A-2) (also referred to as "compound (A-2)");

15




wherein R^1 , R^2 , $n1$, $m2$, L^1 to L^2 , Ar^1 and Ar^2 are as defined in formula (0).

In another embodiment, the compound (A) is preferably a compound represented by formula (A-3) (also referred to as "compound (A-3)"):



wherein L^0 to L^2 , Ar^1 , and Ar^2 are as defined in formula (A-0).

In another embodiment, the compound (A) is preferably a compound represented by formula (A-4) (also referred to as "compound (A-4)"):




wherein R^1 to R^6 , $n1$, $m2$, $k4$, $n5$, $m6$, L^0 to L^2 , and Ar^2 are as defined in formulae (A-0) and (a) to (c), and X represents —O— or —S—; and

L^1 is bonded to one of the carbon atoms at 2-, 3-, and 4-positions of the dibenzofuran skeleton or the dibenzothiophene skeleton (carbon atoms *1, *2, *3, and *4) shown in the following formula:

16

(A-2)

5



Of the compound (A-4) in an embodiment of the invention, a compound represented by formula (A-5) or (A-6) (also referred to as "compound (A-5)" and "compound (A-6), respectively) is more preferred:

15

(A-5)

20

25

30

35

40


45

50


55

60

65




(A-6)



wherein R^1 to R^6 , $n1$, $m2$, $k3$, $k4$, $n5$, $m6$, L^0 to L^2 , and Ar^2 are as defined in formulae (A-0) and (a) to (c), and X represents —O— or —S—.

Of the compounds (A-5) and (A-6) in an embodiment of the invention, a compound represented by formula (A-7) or (A-8) (also referred to as "compound (A-7)" and "compound (A-8), respectively) is more preferred:


(A-7)



17

-continued

(A-8)




wherein R^1 to R^6 , n_1 , m_2 , k_3 , k_4 , n_5 , m_6 , L^0 , L^2 , and Ar^2 15
are as defined in formulae (A-0) and (a) to (c);

R^7 and preferred examples thereof are the same as defined 20
with respect to R^1 in formula (A-0), when more than one R^7
occurs, groups R^7 may be the same or different, and two
selected from groups R^7 may be bonded to each other to
form a ring structure;

m_7 represents an integer of 0 to 4, preferably an integer 25
of 0 to 2, more preferably 0 or 1, and still more preferably
0; and




X represents —O— or —S—.

Examples of the compound (A) in an aspect of the 30
invention are shown below, although not limited thereto.






18

-continued






19

-continued






20

-continued






21

-continued






22

-continued






23

-continued






24

-continued



25

-continued



26

-continued

5

10

15

20

25

30

35

40




45

50

55


60

65








27

-continued






28

-continued






29

-continued




30

-continued



31

-continued



32

-continued

5

10

15

20

25

30

35

40





45

50

55


60

65



33

-continued



34


-continued

5

10

15

20



25

30

35

40



45

50

55




60

65






35

-continued






36

-continued





37

-continued




38

-continued




39

-continued




40

-continued








41

-continued




42

-continued








43

-continued




44

-continued








45

-continued






46

-continued



47

-continued



48

-continued

5

10

15

20

25

30

35

40




45

50

55




60

65






49

-continued




50

-continued








51

-continued






52

-continued






53

-continued




54

-continued



55

-continued



5


10

15

20

56

-continued




25

30

35

40

45





50

55




60

65






57

-continued






58

-continued



59


-continued



60

-continued

5




10

15

20

25




30

35

40

45

50






55

60

65



61

-continued




62

-continued



63

-continued



5


10

15

20

64

-continued




25

30

35

40

45






50

55




60

65



65

-continued



66

-continued

5

10

15

20

25

30

35

40




45

50

55




60

65



67

-continued



68

-continued

5

10

15

20

25

30

35

40




45

50

55




60

65






69

-continued




70






-continued



71
-continued




72
-continued



73

-continued



5


10

15

20

74

-continued




25

30

35

40

45




50

55


60

65



75

-continued



5


10

15

20

76

-continued





25

30

35

40

45





50

55




60

65






77

-continued






78




-continued



79
-continued




80
-continued



81

-continued



5


10

15

20

82

-continued





25

30

35

40

45





50

55


60

65








83

-continued






84

-continued





85

-continued






86

-continued






87

-continued




88

-continued




89

-continued




90

-continued



91

-continued



5

10

15

20

25

30

35

40

45

50




55

60

65




92

-continued





93

-continued




94

-continued



95
-continued



5

10

15

20

25

30

35

40

45




50

55


60

65

96
-continued



97
-continued



5

10

15

20

25

30

35

40

45


50

55

60

65

98
-continued



5

10

15

20

25

30

35

40


45

50

55

60

65




45

50

55

60

65



45


50

55


60

65

99
-continued



100
-continued



30

35

40



45

50


55

60


65



101
-continued



102
-continued



5

10

15

20

25

30

35

40


45

50

55

60

65



40


45

50


55

60


65



103
-continued



104
-continued



5

10

15

20

25

30

35

40




45

50

55




60

65






105

-continued






106

-continued






107

-continued






108




-continued



109
-continued






110
-continued






111

-continued






112

-continued






113

-continued




114





-continued




115
-continued



116
-continued



117
-continued



5

10

15

20

25

30

35

40

45



50

55


60

65

118
-continued



119
-continued



5

10

15

20

25

30

35

40

45


50

55

60

65

120
-continued



5

10

15

20

25

30

35

40


45

50

55

60

65




45

50

55

60

65



45


50

55


60

65

121
-continued



122
-continued



30

35

40



45

50


55

60


65



123
-continued



124
-continued



5

10

15

20


25

30

35

40

45




50


55

60


65



125
-continued



126
-continued



5

10

15

20

25

30

35

40



45

50

55




60

65






127

-continued






128

-continued






129

-continued




130

-continued




131
-continued




5
10
15
20
25


132
-continued







30
35
40







45
50
55
60
65



135
-continued



136
-continued



45




50

55



60

65


137
-continued








138
-continued



139
-continued






140
-continued






141

-continued






142




-continued






143
-continued






144
-continued



145
-continued






146
-continued





147

-continued






148




-continued




149
-continued




150
-continued



151
-continued




152
-continued



30

35



40


45

50

55

60

65



35

40

45


50

55


60

65

153
-continued



154
-continued




30

35

40

45




50


55

60


65



155
-continued



156
-continued



5

10

15

20


25

30

35

40

45




50

55

60

65




50

55


60

65


157
-continued






158
-continued




159
-continued




160
-continued



161
-continued




162
-continued



30

35

40




45

50


55

60




65




163
-continued




164
-continued




165
-continued




166
-continued



167
-continued



168
-continued



5

10

15

20

25

30

35

40



45

50


55

60


65




169
-continued




170
-continued




5
10
15
20
25
30




35
40
45
50
55
60
65



171
-continued



172
-continued



5

10

15

20

25

30

35

40



45

50

55

60


65



65


173

-continued



174

-continued



5

10

15

20

25

30

35

40



45

50


55

60


65




175
-continued




176
-continued




5
10
15
20
25
30



35
40
45
50
55
60
65




177
-continued



178
-continued

5




10

15

20

25




30

35


40

45




50

55







60

65



179


-continued



180

-continued

5




10

15

20

25

30




35

40

45


50




55

60


65



181
-continued







182
-continued



183

-continued




184

-continued

5

10

15



20

25

30

35

40

45

50


55

60


65

Of the above, the compound (A) is preferably any of the following compounds (H-A1) to (H-A10):

(H-A1)




(H-A2)




185
-continued

(H-A3)




186
-continued


(H-A5)



(H-A4)




(H-A6)



187
-continued

(H-A7)



5

10

15

20

25


30

35

188

-continued

(H-A9)



5

10

15

20

25


30

35

40

(H-A10)

(H-A8)




45

50

55


60



Compound (B) in an Aspect of the Invention


65 The compound (B) in an aspect of the invention is preferably a compound represented by formula (B-1) (also referred to as "compound (B-1)");

189



wherein R^1 to R^4 , n_1 , m_2 , k_3 , k_4 , L^1 , L^2 , Ar^1 , and Ar^2 as defined in formula (B-0)

In another embodiment, the compound (B) is preferably a compound represented by formula (B-2) (also referred to as “compound (B-2)”):




wherein R^1 to R^4 , n_1 , m_2 , k_3 , k_4 , L^1 , L^2 , Ar^1 , and Ar^2 are as defined in formula (B-0);

R^8 and preferred examples thereof are the same as defined with respect to Win formula (B-0), when more than one R^8 occurs, groups R^8 may be the same or different, and two selected from groups R^8 may be bonded to each other to form a ring structure; and

m_8 represents an integer of 0 to 4, preferably an integer of 0 to 2, more preferably 0 or 1, and still more preferably 0.


In another embodiment, the compound (B) is preferably a compound represented by formula (B-3) (also referred to as “compound (B-3)”);



wherein R^1 , R^2 , n_1 , m_2 , L^0 to L^2 , Ar^1 , and Ar^2 are as defined in formula (B-0).


190

In another embodiment, the compound (B) is preferably a compound represented by formula (B-4) (also referred to as “compound (B-4)”):



wherein L^0 to L^2 , Ar^1 , and Ar^2 are as defined in formula (B-0).


In another embodiment, the compound (B) is preferably a compound represented by formula (B-5) (also referred to as “compound (B-5)”):



wherein R^1 to R^2 , n_1 , m_2 , k_3 , k_4 , n_5 , m_6 , L^0 to L^2 , and Ar^2 are as defined in formulae (B-0) and (a) to (c);


X represents $-O-$ or $-S-$; and

L^1 is bonded to one of the carbon atoms at 1-, 2-, 3-, and 4-positions of the dibenzofuran skeleton or the dibenzothiophene skeleton (carbon atoms *1, *2, *3, and *4) as shown in the following formula.




Of the compound (B-5) in an embodiment of the invention, a compound represented by formula (B-6) or (B-7) (also referred to as “compound (B-6)” and “compound (B-7)” respectively) is more preferred:

191



(B-6)




(B-7)


wherein R^1 to R^6 , n_1 , m_2 , k_3 , k_4 , n_5 , m_6 , L^0 to L^2 , and Ar^2 are as defined in formulae (B-0) and (a) to (c); and

X represents —O— or —S—.

Of the compounds (B-6) and (B-7) in an embodiment of the invention, a compound represented by formula (B-8) or (B-9) (also referred to as “compound (B-8)” and “compound (B-9)” respectively) is more preferred:



(B-8)



(B-9)

192

wherein R^1 to R^6 , n_1 , m_2 , k_3 , k_4 , n_5 , m_6 , L^0 , L^2 , and Ar^2 are as defined in formulae (B-0) and (a) to (c);

R^7 and preferred examples thereof are the same as defined with respect to R^1 in formula (B-0), when more than one R^7 occurs, groups R^7 may be the same or different, and two selected from groups R^7 may be bonded to each other to form a ring structure;

m_7 represents an integer of 0 to 4, preferably an integer of 0 to 2, more preferably 0 or 1, and still more preferably 0; and

X represents —O— or —S—.


Examples of the compound (B) in an aspect of the invention are shown below, although not limited thereto.

15

20




25

30






(B-8)

193
-continued






194
-continued






195

-continued






196

-continued






65

197
-continued




198
-continued






199

-continued




200





-continued




201
-continued






202
-continued



203
-continued






204
-continued






205

-continued




206

-continued



207
-continued




5

10

15

20

208
-continued




25

30

35

40





45

50

55




60

65







209

-continued




210

-continued



211

-continued



5


10

15

20

212

-continued




25

30

35

40




45

50




55

60


65



213
-continued



214
-continued



15

20

25

30

35

40


45

50


55

60

65



215
-continued



5


10

15

20

25

216
-continued




30

35

40

45





50


55

60


65



217
-continued






218
-continued






219

-continued



220

-continued



5

10

15

20

25

30

35

40

45




50

55




60

65

221
-continued






222
-continued






223

-continued






224

-continued





225

-continued






226

-continued






227

-continued



228

-continued



5

10

15

20

25

30

35

40

45

50


55

60

65

229

-continued



5

10

15

20

25

30

35

40

45

50




55

60

65


230

-continued



231

-continued



5

10


15

20

25

232

-continued



30

35

40



45

50

55


60

65






233

-continued






234




-continued



235
-continued




236
-continued



65






237

-continued






238

-continued





239

-continued




240

-continued



241

-continued



5

10

15

20

25

30

35

40

45

50


55

60

65

242

-continued



5

10

15

20

25

30

35

40


45

50

55

60

65




45

50

55

60

65



45

50


55

60

65

243

-continued



5


10

15

20

244

-continued




25

30

35

40





45

50

55


60

65







245

-continued




246

-continued



247
-continued




5

10

15

20




25

30

35

40




50

55

60

65

248
-continued




5

10

15


20



25

30


35



40

45

50






55

60

65



249

-continued




250


-continued



251
-continued







252
-continued







253

-continued



254

-continued



5

10

15

20

25

30

35

40

45

50





55

60

65





255

-continued







256





-continued



257
-continued







258
-continued







259

-continued




260

-continued



261

-continued



5


10

15

20

262

-continued




25

30

35

40

45





50

55


60

65



263

-continued




5

10

15

20




25

30

35

40

45



50


55

60

65

264

-continued




5

10

15

20




25

30

35

40

45



50




55

60

65





265

-continued



266

-continued



5

10

15

20

25

30

35

40

45

50





55

60

65





267

-continued







268

-continued







269

-continued




270


-continued



271
-continued







272
-continued







273

-continued




274






-continued




275
-continued



276
-continued



277
-continued




5

10

15

20

278
-continued






25

30

35

40

45




50

55




60

65







279

-continued




280

-continued



281



5


10

15

20

282

-continued




25

30

35

40






45

50

55




60

65






283

-continued






284

-continued






285

-continued



286

-continued



35

40

45

50


55

60

65

287

-continued



5

10


15

20

25

288

-continued




25

30

35

40

45





50

55




60

65






289

-continued



290


-continued



65


291

-continued




292

-continued



293
-continued



5

10

15

20

25

30

35

40

45



50

55


60

65

294
-continued



295
-continued



5

10

15

20

25

30

35

40

45


50

55

60

65

296
-continued



5

10

15

20

25

30

35

40


45

50

55

60

65




45

50

55

60

65



45


50

55




60

65

297
-continued




298
-continued




299

-continued




300





-continued






301
-continued






302
-continued






303
-continued






304
-continued



305
-continued






306
-continued






307

-continued






308

-continued






309

-continued




310

-continued



311
-continued



5

10

15

20

25

30

35

40

45



50

55


60

65

312
-continued



313
-continued



5

10

15


20

25

30

35

40



45


50

55

60

65

314
-continued



5

10

15


20

25

30

35

40



45


50

55


60

65

315
-continued




316
-continued



30

35

40



45


50

55




60

65




317
-continued






318
-continued



319
-continued




320
-continued








321

-continued




322

-continued








323

-continued






324

-continued









325

-continued







326





-continued






327
-continued







328
-continued



329
-continued







330
-continued







331

-continued




332

-continued



333

-continued



5


10

15

20

334

-continued




25

30

35

40

45






50





55

60



65




335
-continued



336
-continued



337
-continued



5


10

15

20

25

338
-continued



30

35

40



45

50




55

60


65



339
-continued



340
-continued



25

30

35

40


45

50


55

60


65




341
-continued






342
-continued



343
-continued






344
-continued






345

-continued




346


-continued



347
-continued




348
-continued







349

-continued




350

-continued




351

-continued



352

-continued



5

10

15

20

25

30

35

40



45

50

55




60

65






353

-continued




354

-continued



355

-continued



5


10

15

20

356

-continued






25

30

35

40

45




50

55


60

65



357

-continued



5


10

15

20

358

-continued




25

30

35

40

45





50

55


60

65



359

-continued



5


10

15

20

360

-continued





25

30

35

40

45





50

55



60

65





361

-continued



362


-continued




Of the above, the compound (B) is preferably any of the following compounds (H-B1) to (H-B10):

45

(H-B1)









50




363
-continued

364
-continued




365


-continued



(H-B8)



(H-B9)



(H-B10)

Material for Organic EL Devices

The material for organic EL devices in an aspect of the invention comprises the compound (A), the compound (B), and both the compounds (A) and the compound (B). The material for organic EL devices preferably comprises a compound selected from the compounds (A-1) to (A-8) and the compounds (B-1) to (B-9).

The following description with respect to the compound (A) is equally applicable to the compounds (A-1) to (A-8),

366

and the following description with respect to the compound (B) is equally applicable to the compounds (B-1) to (B-9).

The material for organic EL devices in an aspect of the invention is useful as a material for producing an organic EL device, for example, as a material for at least one organic thin film layer disposed between an anode and a cathode, particularly as a material for a hole transporting layer or a hole injecting layer.

Organic EL Device

The organic EL device in an aspect of the invention will be described below.

Representative device structures (1) to (13) are shown below, although not limited thereto. The device structure (8) is preferably used.

(1) anode/light emitting layer/cathode;

(2) anode/hole injecting layer/light emitting layer/cathode;

(3) anode/light emitting layer/electron injecting layer/cathode;

(4) anode/hole injecting layer/light emitting layer/electron injecting layer/cathode;

(5) anode/organic semiconductor layer/light emitting layer/cathode;

(6) anode/organic semiconductor layer/electron blocking layer/light emitting layer/cathode;

(7) anode/organic semiconductor layer/light emitting layer/adhesion improving layer/cathode;

(8) anode/hole injecting layer/hole transporting layer/light emitting layer/(electron transporting layer) electron injecting layer/cathode;

(9) anode/insulating layer/light emitting layer/insulating layer/cathode;

(10) anode/inorganic semiconductor layer/insulating layer/light emitting layer/insulating layer/cathode;

(11) anode/organic semiconductor layer/insulating layer/light emitting layer/insulating layer/cathode;

(12) anode/insulating layer/hole injecting layer/hole transporting layer/light emitting layer/insulating layer/cathode; and

(13) anode/insulating layer/hole injecting layer/hole transporting layer/light emitting layer/(electron transporting layer) electron injecting layer/cathode.

A schematic structure of an example of the organic EL device in an aspect of the invention is shown in FIG. 1, wherein the organic EL device 1 comprises a substrate 2, an anode 3, a cathode 4, and an emission unit 10 disposed between the anode 3 and the cathode 4. The emission unit 10 comprises a light emitting layer 5 which comprises a host material and a dopant (light emitting material). A hole injecting/transporting layer 6, etc. may be disposed between the light emitting layer 5 and the anode 3, and an electron injecting/transporting layer 7, etc. may be disposed between the light emitting layer 5 and the cathode 4. An electron blocking layer may be disposed on the anode 3 side of the light emitting layer 5, and a hole blocking layer may be disposed on the cathode 4 side of the light emitting layer 5. With these blocking layers, electrons and holes are confined in the light emitting layer 5 to increase the exciton generation in the light emitting layer 5.

The organic EL device in an aspect of the invention comprises an anode, a cathode, and at least one organic thin film layer between the cathode and the anode. The at least one organic thin film layer comprises a light emitting layer and at least one layer of the at least one organic thin film layer comprise at least one selected from the compound (A) represented by formula (A-0) and the compound (B) represented by formula (B-0).

Examples of the organic thin film layer comprising the compound (A) and/or the compound (B) include an anode-side organic thin film layer formed between an anode and a light emitting layer (hole transporting layer, hole injecting layer, etc.), a light emitting layer, a cathode-side organic thin film layer formed between a cathode and a light emitting layer (electron transporting layer, electron injecting layer, etc.), a space layer, and a blocking layer, although not limited thereto.

The compound (A) and/or the compound (B) may be used in any of the organic thin film layers of an organic EL device. In view of driving at a lower voltage, the compound (A) and/or the compound (B) are preferably used in a hole injecting layer or a hole transporting layer, more preferably used in a hole transporting layer.

Namely, the organic EL device in an aspect of the invention is more preferably an organic EL device wherein the at least one organic thin film layer comprises a hole injecting layer comprising the compound (A) and/or the compound (B), a hole transporting layer comprising the compound (A) and/or the compound (B), or both layers.

The content of the compound (A) in the organic thin film layer, preferably in a hole injecting layer or a hole transporting layer, is preferably 30 to 100 mol %, more preferably 50 to 100 mol %, still more preferably 80 to 100 mol %, and further preferably 95 to 100 mol % each based on the total molar amount (100 mol %) of the components in the organic thin film layer.

Similarly, the content of the compound (B) in the organic thin film layer, preferably in a hole injecting layer or a hole transporting layer, is preferably 30 to 100 mol %, more preferably 50 to 100 mol %, still more preferably 80 to 100 mol %, and further preferably 95 to 100 mol % each based on the total molar amount (100 mol %) of the components in the organic thin film layer.

Substrate

The substrate is a support for the emitting device and made of, for example, glass, quartz, and plastics. The substrate may be a flexible substrate, for example, a plastic substrate made of, for example, polycarbonate, polyarylate, polyether sulfone, polypropylene, polyester, polyvinyl fluoride, and polyvinyl chloride. An inorganic deposition film is also usable.

Anode

The anode is formed on the substrate preferably from a metal, an alloy, an electrically conductive compound, and a mixture thereof, each having a large work function, for example, 4.5 eV or more. Examples of the material for the anode include indium oxide-tin oxide (ITO: indium tin oxide), indium oxide-tin oxide doped with silicon or silicon oxide, indium oxide-zinc oxide, indium oxide doped with tungsten oxide and zinc oxide, and graphene. In addition, gold (Au), platinum (Pt), nickel (Ni), tungsten (W), chromium (Cr), molybdenum (Mo), iron (Fe), cobalt (Co), copper (Cu), palladium (Pd), titanium (Ti), and a metal nitride (for example, titanium nitride) are also usable.

These materials are made into a film generally by a sputtering method. For example, a film of indium oxide-zinc oxide is formed by sputtering an indium oxide target doped with 1 to 10% by mass of zinc oxide, and a film of indium oxide doped with tungsten oxide and zinc oxide is formed by sputtering an indium oxide target doped with 0.5 to 5% by mass of tungsten oxide and 0.1 to 1% by mass of zinc oxide. In addition, a vacuum vapor deposition method, a coating method, an inkjet method, and a spin coating method are usable.

A hole injecting layer to be formed in contact with the anode is formed from a composite material which is capable of easily injecting holes independently of the work function of the anode. Therefore a material, for example, a metal, an alloy, an electroconductive compound, a mixture thereof, and a group 1 element and a group 2 element of the periodic table are usable as the electrode material.

A material having a small work function, for example, the group 1 element and the group 2 element of the periodic table, i.e., an alkali metal, such as lithium (Li) and cesium (Cs), an alkaline earth metal, such as magnesium (Mg), calcium (Ca), and strontium (Sr), and an alloy thereof, such as MgAg and AlLi, are also usable. In addition, a rare earth metal, such as europium (Eu) and ytterbium (Yb), and an alloy thereof are also usable. The alkali metal, the alkaline earth metal, and the alloy thereof can be made into the anode by a vacuum vapor deposition or a sputtering method. When a silver paste, etc. is used, a coating method and an inkjet method are usable.

Hole Injecting Layer

The hole injecting layer comprises a highly hole-transporting material.

The hole injecting layer of the organic EL device in an aspect of the invention preferably comprises at least one selected from the compound (A) and the compound (B) in an aspect of the invention.

Such a hole injecting layer may comprise at least one selected from the compound (A) and the compound (B), or may comprise at least one selected from the compound (A) and the compound (B) in combination with the following compound.

Examples of the highly hole-transporting material include molybdenum oxide, titanium oxide, vanadium oxide, rhenium oxide, ruthenium oxide, chromium oxide, zirconium oxide, hafnium oxide, tantalum oxide, silver oxide, tungsten oxide, and manganese oxide.

The following low molecular aromatic amine compound is also usable: 4,4',4''-tris(N,N-diphenylamino)triphenylamine (TDATA), 4,4',4''-tris[N-(3-methylphenyl)-N-phenylamino]triphenylamine (MTDATA), 4,4'-bis[N-(4-diphenylaminophenyl)-N-phenylamino]biphenyl (DPAB), 4,4'-bis[N-(4-[N'-(3-methylphenyl)-N'-phenylamino]phenyl)-N-phenylamino]biphenyl (DNTPD), 1,3,5-tris[N-(4-diphenylaminophenyl)-N-phenylamino]benzene (DPA3B), 3-[N-(9-phenylcarbazole-3-yl)-N-phenylamino]-9-phenylcarbazole (PCzPCA1), 3,6-bis[N-(9-phenylcarbazole-3-yl)-N-phenylamino]-9-phenylcarbazole (PCzPCA2), and 3-[N-(1-naphthyl)-N-(9-phenylcarbazole-3-yl)amino]-9-phenylcarbazole (PCzPCN1).

A polymeric compound, such as an oligomer, a dendrimer, a polymer, is also usable. Examples thereof include poly(N-vinylcarbazole) (PVK), poly(4-vinyltriphenylamine) (PVTPA), poly[N-(4-{N'-(4-(4-diphenylamino)phenyl)phenyl-N'-phenylamino}phenyl)methacrylamide] (PTPDMA), and poly[N,N'-bis(4-butylphenyl)-N,N'-bis(phenyl)benzidine] (Poly-TPD). An acid-added polymeric compound, such as poly(3,4-ethylenedioxythiophene)/poly(styrenesulfonic acid) (PEDOT/PSS) and polyaluminum/poly(styrenesulfonic acid) (PAni/PSS), is also usable.

Hole Transporting Layer

The hole transporting layer comprises a highly hole-transporting material.

The hole transporting layer of the organic EL device in an aspect of the invention preferably comprises at least one selected from the compound (A) and the compound (B) in an aspect of the invention.

Such a hole transporting layer may comprise at least one selected from the compound (A) and the compound (B), or may comprise at least one selected from the compound (A) and the compound (B) in combination with the following compound.

The hole transporting layer may contain an aromatic amine compound, a carbazole derivative, an anthracene derivative, etc., for examples, an aromatic amine compound, such as 4,4'-bis[N-(1-naphthyl)-N-phenylamino]biphenyl (NPB), N,N'-bis(3-methylphenyl)-N,N'-diphenyl-[1,1'-biphenyl]-4,4'-diamine (TPD), 4-phenyl-4'-(9-phenylfluorene-9-yl)triphenylamine (BAFLP), 4,4'-bis[N-(9,9-dimethylfluorene-2-yl)-N-phenylamino]biphenyl (DFLDPBi), 4,4',4''-tris(N,N-diphenylamino)triphenylamine (TDATA), 4,4',4''-tris[N-(3-methylphenyl)-N-phenylamino]triphenylamine (MTDATA), and 4,4'-bis[N-(spiro-9,9'-bifluorene-2-yl)-N-phenylamino]biphenyl (BSPB). The above compounds have a hole mobility of mainly 10^{-6} cm²/Vs or more.


In addition, the hole transporting layer may contain a carbazole derivative, such as CBP, CzPA, and PCzPA, an anthracene derivative, such as t-BuDNA, DNA, and DPAnH, and a polymeric compound, such as poly(N-vinyl-carbazole) (PVK) and poly(4-vinyltriphenylamine) (PVTPA).

Other materials are also usable if their hole transporting ability is higher than their electron transporting ability. The layer comprising a highly hole-transporting material may be a single layer or a laminate of two or more layers each comprising the material mentioned above. For example, the hole transporting layer may be made into a two-layered structure of a first hole transporting layer (anode side) and a second hole transporting layer (light emitting layer side).

In such a two-layered structure, the compound (A) and/or the compound (B) in an aspect of the invention may be used in either of the first hole transporting layer and the second hole transporting layer and preferably used in the second hole transporting layer.

In the organic EL device in an aspect of the invention, a layer comprising an electron-accepting compound (acceptor material) may be formed on the anode-side of the hole transporting layer or the first hole transporting layer, because it is expected that the driving voltage is lowered and the production cost is reduced.

A compound represented by formula (EA) is preferably used as the acceptor compound:



wherein R³¹¹ to R³¹⁶ may be the same or different and each independently represent a cyano group, —CONH₂, a carboxyl group, or —COOR³¹⁷ wherein R³¹⁷ represents an alkyl group having 1 to 20 carbon atoms or a cycloalkyl group having 3 to 20 carbon atoms; and R³¹¹ and R³¹², R³¹³

and R³¹⁴, or R³¹⁵ and R³¹⁶ may be bonded to each other to form a group represented by —CO—O—CO—.

Examples of alkyl group for R³¹⁷ include a methyl group, an ethyl group, a n-propyl group, an isopropyl group, a n-butyl group, an isobutyl group, and a t-butyl group. Examples of cycloalkyl group include a cyclopentyl group and a cyclohexyl group.

The thickness of the layer comprising the acceptor compound is preferably 5 to 20 nm, although not particularly limited thereto.

Guest Material of Light Emitting Layer

The light emitting layer comprises a highly light-emitting material and may be formed from a various kind of materials. For example, a fluorescent emitting compound and a phosphorescent emitting compound are usable as the highly light-emitting material. The fluorescent emitting compound is a compound capable of emitting light from a singlet excited state, and the phosphorescent emitting compound is a compound capable of emitting light from a triplet excited state.

Examples of blue fluorescent emitting material for use in the light emitting layer include a pyrene derivative, a styrylamine derivative, a chrysene derivative, a fluoranthene derivative, a fluorene derivative, a diamine derivative, and a triarylamine derivative, such as N,N'-bis[4-(9H-carbazole-9-yl)phenyl]-N,N'-diphenylstilbene-4,4'-diamine (YGA2S), 4-(9H-carbazole-9-yl)-4'-(10-phenyl-9-anthryl)triphenylamine (YGAPA), and 4-(10-phenyl-9-anthryl)-4'-(9-phenyl-9H-carbazole-3-yl)triphenylamine (PCBAPA).

Examples of green fluorescent emitting material for use in the light emitting layer include an aromatic amine derivative, such as N-(9,10-diphenyl-2-anthryl)-N,9-diphenyl-9H-carbazole-3-amine (2PCAPA), N-[9,10-bis(1,1'-biphenyl-2-yl)-2-anthryl]-N,9-diphenyl-9H-carbazole-3-amine (2PCABPhA), N-(9,10-diphenyl-2-anthryl)-N,N',N'-triphenyl-1,4-phenylenediamine (2DPAPA), N-(9,10-bis(1,1'-biphenyl-2-yl)-2-anthryl)-N,N',N'-triphenyl-1,4-phenylenediamine (2DPABPhA), N-[9,10-bis(1,1'-biphenyl-2-yl)]-N-[4-(9H-carbazole-9-yl)phenyl]-N-phenylanthracene-2-amine (2YGABPhA), and N,N,9-triphenylanthracene-9-amine (DPhAPhA).

Examples of red fluorescent emitting material for use in the light emitting layer include a tetracene derivative and a diamine derivative, such as N,N,N',N'-tetrakis(4-methylphenyl)tetracene-5,11-diamine (p-mPhTD) and 7,14-diphenyl-N,N,N',N'-tetrakis(4-methylphenyl)acenaphtho[1,2-a]fluoranthene-3,10-diamine (p-mPhAFD).

Examples of blue phosphorescent emitting material for use in the light emitting layer include a metal complex, such as an iridium complex, an osmium complex, and a platinum complex. Examples thereof include bis[2-(4',6'-difluorophenyl)pyridinato-N,C2']iridium(III) tetrakis(1-pyrazolyl)borate (FIr₆), bis[2-(4',6'-difluorophenyl)pyridinato-N,C2']iridium(III) picolinato (FIr_{pic}), bis[2-(3',5'-bistrifluoromethylphenyl)pyridinato-N,C2']iridium(III) picolinato (Ir(CF₃ppy)₂(pic)), and bis[2-(4',6'-difluorophenyl)pyridinato-N,C2']iridium(III) acetylacetonato (FIracac).

Examples of green phosphorescent emitting material for use in the light emitting layer include an iridium complex, such as tris(2-phenylpyridinato-N, C2')iridium(III) (Ir(ppy)₃), bis(2-phenylpyridinato-N, C2')iridium(III) acetylacetonato (Ir(ppy)₂(acac)), bis(1,2-diphenyl-1H-benzimidazolato)iridium(III) acetylacetonato (Ir(pbi)₂(acac)), and bis(benzo[h]quinolinato)iridium(III) acetylacetonato (Ir(bzq)₂(acac)).

Examples of red phosphorescent emitting material for use in the light emitting layer include a metal complex, such as

an iridium complex, a platinum complex, a terbium complex, and a europium complex. Examples thereof include an organometallic complex, such as bis[2-(2'-benzo[4,5- α]thienyl)pyridinato-N,C3']iridium(III) acetylacetonato (Ir(btp)₂ (acac)), bis(1-phenylisoquinolino-N,C2')iridium(III) acetylacetonato (Ir(piq)₂(acac)), (acetylacetonato)bis[2,3-bis(4-fluorophenyl)quinoxalino]iridium(III) (Ir(Fdpq)₂ (acac)), and 2,3,7,8,12,13,17,18-octaethyl-21H,23H-porphyrin platinum(II) (PtOEP).

The following rare earth metal complex, such as tris(acetylacetonato) (monophenanthroline)terbium(III) (Tb(acac)₃(Phen)), tris(1,3-diphenyl-1,3-propanedionato) (monophenanthroline)europium(III) (Eu(DBM)₃(Phen)), and tris[1-(2-thenoyl)-3,3,3-trifluoroacetato](monophenanthroline)europium(III) (Eu(TTA)₃(Phen)), emits light from the rare earth metal ion (electron transition between different multiple states), and therefore, usable as a phosphorescent emitting compound.

Host Material for Light Emitting Layer

The light emitting layer may be formed by dispersing the highly light-emitting material (guest material) mentioned above in another material (host material). The material in which the highly light-emitting material is to be dispersed may be selected from various kinds of materials and is preferably a material having a lowest unoccupied molecular orbital level (LUMO level) higher than that of the highly light-emitting material and a highest occupied molecular orbital level (HOMO level) lower than that of the highly light-emitting material.

The material in which the highly light-emitting material is to be dispersed may include, for example,

- (1) a metal complex, such as an aluminum complex, a beryllium complex, and a zinc complex;
- (2) a heterocyclic compound; such as an oxadiazole derivative, a benzimidazole derivative, and a phenanthroline derivative;
- (3) a fused aromatic compound, such as a carbazole derivative, an anthracene derivative, a phenanthrene derivative, a pyrene derivative, and a chrysene derivative; and
- (4) an aromatic amine compound, such as a triarylamine derivative and a fused aromatic polycyclic amine derivative.

Examples thereof include:

a metal complex, such as tris(8-quinolinolato)aluminum(III) (Alq), tris(4-methyl-8-quinolinolato)aluminum(III) (Almq₃), bis(10-hydroxybenzo[h]quinolinolato)beryllium(II) (BeBq₂), bis(2-methyl-8-quinolinolato)(4-phenylphenolato)aluminum(III) (BAAlq), bis(8-quinolinolato)zinc(II) (Znq), bis[2-(2-benzoxazolyl)phenolato]zinc(III) ((ZnPBO), and bis[2-(2-benzothiazolyl)phenolato]zinc(II) (ZnBTZ);

a heterocyclic compound, such as 2-(4-biphenyl)-5-(4-tert-butylphenyl)-1,3,4-oxadiazole (PBD), 1,3-bis[5-(p-tert-butylphenyl)-1,3,4-oxadiazole-2-yl]benzene (OXD-7), 3-(4-biphenyl)-4-phenyl-5-(4-tert-butylphenyl)-1,2,4-triazole (TAZ), 2,2',2''-(1,3,5-benzenetriyl)tris(1-phenyl-1H-benzimidazole) (TPBI), bathophenanthroline (BPhen), and bathocuproin (BCP);

a fused aromatic compound, such as 9-[4-(10-phenyl-9-anthryl)phenyl]-9H-carbazole (CzPA), 3,6-diphenyl-9-[4-(10-phenyl-9-anthryl)phenyl]-9H-carbazole (DPCzPA), 9,10-bis(3,5-diphenylphenyl)anthracene (DPPA), 9,10-di(2-naphthyl)anthracene (DNA), 2-tert-butyl-9,10-di(2-naphthyl)anthracene (t-BuDNA), 9,9'-bianthryl (BANT), 9,9'-(stilbene-3,3'-diyl)diphenanthrene (DPNS), 9,9'-(stilbene-4,4'-diyl)diphenanthrene (DPNS2), 3,3',3''-(benzene-1,3,5-triyl)tripryrene (TPB3), 9,10-diphenylanthracene (DPAnth), and 6,12-dimethoxy-5,11-diphenylchrysene; and

an aromatic amine compound, such as N,N-diphenyl-9-[4-(10-phenyl-9-anthryl)phenyl]-9H-carbazole-3-amine (CzA1PA), 4-(10-phenyl-9-anthryl)triphenylamine (DPhPA), N,9-diphenyl-N-[4-(10-phenyl-9-anthryl)phenyl]-9H-carbazole-3-amine (PCAPA), N,9-diphenyl-N-[4-(10-phenyl-9-anthryl)phenyl]phenyl]-9H-carbazole-3-amine (PCAPBA), N-(9,10-diphenyl-2-anthryl)-N,9-diphenyl-9H-carbazole-3-amine (2PCAPA), NPB (or α -NPD), TPD, DFLDPBi, and BSPB.

- 10 The material (host material) for dispersing the highly light-emitting material (guest material) may be used alone or in combination of two or more.

Electron Transporting Layer

The electron transporting layer comprises a highly electron-transporting material, for example,

- 15 (1) a metal complex, such as an aluminum complex, a beryllium complex, and a zinc complex;
- (2) a heteroaromatic compound, such as an imidazole derivative, a benzimidazole derivative, an azine derivative, a carbazole derivative, and a phenanthroline derivative; and
- 20 (3) a polymeric compound.

Examples of the low molecular organic compound include a metal complex, such as Alq, tris(4-methyl-8-quinolinolato)aluminum (Almq₃), bis(10-hydroxybenzo[h]quinolinolato)beryllium (BeBq₂), BAN, Znq, ZnPBO, and ZnBTZ; and a hetero aromatic compound, such as 2-(4-biphenyl)-5-(4-tert-butylphenyl)-1,3,4-oxadiazole (PBD), 1,3-bis[5-(p-tert-butylphenyl)-1,3,4-oxadiazole-2-yl]benzene (OXD-7), 3-(4-tert-butylphenyl)-4-phenyl-5-(4-biphenyl)-1,2,4-triazole (TAZ), 3-(4-tert-butylphenyl)-4-(4-ethylphenyl)-5-(4-biphenyl)-1,2,4-triazole (p-EtTAZ), bathophenanthroline (BPhen), bathocuproine (BCP), and 4,4'-bis(5-methylbenzoxazole-2-yl)stilbene (BzOs).

The above compounds have an electron mobility of mainly 10⁻⁶ cm²/Vs or more. Other materials are also usable in the electron transporting layer if their electron transporting ability is higher than their hole transporting ability. The electron transporting layer may be a single layer or a laminate of two or more layers each comprising the material mentioned above.

- 40 A polymeric compound is also usable in the electron transporting layer. Examples thereof include poly[(9,9-dihexylfluorene-2,7-diyl)-co-(pyridine-3,5-diyl)] (PF-Py), and poly[(9,9-dioctylfluorene-2,7-diyl)-co-(2,2'-bipyridine-6,6'-diyl)] (PF-BPy).

Electron Injecting Layer

The electron injecting layer comprises a highly electron-injecting material, for example, an alkali metal, an alkaline earth metal, and a compound of these metals, such as lithium (Li), cesium (Cs), calcium (Ca), lithium fluoride (LiF), cesium fluoride (CsF), calcium fluoride (CaF₂), and lithium oxide (LiOx). In addition, an electron transporting material which is incorporated with an alkali metal, an alkaline earth metal or a compound thereof, for example, Alq doped with magnesium (Mg), is also usable. By using such a material, electrons are efficiently injected from the cathode.

- 50 A composite material obtained by mixing an organic compound and an electron donor is also usable in the electron injecting layer. Such a composite material is excellent in the electron injecting ability and the electron transporting ability, because the electron donor donates electrons to the organic compound. The organic compound is preferably a material excellent in transporting the received electrons. Examples thereof are the materials for the electron transporting layer mentioned above, such as the metal complex and the aromatic heterocyclic compound. Any material capable of giving its electron to another organic compound

is usable as the electron donor. Preferred examples thereof are an alkali metal, an alkaline earth metal, and a rare earth metal, such as lithium, cesium, magnesium, calcium, erbium, and ytterbium; an alkali metal oxide and an alkaline earth metal oxide, such as, lithium oxide, calcium oxide, and barium oxide; a Lewis base, such as magnesium oxide; and an organic compound, such as tetrathiafulvalene (TTF).

Cathode

The cathode is formed preferably from a metal, an alloy, an electrically conductive compound, and a mixture thereof, each having a small work function, for example, a work function of 3.8 eV or less. Examples of the material for the cathode include a metal of the group 1 or 2 of the periodic table, for example, an alkali metal, such as lithium (Li) and cesium (Cs), an alkaline earth metal, such as magnesium (Mg), an alloy containing these metals (for example, MgAg and AlLi), a rare earth metal, such as europium (Eu) and ytterbium (Yb), and an alloy containing a rare earth metal.

The alkali metal, the alkaline earth metal, and the alloy thereof can be made into the cathode by a vacuum vapor deposition or a sputtering method. When a silver paste, etc. is used, a coating method and an inkjet method are usable.

When the electron injecting layer is formed, the material for the cathode can be selected independently from the work function and various electroconductive materials, such as Al, Ag, ITO, graphene, and indium oxide-tin oxide doped with silicon or silicon oxide, are usable. These electroconductive materials are made into films by a sputtering method, an inkjet method, and a spin coating method.

Each layer of the organic EL device is formed by a dry film-forming method, such as vacuum vapor deposition, sputtering, plasma, and ion plating, and a wet film-forming method, such as spin coating, dip coating, and flow coating.

In the wet film-forming method, the material for each layer is dissolved or dispersed in a suitable solvent, such as ethanol, chloroform, tetrahydrofuran, and dioxane, and then the obtained solution or dispersion is made into a film. To improve the film-forming properties and prevent pin holes on the film, the solution and the dispersion may include a resin or an additive. Examples of the resin include an insulating resin and a copolymer thereof, such as polystyrene, polycarbonate, polyarylate, polyester, polyamide, polyurethane, polysulfone, polymethyl methacrylate, polymethyl acrylate, and cellulose; and a photoconductive resin, such as poly-N-vinylcarbazole and polysilane; and an electroconductive resin, such as polythiophene and polypyrrole. Examples of the additive include an antioxidant, an ultraviolet absorber, and a plasticizer.

The thickness of each layer is not particularly limited and selected so as to obtain a good device performance. If extremely thick, a large applied voltage is needed to obtain a desired emission output, thereby reducing the efficiency. If extremely thin, pinholes occur on the film to make it difficult to obtain a sufficient luminance even when applying an electric field. The thickness is generally 5 nm to 10 μm and preferably 10 nm to 0.2 μm.

The thickness of the light emitting layer is, but not particularly limited to, preferably 5 to 100 nm, more preferably 7 to 70 nm, and still more preferably 10 to 50 nm.

The thickness of the hole transporting layer is preferably 10 to 300 nm.

When the hole transporting layer is made into a two-layered structure as described above, the thickness of the first hole transporting layer is preferably 50 to 300 nm, more preferably 50 to 250 nm, still more preferably 50 to 200 nm, and further preferably 50 to 150 nm, and the thickness of the second hole transporting layer is preferably 5 to 100 nm,

more preferably 5 to 50 nm, still more preferably 5 to 30 nm, and further preferably 5 to 20 nm, although not limited thereto.

Electronic Equipment

The electronic equipment in an aspect of the invention comprises the organic EL device in an aspect of the invention mentioned above.

Examples of the electronic equipment include display parts, such as organic EL panel module; display devices of television sets, mobile phones, personal computer, etc.; and light emitting sources of lighting equipment and vehicle lighting equipment.

EXAMPLES

The present invention will be described in more detail with reference to the examples and comparative examples. However, it should be noted that the scope of the invention is not limited thereto.

The compounds recited in the claims of this application can be synthesized by referring to the following synthetic reactions while using a known synthetic reaction and a starting material in accordance with the target compound.


Intermediates Commonly Used in Synthesis of Compounds (A) and (B)

Intermediate Synthesis 1-1 (Synthesis of Intermediate (1-1))

Under an argon atmosphere, into a mixture of 28.3 g (100.0 mmol) of 4-iodobromobenzene, 22.3 g (105.0 mmol) of dibenzofuran-4-boronic acid, and 2.31 g (2.00 mmol) of Pd[PPh₃]₄, 150 ml of toluene, 150 ml of dimethoxyethane, and 150 ml (300.0 mmol) of a 2 M aqueous solution of Na₂CO₃ were added, and the resultant mixture was refluxed for 10 h under heating and stirring.

After the reaction, the reaction mixture was cooled to room temperature and extracted with dichloromethane in a separating funnel. The organic layer was dried over MgSO₄, filtered, and concentrated. The residual concentrate was purified by column chromatography to obtain 26.2 g of a white solid (yield: 81%), which was identified by FD-MS analysis (field desorption mass spectrometric analysis) as the intermediate (1-1).

(1-1)




Intermediate Synthesis 1-2 (Synthesis of Intermediate (1-2))

Under an argon atmosphere, into a mixture of 24.0 g (112.0 mmol) of 4'-bromoacetanilide, 28.6 g (135.0 mmol) of dibenzofuran-4-boronic acid, and 2.6 g (2.24 mmol) of Pd[PPh₃]₄, 450 ml of toluene, 100 ml of dimethoxyethane,

375

and 110 ml (220.0 mmol) of a 2 M aqueous solution of Na_2CO_3 were added, and the resultant mixture was refluxed for 10 h under heating and stirring.


After the reaction, the reaction mixture was cooled to room temperature and the precipitated crystal was collected by filtration. The obtained crystal was dissolved in tetrahydrofuran. The obtained solution was filtered through celite/silica gel, and the filtrate was concentrated under reduced pressure. The obtained residue was washed with methanol/hexane and dried to obtain 18.0 g of a white solid (yield: 53%), which was identified by FD-MS analysis as the following intermediate (1-2).



Intermediate Synthesis 1-3 (Synthesis of Intermediate (1-3))

A mixture of 18.0 g (59.7 mmol) of the intermediate (1-2), 120 ml of xylene, 1200 ml of water, and 60 ml of ethanol was stirred. After adding 20.0 g (360.0 mmol) of potassium hydroxide, the resultant mixture was refluxed for 10 h under heating and stirring.

After the reaction, the reaction mixture was cooled to room temperature and extracted with toluene in a separating funnel. The organic layer was dried over MgSO_4 , filtered, and concentrated. The obtained residue was recrystallized from xylene, and the precipitated crystal was collected by filtration and dried to obtain 14.7 g of a white crystal (yield: 95%), which was identified by FD-MS analysis as the following intermediate (1-3).




Intermediate Synthesis 1-4 (Synthesis of Intermediate (1-4))

Under an argon atmosphere, into a mixture of 47.0 g (201.6 mmol) of 4-bromobiphenyl, 23.0 g (90.6 mmol) of iodine, and 9.4 g (41.2 mmol) of periodic acid dihydrate, 42 ml of water, 360 ml of acetic acid, and 11 ml of sulfuric acid

376

were added, and the resultant mixture was stirred at 65° C. for 30 min and further stirred at 90° C. for 6 h.


After the reaction, the reaction mixture was poured into iced water and filtered. The collected solid was washed with water and then methanol to obtain 67.0 g of a white solid (yield: 93%), which was identified by FD-MS analysis as the following intermediate (1-4).



Intermediate Synthesis 1-5 (Synthesis of Intermediate 1-5)

Under an argon atmosphere, into a mixture of 35.9 g (100.0 mmol) of the intermediate (1-4), 16.7 g (100.0 mmol) of carbazole, 0.2 g (1.00 mmol) of copper iodide (CuI), and 42.4 g (210.0 mmol) of tripotassium phosphate, 2 ml of trans-1,2-cyclohexane diamine and 300 ml of 1,4-dioxane were added, and the resultant mixture was stirred at 100° C. for 20 h.

After the reaction, the reaction mixture was liquid-liquid separated after adding 300 ml of water and then the aqueous layer was removed. The organic layer was dried over sodium sulfate and then concentrated. The obtained residue was purified by silica gel column chromatography to obtain 23.1 g of a white solid (yield: 58%), which was identified by FD-MS analysis as the following intermediate (1-5).




Intermediate Synthesis 1-6 (Synthesis of Intermediate (1-6))

Under an argon atmosphere, into a mixture of 28.3 g (100.0 mmol) of 4-iodobromobenzene, 30.1 g (105.0 mmol) of 3-(9H-carbazole-9-yl)phenylboronic acid, and 2.31 g (2.00 mmol) of $\text{Pd}[\text{PPh}_3]_4$, 150 ml of toluene, 150 ml of dimethoxyethane, and 150 ml (300.0 mmol) of a 2 M aqueous solution of Na_2CO_3 were added, and the resultant mixture was refluxed for 10 h under heating and stirring.

After the reaction, the reaction mixture was cooled to room temperature and extracted with dichloromethane in a separating funnel. The organic layer was dried over MgSO_4 , filtered, and concentrated. The residual concentrate was purified by column chromatography to obtain 27.2 g of a white solid (yield: 68%), which was identified by FD-MS analysis as the following intermediate (1-6).

377



Intermediate Synthesis 2-1 (Synthesis of Intermediate (2-1))

Under an argon atmosphere, into a mixture of 32.7 g (100.0 mmol) of bis(4-bromophenyl)amine, 44.5 g (210.0 mmol) of dibenzofuran-4-boronic acid, and 2.31 g (2.00 mmol) of Pd[PPh₃]₄, 200 ml of toluene, 200 ml of dimethoxyethane, and 150 ml (300.0 mmol) of a 2 M aqueous solution of Na₂CO₃ were added, and the resultant mixture was refluxed for 10 h under heating and stirring.

After the reaction, the reaction mixture was cooled to room temperature and extracted with dichloromethane in a separating funnel. The organic layer was dried over MgSO₄, filtered, and concentrated. The obtained residue was purified by column chromatography to obtain 37.6 g of a white crystal (yield: 75%), which was identified by FD-MS analysis as the following intermediate (2-1).

(1-6)


5

20

25

30

(2-1)




Intermediate Synthesis 2-2 (Synthesis of Intermediate (2-2))

In the same manner as in Intermediate Synthesis 2-1 except for using 44.5 g (210.0 mmol) of dibenzofuran-2-boronic acid in place of dibenzofuran-4-boronic acid, 39.1 g of a white crystal was obtained (yield: 78%), which was identified by FD-MS analysis as the following intermediate (2-2).

45

50

(2-2)



Intermediate Synthesis 2-3 (Synthesis of Intermediate (2-3))


In the same manner as in Intermediate Synthesis 2-1 except for using 47.9 g (210.0 mmol) of dibenzophenone-

65

378

4-boronic acid in place of dibenzofuran-4-boronic acid, 37.4 g of a white crystal was obtained (yield: 70%), which was identified by FD-MS analysis as the following intermediate (2-3).

(2-3)




15

Intermediate Synthesis 2-4 (Synthesis of Intermediate (2-4))

In the same manner as in Intermediate Synthesis 2-1 except for using 47.9 g (210.0 mmol) of dibenzothiophene-2-boronic acid in place of dibenzofuran-4-boronic acid, 39.5 g of a white crystal was obtained (yield: 74%), which was identified by FD-MS analysis as the following intermediate (2-4).

(2-4)



40


Synthesis of Compound (A)

Intermediate Synthesis A-1-1 (Synthesis of Intermediate A-1-1))

Under an argon atmosphere, into a mixture of 28.3 g (100.0 mmol) of 4-iodobromobenzene, 23.9 g (105.0 mmol) of dibenzophenone-4-boronic acid, and 2.31 g (2.00 mmol) of Pd[PPh₃]₄, 150 ml of toluene, 150 ml of dimethoxyethane, and 150 ml (300.0 mmol) of a 2 M aqueous solution of Na₂CO₃ were added, and the resultant mixture was refluxed for 10 h under heating and stirring.

After the reaction, the reaction mixture was cooled to room temperature and extracted with dichloromethane in a separating funnel. The organic layer was dried over MgSO₄, filtered, and concentrated. The residual concentrate was purified by column chromatography to obtain 27.1 g of a white solid (yield: 80%), which was identified by FD-MS analysis as the following intermediate (A-1-1).

379




(A-1-1)

Intermediate Synthesis A-1-2 (Synthesis of Intermediate (A-1-2))

Under an argon atmosphere, into a mixture of 24.0 g (112.0 mmol) of 4'-bromoacetanilide, 30.8 g (135.0 mmol) of dibenzophenone-4-boronic acid, and 2.6 g (2.24 mmol) of Pd[PPh₃]₄, 450 ml of toluene, 100 ml of dimethoxyethane, and 110 ml (220.0 mmol) of a 2 M aqueous solution of Na₂CO₃ were added, and the resultant mixture was refluxed for 10 h under heating and stirring.

After the reaction, the reaction mixture was cooled to room temperature and the precipitated crystal was collected by filtration. The obtained crystal was dissolved in tetrahydrofuran. The obtained solution was filtered through celite/silica gel, and the filtrate was concentrated under reduced pressure. The obtained residue was washed with methanol/hexane and dried to obtain 17.8 g of a white solid (yield: 50%), which was identified by FD-MS analysis as the following intermediate (A-1-2).




(A-1-2)

Intermediate Synthesis A-1-3 (Synthesis of Intermediate (A-1-3))

A mixture of 18.0 g (56.1 mmol) of the intermediate (A-1-2) in 120 ml of xylene, 1200 ml of water, and 60 ml of ethanol was stirred. After adding 20.0 g (360.0 mmol) of potassium hydroxide, the resultant mixture was refluxed for 10 h under heating and stirring.

After the reaction, the reaction mixture was cooled to room temperature and extracted with toluene in a separating funnel. The organic layer was dried over MgSO₄, filtered, and concentrated. The obtained residue was recrystallized from xylene, and the precipitated crystal was collected by filtration and dried to obtain 14.7 g of a white crystal (yield: 95%), which was identified by FD-MS analysis as the following intermediate (A-1-3).

380




(A-1-3)

Intermediate Synthesis A-1-4 (Synthesis of Intermediate (A-1-4))

Under an argon atmosphere, into a mixture of 39.7 g (100.0 mmol) of 4-bromo-9,9'-diphenylfluorene, 16.4 g (105.0 mmol) of 4-chlorophenylboronic acid, and 2.31 g (2.00 mmol) of Pd[PPh₃]₄, 150 ml of toluene, 150 ml of dimethoxyethane, and 150 ml (300.0 mmol) of a 2 M aqueous solution of Na₂CO₃ were added, and the resultant mixture was refluxed for 10 h under heating and stirring.

After the reaction, the reaction mixture was cooled to room temperature and extracted with dichloromethane in a separating funnel. The organic layer was dried over MgSO₄, filtered, and concentrated. The residual concentrate was purified by column chromatography to obtain 32.2 g of a white solid (yield: 75%), which was identified by FD-MS analysis as the following intermediate (A-1-4).




(A-1-4)

Intermediate Synthesis A-2-1 (Synthesis of Intermediate (A-2-1))

Under an argon atmosphere, into a mixture of 19.9 g (50.0 mmol) of 4-bromo-9,9'-diphenylfluorene, 13.0 g (50.0 mmol) of the intermediate (1-3), and 9.6 g (100.0 mmol) of sodium t-butoxide, 250 ml of dehydrated toluene was added, and the resultant mixture was stirred. After further adding 225 mg (1.0 mmol) of palladium acetate and 202 mg (1.0 mmol) of tri-*t*-butylphosphine, the mixture was allowed to react at 80° C. for 8 h.


After cooling, the reaction mixture was filtered through celite/silica gel, and the filtrate was concentrated under reduced pressure. The obtained residue was recrystallized from toluene, and the precipitated crystal was collected by filtration and dried to obtain 23.9 g of a white crystal (yield: 83%), which was identified by FD-MS analysis as the following intermediate (A-2-1).

381



Intermediate Synthesis A-2-2 (Synthesis of Intermediate (A-2-2))

In the same manner as in Intermediate Synthesis A-2-1 except for using 13.8 g of the intermediate (A-1-3) in place of the intermediate (1-3), 23.7 g of a white crystal was obtained (yield: 80%), which was identified by FD-MS analysis as the following intermediate (A-2-2).



Synthesis Example A-1 (Synthesis of Compound (H-A1))


Under an argon atmosphere, into a mixture of 3.2 g (10.0 mmol) of the intermediate (1-1), 5.8 g (10.0 mmol) of the

382

intermediate (A-2-1), 0.14 g (0.15 mmol) of $\text{Pd}_2(\text{dba})_3$, 0.087 g (0.3 mmol) of $\text{P}(\text{tBu})_3\text{HBF}_4$, and 1.9 g (20.0 mmol) of sodium t-butoxide, 50 ml of dehydrated xylene was added, and the resultant mixture was refluxed for 8 h under heating.

After the reaction, the reaction mixture was cooled to 50° C., and filtered through celite/silica gel. The filtrate was concentrated and the residual concentrate was purified by column chromatography and recrystallized from toluene to obtain 2.9 g of a white crystal (yield: 35%), which was identified by FD-MS analysis as the following compound (H-A1)


(H-A1)



Synthesis Example A-2 (Synthesis of Compound (H-A2))


In the same manner as in Synthesis Example A-1 except for using 3.4 g (10.0 mmol) of the intermediate (A-1-1) in place of the intermediate (1-1) and using 5.9 g (10.0 mmol) of the intermediate (A-2-2) in place of the intermediate (A-2-1), 4.4 g of a white crystal was obtained (yield: 52%), which was identified by FD-MS analysis as the following compound (H-A2).

383



Synthesis Example A-3 (Synthesis of Compound (H-A3))

In the same manner as in Synthesis Example A-1 except for using 4.0 g (10.0 mmol) of the intermediate (1-5) in place of the intermediate (1-1), 4.2 g of a white crystal was obtained (yield: 47%), which was identified by FD-MS analysis as the following compound (H-A3).




Synthesis Example A-4 (Synthesis of Compound (H-A4))

In the same manner as in Synthesis Example A-1 except for using 4.0 g (10.0 mmol) of 4-bromo-9,9'-diphenylfluorene in place of the intermediate (1-1) and using 5.0 g (10.0 mmol) of the intermediate (2-2) in place of the intermediate


384

(A-2-1), 3.3 g of a white crystal was obtained (yield: 40%), which was identified by FD-MS analysis as the following compound (H-A4).



Synthesis Example A-5 (Synthesis of Compound (H-A5))


In the same manner as in Synthesis Example A-1 except for using 4.0 g (10.0 mmol) of 4-bromo-9,9'-diphenylfluorene in place of the intermediate (1-0 and using 5.3 g (10.0 mmol) of the intermediate (2-4) in place of the intermediate (A-2-1), 3.7 g of a white crystal was obtained (yield: 43%), which was identified by FD-MS analysis as the following compound (H-A5).



385

Synthesis Example A-6 (Synthesis of Compound
(H-A6))


In the same manner as in Synthesis Example A-1 except for using 4.3 g (10.0 mmol) of the intermediate (A-1-4) in place of the intermediate (1-1) and using 5.0 g (10.0 mmol) of the intermediate (2-1) in place of the intermediate (A-2-1), 3.4 g of a white crystal was obtained (yield: 38%), which was identified by FD-MS analysis as the following compound (H-A6).

Synthesis Example A-7 (Synthesis of Compound
(H-A7))


In the Same Manner as in Synthesis Example A-1 Except for Using 4.3 g (10.0 mmol) of the intermediate (A-1-4) in place of the intermediate (1-1) and using 5.0 g (10.0 mmol) of the intermediate (2-2) in place of the intermediate (A-2-1), 3.3 g of a white crystal was obtained (yield: 37%), which was identified by FD-MS analysis as the following compound (H-A7).

386

(H-A7)

Synthesis Example A-8 (Synthesis of Compound
(H-A8))


In the same manner as in Synthesis Example A-1 except for using 4.3 g (10.0 mmol) of the intermediate (A-1-41) in place of the intermediate (1-1) and using 5.3 g (10.0 mmol) of the intermediate (2-3) in place of the intermediate (A-2-1), 4.2 g of a white crystal was obtained (yield: 45%), which was identified by FD-MS analysis as the following compound (H-A8).

Synthesis Example A-9 (Synthesis of Compound
(H-A9))

In the same manner as in Synthesis Example A-1 except for using 4.3 g (10.0 mmol) of the intermediate (A-1-4) in


387

place of the intermediate (1-1) and using 5.3 g (10.0 mmol) of the intermediate (2-4) in place of the intermediate (A-2-1), 3.2 g of a white crystal was obtained (yield: 35%), which was identified by FD-MS analysis as the following compound (H-A9).



Synthesis Example A-10 (Synthesis of Compound (H-A10))

In the same manner as in Synthesis Example A-1 except for using 4.0 g (10.0 mmol) of the intermediate (1-6) in place of the intermediate (1-1), 2.5 g of a white crystal was obtained (yield: 28%), which was identified by FD-MS analysis as the following compound (H-A10).




388

Synthesis of Compound (B)

Intermediate Synthesis B-1-1 (Synthesis of Intermediate (B-1-1))

5 Under an argon atmosphere, into a mixture of 39.7 g (100.0 mmol) of 3-bromo-9,9'-diphenylfluorene, 16.4 g (105.0 mmol) of 4-chlorophenylboronic acid, and 2.31 g (2.00 mmol) of Pd[PPh₃]₄, 150 ml of toluene, 150 ml of dimethoxyethane, and 150 ml (300.0 mmol) of a 2 M aqueous solution of Na₂CO₃ were added, and the resultant mixture was refluxed for 10 h under heating and stirring.


10 After the reaction, the reaction mixture was cooled to room temperature and extracted with dichloromethane in a separating funnel. The organic layer was dried over MgSO₄, filtered, and concentrated. The obtained residue was purified by column chromatography to obtain 34.3 g of a white solid (yield: 80%), which was identified by FD-MS analysis as the following intermediate (B-1-1).



Intermediate Synthesis B-2-1 (Synthesis of Intermediate (B-2-1))

35 Under an argon atmosphere, into a mixture of 13.0 g (50.0 mmol) of the intermediate (1-3), 19.9 g (50.0 mmol) of the intermediate (1-5), and 9.6 g (100.0 mmol) of sodium t-butoxide, 250 ml of dehydrated toluene was added, and the resultant mixture was stirred. After further adding 225 mg (1.0 mmol) of palladium acetate and 202 mg (1.0 mmol) of tri-t-butylphosphine, the mixture was allowed to react at 80° C. for 8 h.

40 After the reaction, the reaction mixture was cooled to room temperature and filtered through celite/silica gel, and the filtrate was concentrated under reduced pressure. The obtained residue was recrystallized from toluene, and the precipitated crystal was collected by filtration and dried to obtain 18.7 g of a white crystal (yield: 65%), which was identified by FD-MS analysis as the following intermediate (B-2-1).




389

Intermediate Synthesis B-2-2 (Synthesis of Intermediate (B-2-2))

Under an argon atmosphere, into a mixture of 19.9 g (50.0 mmol) of 3-bromo-9,9'-diphenylfluorene, 13.0 g (50.0 mmol) of the intermediate (1-3), and 9.6 g (100.0 mmol) of sodium t-butoxide, 250 ml of dehydrated toluene was added, and the resultant mixture was stirred. After further adding 225 mg (1.0 mmol) of palladium acetate and 202 mg (1.0 mmol) of tri-t-butylphosphine, the mixture was allowed to react at 80° C. for 8 h.

After cooling, the reaction mixture was filtered through celite/silica gel, and the filtrate was concentrated under reduced pressure. The obtained residue was recrystallized from toluene, and the precipitated crystal was collected by filtration and dried to obtain 23.9 g of a white crystal (yield: 83%), which was identified by FD-MS analysis as the following intermediate (B-2-2).




Synthesis Example B-1 (Synthesis of Compound (H-B1))

Under an argon atmosphere, into a mixture of 5.0 g (10.0 mmol) of the intermediate (2-1), 4.0 g (10.0 mmol) of 3-bromo-9,9'-diphenylfluorene, 0.14 g (0.15 mmol) of Pd₂(dba)₃, 0.087 g (0.3 mmol) of P(tBu)₃HBF₄, and 1.9 g (20.0 mmol) of sodium t-butoxide, 50 ml of dehydrated xylene was added, and the resultant mixture was refluxed for 8 h under heating.

After the reaction, the reaction mixture was cooled to 50° C. and filtered through celite/silica gel. The filtrate was concentrated and the obtained residue was purified by column chromatography and recrystallized from toluene to obtain 3.3 g of a white crystal (yield: 40%), which was identified by FD-MS analysis as the following compound (H-B1).


390

(H-B1)



Synthesis Example B-2 (Synthesis of Compound (H-B2))

In the same manner as in Synthesis Example B-1 except for using 5.0 g (10.0 mmol) of the intermediate (2-2) in place of the intermediate (2-1), 3.7 g of a white crystal was obtained (yield: 45%), which was identified by FD-MS analysis as the following compound (H-B2).




Synthesis Example B-3 (Synthesis of Compound (H-B3))

In the same manner as in Synthesis Example B-1 except for using 5.3 g (10.0 mmol) of the intermediate (2-3) in place of the intermediate (2-1), 3.6 g of a white crystal was obtained (yield: 42%), which was identified by FD-MS analysis as the following compound (H-B3).


391

392




Synthesis Example B-4 (Synthesis of Compound (H-B4))

In the same manner as in Synthesis Example B-1 except for using 5.3 g (10.0 mmol) of the intermediate (2-4) in place of the intermediate (2-1), 3.2 g of a white crystal was obtained (yield: 38%) which was identified by FD-MS analysis as the following compound (H-B4).



Synthesis Example B-5 (Synthesis of Compound (H-B5))


In the same manner as in Synthesis Example B-1 except for using 5.8 g (10.0 mmol) of the intermediate (B-2-1) in place of the intermediate (2-1), 3.1 g of a white crystal was obtained (yield: 35%), which was identified by FD-MS analysis as the following compound (H-B5).



Synthesis Example B-6 (Synthesis of Compound (H-B6))

Under an argon atmosphere, into a mixture of 5.0 g (10.0 mmol) of the intermediate (2-1), 4.3 g (10.0 mmol) of the intermediate (B-1-1), 0.14 g (0.15 mmol) of Pd₂(dba)₃, 0.087 g (0.3 mmol) of P(tBu)₃HBF₄, and 1.9 g (20.0 mmol) of sodium t-butoxide, 50 ml of dehydrated xylene was added, and the resultant mixture was refluxed for 8 h under heating.

After the reaction, the reaction mixture was cooled to 50° C. and filtered through celite/silica gel. The filtrate was concentrated and the obtained residue was purified by column chromatography and recrystallized from toluene to obtain 3.3 g of a white crystal (yield: 37%), which was identified by FD-MS analysis as the following compound (H-B6).




Synthesis Example B-7 (Synthesis of Compound (H-B7))

In the same manner as in Synthesis Example B-6 except for using 5.0 g (10.0 mmol) of the intermediate (2-2) in place


393

of the intermediate (2-1), 3.1 g of a white crystal was obtained (yield: 35%), which was identified by FD-MS analysis as the following compound (H-B7).



Synthesis Example B-8 (Synthesis of Compound (H-B8))

In the same manner as in Synthesis Example B-6 except for using 5.3 g (10.0 mmol) of the intermediate (2-3) in place of the intermediate (2-1), 3.5 g of a white crystal was obtained (yield: 38%), which was identified by FD-MS analysis as the following compound (H-B8).




Synthesis Example B-9 (Synthesis of Compound (H-B9))

In the same manner as in Synthesis Example B-6 except for using 5.3 g (10.0 mmol) of the intermediate (2-4) in place of the intermediate (2-1), 2.8 g of a white crystal was obtained (yield: 30%), which was identified by FD-MS analysis as the following compound (H-B9).

394

(H-B9)




Synthesis Example B-10 (Synthesis of Compound (H-B10))

25

In the same manner as in Synthesis Example B-1 except for using 5.8 (10.0 mmol) of the intermediate (B-2-2) in place of the intermediate (2-1) and using 4.0 g (10.0 mmol) of the intermediate (1-6) in place of 3-bromo-9,9'-diphenylfluorene, 2.1 g of a white crystal was obtained (yield: 24%), which was identified by FD-MS analysis as the following compound (H-B10).

30

(H-B10)



Production of Organic EL Device Using Compound (A)

55

Examples A-1 to A-10 (Production of Organic EL Device)

A glass substrate of 25 mm×75 mm×1.1 mm having an ITO transparent electrode (product of Geomatec Company) was cleaned by ultrasonic cleaning in isopropyl alcohol for 5 min and then UV (ultraviolet) ozone cleaning for 30 min.

The cleaned glass substrate having a transparent electrode line was mounted to a substrate holder of a vacuum vapor deposition apparatus. First, the following electron-accepting compound (EA1) was vapor-deposited so as to cover the transparent electrode to form a film (EA1) with a thickness of 10 nm.




395

On the film (EA1), the following aromatic amine derivative (X1) as a first hole transporting material was vapor-deposited to form a first hole transporting layer with a thickness of 80 nm. Successively after forming the first hole transporting layer, each of the compounds (H-A1) to (H-A10) obtained in Synthesis Examples A-1 to A-10 as a second hole transporting material was vapor-deposited to form a second hole transporting layer with a thickness of 10 nm.

On the second hole transporting layer, the following host compound (BH) and dopant compound (BD) as fluorescent emitting materials were vapor co-deposited to form a light emitting layer with a thickness of 25 nm. The concentration of the dopant compound (BD) in the light emitting layer was 4% by mass.

Thereafter, on the light emitting layer, the following compound (ET1), the flowing compound (ET2), and LiF were vapor co-deposited into a thickness of 25 nm, 10 nm, and 1 nm, respectively to form an electron transporting/injecting layer.


Further, metallic Al was deposited into a thickness of 80 nm to form a cathode, thereby producing each organic EL device.



396

-continued

(BD)



(ET1)

(EA1)

(X1)

40


45

50


55

60

65



(ET2)



The compounds (H-A1) to (H-A10) obtained Synthesis Examples A-1 to A-10 which were used as the second hole transporting materials are shown below.


397

398

-continued

(H-A1)

(H-A3)



5

10

15


20

25

30

35

40



45

50



55

60

65


(H-A2)

(H-A4)



399
-continued


(H-A5)



5
10
15
20
25


400
-continued

(H-A7)




30
35
40

(H-A6)



45
50
55
60
65


(H-A8)



401

-continued

(H-A9)



5


10

15

20

402

(a1)



25


30

35

(H-A10)

40

45




50

55

60

(a3)




Comparative Examples a-1 to a-4

Each organic EL device of Comparative Examples a-1 to a-4 was produced in the same manner as in Example A-1 except for forming the second hole transporting layer by using each of the following comparative compounds (a1) to (a4) as the second hole transporting material.

65

403

-continued



Evaluation of Emission Efficiency of Organic EL Device

Each organic EL device thus produced was allowed to emit light by driving at a constant current to measure the luminance (L) and the current density. From the measured results, the emission efficiency (cd/A) and the driving voltage (V) at a current density of 10 mA/cm² were determined. In addition, the 80% lifetime at a current density of 50 mA/cm² was determined. The 80% lifetime is the time taken until the luminance is reduced to 80% of the initial luminance when driving at a constant current. The results are shown in Table 1.

TABLE 1

Measured results					
First hole transporting material	Second hole transporting material	Emission efficiency (cd/A) @10 mA/cm ²	Driving voltage (V) @10 mA/cm ²	80% lifetime (h) @50 mA/cm ²	
Examples					
A-1	X1	H-A1	9.8	4.8	300
A-2	X1	H-A2	9.8	4.8	280
A-3	X1	H-A3	9.9	4.6	290
A-4	X1	H-A4	10.1	4.8	270
A-5	X1	H-A5	10	4.7	270
A-6	X1	H-A6	9.8	4.6	320
A-7	X1	H-A7	10	4.6	300
A-8	X1	H-A8	9.9	4.6	310
A-9	X1	H-A9	10	4.7	300
A-10	X1	H-A10	10.3	4.9	310
Comparative Examples					
a-1	X1	a1	9.8	4.8	200
a-2	X1	a2	9.8	4.9	220
a-3	X1	a3	8.2	4.5	220
a-4	X1	a4	7.8	4.3	250

As seen from Table 1, it can be found that each of the compounds (H-A1) to (H-A10) within the compound (A) in an aspect of the invention provides an organic EL device capable of driving at low voltage and has high emission efficiency and long lifetime, because its electron blocking ability and resistance to electron are enhanced by more than one group represented by any of formulae (a) to (c).

404


Production of Organic EL Device Using Compound (B)

Examples B-1 to B-10 (Production of Organic EL Device)


Each organic EL device of Examples B-1 to B-10 was produced in the same manner as in Example A-1 except for forming the second hole transporting layer by using each of the compounds (H-B1) to (H-B10) obtained in Synthesis Examples B-1 to B-10 as the second hole transporting material.

The compounds (H-B1) to (H-B10) obtained in Synthesis Examples B-1 to B-10 which were used in these examples are shown below.

(H-B1)




(H-B2)



405
-continued

(H-B3)




5

10

15

20

(H-B4)



25


30

35

40

45

(H-B5)



50


55

60

65

406
-continued

(H-B6)




5

10

15

20

(H-B7)



25


30

35

40

45

(H-B8)




50

55

60


65

407
-continued





408

(b1)



(b2)



Comparative Example b-1 and b-2

Each organic EL device of Comparative Examples b-1 and b-2 was produced in the same manner as in Example B-1 except for forming the second hole transporting layer by using the following comparative compound (b1) or (b2) as the second hole transporting material.

Evaluation of Emission Efficiency of Organic EL Device

Each organic EL device thus produced was allowed to emit light by driving at a constant current to measure the luminance (L) and the current density. From the measured results, the emission efficiency (cd/A) and the driving voltage (V) at a current density of 10 mA/cm² were determined. In addition, the 80% lifetime at a current density of 50 mA/cm² was determined. The 80% lifetime is the time taken until the luminance is reduced to 80% of the initial luminance when driving at a constant current. The results are shown in Table 2.

TABLE 2

Measured results					
	First hole transporting material	Second hole transporting material	Emission efficiency (cd/A) @10 mA/cm ²	Driving voltage (V) @10 mA/cm ²	80% lifetime (h) @50 mA/cm ²
Examples					
B-1	X1	H-B1	9.8	3.8	290
B-2	X1	H-B2	10.1	3.8	270
B-3	X1	H-B3	9.8	3.8	280
B-4	X1	H-B4	10.0	3.8	260

409

TABLE 2-continued

	First hole transporting material	Second hole transporting material	Measured results		
			Emission efficiency (cd/A) @10 mA/cm ²	Driving voltage (V) @10 mA/cm ²	80% lifetime (h) @50 mA/cm ²
B-5	X1	H-B5	9.7	3.7	290
B-6	X1	H-B6	9.7	3.7	320
B-7	X1	H-B7	9.9	3.7	300
B-8	X1	H-B8	9.7	3.6	310
B-9	X1	H-B9	9.9	3.7	290
B-10	X1	H-B10	10.1	4.0	300
Comparative Examples					
b-1	X1	b1	9.5	3.8	200
b-2	X1	b2	9.8	3.9	220


As seen from Table 2, it can be found that each of the compounds (H-B1) to (H-B10) within the compound (B) in an aspect of the invention provides an organic EL device capable of driving at low voltage and has high emission efficiency and long lifetime, because its electron blocking ability and resistance to electron are enhanced by more than one group represented by any of formulae (a) to (c).

REFERENCE SIGNS LIST

- 1: Organic EL device
- 2: Substrate
- 3: Anode
- 4: Cathode
- 5: Light emitting layer
- 6: Anode-side organic thin film layer
- 7: Cathode-side organic thin film layer
- 10: Emission unit

What is claimed is:

1. An organic electroluminescence device which comprises a cathode, an anode, and at least one organic thin film layer disposed between the cathode and the anode, wherein the at least one organic thin film comprises a light emitting layer and at least one selected from a hole injecting layer comprising a compound represented by formula (A-0) or (B-0) and a hole transporting layer comprising a compound represented by formula (A-0) or (B-0):




(A-0)

410

-continued

(B-0)




wherein R¹ to R⁴ each independently represent a substituted or unsubstituted alkyl group having 1 to 20 carbon atoms, a substituted or unsubstituted aryl group having 6 to 50 ring carbon atoms, a substituted or unsubstituted heteroaryl group having 5 to 50 ring atoms, a halogen atom, a substituted or unsubstituted fluoroalkyl group having 1 to 20 carbon atoms, a substituted or unsubstituted alkoxy group having 1 to 20 carbon atoms, a substituted or unsubstituted fluoroalkoxy group having 1 to 20 carbon atoms, a substituted or unsubstituted aryloxy group having 6 to 50 ring carbon atoms, or a cyano group, and when R¹ to R⁴ are each plurality in number, groups R¹ to groups R⁴ may be the same or different;


k₃ and k₄ each independently represent an integer of 0 to 5, m₂ represents an integer of 0 to 4, and n₁ represents an integer of 0 to 3;

L⁰ to L² each independently represent a single bond, a substituted or unsubstituted arylene group having 6 to 50 ring carbon atoms, or a substituted or unsubstituted heteroarylene group having 5 to 50 ring atoms;


Ar¹ and Ar² each independently represent a group represented by any of formulae (a) to (c):



(a)



(b)



(c)

65


411

wherein R^5 and R^6 are each independently the same as defined with respect to R^1 , when R^5 and R^6 are each plurality in number, groups R^5 and groups R^6 may be the same or different, and R^5 and R^6 may be bonded to each other to form a ring structure;

$m5$ and $m6$ each independently represent an integer of 0 to 4, and each $n5$ independently represents an integer of 0 to 3; and


* represents a bonding site to the nitrogen atom, L^1 , or L^2 in formula (A-0) or (B-0).

2. The organic electroluminescence device according to claim 1, wherein the compound is represented by formula (A-1):




wherein R^1 to R^4 , $n1$, $m2$, $k3$, $k4$, L^1 , L^2 , Ar^1 and Ar^2 are as defined in claim 1.

3. The organic electroluminescence device according to claim 1, wherein the compound is represented by formula (A-2):



wherein R^1 , R^2 , $n1$, $m2$, L^0 to L^2 , Ar^1 , and Ar^2 are as defined in claim 1.


4. The organic electroluminescence device according to claim 1, wherein the compound is represented by formula (A-3):



wherein L^0 to L^2 , Ar^1 , and Ar^2 are as defined in claim 1.


412

5. The organic electroluminescence device according to claim 1, wherein the compound is represented by formula (A-4):




wherein R^1 to R^6 , $n1$, $m2$, $k3$, $k4$, $n5$, $m6$, L^0 to L^2 , and Ar^2 are as defined in claim 1, and X represents $-O-$ or $-S-$.

6. The organic electroluminescence device according to claim 5, wherein the compound is represented by formula (A-5) or (A-6):




wherein R^1 to R^6 , $n1$, $m2$, $k3$, $k4$, $n5$, $m6$, L^0 to L^2 , and Ar^2 are as defined in claim 1, and X represents $-O-$ or $-S-$.



wherein R^1 to R^6 , $n1$, $m2$, $k3$, $k4$, $n5$, $m6$, L^0 to L^2 , and Ar^2 are as defined in claim 1, and X represents $-O-$ or $-S-$.

7. The organic electroluminescence device according to claim 5, wherein the compound is represented by formula (A-7) or (A-8):

413




5

10

15


414

(B-2)



wherein R^1 to R^4 , $n1$, $m2$, $k3$, $k4$, L^1 , L^2 , Ar^1 , and Ar^2 are as defined in claim 1, R^8 is the same as defined with respect to R^1 in claim 1, when more than one R^8 occurs, groups R^8 may be the same or different, two selected from groups R^8 may be bonded to each other to form a ring structure, and $m8$ represents an integer of 0 to 4.

10. The organic electroluminescence device according to claim 1, wherein the compound is represented by formula (B-3):



25


30

35

40


wherein R^1 to R^6 , $n1$, $m2$, $k3$, $k4$, $n5$, $m6$, L^0 , L^2 , and Ar^2 are as defined in claim 5, R^7 is the same as defined with respect to R^1 in claim 5, when more than one R^7 occurs, groups R^7 may be the same or different, two selected from groups R^7 may be bonded to each other to form a ring structure, $m7$ represents an integer of 0 to 4, and X represents —O— or —S—.

8. The organic electroluminescence device according to claim 1, wherein the compound is represented by formula (B-1):




wherein R^1 to R^4 , $n1$, $m2$, $k3$, $k4$, L^1 , L^2 , and Ar^1 and Ar^2 are as defined in claim 1.

9. The organic electroluminescence device according to claim 1, wherein the compound is represented by formula (B-2):



wherein R^1 , R^2 , $n1$, $m2$, L^0 to L^2 , Ar^1 , and Ar^2 are as defined in claim 1.


11. The organic electroluminescence device according to claim 1, wherein the compound is represented by formula (B-4):



wherein L^0 to L^2 , Ar^1 , and Ar^2 are as defined in claim 1.

12. The organic electroluminescence device according to claim 1, wherein the compound is represented by formula (B-5):

415




wherein R^1 to R^6 , $n1$, $m2$, $k3$, $k4$, $n5$, $m6$, L^0 to L^2 , and Ar^2 are as defined in claim 1, and X represents —O— or —S—.

416

-continued


(B-7)




wherein R^1 to R^6 , $n1$, $m2$, $k3$, $k4$, $n5$, $m6$, L^0 to L^2 , and Ar^2 are as defined in claim 12, and X represents —O— or —S—.

14. The organic electroluminescence device according to claim 12, wherein the compound is represented by formula (B-8) or (B-9):

(B-8)



(B-9)




13. The organic electroluminescence device according to claim 12, wherein the compound is represented by formula (B-6) or (B-7):

50


wherein R^1 to R^6 , $n1$, $m2$, $k3$, $k4$, $n5$, $m6$, L^0 , L^2 , and Ar^2 are as defined in claim 12, R^7 is the same as defined with respect to R^1 in claim 12, when more than one R^7 occurs, groups R^7 may be the same or different, two selected from groups R^7 may be bonded to each other to form a ring structure, $m7$ represents an integer of 0 to 4, and X represents —O— or —S—.

(B-6)




15. The organic electroluminescence device according to claim 1, wherein L^0 to L^2 each independently represent a single bond or a group represented by any of formulae (i) and (ii):

(i)



417

-continued




(ii)

5

wherein each R is independently the same as defined with respect to R¹ in claim 1, when more than one R occurs, groups R may be the same or different, two selected from groups R may be bonded to each other to form a ring structure, each m independently represents an integer of 0 to 4, and * and ** each represent a bonding site.


16. The organic electroluminescence device according to claim 1, wherein at least one selected from Ar¹ and Ar² represents a group represented by any of formulae (b-1), (b-2), (c-1), and (c-2):



(b-1)

20

25




(b-2)


30

418

-continued



(c-1)



(c-2)

wherein R⁵, R⁶, n₅, and m₆ are as defined in claim 1, and * represents a bonding site to the nitrogen atom, L¹, or L² in formula (A-0) or (B-0).

17. An electronic equipment comprising the organic electroluminescence device according to claim 1.

* * * * *

专利名称(译)	化合物，有机电致发光元件材料，有机电致发光元件和电子设备		
公开(公告)号	US10516112	公开(公告)日	2019-12-24
申请号	US14/910156	申请日	2015-07-13
申请(专利权)人(译)	出光兴产股份有限公司.		
当前申请(专利权)人(译)	出光兴产股份有限公司.		
[标]发明人	KATO TOMOKI YABUNOUCHI NOBUHIRO FUNAHASHI MASAKAZU FUJIYAMA TAKAHIRO		
发明人	KATO, TOMOKI YABUNOUCHI, NOBUHIRO FUNAHASHI, MASAKAZU FUJIYAMA, TAKAHIRO		
IPC分类号	H01L51/00 C07D209/86 C09K11/06 H01L51/50 C07D209/82 C07D405/12 C07C211/61 C07D333/76 C07D307/91		
CPC分类号	C09K11/06 C07D333/76 H01L51/0072 H01L51/0074 C07D209/82 H01L51/006 H01L51/0061 H01L51/0073 H01L51/50 C07D307/91 C07D405/12 C07C211/61 C07D209/86 H01L51/5012 H01L51/5016 H01L51/5088 H01L51/5056 C09K2211/1014 C09K2211/1011 C07C2603/18 H01L51/5092 C07C2603/42 H01L51/0054 H01L51/5072 C09K2211/1018 H01L51/0052 H01L51/0058 C09K2211/1007 H01L51/5064 C09K2211/1088 C09K2211/1092		
审查员(译)	张, RUIYUN		
优先权	2014143248 2014-07-11 JP 2014143249 2014-07-11 JP 2014255559 2014-12-17 JP 2014255562 2014-12-17 JP 2014255565 2014-12-17 JP		
其他公开文献	US20160181525A1		
外部链接	Espacenet		

摘要(译)

由式 (A-0) 或 (B-0) 表示的化合物可用作有机EL器件的材料，该材料可实现即使在低电压下驱动也具有长寿命的有机EL器件，该有机EL器件也显示出高发射效率：其中，R1 至R4，n1，m2，k3，k4，L0 至L2，Ar1和Ar2 如描述中所定义。

