



(51) International Patent Classification:

A61B 5/00 (2006.01) H04R 1/10 (2006.01)

A61M 21/02 (2006.01)

(21) International Application Number:

PCT/US2018/043061

(22) International Filing Date:

20 July 2018 (20.07.2018)

(25) Filing Language:

English

(26) Publication Language:

English

(30) Priority Data:

15/655,853 20 July 2017 (20.07.2017) US

(71) Applicant: **BOSE CORPORATION** [US/US]; The Mountain, MS 3B1, Framingham, Massachusetts 01701-9168 (US).

(72) Inventors: **KIRSZENBLAT, Romain**; c/o BOSE CORPORATION, The Mountain, MS 3B1, Framingham, Massachusetts 01701-9168 (US). **LIN, Lifun**; c/o BOSE CORPORATION, The Mountain, MS 3B1, Framingham, Massachusetts 01701-9168 (US). **IOFFE, Mikhail**; c/o BOSE CORPORATION, The Mountain, MS 3B1, Framingham, Massachusetts 01701-9168 (US). **AYERS, Tegan**; c/o BOSE CORPORATION, The Mountain, MS 3B1, Framingham, Massachusetts 01701-9168 (US). **CARBO, Randy Michael**; c/o BOSE CORPORATION, The Mountain, MS 3B1, Framingham, Massachusetts 01701-9168 (US).

(74) Agent: **HILL, Misha K.**; BOSE CORPORATION, The Mountain, MS 3B1, Framingham, Massachusetts 01701-9168 (US).

(81) Designated States (unless otherwise indicated, for every kind of national protection available): AE, AG, AL, AM, AO, AT, AU, AZ, BA, BB, BG, BH, BN, BR, BW, BY, BZ, CA, CH, CL, CN, CO, CR, CU, CZ, DE, DJ, DK, DM, DO, DZ, EC, EE, EG, ES, FI, GB, GD, GE, GH, GM, GT, HN, HR, HU, ID, IL, IN, IR, IS, JO, JP, KE, KG, KH, KN, KP, KR, KW, KZ, LA, LC, LK, LR, LS, LU, LY, MA, MD, ME, MG, MK, MN, MW, MX, MY, MZ, NA, NG, NI, NO, NZ, OM, PA, PE, PG, PH, PL, PT, QA, RO, RS, RU, RW, SA, SC, SD, SE, SG, SK, SL, SM, ST, SV, SY, TH, TJ, TM, TN, TR, TT, TZ, UA, UG, US, UZ, VC, VN, ZA, ZM, ZW.

(84) Designated States (unless otherwise indicated, for every kind of regional protection available): ARIPO (BW, GH, GM, KE, LR, LS, MW, MZ, NA, RW, SD, SL, ST, SZ, TZ,

UG, ZM, ZW), Eurasian (AM, AZ, BY, KG, KZ, RU, TJ, TM), European (AL, AT, BE, BG, CH, CY, CZ, DE, DK, EE, ES, FI, FR, GB, GR, HR, HU, IE, IS, IT, LT, LU, LV, MC, MK, MT, NL, NO, PL, PT, RO, RS, SE, SI, SK, SM, TR), OAPI (BF, BJ, CF, CG, CI, CM, GA, GN, GQ, GW, KM, ML, MR, NE, SN, TD, TG).

Published:

— with international search report (Art. 21(3))

(54) Title: EARPHONES FOR MEASURING AND ENTRAINING RESPIRATION

(57) Abstract: An earphone includes a loudspeaker, a microphone, a housing supporting the loudspeaker and microphone, and an ear tip surrounding the housing and configured to acoustically couple both the loudspeaker and the microphone to an ear canal of a user, and to acoustically close the entrance to the users ear canal. A processor receives input audio signals from the microphone, detects peaks having a frequency of around 1 Hz in the input audio signals, based on the detected peaks, computes an instantaneous heart rate, measures a frequency of an oscillation within the instantaneous heart rate, and based on the frequency of the oscillation, computes a rate of respiration.

EARPHONES FOR MEASURING AND ENTRAINING RESPIRATION

RELATED APPLICATIONS

[0001] This application is related to, and incorporates by reference, U.S. Patent
5 Application 15/106,989, filed June 21, 2016; Application 15/348,400, filed
November 10, 2016; and Application 15/352,034, filed November 17, 2016, all titled
Intelligent Earplug System. It is also related to U.S. Patent Application 15/267,567,
entitled *Sleep Assistance Device*; Application 15/267,464, entitled *Sleep Quality*
Scoring and Improvement; Application 15/267,552, entitled *Intelligent Wake-Up*
10 *System*; Application 15/267,848, entitled *Sleep System*; Application 15/267,858,
entitled *User Interface for a Sleep System*; and Application 15/267,886, entitled *Sleep*
Assessment Using a Home Sleep System, all of which were filed on September 16,
2016. It is also related to U.S. Patent Application _____ {Bose Corporation
attorney docket RS-16-247}, titled *Sleep Assistance Device For Multiple Users*, filed
15 simultaneously with this application, which is incorporated here by reference.

BACKGROUND

[0002] This disclosure relates to earphones for measuring and entraining
respiration.

[0003] Sleeplessness and poor or interrupted sleep may significantly affect a
20 person's health. Poor sleep may be caused by such factors as ambient noise, stress,
medical conditions, or discomfort. Thus, there exists a need for a sleep aid that can
help address the underlying causes of poor sleep without adversely affecting the
user's health in other, unintended ways.

SUMMARY

25 **[0004]** In general, in one aspect, a system includes an earphone including a
loudspeaker, a microphone, a housing supporting the loudspeaker and microphone,
and an ear tip surrounding the housing and configured to acoustically couple both

the loudspeaker and the microphone to an ear canal of a user, and to acoustically close the entrance to the user's ear canal. A processor receives input audio signals from the microphone, detects peaks having a frequency of around 1 Hz in the input audio signals, based on the detected peaks, computes an instantaneous heart rate, measures a frequency of an oscillation within the instantaneous heart rate, and based on the frequency of the oscillation, computes a rate of respiration.

[0005] Implementations may include one or more of the following, in any combination. The processor may measure the frequency of the oscillation within the instantaneous heart rate by computing a fast Fourier transform (FFT) of the instantaneous heart rate. The processor may measure the frequency of the oscillation within the instantaneous heart rate by computing a gradient of the instantaneous heart rate, and computing a fast Fourier transform (FFT) of the gradient of the instantaneous heart rate. The processor may measure the frequency of the oscillation within the instantaneous heart rate by detecting peaks of the instantaneous heart rate. The processor may measure the frequency of the oscillation within the instantaneous heart rate by fitting a sine function to the instantaneous heart rate, the frequency of the sine being the frequency of the oscillation.

[0006] The system may include a second earphone, which would include a second loudspeaker, a second microphone, a second housing supporting the second loudspeaker and second microphone, and a second ear tip surrounding the second housing and configured to acoustically couple both the second loudspeaker and the second microphone to a second ear canal of the user, and to acoustically close the entrance to the user's second ear canal, with the processor receiving second input audio signals from the microphone, and detecting the peaks having a frequency of around 1 Hz by combining the input audio signals from the first microphone with the second input audio signals, and detecting peaks within the result of the combination. Combining the input audio signals may include multiplying the amplitude of the first input audio signals by the amplitude of the second input audio

signal, at each time that the two signals may be sampled. The processor may adjust output audio signals based on the rate of respiration, and provide the output audio signals to the loudspeaker. Adjusting the output audio signals may include adjusting a rhythm of the output audio signals to be about one cycle per minute less than the detected respiration rate. Adjusting the output audio signals may include transitioning the output audio signals from respiration entrainment sounds to masking sounds. Adjusting the output audio signals may include transitioning the output audio signals from masking sounds to awakening sounds. The earphone may include a memory storing sound files, and providing the output audio signals may include retrieving a first sound file from the memory. Adjusting the output audio signals may include retrieving a second sound file from the memory and using the second sound file to generate the output audio signal. The processor may be integrated within the earphone. The processor may be integrated within a portable computing device.

[0007] In general, in one aspect, measuring the respiration rate of a user of an earphone includes receiving input audio signals from a microphone supported by a housing and acoustically coupled to the user's ear canal by an ear tip surrounding the housing and acoustically closing the entrance to the user's ear canal, and in a processor, detecting peaks having a frequency of around 1 Hz in the input audio signals, based on the detected peaks, computing an instantaneous heart rate, measuring a frequency of an oscillation within the instantaneous heart rate, and based on the frequency of the oscillation, computing a rate of respiration.

[0008] Advantages include acoustically sensing the respiration rate at the ear without interference from audio signals being generated by the earphone.

[0009] All examples and features mentioned above can be combined in any technically possible way. Other features and advantages will be apparent from the description and the claims.

BRIEF DESCRIPTION OF THE DRAWINGS

[0010] Figures 1 and 2 show cross-sectional views of earphones with an integrated microphones.

[0011] Figure 3 shows an external view of the system of figure 1 or 2.

5 **[0012]** Figures 4-6 show graphs of sensor readings

DESCRIPTION

[0013] Several of the above-referenced applications describe a bedside system that detects a user's respiration rate and uses that to infer and manage their sleep state. In particular, to assist the user with falling to sleep, the system plays sounds
10 that have a rhythm slightly slower than the user's own respiration rate . This naturally leads the user to slow their breathing to match the rhythm of the sounds, in a process referred to as entrainment. As the user slows their rate of respiration, the rate of the sounds is further reduced, in a feedback loop that leads the user gradually to sleep. Once the user falls asleep (as indicated by artifacts in their
15 respiration rate), the system switches to playing masking sounds, which diminish the user's ability to detect, and be disturbed by, external sounds. If the user is detected to be waking up too early, entrainment may be reactivated. When it is time for the user to wake up, the system may coordinate wake-up sounds with the user's sleep state and other information to wake the user in the least-disruptive way
20 possible.

[0014] Others of the above-referenced applications describe intelligent earplugs which the user can wear while sleeping, and which provide masking sounds through the night, and alarm or alert sounds when needed. These earplugs are controlled by a smartphone, but principally operate autonomously, playing stored masking
25 sounds until instructed otherwise by the controlling phone, or based on an internal clock. It would be advantageous if the intelligent earplugs could play the respiration-entraining sounds of the bedside systems, to help the user fall asleep

without disturbing others who may be sharing the bed or room. One solution to that, described in co-pending application {attorney docket RS-16-247}, is for the sleep system to inform the earplugs of the user's respiration rate and sleep state, and for the earplugs to adjust the rate of a rhythmic component in stored entrainment sounds as in the out-loud system.

[0015] This disclosure describes how to add respiration sensing to the earplugs themselves, so that the external system is not required, and the earplugs can operate fully autonomously, or with only a smart phone to control them.

[0016] As shown in figures 1, 2 and 3, sleep-sensing earphones 100 or 200 include an ear tip sealing structure 102 that blocks, or occludes, the entrance to the ear canal. Figures 1 and 2 show cross-sections of two different earphone examples, while figure 2 shows an exterior view, which is the same for the examples of either figure 1 or 2, for reference. A retaining structure 104 helps retain the earphone in the ear, and puts pressure on the sealing structure 102 to maintain the seal by pushing on the concha, opposite to where the sealing structure meets the ear canal. The sealing structure 102 helps to passively block outside sounds from entering the ear, increasing the effectiveness of the masking sounds played by the earphones.

[0017] Another result of occluding the ear canal is that sounds produced by the body, such as the heartbeat and respiration sounds, are amplified within the ear canal. With the addition of a microphone 106 (figure 1) or 206 (figure 2), the heartbeat can be sensed and its rate determined. The processor 108 on-board each earphone (or in one, if they coordinate their action) can then extract the respiration rate from the heartbeat signal, and adjust the timing of entrainment sounds being played to the user through a speaker 110. In the example of figure 1, the microphone 106 and speaker 110 are shown behind a screen 112, as described in U.S. Patent 9,635,452, which is incorporated here by reference. The microphone may be mounted near or on the speaker 110, or integrated into the speaker housing. In the example of figure 2, the microphone 206 is mounted directly to the PCB 208

and the screen 112 is flat, or may not be needed; the volume inside the earbud is coupled to the ear canal via space around the driver 110. As long as the earbud/ear canal system is effectively sealed at the frequencies of interest, the microphone will detect the targeted sounds coming from inside the ear canal. Other configurations
5 that couple the microphone

[0018] The heartbeat is derived from the microphone signals, and the respiration rate is derived from the heart rate variability. Specifically, as shown in figure 4, the microphone coupled to the occluded ear canal detects heartbeats as energy peaks in a signal with a frequency of around 8-10 Hz (the heart rate itself is around 1 Hz). As
10 this rate is far below the frequency range of the masking sounds, those sounds will not interfere with detecting the heartbeat. If both ears are equipped with microphones, and the signals are transmitted to the smart phone (or from one ear to the other) for analysis, combining the amplitudes of the two signals at each time sample, such as by multiplication, can greatly increase the signal to noise ratio, as
15 shown in figure 5. Applying a peak-finding algorithm to the microphone signal and observing the distance between consecutive peaks yields the beat-to-beat, or instantaneous, heart rate value, shown in figure 6.

[0019] Figure 6 shows that there is a cyclic variability to the instantaneous heart rate. The period of this variability happens to be the respiration rate – as the user
20 inhales, their heart rate increases, and as they exhale, their heart rate decreases. Applying another peak detection step, or other frequency analysis such as a fast Fourier transform (FFT) or fitting a sine to the curve, to the instantaneous heart rate or to its gradient, reveals the respiration rate.

[0020] If the earphones happen to include a feedback-based active noise
25 reduction (ANR) system, to further block environmental sounds, the system microphone of the ANR system would be more than adequate for detecting the sound of blood flow and measuring the heart rate. However, an ANR system is likely to consume a lot of power, and may not be suitable or necessary for sleep-focused

earphones. Since the respiration and heart rate sensing is very narrow-band, a simpler MEMS microphone should be sufficient, and a much lower-power component may be used, benefiting the overall battery life and component size of the earphones. Similarly, it may be possible to use an external device, such as a smartphone, to filter and demodulate the microphone signals to detect the heart rate and extract the respiration rate from it, and to modify the output sounds accordingly, but battery life may be better served by doing all the processing within the earphones. The trade-off between power for processing and power for communication may depend on factors unrelated to the acoustics, including battery size, antenna placement, and memory requirements, to name a few.

[0021] Embodiments of the systems and methods described above comprise computer components and computer-implemented steps that will be apparent to those skilled in the art. For example, it should be understood by one of skill in the art that the computer-implemented steps may be stored as computer-executable instructions on a computer-readable medium such as, for example, hard disks, optical disks, solid-state disks, flash ROMS, nonvolatile ROM, and RAM. Furthermore, it should be understood by one of skill in the art that the computer-executable instructions may be executed on a variety of processors such as, for example, microprocessors, digital signal processors, and gate arrays. For ease of exposition, not every step or element of the systems and methods described above is described herein as part of a computer system, but those skilled in the art will recognize that each step or element may have a corresponding computer system or software component. Such computer system and software components are therefore enabled by describing their corresponding steps or elements (that is, their functionality), and are within the scope of the disclosure.

[0022] A number of implementations have been described. Nevertheless, it will be understood that additional modifications may be made without departing from the scope of the inventive concepts described herein, and, accordingly, other embodiments are within the scope of the following claims.

WHAT IS CLAIMED IS:

1. A system comprising:
an earphone comprising:
a loudspeaker;
a microphone;
a housing supporting the loudspeaker and microphone; and
an ear tip surrounding the housing and configured to acoustically couple both the loudspeaker and the microphone to an ear canal of a user, and to acoustically close the entrance to the user's ear canal;
and
a processor configured to:
receive input audio signals from the microphone;
detect peaks having a frequency of around 1 Hz in the input audio signals;
based on the detected peaks, compute an instantaneous heart rate;
measure a frequency of an oscillation within the instantaneous heart rate;
and
based on the frequency of the oscillation, compute a rate of respiration.
2. The system of claim 1, wherein the processor is configured to measure the frequency of the oscillation within the instantaneous heart rate by computing a fast Fourier transform (FFT) of the instantaneous heart rate.
3. The system of claim 1, wherein the processor is configured to measure the frequency of the oscillation within the instantaneous heart rate by computing a gradient of the instantaneous heart rate; and computing a fast Fourier transform (FFT) of the gradient of the instantaneous heart rate.
4. The system of claim 1, wherein the processor is configured to measure the frequency of the oscillation within the instantaneous heart rate by detecting peaks of the instantaneous heart rate.

5. The system of claim 1, wherein the processor is configured to measure the frequency of the oscillation within the instantaneous heart rate by fitting a sine function to the instantaneous heart rate, the frequency of the sine being the frequency of the oscillation.
6. The system of claim 1, further comprising:
a second earphone comprising:
a second loudspeaker;
a second microphone;
a second housing supporting the second loudspeaker and second microphone; and
a second ear tip surrounding the second housing and configured to acoustically couple both the second loudspeaker and the second microphone to a second ear canal of the user, and to acoustically close the entrance to the user's second ear canal;
wherein the processor is further configured to:
receive second input audio signals from the microphone; and
detect the peaks having a frequency of around 1 Hz by combining the input audio signals from the first microphone with the second input audio signals, and detecting peaks within the result of the combination.
7. The system of claim 6, wherein combining the input audio signals comprises multiplying the amplitude of the first input audio signals by the amplitude of the second input audio signal, at each time that the two signals are sampled.
8. The system of claim 1, wherein the processor is further configured to adjust output audio signals based on the rate of respiration, and provide the output audio signals to the loudspeaker.

9. The system of claim 8, wherein adjusting the output audio signals comprises adjusting a rhythm of the output audio signals to be about one cycle per minute less than the detected respiration rate.
10. The system of claim 8, wherein adjusting the output audio signals comprises transitioning the output audio signals from respiration entrainment sounds to masking sounds.
11. The system of claim 8, wherein adjusting the output audio signals comprises transitioning the output audio signals from masking sounds to awakening sounds.
12. The system of claim 8, wherein the earphone further includes a memory storing sound files; and providing the output audio signals comprises retrieving a first sound file from the memory.
13. The system of claim 12, wherein adjusting the output audio signals comprises retrieving a second sound file from the memory and using the second sound file to generate the output audio signal.
14. The system of claim 1, wherein the processor is integrated within the earphone.
15. The system of claim 1, wherein the processor is integrated within a portable computing device.
16. A method of measuring the respiration rate of a user of an earphone, the method comprising:
receiving input audio signals from a microphone supported by a housing and acoustically coupled to the user's ear canal by an ear tip surrounding the housing and acoustically closing the entrance to the user's ear canal; and
in a processor;

- detecting peaks having a frequency of around 1 Hz in the input audio signals,
based on the detected peaks, computing an instantaneous heart rate,
measuring a frequency of an oscillation within the instantaneous heart rate,
and
based on the frequency of the oscillation, computing a rate of respiration.
17. The method of claim 16, wherein measuring the frequency of the oscillation within the instantaneous heart rate comprises computing a fast Fourier transform (FFT) of the instantaneous heart rate.
18. The method of claim 16, wherein measuring the frequency of the oscillation within the instantaneous heart rate comprises:
computing a gradient of the instantaneous heart rate; and
computing a fast Fourier transform (FFT) of the gradient of the instantaneous heart rate.
19. The method of claim 16, wherein measuring the frequency of the oscillation within the instantaneous heart rate comprises detecting peaks of the instantaneous heart rate.
20. The method of claim 16, wherein measuring the frequency of the oscillation within the instantaneous heart rate comprises fitting a sine function to the instantaneous heart rate, the frequency of the sine being the frequency of the oscillation.
21. The method of claim 16, further comprising:
receiving second input audio signals from a second microphone supported by a second housing and acoustically coupled to the user's second ear canal by a second ear tip surrounding the second housing and acoustically closing the entrance to the user's second ear canal;
in the processor, detecting the peaks having a frequency of around 1 Hz by combining the input audio signals from the first microphone with the

second input audio signals, and detecting peaks within the result of the combination.

22. The method of claim 21, wherein combining the input audio signals comprises multiplying the amplitude of the first input audio signals by the amplitude of the second input audio signal, at each time that the two signals are sampled.
23. The method of claim 16, further comprising, in the processor:
adjusting output audio signals based on the rate of respiration, and
providing the output audio signals to the loudspeaker.

INTERNATIONAL SEARCH REPORT

International application No
PCT/US2018/043061

A. CLASSIFICATION OF SUBJECT MATTER

INV. A61B5/00 A61M21/02 H04R1/10
ADD.

According to International Patent Classification (IPC) or to both national classification and IPC

B. FIELDS SEARCHED

Minimum documentation searched (classification system followed by classification symbols)

A61B A61M H04R

Documentation searched other than minimum documentation to the extent that such documents are included in the fields searched

Electronic data base consulted during the international search (name of data base and, where practicable, search terms used)

EPO-Internal, WPI Data

C. DOCUMENTS CONSIDERED TO BE RELEVANT

Category*	Citation of document, with indication, where appropriate, of the relevant passages	Relevant to claim No.
Y	WO 2010/054863 A1 (SONY ERICSSON MOBILE COMM AB [SE]; HAARTSEN JACOBUS [NL]; SAMPIMON GER) 20 May 2010 (2010-05-20)	1-5, 8-20,23
A	page 1, lines 10-30; claims 1-14; figures 1-3 page 4, line 29 - page 5, line 31 page 8, lines 25-34 ----- -/--	6,7,21, 22



Further documents are listed in the continuation of Box C.



See patent family annex.

* Special categories of cited documents :

"A" document defining the general state of the art which is not considered to be of particular relevance

"E" earlier application or patent but published on or after the international filing date

"L" document which may throw doubts on priority claim(s) or which is cited to establish the publication date of another citation or other special reason (as specified)

"O" document referring to an oral disclosure, use, exhibition or other means

"P" document published prior to the international filing date but later than the priority date claimed

"T" later document published after the international filing date or priority date and not in conflict with the application but cited to understand the principle or theory underlying the invention

"X" document of particular relevance; the claimed invention cannot be considered novel or cannot be considered to involve an inventive step when the document is taken alone

"Y" document of particular relevance; the claimed invention cannot be considered to involve an inventive step when the document is combined with one or more other such documents, such combination being obvious to a person skilled in the art

"&" document member of the same patent family

Date of the actual completion of the international search

27 September 2018

Date of mailing of the international search report

10/10/2018

Name and mailing address of the ISA/

European Patent Office, P.B. 5818 Patentlaan 2
NL - 2280 HV Rijswijk
Tel. (+31-70) 340-2040,
Fax: (+31-70) 340-3016

Authorized officer

Righetti, Marco

INTERNATIONAL SEARCH REPORT

International application No

PCT/US2018/043061

C(Continuation). DOCUMENTS CONSIDERED TO BE RELEVANT

Category*	Citation of document, with indication, where appropriate, of the relevant passages	Relevant to claim No.
Y	AXEL SCHÄFER ET AL: "Estimation of Breathing Rate from Respiratory Sinus Arrhythmia: Comparison of Various Methods", ANNALS OF BIOMEDICAL ENGINEERING, KLUWER ACADEMIC PUBLISHERS-PLENUM PUBLISHERS, NE, vol. 36, no. 3, 11 January 2008 (2008-01-11), pages 476-485, XP019568785, ISSN: 1573-9686 page 476 - page 480 -----	1-5, 8-20,23
A	GB 2 532 745 A (INOVA DESIGN SOLUTIONS LTD [GB]) 1 June 2016 (2016-06-01) paragraphs [0112], [0113], [0124], [0125], [0127]; figure 5 -----	1-23
A	RICHARD SINGHATHIP ET AL: "Extracting Respiration Rate From Raw ECG Signals", BIOMEDICAL ENGINEERING: APPLICATIONS, BASIS AND COMMUNICATIONS = YIXUE-GONGC, WORLD SCIENTIFIC, TW, vol. 22, no. 4, 1 August 2010 (2010-08-01), pages 307-314, XP008169483, ISSN: 1016-2372, DOI: 10.4015/S1016237210002079 page 307 - page 309 -----	1-23
A	KIM J M ET AL: "Two Algorithms for Detecting Respiratory Rate from ECG Signal", IMAGING THE FUTURE MEDICINE : WORLD CONGRESS ON MEDICAL PHYSICS AND BIOMEDICAL ENGINEERING 2006, AUGUST 27 - SEPTEMBER 1, 2006, COEX SEOUL, K; [IFMBE PROCEEDINGS, VOL. 14], SPRINGER, DE, vol. 14, 1 January 2007 (2007-01-01), pages 4069-4071, XP008169469, DOI: 10.1007/978-3-540-36841-0_1030 ISBN: 978-3-540-36839-7 the whole document -----	1-23

INTERNATIONAL SEARCH REPORT

Information on patent family members

International application No

PCT/US2018/043061

Patent document cited in search report		Publication date		Patent family member(s)		Publication date
WO 2010054863	A1	20-05-2010	CN	102215740 A		12-10-2011
			EP	2358264 A1		24-08-2011
			JP	2012508605 A		12-04-2012
			US	2010125218 A1		20-05-2010
			WO	2010054863 A1		20-05-2010

GB 2532745	A	01-06-2016	AU	2015352180 A1		01-06-2017
			BR	112017011073 A2		10-07-2018
			CA	2968319 A1		02-06-2016
			CN	106999048 A		01-08-2017
			EP	3224587 A1		04-10-2017
			GB	2532745 A		01-06-2016
			GB	2535279 A		17-08-2016
			JP	2018504157 A		15-02-2018
			KR	20170086562 A		26-07-2017
			US	2017258329 A1		14-09-2017
			WO	2016083807 A1		02-06-2016

专利名称(译)	耳机，用于测量和调节呼吸		
公开(公告)号	EP3654833A1	公开(公告)日	2020-05-27
申请号	EP2018753505	申请日	2018-07-20
[标]申请(专利权)人(译)	伯斯有限公司		
申请(专利权)人(译)	Bose公司		
当前申请(专利权)人(译)	Bose公司		
[标]发明人	KIRSZENBLAT ROMAIN LIN LIFUN IOFFE MIKHAIL AYERS TEGAN CARBO RANDY MICHAEL		
发明人	KIRSZENBLAT, ROMAIN LIN, LIFUN IOFFE, MIKHAIL AYERS, TEGAN CARBO, RANDY MICHAEL		
IPC分类号	A61B5/00 A61M21/02 H04R1/10		
CPC分类号	A61B5/02438 A61B5/0816 A61B5/6803 A61B5/6817 A61B5/6898 A61M21/02 A61M2021/0027 A61M2205/3375 A61M2205/42 A61M2205/8212 A61M2230/42 H04R1/1016 A61M2021/0061 A61M2021/0083 A61M2021/0088 A61M2205/3303 A61M2205/50 A61M2210/0662 A61M2230/06 H04R1/1041 H04R1/1075 H04R3/005		
优先权	15/655853 2017-07-20 US		
外部链接	Espacenet		

摘要(译)

耳机包括：扬声器，麦克风，支撑扬声器和麦克风的壳体，以及围绕该壳体并配置为将扬声器和麦克风声学地耦合到用户的耳道并在声学上封闭入口的耳塞。用户的耳道。处理器从麦克风接收输入音频信号，基于检测到的峰值，检测输入音频信号中频率约为1 Hz的峰值，计算瞬时心率，测量瞬时心率内的振荡频率，以及根据振荡频率，计算呼吸频率。