

(19)



(11)

EP 3 534 785 B1

(12)

EUROPEAN PATENT SPECIFICATION

(45) Date of publication and mention of the grant of the patent:
18.03.2020 Bulletin 2020/12

(51) Int Cl.:
A61B 5/022 ^(2006.01) **A61B 5/00** ^(2006.01)
A61B 5/11 ^(2006.01)

(21) Application number: **17791110.4**

(86) International application number:
PCT/EP2017/077944

(22) Date of filing: **01.11.2017**

(87) International publication number:
WO 2018/083108 (11.05.2018 Gazette 2018/19)

(54) **A DEVICE COMPRISING A BLOOD PRESSURE SENSOR AND A METHOD FOR CONTROLLING THE DEVICE**

VORRICHTUNG MIT EINEM BLUTDRUCKSENSOR UND VERFAHREN ZUR STEUERUNG DER VORRICHTUNG

DISPOSITIF COMPRENANT UN CAPTEUR DE PRESSION SANGUINE ET PROCÉDÉ DE COMMANDE DU DISPOSITIF

(84) Designated Contracting States:
AL AT BE BG CH CY CZ DE DK EE ES FI FR GB GR HR HU IE IS IT LI LT LU LV MC MK MT NL NO PL PT RO RS SE SI SK SM TR

(72) Inventor: **AELEN, Paul**
5656 AE Eindhoven (NL)

(30) Priority: **07.11.2016 EP 16197456**

(74) Representative: **Smears, Nicholas**
Philips Intellectual Property & Standards
High Tech Campus 5
5656 AE Eindhoven (NL)

(43) Date of publication of application:
11.09.2019 Bulletin 2019/37

(56) References cited:
US-A1- 2007 276 266 US-A1- 2010 049 059
US-A1- 2013 237 865

(73) Proprietor: **Koninklijke Philips N.V.**
5656 AG Eindhoven (NL)

EP 3 534 785 B1

Note: Within nine months of the publication of the mention of the grant of the European patent in the European Patent Bulletin, any person may give notice to the European Patent Office of opposition to that patent, in accordance with the Implementing Regulations. Notice of opposition shall not be deemed to have been filed until the opposition fee has been paid. (Art. 99(1) European Patent Convention).

Description

Technical Field of the Invention

[0001] The invention relates to a device comprising a blood pressure sensor and a method for controlling the device.

Background to the Invention

[0002] Blood pressure (BP), or more precisely, arterial blood pressure, is the pressure exerted by circulating blood on arterial vessel walls. It is one of the key vital signs to establish the well-being of a subject. Since blood pressure is dynamic and changes periodically due the pumping action of the heart, blood pressure is typically described by systolic blood pressure (SBP), which is the maximal blood pressure during the heart cycle, diastolic blood pressure (DBP), which is the minimal blood pressure during the heart cycle, and mean arterial blood pressure (MAP), which is the average blood pressure during the heart cycle.

[0003] In the past, non-invasive blood pressure measurements were typically performed by using a sphygmomanometer, which uses a column of mercury to reflect blood pressure. Nowadays, devices for blood pressure measurements are often cuff-based. The measurement procedure is often automated, especially when the device is not intended for the professional caregiver. The most commonly used and clinically accepted automatic blood pressure measurement uses the oscillometric blood pressure measurement principle. This measurement principle generally consists of placing a cuff around a limb (usually the upper arm) of a subject and inflating it rapidly. After this, cuff pressure is gradually or stepwise decreased, during which the arterial volume oscillations cause small pressure oscillations in the cuff. The diastolic blood pressure (DBP) and the systolic blood pressure (SBP) are estimated from these cuff pressure dependent amplitudes of the cuff pressure or volume oscillations using heuristic algorithms. The mean arterial pressure (MAP) is then usually calculated from the diastolic blood pressure (DBP) and the systolic blood pressure (SBP) using a heuristic formula or by assuming it is equal to the pressure at maximum oscillations. Instead of using the pressure oscillations during deflation, the oscillations can also be measured during inflation.

[0004] Other blood pressure measurement techniques have been developed that do not require an external cuff. This has been possible due to the rapid developments in the mobile device industry (particularly, the smartphone industry), which allow a user to have a plurality of high quality sensors in a single device. For example, a user of a smartphone is now able to perform an oscillometric blood pressure measurement using sensors in a smartphone. WO 2016/096919 A1 discloses an example of a personal hand-held monitor for the measurement of a subject's blood pressure, where a pressure sensor is

embedded in the monitor to provide an electrical signal indicative of the pressure applied to it by a body part of the subject such that the flow of blood in the body part can be detected and a blood pressure measurement provided.

[0005] However, while these recent techniques that eliminate the need for a cuff are more convenient for the user, the blood pressure measurements acquired by these techniques can suffer from inaccuracies due to the effects of hydrostatic pressure. In order to avoid the effects of hydrostatic pressure, blood pressure measurements need to be taken at or close to the level of the heart of the user since any height difference between the blood pressure measurement location and the heart level will result in a hydrostatic offset. If the blood pressure measurements are taken above the level of the heart, the measurement results will be too low, whereas if the blood pressure measurements are taken below the level of the heart, the measurement results will be too high. For every centimetre difference between the blood pressure measurement location and the heart level, 0.73 mm-Hg is erroneously introduced to the blood pressure measurement. Thus, if the blood pressure measurement is taken from a finger while the arm is in a relaxed (i.e. in a hanging position), a height difference of 50 cm can easily be made, which can result in hydrostatic offsets of approximately 37 mmHg. Document US 2013/237865 provides an example of cuff-based blood pressure measurement device and a control method thereof that can calculate the location of a patient's wrist accurately to improve blood pressure measurement accuracy.

[0006] As an untrained user usually takes the blood pressure measurement in the home environment, it is often the case that the blood pressure measurements are taken at heights that are significantly different to the heart level of the user, which can introduce large errors in the blood pressure measurements. This is especially relevant for cuff-less devices, as cuff-less devices do not restrict the counter pressure to be applied at heart level, whereas cuff-based measurements on an upper arm will always be relatively close to the heart level. Therefore, a device aimed at minimising, preventing or eliminating hydrostatic effects to provide more accurate blood pressure measurements is required.

[0007] There is thus a need for an improved device comprising a blood pressure sensor and an improved method for controlling the device.

Summary of the Invention

[0008] As noted above, the limitation with existing approaches is that errors can be introduced into blood pressure measurements due to hydrostatic effects. It would thus be valuable to have a device comprising a blood pressure sensor and a method for controlling the device in a manner that overcomes these existing problems.

[0009] Therefore, according to a first aspect of the invention, there is provided a method for controlling a de-

vice comprising a blood pressure sensor for sensing blood pressure. The method comprises determining an angle of the device with respect to the direction of gravity, identifying a location of one or more features of the user holding the device, determining a height of the blood pressure sensor relative to a heart level of the user based on the determined angle of the device with respect to the direction of gravity and the identified location of the one or more features of the user, and controlling the device based on the determined height of the blood pressure sensor relative to the heart level of the user.

[0010] In some embodiments, the one or more features of the user holding the device may comprise one or more anatomical features of the user holding the device. In some embodiments, the location of the one or more features may be identified in a displayed image of the user. In some embodiments, the location of the one or more features may be identified relative to a displayed predefined location range. In these embodiments, the height of the blood pressure sensor relative to a heart level of the user may be determined based on the determined angle of the device with respect to the direction of gravity and the identified location of the one or more features of the user in the image relative to the predefined location range.

[0011] In some embodiments, the height of the blood pressure sensor may be determined to be different to the heart level of the user where the determined angle of the device with respect to the direction of gravity is outside a predefined angle range and/or the identified location of the one or more features of the user is outside a predefined location range.

[0012] In some embodiments, the height of the blood pressure sensor may be determined to be at the heart level of the user where the determined angle of the device with respect to the direction of gravity is within a predefined angle range and/or the identified location of the one or more features of the user is within a predefined location range.

[0013] In some embodiments, controlling the device based on the determined height of the blood pressure sensor may comprise controlling the device to output to the user one or more of the determined angle of the device with respect to the direction of gravity and the identified location of the one or more features of the user when the height of the blood pressure sensor is determined to be different to the heart level of the user.

[0014] In some embodiments, controlling the device based on the determined height of the blood pressure sensor may comprise controlling the device to output to the user an instruction to adjust one or more of the angle of the device with respect to the direction of gravity and the location of the one or more features of the user when the height of the blood pressure sensor is determined to be different to the heart level of the user.

[0015] In some embodiments, controlling the device based on the determined height of the blood pressure sensor may comprise controlling the device to output to

the user an error notification when the height of the blood pressure sensor is determined to be different to the heart level of the user.

[0016] In some embodiments, controlling the device based on the determined height of the blood pressure sensor may comprise controlling the blood pressure sensor to acquire a blood pressure measurement from the user when the height of the blood pressure sensor is determined to be at the heart level of the user.

[0017] In some embodiments, controlling the device based on the determined height of the blood pressure sensor may comprise controlling the blood pressure sensor to acquire a blood pressure measurement from the user when the height of the blood pressure sensor is determined to be different to the heart level of the user, and adjusting the acquired blood pressure measurement based on the difference between the height of the blood pressure sensor and the heart level of the user.

[0018] In some embodiments, the one or more features of the user may comprise any one or more of one or both eyes of the user, the mouth of the user, the nose of the user, and the facial outline of the user.

[0019] According to a second aspect of the invention, there is provided a computer program product comprising a computer readable medium, the computer readable medium having computer readable code embodied therein, the computer readable code being configured such that, on execution by a suitable computer or processor, the computer or processor is caused to control a device comprising a blood pressure sensor for sensing blood pressure by implementing the method or the methods described above.

[0020] According to a third aspect of the invention, there is provided a device comprising a blood pressure sensor for acquiring a blood pressure measurement from a user holding the device and a control unit. The control unit is configured to determine an angle of the device with respect to the direction of gravity, identify a location of one or more features of the user holding the device, determine a height of the blood pressure sensor relative to a heart level of the user based on the determined angle of the device with respect to the direction of gravity and the identified location of the one or more features of the user, and control the device based on the determined height of the blood pressure sensor relative to the heart level of the user.

[0021] In some embodiments, the one or more features of the user holding the device may comprise one or more anatomical features of the user holding the device. In some embodiments, the location of the one or more features may be identified in a displayed image of the user. In some embodiments, the location of the one or more features may be identified relative to a displayed predefined location range. In these embodiments, the height of the blood pressure sensor relative to a heart level of the user may be determined based on the determined angle of the device with respect to the direction of gravity and the identified location of the one or more features of

the user in the image relative to the predefined location range.

[0022] In some embodiments, the device may further comprise an angular sensor and the control unit may be configured to control the angular sensor to determine the angle of the device with respect to the direction of gravity.

[0023] In some embodiments, the device may further comprise a camera and the control unit may be configured to control the camera to identify the location of the one or more features of the user when the user is, at least partially, in the field of view of the camera.

[0024] In some embodiments, the device may further comprise a user interface and, when the height of the blood pressure sensor is determined to be different to the heart level of the user, the control unit may be configured to control the user interface to output to the user any one or more of the determined angle of the device with respect to the direction of gravity, the identified location of the one or more features of the user, an instruction to adjust any one or more of the angle of the device with respect to the direction of gravity, the location of the one or more features of the user, and an angle of the body of the user, and an error notification.

[0025] In some embodiments, the blood pressure sensor may comprise any one or more of a volume sensor and a pressure sensor.

[0026] According to the aspects and embodiments described above, the limitations of existing techniques are addressed. In particular, according to the above-described aspects and embodiments, hydrostatic effects in blood pressure measurements can be prevented, reduced, or eliminated. In this way, more accurate blood pressure measurements can be acquired by way of a simple yet effective method.

[0027] There is thus provided an improved device comprising a blood pressure sensor and an improved method for controlling the device, which overcomes the existing problems. The invention is defined by appended claims 1-15.

Brief Description of the Drawings

[0028] For a better understanding of the invention, and to show more clearly how it may be carried into effect, reference will now be made, by way of example only, to the accompanying drawings, in which:

Figure 1 is a block diagram of a device according to an embodiment;

Figure 2 is a flow chart illustrating a method according to an embodiment; and

Figure 3 is an illustration of a device in use according to an embodiment.

Detailed Description of the Preferred Embodiments

[0029] As noted above, the invention provides an improved device comprising a blood pressure sensor and an improved method for controlling the device, which overcomes the existing problems.

[0030] **Figure 1** shows a block diagram of a device 100 according to an embodiment. In some embodiments, the device 100 may be a device dedicated for blood pressure measurements. In other words, the device 100 can be a blood pressure measurement device. Alternatively, in some embodiments, in addition to blood pressure measurements, the device 100 may also be intended for other purposes or uses. The device 100 may be a mobile device. For example, the device 100 can be a smart phone, a tablet, a smart watch, or any other mobile device.

[0031] As illustrated in **Figure 1**, the device 100 comprises a blood pressure sensor 102 for sensing blood pressure (or for acquiring a blood pressure measurement) from a user holding the device 100. In operation, to acquire a blood pressure measurement, the user holds the device 100 (for example, in front of them) such that a part of the body of the user (for example, a finger or thumb of the user) is positioned at or contacts with the blood pressure sensor 102. The part of the body of the user may be in direct contact with the blood pressure sensor 102 or indirect contact with the blood pressure sensor 102.

[0032] In some embodiments, the user may be instructed (such as via a user interface of the device 100) to increase the pressure applied by the part of the body that is in contact with the blood pressure sensor 102. For example, the user may be instructed to increase the pressure applied by the part of the body that is in contact with the blood pressure sensor 102 by a pressure profile generated over time, which the user can follow by increasing the applied pressure. Examples of a pressure profile include, but are not limited to, a numerical target that increases over time, a line or bar that becomes increasingly full as pressure is increased with target pressures at one or more points in time, or any other pressure profile.

[0033] The blood pressure sensor 102 of the device 100 can comprise any sensor, or any combination or sensors, suitable to acquire a blood pressure measurement from a user holding the device 100. The blood pressure measurement may, for example, be acquired from arterial oscillations detected by the blood pressure sensor 102. An increase in pressure applied by the part of the body of the user that is in contact with the blood pressure sensor 102 can result in arterial oscillations, which can then be detected by the blood pressure sensor 102. The blood pressure sensor 102 can comprise any one or more of a volume sensor, a pressure sensor, or any other sensor, or any combination of sensors, suitable to acquire a blood pressure measurement from a user holding the device 100.

[0034] A volume sensor can comprise any volume sensor that is suitable to detect arterial oscillations (specifi-

cally, volumetric oscillations) from the part of the body of the user that is positioned at the volume sensor of the device 100, which can be used to acquire a blood pressure measurement. Examples of a volume sensor include, but are not limited to, a light sensor, or any other volume sensor, or any combination of volume sensors. A light sensor can comprise any light sensor that is suitable to detect light indicative of volumetric oscillations from a user holding the device 100, which can be used to acquire a blood pressure measurement. For example, a light sensor can comprise an image sensor, a plethysmography (PG) sensor (such as a photoplethysmography (PPG) sensor), or any other light sensor, or any combination of light sensors.

[0035] An image sensor can comprise any image sensor that is suitable to acquire an image from a user holding the device 100, which can be used to acquire a blood pressure measurement. Examples of an image sensor include, but are not limited to, a camera, a video recording device, or any other image sensor, or any combination of image sensors. The image may comprise a single image frame or a plurality of image frames. For example, the plurality of image frames may be in the form of a "live", instantaneous, or real-time (or near real-time) series of image frames or video of the user holding the device. The image acquired by the image sensor can be indicative of arterial oscillations (specifically, volumetric oscillations) in the part of the body of the user that is in the image. In some embodiments, for example, the image acquired by the image sensor may be averaged to acquire a volume measurement.

[0036] A photoplethysmography (PPG) sensor can comprise any photoplethysmography sensor suitable to acquire photoplethysmographic data from the user holding the device 100, which can be used to acquire a blood pressure measurement. Examples of a photoplethysmography sensor include, but are not limited to, a reflective PPG sensor, a transmissive PPG sensor, or any other photoplethysmography sensor, or any combination of photoplethysmography sensors. The photoplethysmographic data acquired by the photoplethysmography sensor can be indicative of arterial oscillations (specifically, volumetric oscillations) in the part of the body of the user that is positioned at the photoplethysmography sensor of the device 100.

[0037] In some embodiments, a light sensor (such as a PPG sensor) can comprise a light source (for example, a white light emitting diode LED, a single wavelength light such as a light emitting in the red region, or any other light source) and an associated light detector. For example, in some embodiments, a light source may be operable to project light onto a part of the body of the user holding the device 100 and the light detector may be operable to detect transmitted or reflected light. The light detected by the light detector can be indicative of arterial oscillations (specifically, volumetric oscillations) in the part of the body of the user onto which light is projected.

[0038] A pressure sensor can comprise any pressure

sensor that is suitable to acquire the applied pressure and the arterial oscillations (specifically, pressure oscillations) from a part of the body of the user that is in direct or indirect contact with the pressure sensor of the device 100, which can be used to acquire a blood pressure measurement. Examples of a pressure sensor include, but are not limited to, a pressure sensitive display, a pressure sensitive element below a display (such as a foil, thin-film flexible printed circuit, or similar), a force sensor where a contact area of the force sensor with a part of the body of the user is known (for example, assumed to be constant) or can be measured, or any other pressure sensor, or any combination of pressure sensors. The pressure oscillations can be determined from the force detected by a force sensor where the contact area is known or measured since pressure is equal to the force per unit area. In some embodiments, a pressure sensor can comprise multiple force sensors integrated over an area.

[0039] A force sensor can comprise any force sensor suitable to detect a force applied by the user holding the device 100, which can be used to acquire a blood pressure measurement. Examples of a force sensor include, but are not limited to, a force sensitive display, a force sensitive element below a display (such as a foil, thin-film flexible printed circuit, or similar), a strain gauge, a load cell (for example, a structure comprising multiple strain gauges, or any other force sensor, or any combination of force sensors).

[0040] Although examples have been provided for the blood pressure sensor 102, it will be understood that any other blood pressure sensor, or any combination of blood pressure sensors, suitable to acquire a blood pressure measurement from the user can be used.

[0041] As illustrated in Figure 1, the device 100 also comprises a control unit 104. The control unit 104 controls the operation of the device 100 and can implement the method describe herein. The control unit 104 can comprise one or more processors, processing units, multi-core processors or modules that are configured or programmed to control the device 100 in the manner described herein. In particular implementations, the control unit 104 can comprise a plurality of software and/or hardware modules that are each configured to perform, or are for performing, individual or multiple steps of the method according to embodiments of the invention.

[0042] Briefly, the control unit 104 is configured to determine an angle of the device with respect to the direction of gravity, identify a location of one or more features of the user holding the device, determine a height of the blood pressure sensor relative to a heart level of the user based on the determined angle of the device with respect to the direction of gravity and the identified location of the one or more features of the user, and control the device based on the determined height of the blood pressure sensor relative to the heart level of the user.

[0043] In some embodiments, as illustrated in Figure 1, the device 100 can further comprise an angular sensor

106. Examples of an angular sensor include, but are not limited to, an accelerometer or gravitational sensor (such as a single-axis accelerometer, a dual-axis accelerometer, or a three-axis accelerometer), a gyroscope, a tilt-sensor, or any other angular sensor, or any combination of angular sensors. The angular sensor 106 can be for use in determining the angle of the device with respect to the direction of gravity. For example, in embodiments where the device 100 comprises an angular sensor 106, the control unit 104 can be configured to control the angular sensor 106 to determine the angle of the device with respect to the direction of gravity.

[0044] In some embodiments, as illustrated in Figure 1, the device 100 can further comprise a camera 108. The camera 108 can be for use in identifying the location of the one or more features of the user when the user is, at least partially, in the field of view of the camera 108. For example, the control unit 104 can be configured to control the camera 108 to identify the location of the one or more features of the user when the user is, at least partially, in the field of view of the camera 108. The camera 108 can be any camera that is directed at the user. Thus, alternatively or in addition to the device comprising a camera 108, a camera 108 may be external to (i.e. separate to or remote from) the device 100.

[0045] In some embodiments, as illustrated in Figure 1, the device 100 can further comprise a user interface 110. Alternatively or in addition, a user interface 110 may be external to (i.e. separate to or remote from) the device 100. A user interface 100 can be for use in providing a user of the device 100 with information, data, signals, or measurements resulting from the method according to the invention. For example, the control unit 104 can be configured to control a user interface 110 to provide (for example, render, output, or display) information, data, signals, or measurements resulting from the method to the user of the device 100.

[0046] In some embodiments, the control unit 104 may be configured to control a user interface 110 to display an image of the user. As mentioned earlier, the image may comprise a single image frame or a plurality of image frames. For example, the control unit 104 may be configured to control the user interface 110 to display a "live", instantaneous, or real-time (or near real-time) series of image frames or video of the user holding the device 100. The control unit 104 may also be configured to control the user interface 110 to display a predefined location range for the one or more features of the user. For example, the predefined location range may be displayed over or through the image of the user. In some embodiments, the image of the user and the predefined location range may be displayed on the device 100 comprising the blood pressure sensor 102. Alternatively, in other embodiments, the image of the user and the predefined location range may be displayed on a device that is a different device to the device 100 that comprises the blood pressure sensor 102. For example, the device on which the image of the user and the predefined location range

are displayed may be external to (i.e. separate to or remote from) the device 100 comprising the blood pressure sensor 102.

[0047] In some embodiments, for example, the control unit 104 can be configured to control a user interface 110 to provide (for example, render, output, or display) to the user one or more blood pressure measurements acquired by the blood pressure sensor 102 of the device 100. Alternatively or in addition, in some embodiments, when the control unit 104 of the device 100 determines that the height of the blood pressure sensor 102 is different to the heart level of the user, the control unit 104 can be configured to control a user interface 110 to provide (for example, render, output, or display) to the user any one or more of the determined angle of the device with respect to the direction of gravity, the identified location of the one or more features of the user, an instruction to adjust one or more of the angle of the device with respect to the direction of gravity and the location of the one or more features of the user, an error notification, or any other information resulting from the method described herein.

[0048] Alternatively or in addition, a user interface 110 may be configured to receive a user input. In other words, a user interface 110 may allow a user of the device 100 to manually enter instructions, data, or information. The control unit 104 may be configured to acquire a user input from the user interface 110.

[0049] A user interface 110 may be any user interface that enables rendering (or output or display) of information, data, signals, or measurements to a user of the device 100. Alternatively or in addition, a user interface 110 may be any user interface that enables a user of the device 100 to provide a user input, interact with and/or control the device 100. For example, a user interface 110 may comprise one or more switches, one or more buttons, a keypad, a keyboard, a touch screen or an application (for example, on a smartphone, tablet, or similar), a display screen, a graphical user interface GUI or any other visual rendering component, one or more speakers, one or more microphones or any other audio component, one or more lights, a component for providing tactile feedback (such as a vibration function), or any other user interface component, or combination of user interface components.

[0050] Although not illustrated in Figure 1, in some embodiments, the device 100 may also comprise a memory configured to store program code that can be executed by the control unit 104 to perform the method described herein. The memory can be used to store information, data, signals and measurements acquired or made by the control unit 104 of the device 100. For example, the memory may be used to store blood pressure measurements acquired by the blood pressure sensor 102 from the user of the device 100.

[0051] Although not illustrated in Figure 1, in some embodiments, the device 100 may also comprise a communications interface for enabling the device 100 to com-

municate with any sensors, interfaces, units, memories, devices or any other components that are internal or external to the device 100. The communications interface may communicate with any sensors, interfaces, units, memories, devices or any other components wirelessly or via a wired connection. For example, in an embodiment where the camera 108 is external to the device 100, the communications interface may communicate with the external camera 108 wirelessly or via a wired connection. Similarly, in an embodiment where a user interface 110 is external to the device 100, the communications interface may communicate with the external user interface wirelessly or via a wired connection.

[0052] Thus, it will be appreciated that Figure 1 only shows the components required to illustrate this aspect of the invention, and in a practical implementation the device 100 may comprise additional components to those shown. For example, the device 100 may comprise a battery or other power supply for powering the device 100 or means for connecting the device 100 to a mains power supply.

[0053] Figure 2 illustrates a method 200 for controlling the device 100 comprising the blood pressure sensor 102. The illustrated method 200 can generally be performed by or under the control of the control unit 104 of the device 100.

[0054] As mentioned previously, in operation, the user holds the device 100 (for example, in front of them) such that a part of the body of the user (for example, a finger or thumb of the user) is positioned at or contacts with the blood pressure sensor 102. In some embodiments, although not illustrated, the position of the part of the body of the user on the device may be detected to ensure that the user is holding the device 100 correctly. For example, where the blood pressure sensor 102 comprises a camera and a display (such as a force or pressure sensitive display) of the device 100, the user may place a finger (such as an index finger) of a hand in front of the camera and a thumb of the hand on the display for the blood pressure measurement. The position of the thumb on the display can be measured and the camera can be used to detect the position of the finger to ensure that the user is holding the device 100 correctly. Alternatively or in addition, in some embodiments, the blood pressure sensor 102 may be located at one or more fixed points on the device 100, which can be indicated to the user. For the purpose of the method disclosed herein, it may be assumed that the device 100 is held approximately or exactly perpendicular to the body of the user.

[0055] With reference to Figure 2, at block 202, an angle of the device 100 is determined with respect to the direction of gravity (or compared to the ground level or earth). For example, as mentioned earlier, the control unit 104 can be configured to control an angular sensor 106 of the device 100 to determine the angle of the device with respect to the direction of gravity. In some embodiments, the angle of the body of the user may be inferred from the angle of the device 100 with respect to the di-

rection of gravity.

[0056] As an angular sensor can measure gravitational force, the gravitational force component on the angular sensor can be used to determine the angle of the device 100 with respect to gravity. As mentioned earlier, the angular sensor can comprise an accelerometer (such as a single-axis accelerometer, a dual-axis accelerometer, a three-axis accelerometer), a gyroscope, a tilt-sensor, or similar and thus the angle of the device 100 with respect to gravity can be determined in any of the standard ways in respect of these angular sensors. For example, as is known, the acceleration due to gravity can be measured and related back to the reference frame of the device 100 to determine the angle of the device 100 with respect to gravity.

[0057] At block 204, a location of one or more features (or landmarks) of the user holding the device 100 are identified. For example, as mentioned earlier, the control unit 104 can be configured to control a camera 108 of the device 100 to identify the location of the one or more features of the user when the user is (at least partially) in the field of view of the camera 108. The one or more features of the user can comprise one or more anatomical (e.g. physical) features of the user. In some embodiments, the one or more features of the user may comprise one or more features of the torso (or upper torso) of the user, such as one or more shoulders of the user, or any other features of the torso of the user, or any combination of features of the torso of the user. Alternatively or in addition, in some embodiments, the one or more features of the user may comprise the neck of the user. Alternatively or in addition, in some embodiments, the one or more features of the user may comprise one or more facial features of the user, for example, any one or more of the facial outline of the user, one or both eyes of the user, the nose of the user, the mouth of the user, or any other facial features of the user, or any combination of facial features of the user. Although examples have been provided for the one or more features of the user, the person skilled in the art will be aware of other features of the user, or any combination of features of the user, that may be used.

[0058] In some embodiments, the method may further comprise determining the distance of the device 100 with respect to the body based on the size, location, or both the size and location, of the one or more features. The distance may, for example, be determined as a horizontal distance. The distance can be indicative of the amount an arm of the user is stretched while holding the device 100 and can be used to improve the measurement of height of the device relative to the heart level. The distance may, for example, be determined based on the apparent size of the one or more features identified by the camera 108. For example, the larger a feature appears, the closer the feature is to the camera 108 (which can be indicative of a bent arm) and, similarly, the smaller a feature appears, the farther the feature is from the camera 108 (which can be indicative of a straight arm).

[0059] At block 206, a height of the blood pressure sensor 102 relative to a heart level of the user is determined based on the determined angle of the device 100 with respect to the direction of gravity and the identified location of the one or more features of the user.

[0060] In some embodiments, the method comprises determining whether the determined angle of the device 100 with respect to the direction of gravity is within (or outside) a predefined angle range. In other words, it may be determined whether the determined angle of the device 100 with respect to the direction of gravity is between (or falls outside) a minimum threshold value for the angle and a maximum threshold value for the angle. The predefined angle range (or minimum and maximum threshold values for the angle) can be set to indicate that the device 100 is held upright or substantially upright. In one example, the predefined angle range is between -30 degrees and +30 degrees. However, it will be understood that other predefined angles may be used instead. Similarly, in some embodiments, the method may further comprise determining whether the identified location of the one or more features of the user is within (or outside) a predefined location range. For example, the predefined location range may be a predefined location range on a display of the device 100 comprising the blood pressure sensor 102 or another device. The predefined location range on the display may be defined by one or more lines or shapes.

[0061] In these embodiments, the height of the blood pressure sensor 102 may be determined to be different to the heart level of the user where the determined angle of the device with respect to the direction of gravity is outside a predefined angle range, the identified location of the one or more features of the user is outside a predefined location range, or both the determined angle of the device with respect to the direction of gravity is outside a predefined angle range and the identified location of the one or more features of the user is outside a predefined location range.

[0062] Similarly, the height of the blood pressure sensor may be determined to be at the heart level of the user where the determined angle of the device with respect to the direction of gravity is within a predefined angle range, the identified location of the one or more features of the user is within a predefined location range, or both the determined angle of the device with respect to the direction of gravity is within a predefined angle range and the identified location of the one or more features of the user is within a predefined location range.

[0063] Thus, in some embodiments, both of the described parameters (namely, the parameters of the determined angle of the device 100 with respect to the direction of gravity and the identified location of the one or more anatomical features of the user in the image relative) may be checked. If one or both of these parameters are outside their respective predefined ranges, the height of the blood pressure sensor 102 may be determined to be different to the heart level of the user (which may, for

example, be a height that is inappropriate or less than optimal for blood pressure measurements). On the other hand, if one or both of these parameters are within their respective predefined ranges, the height of the blood pressure sensor 102 may be determined to be at the heart level of the user (which may, for example, be a height that is appropriate or optimal for blood pressure measurements).

[0064] In embodiments in which the distance of the device 100 with respect to the body is determined based on the location of the one or more features, the determination of the height of the blood pressure sensor 102 relative to the heart level of the user may be further based on this determined distance. In this way, the height of the blood pressure sensor 102 relative to the heart level may be determined more precisely, or an absolute deviation of the height of the blood pressure sensor 102 from the heart level (for example, in centimetres) may be determined.

[0065] Figure 3 is an illustration of the device 100 in use by a user 300 according to an embodiment. As illustrated in Figure 3, an angular sensor is used to determine the angle that the device 100 makes relative to the direction of gravity and a camera is used to identify the location of one or more features of the user 300 when the user 300 is (at least partially) in the field of view 302 of the camera.

[0066] In this illustrated example embodiment, an image of the user and a predefined location range 306 is displayed on a display 308 of the device 100 comprising the blood pressure sensor 100. However, as described earlier, the image of the user and the predefined location range 306 may instead be displayed on a display of a device 100 that is a different device to the device 100 comprising the blood pressure sensor 100 according to other example embodiments. The predefined location range 306 defines a location range on the display 308 of the device 100 for the user to align one or more of their features (such as any of those mentioned earlier). In the example embodiment shown in Figure 3, the one or more features of the user are the eyes 304 of the user. Thus, in the example embodiment shown in Figure 3, the location of the eyes 304 of the user relative to the predefined location range 306 of the display 308 of the device 100 are identified (at block 204 of Figure 2). As described above, a height of the blood pressure sensor of the device 100 relative to a heart level 310 of the user 300 can be determined (at block 206 of Figure 2) based on the determined angle of the device 100 with respect to the direction of gravity and the identified location of the one or more features of the user 300.

[0067] Through the determined height of the blood pressure sensor 102 relative to the heart level of the user, the combination of the determined angle of the device 100 with respect to the direction of gravity and the identified location of one or more features of the user holding the device 100 (or the combination of an angular sensor and a camera) can be used to control the device 100 to

ensure that hydrostatic effects are minimised or eliminated. Thus, returning back to Figure 2, at block 208, the device 100 is controlled based on the determined height of the blood pressure sensor 102 relative to the heart level of the user. The device 100 can be controlled based on the determined height of the blood pressure sensor 102 relative to the heart level of the user in a variety of ways.

[0068] In some embodiments, when the height of the blood pressure sensor is determined to be at the heart level of the user, the blood pressure sensor 102 of the device 100 may be controlled to acquire a blood pressure measurement from the user.

[0069] In some embodiments, when the height of the blood pressure sensor 102 is determined to be different to the heart level of the user, the device 100 may be controlled to output to the user one or more of the determined angle of the device 100 with respect to the direction of gravity and the identified location of the one or more features of the user (such as via a user interface 110, which can be a user interface of the device or a user interface external to the device). In some embodiments, the predefined angle range, the predefined location range, or both the predefined angle range and the predefined location range may also be output to the user (such as via a user interface 110, which can be a user interface of the device or a user interface external to the device). In this way, information is provided that enables the user to ensure that the device 100 is positioned to avoid hydrostatic effects such that an accurate blood pressure measurement can be acquired from the blood pressure sensor 102.

[0070] Alternatively or in addition, in some embodiments, when the height of the blood pressure sensor 102 is determined to be different to the heart level of the user, the device 100 may be controlled to output to the user an instruction to adjust any one or more of the angle of the device 100 with respect to the direction of gravity, the location (for example, the height) of the one or more features of the user, and the angle of the body (or posture) of the user. As mentioned earlier, the angle of the body of the user may be inferred from the angle of the device 100 with respect to the direction of gravity. The device 100 may be controlled to output the instruction to the user via a user interface 110, which can be a user interface of the device or a user interface external to the device.

[0071] The instruction may be, for example, an instruction to move the device 100 in a certain direction, an instruction to tilt the device 100 in a certain direction, an instruction to alter the angle of the body (or posture) of the user, or any combination of these instructions. In some embodiments, an instruction may be output whenever the height of the blood pressure sensor 102 is determined to be different to the heart level of the user. For example, in some embodiments, an instruction may be output whenever the determined angle of the device 100 with respect to the direction of gravity is outside the predefined angle range, the identified location of the one or

more features of the user is outside the predefined location range, or both the determined angle of the device 100 with respect to the direction of gravity is outside the predefined angle range and the identified location of the one or more features of the user is outside the predefined location range. In this way, feedback can be provided to the user to guide the user to position the device 100 at (or near or closer to) the heart level of the user at the appropriate orientation to reduce or eliminate hydrostatic effects.

[0072] Alternatively or in addition, in some embodiments, when the height of the blood pressure sensor is determined to be different to the heart level of the user, the device 100 may be controlled to output to the user an error notification (such as via a user interface 110, which can be a user interface of the device or a user interface external to the device). The error notification may, for example, indicate that a blood pressure measurement is false, incorrect, or has not been determined.

[0073] In some embodiments, an error notification may be output whenever the height of the blood pressure sensor 102 is determined to be different to the heart level of the user. For example, in some embodiments, an error notification may be output whenever the determined angle of the device 100 with respect to the direction of gravity is outside the predefined angle range, the identified location of the one or more features of the user is outside the predefined location range, or both the determined angle of the device 200 with respect to the direction of gravity is outside the predefined angle range and the identified location of the one or more features of the user is outside the predefined location range. In this way, the user can be guided to position the device 100 differently until the device 100 is at (or near) the heart level of the user at the appropriate orientation to reduce or eliminate hydrostatic effects.

[0074] In some embodiments, the error notification may be output where the angle of the device 100 with respect to the direction of gravity is more than a predefined threshold value. For example, the predefined threshold value may be at or around 90 degrees to prevent blood pressure measurements being acquired when the user is laying down (since, as mentioned earlier, the angle of the body of the user may be inferred from the angle of the device 100 with respect to the direction of gravity).

[0075] Alternatively or in addition, in some embodiments, when the height of the blood pressure sensor 102 is determined to be different to the heart level of the user, the blood pressure sensor 102 of the device 100 may be controlled to acquire a blood pressure measurement from the user. In these embodiments, the acquired blood pressure measurement can then be adjusted based on the difference between the height of the blood pressure sensor and the heart level of the user.

[0076] The difference between the height of the blood pressure sensor and the heart level of the user can be determined as an absolute height difference. In some

embodiments, for example, the difference between the height of the blood pressure sensor and the heart level of the user may be determined based on the location of the one or more features of the user holding the device in relation to a target location for the one or more features of the user for the blood pressure sensor 102 of the device 100 to be positioned at the heart level of the user. The height difference may be determined as the number of pixels between the identified location of the one or more features of the user holding the device and the target location for the one or more features. In some embodiments, a scaling factor may be used to relate the number of pixels to a distance measurement (for example, centimetres) for the height difference. For example, where a feature of the user is located six pixels below the target location for that feature, the height difference may be determined as six pixels times the scaling factor.

[0077] In embodiments where the distance of the device 100 with respect to the body is determined based on the location of the one or more features, the determined distance may also be used in the determination of the height difference. For example, the scaling factor can be made dependent on the determined distance of the device 100 with respect to the body.

[0078] The error that is made in a blood pressure measurement with hydrostatic effects is based on the difference between the height of the blood pressure sensor and the heart level of the user. Thus, adjustment of the acquired blood pressure measurement can comprise determining the hydrostatic offset from the determined difference between the height of the blood pressure sensor and the heart level of the user. Then, the determined hydrostatic offset can be used to remove hydrostatic effects from the acquired blood pressure measurement. For example, where the determined difference between the height of the blood pressure sensor and the heart level of the user indicates that the blood pressure sensor is above the heart level over the user, the determined hydrostatic effect is removed from the acquired blood pressure measurement by adding the hydrostatic offset to the acquired blood pressure measurement. Similarly, where the determined difference between the height of the blood pressure sensor and the heart level of the user indicates that the blood pressure sensor is below the heart level over the user, the determined hydrostatic effect is removed from the acquired blood pressure measurement by subtracting the hydrostatic offset to the acquired blood pressure measurement.

[0079] The hydrostatic offset in an acquired blood pressure measurement is approximately 0.75 mmHg per cm of height difference between the height of the blood pressure sensor and the heart level of the user. Thus, for example, where the blood pressure sensor 102 is determined to be 10 cm above the heart level of the user, the acquired blood pressure measurement can be adjusted by adding $10 \times 0.75 = 7.5$ mmHg to the acquired blood pressure measurement. In this way, any hydrostatic effects that would otherwise distort the acquired blood

pressure measurement can be compensated (or corrected) to thus provide a more accurate blood pressure measurement.

[0080] In any of the embodiments where the blood pressure sensor 102 of the device 100 is controlled to acquire a blood pressure measurement from the user, the blood pressure measurement may be acquired from the user using any suitable technique for acquiring a blood pressure measurement. As mentioned earlier, the blood pressure measurement may be acquired from arterial oscillations detected by the blood pressure sensor 102. The arterial oscillations can comprise volumetric oscillations, pressure oscillations, or both volumetric and pressure oscillations. The arterial oscillations can be detected as a function of applied pressure. In these embodiments, the arterial oscillations versus applied pressure can be processed using standard techniques to acquire the blood pressure measurement (such as any one or more of a value for the systolic blood pressure, the diastolic blood pressure, and mean arterial blood pressure).

[0081] In any of the embodiments in which a blood pressure measurement is acquired, the method may further comprise providing (for example, rendering, outputting, or displaying) the acquired blood pressure measurement to the user. For example, as mentioned earlier, the control unit 104 may control a user interface 110 (which may be a user interface of the apparatus 100 or a user interface external to the device) to provide (for example, render, output, or display) to the user the acquired blood pressure measurement.

[0082] There is therefore provided an improved device comprising a blood pressure sensor and an improved method for controlling the device. As described herein, the device can be controlled in a manner that can help to reduce, prevent, or eliminate hydrostatic effects in blood pressure measurements. In this way, more accurate blood pressure measurements can be acquired by way of a simple yet effective method.

[0083] There is also provided a computer program product comprising a computer readable medium, the computer readable medium having computer readable code embodied therein. The computer readable code is configured such that, on execution by a suitable computer or processor, the computer or processor is caused to perform the method or methods described herein.

[0084] The invention is defined by appended claims 1-15. In the claims, the word "comprising" does not exclude other elements or steps, and the indefinite article "a" or "an" does not exclude a plurality. A single processor or other unit may fulfil the functions of several items recited in the claims. The mere fact that certain measures are recited in mutually different dependent claims does not indicate that a combination of these measures cannot be used to advantage. A computer program may be stored/distributed on a suitable medium, such as an optical storage medium or a solid-state medium supplied together with or as part of other hardware, but may also

be distributed in other forms, such as via the Internet or other wired or wireless telecommunication systems. Any reference signs in the claims should not be construed as limiting the scope.

Claims

1. A method (200) for controlling a device (100) comprising a blood pressure sensor (102) for sensing blood pressure, the method comprising:

determining (202) an angle of the device (100) with respect to the direction of gravity;
 identifying (204), in a displayed image of the user, a location of one or more anatomical features of the user holding the device (100) relative to a displayed predefined location range;
 determining (206) a height of the blood pressure sensor (102) relative to a heart level of the user based on the determined angle of the device with respect to the direction of gravity and the identified location of the one or more anatomical features of the user in the image relative to the predefined location range; and
 controlling (208) the device based on the determined height of the blood pressure sensor (102) relative to the heart level of the user.

2. A method as claimed in claim 1, wherein the height of the blood pressure sensor (102) is determined to be different to the heart level of the user where one or both of:

the determined angle of the device (100) with respect to the direction of gravity is outside a predefined angle range; and
 the identified location of the one or more anatomical features of the user is outside the predefined location range.

3. A method as claimed in claim 1, wherein the height of the blood pressure sensor (102) is determined to be at the heart level of the user where one or both of:

the determined angle of the device (100) with respect to the direction of gravity is within a predefined angle range; and
 the identified location of the one or more anatomical features of the user is within the predefined location range.

4. A method as claimed in any one of the preceding claims, wherein controlling the device (100) based on the determined height of the blood pressure sensor comprises:
 controlling the device (100) to output to the user one or more of the determined angle of the device (100)

with respect to the direction of gravity and the identified location of the one or more anatomical features of the user when the height of the blood pressure sensor (102) is determined to be different to the heart level of the user.

5. A method as claimed in any one of the preceding claims, wherein controlling the device (100) based on the determined height of the blood pressure sensor (102) comprises:
 controlling the device (100) to output to the user an instruction to adjust one or more of the angle of the device (100) with respect to the direction of gravity and the location of the one or more anatomical features of the user when the height of the blood pressure sensor (102) is determined to be different to the heart level of the user.

6. A method as claimed in any one of the preceding claims, wherein controlling the device (100) based on the determined height of the blood pressure sensor (102) comprises:
 controlling the device (100) to output to the user an error notification when the height of the blood pressure sensor (102) is determined to be different to the heart level of the user.

7. A method as claimed in any one of the preceding claims, wherein controlling the device (100) based on the determined height of the blood pressure sensor (102) comprises:
 controlling the blood pressure sensor (102) to acquire a blood pressure measurement from the user when the height of the blood pressure sensor (102) is determined to be at the heart level of the user.

8. A method as claimed in any one of the preceding claims, wherein controlling the device (100) based on the determined height of the blood pressure sensor (102) comprises:

controlling the blood pressure sensor (102) to acquire a blood pressure measurement from the user when the height of the blood pressure sensor (102) is determined to be different to the heart level of the user; and
 adjusting the acquired blood pressure measurement based on the difference between the height of the blood pressure sensor (102) and the heart level of the user.

9. A method as claimed in any one of the preceding claims, wherein the one or more anatomical features of the user comprise any one or more of:

one or both eyes of the user;
 the mouth of the user;
 the nose of the user;

the facial outline of the user;
a neck of the user; and
one or more shoulders of the user.

10. A computer program product comprising a computer readable medium, the computer readable medium having computer readable code embodied therein, the computer readable code being configured such that, on execution by a suitable computer or processor, the computer or processor is caused to control a device (100) comprising a blood pressure sensor (102) for sensing blood pressure by implementing the following steps:

determining (202) an angle of the device (100) with respect to the direction of gravity;
identifying (204), in the displayed image of the user, a location of one or more anatomical features of the user holding the device (100) relative to a displayed predefined location range;
determining (206) a height of the blood pressure sensor (102) relative to a heart level of the user based on the determined angle of the device with respect to the direction of gravity and the identified location of the one or more anatomical features of the user in the image relative to the predefined location range; and
controlling (208) the device based on the determined height of the blood pressure sensor (102) relative to the heart level of the user;

from a determined angle value of the device and the known direction of gravity, the image of the user to be displayed and a range of predefined locations of one or more anatomical features of a user holding the device to be displayed.

11. A device (100) comprising:

a blood pressure sensor (102) for acquiring a blood pressure measurement from a user holding the device (100); and
a control unit (104) configured to:

determine an angle of the device (100) with respect to the direction of gravity;
identify, in a displayed image of the user, a location of one or more anatomical features of the user holding the device (100) relative to a displayed predefined location range;
determine a height of the blood pressure sensor (102) relative to a heart level of the user based on the determined angle of the device (100) with respect to the direction of gravity and the identified location of the one or more anatomical features of the user in the image relative to the predefined location range; and

control the device (100) based on the determined height of the blood pressure sensor (102) relative to the heart level of the user.

12. A device (100) as claimed in claim 11, the device (100) further comprising:

an angular sensor (106),
wherein the control unit (104) is configured to control the angular sensor (106) to determine the angle of the device (100) with respect to the direction of gravity.

13. A device (100) as claimed in any one of claims 11 or 12, the device (100) further comprising:

a camera (108),
wherein the control unit (104) is configured to control the camera (108) to identify the location of the one or more anatomical features of the user when the user is, at least partially, in the field of view of the camera (108).

14. A device (100) as claimed in any one of claims 11, 12, or 13, the device (100) further comprising:

a user interface (110),
wherein when the height of the blood pressure sensor (102) is determined to be different to the heart level of the user, the control unit (104) is configured to control the user interface (110) to output to the user any one or more of:

the determined angle of the device with respect to the direction of gravity;
the identified location of the one or more anatomical features of the user;
an instruction to adjust any one or more of the angle of the device with respect to the direction of gravity, the location of the one or more anatomical features of the user, and an angle of the body of the user; and
an error notification.

15. A device (100) as claimed in any one of claims 11 to 14, wherein the blood pressure sensor (102) comprises any one or more of:

a volume sensor; and
a pressure sensor.

Patentansprüche

1. Verfahren (200) zum Steuern einer Vorrichtung (100), die einen Blutdrucksensor (102) zum Erfassen des Blutdrucks umfasst, wobei das Verfahren

umfasst:

Bestimmen (202) eines Winkels der Vorrichtung (100) in Bezug auf die Richtung der Schwerkraft; Identifizieren (204), in einem angezeigten Bild des Benutzers, eines Ortes von einem oder mehreren anatomischen Merkmalen des Benutzers, der die Vorrichtung (100) hält, relativ zu einem angezeigten vordefinierten Ortsbereich; Bestimmen (206) einer Höhe des Blutdrucksensors (102) relativ zu einem Herzniveau des Benutzers basierend auf dem bestimmten Winkel der Vorrichtung in Bezug auf die Richtung der Schwerkraft und dem identifizierten Ort von dem einem oder den mehreren anatomischen Merkmalen des Benutzers in dem Bild relativ zu dem vordefinierten Ortsbereich; und Steuern (208) der Vorrichtung basierend auf der bestimmten Höhe des Blutdrucksensors (102) relativ zu dem Herzniveau des Benutzers.

2. Verfahren nach Anspruch 1, wobei bestimmt wird, dass sich die Höhe des Blutdrucksensors (102) von dem Herzniveau des Benutzers unterscheidet, wenn eines oder beide vorliegen von:

der bestimmte Winkel der Vorrichtung (100) in Bezug auf die Richtung der Schwerkraft liegt außerhalb eines vordefinierten Winkelbereichs; und
der identifizierte Ort von dem einem oder den mehreren anatomischen Merkmalen des Benutzers liegt außerhalb des vordefinierten Ortsbereichs.

3. Verfahren nach Anspruch 1, wobei bestimmt wird, dass sich die Höhe des Blutdrucksensors (102) auf dem Herzniveau des Benutzers befindet, wenn eines oder beide vorliegen von:

der bestimmte Winkel der Vorrichtung (100) in Bezug auf die Richtung der Schwerkraft liegt innerhalb eines vordefinierten Winkelbereichs; und der identifizierte Ort von dem einem oder den mehreren anatomischen Merkmalen des Benutzers liegt innerhalb des vordefinierten Ortsbereichs.

4. Verfahren nach einem der vorstehenden Ansprüche, wobei das Steuern der Vorrichtung (100) basierend auf der bestimmten Höhe des Blutdrucksensors umfasst:

Steuern der Vorrichtung (100), um einen oder mehrere von den bestimmten Winkeln der Vorrichtung (100) in Bezug auf die Richtung der Schwerkraft und dem identifizierten Ort von einem oder mehreren anatomischen Merkmalen des Benutzers an den Benutzer auszugeben, wenn bestimmt wird, dass sich die Höhe des Blutdrucksensors (102) von dem Herzniveau des Benutzers unterscheidet.

5. Verfahren nach einem der vorstehenden Ansprüche, wobei das Steuern der Vorrichtung (100) basierend auf der bestimmten Höhe des Blutdrucksensors (102) umfasst:

Steuern der Vorrichtung (100), um eine Anweisung zum Anpassen eines oder mehrerer von dem Winkel der Vorrichtung (100) in Bezug auf die Richtung der Schwerkraft und dem identifizierten Ort von einem oder mehreren anatomischen Merkmalen des Benutzers an den Benutzer auszugeben, wenn bestimmt wird, dass sich die Höhe des Blutdrucksensors (102) von dem Herzniveau des Benutzers unterscheidet.

6. Verfahren nach einem der vorstehenden Ansprüche, wobei das Steuern der Vorrichtung (100) basierend auf der bestimmten Höhe des Blutdrucksensors (102) umfasst:

Steuern der Vorrichtung (100), um eine Fehlerbenachrichtigung an den Benutzer auszugeben, wenn bestimmt wird, dass sich die Höhe des Blutdrucksensors (102) von dem Herzniveau des Benutzers unterscheidet.

7. Verfahren nach einem der vorstehenden Ansprüche, wobei das Steuern der Vorrichtung (100) basierend auf der bestimmten Höhe des Blutdrucksensors (102) umfasst:

Steuern des Blutdrucksensors (102), um eine Blutdruckmessung von dem Benutzer zu erhalten, wenn bestimmt wird, dass sich die Höhe des Blutdrucksensors (102) auf dem Herzniveau des Benutzers befindet.

8. Verfahren nach einem der vorstehenden Ansprüche, wobei das Steuern der Vorrichtung (100) basierend auf der bestimmten Höhe des Blutdrucksensors (102) umfasst:

Steuern des Blutdrucksensors (102), um eine Blutdruckmessung von dem Benutzer zu erlangen, wenn bestimmt wird, dass sich die Höhe des Blutdrucksensors (102) von dem Herzniveau des Benutzers unterscheidet; und Anpassen der erlangten Blutdruckmessung basierend auf der Differenz zwischen der Höhe des Blutdrucksensors (102) und dem Herzniveau des Benutzers.

9. Verfahren nach einem der vorstehenden Ansprüche, wobei das eine oder die mehreren anatomischen Merkmale des Benutzers eines oder mehrere umfassen von:

einem oder beiden Augen des Benutzers;
dem Mund des Benutzers;
der Nase des Benutzers;
den Gesichtsumrissen des Benutzers;
einem Hals des Benutzers; und
einer oder mehreren Schultern des Benutzers.

10. Computerprogrammprodukt, umfassend ein computerlesbares Medium, wobei das computerlesbare Medium darauf verkörpertem computerlesbaren Code aufweist, wobei der computerlesbare Code konfiguriert ist, sodass bei Ausführung durch einen geeigneten Computer oder Prozessor der Computer oder Prozessor veranlasst wird, eine Vorrichtung (100), die einen Blutdrucksensor (102) zum Erfassen des Blutdrucks umfasst, zu steuern, durch Implementieren der folgenden Schritte:

Bestimmen (202) eines Winkels der Vorrichtung (100) in Bezug auf die Richtung der Schwerkraft; Identifizieren (204), in einem angezeigten Bild des Benutzers, eines Ortes von einem oder mehreren anatomischen Merkmalen des Benutzers, der die Vorrichtung (100) hält, relativ zu einem angezeigten vordefinierten Ortsbereich; Bestimmen (206) einer Höhe des Blutdrucksensors (102) relativ zu einem Herzniveau des Benutzers basierend auf dem bestimmten Winkel der Vorrichtung in Bezug auf die Richtung der Schwerkraft und dem identifizierten Ort von dem einem oder den mehreren anatomischen Merkmalen des Benutzers in dem Bild relativ zu dem vordefinierten Ortsbereich; und Steuern (208) der Vorrichtung basierend auf der bestimmten Höhe des Blutdrucksensors (102) relativ zu dem Herzniveau des Benutzers; von einem vorbestimmten Winkelwert der Vorrichtung und der bekannten Richtung der Schwerkraft, des Bildes des Benutzers, das angezeigt werden soll, und eines Bereichs von vordefinierten Orten von dem einen oder den mehreren Merkmalen eines Benutzers, der die Vorrichtung hält, der angezeigt werden soll.

11. Vorrichtung (100), umfassend:

einen Blutdrucksensor (102) zum Erlangen einer Blutdruckmessung von einem Benutzer, der die Vorrichtung (100) hält; und eine Steuereinheit (104), die konfiguriert ist zum:

Bestimmen eines Winkels der Vorrichtung (100) in Bezug auf die Richtung der Schwerkraft; Identifizieren, in einem angezeigten Bild des Benutzers, eines Ortes von einem oder mehreren anatomischen Merkmalen des Benutzers, der die Vorrichtung (100) hält, relativ zu einem angezeigten vordefinierten Ortsbereich; Bestimmen einer Höhe des Blutdrucksensors (102) relativ zu einem Herzniveau des Benutzers basierend auf dem bestimmten Winkel der Vorrichtung (100) in Bezug auf

die Richtung der Schwerkraft und dem identifizierten Ort von dem einem oder den mehreren anatomischen Merkmalen des Benutzers in dem Bild relativ zu dem vordefinierten Ortsbereich; und Steuern der Vorrichtung (100) basierend auf der bestimmten Höhe des Blutdrucksensors (102) relativ zu dem Herzniveau des Benutzers.

12. Vorrichtung (100) nach Anspruch 11, wobei die Vorrichtung (100) weiter umfasst:

einen Winkelsensor (106), wobei die Steuereinheit (104) konfiguriert ist, um den Winkelsensor (106) zu steuern, um den Winkel der Vorrichtung (100) in Bezug auf die Richtung der Schwerkraft zu bestimmen.

13. Vorrichtung (100) nach einem der Ansprüche 11 oder 12, wobei die Vorrichtung (100) weiter umfasst:

eine Kamera (108), wobei die Steuereinheit (104) konfiguriert ist, um die Kamera (108) zu steuern, um den Ort von dem einen oder den mehreren anatomischen Merkmalen des Benutzers zu identifizieren, wenn sich der Benutzer zumindest teilweise in dem Sichtfeld befindet der Kamera (108).

14. Vorrichtung (100) nach einem der Ansprüche 11, 12 oder 13, wobei die Vorrichtung (100) weiter umfasst:

eine Benutzerschnittstelle (110), wobei, wenn bestimmt wird, dass sich die Höhe des Blutdrucksensors (102) von dem Herzniveau des Benutzers unterscheidet, die Steuereinheit (104) konfiguriert ist, um die Benutzerschnittstelle (110) zu steuern, um an den Benutzer eines oder mehrere auszugeben von:

dem bestimmten Winkel der Vorrichtung in Bezug auf die Richtung der Schwerkraft; dem identifizierten Ort von dem einen oder den mehreren anatomischen Merkmalen des Benutzers; einer Anweisung, eines oder mehrere von dem Winkel der Vorrichtung in Bezug auf die Richtung der Schwerkraft, dem Ort von dem einen oder den mehreren anatomischen Merkmalen des Benutzers und einem Körperwinkel des Benutzers anzupassen; und einer Fehlermeldung.

15. Vorrichtung (100) nach einem der Ansprüche 11 bis 14, wobei der Blutdrucksensor (102) eines oder mehrere umfasst von:

einem Volumensensor; und
einem Drucksensor.

Revendications

1. Procédé (200) pour commander un dispositif (100) comprenant un capteur de pression sanguine (102) pour capter la pression sanguine, le procédé comprenant :

la détermination (202) d'un angle du dispositif (100) par rapport au sens de la pesanteur ;
l'identification (204), dans une image affichée de l'utilisateur, d'une localisation d'un ou plusieurs sites anatomiques de l'utilisateur portant le dispositif (100) par rapport à une plage prédéfinie affichée de localisations ;

la détermination (206) d'une hauteur du capteur de pression sanguine (102) par rapport à un niveau du cœur de l'utilisateur sur la base de l'angle déterminé du dispositif par rapport au sens de la pesanteur et de la localisation identifiée des un ou plusieurs sites anatomiques de l'utilisateur dans l'image par rapport à la plage prédéfinie de localisations ; et

la commande (208) du dispositif sur la base de la hauteur déterminée du capteur de pression sanguine (102) par rapport au niveau du cœur de l'utilisateur.

2. Procédé selon la revendication 1, dans lequel la hauteur du capteur de pression sanguine (102) est déterminée comme différente du niveau du cœur de l'utilisateur dans le cas d'une ou des deux situations suivantes :

l'angle déterminé du dispositif (100) par rapport au sens de la pesanteur se situe en dehors d'une plage prédéfinie d'angles ; et

la localisation identifiée des un ou plusieurs sites anatomiques se situe en dehors de la plage prédéfinie de localisations.

3. Procédé selon la revendication 1, dans lequel la hauteur du capteur de pression sanguine (102) est déterminée pour être au niveau du cœur de l'utilisateur dans le cas d'une ou des deux situations suivantes :

l'angle déterminé du dispositif (100) par rapport au sens de la pesanteur se situe dans une plage prédéfinie d'angles ; et

la localisation identifiée des un ou plusieurs sites anatomiques se situe dans la plage prédéfinie de localisations.

4. Procédé selon l'une quelconque des revendications

précédentes, dans lequel la commande du dispositif (100) sur la base de la hauteur déterminée du capteur de pression sanguine comprend :

la commande du dispositif (100) pour délivrer à l'utilisateur un(e) ou plusieurs de l'angle déterminé du dispositif (100) par rapport au sens de la pesanteur et de la localisation identifiée des un ou plusieurs sites anatomiques de l'utilisateur lorsque la hauteur du capteur de pression sanguine (102) est déterminée comme étant différente du niveau du cœur de l'utilisateur.

5. Procédé selon l'une quelconque des revendications précédentes, dans lequel la commande du dispositif (100) sur la base de la hauteur déterminée du capteur de pression sanguine (102) comprend :

la commande du dispositif (100) pour délivrer à l'utilisateur une instruction pour ajuster un(e) ou plusieurs de l'angle du dispositif (100) par rapport au sens de la pesanteur et de la localisation des un ou plusieurs sites anatomiques de l'utilisateur lorsque la hauteur du capteur de pression sanguine (102) est déterminée comme étant différente du niveau du cœur de l'utilisateur.

6. Procédé selon l'une quelconque des revendications précédentes, dans lequel la commande du dispositif (100) sur la base de la hauteur déterminée du capteur de pression sanguine (102) comprend :

la commande du dispositif (100) pour délivrer à l'utilisateur une notification d'erreur lorsque la hauteur du capteur de pression sanguine (102) est déterminée comme étant différente du niveau du cœur de l'utilisateur.

7. Procédé selon l'une quelconque des revendications précédentes, dans lequel la commande du dispositif (100) sur la base de la hauteur déterminée du capteur de pression sanguine (102) comprend :

la commande du capteur de pression sanguine (102) pour acquérir une mesure de pression sanguine de l'utilisateur lorsque la hauteur du capteur de pression sanguine (102) est déterminée comme se situant au niveau du cœur de l'utilisateur.

8. Procédé selon l'une quelconque des revendications précédentes, dans lequel la commande du dispositif (100) sur la base de la hauteur déterminée du capteur de pression sanguine (102) comprend :

la commande du capteur de pression sanguine (102) qui acquérir une mesure de pression sanguine de l'utilisateur lorsque la hauteur du capteur de pression sanguine (102) est déterminée comme étant différente du niveau du cœur de l'utilisateur ; et

l'ajustement de la mesure de pression sanguine acquise sur la base de la différence entre la hau-

teur du capteur de pression sanguine (102) et le niveau du cœur de l'utilisateur.

9. Procédé selon l'une quelconque des revendications précédentes, dans lequel les un ou plusieurs sites anatomiques de l'utilisateur comprennent l'un quelconque ou plusieurs des suivants :

un seul ou les deux yeux de l'utilisateur ;
la bouche de l'utilisateur ;
le nez de l'utilisateur ;
le profil facial de l'utilisateur ;
un cou de l'utilisateur ; et
une ou plusieurs épaules de l'utilisateur.

10. Produit de programme d'ordinateur comprenant un support lisible par ordinateur, le support lisible par ordinateur ayant un code lisible par ordinateur qui y est mis en œuvre, le code lisible par ordinateur étant configuré de sorte que, lors de l'exécution par un ordinateur ou un processeur approprié, l'ordinateur ou le processeur soit amené à commander un dispositif (100) comprenant un capteur de pression sanguine (102) pour capter la pression sanguine en mettant en œuvre les étapes suivantes :

la détermination (202) d'un angle du dispositif (100) par rapport au sens de la pesanteur ;
l'identification (204), dans l'image affichée de l'utilisateur, d'une localisation d'un ou plusieurs sites anatomiques de l'utilisateur portant le dispositif (100) par rapport à une plage prédéfinie affichée de localisations ;
la détermination (206) d'une hauteur du capteur de pression sanguine (102) par rapport à un niveau du cœur de l'utilisateur sur la base de l'angle déterminé du dispositif par rapport au sens de la pesanteur et de la localisation identifiée des un ou plusieurs sites anatomiques de l'utilisateur dans l'image par rapport à la plage prédéfinie de localisations ; et
la commande (208) du dispositif sur la base de la hauteur déterminée du capteur de pression sanguine (102) par rapport au niveau du cœur de l'utilisateur ;
à partir d'une valeur angulaire déterminée du dispositif et du sens connu de la pesanteur, de l'image de l'utilisateur à afficher et d'une plage de localisations prédéfinies d'un ou plusieurs sites anatomiques d'un utilisateur portant le dispositif à afficher.

11. Dispositif (100) comprenant :

un capteur de pression sanguine (102) pour acquérir une mesure de pression sanguine d'un utilisateur portant le dispositif (100) ; et
une unité de commande (104) configurée pour :

déterminer un angle du dispositif (100) par rapport au sens de la pesanteur ;
identifier, dans une image affichée de l'utilisateur, une localisation d'un ou plusieurs sites anatomiques de l'utilisateur portant le dispositif (100) par rapport à une plage prédéfinie affichée de localisations ;
déterminer une hauteur du capteur de pression sanguine (102) par rapport à un niveau de cœur de l'utilisateur sur la base de l'angle déterminé du dispositif (100) par rapport au sens de la pesanteur et de la localisation identifiée des un ou plusieurs sites anatomiques de l'utilisateur dans l'image par rapport à la plage prédéfinie de localisations ; et
commander le dispositif (100) sur la base de la hauteur déterminée du capteur de pression sanguine (102) par rapport au niveau du cœur de l'utilisateur.

12. Dispositif (100) selon la revendication 11, le dispositif (100) comprenant en outre :

un capteur angulaire (106),
dans lequel l'unité de commande (104) est configurée pour commander le capteur angulaire (106) afin de déterminer l'angle du dispositif (100) par rapport au sens de la pesanteur.

13. Dispositif (100) selon l'une quelconque des revendications 11 ou 12, le dispositif (100) comprenant en outre :

une caméra (108),
dans lequel l'unité de commande (104) est configurée pour commander la caméra (108) afin d'identifier la localisation des un ou plusieurs sites anatomiques de l'utilisateur lorsque l'utilisateur se trouve au moins en partie dans le champ de vision de la caméra (108).

14. Dispositif (100) selon l'une quelconque des revendications 11, 12 ou 13, le dispositif (100) comprenant en outre :

une interface utilisateur (110),
dans lequel, lorsque la hauteur du capteur de pression sanguine (102) est déterminée comme étant différente du niveau du cœur de l'utilisateur, l'unité de commande (104) est configurée pour commander l'interface utilisateur (110) afin de délivrer à l'utilisateur l'un quelconque ou plusieurs des éléments suivants :

l'angle déterminé du dispositif par rapport au sens de la pesanteur ;
la localisation identifiée des un ou plusieurs

sites anatomiques de l'utilisateur ;
une instruction pour ajuster l'un(e) quelconque ou plus de l'angle du dispositif par rapport au sens de la pesanteur, de la localisation des un ou plusieurs sites anatomiques de l'utilisateur et d'un angle du corps de l'utilisateur ; et
une notification d'erreurs.

5

15. Dispositif (100) selon l'une quelconque des revendications 11 à 14, dans lequel le capteur de pression sanguine (102) comprend l'un quelconque ou plus des suivants :

10

un capteur de volume ; et
un capteur de pression.

15

20

25

30

35

40

45

50

55




Figure 1




Figure 2




Figure 3

REFERENCES CITED IN THE DESCRIPTION

This list of references cited by the applicant is for the reader's convenience only. It does not form part of the European patent document. Even though great care has been taken in compiling the references, errors or omissions cannot be excluded and the EPO disclaims all liability in this regard.

Patent documents cited in the description

- WO 2016096919 A1 [0004]
- US 2013237865 A [0005]

专利名称(译)	具有血压传感器的装置和用于控制该装置的方法		
公开(公告)号	EP3534785B1	公开(公告)日	2020-03-18
申请号	EP2017791110	申请日	2017-11-01
[标]申请(专利权)人(译)	皇家飞利浦电子股份有限公司		
申请(专利权)人(译)	皇家飞利浦N.V.		
当前申请(专利权)人(译)	皇家飞利浦N.V.		
[标]发明人	AELEN PAUL		
发明人	AELEN, PAUL		
IPC分类号	A61B5/022 A61B5/00 A61B5/11		
CPC分类号	A61B5/02225 A61B5/1121 A61B5/1126 A61B5/1128 A61B5/681 A61B5/6898 A61B5/70 A61B5/7221 A61B2560/0261 A61B2562/0219 A61B2562/0247 A61B2562/0252 A61B2562/0261 A61B5/0077 A61B5/4887 A61B5/6844 A61B5/742 A61B5/7475		
代理机构(译)	涂片NICHOLAS		
优先权	2016197456 2016-11-07 EP		
其他公开文献	EP3534785A1		
外部链接	Espacenet		

摘要(译)

提供了一种包括用于感测血压的血压传感器的设备以及用于控制该设备的方法。确定设备相对于重力方向的角度 (202)，并识别握持设备的用户的一个或多个特征的位置 (204)。基于设备相对于重力的确定角度以及用户的一个或多个特征的识别位置来确定血压传感器相对于用户的心脏水平的高度 (206)。基于所确定的血压传感器相对于用户的心脏水平的高度来控制设备 (208)。




Figure 1