



(12) **EUROPEAN PATENT APPLICATION**
published in accordance with Art. 153(4) EPC

(43) Date of publication:
12.09.2018 Bulletin 2018/37

(51) Int Cl.:
A61B 5/0245^(2006.01) A61B 5/00^(2006.01)

(21) Application number: **15907801.3**

(86) International application number:
PCT/JP2015/081122

(22) Date of filing: **05.11.2015**

(87) International publication number:
WO 2017/077615 (11.05.2017 Gazette 2017/19)

(84) Designated Contracting States:
AL AT BE BG CH CY CZ DE DK EE ES FI FR GB GR HR HU IE IS IT LI LT LU LV MC MK MT NL NO PL PT RO RS SE SI SK SM TR
Designated Extension States:
BA ME
Designated Validation States:
MA MD

- **MAEDA, Kazuho**
Kawasaki-shi
Kanagawa 211-8588 (JP)
- **INOMATA, Akihiro**
Kawasaki-shi
Kanagawa 211-8588 (JP)

(71) Applicant: **Fujitsu Limited**
Kawasaki-shi, Kanagawa 211-8588 (JP)

(74) Representative: **Haseltine Lake LLP**
Lincoln House, 5th Floor
300 High Holborn
London WC1V 7JH (GB)

(72) Inventors:
• **MORI, Tatsuya**
Kawasaki-shi
Kanagawa 211-8588 (JP)

(54) **MEAL DETECTION DEVICE, MEAL DETECTION METHOD, AND MEAL DETECTION PROGRAM**

(57) A meal intake detection device includes: a detection unit configured to detect a rise of heart rate; a separation unit configured to extract as a meal intake candidate a time range from a detected rise by the detection unit to time when the heart rate decreases to a predetermined value in temporal changes in heart rate, and when a second meal intake candidate is extracted in a time range of an extracted first meal intake candidate, separate the first meal intake candidate and the second meal intake candidate along a predetermined line; and another detection unit configured to detect whether each of the first meal intake candidate and the second meal intake candidate is a meal intake based on feature quantities relating to the first meal intake candidate and the second meal intake candidate separated by the separation unit.

FIG. 2A





FIG. 2B



Description**FIELD**

[0001] The present case relates to a meal intake detection device, a meal intake detection method, and a meal intake detection program.

BACKGROUND

[0002] A technique for detecting a meal intake has been desired. For example, disclosed is a technique that detects temporal changes in heart rate and determines the peak of the heart rate satisfying a predetermined condition as a meal intake (see Patent Document 1, for example).

PRIOR ART DOCUMENT**PATENT DOCUMENT**

[0003] Patent Document 1: Japanese Laid-open Patent Publication No. 2010-158267.

DISCLOSURE OF THE INVENTION**PROBLEMS TO BE SOLVED BY THE INVENTION**

[0004] However, when peaks of the heart rate overlap because of a short interval between meals, the accuracy of the detection of a meal intake may decrease.

[0005] According to an aspect of the present case, provided is a meal intake detection device, a meal intake detection method, and a meal intake detection program capable of improving the accuracy of the detection of a meal intake.

MEANS FOR SOLVING THE PROBLEMS

[0006] In a first aspect, a meal intake detection device includes: a detection unit configured to detect a rise of heart rate; a separation unit configured to extract as a meal intake candidate a time range from a detected rise by the detection unit to time when the heart rate decreases to a predetermined value in temporal changes in heart rate, and when a second meal intake candidate is extracted in a time range of an extracted first meal intake candidate, separate the first meal intake candidate and the second meal intake candidate along a predetermined line; and another detection unit configured to detect whether each of the first meal intake candidate and the second meal intake candidate is a meal intake based on feature quantities relating to the first meal intake candidate and the second meal intake candidate separated by the separation unit.

EFFECTS OF THE INVENTION

[0007] The accuracy of the detection of a meal intake is improved.

BRIEF DESCRIPTION OF DRAWINGS**[0008]**

FIG. 1 is a block diagram of a hardware configuration of a meal intake detection device in accordance with a first embodiment;

FIG. 2A is a block diagram of functions implemented by the execution of a meal intake detection program, and FIG. 2B is a functional block diagram of functions of a meal intake detection unit;

FIG. 3A illustrates temporal changes in heart rate during a meal, and FIG. 3B illustrates temporal changes in heart rate when the interval between meals is short;

FIG. 4 illustrates detection of meal intake candidates; FIG. 5 illustrates separation of meal intake candidates;

FIG. 6A through FIG. 6C illustrate correction of meal intake candidates;

FIG. 7A and FIG. 7B illustrate calculation of a feature vector;

FIG. 8 is a flowchart of a concrete example of a meal intake detection process;

FIG. 9A is a block diagram of functions implemented by the execution of the meal intake detection program, and FIG. 9B is a functional block diagram of functions of the meal intake detection unit;

FIG. 10 illustrates meal intake candidates;

FIG. 11A and FIG. 11B illustrate elimination of a meal intake candidate;

FIG. 12 is a flowchart of a concrete example of a meal intake detection process in accordance with a second embodiment;

FIG. 13A is real data of temporal changes in heart rate when the interval between two meals was made to be short, and FIG. 13B illustrates separation of meal intake candidates; and

FIG. 14A and FIG. 14B illustrate other device structures of the meal intake detection device.

DESCRIPTION OF EMBODIMENTS

[0009] Hereinafter, a description will be given of embodiments with reference to drawings.

(First Embodiment)

[0010] FIG. 1 is a block diagram of a hardware configuration of a meal intake detection device 100 in accordance with a first embodiment. As illustrated in FIG. 1, the meal intake detection device 100 includes a CPU 101, a RAM 102, a storage device 103, a display device 104, a

heartbeat measuring device 105, an acceleration sensor 106, and the like. These devices are interconnected through a bus or the like.

[0011] The CPU (Central Processing Unit) 101 is a central processing unit. The CPU 101 includes one or more cores. The RAM (Random Access Memory) 102 is a volatile memory that temporarily stores programs executed by the CPU 101 and data processed by the CPU 101.

[0012] The storage device 103 is a nonvolatile storage device. For example, a ROM (Read Only Memory), a solid state drive (SSD) such as a flash memory, or a hard disk driven by a hard disk drive can be used as the storage device 103. The meal intake detection program of the present embodiment is stored in the storage device 103. The display device 104 is a liquid crystal display, an electroluminescence panel, or the like, and displays the result of the meal intake detection process described later.

[0013] The heartbeat measuring device 105 is a device that measures the heartbeat (pulse) of a user. The heartbeat measuring device 105 is not particularly limited as long as it can measure heartbeat (pulse). For example, the heartbeat measuring device 105 may be an electrocardiograph or a pulsation sensor. The acceleration sensor 106 is a sensor that detects an acceleration of a part to which the sensor is attached of the user.

[0014] The meal intake detection program stored in the storage device 103 is deployed in the RAM 102 in an executable manner. The CPU 101 executes the meal intake detection program deployed in the RAM 102. This causes the meal intake detection device 100 to execute each process. FIG. 2A is a block diagram of functions implemented by the execution of the meal intake detection program. The execution of the meal intake detection program implements a heart rate acquisition unit 10, a meal intake candidate detection unit 20, a heartbeat peak extraction unit 30, a heartbeat peak correction unit 40, an acceleration acquisition unit 50, an action detection unit 60, a meal intake detection unit 70, a meal index estimation unit 80, and the like.

[0015] FIG. 2B is a functional block diagram of functions of the meal intake detection unit 70. As illustrated in FIG. 2B, the meal intake detection unit 70 functions as an area feature quantity calculation unit 71, a speed feature quantity calculation unit 72, an amplitude feature quantity calculation unit 73, a time feature quantity calculation unit 74, a model creation unit 75, a feature quantity database 76, a meal intake time estimation unit 77, a determination unit 78, and the like.

[0016] Here, a description will be given of temporal changes in heart rate resulting from a meal intake. FIG. 3A illustrates temporal changes in heart rate resulting from a meal intake. In FIG. 3A, the horizontal axis represents elapsed time, and the vertical axis represents heart rate. The heart rate is the number of beats per unit time, more specifically, the number of beats per minute. Hereinafter, unless otherwise specified, the heart rate means the number of beats per minute.

[0017] As illustrated in FIG. 3A, two peaks appear in the heart rate increase section occurring with a meal intake. The start point of the increase section where the rise of the first peak is detected is a meal intake start time. For example, the start point at which the ascent rate of the heart rate is equal to or greater than a threshold value and the rise in heart rate is equal to or greater than another threshold value can be detected as the rise. The time of the first peak is a meal intake end time. The time when the heart rate of the second peak has returned to a predetermined value is the end point of the heart rate increase section. For example, the time when the heart rate of the second peak returns to the heart rate at the meal intake start time may be defined as the end point of the heart rate increase section, or time when the heart rate of the second peak returns to the value calculated by adding a predetermined value to the heart rate at the meal intake start time or multiplying the heart rate at the meal intake start time by the predetermined value may be defined as the end point of the heart rate increase section. The waveform of the heart rate from the start point to the end point of the heart rate increase section occurring with a meal intake is referred to as a heartbeat peak.

[0018] Meal intakes at predetermined intervals allow heartbeat peaks illustrated in FIG. 3 to be sufficiently separated and detected. Thus, a meal intake can be accurately detected. However, when the interval between meals is short, as illustrated in FIG. 3B, heartbeat peaks overlap with each other. In the example of FIG. 3B, following the first peak in the previous meal, the second peak in the subsequent meal appears. In this case, the accuracy of the detection of a meal intake decreases. Thus, the present embodiment describes an example that improves the accuracy of the detection of a meal intake by detecting heartbeat peak candidates, and extracting individual heartbeat peaks.

(Meal Intake Detection Process)

[0019] First, the acceleration acquisition unit 50 acquires the detection result of the acceleration sensor 106. When the acceleration of the user satisfies a predetermined condition, this indicates that the user is exercising, such as running, walking, or the like. Thus, the action detection unit 60 detects the exercise interval of the user based on the detection results acquired by the acceleration acquisition unit 50. The heart rate acquisition unit 10 acquires temporal changes in heart rate by acquiring heartbeat from the heartbeat measuring device 105. The heart rate acquisition unit 10 then eliminates the variation in heart rate during the exercise interval. This process eliminates as a noise the exercise interval during which it is estimated that the user is not having a meal.

[0020] Then, the meal intake candidate detection unit 20 detects meal intake candidates from the temporal changes in heart rate. In the present embodiment, when the rise at which the degree of increase in heart rate per

unit time (the ascent rate of the heart rate) is equal to or greater than a threshold value is detected, the meal intake candidate detection unit 20 detects the period after the rise as a meal intake candidate. The detection condition may be looser than the detection condition by the meal intake detection unit 70 so that the actual meal intake can be reliably detected. For example, when the section in which the ascent rate of heart rate within 20 minutes from the rise of the heart rate to the maximum point is 10/min or greater is detected, the meal intake candidate detection unit 20 detects the period after the rise as a meal intake candidate. In the example of FIG. 4, two candidates including a first meal intake candidate A and a second meal intake candidate B are detected.

[0021] The heartbeat peak extraction unit 30 then extracts the heartbeat peak of each meal intake candidate. In the present embodiment, as an example, the heartbeat peak extraction unit 30 detects the rise of the heart rate as the start point of the heartbeat peak of the meal intake candidate, and detects, as the end point of the heartbeat peak of the meal intake candidate, the time when the heart rate returns to the heart rate at the meal intake start time. As illustrated in FIG. 5, the heartbeat peaks of the first meal intake candidate A and the second meal intake candidate B are detected in a manner that the heartbeat peak of the second meal intake candidate B is added to the heartbeat peak of the first meal intake candidate A.

[0022] The heartbeat peak extraction unit 30 then extracts heartbeat peaks overlapping with each other as a collection of meal intake candidates. For example, when the time ranges of heartbeat peaks overlap, the heartbeat peak extraction unit 30 determines that the heartbeat peaks overlap. Then, the heartbeat peak extraction unit 30 separates the waveform of the overlapping heartbeat peaks into individual heartbeat peaks along a predetermined line by drawing the predetermined line in the waveform. For example, the period from the start point of the subsequent heartbeat peak to the time at which the heart rate returns to the heart rate at the start point may be set as the subsequent heartbeat peak and separated from the previous heartbeat peak. Alternatively, at the start point of the subsequent heartbeat peak, the subsequent heartbeat peak may be separated from the previous heartbeat peak.

[0023] Then, the heartbeat peak correction unit 40 corrects the heartbeat peaks overlapping with each other. In the present embodiment, the heartbeat peak correction unit 40 corrects the previous and subsequent heartbeat peaks by using the previous heartbeat peak to the start point of the subsequent heartbeat peak. For example, it is assumed that the speed at which the rise in heartbeat accompanying with a meal intake comes close to the original level before the start of the meal intake is constant after the start time of the subsequent meal intake candidate. More specifically, the heartbeat peak correction unit 40 corrects the previous and subsequent heartbeat peaks by drawing a line from the start point of the subsequent meal intake candidate, the line having a

slope equal to the slope of the heartbeat peak of the previous meal intake candidate. The dashed line in FIG. 6A illustrates a line for correcting the previous and subsequent heartbeat peaks. FIG. 6B illustrates a corrected previous heartbeat peak. FIG. 6C illustrates a corrected subsequent heartbeat peak.

[0024] Then, the meal intake detection unit 70 calculates the feature vector based on each corrected heartbeat peak by the heartbeat peak correction unit 40 as illustrated in FIG. 7A and FIG. 7B. First, the area feature quantity calculation unit 71 calculates the area of each of the first peak and the second peak of the heartbeat peaks. For example, the area from the meal intake start time to the fall through the peak can be calculated as the area of the first peak. Similarly, the area from the rise after the first peak to the end of the meal through the peak can be calculated as the area of the second peak.

[0025] The speed feature quantity calculation unit 72 calculates a response speed of the heart rate. For example, the speed feature quantity calculation unit 72 calculates the ascent rate from the meal intake start time to the first peak, the descent rate from the first peak to the next rise, the ascent rate from the rise to the second peak, and the descent rate from the second peak to the end of the meal.

[0026] Then, the amplitude feature quantity calculation unit 73 calculates the heart rate of the first peak and the heart rate of the second peak as amplitude values. Then, the time feature quantity calculation unit 74 calculates the time from the start of the meal to the first peak, the time from the start of the meal to the second peak, and the time from the start of the meal to the end of the meal.

[0027] The above-described feature vector is a vector including at least one of the feature quantities calculated by the area feature quantity calculation unit 71, the speed feature quantity calculation unit 72, the amplitude feature quantity calculation unit 73, and the time feature quantity calculation unit 74. The feature vector may include a pre-meal feature quantity. For example, the feature vector may include a pre-meal feature quantity such as the area from the start of the meal to time a predetermined time before the start of the meal or the heart rate at the meal intake start time. As the area from the start of the meal to time a predetermined time before the start of the meal, the area between the value of the heart rate and the heart rate at the meal intake start time may be used.

[0028] The feature quantity database 76 stores in advance as feature vectors the feature quantities calculated by using the changes in heart rate of one or more users who actually had a meal. The model creation unit 75 creates an estimation model based on the feature vectors stored in the feature quantity database 76. The meal time estimation unit 77 estimates a meal time by applying the estimation model to the calculated feature vector. The determination unit 78 determines whether the subject meal intake candidate is a meal intake according to the estimation result of the meal time estimation unit 77. The determination unit 78 may reflect the matching result be-

tween a meal intake action detected by the action detection unit 60 based on the detection result of the acceleration sensor 106 and a meal intake action pattern. When the meal intake action detected by the action detection unit 60 is distant from (is not similar to) the meal intake action pattern, it may be determined that the subject meal intake candidate is not a meal intake.

[0029] The meal index estimation unit 80 then estimates indexes relating to a meal intake by using the feature vector of the heartbeat peak determined as a meal intake by the determination unit 78. The indexes relating to a meal intake include a condition of a human, an eating action, calories, and the like. The index relating to a meal intake can be expressed as a function of the feature vector, and thus the index relating to a meal intake can be expressed as $f(x)$ wherein x represents the feature vector. As an example, when calories are used as the index relating to a meal intake, the area of the second peak calculated by the area feature quantity calculation unit 71 can be used as x . Alternatively, after the feature vector is calculated based on the heartbeat peaks determined as meal intakes, the index relating to meal intakes may be estimated. For example, when z represents the feature vector calculated based on two heartbeat peaks determined as meal intakes, the index relating to a meal intake can be expressed as $g(y)$. As an example, presented is a case where the index indicating an excessively short interval between meals is calculated. When the feature vector y includes two scalar values y_1 and y_2 , the area of the second peak of the previous meal is represented by y_1 , and the area after the start time of the subsequent meal in the second peak is represented by y_2 , $g(y)$ can be expressed by y_2/y_1 .

[0030] FIG. 8 is a flowchart of a concrete example of the above-described meal intake detection process. Hereinafter, the concrete example of the above-described meal intake detection process will be described along the flowchart of FIG. 8. As illustrated in FIG. 8, the heart rate acquisition unit 10 acquires the heart rate by using the heartbeat obtained from the heartbeat measuring device 105 (step S1). Then, the heart rate acquisition unit 10 determines whether it has acquired all the heart rate for one day (step S2). When the determination at step S2 is "No", the process is executed again from step S1.

[0031] When the determination at step S2 is "Yes", the meal intake candidate detection unit 20 detects meal intake candidates from temporal changes in heart rate (step S3). The heart rate acquisition unit 10 may eliminate as a noise the variation in heart rate during the exercise interval of the user detected by the action detection unit 60 before the execution of step S3. The heartbeat peak extraction unit 30 then extracts the heartbeat peak of each meal intake candidate (step S4). The heartbeat peak extraction unit 30 then determines whether the heartbeat peak is extracted for all the meal intake candidates (step S5). When the determination at step S5 is "No", the process is executed again from step S4.

[0032] When the determination at step S5 is "Yes", the heartbeat peak extraction unit 30 extracts the heartbeat peaks overlapping with each other as a collection of meal intake candidates (step S6). Then, the heartbeat peak correction unit 40 corrects the heartbeat peak after the start of the next meal intake candidate (step S7). At the first execution of step S7, the heartbeat peak after the start of the second meal intake candidate is corrected. Then, the heartbeat peak extraction unit 30 determines whether correction for all the meal intake candidates in the collection of overlapping meal intake candidates ends (step S8). When the determination at step S8 is "No", step S7 is executed again.

[0033] When the determination at step S8 is "Yes", the meal intake detection unit 70 calculates the feature vector based on each corrected heartbeat peak by the heartbeat peak correction unit 40 (step S9). Then, the meal intake detection unit 70 determines whether each meal intake candidate is a meal intake (step S10). Then, the meal intake detection unit 70 determines whether the determination is conducted to all the meal intake candidates in the collection of overlapping meal intake candidates (step S11). When the determination at step S11 is "No", step S10 is executed again. When the determination at step S11 is "Yes", the heartbeat peak extraction unit 30 determines whether all the collections of overlapping meal intake candidates are extracted (step S12). When the determination at step S12 is "No", the process is executed again from step S6. When the determination at step S12 is "Yes", the execution of the flowchart ends.

[0034] In the present embodiment, the rise at which the ascent rate of the heart rate is equal to or greater than a threshold value in temporal changes in heart rate is detected. In the temporal changes in heart rate, the time range from the detected rise to the time at which the heart rate decreases to a predetermined value is extracted as a meal intake candidate. Among a plurality of meal intake candidates, when the second meal intake candidate is extracted in the time range of the first meal intake candidate, the first meal intake candidate and the second meal intake candidate are separated along a predetermined line. Based on the feature quantities relating to a meal intake of the separated first meal intake candidate and the separated second meal intake candidate, each of the first meal intake candidate and the second meal intake candidate is determined whether it is a meal intake. This configuration allows the meal intake detection based on the feature quantity for each meal intake candidate. This improves the accuracy of the detection of a meal intake.

[0035] The accuracy of the extraction of the first meal intake candidate and the second meal intake candidate is improved by obtaining the above-described predetermined line by using the first meal intake candidate to the start point of the second meal intake candidate. This is because the tendency of the first meal intake candidate can be used. When the heart rate of the first meal intake candidate tends to decrease at the time of the rising of

the second meal intake candidate, a line that starts from the time of the rising of the second meal intake candidate and has a slope equal to that of the first meal intake candidate at the time of the rising of the second meal intake candidate is preferably obtained as the above-described predetermined line. When the heart rate of the first meal intake candidate tends to decrease, the heart rate tends to decrease at a constant rate.

(Second Embodiment)

[0036] FIG. 9A is a functional block diagram of a meal intake detection device 100a in accordance with a second embodiment. The device structure is the same as that illustrated in FIG. 1A. As illustrated in FIG. 9A, the meal intake candidate elimination unit 90 is newly implemented by the execution of the meal intake detection program of the second embodiment. As illustrated in FIG. 9B, the functional block of the meal intake detection unit 70 is the same as that of FIG. 2B.

[0037] The meal intake candidate elimination unit 90 eliminates from candidates the meal intake candidate that is determined as not being a meal intake. This inhibits the meal intake candidate that is determined as not being a meal intake from affecting the heartbeat peaks of other meal intake candidates. Accordingly, the accuracy of the detection of a meal intake and the accuracy of the detection of the index relating to a meal intake are improved.

[0038] In the temporal changes in heart rate illustrated in FIG. 10, it is assumed that the first meal intake candidate A and the second meal intake candidate B are meal intakes, and the third meal intake candidate C is not a meal intake. In this case, when the third meal intake candidate C is not eliminated from candidates, as illustrated in FIG. 11A, the corrected heartbeat peak of the second meal intake candidate B is affected by the third meal intake candidate C, and the feature vector of the second meal intake candidate B is thereby affected. Thus, as illustrated in FIG. 11B, the elimination of the third meal intake candidate C from meal intake candidates by the meal intake candidate elimination unit 90 eliminates the influence of the third meal intake candidate C, and allows the original heartbeat peak of the second meal intake candidate B to be obtained. Accordingly, the original feature vector of the second meal intake candidate B can be calculated.

[0039] FIG. 12 is a flowchart of a concrete example of a meal intake detection process in accordance with the second embodiment. As illustrated in FIG. 12, processes at step S21 through step S25 are the same as those at step S1 through step S5 in FIG. 8. When the determination at step S25 is "Yes", the heartbeat peak correction unit 40 corrects the heartbeat peak after the start of the next meal intake candidate (step S26). At the first execution of step S26, the heartbeat peak after the start of the second meal intake candidate is corrected. Then, the heartbeat peak extraction unit 30 determines whether the heartbeat peaks that need to be corrected are cor-

rected for all the meal intake candidates (step S27). When the determination at step S27 is "No", step S26 is executed again.

[0040] When the determination at step S27 is "Yes", the meal intake detection unit 70 calculates the feature vectors of the heartbeat peaks of all the meal intake candidates (step S28). Then, the meal intake detection unit 70 determines whether each meal intake candidate is a meal intake (step S29). Then, the meal intake detection unit 70 determines whether the determination of whether each meal intake candidate is a meal intake has been conducted for all the meal intake candidates (step S30). When the determination at step S30 is "No", step S29 is executed again. When the determination at step S30 is "Yes", the meal intake candidate elimination unit 90 eliminates from candidates the meal intake candidate that is determined as being unlikely to be a meal intake (as not being a meal intake) (step S31). Then, the meal intake candidate elimination unit 90 determines whether there is no meal intake candidate that is determined as not being a meal intake (step S32). When the determination at step S32 is "No", the process is executed again from step S24. Accordingly, the heartbeat peak of each meal intake candidate is extracted again after the meal intake candidate that is determined as not being a meal intake is eliminated from candidates. When the determination at step S32 is "Yes", the execution of the flowchart ends.

[0041] In the present embodiment, the meal intake candidate that is determined as not being a meal intake is eliminated from meal intake candidates. Accordingly, the meal intake candidate that is determined as not being a meal intake is inhibited from affecting other meal intake candidates. Therefore, the accuracy of the detection of a meal intake is improved.

(Example of Effects in Real Data)

[0042] FIG. 13A is measurement data of temporal changes in heart rate when the interval between two meals was made to be short. As an example, the period from the time when the heart rate increases by 10 bpm or more to the time when the heart rate decreases by more than half of the rise is detected as a meal intake. Since the interval between meals is short, the heart rate increase occurring with the second meal intake starts before the heart rate decreases by more than half of the rise of the heart rate. Thus, two meals may be detected as one meal.

[0043] FIG. 13B illustrates separation between the first meal intake candidate A and the second meal intake candidate B according to the above embodiments. More specifically, the correction is made under the assumption where the decrease of the heart rate of the first meal intake candidate A continues after the second meal intake candidate B starts. Such a correction improves the accuracy of the detection of a meal intake for two meal intake candidates.

[0044] FIG. 14A and FIG. 14B illustrate other device

configurations of the meal intake detection device 100 and the meal intake detection device 100a. As illustrated in FIG. 14A, the meal intake detection device may have a configuration in which data is exchanged over radio between a server including: the CPU 101; the RAM 102; the storage device 103; and a wireless device 107 and a wearable device including: the display device 104; the heartbeat measuring device 105; the acceleration sensor 106; and a wireless device 108. Alternatively, as illustrated in FIG. 14B, the meal intake detection device may have a configuration in which data is exchanged over radio among a server including: the CPU 101; the RAM 102; the storage device 103; and the wireless device 107, a terminal including: the display device 104 and the wireless device 108, and a wearable device including: the heartbeat measuring device 105; the acceleration sensor 106; and a wireless device 109.

[0045] In the above embodiments, the meal intake candidate detection unit 20 functions as an example of a detection unit that detects a rise at which the ascent rate of the heart rate is equal to or greater than a threshold value. The heartbeat peak extraction unit 30 and the heartbeat peak correction unit 40 function as an example of a separation unit that extracts as a meal intake candidate a time range from a detected rise by the detection unit to the time at which the heart rate decreases to a predetermined value in temporal changes in heart rate, and when the second meal intake candidate is extracted in the extracted time range of the first meal intake candidate, separates the first meal intake candidate and the second meal intake candidate along a predetermined line. The meal intake detection unit 70 functions as an example of another detection unit that detects whether each of the first meal intake candidate and the second meal intake candidate is a meal intake based on feature quantities relating to a meal intake of the separated first meal intake candidate and the separated second meal intake candidate. The meal intake candidate elimination unit 90 functions as an example of an elimination unit that eliminates from meal intake candidates the meal intake candidate that is detected as not being a meal intake by the detection unit among the meal intake candidates extracted by the extraction unit. The meal index estimation unit 80 functions as an example of an estimation unit that estimates an index relating to a meal intake for the meal intake candidate detected as a meal intake by the detection unit.

[0046] Embodiments of the present invention have been described in detail. However, the present invention is not limited to the specific embodiments but may be varied or changed within the scope of the claimed invention.

Claims

1. A meal intake detection device **characterized by** comprising:

a detection unit configured to detect a rise of heart rate;

a separation unit configured to extract as a meal intake candidate a time range from a detected rise by the detection unit to time when the heart rate decreases to a predetermined value in temporal changes in heart rate, and when a second meal intake candidate is extracted in a time range of an extracted first meal intake candidate, separate the first meal intake candidate and the second meal intake candidate along a predetermined line; and

another detection unit configured to detect whether each of the first meal intake candidate and the second meal intake candidate is a meal intake based on feature quantities relating to the first meal intake candidate and the second meal intake candidate separated by the separation unit.

2. The meal intake detection device according to claim 1, **characterized in that** the separation unit is configured to obtain the predetermined line by using the first meal intake candidate to a start point of the second meal intake candidate.
3. The meal intake detection device according to claim 1, **characterized in that** the separation unit is configured to, when a heart rate of the first meal intake candidate tends to decrease at a time of a rising of the second meal intake candidate, obtain as the predetermined line a line that starts from the time of the rising of the second meal intake candidate and has a slope equal to a slope of heart rate of the first meal intake candidate at the time of the rising of the second meal intake candidate.
4. The meal intake detection device according to claim 1, **characterized by** further comprising: an elimination unit configured to eliminate from meal intake candidates a meal intake candidate that is detected as not being a meal intake by the another detection unit among meal intake candidates extracted by the extraction unit.
5. The meal intake detection device according to claim 1, **characterized by** further comprising: an estimation unit configured to estimate an index relating to a meal intake for a meal intake candidate that is detected as a meal intake by the another detection unit.
6. A meal intake detection method **characterized in that:**

a detection unit detects a rise of heart rate;

a time range from a detected rise by the detection unit to time when heart rate decreases to a predetermined value in temporal changes in the heart rate is extracted as a meal intake candidate; 5

when a second meal intake candidate is extracted in a time range of an extracted first meal intake candidate, a separation unit separates the first meal intake candidate and the second meal intake candidate along a predetermined line; 10

and

another detection unit detects whether each of the first meal intake candidate and the second meal intake candidate is a meal intake based on feature quantities relating to the first meal intake candidate and the second meal intake candidate separated by the separation unit. 15

7. A meal intake detection program causing a computer to execute a process, the process **characterized by** comprising: 20

detecting a rise of heart rate;

extracting as a meal intake candidate a time range from a detected rise to time when heart rate decreases to a predetermined value in temporal changes in the heart rate; 25

when a second meal intake candidate is extracted in a time range of an extracted first meal intake candidate, separating the first meal intake candidate and the second meal intake candidate along a predetermined line; and 30

detecting whether each of the first meal intake candidate and the second meal intake candidate is a meal intake based on feature quantities relating to the first meal intake candidate and the second meal intake candidate that are separated. 35

40

45

50

55

FIG. 1




FIG. 2A




FIG. 2B




FIG. 3A
HEART RATE




FIG. 3B




FIG. 4




FIG. 5




FIG. 6A




FIG. 6B




FIG. 6C






FIG. 7A



FEATURE VECTOR OF MEAL INTAKE CANDIDATE A	①AREA FEATURE QUANTITY	②SPEED FEATURE QUANTITY
	③AMPLITUDE FEATURE QUANTITY	④TIME FEATURE QUANTITY

DETECT WHETHER MEAL INTAKE CANDIDATE A IS MEAL INTAKE

FIG. 7B



FEATURE VECTOR OF MEAL INTAKE CANDIDATE B	①AREA FEATURE QUANTITY	②SPEED FEATURE QUANTITY
	③AMPLITUDE FEATURE QUANTITY	④TIME FEATURE QUANTITY

DETECT WHETHER MEAL INTAKE CANDIDATE B IS MEAL INTAKE

FIG. 8




FIG. 9A




FIG. 9B




FIG. 10




FIG. 11A




FIG. 11B




FIG. 12




FIG. 13A




FIG. 13B




FIG. 14A





FIG. 14B



INTERNATIONAL SEARCH REPORT

International application No.

PCT/JP2015/081122

A. CLASSIFICATION OF SUBJECT MATTER

A61B5/0245(2006.01) i, A61B5/00(2006.01) i

According to International Patent Classification (IPC) or to both national classification and IPC

B. FIELDS SEARCHED

Minimum documentation searched (classification system followed by classification symbols)

A61B5/00-5/03, G06Q50/22-50/24

Documentation searched other than minimum documentation to the extent that such documents are included in the fields searched

Jitsuyo Shinan Koho 1922-1996 Jitsuyo Shinan Toroku Koho 1996-2016

Kokai Jitsuyo Shinan Koho 1971-2016 Toroku Jitsuyo Shinan Koho 1994-2016

Electronic data base consulted during the international search (name of data base and, where practicable, search terms used)

C. DOCUMENTS CONSIDERED TO BE RELEVANT

Category*	Citation of document, with indication, where appropriate, of the relevant passages	Relevant to claim No.
A	JP 2000-245713 A (Sanyo Electric Co., Ltd.), 12 September 2000 (12.09.2000), paragraphs [0006], [0007] (Family: none)	1-7
A	JP 10-504739 A (Laniado Eran Meia), 12 May 1998 (12.05.1998), page 6, lines 4 to 6; page 9, line 25 to page 10, line 5; fig. 2 & US 5398688 A column 1, lines 6 to 9; column 3, lines 56 to 68; fig. 2 & WO 1996/003076 A1 & EP 771173 A1 & AU 1918795 A & IL 112382 A & CA 2195547 A1	1-7

☒ Further documents are listed in the continuation of Box C.
 ☐ See patent family annex.

* Special categories of cited documents:

"A" document defining the general state of the art which is not considered to be of particular relevance

"E" earlier application or patent but published on or after the international filing date

"L" document which may throw doubts on priority claim(s) or which is cited to establish the publication date of another citation or other special reason (as specified)

"O" document referring to an oral disclosure, use, exhibition or other means

"P" document published prior to the international filing date but later than the priority date claimed

"T" later document published after the international filing date or priority date and not in conflict with the application but cited to understand the principle or theory underlying the invention

"X" document of particular relevance; the claimed invention cannot be considered novel or cannot be considered to involve an inventive step when the document is taken alone

"Y" document of particular relevance; the claimed invention cannot be considered to involve an inventive step when the document is combined with one or more other such documents, such combination being obvious to a person skilled in the art

"&" document member of the same patent family

Date of the actual completion of the international search
08 January 2016 (08.01.16)Date of mailing of the international search report
19 January 2016 (19.01.16)Name and mailing address of the ISA/
Japan Patent Office
3-4-3, Kasumigaseki, Chiyoda-ku,
Tokyo 100-8915, Japan

Authorized officer

Telephone No.

Form PCT/ISA/210 (second sheet) (January 2015)

INTERNATIONAL SEARCH REPORT

International application No.

PCT/JP2015/081122

C (Continuation). DOCUMENTS CONSIDERED TO BE RELEVANT

Category*	Citation of document, with indication, where appropriate, of the relevant passages	Relevant to claim No.
A	Kazunari OUCHI et al., "Healthcare Services Using a Wearable Device", IPSJ SIG Notes, 23 February 2007 (23.02.2007), vol.2007, no.14, pages 29 to 36	1-7

Form PCT/ISA/210 (continuation of second sheet) (January 2015)

REFERENCES CITED IN THE DESCRIPTION

This list of references cited by the applicant is for the reader's convenience only. It does not form part of the European patent document. Even though great care has been taken in compiling the references, errors or omissions cannot be excluded and the EPO disclaims all liability in this regard.

Patent documents cited in the description

- JP 2010158267 A [0003]

专利名称(译)	膳食检测装置，膳食检测方法和膳食检测程序		
公开(公告)号	EP3372153A4	公开(公告)日	2018-10-31
申请号	EP2015907801	申请日	2015-11-05
[标]申请(专利权)人(译)	富士通株式会社		
申请(专利权)人(译)	FUJITSU LIMITED		
当前申请(专利权)人(译)	富士通有限公司		
[标]发明人	MORI TATSUYA MAEDA KAZUHO INOMATA AKIHIRO		
发明人	MORI, TATSUYA MAEDA, KAZUHO INOMATA, AKIHIRO		
IPC分类号	A61B5/0245 A61B5/00		
CPC分类号	A61B5/4866 A61B5/02405 A61B5/02438 A61B5/7278 A61B5/7282 G16H20/60 G16H50/20		
代理机构(译)	慧智林LLP		
优先权	PCT/JP2015/081122 2015-11-05 WO		
其他公开文献	EP3372153A1		
外部链接	Espacenet		

摘要(译)

进餐检测装置包括：检测单元，被配置为检测心率的上升；分离单元，被配置为从检测单元的检测到心率的上升时间变化中心率降低到预定值的时间，以及当提取第二膳食摄入候选时，提取作为进餐候选的时间范围。提取的第一膳食摄入候选的时间范围，沿预定线分开第一膳食摄入候选和第二膳食摄入候选；另一检测单元，被配置为基于与由分离单元分离的第一膳食摄入候选和第二膳食摄入候选相关的特征量来检测第一膳食摄入候选和第二膳食摄入候选中的每一个是否是膳食摄入。