(19)

(12)





(11) **EP 2 441 015 B1**

EUROPEAN PATENT SPECIFICATION

- (45) Date of publication and mention of the grant of the patent: 05.12.2018 Bulletin 2018/49
- (21) Application number: 10786670.9
- (22) Date of filing: 08.06.2010

(51) Int Cl.: G06F 17/00 ^(2006.01) A61B 5/00 ^(2006.01) A61B 5/0452 ^(2006.01)

G06F 19/00 ^(2018.01) G16H 15/00 ^(2018.01) A61B 5/0468 ^(2006.01)

- (86) International application number: PCT/US2010/037728
- (87) International publication number: WO 2010/144413 (16.12.2010 Gazette 2010/50)

(54) SYSTEMS AND METHODS FOR VIEWING PATIENT DATA SYSTEME UND VERFAHREN ZUR ANSICHT VON PATIENTENDATEN SYSTÈMES ET PROCÉDÉS DE VISUALISATION DE DONNÉES DE PATIENT

- (84) Designated Contracting States: AL AT BE BG CH CY CZ DE DK EE ES FI FR GB GR HR HU IE IS IT LI LT LU LV MC MK MT NL NO PL PT RO SE SI SK SM TR
- (30) Priority: 08.06.2009 US 185096 P
- (43) Date of publication of application: 18.04.2012 Bulletin 2012/16
- (73) Proprietor: AirStrip IP Holdings, LLC San Antonio, TX 78218 (US)
- (72) Inventors:
 - POWELL, William Cameron San Antonio Texas 78218 (US)

- MOORE, Stephen Trey San Antonio Texas 78261 (US)
- (74) Representative: Conroy, John et al Fish & Richardson P.C. Highlight Business Towers Mies-van-der-Rohe-Straße 8 80807 München (DE)
- WO-A1-2006/078954
 WO-A2-2009/034507

 US-A1-4989610
 US-A1-2002052559

 US-A1-2002151812
 US-A1-2004054296

 US-A1-2006217623
 US-A1-2007179356

 US-A1-2008188765
 US-A1-2009054743

 US-B1-7137074
 US-B1-7346174

Note: Within nine months of the publication of the mention of the grant of the European patent in the European Patent Bulletin, any person may give notice to the European Patent Office of opposition to that patent, in accordance with the Implementing Regulations. Notice of opposition shall not be deemed to have been filed until the opposition fee has been paid. (Art. 99(1) European Patent Convention).

Description

FIELD

[0001] This invention generally relates to systems and methods for transmitting, receiving and displaying data and/or information over wireless communication and data processing devices, and more specifically to a system and method for collecting, uploading, transmitting, receiving, downloading, manipulating, and displaying medical patient data and/or information to a remote device operable by a health care provider.

BACKGROUND

[0002] While physicians and other health care providers currently utilize a large number of products and systems that benefit from advances in wireless communication technology, there are still significant limitations to the information that can be transmitted, received, and displayed over these devices in a practical and efficient manner. There are many limitations that are intrinsic to mobile devices, especially those constraints related to speed, performance, memory, and display size. In addition, because of the critical nature of medical data, it is important that the technology work reliably and efficiently over potentially low speed, low bandwidth, and sometimes intermittent wireless connections.

[0003] Efforts have been made in the past to transmit medical information through various telecommunication means to health care professionals for review and analysis. Some such efforts are outlined in commonly assigned U.S. Pat. App. No. 11/301,348, filed on December 12, 2005. Such examples utilize wireless data communication technologies to transmit medical information to health care providers, or to condition data such that it may be useful for remote monitoring purposes.

[0004] US 2008/0188765 describes a computer-implemented method for locating an arrhythmogenic focus or pathway in a heart of a living subject, which is carried out by recording a reference set of electrocardiographic signals from the subject, stimulating the heart at multiple locations endocardially or epicardially, and while stimulating at the multiple locations, recording respective sets of pace-mapped electrocardiographic signals.

[0005] US 2009/0054743 describes a method of generating and representing the status of various physiological parameters that are monitored for patients during hospitalization.

[0006] US 2002/0151812 describes an apparatus for outputting heart sounds includes an implantable system and an external system. The implantable system includes a sensor for generating sensed signals representing detected heart sounds, an interface circuit and a control circuit for receiving the sensed signals, generating data representing the heart sounds therefrom, and transmitting the data to the external system via the interface circuit for curcuit for

communicating with the implantable system, and a control circuit for receiving the data representing the heart sounds and for generating control signals that cause an output device to generate outputs representing the sounds.

[0007] WO2009034507 describes an ECG monitoring system continuously monitors a patient's ECG waveform and periodically identifies the patient's QT interval.

[0008] US 2006/0217623 describes a distributed system wherein remote mobile devices communicate with a computer processing unit accessing patient data from a database entity, wherein patient data comprises ECG data. Users may review, annotate and measure features of interest in the retrieved ECG data, wherein said meas-

¹⁵ urements are also stored in the database entity.

SUMMARY

[0009] The invention is defined in the appended claims. 20 [0010] One example method of measuring features of a digitally generated waveform includes communicating patient data to a device that is remote from a source of the patient data, generating the waveform on a touchscreen display of the device, and measuring along an 25 axis of the waveform. In some aspects, the measuring includes generating a first point corresponding to the waveform based on contact with the touch-screen display, generating a second point corresponding to the waveform based on contact with the touch-screen dis-30 play, automatically measuring a distance between the first point and the second point along the axis upon generation of the second point, and displaying a value corresponding to the distance on the touch-screen display. [0011] In some aspects, the value includes a time val-35 ue.

[0012] In some aspects, the value includes a voltage value.

[0013] In some aspects, the method further includes generating a digital caliper in the touch-screen display,
the caliper including a first and a second jaw that are movable along the axis, the first point being generated based on an intersection between the first jaw and the waveform, and the second point being generated based on an intersection between the second jaw and the wave-

⁴⁵ form. The caliper is generated based on a user demand.[0014] In some aspects, the axis includes one of a time axis and a voltage axis.

[0015] In some aspects, the waveform corresponds to one of an electrocardiogram (ECG), a blood pressure, an oxygen saturation, and an end-tidal CO₂.

[0016] In some aspects, the method further includes moving at least one of the first point and the second point along the axis, and updating the value in real-time based on movement of the at least one of the first point and the second point along the axis.

[0017] In some aspects, the method further includes storing the value in a memory of the device.

[0018] In some aspects, the method further includes

50

transmitting the value to a patient information system located at a facility.

[0019] In other aspects, the present invention provides a method of monitoring patient data using a device. In some aspects, the method includes communicating patient data to the device, the device being remote from a source of the patient data, generating a waveform on a display of the device based on the patient data, identifying an occurrence of a waveform feature, and generating a sound based on the occurrence of the waveform feature. [0020] In some aspects, the generating a sound com-

prises repetitively generating the sound in response to periodic occurrences of the waveform feature.

[0021] In some aspects, the generating a sound comprises generating a persistent sound.

[0022] In some aspects, the method further includes storing an audio file in memory of the device, and retrieving the audio file from memory based on generating the waveform, the sound being generated based on the audio file.

[0023] In some aspects, the method further includes storing a plurality of audio files in memory of the device, and selecting an audio file from the plurality of audio files based on a type of the waveform, the sound being generated based on the audio file.

[0024] In some aspects, the waveform feature includes one of a spike, a peak, a trough and a flat line.

[0025] In some aspects, the waveform corresponds to one of a heart rate, a blood pressure, an oxygen saturation, and an end-tidal CO₂.

[0026] In still other aspects, the present invention provides a method of notifying a user of an alert. In some aspects, the method includes generating an alert based on patient data, providing the alert to a third-party notification service, forwarding the alert to a device, the device being remote from a source of the patient data, receiving the alert at the device, and presenting an indication of the alert on a display of the device.

[0027] In some aspects, the alert is generated at an 40 information system that is resident at a facility, at which the patient data is collected.

[0028] In some aspects, the alert is generated at a data management system that is remote from the source of the patient data.

[0029] In some aspects, the alert corresponds to an application that is resident on the device, and that is executable using the device. In some aspects, the application is dormant when the alert is received at the device.

[0030] In some aspects, the indication includes at least one of a badge associated with an application icon, and 50 an alert summary. The alert summary provides patient information. In some aspects, the method includes selecting the alert summary, and displaying detailed alert information on the display of the device in response to the selecting.

[0031] Other aspects provide a computer-readable storage medium encoded with a computer program comprising instructions that, when executed, operate to

cause one or more processors to perform one or more of the methods provided herein.

[0032] Still other aspects provide a system including one or more processors, and a computer-readable me-

5 dium coupled to the one or more processors having instructions stored thereon which, when executed by the one or more processors, cause the one or more processors to perform one or more of the methods provided herein.

10 [0033] It is appreciated that methods in accordance with the present disclosure can include any combination of the aspects and features described herein. That is to say that methods in accordance with the present disclosure are not limited to the combinations of aspects and 15

features specifically described herein, but also include any combination of the aspects and features provided. [0034] The details of one or more embodiments are set forth in the accompanying drawings and the description below. Other features, objects, and advantages will 20 be apparent from the description and drawings, and from the claims.

DESCRIPTION OF DRAWINGS

25 [0035]

30

35

45

FIG. 1 is a schematic illustration of an exemplar system architecture in accordance with the present disclosure

FIG. 2 is a schematic illustration of another exemplar system architecture in accordance with the present disclosure.

FIG. 3 is a functional block diagram of components that can be used to implement the present disclosure.

FIG. 4 is a more detailed view of the functional block diagram of FIG. 3.

FIGs. 5A-5H provide exemplar screenshots on an exemplar mobile device in accordance with the present disclosure.

FIGs. 6A-6C provide exemplar screenshots illustrating features in accordance with the present disclosure.

FIG. 7 is a flowchart illustrating exemplar steps that can be executed to provide waveform measuring in accordance with the present disclosure.

FIG. 8 is a flowchart illustrating exemplar steps that can be executed to provide audible monitoring of patient information in accordance with the present disclosure.

FIG. 9 provides an exemplar screenshot illustrating a push-notification feature in accordance with the present disclosure.

FIG. 10 is a flowchart illustrating exemplar steps that can be executed to provide push-notification of patient data alerts in accordance with the present disclosure.

[0036] Like reference symbols in the various drawings indicate like elements.

DETAILED DESCRIPTION

[0037] The present disclosure provides a healthcare provider with secure, remote access to patient data. The present disclosure builds on that of commonly assigned U.S. Pat. App. No. 11/301,348, filed on December 12, 2005. U.S. Pat. App. No. 11/301,348 claims the benefit of U.S. Prov. App. No. 60/641,057, filed on January 3, 2005. The present disclosure also builds on that of commonly assigned U.S. Pat. App. No. 11/301,348, filed on December 12, 2005. The present disclosure also builds on that of commonly assigned U.S. Pat. App. No. 11/301,348, filed on December 12, 2005. For purposes of the instant description, and by way of non-limiting example, implementations of the present disclosure will be described in the context of patient data corresponding to maternity patients (e.g., obstetric (OB) patient). Implementations of the present disclosure are applicable to any variety of patients and corresponding patient data.

[0038] Referring now to FIG. 1, an exemplar system architecture 10 is illustrated, and includes a remote device 12, connectivity interface(s) 14, a network 16, a first facility system 18, and a second facility system 20. As discussed in further detail herein, data is transferred from each of the first and second facility systems 18, 20 through the network 16 and connectivity interface(s) 14 for presentation, or display on the remote device 12. Further, data can be transferred from the remote device 12 through the connectivity interface(s) 14 and network 16 to each of the first and second facility systems 18, 20. Although a single remote device 12 is illustrated, it is contemplated that one or more remote devices 12 can communicate with each of the first and second facility systems 18, 20 through the network 16 and connectivity interface(s) 14. Similarly, although two facility systems are illustrated, the present disclosure can be implemented with one or more facility systems.

[0039] The remote device 12 can include any number of exemplar devices. Such exemplar devices include, but are not limited to, a mobile phone, a smartphone, a personal digital assistant (PDA), a laptop, a tablet personal computer (PC), a desktop PC, and/or combinations thereof. The remote device 12 includes a display 22, a processor 24, memory 26, an input interface 28, and a communication interface 30. The processor 24 can process instructions for execution of implementations of the present disclosure. The instructions can include, but are not limited to, instructions stored in the memory 26 to display graphical information on the display 22. Exemplar displays include, but are not limited to, a thin-film-transistor (TFT) liquid crystal display (LCD), or an organic light emitting diode (OLED) display.

[0040] The memory 26 stores information within the remote device 12. In some implementations, the memory 26 can include a volatile memory unit or units, and/or a non-volatile memory unit or units. In other implementations, removable memory can be provided, and can in-

clude, but is not limited to, a memory card. Exemplar memory cards can include, but are not limited to, a secure digital (SD) memory card, a mini-SD memory card, a USB stick, and the like.

⁵ [0041] The input interface 28 can include, but is not limited to, a keyboard, a touchscreen, a mouse, a trackball, a microphone, a touchpad, and/or combinations thereof. In some implementations, an audio codec (not shown) can be provided, which receives audible input

from a user or other source through a microphone, and converts the audible input to usable digital information. The audio codec can generate audible sound, such as through a speaker that is provided with the remote device 12. Such sound may include, but is not limited to, sound

¹⁵ from voice telephone calls, recorded sound (e.g., voice messages, music files, etc.), and sound generated by applications operating on the remote device 12.

[0042] The remote device 12 may communicate wirelessly through the communication interface(s) 14, which
 ²⁰ can include digital signal processing circuitry. The communication interface(s) 14 may provide communications under various modes or protocols including, but not limited to, GSM voice calls, SMS, EMS or MMS messaging,

CDMA, TDMA, PDC, WCDMA, CDMA2000, and/or
 GPRS. Such communication may occur, for example, through a radio-frequency transceiver (not shown). Further, the remote device can be capable of short-range communication using features including, but not limited to, Bluetooth and/or WiFi transceivers (not shown).

30 [0043] The remote device 12 communicates with the network 16 through the connectivity interface(s) 14. The connectivity interface(s) 14 can include, but is not limited to, a satellite receiver, cellular network, a Bluetooth system, a Wi-Fi system (e.g., 802.x), a cable modem, a

³⁵ DSL/dial-up interface, and/or a private branch exchange (PBX) system. Each of these connectivity interfaces 14 enables data to be transmitted to/from the network 16. The network 16 can be provided as a local area network (LAN), a wide area network (WAN), a wireless LAN

40 (WLAN), a metropolitan area network (MAN), a personal area network (PAN), the Internet, and/or combinations thereof.

[0044] In the exemplar systems of FIGs. 1 and 2, the first facility system 18 includes a plurality of facilities 40,

⁴⁵ and the second facility system 20 includes a facility 40. It is contemplated that each facility system 18, 20 can include one or more facilities, and is not limited to the exemplar arrangement described herein. In the case of multiple facilities, the facilities can be remotely located
⁵⁰ from one another, and/or can be located at a common location, or site (e.g., separate departments in a common building). Each facility system 18, 20 can be provided as a medical care system, for example, which medical care system can include one or more hospitals, hospital systems, clinics, physician offices, and the like.

[0045] Each facility 40 includes an associated information system 42, computer interface(s) 44, and patient monitoring device(s) 46. Exemplar information systems

can include, but are not limited to, a clinical information system (CIS), and/or a hospital information system (HIS). Each information system 42 can be provided as a server, and supports the acquisition, storage, modification, and distribution of clinical information, such as patient data, throughout the facility 40 and/or facility system 18, 20. Exemplar information systems include, but are not limited to, the Integriti Enterprise Wide CIS, the QS Perinatal CIS, and/or the QS Critical Care CIS, each provided by General Electric (GE), the OBiX Perinatal Data System provided by Clinical Computer Systems, Inc., the Intelli-Vue Clinical Information Portfolio (ICIP), Critical Care and/or OB TraceVue Perinatal Data System provided by Royal Philips Electronics, the Essentris Perinatal, Acute Care and/or Critical Care systems provided by CliniComp International, Inc., the CALM Perinatal Data System provided by LMS Medical Systems, the Horizon Lab, Medical Imaging, Cardiology, Emergency Care and/or Perinatal Care provided by McKesson Corporation, and/or the NaviCare WatchChild System provided by Hill-Rom. Each information system 42 can communicate with one or more ancillary information systems (not shown) that can include, but are not limited to, a pharmacy management system, a laboratory management system, and/or a radiology management system. Although the exemplar system architecture 10 includes an information system 42 located at each facility 40, it is contemplated that the facilities 40 can communicate with a common information system 42 that is remotely located from either facility 40, or that is located at one of the facilities 40 within the facility system 18, 20.

[0046] The computer interface 44 can communicate with the information system 42 to enable access to information that is stored within, and managed by the information system 42. The computer interface 44 can include, but is not limited to, a personal computer (PC) (e.g., desktop, laptop, or tablet). Although a single computer interface 44 is illustrated in the exemplar architectures described herein, it is contemplated that one or more computer interface 44 and the information system 42 can be achieved via a direct connection, or remotely through a network (not shown) that can include, but is not limited to, a LAN, a WLAN, amd/or the Internet.

[0047] Each patient monitoring device 46 monitors physiological characteristics of a particular patient 50, and generates data signals based thereon. Exemplar patient monitoring devices include, but are not limited to, maternal/fetal heart rate monitors, blood pressure monitors, respiratory monitors, vital signs monitors, electrocardiogram monitors, oximetry and/or anesthesia monitors. Exemplar patient monitoring devices can include, but are not limited to the Corometric Series Monitors, DINAMAP Series Monitors, DASH Series Monitors, and/or Solar Series monitors provided by GE Healthcare, IntelliVue and/or SureSigns Series patient monitors, and/or Avalon Series Fetal Monitors provided by Royal

Philips Electronics, and/or Infinity Series patient monitors provided by Draeger Medical. The data signals are communicated to the information system 42, which collects patient data based thereon, and stores the data to a patient profile that is associated with the particular patient. Although a single patient monitoring device 46 is illustrated per each patient 50, it is contemplated that multiple patient monitoring devices 46 can monitor a particular

patient 50. The patient monitoring device(s) 46 can communicate with the information system 42 via a direct connection, or remotely through a network (not shown) that can include, but is not limited to, a LAN, a WAN, a WLAN, and/or the Internet.

[0048] The patient data is made available for display
on the computer device 44. A healthcare provider (e.g., a nurse and/or physician) can augment the patient data by inputting patient information that is also stored to the information system 44. More specifically, the healthcare provider can input patient information corresponding to
a particular patient 50, which patient information can be stored to the patient profile. By way of one non-limiting example, a nurse can input nursing notes, which nursing

notes can be stored to the patient profile in the information system. As used herein, the term patient information in-²⁵ cludes any information corresponding to a patient that is input and stored to the information system 42 through the computer interface 44. Patient information is dis-

cussed in further detail below.
[0049] As discussed above, each information system
42 stores patient data that can be collected from the patient monitoring devices 46, as well as additional patient information, that can include information that is input by a healthcare provider. The information system 46 communicates the patient data and/or the additional patient
data to a data management system (DMS) 60. The DMS 60 can be provided as a server, or a virtual server, that runs server software components, and can include data storage including, but not limited to, a database and/or flat files. In the exemplar system architecture of FIG. 1,

40 each facility system 18, 20 includes a corresponding DMS 60. In such an arrangement, each information system 42 communicates patient data, and/or additional patient data to the DMS 60. Furthermore, and as discussed in further detail below, the DMS 60 can communicate

⁴⁵ ancillary information to the information system 42. Communication between the DMS 60 and the information system(s) 42 can be achieved via a direct connection, or remotely through a network (not shown) that can include, but is not limited to, a LAN, a WAN, a WLAN, and/or the
 ⁵⁰ Internet.

[0050] A DMS 60 corresponding to a particular facility system can be remotely located from any of the facilities 40 of the facility system 18, 20, or can be located at a particular facility 40 of the facility system 18, 20. In the exemplar system architecture of FIG. 1, the DMS 60 is remotely located from either facility 40 within each of the facility systems 18, 20. It is contemplated, however, that the DMS 60 can be located at one of the facilities 40, and

5

remote from the other facility 40.

[0051] In the exemplar system architecture of FIG. 2, a common DMS 60' is provided. The common DMS 60' is common to various facility systems 18, 20, and is not associated with a particular facility system 18, 20. Each information system 42 communicates with the DMS 60' via a direct connection, or remotely through a network (not shown) that can include, but is not limited to, a LAN, a WAN, a WLAN, and/or the Internet. In the exemplar arrangement of FIG. 2, the DMS 60' communicates with each of the information systems 42 through the network 16. The information systems 42 communicate patient data and/or patient information to the DMS 60', and the DMS 60' can communicate ancillary information to the information system 42, as discussed in further detail below.

[0052] In the exemplar system architecture of FIG. 1, the facility 40, or facility system 18, 20 installs the DMS 60 as a local DMS, and the DMS 60 sits at the local site with other servers that can include, but are not limited to, the information system 42. In some implementations, the DMS 60 can be sectioned off, or separated from a logical network perspective, but still physically exists with the other servers that belong to the respective facility 40. Server components are installed on the DMS 60, which components can include, but are not limited to, a database component, a database synchronization component, a web services component, and/or a structured query language (SQL) component. An information system interface can also be installed on the DMS 60, and functions as the interface to the information system 42. By way of non-limiting example, the information system interface can include OBLink, provided by GE Healthcare. In some implementations, the DMS 60 can be arranged in a multiple server configuration, in which one server only hosts web service related components and is logically segregated, and another server has the remaining necessary server components installed.

[0053] The exemplar system architecture of FIG. 2, provides for the remote location of data collection at the DMS 60'. In such implementations, the DMS 60' can be provided at a third-party site, remote from any of the facilities 40, or facility systems 18, 20. The third-party functions as a DMS host, and the necessary server components are installed on the remotely hosted DMS 60'. In some implementations, a business-to-business (B2B) virtual private network (VPN) can be created between the remotely hosted DMS 60' and the network of the facility 40 or facility system 18, 20. In this manner, the facility 40 and/or facility system 18, 20 forgoes the purchase and/or maintenance of another physical server, or DMS 60. Further, the up-time and the status of availability of the DMS 60' are easier to manage on the part of a dedicated third-party. The DMS' access to the network can be attended to by the third-party, as opposed to burdening the facility 40, or the facility systems 18, 20. Further, the third-party can implement virtual server technologies to leverage multiple DMS installations on a single physical server. In such implementations, a plurality of virtual servers are logically partitioned in a single physical server, and each virtual server has the capability of running its own operating system and server components, and can be independently booted.

[0054] The DMS 60, 60' synchronizes and transfers data between the remote device 12, or multiple remote devices 12, and multiple information systems 42. More specifically, the DMS 60, 60' processes and prepares the

¹⁰ patient data and/or patient information for transfer to and presentation on multiple remote devices 12, from the information systems 42. The DMS 60, 60' also processes and prepares ancillary information for transfer to and storage in the information system 42 from the remote device

 12, or multiple remote devices 12 for potential presentation at a corresponding computer device 44. Exemplar
 DMSs can include, but are not limited to, the AirStrip Server provided by AirStrip Technologies, LLC, which AirStrip Server includes AirStrip Server Components in stalled therein.

[0055] Referring now to FIGs. 3 and 4, an exemplar software component, or module structure 70 to implement the features of the present disclosure will be described in detail. The exemplar structure enables patient

²⁵ data and patient information to be communicated to/from, and to be synchronized between the information system 42 and the remote device 12, regardless of the operating system, or platform, operating on the remote device 12. Exemplar platforms include, but are not limited to, RIM

³⁰ Blackberry, Apple iPhone, MS Pocket PC 2003, Win Mobile 5.x (Pocket PC, Smartphone), Win Mobile 6.x (standard, professional) and/or any platforms to be developed (e.g., Google Android, and Palm PRE).

[0056] FIG. 3 illustrates an overview of the exemplar
module structure 70, which includes a platform 72, or operating system, of the remote device 12, intermediary components 74, a connectivity mechanism 76, and an operating system 78 of the information system 42. In this arrangement, the remote device 12 is a client that executes a client application thereon. The intermediary components 74 are resident on the DMS 60, 60', and include a client services module 80, an integration services module 82, and an adapter services module 84. The DMS 60, 60' functions as an intermediary between the platform

⁴⁵ 72 resident on the remote device 12 and the operating system 78 of the information system 42. A plurality of platforms 72 is illustrated to exemplify the ability of the DMS 60, 60' to transfer data to and from any platform 72 operating on the remote device 12. The connectivity
⁵⁰ mechanism 76 enables communication between the

DMS 60, 60' and a particular information system 42. A plurality of connectivity mechanisms 76 and corresponding operating systems 78 is illustrated to exemplify the ability of the DMS 60, 60' to transfer data to and from any operating system 78 on the information system 42.

[0057] In the exemplar structure illustrated in FIG. 4, the client services module 80 includes an alert and notification services module 90, an observer client services

10

module 92, and a global services module 94. The integration services module 82 includes a synchronization services module 96, and an alert engines rule 98. The synchronization services module 96 can communicate with a synchronization database 100 to provide so-called intelligent synchronization. The adapter services module 84 includes a configuration module 102, an authentication module 104, an admission, discharge and transfer (ADT) module 106, and a patient data module 108.

[0058] The alert and notification services module 90 sends alerts and/or notifications to the remote device 12, as discussed in further detail below. The observer client services module 92 facilitates communication between client applications, running on the remote device 12, and backend server components that provide access to application data. The observer client services module 92 transmits data through a formatted request, and receives data in a proprietary data format. An exemplar data format includes, but is not limited to, JavaScript Object Notation (JSON), which is a lightweight computer data interchange format that provides a text-based, humanreadable format for representing simple data structures and associative arrays, called objects). The global services module 94 communicates with the client running on the remote device 12 and performs registration and client application configuration settings. Client application settings can be customized by the user of the remote device 12, and the facility 40 and/or facility systems 18, 20, for which the remote device 12 is configured to receive data.

[0059] The integration services module 82 is responsible for routing requests that are received from the observer client services module 92 to retrieve and package requested data, and to send a corresponding response. More specifically, the integration services module 82 requests data from the adapter services module 84, or from the synchronization database 100 depending on how the particular DMS 60, 60' is configured. If the DMS 60, 60' is configured to use a vendor adapter, the request goes directly to the adapter services module 84 to retrieve the data. If the DMS 60, 60' is configured for synchronization, then the data is retrieved from the synchronization database 100. The synchronization services module 96 communicates with the adapter services module 84 to maintain the synchronization database 100 current using intelligent synchronization.

[0060] Intelligent synchronization is synchronization executed based on variable configuration parameters, which enable the possibility of only some of the patient data and/or patient information to be synchronized as opposed to all of the available data being continuously synchronized. By using custom business rule logic to intelligently determine which patient data and/or information should be synchronized, and which patient data and/or information should be synchronized, the DMS 60, 60' functions more efficiently and can service an increased number of clients and configurations. By way of non-limiting example, prior to a user logging on to the DMS 60, 60' via the remote device 12, no specific patient

data and/or information is synchronized. Instead, only a patient census list and specific data elements corresponding to particular patients 50 are synchronized between the DMS 60, 60' and the information system(s) 42. Once the user logs on, and selects a particular patient 50 to review, the synchronization services begin synching all of the available patient data and/or information for that particular patient 50. Consequently, subsequent reviews of the particular patient 50 are much faster, because the patient data and/or information has been syn-

chronized.[0061] The adapter services module 84 is the mechanism that retrieves data from the information system 42, through the connectivity mechanism module 76, and that

¹⁵ structures the data for the DMS 60, 60'. The data is formatted and rules are applied for the specific DMS 60, 60', for which the adapter has been written, regardless of whether the data is directly requested for a client through the integration services module 82, or is retrieved

through the synchronization services module 96. The configuration module 102 captures configuration settings used by the information system(s) 42. The configuration module 102 can use already existing configuration information so that it does not have to be replicated in the

²⁵ DMS 60, 60'. By way of non-limiting example, all of the patient beds of a particular facility 40, and to which unit(s) they belong are typically stored in the information system(s) 42. The configuration module 102 reduces, or obviates manual effort in entering the configuration infor-

³⁰ mation. The configuration module 102 can also prevent problems from occurring when a configuration change is made in the information system(s) 42, but a system administrator forgets to make the change in the DMS 60, 60'.

³⁵ [0062] The authentication module 104 handles the authentication needs of the DMS 60, 60', which can include, but are not limited to active directory authentication, vendor authentication, device ID restrictions, device phone number restrictions, and any combination thereof. Each
 ⁴⁰ facility system 18, 20 and/or facility 40 is configured to authenticate using any combination of such authentica-

 tion mechanisms. Device ID restriction is the ability for an authentication service to look at a pre-configured list of device ID's, associated with respective remote devices
 that are authorized to connect to the facility system

⁴⁵ 12, that are authorized to connect to the facility system
18, 20 and/or facility 40, and only authorizes call from software client that originate with that device ID (i.e., from the particular remote device 12). The device phone number restriction restricts access to remote devices 12
⁵⁰ that have a phone number that has been pre-configured in the authentication system.

[0063] The ADT module 106 enables the use of existing ADT interfaces within the facility system 18, 20 and/or facility 40 to obtain patient admission, discharge and transfer information in order to always know which patient is associated to which bed and/or unit. The patient data module 108 provides all waveform and non-waveform patient data and/or information from the information sys-

7

30

tem(s) 42 to the DMS 60, 60'. The patient data module 108 can also provide all waveform and non-waveform acquired from a data acquisition system such as the Air-Strip data collector or an independent data collecting system including but not limited to Capsule Technologies' Data Captor system. This includes, but is not limited to, all nursing charting information as well as any automated means of data collection used by the information system(s) 42.

[0064] In the exemplar structure illustrated in FIG. 4, each connectivity mechanism module 76 includes a database module 110, a web services module 112, a request module 114, and an application layer protocol module 116. By way of non-limiting example, the request module 114 can manage HTTP requests, and/or the application layer protocol can include the health level seven (HL7) application layer protocol. The connectivity mechanism module 76 enables the DMS 60, 60' to connect to and communicate with each particular information system 42. In some implementations, the connectivity mechanism module 76 can include application protocol interfaces (APIs), through which it communicates with the information system 42. In other implementations, the connectivity mechanism module 76 can directly access the information system 42.

[0065] As discussed at the outset, the present disclosure provides a healthcare provider, or user of the remote device 12, with secure, remote access to patient data and/or patient information. As used herein, the term patient data refers to physiological data that can be obtained from the patient monitoring device(s), and/or physiological patient data that is input into the information system 42 by a local healthcare provider (e.g., a nurse, or physician). The term patient information refers to information corresponding to a particular patient that is input into the information system 42 by the local healthcare provider. Exemplar patient information can include, but is not limited to, the patient's name, the name of the doctor(s) assigned to the patient, the nurse(s) assigned to the patient, a facility identification, a patient bed identification, a summary of key patient data, and/or chart annotations. In the exemplar case of a maternity patient, the key patient data can include, but is not limited to, delivery progress information such as cervical exam status, membrane status, gravida, para, epidural status, and/or whether the patient is attempting a vaginal birth after cesarean (VBAC).

[0066] The patient data and/or patient information provided to the remotely located user can be provided in real-time data, and/or as historical data and information. The patient data and/or patient information is communicated between the remote device 12 and the DMS 60, 60' using a secure connection that is established over the network 16. A secure log-in, or sign-on process is provided, which is preferably compliant with the provisions of the Health Insurance Portability and Accountability Act (HIPAA). The secure sign-on authenticates the identity of the user of the remote device 12 based on a unique user ID and password combination. Both the user

ID and the password must be correct in order to establish the secure communication between the remote device 12 and the DMS 60, 60'. Implementations of sign-on and authentication processes are described in further detail below.

[0067] A census, or patient list is provided to the remote device 12, which captures a variety of the information and/or data described herein that is associated with each of one or more monitored patients 50. Strip charting is

¹⁰ also provided, in which patient data and/or information can be presented to the user in graphical form. In the exemplar case of a maternity patient, a fetal strip and maternal contraction information can be provided for a particular patient 50. More specifically, the particular pa-

¹⁵ tient 50 is selected from the patient list, and the patient information and/or data is subsequently presented. The presented information and/or data can include a fetal strip and maternal contraction waveform, the patient name, the hospital name, the patient room and/or bed number,

and the date and time. The strip charting can provide a real-time view of the patient data, as well as a historical view of the patient data. More specifically, the waveform display can be updated in real-time, such that the user of the remote device 12 observes the patient data as it occurs and/or is recorded. The user can scroll through

occurs and/or is recorded. The user can scroll through the waveform display, to view historical patient data, as described in further detail below.

[0068] Several navigation features can be provided that enable the user to manipulate a view of the waveform display. In some implementations, the user can zoom in/out of the displayed image. In this manner, the user can view very specific waveform information, and/or other waveform micro-characteristics by zooming in, for example, and/or can view patterns or other waveform mac-

³⁵ ro-characteristics by zooming out, for example. In some implementations, the user can scroll forward or backward through the waveform display. In this manner, the user can view historical patient data.

[0069] A patient data display can also be provided. In
 some implementations, the patient data display can overlay the strip charting described herein. In other implementation, the patient data display can be provided as an overlay, and/or as a separate display. The patient data display can include, but is not limited to, the patient's
 ⁴⁵ name age fetal gestation gravida parity cervical exam

name, age, fetal gestation, gravida, parity, cervical exam information, and physician name.

[0070] Implementations of the present disclosure can be realized on any one of a number of operating systems, or platforms 72 associated with the particular remote de-

⁵⁰ vice 12. As discussed above with reference to FIGs. 3 and 4, exemplar platforms include, but are not limited to, RIM Blackberry, Apple iPhone, MS Pocket PC 2003, Win Mobile 5.x (Pocket PC, Smartphone), Win Mobile 6.x (standard, professional) and/or any platforms to be developed (e.g., Google Android, and Palm PRE). Referring now to FIGs. 5A-5K exemplar implementations of the present disclosure will be described with reference to screen-shots of an exemplar remote device 12. The re-

mote device 12 of the instant example includes a mobile device, such as a cellular telephone, or smartphone, that includes an exemplar platform (e.g., Apple iPhone). It is appreciated, however, that implementations of the present disclosure can be executed on any type of remote device 12, and/or using any type of platform 72 that is supported by the remote device 12. It is appreciated that the screen-shots illustrated and described herein are merely exemplar in nature, and are not exhaustive of the functionality and features provided in implementations of the present disclosure.

[0071] FIG. 5A illustrates an exemplar screen-shot of a loading screen 120 that is initiated after the user inputs a user ID and password combination. If the user ID and password combination is authenticated, secure communication between the remote device 12 and the DMS 60, 60' is established, and the remote device 12 retrieves patient data and/or information from the DMS 60, 60'. In some implementations, the user may be associated with more than one facility system 18, 20, with each facility system 18, 20 including its own DMS 60 (see, for example, FIG. 1). In such cases, secure communication between each of the DMS 60 and the remote device 12 is established upon the confirmation of the user ID and password combination, as explained in further detail herein.

[0072] FIG. 5B illustrates an exemplar screen-shot of a facility summary display 122 that provides a summary of the facility system(s), and/or particular facility, or facilities, with which the user is associated. The facility summary display 122 includes a plurality of selectable icons. The exemplar illustration of FIG. 5B provides a facility icon 124 (e.g., "Community Hospital"), and a facility system (e.g., "Anyplace Health (WAN)") that includes two facility icons 126, 128 associated therewith (e.g., "Northside Hospital," and "Southside Hospital"). The facility (e.g., "Community Hospital") can be a stand-alone facility that is not associated with a facility system (e.g., "Anyplace Health (WAN)"). In this case, the facility can be described as "non-WAN", because it is not networked with other facilities, and/or a facility system. The facility system can be described as "WAN," because it is a facility system that includes a plurality of inter-communicating facilities associated therewith.

[0073] With particular reference to the facility system icons 126, 128, attributes can be provided. Exemplar attributes can include, but are not limited to, patient counts. A first patient count 130 provides the total number of patients at the facility, for which the particular user is responsible. For example, if the user is a physician, the first patient count 130 illustrates the total number of patients that are under the care of that particular physician. In the exemplar illustration of FIG. 5B, the total number of patients associated with the user at "Community Hospital" is twelve, the total number of patients associated with the user at "Southside Hospital" is fifteen. A second patient count

132 can be provided, which displays a specific patient count. The specific patient count can include the number of patients deemed to be new patients. In the exemplar illustration of FIG. 5B, a specific patient count of two is associated with the "Community Hospital." This can indicate, for example, that of the twelve patients at "Com-

munity Hospital," two are deemed to be new patients.[0074] The exemplar facility summary display of FIG.5B further includes a shortcut menu 134 that provides

¹⁰ links to exemplar functions, and/or other displays. Although the illustrated exemplar links include "Search," "Recently Viewed," and "All Patients," it is contemplated that the shortcut menu 134 can be customized by the user to provide any available links that the user desires.

¹⁵ By selecting "Search," a search screen is provided, in which the user can input search terms to search for patients, facilities, facility systems, and the like. By selecting "Recently Viewed," a display screen is provided, in which a number of patients, whose patient data has been re-

20 cently viewed by the user using the remote device are listed. By way of non-limiting example, the list of patients can be determined by a fixed count (e.g., the last X number of patients that the user has viewed), and/or can be determined by a time (e.g., the patients viewed by the

²⁵ user over the last X day(s)). By selecting "All Patients," a display screen is provided, which lists all of the patients that are assigned to the specific user, regardless of facility or facility system. The "All Patients" link can also include a total patient count 130, and a specific patient count

30 132. In this case, the total patient count 130 within the shortcut menu 134 indicates the number of patients that are under the care of that particular user, regardless of the facility, and the specific patient count 132 can indicate the number of new patients of the total.

³⁵ [0075] The user can navigate from the facility summary display 122 by selecting any one of the icons. An icon can be selected in any one of a number of manners that is supported by the particular platform. By way of non-limiting examples, an icon can be selected by touching
⁴⁰ the screen with a digit (i.e., finger), a stylus, and/or other pointing device, as well as with a digital cursor, and/or a keypad.

[0076] FIG. 5C illustrates an exemplar screen-shot of a patient summary display 136 that provides a summary 45 of the patients associated with a particular facility (e.g., "Memorial Hospital" in the exemplar illustration of FIG. 5C). The summary can include patient data and/or information. In the exemplar illustration of FIG. 5C, the summary information includes the patient's name, the attend-50 ing nurse's name, the responsible physician's name, the patient's bed number, the date and time of the most recent, or last, medical event, a condition (e.g., "Unstable Angina," "Urosepsis," and/or "Congestive Heart Failure (CHF)"), as well as a particular medication prescribed to 55 the patient. A particular summary type can be selected from a menu 138. In the exemplar illustration of FIG. 5C, the menu 138 is provided as a touch screen menu, and includes a plurality of selectable options. It is contemplat-

30

35

40

ed, however, that the menu 138 can be provided in any one of a number of manners including, but not limited to, a drop-down menu. The illustrated, exemplar options of the menu 138 include "Patients," "My Patients," "New Patients," "Alerts," as well as the option "More" to display additional options. In the exemplar illustration of FIG. 5C, the patient summary display 136 lists the patients associated with the particular user (e.g., "Dr. Craig") at the particular facility (e.g., "Memorial Hospital"). By selecting "Patients," all of the patients at the particular facility can be displayed. By selecting "New Patients," only those patients that are deemed to be new patients are displayed. By selecting "Alerts," patients having a corresponding alert status, discussed in further detail herein, are displayed. A selectable chart 140 icon can also be provided for each patient listed. By selecting the chart icon, one or more graphical strip charts of patient data and/or patient information can be displayed, as discussed in further detail below.

[0077] By selecting a particular patient from the patient summary display 136, a specific patient summary display 142 is provided. FIG. 5D illustrates an exemplar specific patient summary display 142 for the patient "Abraham, Natalie" selected from the patient summary display 136. The specific patient summary display 142 can provide a variety of summarized patient data and/or information 144. The specific patient summary 142 further includes selectable icons for drilling down to more specific patient information. For example, a monitor icon 146 can be provided, which enables the user to view graphical strip charts of patient data and/or patient information, as discussed in further detail below. In the exemplar context of a maternity patient, the selectable icon is provided as a "Fetal Monitor" icon. Other patient data and/or information can be viewed on the specific patient summary display. In the exemplar illustration of FIG. 5D, a selectable menu is provided, through which the user can select particular summary data and/or information to view. The exemplar options illustrated in FIG. 5D include, but are not limited to, a medication dosage history, a progress history, vitals, and laboratory results. FIGs. 5E and 5F illustrate other, exemplar specific patient summary displays 142 that include other monitor icons 146 (e.g., "Patient Monitor," and "Ventilator Monitor"), as well as other available summary data and/or information (e.g., electrocardiograms (ECGs or EKGs), charts, and PACS).

[0078] Referring now to FIG. 5G, an exemplar screenshot of a patient vital display 150. The patient vital display 150 can provide patient data values and/or can display the patient data graphical form (e.g., as a strip). In the exemplar illustration of FIG. 5G, values of patient vitals are provided, and the patient vitals are shown in graphical form. The exemplar patient vitals include, but are not limited to, heart rate, blood pressure, oxygen saturation, end-tidal CO₂, Swan tracing, Arterial Line Tracing, Central Venous Pressure, EKG/ECG, Ventilator waveforms and body temperature. The patient vitals can be provided as a static display, can be displayed in real-time (i.e., updated as measurements are taken by the patient monitoring device(s)), and/or can be played back (i.e., playback stored patient data to provide a historical display). **[0079]** FIG. 5H illustrates an exemplar screen-shot of a patient display 152, which display summary strips 154 associated with particular patient data. In the exemplar context of a maternity patient, the display summary strips 154 include, but are not limited to a fetal strip, labor curve, and blood pressure. A note summary 156 can also be

¹⁰ provided. By selecting one of the display summary strips 154, the corresponding strip can be displayed in more detail, as described below with respect to FIGs. 5I and 5J. By selecting the note summary 156, nursing notes and information pertinent to the particular patient can be ¹⁵ displayed to provide specific detail.

[0080] The exemplar implementations of FIGs. 5I and 5J provide a fetal strip 158. It is appreciated, however, that implementations of the present disclosure can display any type of pertinent data strip including, but not 20 limited to, a fetal strip, a labor curve, blood pressure, heart rate, oxygen saturation, end-tidal CO₂, Swan tracing, Arterial Line Tracing, Central Venous Pressure, EKG/ECG, Ventilator waveforms and/or body temperature. The exemplar illustration of FIG. 5I provides the fetal 25 strip in a portrait layout, and the exemplar illustration of FIG. 5J provides the fetal strip in a landscape layout. The landscape layout enables the user to either view a greater amount of patient data over a longer time period, or view the patient data in expanded detail across the same time

period.
[0081] Upon selecting the particular strip for display, a request is made from the remote device 12 to the corresponding information system 42 to transmit the patient data and/or information for the particular patient. The patient data and/or information is provided to the remote device 12, with the remote device 12 buffering the patient data and/or information to provide real-time viewing thereof. Basic real-time viewing of the patient data is provided on a background grid with a timing mark shown and patient information being provided. In implementations of the present disclosure, the patient data trace moves from right to left across the display.

[0082] In implementations of the present disclosure, provide zoom in and out functionality. In each case, the 45 user can take advantage of viewing a trend (e.g., zoom out), or a specific data segment (e.g., zoom in) to facilitate a judgment with regard to the condition of the patient. Implementations of the present disclosure also provide variable speed scroll functionality of the data strip. More 50 specifically, the user of the remote device 12 can be presented with a bi-directional, multilevel selection bar, and/or virtual controls that regulate the direction and the scrolling speed of the data strip. In this manner, the user can customize viewing of the patient data to personal 55 preferences, or to the specific situations that dictate review of the patient data. For example, the user may quickly scroll through the data strip to a point, at which a particular anomaly occurred, and can more slowly scroll the

data strip around that point to study the patient data in further detail.

[0083] Referring now to FIGs. 6A-7, touch-measurement of waveforms displayed on the remote device 12 will be described. With particular reference to FIG. 6A, an exemplar screen-shot of a patient vital display 250 is illustrated, and is similar to that shown in FIG. 5G. The patient vital display 250 can provide patient data values and/or can display the patient data graphical form (e.g., as a strip, or waveform). In the exemplar illustration of FIG. 6A, values of patient vitals are provided, and the patient vitals are shown in graphical form. The exemplar patient vitals include, but are not limited to, heart rate, blood pressure, oxygen saturation, end-tidal CO₂, Swan tracing, Arterial Line Tracing, Central Venous Pressure, EKG/ECG, Ventilator waveforms and body temperature. The patient vitals can be provided as a static display, can be displayed in real-time (i.e., updated as measurements are taken by the patient monitoring device(s)), and/or can be played back (i.e., playback stored patient data to provide a historical display).

[0084] The user of the remote device 12 can select a particular waveform to be presented in detail on the display of the device 12. For example, the display can be provided as a touch-screen display, in which contact with the display can be registered as input to the device 12 to regulate operation thereof. Such contact can be achieved by direct contact by the user (e.g., using fingertips), and/or contact using a stylus. If the user selects the heart rate waveform in FIG. 6A, the exemplar screenshots of FIGs. 6B and 6C can be displayed. With particular reference to FIG. 6A, the heart rate waveform 252 can be shown in real-time as the underlying patient data is received by the remote device. For example, the user can select a "Real Time" display button to view the waveform 252 in real-time. Playback buttons 256 are also included to provide a historical review of the waveform 252, and to pause the real-time updating of the waveform 252. [0085] A measurement button 258 is provided to enable the user to measure select waveform features. By selecting the measurement button, a digital caliper is generated on the display and includes a first caliper line, or jaw 260, and a second caliper line, or jaw 262. If the user would like to make a waveform measurement along a horizontal direction 264 (e.g., along a time axis) the caliper lines 260, 262 are aligned perpendicular to the horizontal direction 264, and are movable therealong (see FIG. 6B). Points 266, 268 can be generated on the caliper lines 260, 262, respectively, corresponding to where the first and second caliper lines 260, 262 intersect the waveform 252. A measurement value 270 is automatically generated based on the positions of the caliper lines 260, 262 along the horizontal direction 264. The respective positions of the caliper lines 260, 262 can be manipulated by touching the display and dragging a selected caliper line 260, 262 along the horizontal direction 264. As the selected caliper line 260, 262 moves, the measurement value 270 can be automatically updated

in real-time as the movement occurs. In the exemplar screen-shot of FIG. 6B, the measurement value 270 corresponds to a time measurement between peaks of the waveform 252.

- ⁵ **[0086]** If the user would like to make a waveform measurement in the vertical direction 272 (i.e., along a voltage axis) the caliper lines 260, 262 are aligned perpendicular to the vertical direction 272, and are movable therealong (see FIG. 6C). Points 266, 268 are generated on the cal-
- ¹⁰ iper lines 260, 262, respectively, corresponding to where the first and second caliper lines 260, 262 intersect the waveform 252. A measurement value 274 is automatically generated based on the positions of the caliper lines 260, 262 along the vertical direction 272. The respective

¹⁵ positions of the caliper lines 260, 262 can be manipulated by touching the display and dragging a selected caliper line 260, 262 along the vertical direction 272. As the selected caliper line 260, 262 moves, the measurement value 274 can be automatically updated in real-time as the movement occurs. In the exemplar screen-shot of FIG.

movement occurs. In the exemplar screen-shot of FIG. 6C, the measurement value 274 corresponds to a voltage measurement between a peak and a trough of the waveform 252.

[0087] Referring now to FIG. 7, a flowchart illustrates exemplar steps that can be executed to provide waveform measurement on the display of the device 12. In step 700, patient data is communicated to a device, which is remote from a source of the patient data. In step 702, a waveform is generated on a touch-screen display of the device. A first point is generated corresponding to

the waveform based on contact with the touch-screen display in step 704, and a second point is generated corresponding to the waveform based on contact with the touch-screen display in step 706. In step 708, a distance

³⁵ between the first point and the second point is automatically measured along the axis upon generation of the second point. In step 710, a value corresponding to the distance is displayed on the touch-screen display. The value can include one of a time value and a voltage value.

40 As discussed above at least one of the first point and the second point can be moved along the axis, and the value updated in real-time based on movement of the at least one of the first point and the second point along the axis. The value can be stored in a memory of the device, and/or

⁴⁵ the value can be communicated to a patient information system located at a facility.

[0088] As seen in each of FIGs. 6A-6C, an audio button 280 can be provided in the display. The audio button 280 can be selected to turn auditory features of the device 12 ON or OFF. The auditory features can correspond to auditory features that are available from the patient monitoring devices 46 that directly monitor the patient 50 at a facility 40. More specifically, the audio features of the device 12 simulate those of the patient monitoring devices 46. In this manner, the user of the device 12 can audibly monitor the patient from a remote location, as if the user were audibly monitoring the patient directly at the facility 40. The auditory features can be emitted from the

device 12 using a speaker.

[0089] The auditory features can be provided for each of the exemplar waveforms described herein. By way of non-limiting example, auditory features can be provided for pulse oximetry and/or heart rate. With particular reference to 6A, the user of the device 12 is presented with waveforms for particular patient vital signs, which waveforms may be updated in real-time based on received patient data. As certain features (e.g., spike, peak, trough, flat line) occur for a particular waveform, a sound is generated corresponding to the occurrence of the features. In the case of a heart rate waveform, a sound can be generated based on the waveform spikes, or peaks that correspond to a patient's heartbeat. In this manner, the sound is periodically repeated and an audible cadence is presented to the user, enabling the user to audibly monitor the patient's heart rate. In some cases, such as when the waveform is flat, or featureless, a persistent sound can be generated. Such a case can occur, for example, when the patient's heart stops beating and is in a so-called "flat line" condition. The sound can be stored as an audio file, or multiple audio files in memory 26 of the device 12, and can correspond to a particular audio file format (e.g., wav, mp3, m4p).

[0090] Referring now to FIG. 8, a flowchart illustrates exemplar steps that can be executed to provide the above-described auditory features. In step 800, patient data is communicated to the device, the device being remote from a source of the patient data. In step 802, a waveform is generated on a display of the device based on the patient data. In some cases, the waveform can correspond to one of a heart rate, a blood pressure, an oxygen saturation, and an end-tidal CO₂. In some cases, the waveform feature can include one or more of a spike, a peak, a trough and a flat line. An occurrence of a waveform feature is identified in step 804, and a sound is generated based on the occurrence of the waveform feature in step 806. The sound can be repetitively generated in response to periodic occurrences of the waveform feature. The sound can be a persistent sound. In some cases, an audio file can be stored in memory of the device, and can be retrieved based on generating the waveform, the sound being generated based on the audio file. In some cases, a plurality of audio files can be stored in memory of the device, and an audio file can be selected from the plurality of audio files based on a type of the waveform, the sound being generated based on the audio file.

[0091] Referring now to FIGs. 9 and 10, a push-notification feature is provided. More specifically, routines can be executed at the DMS 60, 60' to analyze and review patient data as it is received from the information system(s) 42, and alerts can be generated based on this analysis and review. In some cases, the information system 42 can analyze and review patient data, and generate alerts based on this analysis and review. These alerts can be pushed to the device 12 using a push-notification infrastructure. More specifically, the alerts resident at the DMS 60, 60' (regardless of whether the alerts were generated at the DMS 60, 60', or the information system 42) can be forwarded to a third-party push notification service, which pushes the alerts to the device 12. In this manner, the underlying application does not have to be run-

ning on the device in order to receive such alerts. [0092] With particular reference to FIG. 9, a display of the device 12 includes an application icon 300. In the exemplar illustration of FIG. 9, the application includes

¹⁰ AirStrip Critical Care (CC) provided by AirStrip Technologies, LLC. It is appreciated, however, that the application can include any application that is executed on the device 12 to display patient data on the device 12. Such applications can also include, but are not limited to, Air-

¹⁵ Strip OB, AirStrip Cardiology, AirStrip Laboratory, and/or AirStrip Imaging. The application icon 300 includes a badge 302 that, in the exemplar illustration, indicates that two alerts have been pushed to the device. Upon receiving an alert, the device 12 can display an alert summary

20 304 that provides relevant patient and alert information. In this manner, the user can decide whether they should immediately view the alert. The badge notification and/or alert summary is automatically generated and/or updated while the underlying application is dormant (i.e., not being

executed). In other words, the application does not need to be active and executing on the device 12 in order for the device 12 to receive the alerts. Furthermore, an audible (i.e., sound), or physical (e.g., vibration) indicator can be generated when an alert is received, notifying the user that an alert has been received. This provides significant benefits in that the user can receive the alerts while working in another application on the device 12, and can receive the alerts when not using the device 12 at all.

³⁵ [0093] Referring now to FIG. 10, exemplar steps that can be executed to provide push-notification will be described. In step 1000, an alert is generated based on patient data. In some cases, the alert can be generated at an information system that is resident at a facility, at
⁴⁰ which the patient data is collected. In some cases, the

alert can be generated at a data management system that is remote from the source of the patient data. In step 1002, the alert is provided to a third-party notification service. The alert is communicated to a device, the device

⁴⁵ being remote from a source of the patient data, in step 1004, and the alert is received at the device in step 1006. The alert can correspond to an application that is resident on the device, and that is executable using the device. The application can be dormant when the alert is received
⁵⁰ at the device. In step 1008, an indication of the alert is presented on a display of the device. The indication can include at least one of a badge associated with an appli-

cation icon, and an alert summary. The alert summary can provide patient information. The alert summary can
⁵⁵ be selected, and detailed alert information can be displayed on the display of the device in response to the selecting.

[0094] The present disclosure can be implemented in

20

25

30

digital electronic circuitry, or in computer hardware, firmware, software, or in combinations thereof. The invention can be implemented as a computer program product, i.e., a computer program tangibly embodied in an information carrier, e.g., in a machine-readable storage device, for execution by, or to control the operation of, data processing apparatus, e.g., a programmable processor, a computer, or multiple computers. A computer program can be written in any form of programming language, including compiled or interpreted languages, and it can be deployed in any form, including as a standalone program or as a module, component, subroutine, or other unit suitable for use in a computing environment. A computer program can be deployed to be executed on one computer or on multiple computers at one site or distributed across multiple sites and interconnected by a communication network. Such a computer program can include modules and/or code segments for executing one or more of the features, aspects and/or implementations provided herein.

[0095] Method steps of the present disclosure can be performed by one or more programmable processors executing a computer program product to perform functions of the present disclosure by operating on input data and generating output. By way of one non-limiting example, a computer program product can include modules and/or code segments corresponding to each of the method steps, aspects and/or features provided herein. Method steps can also be performed by, and apparatus of the present disclosure can be implemented as, special purpose logic circuitry, e.g., an FPGA (field programmable gate array) or an ASIC (application-specific integrated circuit).

[0096] Processors suitable for the execution of a computer program include, by way of example, both general 35 and special purpose microprocessors, and any one or more processors of any kind of digital computer. Generally, a processor will receive instructions and data from a read-only memory or a random access memory or both. 40 The essential elements of a computer are a processor for executing instructions and one or more memory devices for storing instructions and data. Generally, a computer will also include, or be operatively coupled to receive data from or transfer data to, or both, one or more mass storage devices for storing data, e.g., magnetic, 45 magneto-optical disks, or optical disks. Information carriers suitable for embodying computer program instructions and data include all forms of non-volatile memory, including by way of example semiconductor memory devices, e.g., EPROM, EEPROM, and flash memory de-50 vices; magnetic disks such as internal hard disks and removable disks; magneto-optical disks; and CD-ROM and DVD-ROM disks. The processor and the memory can be supplemented by, or incorporated in special pur-55 pose logic circuitry.

[0097] The present disclosure can be implemented in a system including, but not limited to the exemplar systems described herein, which include a back-end component, e.g., as a data server, or that includes a middleware component, e.g., an application server, or that includes a front-end component, e.g., a client device, such as the remote device 12, having a graphical user interface or a Web browser through which a user can interact with an implementation of the invention, or any combination of such back-end, middleware, or front-end components. The components of the system can be interconnected by any form or medium of digital data communication, e.g., a communication network.

10

Claims

15 1. A method of measuring features of a digitally generated waveform, comprising:

> synchronizing and transferring, by a data management system (60, 60'), patient data between multiple information systems (42) in communication with a source (46) of the patient data and a remote mobile device (12)), the data management system (60, 60') configured to function as an intermediary between the remote mobile device (12) and the multiple information systems (42) and including a synchronization services module (96) communicating with a synchronization database (100) that stores patient data, said patient data being synchronized between the data management system and the multiple information systems, the data management system communicating (700) patient data retrieved from the synchronization database (100) to the mobile device that is remote from the source (46) of the patient data;

generating (702) the waveform (252) on a touchscreen display of the remote mobile device based on the patient data;

measuring along an axis of the waveform, the measuring comprising:

generating (704) a first point (266, 268) corresponding to the waveform based on contact with the touch-screen display,

generating (706) a second point (266, 268) corresponding to the waveform based on contact with the touch-screen display,

automatically measuring (708) a distance between the first point and the second point along the axis upon generation of the second point,

displaying (710) a value (270) corresponding to the distance on the touch-screen display; and

transmitting the value to a patient information system (42) located at a facility (40).

20

30

35

45

50

55

- **2.** The method of claim 1, wherein the value includes one of a time value and a voltage value.
- The method of claim 1, further comprising generating a digital caliper in the touch-screen display based on 5 a user demand, the caliper including a first and a second jaw that are movable along the axis, the first point being generated based on an intersection between the first jaw and the waveform, and the second point being generated based on an intersection between the second jaw and the waveform.
- **4.** The method of claim 1, wherein the axis includes one of a time axis and a voltage axis.
- 5. The method of claim 1, wherein the waveform corresponds to one of an electrocardiogram, a blood pressure, an oxygen saturation, and an end-tidal CO_2 .
- 6. The method of claim 1, further comprising:

moving at least one of the first point and the second point along the axis; and updating the value in real-time based on movement of the at least one of the first point and the second point along the axis.

- **7.** The method of claim 1, further comprising storing the value in a memory of the device.
- 8. A computer-readable storage medium encoded with a computer program comprising instructions that, when executed, operate to cause one or more processors to perform the method of one of claims 1-7.

Patentansprüche

1. Verfahren zum Messen von Merkmalen einer digital ⁴⁰ erzeugten Wellenform, umfassend:

Synchronisieren und Übertragen, durch ein Datenmanagementsystem (60, 60'), von Patientendaten zwischen mehreren Informationssystemen (42) in Kommunikation mit einer Quelle (46) der Patientendaten und einem abgesetzten Mobilgerät (12), wobei das Datenmanagementsystem (60, 60') ausgelegt ist zum Fungieren als ein Vermittler zwischen dem abgesetzten Mobilgerät (12) und den mehreren Informationssystemen (42) und ein Synchronisationsdienstemodul (96) aufweist, das mit einer Synchronisationsdatenbank (100) kommuniziert, die Patientendaten speichert, wobei die Patientendaten zwischen dem Datenmanagementsystem und den mehreren Informationssystemen synchronisiert werden, wobei das Datenmanagementsystem aus der Synchronisationsdatenbank (100) abgerufene Patientendaten an das Mobilgerät, das von der Quelle (46) der Patientendaten abgesetzt ist, kommuniziert (700); Erzeugen (702) der Wellenform (252) auf einem

Berührbildschirm des abgesetzten Mobilgeräts basierend auf den Patientendaten;

Messen entlang einer Achse der Wellenform, wobei das Messen Folgendes umfasst:

Erzeugen (704) eines ersten Punkts (266, 268), entsprechend der Wellenform, basierend auf Kontakt mit dem Berührbildschirm, Erzeugen (706) eines zweiten Punkts (266, 268), entsprechend der Wellenform, basierend auf Kontakt mit dem Berührbildschirm, automatisches Messen (708) einer Distanz zwischen dem ersten Punkt und dem zweiten Punkt entlang der Achse bei Erzeugung des zweiten Punkts,

Anzeigen (710) eines Werts (270), der der Distanz auf dem Berührbildschirm entspricht; und

Übermitteln des Werts an ein in einer Einrichtung (40) befindliches Patienteninformationssystem (42).

- Verfahren nach Anspruch 1, wobei der Wert einen Zeitwert oder einen Spannungswert aufweist.
- 3. Verfahren nach Anspruch 1, ferner umfassend Erzeugen eines digitalen Messschiebers auf dem Berührbildschirm, basierend auf einem Benutzerwunsch, wobei der Messschieber einen ersten und einen zweiten Schenkel aufweist, die entlang der Achse bewegbar sind, wobei der erste Punkt basierend auf einem Schnittpunkt zwischen dem ersten Schenkel und der Wellenform erzeugt wird und der zweite Punkt basierend auf einem Schnittpunkt zwischen dem zweiten Schenkel und der Wellenform erzeugt wird.
- **4.** Verfahren nach Anspruch 1, wobei die Achse eine Zeitachse oder eine Spannungsachse umfasst.
- **5.** Verfahren nach Anspruch 1, wobei die Wellenform einem Elektrokardiogramm oder einem Blutdruck oder einer Sauerstoffsättigung oder einem endex-spiratorischen CO₂ entspricht.
- 6. Verfahren nach Anspruch 1, ferner umfassend:

Bewegen des ersten Punkts und/oder des zweiten Punkts entlang der Achse; und Aktualisieren des Werts in Echtzeit, basierend auf Bewegung des ersten Punkts und/oder des zweiten Punkts entlang der Achse.

10

15

- 7. Verfahren nach Anspruch 1, ferner umfassend Speichern des Werts in einem Arbeitsspeicher des Geräts.
- 8. Computerlesbares Speichermedium, codiert mit einem Computerprogramm, umfassend Anweisungen, die, wenn sie ausgeführt werden, bewirken, dass ein oder mehrere Prozessoren das Verfahren nach einem der Ansprüche 1-7 durchführen.

Revendications

1. Procédé de mesure de caractéristiques d'une forme d'onde générée numériquement consistant :

à synchroniser et à transférer, au moyen d'un système de gestion de données (60, 60'), des données de patient entre de multiples systèmes d'informations (42) en communication avec une 20 source (46) des données de patient et un dispositif mobile distant (12), le système de gestion de données (60, 60') étant configuré pour faire office d'intermédiaire entre le dispositif mobile 25 distant (12) et les multiples systèmes d'informations (42) et comprenant un module de services de synchronisation (96) communiquant avec une base de données de synchronisation (100) qui stocke des données de patient, lesdites données de patient étant synchronisées entre le 30 système de gestion de données et les multiples systèmes d'informations, le système de gestion de données communiquant (700) des données de patient récupérées de la base de données de synchronisation (100) au dispositif mobile qui 35 est distant de la source (46) des données de patient ;

à générer (702) la forme d'onde (252) sur un dispositif d'affichage à écran tactile du dispositif mobile distant en se basant sur les données de patient ;

à mesurer le long d'un axe de la forme d'onde, la mesure consistant :

à générer (704) un premier point (266, 268) correspondant à la forme d'onde sur la base d'un contact avec le dispositif d'affichage à écran tactile,

à générer (706) un second point (266, 268) correspondant à la forme d'onde sur la base ⁵⁰ d'un contact avec le dispositif d'affichage à écran tactile,

à mesurer automatiquement (708) une distance entre le premier point et le second point le long de l'axe lors de la génération du second point,

à afficher (710) une valeur (270) correspondant à la distance sur le dispositif d'affichage à écran tactile ; et

à transmettre la valeur à un système d'information de patient (42) situé dans une installation (40).

- 2. Procédé selon la revendication 1, dans lequel la valeur comprend soit une valeur de temps, soit une valeur de tension.
- 3. Procédé selon la revendication 1, consistant en outre à générer un pied à coulisse numérique dans le dispositif d'affichage à écran tactile en se basant sur une demande de l'utilisateur, le pied à coulisse comprenant des premières et seconde mâchoires qui sont mobiles le long de l'axe, le premier point étant généré en se basant sur une intersection entre la première mâchoire et la forme d'onde et le second point étant généré en se basant sur une intersection entre la seconde mâchoire et la forme d'onde.
- **4.** Procédé selon la revendication 1, dans lequel l'axe comprend soit un axe de temps, soit un axe de tension.
- Procédé selon la revendication 1, dans lequel la forme d'onde correspond soit à un électrocardiogramme, soit à une pression sanguine, soit à une saturation en oxygène, soit au CO₂ en fin d'expiration.
- 6. Procédé selon la revendication 1, consistant en outre :

à déplacer le premier point et/ou le second point le long de l'axe ; et

à mettre à jour la valeur en temps réel en se basant sur un mouvement du premier point et/ou du second point le long de l'axe.

- 7. Procédé selon la revendication 1, consistant en outre à stocker la valeur dans une mémoire du dispositif.
- 8. Support de stockage lisible par ordinateur codé avec un programme d'ordinateur comprenant des instructions qui, lorsqu'elles sont exécutées, opèrent pour contraindre un ou plusieurs processeurs à réaliser le procédé selon l'une des revendications 1 à 7.

55

40







FIG. 3







FIG. 5B

FIG. 5A



EP 2 441 015 B1

FIG. 5C







150 мер тина мер тина м.т. 117/78 70 (94) ● 5002 % Sp02 % Sp etC02 mmHg awr pm 50**30** 8 12 \square 4 Settings NBP mmHg 130/88 (99) 37.3 Temp °C Sys. 705 Auto 15 min 11:15 36.0 37 7 PVC0 Memorial Hospital... | Ward Real-Time Abraham, Natalie 🗖 ABP low alarm | 10:58 PM 10:59 PM 5:20 PM Measure со₂ 60 Summary Playback ∠m< Pleth 4BP 125-

FIG. 5G

FIG. 5H



EP 2 441 015 B1



FIG. 6C







FIG. 9



REFERENCES CITED IN THE DESCRIPTION

This list of references cited by the applicant is for the reader's convenience only. It does not form part of the European patent document. Even though great care has been taken in compiling the references, errors or omissions cannot be excluded and the EPO disclaims all liability in this regard.

Patent documents cited in the description

- US 30134805 A [0003] [0037]
- US 20080188765 A [0004]
- US 20090054743 A [0005]
- US 20020151812 A [0006]

- WO 2009034507 A [0007]
- US 20060217623 A [0008]
- US 301348 A [0037]
- US 64105705 P [0037]

patsnap

专利名称(译)	用于查看患者数据的系统和方法		
公开(公告)号	EP2441015B1	公开(公告)日	2018-12-05
申请号	EP2010786670	申请日	2010-06-08
申请(专利权)人(译)	跑道IP控股有限责任公司		
当前申请(专利权)人(译)	跑道IP控股有限责任公司		
[标]发明人	POWELL WILLIAM CAMERON MOORE STEPHEN TREY		
发明人	POWELL, WILLIAM CAMERON MOORE, STEPHEN TREY		
IPC分类号	G06F17/00 G06F19/00 A61B5/00 G16H15/00 A61B5/0452 A61B5/0468 G16B45/00 G16H10/60		
CPC分类号	A61B5/0022 A61B5/0452 A61B5/7415 G06F19/34 G06F19/3418 G16H10/60 G16H15/00 G16H40/67 G16H50/20 A61B5/0006 A61B5/0468 A61B5/74 A61B5/7435 A61B5/7455 A61B5/748		
代理机构(译)	康罗伊,JOHN		
优先权	61/185096 2009-06-08 US		
其他公开文献	EP2441015A4 EP2441015A1		
外部链接	Espacenet		

摘要(译)

测量数字生成波形的特征的方法包括将患者数据传送到远离患者数据源 的设备,在设备的触摸屏显示器上生成波形,以及沿波形轴测量。测量 包括基于与触摸屏显示器的接触产生对应于波形的第一点,基于与触摸 屏显示器的接触产生对应于波形的第二点,自动测量第一点和第二点之 间的距离在产生第二点时沿轴指向,并在触摸屏显示器上显示与该距离 对应的值。

