

(19) World Intellectual Property Organization  
International Bureau



(43) International Publication Date  
10 August 2006 (10.08.2006)

PCT

(10) International Publication Number  
**WO 2006/081975 A1**

(51) International Patent Classification:  
A61B 5/00 (2006.01) A61M 5/142 (2006.01)

Ersigen (CH). JECKELMANN, Joel [CH/CH]; Chemin de la Fontaine 5, CH-1752 Villars-sur-Glane (CH).

(21) International Application Number:  
PCT/EP2006/000663

(74) Agent: KÜNG, Peter; Disetronic Medical Systems AG, Kirchbergstrasse 190, CH-3401 Burgdorf (CH).

(22) International Filing Date: 26 January 2006 (26.01.2006)

(81) Designated States (unless otherwise indicated, for every kind of national protection available): AE, AG, AL, AM, AT, AU, AZ, BA, BB, BG, BR, BW, BY, BZ, CA, CH, CN, CO, CR, CU, CZ, DE, DK, DM, DZ, EC, EE, EG, ES, FI, GB, GD, GE, GH, GM, HR, HU, ID, IL, IN, IS, JP, KE, KG, KM, KN, KP, KR, KZ, LC, LK, LR, LS, LT, LU, LV, LY, MA, MD, MG, MK, MN, MW, MX, MZ, NA, NG, NI, NO, NZ, OM, PG, PH, PL, PT, RO, RU, SC, SD, SE, SG, SK, SL, SM, SY, TJ, TM, TN, TR, TT, TZ, UA, UG, US, UZ, VC, VN, YU, ZA, ZM, ZW.

(25) Filing Language: English

(26) Publication Language: English

(30) Priority Data:  
05002074.2 2 February 2005 (02.02.2005) EP

(71) Applicant (for all designated States except US): DIS-ETRONIC LICENSING AG; Kirchbergstrasse 190, CH-3401 Burgdorf (CH).

(72) Inventors; and

(75) Inventors/Applicants (for US only): ESSENPREIS, Matthias [DE/CH]; Thunstrasse 62, CH-3400 Burgdorf (CH). HAUETER, Ulrich [CH/CH]; Kirchgasse 2, CH-3506 Grossshoechstetten (CH). BERNINI, Nicole [CH/CH]; Dorfstrasse 44, CH-3423 Ersigen (CH). FANKHAUSER, Sybille [CH/CH]; Allmendstrasse 15, CH-3052 Zollikofen (CH). LA BASTIDE, Sebastiaan [BE/CH]; Pourtalèstrasse 2, CH-3074 Muri Bei Bern (CH). MEYER OLDEN, Gunnar [SE/CH]; Thunstrasse 110, CH-3400 Burgdorf (CH). SCHOEMAKER, Michael [DE/DE]; Waldparkstrasse 25a, 68183 Mannheim (DE). HEATON, Kelly [US/CH]; Hofacherweg 6, CH-3423

(84) Designated States (unless otherwise indicated, for every kind of regional protection available): ARIPO (BW, GH, GM, KE, LS, MW, MZ, NA, SD, SL, SZ, TZ, UG, ZM, ZW), Eurasian (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM), European (AT, BE, BG, CH, CY, CZ, DE, DK, EE, ES, FI, FR, GB, GR, HU, IE, IS, IT, LT, LU, LV, MC, NL, PL, PT, RO, SE, SI, SK, TR), OAPI (BF, BJ, CF, CG, CI, CM, GA, GN, GQ, GW, ML, MR, NE, SN, TD, TG).

Published:  
— with international search report

For two-letter codes and other abbreviations, refer to the "Guidance Notes on Codes and Abbreviations" appearing at the beginning of each regular issue of the PCT Gazette.

(54) Title: AMBULATORY MEDICAL DEVICE AND METHOD OF COMMUNICATION BETWEEN MEDICAL DEVICES

(57) Abstract: The present invention relates to an ambulatory medical device and a method of communication between medical devices. The inventive medical device comprises a module for communication with at least a second medical device wherein said module for communication is adapted to be activated by a value of a physiological parameter of an animal. The method of the present invention comprises a first medical device and at least a second medical device wherein the communication between said medical devices is activated by a value of a physiological parameter of an animal.



WO 2006/081975 A1

**Ambulatory medical device and method of communication between medical devices**5 Technical field of the invention

The present invention relates to an ambulatory medical device and a method of communication for medical devices.

Background Art

10 Ambulatory medical devices for the treatment of diabetes include e.g. extra corporal insulin pumps and blood glucose measuring devices such as e.g. hand held glucose meters. Insulin pumps allow a good control of blood glucose concentrations by continuously infusing a basic amount of insulin in a human body (basal insulin rate) and manually controlled additional “meal bolus” insulin quantities thereby reflecting the  
15 insulin secretion by the pancreas. Furthermore, the development of continuous glucose sensors will allow to measure in vivo glucose concentrations over the whole day. The measured glucose data can be used to adjust the diabetes therapy to individual needs.

In order to improve the treatment of diabetes it is important to provide means and  
20 methods to transfer data between medical devices in a quality assuring way

It is therefore the aim of the present invention to provide a medical device allowing a controlled data transfer between medical devices and a method of controlled data transfer.

25 Disclosure of the invention

In a first aspect, the present invention relates to a medical device comprising a module for communication with at least a second medical device wherein the module for communication in said medical device is adapted to be activated by a value of a  
30 physiological parameter of an animal.

The inventive medical device preferably comprises a telemetry system for wireless communication, preferably a telemetry system for RF communication.

Preferably the medical device is selected from the group consisting of a remote control, a PDA, an analyte measuring device, preferably a glucose measuring device such as e.g. a hand held glucose meter, more preferably a strip based glucose meter or combinations thereof.

5

The physiological parameter is preferably selected from the group consisting of an analyte concentration, a physiological characteristic like conductivity of an animal, a physiological vital sign like heart or breath rate, temperature, movement, air- or structure-borne sound, ECG (electrocardiogram) and the like.

10

In a preferred embodiment of the present invention the analyte concentration is a blood glucose concentration.

Preferably, the medical device of the present invention comprises an electrochemical or photometric module for measuring blood glucose. Suitable medical devices are e.g. strip based glucose meters such as AccuChek Compact.

In a second aspect the present invention relates to a system of medical devices. Said system comprises a first medical device of the present invention as described in the previous section and at least a second medical device capable to communicate with said first medical device.

In a preferred embodiment the second medical device is selected from the group consisting of an extra corporal infusion pump, an implantable infusion pump, a pacesetter, an analyte or vital sign sensor, preferably a continuous analyte or vital sign sensor, more preferably a continuous glucose sensor.

In a further preferred embodiment the first medical device and the at least second medical device comprise a telemetry system for wireless communication, preferably a telemetry system for RF communication.

In a third aspect, the present invention relates to a method of communication between a first medical device and at least a second medical device wherein the communication

between said medical devices is enabled and/or activated by a value of a physiological parameter of an animal.

In a preferred embodiment, the communication between the at least two medical devices is enabled and/or activated for a predetermined time. Time duration can be fixed, random  
5 or dependent on the physiological parameter enabling and/or activating the communication or other physiological parameters of the animal body.

The physiological parameter is preferably selected from the group consisting of an analyte concentration, a physiological characteristic like conductivity of an animal, a  
10 physiological vital sign like heart or breath rate, temperature, movement, air- or structure-borne sound, ECG (electrocardiogram) and the like. Preferably the analyte concentration is a blood glucose concentration.

In a preferred embodiment, the activation of communication between the medical devices  
15 is performed on the first medical device by a value of the physiological parameter.

In a further preferred embodiment, the first medical device is selected from the group consisting of a remote control, a PDA, an analyte measuring device, preferably a glucose measuring device, more preferably a strip based glucose meter.  
20

The second medical device is preferably selected from the group consisting of an extra corporal infusion pump, an implantable infusion pump, a pacesetter, an analyte sensor, preferably a continuous analyte sensor, more preferably a continuous glucose sensor.

25 In a preferred embodiment, the communication between said medical devices is a wireless communication, preferably a RF communication.

In a further preferred embodiment, the first medical device receives data from the second medical device.  
30

In a further preferred embodiment, the first medical device sends commands to the second medical device controlling at least partially the function of said device.

Detailed description of the invention

In one aspect, the present invention relates to a novel method for controlling and/or enabling communication between medical devices, in particular medical sensory devices  
5 such as continuous glucose sensors and/or therapeutic devices such as insulin pumps and/or diagnostic medical devices such as glucose meters.

For example, the communication between a continuous glucose sensor applied to a human body and a blood glucose meter can only be established when a blood glucose  
10 measurement has been made in the blood glucose meter. The generation of the blood glucose value in the blood glucose meter enables and/or activates communication between the two devices for a specified time limit. During the time window data can be transferred from the sensor to the glucose meter and/or commands from the glucose meter can be sent to the sensor. After expiration of a time limit, communication between  
15 the two devices is deactivated. In order to establish a further communication, the communication link between the two devices has to be activated by generating a further blood glucose value in the glucose meter.

The term "generation of a value" as it is used herein encompasses any method or  
20 procedure for the determination of physiological parameters such as methods for the measurement of analyte values, in particular blood glucose values. Suitable methods for the determination of blood glucose values are e.g. electrochemical methods and photometric methods which are known to a person skilled in the art.

25 The dependence of the communication link between medical devices on an actual analyte value ensures the quality of the data transmitted from the medical sensory device and/or medical therapeutical device to the medical diagnostic device.

The data transferred from the sensor to the diagnostic device can be stored on the  
30 diagnostic device e.g. a glucose meter and be transferred to a third device such as a PDA or a computer, for further processing and/or analysis. By means of suitable software the data can be analyzed and used for e.g. bolus recommendation or adjustment of basal insulin rates for patients using an extra- or intra corporal insulin pump.

The communication link between the diagnostic device and a third device e.g. a computer, does not need activation by generation of a blood glucose value in said diagnostic device.

In a preferred embodiment, the present invention relates to a method of communication  
5 between a diagnostic medical device, preferably a blood glucose meter, and an infusion  
pump, preferably an extra corporal insulin pump. In this specific embodiment, the  
diagnostic medical device is used as a remote control to control the function of the  
infusion pump. After a blood glucose value has been generated in the blood glucose  
meter a communication link between meter and pump is enabled and/or activated for a  
10 defined time and commands can be transferred from the remote control i.e. the glucose  
meter, to the pump. It is as well possible to transfer data stored on the pump to the  
diagnostic device during the communication time window.

When the remote control of the infusion pump does not comprise a module for measuring  
15 blood glucose concentration, the communication between pump and remote control is  
activated by entering a current blood glucose value measured in a blood glucose meter in  
the remote control. The value can e.g. be entered using buttons of the remote control or  
can be transferred via a wireless or wired connection to the glucose meter. After the  
blood glucose value has been entered in the remote control, a communication link  
20 between remote control and infusion pump is established, preferably for a predetermined  
time span. After expiration of the time span, the communication is interrupted and no  
data exchange between the two devices is anymore possible. A further round of  
communication needs a new activation of the communication by entering a new, current  
blood glucose value in the remote control. The term remote control as used herein  
25 encompasses PDA, smart phones, a handy and pump specific remote controls.

The data transfer between the medical devices can be performed using known  
technologies and comprise wired connections as well as wireless communications. These  
technologies are known to a person skilled in the art. The preferred communication is a  
wireless communication, more preferably RF communication.

30

The data transfer between the devices can be encrypted in order to ensure that non-  
authorized third parties do not gain access to personal data of patients. Methods of  
encrypting data are known to a person skilled in the art.

In a further preferred embodiment, the communication between the medical devices is activated by a manipulation on the second medical device e.g. an insulin pump, such as pressing a button or lever, inserting a battery, using the touch screen, shaking, bumping or squeezing or the like.

5

In the following paragraph a preferred embodiment of the present invention is described.

The preferred system of medical devices comprises a continuous glucose sensor device which is placed on a human body in order to measure glucose value in interstitial fluid and a glucose meter. The sensor device comprises an electrochemical glucose sensor measuring the glucose concentration in the interstitial tissue in a predetermined manner. The sensor device further comprises an extra corporal part including processor means for controlling the sensor, memory for storing measured glucose values and a telemetry system for transmitting the data to a glucose meter, preferably a strip-based glucose meter. The glucose values stored on the sensor device are then transferred to a glucose meter via the telemetry system.

The communication between the two devices i.e. the wireless link, is established and/or activated by measuring the glucose concentration in a blood sample of a patient using the glucose meter, preferably a strip-based glucose meter. When a strip-based glucose meter is used, the patient inserts a strip in the glucose meter and puts a droplet of blood on the strip. The glucose meter measures and indicates on its display the blood glucose value. After measurement of the blood glucose value, the communication link can then be activated/established either by pressing a button on the glucose meter e.g. an activation button or by a direct electronic link to the processor controlling the glucose telemetry system such that the completion of the blood glucose measurement automatically activates the wireless link between the devices.

The communication link is then established and a data transfer between the medical devices is possible for a defined time span. After expiration of the defined time span the communication link is deactivated and no further data/commands can be transmitted between the medical devices. A new blood glucose measurement in the glucose meter is then necessary to open a new wireless link between the medical devices.

In a further aspect, the present invention relates to a method of data processing or data use. Said method is characterised in that data processing or data use is only possible after activation by a value of a physiological parameter. The method is preferably used for the processing of medical data such as data measured by a sensor applied on a human body.

5

In a preferred embodiment, the method is used for the processing of medical data which have been measured by a sensor device applied on a human being, preferably a continuous glucose sensor. The data are then e.g. transferred to a diagnostic medical device, preferably a blood glucose meter. The data are preferably transferred via a  
10 wireless link from the sensor device to the diagnostic device. In this case, each of the at least two medical devices comprises a telemetry system for wireless communication. The wireless communication can be bidirectional or unidirectional.

There is preferably a permanent communication link between said two medical devices  
15 but the data stored e.g. in the memory of the medical sensor device and transferred to the diagnostic device can only be further processed on the diagnostic device after the processing has been activated by a value of a physiological parameter. After activation by a value of a physiological parameter, preferably a blood glucose value, the data stored in the memory of the diagnostic device can be processed or used. For example, data are  
20 transferred from a continuous glucose sensor to a glucose meter and stored in the memory of the glucose meter. The further processing of these data is then only possible after activation of the processing by a value of a physiological parameter, preferably a blood glucose value.

25 In a preferred embodiment, the processing of the data is only possible for a limited time span after activation by a value of a physiological parameter. When the defined time span for data processing has lapsed, no further data processing is possible without a new activation by a value of a physiological parameter.

30 In a further aspect, the present invention relates to a medical device comprising a module for data processing which is adapted to be activated by a value of a physiological parameter. Preferably said module comprises a microprocessor with a memory for storing data.

Said medical device is preferably a blood glucose meter. Preferably, the processing of data stored in the memory of the blood glucose meter is either activated by pressing a button on the glucose meter (an activation button) or by a direct electronic link to the processor controlling the data processing module/system such that the completion of the  
5 blood glucose measurement automatically activates data processing

The terms "data processing" or "data use" as they are used herein refer to any manipulation of data and comprise analysis of data, presentation of data, interpretation of data and indication of data.

Claims

1. A medical device comprising a module for communication with at least a second medical device wherein the module for communication in said first medical device is adapted to be activated by a value of a physiological parameter of an animal.  
5
2. The medical device of claim 1, wherein the module for communication is a telemetry system for wireless communication, preferably a telemetry system for RF communication.  
10
3. The medical device of claim 1 or 2, wherein the medical device is selected from the group consisting of a remote control, a PDA, an analyte measuring device, preferably a glucose measuring device, more preferably a strip based glucose measuring device.  
15
4. The medical device of claims 1 to 3, wherein the physiological parameter is an analyte concentration of an animal.
- 20 5. The medical device of claim 4, wherein the analyte concentration is a blood glucose concentration.
6. The medical device of claim 5, wherein the first medical device comprises an electrochemical module for measuring blood glucose.  
25
7. The medical device of claim 5, wherein the first medical device comprises a photometric module for measuring blood glucose.
8. A system of medical devices comprising:  
30 a) a first medical device according to claims 1 to 7 and  
b) at least a second medical device capable to communicate with said first medical device.

9. The system of claim 8, wherein the second medical device is selected from the group consisting of an extra corporal infusion pump, an implantable infusion pump, a pacesetter, an analyte sensor, preferably a continuous analyte sensor, more preferably a continuous glucose sensor.
- 5
10. The system of claim 8 or 9, wherein the first medical device and the at least second medical device comprise a telemetry system for wireless communication, preferably a telemetry system for RF communication.
- 10 11. A method of communication between a first medical device and at least a second medical device wherein the communication between said medical devices is enabled and/or activated by a value of a physiological parameter of an animal.
12. The method of claim 11, wherein the communication is enabled and/or activated  
15 for a predetermined time window.
13. The method of claim 12, wherein the time window is established according to a value of a physiological characteristic of an animal or according to a set of data gained during previous time periods.
- 20
14. The method of claims 11 to 13, wherein the physiological parameter is selected from the group consisting of an analyte concentration of an animal, a heart rate, an electrophysiological value, preferably a blood glucose concentration.
- 25 15. The method of claim 11 to 14, wherein the activation of the communication is performed on the first medical device by generating a value of the physiological parameter in said first medical device.
16. The method of claims 11-15, wherein the first medical device is selected from the  
30 group consisting of a remote control, a PDA, an analyte measuring device, preferably a glucose measuring device, more preferably a strip-based glucose measuring device.

17. The method of claims 11-16, wherein the second medical device is selected from the group consisting of an extra corporal infusion pump, an implantable infusion pump, a pacesetter, an analyte sensor, preferably a continuous analyte sensor, more preferably a continuous glucose sensor.
- 5
18. The method of claims 11-17, wherein the communication between said medical devices is a wireless communication, preferably a RF communication.
19. The method of claims 11-18, wherein the first medical device receives data from  
10 the second medical device.
20. The method of claims 11-19, wherein the first medical device sends commands to the second medical device to control at least partially said second device.

## INTERNATIONAL SEARCH REPORT

International application No  
PCT/EP2006/000663A. CLASSIFICATION OF SUBJECT MATTER  
INV. A61B5/00 A61M5/142

According to International Patent Classification (IPC) or to both national classification and IPC

## B. FIELDS SEARCHED

Minimum documentation searched (classification system followed by classification symbols)  
A61B A61M

Documentation searched other than minimum documentation to the extent that such documents are included in the fields searched

Electronic data base consulted during the international search (name of data base and, where practical, search terms used)

EPO-Internal

## C. DOCUMENTS CONSIDERED TO BE RELEVANT

Category*	Citation of document, with indication, where appropriate, of the relevant passages	Relevant to claim No.
X	US 2004/167464 A1 (IRELAND JEFFREY R ET AL) 26 August 2004 (2004-08-26) abstract; figures 1-5 paragraphs [0007], [0034], [0037], [0057] - [0061]	1-20
X	US 2004/225338 A1 (LEBEL RONALD J ET AL) 11 November 2004 (2004-11-11) abstract; figures 1-3 paragraphs [0107], [0108], [0121], [0222] - [0227]	1-20
X	US 2002/049389 A1 (ABREU MARCIO MARC) 25 April 2002 (2002-04-25) abstract; figures 70,71 paragraphs [0182] - [0185], [1018] - [1023]	1-20
	----- -/--	

 Further documents are listed in the continuation of Box C. See patent family annex.

\* Special categories of cited documents:

\*A\* document defining the general state of the art which is not considered to be of particular relevance

\*E\* earlier document but published on or after the international filing date

\*L\* document which may throw doubts on priority claim(s) or which is cited to establish the publication date of another citation or other special reason (as specified)

\*O\* document referring to an oral disclosure, use, exhibition or other means

\*P\* document published prior to the international filing date but later than the priority date claimed

\*T\* later document published after the international filing date or priority date and not in conflict with the application but cited to understand the principle or theory underlying the invention

\*X\* document of particular relevance; the claimed invention cannot be considered novel or cannot be considered to involve an inventive step when the document is taken alone

\*Y\* document of particular relevance; the claimed invention cannot be considered to involve an inventive step when the document is combined with one or more other such documents, such combination being obvious to a person skilled in the art.

\*G\* document member of the same patent family

Date of the actual completion of the international search

28 April 2006

Date of mailing of the international search report

08/05/2006

Name and mailing address of the ISA/

European Patent Office, P.B. 5818 Patentlaan 2  
NL - 2280 HV Rijswijk  
Tel. (+31-70) 340-2040, Tx. 31 651 epo nl,  
Fax: (+31-70) 340-3016

Authorized officer

Jonsson, P.O.

# INTERNATIONAL SEARCH REPORT

International application No  
PCT/EP2006/000663

C(Continuation). DOCUMENTS CONSIDERED TO BE RELEVANT		
Category*	Citation of document, with indication, where appropriate, of the relevant passages	Relevant to claim No.
X	EP 0 098 592 A (FUJISAWA PHARMACEUTICAL CO., LTD) 18 January 1984 (1984-01-18) abstract; figures 1-3 -----	1, 8, 11

# INTERNATIONAL SEARCH REPORT

Information on patent family members

International application No PCT/EP2006/000663
---

Patent document cited in search report	Publication date	Patent family member(s)	Publication date
US 2004167464 A1	26-08-2004	AU 2003256694 A1 WO 2004009161 A1	09-02-2004 29-01-2004
US 2004225338 A1	11-11-2004	US 2002173702 A1	21-11-2002
US 2002049389 A1	25-04-2002	WO 02067688 A1 WO 0025662 A1 US 2003069489 A1 US 6123668 A US 2003139687 A1 US 2004039297 A1 US 2004039298 A1 US 6213943 B1 US 5830139 A US 2002049374 A1	06-09-2002 11-05-2000 10-04-2003 26-09-2000 24-07-2003 26-02-2004 26-02-2004 10-04-2001 03-11-1998 25-04-2002
EP 0098592 A	18-01-1984	NONE	

专利名称(译)	手术针和与其一起使用的缝合线		
公开(公告)号	<a href="#">EP1890588A1</a>	公开(公告)日	2008-02-27
申请号	EP2006703880	申请日	2006-01-26
[标]申请(专利权)人(译)	迪斯特朗尼克许可公司		
申请(专利权)人(译)	DISETRONIC许可AG		
当前申请(专利权)人(译)	DISETRONIC许可AG		
[标]发明人	ESSENPREIS MATTHIAS HAUETER ULRICH BERNINI NICOLE FANKHAUSER SYBILLE LA BASTIDE SEBASTIAAN MEYER OLDEN GUNNAR SCHOEMAKER MICHAEL HEATON KELLY JECKELMANN JOEL		
发明人	ESSENPREIS, MATTHIAS HAUETER, ULRICH BERNINI, NICOLE FANKHAUSER, SYBILLE LA BASTIDE, SEBASTIAAN MEYER OLDEN, GUNNAR SCHOEMAKER, MICHAEL HEATON, KELLY JECKELMANN, JOEL		
IPC分类号	A61B5/00 A61M5/142		
CPC分类号	A61B5/0002 A61B5/14532 A61M5/14244 A61M5/14276 A61M2205/3523 A61M2205/3569 A61M2205/3592 A61M2230/201		
优先权	2005002074 2005-02-02 EP		
其他公开文献	EP1890588B1		
外部链接	<a href="#">Espacenet</a>		

#### 摘要(译)

本发明涉及一种移动医疗设备和医疗设备之间的通信方法。本发明的医疗设备包括用于与至少第二医疗设备通信的模块，其中所述用于通信的模块适于由动物的生理参数的值激活。本发明的方法包括第一医疗设备和至少第二医疗设备，其中所述医疗设备之间的通信由动物的生理参数的值激活。

