



(11) **EP 3 035 848 B1**

(12) **EUROPEAN PATENT SPECIFICATION**

(45) Date of publication and mention
of the grant of the patent:
11.03.2020 Bulletin 2020/11

(51) Int Cl.:
A61B 5/145 ^(2006.01) **A61B 5/00** ^(2006.01)
A61B 5/024 ^(2006.01) **A61M 5/172** ^(2006.01)

(21) Application number: **13866494.1**

(86) International application number:
PCT/IB2013/003256

(22) Date of filing: **23.08.2013**

(87) International publication number:
WO 2015/025187 (26.02.2015 Gazette 2015/08)

(54) **METHOD AND DEVICE FOR IMPROVING PREDICTION OF CHANGE IN A PHYSIOLOGICAL CONDITION**

VERFAHREN UND VORRICHTUNG ZUR VERBESSERUNG DER VORHERSAGE VON
VERÄNDERUNGEN EINES PHYSIOLOGISCHEN ZUSTANDS

PROCÉDÉ ET DISPOSITIF D'AMÉLIORATION DE LA PRÉVISION D'UN CHANGEMENT D'UN ÉTAT
PHYSIOLOGIQUE

(84) Designated Contracting States:
**AL AT BE BG CH CY CZ DE DK EE ES FI FR GB
GR HR HU IE IS IT LI LT LU LV MC MK MT NL NO
PL PT RO RS SE SI SK SM TR**

(56) References cited:
**WO-A1-2005/037092 WO-A1-2008/135985
WO-A1-2010/134068 WO-A2-2009/138976
US-A1- 2006 281 980**

(43) Date of publication of application:
29.06.2016 Bulletin 2016/26

(73) Proprietor: **Medicus Engineering ApS
8200 Aarhus (DK)**

(72) Inventors:
• **FLEISCHER, Jesper
DK-8270 Højbjerg (DK)**
• **CICHOSZ, Simon Lebech
DK-8200 Aarhus N (DK)**

(74) Representative: **Zwicker, Jörk
ZSP Patentanwälte PartG mbB
Hansastraße 32
80686 München (DE)**

- **Fj Gimeno-Blanes ET AL: "On the feasibility of tilt test outcome early prediction using ECG and pressure parameters", EURASIP Journal on Advances in Signal Processing, vol. 33 1 January 2011 (2011-01-01), pages 1-7, XP055132750, Retrieved from the Internet:
URL:<http://asp.eurasipjournals.com/content/pdf/1687-6180-2011-33.pdf> [retrieved on 2014-07-31]**
- **Mostefa Mesbah ET AL: "Automatic seizure detection based on the combination of newborn multi-channel EEG and HRV information", EURASIP Journal on Advances in Signal Processing, vol. 215 1 January 2012 (2012-01-01), pages 1-14, XP055132749, Retrieved from the Internet:
URL:<http://asp.eurasipjournals.com/content/pdf/1687-6180-2012-215.pdf> [retrieved on 2014-07-31]**

Note: Within nine months of the publication of the mention of the grant of the European patent in the European Patent Bulletin, any person may give notice to the European Patent Office of opposition to that patent, in accordance with the Implementing Regulations. Notice of opposition shall not be deemed to have been filed until the opposition fee has been paid. (Art. 99(1) European Patent Convention).

Description

[0001] The present invention relates generally to monitoring and prediction of changes in heart rate variability and glucose level.

BACKGROUND ART

[0002] Autonomic nervous system (ANS) is a multifunctional system regulated by the sympathetic nervous system and the parasympathetic system, providing a rapidly responding mechanism to control a wide range of bodily functions such as, for example, cardiovascular, respiratory, gastrointestinal, genitor-urinary, exocrine and endocrine secretions, and microcirculation. Furthermore, ANS is involved in the regulation of immune and inflammatory processes. Autonomic dysfunction may affect both the sympathetic nervous system and the parasympathetic nervous system and may affect any organ that is innervated by the autonomic nervous system.

[0003] Heart rate (HR) and heart rate variability (HRV) are affected by both internal and external changes in, for example, breathing, blood pressure, hormone status, mental condition and physical conditions. A number of pathophysiological conditions may shift the balance in the ANS thereby decreasing or increasing stimulation to heart's sinoatrial node which controls HR and HRV. For example, increase in blood pressure causes arteries to stretch, thereby causing increase in baroreceptor discharge frequency which, in turn, causes increase in parasympathetic and decrease in sympathetic activity. Similarly, carotid chemoreceptor stimulation by noradrenalin leads to slowing HR and increase in rate and depth of respiration.

[0004] International application publication number WO 2005/037092 A1 discloses to detect physical conditions by combined measurement of HRV and blood glucose.

[0005] In the invention, the scope of which is solely defined by the appended claims, a method for predicting and/or detecting a change in a physiological condition of a subject is disclosed. The method may include analyzing changes in a heart rhythm of a subject; analyzing a signal related to a glucose level of the interstitial fluid that is associated with a physiological condition of the subject; and determining, based on the changes in the heart rhythm and the signal related to the glucose level of the interstitial fluid, whether there is a change in the physiological condition of the subject during a time period.

[0006] In the invention, a device for predicting and/or detecting a change in a physiological condition of a subject is disclosed. The, the system may include a device comprising one or more processors configured to (a) analyze changes in a heart rhythm of a subject; (b) analyze a signal related to a glucose level of the interstitial fluid that is associated with a physiological condition of the subject; and (c) determine, based on the changes in the heart rhythm and the signal related to the glucose level of the interstitial fluid, whether there is a change in the physiological condition of the subject during a time period; one or more sensors configured to measure the heart rhythm of the subject; and one or more sensors configured to measure the signal.

BRIEF DESCRIPTION OF DRAWINGS

[0007] In the present disclosure, reference is made to the accompanying drawings, which form a part hereof. In the drawings, similar symbols typically identify similar components, unless context dictates otherwise. Various embodiments described in the detailed description, drawings, and claims are illustrative and not meant to be limiting. It will be understood that the aspects of the present disclosure, as generally described herein, and illustrated in the Figures, can be arranged, substituted, combined, separated, and designed in a wide variety of different configurations, all of which are contemplated herein.

Figure 1 depicts an illustrative process for a method of monitoring and predicting a change in a physiological condition using Heart Rate Variability (HRV) in combination with one or more biomarkers.

Figure 2 depicts an illustrative pattern recognition model.

Figure 3 depicts a block diagram of a device used for analysis of HRV data in accordance with various aspects and principles of the present disclosure.

Figure 4 shows an example of detection of hypoglycemia based on HRV data and data from a Continuous Glucose Monitor (CGM) for a subject.

DETAILED DESCRIPTION

[0008] Before the present methods and systems are described, it is to be understood that this disclosure is not limited to the particular processes, methods and devices described herein, as these may vary. It is also to be understood that the terminology used herein is for the purpose of describing the particular versions or embodiments only, and is not intended to limit the scope of the present invention which will be limited only by the appended claims. Unless otherwise defined, all technical and scientific terms used herein have the same meanings as commonly understood by one of ordinary skill in the art.

[0009] It must also be noted that as used herein and in the appended claims, the singular forms "a", "an", and "the" include plural reference unless the context clearly dictates otherwise. Thus, for example, reference to a "biomarker" is a reference to one or more biomarkers and equivalents thereof known to those skilled in the art, and so forth. Nothing in this disclosure is to be construed as an admission that the embodiments described in this disclosure are not entitled to antedate such disclosure by virtue of prior invention. As used in this document, the term "comprising" means "including, but not limited to."

[0010] As used herein, the term "biomarker", interchangeably used with the term "biological marker", refers to an objectively measurable indicator of a biological state. Biomarkers may be used as indicators of, for example, biological processes, pathogenic processes, pharmacologic responses to a therapeutic intervention. Examples of biomarkers include, but are not limited to, heart rate, heart rate variability, electrical activity in an organ such as brain, heart or a muscle, electrooculogram, sudomotor function, breathing rate, partial oxygen pressure, blood pressure, blood glucose levels, blood alcohol levels, presence or absence of proteins in blood and/or cells, bioimpedance, galvanic skin response, nerve conduction, pulse wave measurement, pulse wave velocity, magnetic resonance imaging (MRI), motion detection and/or analysis, rates of absorption, distribution, metabolism and/or elimination of a chemical, radioactive or biochemical substance in the body, and so forth. In the present invention a surrogate for a biomarker is used as a measurable indicator of a biological state. Particularly, Continuous Glucose Monitor (CGM) is a surrogate measure for blood glucose measurement. CGM devices measure the glucose level of interstitial fluid and is calibrated with a traditional blood glucose measurement. Typically, glucose levels in interstitial fluid lag behind blood glucose values.

[0011] In various embodiments, biomarker measurements may be obtained periodically. For example, blood glucose values may be obtained every 5 minutes, or every 10 minutes, and so forth. Periodicity of measurement of biomarker data may vary for different biomarkers and may depend on factors such as, for example, typical frequency of biomarker measurement may be once every 1 second, once every 30 seconds, once every 1 minute, once every 5 minutes, once every 10 minutes, once every 30 minutes, once every 1 hour, or any frequency between any two of these frequencies.

[0012] A processor refers to a machine for data processing. For example, the processor could be a microprocessor chip.

[0013] A physiological condition refers to the condition or state of the body or bodily functions. For example, a physiological condition could be a condition characteristic of or appropriate to an organism's healthy or normal functioning.

[0014] Biomarkers may be used to make a clinical determination of a physiological condition, which includes a pathophysiological condition and may be used alone or in conjunction with other biomarkers or indicators (e.g., a patient's medical history) and symptoms. A change in a measurement of a biomarker or a surrogate of a biomarker may have physiological significance, i.e., a characteristic of or appropriate to an organism's healthy or normal functioning. For example, a drop in blood glucose level may indicate onset of hypoglycemia which may, in certain cases, require clinical intervention.

[0015] As used herein, "heart rate variability" (HRV) refers to variation in the time interval between heartbeats. HRV has been found to be a measure of the balance in the autonomic nervous system and is dependent on both internal and external changes in the body. Decreased parasympathetic nervous system activity or increased sympathetic nervous system activity results in reduced HRV. HRV may be measured using, for example, electrocardiogram, blood pressure, ballistocardiograms, pulse wave signals derived from photoplethysmograph, and so forth. In various examples, HRV may be measured at different sampling rates such as, for example, 0.01 Hz, 0.05 Hz, 0.1 Hz, 0.5 Hz, 1 Hz, 5 Hz, 10 Hz, 50 Hz, 100 Hz, 500 Hz, 1 kHz, and so forth or at any sampling rate between any two of these sampling rates.

[0016] By combining the complex dynamic/pattern of HRV with a surrogate measure of a biomarker it may be possible to improve the detection and prediction of a given change in a physiological condition which is measured by the biomarker surrogate. The HRV dynamic/pattern adds important information regarding the modulation of the autonomic nervous system and thereby can be used to clarify whether a change or event measured by the biomarker is of physiological significance, which could include a change or event of clinical interest that might require clinical intervention. This clarification is more significant when using a surrogate measure of a biomarker. As in the present invention, when the biomarker surrogate is CGM, there is a lag-time between CGM measurements and actual blood glucose levels (glucose levels in interstitial fluid lag behind blood glucose values) causing poor accuracy in event detection. Therefore, in terms of detection of hypoglycemia, CGM devices, have poor specificity and thus result in numerous false positive alerts. By combining pattern recognition of HRV with a CGM device the detection and prediction of hypoglycemia may be significantly improved. Besides detection and prediction of hypoglycemia the methods disclosed herein may be used in any biomarker

surrogates that are influenced by the autonomic nervous system.

[0017] Disclosed herein are methods for monitoring and predicting changes in physiological conditions using changes in heart rate and heart variability in conjunction with one or more suitable biomarkers. Embodiments disclosed herein also describe devices and systems for implementing those methods and methods of use of such devices and systems.

[0018] Figure 1 depicts an illustrative process for a method of predicting a change in a physiological condition using Heart Rate Variability (HRV) in combination with the glucose level of the interstitial fluid according to the present invention. At block 110, HRV of a subject is measured by a sensor. The HRV data fed to a processor P which, at block 150, analyzes the HRV data based on a pre-determined algorithm. At block 130, processed HRV data is combined (using, e.g., another processor not shown in Figure 1) with measurements relating to a glucose level of interstitial fluid from sensors gathered at block 120 and analyzed for change in a physiological condition. This analysis may be fed back to processor P for analysis at block 150. If the change in the physiological condition is deemed, based on a pre-determined set of criteria, a reaction R is provided at block 175.

[0019] In various examples, the patterns in the HRV data may be used to evaluate the clinical relevance of each data point obtained from the biomarker measurements. For example, glucose measurement is used for detection of hypoglycemia. In such example, glucose levels are measured periodically (e.g., every 5 minutes) and patterns in HRV data are used to determine whether a particular glucose measurement indicates an onset of hypoglycemia. In other examples, other biomarkers may be used and measurements obtained at a different frequency. In some embodiments, the biomarker data may undergo processing similar to the HRV data.

[0020] In various examples, physiological conditions may be induced under controlled clinical conditions while gathering HRV data. In many examples, HRV data may be gathered for up to 10 hours prior to induction of the physiological event and up to 10 hours after the induction of the physiological event. As such, incidence of various features and patterns extracted from the HRV data may be correlated with the particular physiological event being induced based on the analysis being performed.

[0021] HRV of a subject may be measured using any device or method. For example, HRV of a subject is measured using electrocardiogram (ECG). Figure 2 depicts an illustrative pattern recognition model according to an embodiment. In various examples, analysis of HRV at block 150 may include, for example, preprocessing at block 210, feature extraction at block 220, feature reduction at block 230, and classification at block 240.

[0022] In examples where HRV is measured using ECG, a signal from the ECG is preprocessed, at block 210, for detection of peaks and calculation of RR-intervals. RR-interval, as used herein, is the interval between an R wave and the next R wave as measured by the ECG. In various examples, RR-intervals may be divided in epochs of several minutes. It will be understood by one skilled in the art that any time length of an epoch may be chosen and will depend on factors such as, for example, data sampling rate, processing power, memory available to the processor, efficiency of algorithms used for analysis, and so forth. In an embodiment, for example, duration of an epoch may be 5 minutes.

[0023] RR-interval outliers from each epoch may then be replaced with a mean from that particular epoch. Outliers, in some examples, may be defined as RR-intervals deviating 50% from previous data RR-interval or outside 3 standard deviations. Epochs may be analyzed using proprietary or commercially available tools. The analysis may be performed using one or more of analysis tools such as, for example, of Poincare Plots, Nonlinear analysis, time-frequency analysis and performed in time domain or frequency domain. Power spectra density may then be estimated using parametric or non-parametric models such as, for example, Welch's method, auto regression, periodogram, Bartlett's method, autoregressive moving average, maximum entropy, least-squares spectral analysis, and so forth.

[0024] Preprocessing of the ECG signal may be followed by feature extraction, at block 220. Preprocessed RR-interval data is sent to block 220 to find, preferably, a small number of features that are particularly distinguishing and/or informative for classification of the features based on physiological conditions being induced. In various examples, features extracted, at block 220, from the RR-interval data up to several epochs prior to the physiological event may be used for calculating various features. In some examples, analysis may be performed on data, for example, 10 epochs, 15 epochs, 20 epochs, 30 epochs, 40 epochs, 50 epochs, 100 epochs or any number of epochs therebetween, prior to the physiological event.

[0025] Analysis performed on the RR-interval data at block 220 may, in various examples, include, for example, differentiation, averaging, calculation of slope, ratios of instantaneous values, standard deviation, skewness, regression coefficients, slopes of regression ratios, and standardized moment, and so forth. Features extracted from the HRV data may include, for example, median heart rate average from particular epoch range prior to an event, or the skewness of standard deviation of normal-to-normal intervals from particular epoch range prior to an event, and so forth.

[0026] RR-interval data extracted at block 220 may include a large number of different features may be evaluated for their ability to discriminate for a physiological event. Such features may then, be passed down to block 230 to be grouped to form patterns that may be indicative of a particular physiological event. At block 230, a ranking algorithm based on e.g. a t-test may be used, in some embodiments, for eliminating features that do not signify an event.

[0027] In some examples, the ranking algorithm may calculate an average separability criterion for each feature. Such

a criterion may reflect the ability of the classification method to separate the means of any two classes of features in relation to the variance of each class. Subsequently, various features may be correlated with physiological events. Features with lowest separability may be eliminated if correlation with higher ranking features exceeds a threshold. In an example, a correlation threshold of, for example, 0.7 may be used. In various examples, the correlation threshold may be chosen depending on the desired specificity and sensitivity of prediction of the physiological event. In many examples, cross-validation may be performed to reduce generalization errors.

[0028] Once the features are extracted and reduced, particular features may be chosen for their ability to predict a physiological event based on correlation factors. This is followed by classification, at block 240, of the features to correlate them with particular physiological events. Various classification models may then be used for classifying physiological events as normal or abnormal based on such features. For example, in an example, non-probabilistic binary linear classifier support vector machine may be used. A skilled artisan will appreciate that other classification methods may be also used, alone or in combination. For example, linear classifier models such as Fisher's linear discriminant, logistic regression, naive Bayes classifier, Perceptron, may be used for classification. Other examples of classification models include, but are not limited to, quadratic classifiers, k-nearest neighbor kernel estimation, random forests decision trees, neural networks, Bayesian networks, Hidden Markov models, Gaussian mixture models, and so forth. In some embodiments, multi-class classification may also be used, if needed.

[0029] In an example, at block 240, forward selection may be used to select a subset of features for optimal classification. This selection may be performed by including a cross-validation with, for example, 10 groups and allocating a particular number of events for training the model. Forward selection may start with no features followed by assessing each feature to find the best feature that correlates with the particular physiological event. Such feature may, then, be included in an optimal feature subset for appropriate classification. Selection of new features may be repeated until addition of new features does not result in improved predictive performance of the model.

[0030] Figure 3 depicts a block diagram of a device used for analysis of HRV data in accordance with various aspects and principles of the present disclosure. Device 300 used for analysis of HRV data may include processor 310 configured to run algorithm 320 that enables prediction or detection of a physiological event. Heart rhythm 350 along with at least one biomarker 375 and their time of measurement are received and analyzed by algorithm 320. In some examples, measurements of heart rhythm 350 and biomarker 375 may be entered manually. In other examples, the measurements may be transmitted automatically to processor 310 using a wired or a wireless connection to device 300. Algorithm 320 may include, calculating one or more statistical measures, at block 322, of heart rhythm 350 and biomarker 375 data. At block 324, the physiological state or change in the physiological state is estimated and analyzed for a possibility that the physiological state or change in the physiological state may be non-healthy. At block 326, an output is generated based on the analysis of block 324. For example, if it is determined, at block 324, that a change in physiological state is non-healthy, an alarm signal is generated at block 326. Device 300 may produce a reaction 340 based on the output generated at block 326. In various embodiments, reaction 340 may be a visual, audio, or audiovisual signal such as, for example, an alarm, a text message, a flashing light, and so forth.

[0031] In many examples, processor 310 may be part of a computer, a tablet, a smartphone, or a standalone device. In some examples, the device may have in-built sensors for measuring HRV data 350. For example, a smartphone having a light emitting diode (LED) capable of producing infra-red light and an optical sensor (e.g., a camera) may be able to obtain HRV data using IR thermography. In many examples, the device used for analyzing the HRV data may include, for example, a controlling unit (e.g., a digital signal processor or DSP), a memory (e.g., random access memory, and/or non-volatile memory), one or more sensors (e.g., IR sensors, electrodes, etc.), one or more feedback mechanisms (e.g., display, a printer, speakers, LEDs or other light sources, etc.), and/or one or more input ports. The device for analyzing HRV data may also include sensors for measuring and analyzing any other biomarker(s).

[0032] In a non-claimed example, HRV measurements 350 may be combined, at block 322, with measurements of blood glucose levels 375 for monitoring and prediction of hypoglycemia. In such embodiments, HRV data 350 may be combined with, e.g., blood glucose measurements 375 taken over a period of time prior to a hypoglycemic event. Patterns from the combination of HRV and blood glucose data may be used to discriminate between normoglycemia and hypoglycemia. A model may be trained by analyzing HRV features over, e.g., 10-20 epochs combined with blood glucose measurements prior to an induced hypoglycemic event. Once trained to discriminate between normoglycemic events and hypoglycemic events, the model may then be used to predict, at block 324, the occurrence of a hypoglycemic event based on HRV and blood glucose measurements.

[0033] Blood glucose data 375 may be obtained intermittently or continuously. In some non-claimed examples, it may be possible to obtain blood glucose data using non-invasive technologies that include, for example, infra-red detection, ultrasound or dielectric spectroscopy and so forth. In many non-claimed examples, such technologies may be integrated with equipment used for obtaining HRV data. In other embodiments, an implanted chip may be used for obtaining continuous blood glucose data.

[0034] Table 1 provides a list of biomarkers that may be used in concert with HRV for predicting and monitoring various physiological conditions.

Table 1: List of biomarkers or biomarker surrogates used for detection/prediction for physiological events/conditions (EEG - electroencephalogram; EMG - Electromyography; ECG - Electrocardiography).

Physiological condition	Biomarker or surrogate measure of a biomarker
Epileptic attack	EEG, EMG, motion detection
Asthma attack	EEG, breathing (sounds and rate)
Panic attack	EEG, ECG, breathing (sounds and rate), sudomotor function
Heart attack or event	ECG, pulse wave velocity
Sudden hypotension	Blood pressure
Sleep apnea	EEG, breathing (sounds and rate)
Fatigue	ECG, EMG, motion detection
Stress, including post-traumatic stress	EEG, bioimpedance, breathing (sounds and rate)
Neuropathy	Bioimpedance, nerve conduction, EEG, EMG, dolorimeter, vibration testing, motion detection
Dehydration	Blood pressure, bioimpedance, breathing
Liveness detection	Bioimpedance
Lie detection	Polygraph

[0035] Another example is implemented as a program product for implementing systems and methods described herein. Some embodiments can take the form of an entirely hardware embodiment, an entirely software embodiment, or an embodiment containing both hardware and software elements. One embodiment is implemented in software, which includes but is not limited to firmware, resident software, microcode, etc.

[0036] Furthermore, the present invention takes the form of a computer program product (or machine-accessible product) accessible from a computer-usable or computer-readable medium providing program code for use by or in connection with a computer or any instruction execution system. For the purposes of this description, a computer-usable or computer readable medium can be any apparatus that can contain, store, communicate, propagate, or transport the program for use by or in connection with the instruction execution system, apparatus, or device.

[0037] The medium can be an electronic, magnetic, optical, electromagnetic, infrared, or semiconductor system (or apparatus or device). Examples of a computer-readable medium include a semiconductor or solid-state memory, magnetic tape, a removable computer diskette, a random access memory (RAM), a read-only memory (ROM), a rigid magnetic disk, and an optical disk. Current examples of optical disks include compact disk - read only memory (CD-ROM), compact disk - read/write (CD-R/W), and DVD.

[0038] A data processing system suitable for storing and/or executing program code will include at least one processor coupled directly or indirectly to memory elements through a system bus. The memory elements can include local memory employed during actual execution of the program code, bulk storage, and cache memories which provide temporary storage of at least some program code in order to reduce the number of times code must be retrieved from bulk storage during execution.

[0039] The logic as described above may be part of the design for an integrated circuit chip. The chip design is created in a graphical computer programming language, and stored in a computer storage medium (such as a disk, tape, physical hard drive, or virtual hard drive such as in a storage access network). If the designer does not fabricate chips or the photolithographic masks used to fabricate chips, the designer transmits the resulting design by physical means (e.g., by providing a copy of the storage medium storing the design) or electronically (e.g., through the Internet) to such entities, directly or indirectly. The stored design is then converted into the appropriate format (e.g., GDSII) for the fabrication.

[0040] The resulting integrated circuit chips can be distributed by the fabricator in raw wafer form (that is, as a single wafer that has multiple unpackaged chips), as a bare die, or in a packaged form. In the latter case, the chip is mounted in a single chip package (such as a plastic carrier, with leads that are affixed to a motherboard or other higher level carrier) or in a multichip package (such as a ceramic carrier that has either or both surface interconnections or buried interconnections). In any case, the chip is then integrated with other chips, discrete circuit elements, and/or other signal processing devices as part of either (a) an intermediate product, such as a motherboard, or (b) an end product.

[0041] The foregoing detailed description has set forth various embodiments of the devices and/or processes by the

use of diagrams, flowcharts, and/or examples. Insofar as such diagrams, flowcharts, and/or examples contain one or more functions and/or operations, it will be understood by those within the art that each function and/or operation within such diagrams, flowcharts, or examples can be implemented, individually and/or collectively, by a wide range of hardware, software, firmware, or virtually any combination thereof.

[0042] Those skilled in the art will recognize that it is common within the art to describe devices and/or processes in the fashion set forth herein, and thereafter use engineering practices to integrate such described devices and/or processes into data processing systems. That is, at least a portion of the devices and/or processes described herein can be integrated into a data processing system via a reasonable amount of experimentation.

[0043] The herein described subject matter sometimes illustrates different components contained within, or connected with, different other components. It is to be understood that such depicted architectures are merely exemplary, and that in fact many other architectures can be implemented which achieve the same functionality. In a conceptual sense, any arrangement of components to achieve the same functionality is effectively "associated" such that the desired functionality is achieved. Hence, any two components herein combined to achieve a particular functionality can be seen as "associated with" each other such that the desired functionality is achieved, irrespective of architectures or intermediate components.

[0044] With respect to the use of substantially any plural and/or singular terms herein, those having skill in the art can translate from the plural to the singular and/or from the singular to the plural as is appropriate to the context and/or application. The various singular/plural permutations may be expressly set forth herein for sake of clarity.

[0045] While various aspects and embodiments have been disclosed herein, other aspects and embodiments will be apparent to those skilled in the art. The various aspects and embodiments disclosed herein are for purposes of illustration and are not intended to be limiting, with the true scope of protection that is entirely defined by the following claims.

EXAMPLES

[0046] Disclosures illustrating the devices, methods and systems described herein may be further understood by reference to the following non-limiting examples:

Patients with type-1 diabetes following a strict glycemic control are disposed to suffer severe hypoglycemia.

Detection of Hypoglycemia based on Heart Rate Variability and CGM data

[0047] The examples may utilize the devices, methods and processes described herein with respect Figures 1-3.

Data collection:

[0048] Data from 10 patients was obtained. 10 adults with type I diabetes were recruited for studies into hypoglycemia under clinical settings. None of the patients with diabetes had a history of cardiovascular disease. None of the patients were taking drugs affecting the cardiovascular system, and all had normal electrocardiograms.

[0049] On the study day, hypoglycemia was induced by a single subcutaneous bolus of insulin aspart. Subjects were placed in a hospital bed with the back rest elevated to a comfortable position. Equipment for measuring the ECG (lead II) and a CGM device (Guardian RT, Minimed, Inc., Northridge, CA) producing a reading every 5 minutes were mounted and an intravenous cannula was placed in an antecubital vein in both forearms. Blood samples for measurements of insulin were taken at the beginning and end of a baseline period. Throughout the experiment, blood glucose measurements were obtained frequently from earlobe capillary blood.

[0050] Blood glucose readings were spline resampled with a rate of 5 minutes equivalent to each reading of the CGM device. The blood glucose readings were used as reference for periods/events with hypoglycemia and categorize events as (i) hypoglycemia - defined as the point of time of a blood sample closest to the value of 3 mmol/l glucose, and normoglycemia - defined as the point of time of a blood sample approximately 1 hour prior to the hypoglycemic event.

[0051] Once the HRV and blood glucose data is collected, all data processing was performed using custom analysis software developed in MATLAB R2011b (Mathworks, Natick, MA).

Preprocessing:

[0052] The ECG V5 signal was used for detection of peaks and calculation of RR-intervals. RR-intervals were divided in epochs of 5 minutes during the trial. RR-interval outliers from each epoch were replaced with the mean from that particular epoch. Outliers were defined as RR-intervals deviating 50% from previous data RR-interval or outside 3 standard deviations.

[0053] Epochs were analyzed using HRV analysis software (HRVAS) module and 103 measures ranging from time domain, Poincare, Nonlinear, time-frequency to frequency domain were derived from the epoch. Two different models were used to estimate power spectra density: welch and auto regression.

Feature extraction and reduction:

[0054] In short, feature extraction and reduction is performed to find preferably small number of features that are particularly distinguishing or informative for the classification. Measures derived from RR-interval epochs 10-40 prior to an event were used for calculating multiple features. Table 2 shows calculations used to combine different epoch measures.

Table 2: List of equations used to combine HRV measures into features. M_y represent a HRV measure y , epc_{x1} represent an 5 minutes RR-interval epoch, μ is the arithmetic mean, α is the slope regression coefficients, σ is the standard deviation, γ_1 is the third standardized moment.

Description	Equation
Differentiation	$M_{yepC_{x1}} - M_{yepC_{x2}}$
Averaging	$\mu (M_{yepC_{x1}} \dots M_{yepC_{xn}})$
Slope	$\alpha (M_{yepC_{x1}} \dots M_{yepC_{xn}})$
Standard deviation	$\sigma (M_{yepC_{x1}} \dots M_{yepC_{xn}})$
Skewness	$\gamma_1(M_{yepC_{x1}} \dots M_{yepC_{xn}})$
Ratio	$M_{yepC_{x1}} / M_{yepC_{x2}}$

[0055] Example of features could be (a) the median heart rate averaged from epochs 10-20 prior to an event or (b) the skewness of standard deviation of Normal-to-Normal intervals (SDNN) from epochs 10-40 prior to an event.

[0056] To classify the patterns, 3296 different features were evaluated for their discrimination abilities. A ranking algorithm based upon a t-test was used to eliminate features. The ranking algorithm calculates an average separability criterion for each feature, which is the ability to separate the means of the two classes in relation to the variance of each class. The features are then correlated, and the feature with the lowest separability criteria is eliminated if correlation with higher ranking features exceeds the threshold. In this study a correlation threshold of 0.7 was used. To ensure that the features obtained would not be over fitted, i.e. to reach a low generalization error, a cross-validation method was used. A total of the best 20 features were used to inclusion in the classification model.

Classification model:

[0057] Non-probabilistic binary linear classifier Support vector machines (SVM) was used to classify the events of normoglycemia and the events of hypoglycemia. First a forward selection method was used to select a subset of features for the optimal classification model. This selection was done including a cross-validation with ten groups, leaving 2 events out for classification and 18 events for training. Forward selection starts with no features and assesses every single feature and finds the best feature. This feature is then included as part of the optimal feature subset. All other features are added again to form a two-feature subset etc. this is repeated until new features doesn't increase the performance.

[0058] A subset of features selected is then used for the final classification model, which also included a ten-fold cross-validation. Sensitivity and specificity is used to evaluate the classification model.

Results:

[0059] A total of 903 samples equivalent to 4515 minutes among 10 patients with 16 hypoglycemic events were analyzed and classified using the model. The sample-based evaluation yielded a ROC AUC of 0.98. With a specificity of 99% the model had a sensitivity of 79%. This is a significant improvement over CGM alone. Event-based, the model classified all hypoglycemic events correctly, did not detect any false-positive events and had a lead-time of $22 \pm (12)$ minutes. CGM alone was able to detect 12 out of 16 events with a lead-time $0 \pm (11)$ minutes. Figure 4 shows the data for one patient where CGM alone detects hypoglycemia, indicated by 430, late after the real onset, indicated by 410, while the present method detects the hypoglycemic event, indicated by 420, one minute after the real onset.

Claims

1. A device comprising one or more processors (150) configured to:

a) obtain, via one or more sensors (120), a signal related to a heart rhythm (110) of a subject and a signal related to a glucose level of interstitial fluid of the subject;
 b) analyze changes in heart rate variability of the subject based on the heart rhythm signal;
 c) analyze changes in the glucose level of the interstitial fluid based on the interstitial glucose level signal; and
 d) predict, for a physiological condition of the subject for which the glucose level of the interstitial fluid is a surrogate measurement, whether there is a change in the physiological condition of the subject during a time period, wherein the prediction is based on the changes in the heart rate variability and the changes in the glucose level of the interstitial fluid.

2. The device of claim 1, wherein the one or more processors (150) are configured to process or correlate data related to the changes in the heart rate variability to determine whether the heart rhythm (110) signal or a change in the heart rhythm (110) signal is of a physiological significance.

3. The device of any one of claims 1-2, further comprising at least one of the one or more sensors (120) configured to obtain the heart rhythm (110) signal or the interstitial glucose level signal.

4. The device of any one of claims 1-3, wherein the one or more processors (150) are configured to predict whether there is a change in the physiological condition of the subject based on

(i) the changes in the heart rate variability,
 (ii) the changes in the glucose level of the interstitial fluid, and
 (iii) a pattern recognition model trained using prior heart rhythm measurements of the subject and prior glucose level measurements of the subject.

5. The device of any one of claims claim 1-4, wherein the one or more processors (150) are further configured to determine whether the changes in the heart rate variability of the subject are to be treated as a non-healthy incidence.

6. The device of any one of claims 1-5, wherein the interstitial fluid glucose level signal is periodically obtained via the one or more sensors (120).

7. The device of any one of claims 1-6, wherein the one or more processors (150) are further configured to analyze motion of the subject using audio or visual guidance and wherein the one or more processors (150) are configured to predict the physiological condition of the subject, further based on the analysis of the motion of the subject.

8. The device of any one of claims 1-7, further comprising a feedback mechanism for providing an audio, visual, or audio-visual feedback to the subject when a non-healthy physiological change is detected.

9. The device of any one of claims 1-8, wherein the one or more processors (150) are configured to analyze changes in the heart rate variability by detecting patterns or changes in patterns of the heart rhythm (110) in the heart rhythm signal.

10. A method comprising the steps of:

a) obtaining, via one or more sensors (120), a signal related to a heart rhythm (110) of a subject and a signal related to a glucose level of interstitial fluid of the subject;
 b) analyzing, via one or more sensors (120), changes in a heart rate variability of the subject based on the heart rhythm (110) signal;
 c) analyzing, via the one or more processors (150), changes of the glucose level of the interstitial fluid based on the interstitial fluid glucose level signal; and
 d) predict, via the one or more processors (150), for a physiological condition of the subject for which the glucose level of the interstitial fluid is a surrogate measurement, whether there is a change in the physiological condition of the subject during a time period, wherein the prediction is based on the changes in the heart rate variability and the changes in the glucose level of the interstitial fluid.

11. The method of claim 10, wherein the one or more processors (150) are configured to predict whether there is a change in the physiological condition of the subject based on

(i) the changes in the heart rate variability;

- (ii) the changes in the glucose level of the interstitial fluid, and
- (iii) a pattern recognition model trained using prior heart rhythm measurements of the subject and prior glucose level measurements of the subject.

5 12. A computer-readable medium comprising computer-readable code physically embodied thereon which, when executed by a processor of a device according to claim 1, causes the processor to perform a method of any one of claims 10 or 11.

10 Patentansprüche

1. Vorrichtung, umfassend einen oder mehrere Prozessoren (150), konfiguriert um:

- 15 (a) ein zu einem Herzrhythmus zugeordnetes Signal (110) eines Subjekts, und ein zu einem Glukoselevel eines interstitiellen Fluids des Subjekts zugeordnetes Signal zu erhalten über einen oder mehrere Sensoren (120) zu erhalten;
- (b) Veränderungen in der Herzfrequenzvariabilität des Subjekts basierend auf dem Herzrhythmus signal zu analysieren;
- 20 (c) Veränderungen im Glukoselevel des interstitiellen Fluids basierend auf dem interstitiellen Glukoselevelsignal zu analysieren; und
- (d) für eine physiologische Verfassung des Subjekts, für welches das Glukoselevel des interstitiellen Fluids ein Surrogat-Parameter ist, vorherzusagen, ob eine Veränderung in der physiologischen Verfassung des Subjekts während einer Zeitdauer vorliegt, wobei die Vorhersage auf den Veränderungen in der Herzfrequenzvariabilität und den Veränderungen der Glukoselevel des interstitiellen Fluids basiert.

25 2. Vorrichtung gemäß Anspruch 1, wobei der eine oder mehrere Prozessoren (150) konfiguriert sind, um Daten bezogen auf die Veränderungen in der Herzfrequenzvariabilität zu prozessieren oder korrelieren, um zu bestimmen, ob das Herzrhythmus signal (110) oder eine Veränderung im Herzrhythmus signal (110) von physiologischer Signifikanz ist.

30 3. Vorrichtung gemäß einem der Ansprüche 1-2, weiterhin umfassend mindestens einen der einen oder mehreren Sensoren (120), die konfiguriert sind, um das Herzrhythmus signal (110) oder das interstitielle Glukoselevelsignal zu erhalten.

35 4. Vorrichtung gemäß einem der Ansprüche 1-3, wobei der eine oder mehrere Prozessoren konfiguriert sind, um vorherzusagen, ob eine Veränderung in der physiologischen Verfassung des Subjekts vorliegt, basierend auf

- (i) den Veränderungen in der Herzfrequenzvariabilität,
- (ii) den Veränderungen im Glukoselevel des interstitiellen Fluids, und
- 40 (iii) einem Mustererkennungsmodell, welches unter Verwendung von vorherigen Herzrhythmusmessungen und vorherigen Glukoselevelmessungen des Subjekts trainiert ist.

45 5. Vorrichtung gemäß einem der Ansprüche 1-4, wobei der eine oder mehrere Prozessoren (150) weiterhin konfiguriert sind, um zu bestimmen, ob die Veränderungen in der Herzfrequenzvariabilität des Subjekts als eine nicht-gesunde Inzidenz behandelt wird.

6. Vorrichtung gemäß einem der Ansprüche 1-5, wobei das Glukoselevelsignal des interstitiellen Fluids periodisch über den einen oder mehrere Sensoren erhalten wird.

50 7. Vorrichtung gemäß einem der Ansprüche 1-6, wobei der eine oder mehrere Prozessoren (150) weiterhin konfiguriert sind, um Bewegungen des Subjekts unter der Verwendung von audio- oder visueller Führung zu analysieren, und wobei der eine oder mehrere Prozessoren (150) konfiguriert sind, um die physiologische Verfassung des Subjekts, weiterhin basierend auf der Analyse der Bewegung des Subjekts, vorherzusagen.

55 8. Vorrichtung gemäß einem der Ansprüche 1-7, weiterhin umfassend einen Feedback-Mechanismus, um ein audio-, visuelles oder audio-visuelles Feedback zum Subjekt bereitzustellen, wenn eine nicht-gesunde physiologische Veränderung detektiert wird.

9. Vorrichtung gemäß einem der Ansprüche 1-8, wobei der eine oder mehrere Prozessoren (150) konfiguriert sind,

um Veränderungen in der Herzfrequenzvariabilität durch Detektion von Mustern oder Veränderungen in Mustern des Herzrhythmus (110) im Herzrhythmusignal zu analysieren.

10. Verfahren, die folgenden Schritte umfassend:

- a) Erhalten, über einen oder mehreren Sensoren (120), von einem zu einem Herzrhythmus zugeordneten Signal (110) eines Subjekts und von einem zu einem Glukoselevel eines interstitiellen Fluids des Subjekts zugeordneten Signal;
- b) Analysieren, über einen oder mehrere Sensoren (120) von Veränderungen in der Herzfrequenzvariabilität des Subjekts basierend auf dem Herzrhythmusignal (110);
- c) Analysieren, über den einen oder mehrere Prozessoren (150), von Veränderungen des Glucoselevels des interstitiellen Fluids basierend auf dem interstitiellen Fluid Glucoselevelsignal; und
- d) Vorhersagen, über den einen oder mehrere Prozessoren (150), für eine physiologische Verfassung des Subjekts, für welches das Glucoselevel des interstitiellen Fluids eine Surrogatmessung ist, ob eine Veränderung in einer physiologischen Verfassung des Subjekts während einer Zeitdauer vorliegt, wobei die Vorhersage auf den Veränderungen in der Herzfrequenzvariabilität und den Veränderungen im Glucoselevel des interstitiellen Fluids basiert.

11. Verfahren gemäß Anspruch 10, wobei der eine oder mehrere Prozessoren (150) konfiguriert sind, um eine Veränderung in der physiologischen Verfassung des Subjekts vorherzusagen, basierend auf

- (i) den Veränderungen in der Herzfrequenzvariabilität;
- (ii) den Veränderungen im Glucoselevel des interstitiellen Fluids, und
- (iii) einem Mustererkennungsmodell, welches unter Verwendung vorheriger Herzrhythmusmessungen des Subjekts und vorheriger Glucoselevelmessungen des Subjekts trainiert ist.

12. Computer-lesbares Medium, umfassend einen physisch darauf aufgebracht Computerlesbaren Code, welcher, wenn durch einen Prozessor einer Vorrichtung gemäß Anspruch 1 ausgeführt, den Prozessor veranlasst, das Verfahren gemäß einem der Ansprüche 10 oder 11 durchzuführen.

Revendications

1. Dispositif comprenant un ou plusieurs processeurs (150) conçus pour :

- a) obtenir, via un ou plusieurs capteurs (120), un signal associé à un rythme cardiaque (110) d'un sujet et un signal associé à un niveau de glucose du liquide interstitiel du sujet ;
- b) analyser des changements de la variabilité du rythme cardiaque du sujet en fonction du signal du rythme cardiaque ;
- c) analyser les changements du niveau de glucose du liquide interstitiel en fonction du signal du niveau de glucose du fluide interstitiel ; et
- d) prévoir, pour un état physiologique du sujet pour lequel le niveau de glucose du liquide interstitiel est une mesure de substitution, s'il y a un changement de l'état physiologique du sujet pendant une période donnée, où la prévision est basée sur les changements de la variabilité du rythme cardiaque et les changements du niveau de glucose du liquide interstitiel.

2. Dispositif selon la revendication 1, dans lequel les un ou plusieurs processeurs (150) sont conçus pour traiter ou corréler des données associées aux changements de la variabilité du rythme cardiaque pour déterminer si le signal du rythme cardiaque (110) ou un changement du signal du rythme cardiaque (110) a une importance physiologique.

3. Dispositif selon l'une quelconque des revendications 1-2, comprenant en outre au moins l'un des un ou plusieurs capteurs (120) conçus pour obtenir le signal du rythme cardiaque (110) ou le signal du niveau de glucose interstitiel.

4. Dispositif selon l'une quelconque des revendications 1-3, dans lequel les un ou plusieurs processeurs (150) sont conçus pour prévoir s'il existe un changement de l'état physiologique du sujet en se basant sur

- (i) les changements de la variabilité du rythme cardiaque,
- (ii) les changements du niveau de glucose du liquide interstitiel, et

(iii) un modèle de reconnaissance de profil formé au moyen de mesures antérieures du rythme cardiaque du sujet et de mesures antérieures du niveau de glucose du sujet.

5 5. Dispositif selon l'une quelconque des revendications 1-4, dans lequel les un ou plusieurs processeurs (150) sont en outre conçus pour déterminer si les changements de la variabilité du rythme cardiaque du sujet doivent être traités comme une incidence de mauvaise santé.

10 6. Dispositif selon l'une quelconque des revendications 1-5, dans lequel le signal du niveau de glucose du liquide interstitiel est obtenu périodiquement via les un ou plusieurs capteurs (120).

15 7. Dispositif selon l'une quelconque des revendications 1-6, dans lequel les un ou plusieurs processeurs (150) sont en outre conçus pour analyser le mouvement du sujet à l'aide d'un guidage audio ou visuel et dans lequel les un ou plusieurs processeurs (150) sont conçus pour prévoir l'état physiologique du sujet, en se basant en outre sur l'analyse du mouvement du sujet.

8. Dispositif selon l'une quelconque des revendications 1-7, comprenant en outre un mécanisme de retour pour fournir un retour audio, visuel, ou audiovisuel au sujet lorsqu'un changement physiologique de mauvaise santé est détecté.

20 9. Dispositif selon l'une quelconque des revendications 1-8, dans lequel les un ou plusieurs processeurs (150) sont conçus pour analyser des changements de la variabilité du rythme cardiaque en détectant des profils ou des changements des profils du rythme cardiaque (110) du signal du rythme cardiaque.

10. Procédé comprenant les étapes suivantes :

25 a) obtenir, via un ou plusieurs capteurs (120), un signal associé à un rythme cardiaque (110) d'un sujet et un signal associé à un niveau de glucose du liquide interstitiel du sujet ;

b) analyser, via un ou plusieurs capteurs (120), des changements d'une variabilité du rythme cardiaque du sujet à partir du signal du rythme cardiaque (110) ;

30 c) analyser via les un ou plusieurs processeurs (150), des changements du niveau de glucose du fluide interstitiel à partir du signal du niveau de glucose du liquide interstitiel ; et

d) prévoir, via les un ou plusieurs processeurs (150), pour un état physiologique du sujet pour lequel le niveau de glucose du liquide interstitiel est une mesure de substitution, s'il y a un changement de l'état physiologique du sujet pendant une période donnée, où la prévision est basée sur les changements de la variabilité du rythme cardiaque et les changements du niveau de glucose du liquide interstitiel.

35 11. Procédé selon la revendication 10, dans lequel les un ou plusieurs processeurs (150) sont conçus pour prévoir s'il y a un changement de l'état physiologique du sujet en basant sur

(i) les changements de la variabilité du rythme cardiaque,

40 (ii) les changements du niveau de glucose du liquide interstitiel, et

(iii) un modèle de reconnaissance de profil formé au moyen de mesures antérieures du rythme cardiaque du sujet et de mesures antérieures du niveau de glucose du sujet.

45 12. Support lisible par ordinateur comprenant un code lisible par ordinateur réalisé physiquement sur celui-ci qui, en cas d'exécution par un processeur d'un dispositif selon la revendication 1, permet au processeur d'effectuer un procédé selon l'une quelconque des revendications 10 ou 11.




Figure 1

200




Figure 2




Figure 3




Figure 4

REFERENCES CITED IN THE DESCRIPTION

This list of references cited by the applicant is for the reader's convenience only. It does not form part of the European patent document. Even though great care has been taken in compiling the references, errors or omissions cannot be excluded and the EPO disclaims all liability in this regard.

Patent documents cited in the description

- WO 2005037092 A1 **[0004]**

专利名称(译)	改善生理状态变化预测的方法和装置		
公开(公告)号	EP3035848B1	公开(公告)日	2020-03-11
申请号	EP2013866494	申请日	2013-08-23
[标]申请(专利权)人(译)	MEDICUS ENG		
申请(专利权)人(译)	MEDICUS工程APS		
当前申请(专利权)人(译)	MEDICUS工程APS		
[标]发明人	FLEISCHER JESPER CICHOSZ SIMON LEBECH		
发明人	FLEISCHER, JESPER CICHOSZ, SIMON LEBECH		
IPC分类号	A61B5/145 A61B5/00 A61B5/024 A61M5/172		
CPC分类号	A61B5/02405 A61B5/14532 A61B5/7267 A61B5/7275 A61B5/746 A61M5/1723 G06F19/00 G16H50/20 A61B5/0205 A61B5/7405 A61B5/742		
其他公开文献	EP3035848A1		
外部链接	Espacenet		

摘要(译)

公开了用于预测和检测对象的生理状况的变化的设备，方法和系统。一种用于检测和预测受试者的生理状况变化的设备，可以包括一个或多个处理器，该处理器被配置为：(i) 分析受试者的心律的变化；(ii) 分析来自与受试者的生理状况相关的一种或多种生物标志物的信号；(iii) 基于心律的变化和来自一种或多种生物标志物的信号，确定受试者在一段时间内的生理状况是否发生变化。




Figure 1