



(12) **EUROPEAN PATENT APPLICATION**

(43) Date of publication:
19.10.2016 Bulletin 2016/42

(51) Int Cl.:
A61B 5/00 (2006.01) A61B 5/22 (2006.01)

(21) Application number: **16164775.5**

(22) Date of filing: **07.12.2007**

(84) Designated Contracting States:
AT BE BG CH CY CZ DE DK EE ES FI FR GB GR HU IE IS IT LI LT LU LV MC MT NL PL PT RO SE SI SK TR

(30) Priority: **19.12.2006 US 875606 P**
21.12.2006 US 876128 P
08.03.2007 US 905761 P
12.06.2007 US 811844

(62) Document number(s) of the earlier application(s) in accordance with Art. 76 EPC:
07862660.3 / 2 094 152

(71) Applicant: **Valencell, Inc.**
Raleigh, NC 27609 (US)

(72) Inventors:
• **LEBOEUF, Steven Francis**
Raleigh, NC North Carolina 27603 (US)
• **TUCKER, Jesse Berkley**
Knightdale, NC North Carolina 27545 (US)
• **AUMER, Michael Edward**
Raleigh, NC North Carolina 27608 (US)

(74) Representative: **Yeadon IP Limited**
Leeds Innovation Centre
103 Clarendon Road
Leeds LS2 9DF (GB)

Remarks:

This application was filed on 11-04-2016 as a divisional application to the application mentioned under INID code 62.

(54) **TELEMETRIC APPARATUS FOR HEALTH AND ENVIRONMENTAL MONITORING**

(57) Wearable apparatus for monitoring various physiological and environmental factors are provided. Real-time, noninvasive health and environmental monitors include a plurality of compact sensors integrated

within small, low-profile devices, such as earpiece modules. Physiological and environmental data is collected and wirelessly transmitted into a wireless network, where the data is stored and/or processed.




FIG. 1

Description

RELATED APPLICATION

[0001] This application claims the benefit of and priority to U.S. Provisional Patent Application No. 60/905,761, filed March 8, 2007, U.S. Provisional Patent Application No. 60/876,128, filed December 21, 2006, and U.S. Provisional Patent Application No. 60/875,606, filed December 19, 2006, the disclosures of which are incorporated herein by reference as if set forth in their entireties.

FIELD OF THE INVENTION

[0002] The present invention relates generally to health and environmental monitors and, more particularly, to wireless health and environment monitors.

BACKGROUND OF THE INVENTION

[0003] There is growing market demand for personal health and environmental monitors, for example, for gauging overall health and metabolism during exercise, athletic training, dieting, and physical therapy. However, traditional health monitors and environmental monitors may be bulky, rigid, and uncomfortable - generally not suitable for use during daily physical activity. There is also growing interest in generating and comparing health and environmental exposure statistics of the general public and particular demographic groups. For example, collective statistics enable the healthcare industry and medical community to direct healthcare resources to where they are most highly valued. However, methods of collecting these statistics may be expensive and laborious, often utilizing human-based recording/analysis steps at multiple sites.

[0004] As such, improved ways of collecting, storing and analyzing personal health and environmental information are needed. In addition, improved ways of distributing raw and analyzed personal health and environmental information are desirable to support efforts to enhance healthcare quality and reduce costs.

SUMMARY

[0005] In view of the above discussion, apparatus for monitoring various physiological and environmental factors are provided. According to some embodiments of the present invention, real-time, noninvasive health and environmental monitors include a plurality of compact sensors integrated within small, low-profile devices. Physiological and environmental data is collected and wirelessly transmitted into a wireless network, where the data is stored and/or processed.

[0006] In some embodiments of the invention, an earpiece functions as a physiological monitor, an environmental monitor, and a wireless personal communicator. The earpiece can take advantage of commercially avail-

able open-architecture wireless paradigms, such as Bluetooth®, Wi-Fi, or ZigBee. In some embodiments, a small, compact earpiece contains at least one microphone and one speaker, and is configured to transmit information wirelessly to a recording device such as, for example, a cell phone, a personal digital assistant (PDA), and/or a computer. The earpiece contains a plurality of sensors for monitoring personal health and environmental exposure. Health and environmental information, sensed by the sensors is transmitted wirelessly, in real-time, to a recording device, capable of processing and organizing the data into meaningful displays, such as charts. In some embodiments, an earpiece user can monitor health and environmental exposure data in real-time, and may also access records of collected data throughout the day, week, month, etc., by observing charts and data through an audio-visual display.

[0007] In some embodiments, an earpiece can integrate personal physiological and environmental exposure information with biofeedback and personal entertainment. In other embodiments of the present invention, earpiece monitor devices enable a variety of networks, applications, games, and business methods.

[0008] In some embodiments of the present invention, a monitoring apparatus includes a housing configured to be attached to the body of a person, one or more physiological sensors and one or more environmental sensors supported by (within and/or on) the housing. Each physiological sensor is configured to detect and/or measure physiological information from the person, and each environmental sensor is configured to detect and/or measure environmental conditions in a vicinity of the person wearing the apparatus. The apparatus also includes a signal processor that is configured to receive and process signals produced by the physiological and environmental sensors. A wireless transmitter is responsive to the signal processor and is configured to wirelessly transmit physiological and environmental sensor signals as processed by the signal processor from the signal processor to a remote terminal in real-time.

[0009] Each physiological sensor is configured to detect and/or measure one or more of the following types of physiological information: heart rate, pulse rate, breathing rate, blood flow, heartbeat signatures, cardiopulmonary health, organ health, metabolism, electrolyte type and/or concentration, physical activity, caloric intake, caloric metabolism, blood metabolite levels or ratios, blood pH level, physical and/or psychological stress levels and/or stress level indicators, drug dosage and/or dosimetry, physiological drug reactions, drug chemistry, biochemistry, position and/or balance, body strain, neurological functioning, brain activity, brain waves, blood pressure, cranial pressure, hydration level, auscultatory information, auscultatory signals associated with pregnancy, physiological response to infection, skin and/or core body temperature, eye muscle movement, blood volume, inhaled and/or exhaled breath volume, physical exertion, exhaled breath physical and/or chemical com-

position, the presence and/or identity and/or concentration of viruses and/or bacteria, foreign matter in the body, internal toxins, heavy metals in the body, anxiety, fertility, ovulation, sex hormones, psychological mood, sleep patterns, hunger and/or thirst, hormone type and/or concentration, cholesterol, lipids, blood panel, bone density, organ and/or body weight, reflex response, sexual arousal, mental and/or physical alertness, sleepiness, auscultatory information, response to external stimuli, swallowing volume, swallowing rate, sickness, voice characteristics, voice tone, voice pitch, voice volume, vital signs, head tilt, allergic reactions, inflammation response, auto-immune response, mutagenic response, DNA, proteins, protein levels in the blood, water content of the blood, pheromones, internal body sounds, digestive system functioning, cellular regeneration response, healing response, stem cell regeneration response

[0010] Each environmental sensor is configured to detect and/or measure one or more of the following types of environmental information: climate, humidity, temperature, pressure, barometric pressure, soot density, airborne particle density, airborne particle size, airborne particle shape, airborne particle identity, volatile organic chemicals (VOCs), hydrocarbons, polycyclic aromatic hydrocarbons (PAHs), carcinogens, toxins, electromagnetic energy, optical radiation, X-rays, gamma rays, microwave radiation, terahertz radiation, ultraviolet radiation, infrared radiation, radio waves, atomic energy alpha particles, atomic energy beta-particles, gravity, light intensity, light frequency, light flicker, light phase, ozone, carbon monoxide, carbon dioxide, nitrous oxide, sulfides, airborne pollution, foreign material in the air, viruses, bacteria, signatures from chemical weapons, wind, air turbulence, sound and/or acoustical energy, ultrasonic energy, noise pollution, human voices, animal sounds, diseases expelled from others, exhaled breath and/or breath constituents of others, toxins from others, pheromones from others, industrial and/or transportation sounds, allergens, animal hair, pollen, exhaust from engines, vapors and/or fumes, fuel, signatures for mineral deposits and/or oil deposits, snow, rain, thermal energy, hot surfaces, hot gases, solar energy, hail, ice, vibrations, traffic, the number of people in a vicinity of the person, coughing and/or sneezing sounds from people in the vicinity of the person, loudness and/or pitch from those speaking in the vicinity of the person.

[0011] In some embodiments, the signal processor is configured to process signals produced by the physiological and environmental sensors into signals that can be heard and/or viewed by the person wearing the apparatus. In some embodiments, the signal processor is configured to selectively extract environmental effects from signals produced by a physiological sensor and/or selectively extract physiological effects from signals produced by an environmental sensor.

[0012] In some embodiments of the present invention, a monitoring apparatus configured to be worn by a person includes a physiological sensor that is oriented in a di-

rection towards the person and an environmental sensor that is oriented in a direction away from the person. A buffer material is positioned between the physiological sensor and environmental sensors and is configured to selectively reflect and/or absorb energy emanating from the environment and/or the person.

[0013] In some embodiments of the present invention, a monitoring apparatus may include a receiver that is configured to receive audio and/or video information from a remote terminal, and a communication module that is configured to store and/or process and/or play audio and/or video information received from the remote terminal. In some embodiments, the communication module may be configured to alert (e.g., via audible and/or visible and/or physical alerts) a person wearing the apparatus when a physiological sensor detects certain physiological information from the person and/or when an environmental sensor detects certain environmental information from the vicinity of the person. In some embodiments, the communication module is configured to audibly present vital sign information to the person wearing the apparatus. In some embodiments, the communication module may be configured to store content generated by the person.

[0014] In some embodiments of the present invention, a monitoring apparatus may include a transmitter that is configured to transmit signals produced by physiological and environmental sensors associated therewith to a gaming device. The monitoring apparatus may also be configured to receive feedback regarding monitored health and environmental parameters. As such, personal health and environmental feedback can be an active component of a game.

[0015] In some embodiments, the apparatus is an earpiece module that is configured to be attached to the ear of a person, and includes a speaker, microphone, and transceiver that is electronically connected to the speaker and microphone and that permits bidirectional wireless communications between the earpiece module and a remote terminal, such as a cell phone. The transceiver (e.g., a Bluetooth®, Wi-Fi, or ZigBee transceiver) is electronically connected to the signal processor and is configured to transmit physiological and environmental sensor signals from the signal processor to the remote terminal. In some embodiments, the earpiece module may include an arm that is attached to the housing and that supports the microphone. The arm may be movable between a stored position and an extended, operative position. The arm may also include one or more physiological sensor and/or environmental sensors.

[0016] In some embodiments of the present invention, an earpiece module that is configured to be attached to the ear of a person includes a first acoustical sensor oriented in a direction towards a tympanic membrane of the ear and is configured to detect acoustical energy emanating from the tympanic membrane. A second acoustical sensor is oriented in a direction away from the person. The signal processor is configured to utilize signals pro-

duced by the second acoustical signal to extract environmental acoustical energy not emanating from the tympanic membrane from signals produced by the first acoustical sensor. In some embodiments, the earpiece module may include an optical emitter that directs optical energy towards the tympanic membrane, and an optical detector that is configured to detect secondary optical energy emanating from the tympanic membrane. The signal processor is configured to extract selected optical energy from the secondary optical energy emanating from the tympanic membrane. The signal processor may also be configured to extract optical noise from the secondary optical energy emanating from the tympanic membrane. In some embodiments, the optical detector may include a filter configured to pass secondary optical energy at selective wavelengths.

[0017] In some embodiments of the present invention, an earpiece module that is configured to be attached to the ear of a person includes an optical detector that is configured to detect acoustically modulated blackbody IR radiation emanating from the tympanic membrane.

[0018] In some embodiments of the present invention, an earpiece module that is configured to be attached to the ear of a person includes an optical emitter that directs optical energy towards the tympanic membrane, and an optical detector configured to detect secondary optical energy emanating from the tympanic membrane. In some embodiments, the signal processor may be configured to extract selected optical energy and/or optical noise from the secondary optical energy emanating from the tympanic membrane. In some embodiments, the optical detector may include a filter configured to pass secondary optical energy at selective wavelengths.

[0019] In some embodiments of the present invention, an earpiece module that is configured to be attached to the ear of a person includes an ear hook that is configured to attach to an ear of a person. One or more physiological sensors and/or one or more environmental sensors may be supported by the ear hook. In some embodiments, the hook may include a pinna cover that is configured to contact a portion of the pinna of an ear. One or more physiological and/or environmental sensors may be supported by the pinna cover.

[0020] In some embodiments of the present invention, an earpiece module may include an arm that extends outwardly therefrom and that supports one or more physiological sensors and/or environmental sensors. For example, the arm may be configured to support physiological sensors configured to detect and/or measure jaw motion and/or arterial blood flow near the neck of a person wearing the earpiece module.

[0021] In some embodiments of the present invention, an earpiece module may include an earpiece fitting configured to be inserted near or within the ear canal of a person wearing the earpiece. The earpiece fitting may include one or more physiological sensors configured to detect information from within the ear canal.

[0022] In some embodiments of the present invention,

an earpiece module may include a transmittance pulse oximeter and/or reflectance pulse oximeter. For example, the earpiece module may include an earlobe clip having a transmittance pulse oximeter and/or reflectance pulse oximeter supported thereby. As another example, the earpiece module may include a transmitter pulse oximeter and/or reflectance pulse oximeter supported at the front or back of the ear.

[0023] In some embodiments of the present invention, a monitoring apparatus is an earring. The earring may be configured to operate independently of other monitoring apparatus, such as an earpiece module, or may operate in conjunction with another monitoring apparatus. For example, an earring may include one or more physiological sensors configured to detect and/or measure physiological information from the person, and one or more environmental sensors configured to detect and/or measure environmental conditions in a vicinity of the person wearing the earring. The earring may also include a signal processor that receives and processes signals produced by the physiological and environmental sensors, and a transmitter that transmits physiological and environmental sensor signals from the signal processor to a remote terminal in real-time.

[0024] In some embodiments of the present invention, a monitoring apparatus configured to be attached to the ear of a person may include a housing containing one or more physiological and environmental sensors wherein the housing is configured to be positioned in adjacent contacting relationship with the temple of the person.

[0025] Monitoring apparatus, according to some embodiments of the present invention, may include various additional devices/features. For example, a monitoring apparatus may include an air sampling system that samples air in a vicinity of the person wearing the apparatus. In some embodiments, one or more physiological sensors in a monitoring apparatus may be configured to detect drowsiness of the person wearing the apparatus. An alarm may be provided that is configured to alert the person in response to one or more physiological sensors detecting drowsiness. In some embodiments, a monitoring apparatus may include a user interface that provides user control over one or more of the physiological and/or environmental sensors. A user interface may be provided on the monitoring apparatus or may be included on a remote device in wireless communication with the monitoring apparatus. In some embodiments, a monitoring apparatus may include a user interface that is configured to allow the person to store a time mark indicating a particular point in time.

[0026] Monitoring apparatus, according to some embodiments of the present invention, may be configured to send a signal to a remote terminal when one or more of the physiological and/or environmental sensors are turned off by a user and/or when one or more of the physiological and/or environmental sensors malfunction or fail. In some embodiments, a signal may be sent to a remote terminal when potentially erroneous data has

been collected by one or more of the physiological and/or environmental sensors, such as when a person wearing a monitoring apparatus is surrounded by loud noises.

[0027] Monitoring apparatus, according to some embodiments of the present invention, may be configured to detect damage to a portion of the body of the person wearing the apparatus, and may be configured to alert the person when such damage is detected. For example, when a person is exposed to sound above a certain level that may be potentially damaging, the person is notified by the apparatus to move away from the noise source. As another example, the person may be alerted upon damage to the tympanic membrane due to loud external noises.

BRIEF DESCRIPTION OF THE DRAWINGS

[0028]

Fig. 1 is a block diagram of a telemetric earpiece module for physiological and environmental monitoring and personal communication, according to some embodiments of the present invention.

Fig. 2 is a block diagram of a telemetric network for health and environmental monitoring through portable telemetric sensor modules, such as the earpiece module of **Fig. 1**, according to some embodiments of the present invention.

Fig. 3 illustrates a graphical user interface for displaying data, according to some embodiments of the present invention.

Fig. 4 is a block diagram that illustrates a method of extracting physiological and environmental information using a plurality of sensors and a signal processor, according to some embodiments of the present invention.

Fig. 5 illustrates an auscultatory signal extraction technique according to the methodology illustrated in **Fig. 4**.

Fig. 6 illustrates an optical physiological signal extraction technique, according to some embodiments of the present invention, and wherein optical information scattered from the tympanic membrane is digitally compared with acoustical energy from the environment to generate an extracted signal containing cleaner physiological information than raw optical information scattered from the tympanic membrane.

Fig. 7 illustrates an optical source detector configuration, according to some embodiments of the present invention, for the physiological signal extraction method illustrated in **Fig. 6**.

Fig. 8 illustrates experimental auscultatory data obtained via the auscultatory signal extraction approach of **Fig. 5**.

Fig. 9 illustrates an earpiece module according to some embodiments of the present invention.

Fig. 10 is a side view of the earpiece module of **Fig.**

9 showing a placement of physiological sensors, according to some embodiments of the present invention.

Fig. 11 is a front view of the earpiece module of **Fig. 9** showing a placement of environmental sensors, according to some embodiments of the present invention.

Fig. 12 is an exploded view of the earpiece module of **Fig. 9** showing a location of various physiological sensors, according to some embodiments of the present invention.

Fig. 13 is a side view of a flexible substrate configured to place sensors in selected locations in the vicinity of the ear, according to some embodiments of the present invention.

Figs. 14A-14B illustrates an earpiece module with an adjustable mouthpiece for monitoring physiological and environmental information near the mouth, according to some embodiments of the present invention, wherein **Fig. 14A** illustrates the mouthpiece in a stored position and wherein **Fig. 14B** illustrates the mouthpiece in an extended operative position.

Fig. 15 illustrates an earpiece module incorporating various physiological and environmental sensors, according to some embodiments of the present invention, and being worn by a user.

Fig. 16 illustrates an earpiece module according to other embodiments of the present invention that includes a temple module for physiological and environmental monitoring.

Fig. 17 illustrates a pulse-oximeter configured to be attached to an ear of a user and that may be incorporated into an earpiece module, according to some embodiments of the present invention. The illustrated pulse-oximeter is in transmission mode.

Fig. 18 illustrates a pulse-oximeter configured to be integrated into an earpiece module, according to some embodiments of the present invention. The illustrated pulse-oximeter is in reflection mode.

Fig. 19 illustrates a sensor module having a plurality of health and environmental sensors and mounted onto a Bluetooth headset module, according to some embodiments of the present invention.

Fig. 20 is a pie chart that graphically illustrates exemplary power usage of an earpiece module for monitoring health and environmental exposure, according to some embodiments of the present invention.

DETAILED DESCRIPTION

[0029] The present invention now is described more fully hereinafter with reference to the accompanying drawings, in which preferred embodiments of the invention are shown. This invention may, however, be embodied in many different forms and should not be construed as limited to the embodiments set forth herein; rather, these embodiments are provided so that this disclosure

will be thorough and complete, and will fully convey the scope of the invention to those skilled in the art.

[0030] Like numbers refer to like elements throughout. In the figures, the thickness of certain lines, layers, components, elements or features may be exaggerated for clarity.

[0031] The terminology used herein is for the purpose of describing particular embodiments only and is not intended to be limiting of the invention. As used herein, the singular forms "a", "an" and "the" are intended to include the plural forms as well, unless the context clearly indicates otherwise. It will be further understood that the terms "comprises" and/or "comprising," when used in this specification, specify the presence of stated features, integers, steps, operations, elements, and/or components, but do not preclude the presence or addition of one or more other features, integers, steps, operations, elements, components, and/or groups thereof. As used herein, the term "and/or" includes any and all combinations of one or more of the associated listed items.

[0032] Unless otherwise defined, all terms (including technical and scientific terms) used herein have the same meaning as commonly understood by one of ordinary skill in the art to which this invention belongs. It will be further understood that terms, such as those defined in commonly used dictionaries, should be interpreted as having a meaning that is consistent with their meaning in the context of the specification and relevant art and should not be interpreted in an idealized or overly formal sense unless expressly so defined herein. Well-known functions or constructions may not be described in detail for brevity and/or clarity.

[0033] It will be understood that when an element is referred to as being "on", "attached" to, "connected" to, "coupled" with, "contacting", etc., another element, it can be directly on, attached to, connected to, coupled with or contacting the other element or intervening elements may also be present. In contrast, when an element is referred to as being, for example, "directly on", "directly attached" to, "directly connected" to, "directly coupled" with or "directly contacting" another element, there are no intervening elements present. It will also be appreciated by those of skill in the art that references to a structure or feature that is disposed "adjacent" another feature may have portions that overlap or underlie the adjacent feature.

[0034] Spatially relative terms, such as "under", "below", "lower", "over", "upper" and the like, may be used herein for ease of description to describe one element or feature's relationship to another element(s) or feature(s) as illustrated in the figures. It will be understood that the spatially relative terms are intended to encompass different orientations of the device in use or operation in addition to the orientation depicted in the figures. For example, if the device in the figures is inverted, elements described as "under" or "beneath" other elements or features would then be oriented "over" the other elements or features. Thus, the exemplary term "under" can en-

compass both an orientation of "over" and "under". The device may be otherwise oriented (rotated 90 degrees or at other orientations) and the spatially relative descriptors used herein interpreted accordingly. Similarly, the terms "upwardly", "downwardly", "vertical", "horizontal" and the like are used herein for the purpose of explanation only unless specifically indicated otherwise.

[0035] The term "earpiece module" includes any type of device that may be attached to or near the ear of a user and may have various configurations, without limitation.

[0036] The term "real-time" is used to describe a process of sensing, processing, or transmitting information in a time frame which is equal to or shorter than the minimum timescale at which the information is needed. For example, the real-time monitoring of pulse rate may result in a single average pulse-rate measurement every minute, averaged over 30 seconds, because an instantaneous pulse rate is often useless to the end user. Typically, averaged physiological and environmental information is more relevant than instantaneous changes. Thus, in the context of the present invention, signals may sometimes be processed over several seconds, or even minutes, in order to generate a "real-time" response.

[0037] The term "monitoring" refers to the act of measuring, quantifying, qualifying, estimating, sensing, calculating, interpolating, extrapolating, inferring, deducing, or any combination of these actions. More generally, "monitoring" refers to a way of getting information via one or more sensing elements. For example, "blood health monitoring" includes monitoring blood gas levels, blood hydration, and metabolite/electrolyte levels.

[0038] The term "physiological" refers to matter or energy of or from the body of a creature (e.g., humans, animals, etc.). In embodiments of the present invention, the term "physiological" is intended to be used broadly, covering both physical and psychological matter and energy of or from the body of an organism. However, in some cases, the term "psychological" is called-out separately to emphasize aspects of physiology that are more closely tied to conscious or subconscious brain activity rather than the activity of other organs, tissues, or cells.

[0039] The term "psychosocial stress" refers to events of psychological or social origin which challenge the homeostatic state of biological systems.

[0040] The term "body" refers to the body of a person (or animal) that may utilize an earpiece module according to embodiments of the present invention. Monitoring apparatus, according to embodiments of the present invention may be worn by humans and animals.

[0041] In the following figures, earpiece modules will be illustrated and described for attachment to the ear of the human body. However, it is to be understood that embodiments of the present invention are not limited to those worn by humans. Moreover, monitoring apparatus according to embodiments of the present invention are not limited to earpiece modules and/or devices configured to be attached to or near the ear. Monitoring appa-

ratus according to embodiments of the present invention may be worn on various parts of the body.

[0042] Some embodiments of the present invention may arise from a discovery that the ear is an ideal location on the human body for a wearable health and environmental monitor. The ear is a relatively immobile platform that does not obstruct a person's movement or vision. Devices located along the ear have access to the inner-ear canal and tympanic membrane (for measuring core body temperature), muscle tissue (for monitoring muscle tension), the pinna and earlobe (for monitoring blood gas levels), the region behind the ear (for measuring skin temperature and galvanic skin response), and the internal carotid artery (for measuring cardiopulmonary functioning). The ear is also at or near the point of exposure to: environmental breathable toxicants of interest (volatile organic compounds, pollution, etc.; noise pollution experienced by the ear; and lighting conditions for the eye. Furthermore, as the ear canal is naturally designed for transmitting acoustical energy, the ear provides an optimal location for monitoring internal sounds, such as heartbeat, breathing rate, and mouth motion.

[0043] Bluetooth-enabled and/or other personal communication earpiece modules may be configured to incorporate physiological and/or environmental sensors, according to some embodiments of the present invention. Bluetooth earpiece modules are typically lightweight, unobtrusive devices that have become widely accepted socially. Moreover, Bluetooth earpiece modules are cost effective, easy to use, and are often worn by users for most of their waking hours while attending or waiting for cell phone calls. Bluetooth earpiece modules configured according to embodiments of the present invention are advantageous because they provide a function for the user beyond health monitoring, such as personal communication and multimedia applications, thereby encouraging user compliance. Exemplary physiological and environmental sensors that may be incorporated into a Bluetooth or other type of earpiece module include, but are not limited to accelerometers, auscultatory sensors, pressure sensors, humidity sensors, color sensors, light intensity sensors, pressure sensors, etc.

[0044] Wireless earpiece devices incorporating low-profile sensors and other electronics, according to embodiments of the present invention, offer a platform for performing near-real-time personal health and environmental monitoring in wearable, socially acceptable devices. The capability to unobtrusively monitor an individual's physiology and/or environment, combined with improved user compliance, is expected to have significant impact on future planned health and environmental exposure studies. This is especially true for those that seek to link environmental stressors with personal stress level indicators. The large scale commercial availability of this low-cost device can enable cost-effective large scale studies. The combination of monitored data with user location via GPS data can make on-going geographic studies possible, including the tracking of infection over large

geographic areas. The commercial application of the proposed platform encourages individual-driven health maintenance and promotes a healthier lifestyle through proper caloric intake and exercise.

[0045] Accordingly, some embodiments of the present invention combine a personal communications earpiece device with one or more physiological and/or environmental sensor. Other embodiments may combine physiological and/or environmental sensors into an earpiece device.

[0046] Embodiments of the present invention are not limited to devices that communicate wirelessly. In some embodiments of the present invention, devices configured to monitor an individual's physiology and/or environment may be wired to a device that stores and/or processes data. In some embodiments, this information may be stored on the earpiece module itself.

[0047] Fig. 1 is a block diagram illustrating an earpiece module **100**, according to some embodiments of the present invention. The illustrated earpiece module **100** includes one or more of the following: at least one physiological sensor **101**, at least one environmental sensor **102** (also referred to as an external energy sensor), at least one signal processor **103**, at least one transmitter/receiver **104**, at least one power source **106**, at least one communication & entertainment module **107**, at least one earpiece attachment component **105**, and at least one housing **108**. Though the health and environmental sensor functionality can be obtained without the communication and entertainment module **107**, having this additional module may promote use of the earpiece module **100** by users. The illustrated earpiece module **100** is intended primarily for human use; however, the earpiece module **100** may also be configured for use with other animals having ears sufficient to support an earpiece, such as primates, canines, felines, cattle, and most other mammals.

[0048] A physiological sensor **101** can be any compact sensor for monitoring the physiological functioning of the body, such as, but not limited to, sensors for monitoring: heart rate, pulse rate, breathing rate, blood flow, heart-beat signatures, cardio-pulmonary health, organ health, metabolism, electrolyte type and concentration, physical activity, caloric intake, caloric metabolism, metabolomics, physical and psychological stress levels and stress level indicators, physiological and psychological response to therapy, drug dosage and activity (drug dosimetry), physiological drug reactions, drug chemistry in the body, biochemistry, position & balance, body strain, neurological functioning, brain activity, brain waves, blood pressure, cranial pressure, hydration level, auscultatory information, auscultatory signals associated with pregnancy, physiological response to infection, skin and core body temperature, eye muscle movement, blood volume, inhaled and exhaled breath volume, physical exertion, exhaled breath physical and chemical composition, the presence, identity, and concentration of viruses & bacteria, foreign matter in the body, internal toxins,

heavy metals in the body, anxiety, fertility, ovulation, sex hormones, psychological mood, sleep patterns, hunger & thirst, hormone type and concentration, cholesterol, lipids, blood panel, bone density, body fat density, muscle density, organ and body weight, reflex response, sexual arousal, mental and physical alertness, sleepiness, auscultatory information, response to external stimuli, swallowing volume, swallowing rate, sickness, voice characteristics, tone, pitch, and volume of the voice, vital signs, head tilt, allergic reactions, inflammation response, autoimmune response, mutagenic response, DNA, proteins, protein levels in the blood, body hydration, water content of the blood, pheromones, internal body sounds, digestive system functioning, cellular regeneration response, healing response, stem cell regeneration response, and the like. Vital signs can include pulse rate, breathing rate, blood pressure, pulse signature, body temperature, hydration level, skin temperature, and the like. A physiological sensor may include an impedance plethysmograph for measuring changes in volume within an organ or body (usually resulting from fluctuations in the amount of blood or air it contains). For example, the earpiece module **100** may include an impedance plethysmograph to monitor blood pressure in real-time.

[0049] An external energy sensor **102**, serving primarily as an environmental sensor, can be any compact sensor for monitoring the external environment in the vicinity of the body, such as, but not limited to, sensors for monitoring: climate, humidity, temperature, pressure, barometric pressure, pollution, automobile exhaust, soot density, airborne particle density, airborne particle size, airborne particle shape, airborne particle identity, volatile organic chemicals (VOCs), hydrocarbons, polycyclic aromatic hydrocarbons (PAHs), carcinogens, toxins, electromagnetic energy (optical radiation, X-rays, gamma rays, microwave radiation, terahertz radiation, ultraviolet radiation, infrared radiation, radio waves, and the like), EMF energy, atomic energy (alpha particles, beta-particles, gamma rays, and the like), gravity, light properties (such as intensity, frequency, flicker, and phase), ozone, carbon monoxide, greenhouse gases, CO₂, nitrous oxide, sulfides, airborne pollution, foreign material in the air, biological particles (viruses, bacteria, and toxins), signatures from chemical weapons, wind, air turbulence, sound and acoustical energy (both human audible and inaudible), ultrasonic energy, noise pollution, human voices, animal sounds, diseases expelled from others, the exhaled breath and breath constituents of others, toxins from others, bacteria & viruses from others, pheromones from others, industrial and transportation sounds, allergens, animal hair, pollen, exhaust from engines, vapors & fumes, fuel, signatures for mineral deposits or oil deposits, snow, rain, thermal energy, hot surfaces, hot gases, solar energy, hail, ice, vibrations, traffic, the number of people in a vicinity of the user, the number of people encountered throughout the day, other earpiece module users in the vicinity of the earpiece module user, coughing and sneezing sounds from people in the vicinity

of the user, loudness and pitch from those speaking in the vicinity of the user, and the like.

[0050] In some embodiments, a physiological sensor **101** and/or an environmental sensor **102** may be configured to identify a person to whom the earpiece module **100** is attached.

[0051] In some embodiments, a physiological sensor **101** and/or an environmental sensor **102** may be configured to monitor physical aging rate of a person or subject. The signal processor **103** may be configured to process information from a physiological sensor and/or an environmental sensor to assess aging rate. Physiological sensors configured to assess aging rate may include pulse rate sensors, blood pressure sensors, activity sensors, and psychosocial stress sensors. Environmental sensors configured to assess aging rate may include UV sensors and pollution sensors.

[0052] In some embodiments, a physiological sensor **101** and/or an environmental sensor **102** may be configured to be regenerated through a physical and/or chemical change. For example, it is anticipated that an earpiece module **100**, or other device incorporating physiological and/or environmental sensors according to embodiments of the present invention may be coupled to an apparatus that is configured to "recharge" or regenerate one or more environmental and/or physiological sensors via a physical process or a chemical process, etc.

[0053] Because the earpiece module is capable of measuring and transmitting sensor information in real-time over a duration of time, the physiological and environmental sensors **101, 102** can be used to sense the aforementioned parameters over time, enabling a time-dependent analysis of the user's health and environment as well as enabling a comparison between the user's health and environment. Combined with proximity or location detection, this allows an analysis for pinpointing the location where environmental stress and physical strain took place. The signal processor **103** provides a means of converting the digital or analog signals from the sensors **101, 102** into data that can be transmitted wirelessly by the transmitter **104**. The signal processor **103** may be composed of, for example, signal conditioners, amplifiers, filters, digital-to-analog and analog-to-digital converters, digital encoders, modulators, mixers, multiplexers, transistors, various switches, microprocessors, or the like. For personal communication, the signal processor **103** processes signals received by the receiver **104** into signals that can be heard or viewed by the user. The received signals may also contain protocol information for linking various telemetric modules together, and this protocol information can also be processed by the signal processor **103**. The signal processor **103** may utilize one or more "compression/decompression algorithms used in digital media" (CODECs) for processing data. The transmitter **104** can be comprised of a variety of compact electromagnetic transmitters. A standard compact antenna is used in the standard Bluetooth headset protocol, but any kind of electromagnetic antenna

suitable for transmitting at human-safe electromagnetic frequencies may be utilized. The receiver **104** can also be an antenna. In some embodiments, the receiving antenna and the transmitting antenna are physically the same. The receiver/transmitter **104** can be, for example, a non-line-of-sight (NLOS) optical scatter transmission system. These systems typically use short-wave (blue or UV) optical radiation or "solar blind" (deep-UV) radiation in order to promote optical scatter, but IR wavelengths can also suffice. Additionally, a sonic or ultrasonic transmitter can be used as the receiver/transmitter **104** of the earpiece module **100**, but preferably using sounds that are higher or lower than the human hearing range. A variety of sonic and ultrasonic receivers and transmitters are available in the marketplace and may be utilized in accordance with embodiments of the present invention. If a telecommunication device **210** (**Fig. 2**) receiving wireless data signal **109** from the earpiece module **100** is in close proximity to the earpiece module, a variety of transmission schemes can be used. For communicating audible conversational information directly to the earpiece user, encoded telemetric conversational data received by the receiver **104** can be decoded by the signal processing module **103** to generate an electrical signal that can be converted into audible sound by the communication module **107**.

[0054] In some embodiments, the transmitter/receiver **104** is configured to transmit signals from the signal processor to the remote terminal following a predetermined time interval. For example, the transmitter may delay transmission until a certain amount of detection time has elapsed, until a certain amount of processing time has elapsed, etc.

[0055] The power source can be any portable power source **106** capable of fitting inside the earpiece module housing. According to some embodiments, the power source **106** is a portable rechargeable lithium-polymer or zinc-air battery. Additionally, portable energy-harvesting power sources can be integrated into the earpiece module **100** and can serve as a primary or secondary power source. For example, a solar cell module can be integrated into the earpiece module **100** for collecting and storing solar energy. Additionally, piezoelectric devices or microelectromechanical systems (MEMS) can be used to collect and store energy from body movements, electromagnetic energy, and other forms of energy in the environment or from the user himself. A thermoelectric or thermovoltaic device can be used to supply some degree of power from thermal energy or temperature gradients. In some embodiments, a cranking or winding mechanism can be used to store mechanical energy for electrical conversion or to convert mechanical energy into electrical energy that can be used immediately or stored for later.

[0056] The various components describe above are configured to fit within the earpiece housing **108** and/or be attached thereto. The earpiece module housing **108** may be formed from any safe and comfortable solid ma-

terial, such as metal, rubber, wood, polymers, ceramic, organic materials, or various forms of plastic. The earpiece attachment component **105** is attached to the earpiece module housing **108** and is designed to fit around or near the ear. For example, the standard Bluetooth headset includes an earpiece attachment that is connected to the headset housing via a double-jointed socket, to provide comfort and positioning flexibility for the user. In some embodiments, the earpiece attachment component **105** can be part of the housing **108**, such that the entire earpiece module is one largely inflexible, rigid unit. In such case, a counterweight may be incorporated into the earpiece module **100** to balance the weight of the earpiece electronics and power source. In some embodiments, the earpiece attachment component **105** can contain physiological and environmental sensors, and the earpiece attachment component **105** may be detachable. In some embodiments, more than one earpiece attachment **105** can be attached to the earpiece module housing **108**.

[0057] The communication and entertainment module **107** (also interchangeably referred to as a "communication module") is used for, but not limited to: processing or generating an audible sound from information received via the receiver **104** (from a cell phone, computer, network, database, or the like) and/or processing or generating an electrical signal from an audible sound from the user such that the electrical signal can be transmitted telemetrically via the transmitter **104**. For example, in standard Bluetooth protocol, communication electronics are used to convert an audible conversation into an electrical signal for telemetric conversation; communication electronics are also used to convert a digitized telemetric conversation into an audible conversation for the earpiece user. Additionally, the communication and entertainment module **107** can be used to store, process, or play analog or digital information from music, radio shows, videos, or other audible entertainment and to communicate this information to an earpiece user. In many cases, this information includes information received by the receiver **104**. In many cases, the analog or digital information is not stored in the communication and entertainment module **107** but, rather, is stored in a portable telecommunication device **210** (**Fig. 2**). In such case, the communication and entertainment module **107** is used for converting the analog or digital information into audible sound for the earpiece user. The communication and entertainment module **107** may contain at least one microphone, speaker, signal processor (similar to **103**), and digital memory. In some embodiments, the communication and entertainment module **107** may apply at least one CODEC for encoding or decoding information. The communication and entertainment module may utilize non-audible forms of communication with the user, such as visual, physical, or mental (*i.e.*, brainwaves or neural stimulation) communication with the user.

[0058] In some embodiments, an audible communicator is provided that is configured to communicate thera-

peutic sounds (e.g., music therapy, etc.) to the person in response to physiological or psychosocial stress. The audible communicator may be embodied in the communication and entertainment module **107** or may be a separate speaker. In some embodiments, light therapy may be provided to the person in response to physiological or psychosocial stress. In some embodiments, the communication and entertainment module **107** may be configured to communicate a treatment, therapy, and/or plan of action to the person upon detection of physiological and/or environmental concerns. For example, if it is detected that the person is being exposed to unhealthy doses of UV radiation, the communication and entertainment module **107** may audibly instruct the person to move away from the person's current location (e.g., move indoors, etc.).

[0059] Like the other components of the earpiece module **100** shown in **Fig. 1**, the components of the communication and entertainment module **107** are not necessarily located in the same physical vicinity. The microphone and speaker of the communication module **107**, for example, are located closer to the mouth and ear respectively. Furthermore, the signal processor **103** can be composed of several components located throughout the earpiece module. It should be understood that the word "module" does not necessarily imply a unified physical location. Rather, "module" is used to imply a unified function.

[0060] Bluetooth devices conventionally contain a communication module, such as communication module **107**, for converting digital or analog information into audible sounds for the user. However, when combined with the health and environmental monitoring properties of an earpiece module **100** according to embodiments of the present invention, the communication and entertainment module **107** can provide functionality. For example, the earpiece module can serve as a biofeedback device. As a non-limiting example, if a user is in a polluted environment, such as air filled with VOCs, the communication module **107** may notify the user to move to a new environment. As another example, if one or more of the physiological and environmental sensors **101**, **102** of the earpiece module **100** pick up a high particulate density in the environment, with an elevation in core body temperature, and a change in voice pitch occurring simultaneously (or near-simultaneously) within a common time-frame, the communication module **107** may alert the user that he/she may be having an allergic response. As a further example, the user can use the communication and entertainment module **107** to execute biofeedback for willfully controlling blood pressure, breathing rate, body temperature, pulse rate, and the like. The communication module **107** may utilize audible or visible alerts if the user is meeting their physiological targets or exceeding safe physiological limits. Alerting a user by physical or electrical force, such as the sense of touch or tingling from an electric pulse or vibration, can also be utilized. Thus, although communication by audible means

is often utilized, the communication module **107** can alert, signify, or communicate with the user through sound, light, electrical actuation, and physical actuation.

[0061] As a second example of this biofeedback method, basic vital signs collected by the physiological sensors **101** and processed by the signal processor **103** can be presented to the earpiece user audibly, through the communication and entertainment module **107**. For example, the user may be able to listen to his/her breathing rate, pulse rate, and the like. Additionally, an entertaining or aggravating sound or song can be used to alert the user to favorable or unfavorable personal health and environmental factors occurring in real-time. This technique may be applied towards education, such as positive or negative feedback for educational games, learning games, or games of deception (e.g., poker, etc.).

[0062] In some embodiments, the earpiece module **100** may be configured to deliver and/or monitor drugs. For example, a transdermal drug delivery system may be provided that is controlled by earpiece electronics. Earpiece sensors can monitor the drug dosage and the physiological effects of the drug in real-time.

[0063] A health and environmental network **200** according to embodiments of the present invention that may incorporate the earpiece module **100** of **Fig. 1** is illustrated in **Fig. 2**. The earpiece module **100** is a specific sensor module **201** of the network **200**, though other modules located at various other parts of the body can be used in conjunction with, or in place of, the earpiece module **100**. The terms "earpiece module **100**" and "sensor module **200**" are used interchangeably herein in accordance with various embodiments of the present invention. The health and environmental network **200** is composed of at least one sensor module **201** (e.g., earpiece module **100**) at least one portable telecommunication module **210**, at least one transmission system **211**, at least one user interface **214**, at least one personal database **212**, and at least one anonymous database **213**.

[0064] The sensor module **201** can be composed of a primary module alone or a primary module and at least one secondary module. The secondary modules can be located at any location of the body, but are preferably located in a region near the ear, and preferably the earpiece module **100** serves as the primary module. In most cases, the secondary modules are not necessary. But in some cases, secondary modules may be located, for example, behind the ear (near the lymph nodes), at or near the earlobes (such as one or more earrings or ear clips), at the front of the ear (near the carotid artery), at the temples, along the neck, or other locations near the ear. These wearable secondary modules can be connected with either a "hard" connection to the primary module (such as an electric cable) or a "soft" connection to the primary module (such as a wireless connection). In Bluetooth protocol, each secondary module can be simultaneously in direct wireless communication with the primary module. Primary modules and secondary modules in the same location can promote quick-donning, ease-of-

use, and comfortability for the end user. Users are not prone to accept multiple modules at multiple locations of the body.

[0065] The earpiece sensor module **201** communicates wirelessly with the portable telecommunication device **210**, preferably in an open architecture configuration, such as Bluetooth or ZigBee. The telecommunication device **210** can be any portable device, such as a cell phone, PDA, laptop computer, Blackberry, another earpiece, or other portable, telemetric device. The portable telecommunication device **210** and the earpiece module **201** can telemetrically communicate both to and from each other. Though the main purpose of the portable telecommunication device is to transmit the local wireless signal from the sensor module **101** over longer distances unattainable by the transmitter **104** of the sensor module **201**, the telecommunication **210** can also serve as a method of personal communication and entertainment for the earpiece user.

[0066] In some embodiments, the telecommunication device **210** transmits data in only one direction or particular directions. For example, in one embodiment, the portable telecommunication device **210** can receive telemetric information from the sensor module **201** but cannot send out signals to a transmission system **211**. The portable telecommunication device **210** may also contain an end-user graphical interface, such as a user interface **214** in the network **200**, such that data from the earpiece module **201** can be stored, analyzed, summarized, and displayed on the portable telecommunication device **210**. For example, charts relating health and environment, as well as real-time biofeedback and the like, can be displayed on a cell phone, media player, PDA, laptop, or other device. The telecommunication device **210** may also contain physiological and environmental sensors itself, such as blood pressure, pulse rate, and pulse-oximetry, and the like. Additionally, the telecommunication device **210** can communicate with the earpiece module **201** to transfer commands, activate or deactivate sensors, communicate with the user, and the like.

[0067] The portable telecommunication device **210** sends/receives wireless information directly to/from a transmission system **211** for transmission to a database (such as personal database **312** and/or anonymous database **313**) for storage, analysis, and retrieval of data. The style of transmission system depends largely on the location of the database. For example, if the database is located in a local computer, the wireless information from the telecommunication device **210** can be sent directly to the local computer. This computer may be connected with the Internet, allowing access to the database from the web. However, the database is more typically located far away from the user and telecommunication module. In this case, the wireless signal from the telecommunication device **210** can be sent to a reception tower and routed through a base station. This information can then be sent to a database through the Internet. A variety of other transmission protocols can be applied for connec-

tion between the telecommunication device **210** and the databases **212**, **213**.

[0068] The personal and anonymous databases **212**, **213** represent databases that may or may not be located on the same computer. A key difference between these two databases is not the physical location of the database but rather the type of information available on each database. For example, the anonymous database **213**, containing health and environmental data from multiple indistinct earpiece users, can be public and accessible through the Internet by various users. In contrast, the personal database **212** contains health and environmental data that is personalized for each user, including personalized information such as name, birth date, address, and the like. Users can log-in to their personalized information in the personal database **212** through an interactive user interface **214** and compare this information with information from multiple users in the anonymous database **213** via a graphical user interface.

[0069] The user interface **214** can be a computer monitor, a cell phone monitor, a PDA monitor, a television, a projection monitor, a visual monitor on the earpiece module **201**, or any method of visual display. (Audible methods and audio-visual methods can also be used for the user interface **214**.) For example, the user may log-in to their personal database **212** through a computer user interface **214** and compare real-time personal health and environmental exposure data with that of other users on the network **200**. In some cases, the data from other users may be anonymous statistics. In some cases, one or more users may have agreements to view the data of one or more other users, and in other cases, users may agree to share mutual personalized data through the Internet.

[0070] A specific embodiment of a graphical user interface **300** is presented in Fig. 3. Fig. 3 shows an example of how a computer monitor may appear to a user logging-in to their personal database **212** and comparing their own personal data with that of anonymous users in the same network **200**. In this case, data from anonymous users is averaged into certain demographics; the choice of the demographics to be displayed can be selected by the user accessing the personalized database. In the graphical user interface **300** of Fig. 3, the user's personalized data, signified by a star, is compared with statistics from other users in an anonymous database **213**. This allows the user to compare his/her health and environment with that of others in selected demographics. Thus, this network **200** serves not only as a source of useful information from a medical standpoint, but also as a form of entertainment for curious users.

[0071] The network **200** can be used in medicine for a variety of important functions. As one example, a doctor can monitor the health of patients through each patient's personalized database **212**. If the earpiece module **201** contains a dosimeter, the doctor can even monitor the efficacy of prescribed medications, and the physiological response to medications, over time. This dosimetry ap-

proach is directly applicable to clinical studies of various treatments. For example, during a clinical trial, the earpiece module **201** can collect environmental data, drug dosimetry data, and physiological data from the earpiece user such that researchers can understand the etymology between drugs, genes, physiology, environment, and personal health.

[0072] Because of the high compliance of the earpiece module **100**, primarily due to the dual-modality as a health/environmental monitor and a personal communication/entertainment device, users are prone to wear this device throughout clinical trials, providing more valuable information for drug discovery and the pharmaceuticals market.

[0073] As a further example, the health and environmental network **200** can be used by dieticians to track the caloric intake, health, and physical activity of dieters. Similarly, the network **200** can be used by athletic trainers to monitor the diet, physical activity, health, and environment of athletes. In many cases professionals are not necessary, and the user can monitor his/her own diet, activity, athletic performance, etc. through the network without professionals, parents, guardians, or friends monitoring their personal statistics.

[0074] In a specific example of the network **200**, an earpiece user is a test subject in a clinical trial for a new treatment, such as a new drug, physical therapy, medical device, or the like. The earpiece user's health and environment are monitored in real-time, and this data is stored on the earpiece module **201**, the portable telecommunication device **210**, the personal database **212**, or the anonymous database **213**. By accessing the stored data, researchers managing the clinical trial can then compare the statistics from multiple users to make correlations between user environment, health, and the effectiveness of treatment.

[0075] It should be noted that algorithms for processing personal health and environmental data, diagnosing medical conditions, assessing health states, and the like do not need to be limited to the illustrated network **200**. Various algorithms can also be integrated into the earpiece module **201** or telecommunication device **210** according to embodiments of the present invention. A data storage component in at least one of these units allows processed signal data to be stored, analyzed, and manipulated to provide new knowledge to the user. This storage component can be any solid-state storage device, such as flash memory, random-access memory (RAM), magnetic storage, or the like. For example, the earpiece module **201** can be programmed to monitor certain habits, such as nail-biting. In this non-limiting example, the earpiece module physiological sensors **101** may monitor internal sounds, and an algorithm can be implemented to monitor signatures of nail-biting sounds in real-time. If the habit is identified by the algorithm, the earpiece communication module **107** may instantly warn the user that the habit is occurring. Alternatively, the algorithm may count the number of times a day the habit

occurred, monitor physiological and psychological stress indicators during each occurrence, log each time when the habit occurred, and store environmental data associated with the habit. This stored data can be accessed at a later time, allowing the user to determine what environmental factors cause the physiological or psychological stress associated with nail-biting. As this example shows, these algorithms can take advantage of both physiological sensor **101** data and environmental sensor **102** data.

[0076] A data storage component may include various algorithms, without limitation. In some embodiments, at least one algorithm is configured to focus processing resources on the extraction of physiological and/or environmental information from the various environmental and/or physiological sensors. Algorithms may be modified and/or uploaded wirelessly via a transmitter (e.g., receiver/transmitter **104** of the earpiece module **100**)

[0077] The biofeedback functionality of the telemetric earpiece module **100** can be applied towards various gaming applications. For example, one or more earpiece users can connect their earpiece modules **100** to one or more gaming devices wirelessly through the open architecture network provided by Bluetooth, ZigBee, or other such networks. This allows personal health and environmental information to be transferred wirelessly between the earpiece module **100** and a gaming device. As earpiece users play a game, various personal health and environmental feedback can be an active component of the game. In a non-limiting embodiment, two users playing a dancing game, such as Dance Dance Revolution, can monitor their vital signs while competing in a dancing competition. In some cases, users having healthier vital signs, showing improved athletic performance, will get extra points ("Vital Points"). In another specific example, this personal health and environmental information can be sent telemetrically to a gaming device to make entertaining predictions about one or more users. Namely, the gaming device may predict someone's life expectancy, love-life, future occupation, capacity for wealth, and the like. These predictions can be true predictions, purely entertaining predictions, or a mixture of both. Sensors measuring external stressors (such as outside noise, lighting conditions, ozone levels, etc.) and sensors measuring internal stresses (such as muscle tension, breathing rate, pulse rate, etc.) integrated into the earpiece module **100** can be used to facilitate predictions by the gaming device. For example, the information from the sensors can be recorded from one or more earpiece users during a series of questions or tasks, and the information can be sent telemetrically to a gaming device. An algorithm processed in the gaming device can then generate an entertaining assessment from the information. This game can be in the form of a video game, with a graphical user interface **214**, or it can be a game "in person" through an entertainer. Other games can involve competitions between multiple earpiece monitor users for health-related purposes, such as online dieting com-

petitions, fitness competitions, activity competitions, or the like. Combining the telemetric earpiece module **100** with gaming, according to embodiments of the present invention, provides seamless interaction between health and environmental monitoring and the game, through a comfortable telemetric module. Other sensor modules **201** located at other parts of the body can also be used.

[0078] An additional non-limiting embodiment of the biofeedback functionality of the earpiece module **201** can be monitoring psychological and physiological stress (such as monitoring stress indicators) during a poker game. These stress indicators can be breathing rate, muscle tension, neurological activity, brain wave intensity and activity, core body temperature, pulse rate, blood pressure, galvanometric response, and the like. Users may, for example, use the earpiece module **201** to record or display their psychological and physiological stress during a poker game in real-time. This information can be stored or displayed on a portable telecommunication device **210** or sent wirelessly to other parts of the network **200**. The user can use this biofeedback to adjust their psychological and physiological stress (or stress indicators) through force of will. This biofeedback process allows earpiece users to self-train themselves to project a certain "poker face," such as a stoic cold look, a calm cool look, or another preferred look. Additionally, external stressors, such as light intensity and color, external sounds, and ambient temperature, can be sensed, digitized, and transmitted by the earpiece module **100** to a telecommunication device (for storage), providing the user with important information about how the external environment may be affecting their stress response and, hence, poker game. In some games, the stress indicators may be displayed for outside viewers (who are not part of the poker game) as a form of entertainment when watching a group of poker players (each having earpiece modules **201**) in a casino, television, or through the Internet.

[0079] The biofeedback approach is also directly relevant to personal education as a learning tool. For example, monitoring the physiological and psychological response to learning can be used to help users understand if they are learning efficiently. For example, in the course of reading, the earpiece module **201** can monitor alertness through galvanometric, brainwave, or vital sign monitoring. The user can then use this information to understand what reading methods or materials are stimulating and which are not stimulating to the earpiece user.

[0080] In the broader sense, the discussed earpiece-enabled biofeedback method can be used as a self-training tool for improving performance in public speaking, athletic activity, teaching, and other personal and job-related activities.

[0081] The health and environmental network **200** enables a variety of additional business methods. For example, users can be charged a fee for downloading or viewing data from the personal and/or anonymous databases **212, 213**. Alternatively, users may be allowed free

access but be required to register online, providing personal information with no restrictions on use, for the right to view information from the databases. In turn, this personal information can be traded or sold by the database owner(s). This information can provide valuable marketing information for various companies and government interests. The health and environmental data from the databases **212, 213** can be of great value itself, and this data can be traded or sold to others, such as marketing groups, manufacturers, service providers, government organizations, and the like. The web-page or web-pages associated with the personal and anonymous databases **212, 213** may be subject to targeted advertising. For example, if a user shows a pattern of high blood pressure on a personal database **212**, a company may target blood pressure treatment advertisements on the user interface **214** (i.e. web page) while the user is logged-in to the personal database through the user interface **214**. For example, because various health and environmental statistics of earpiece users will be available on the database, this information can be used to provide a targeted advertising platform for various manufacturers. In this case, a database manager can sell information to others for targeted advertising linked to a user's personal statistics. In some cases, a database owner does not need to sell the statistics in order to sell the targeted advertising medium. As a specific example, a company can provide a database owner with statistics of interest for targeted advertising. For example, the company may request advertising a weight-loss drug to anonymous users having a poor diet, high caloric intake, and/or increasing weight. A database manager can then charge the company a fee for distributing these advertisements to the targeted users as they are logged-in to the database website(s). In this way, the users remain anonymous to the company. Because targeted advertisements can be such a lucrative market, income from these sources may eliminate the need for charging users a fee for logging-in to the databases **212, 213**.

[0082] The earpiece module **201** and earpiece module network **200** can enable a variety of research techniques. For example, a plurality of earpiece modules **100** worn by users can be used in marketing research to study the physiological and psychological response of test subjects to various marketing techniques. This technique solves a major problem in marketing research: deciphering objective responses in the midst of human subjectivity. This is because the physiological and psychological response of the earpiece user largely represents objective, unfiltered information. For example, users that are entertained by a pilot TV program would have difficulty hiding innate vital signs in response to the program. The data generated by the earpiece module **201** during market research can be transmitted through any component of the telemetric network **200** and used by marketing researchers to improve a product, service, or method.

[0083] Another business method provided by the network **200** is to charge users of the network for usage and

service (such as compilation service). For example, a clinical trial company may pay a fee for accessing the databases **212, 213** of their test subjects during medical research. In this case, these companies may buy earpiece modules **201** and pay for the service, or the earpiece modules **201** may be provided free to these companies, as the database service can provide a suitable income itself. Similarly, doctors may pay for this service to monitor patients, fire fighters and first responders may pay for this service to monitor personnel in hazardous environments, and athletic trainers may pay for this service to monitor athletes. Also, users can pay for the database service directly themselves. Because these databases **212, 213** are dynamic, updated regularly via the earpiece module **201** of each user, and changing with time for individual users and users en mass, these databases can maintain a long-term value. In other words, there may always be new information on the databases **212, 213**.

[0084] Another embodiment of the present invention involves methods of combining information from various earpiece health sensors into a meaningful real-time personal health and environmental exposure assessment in a recording device. The meaningful assessment is generated by algorithms that can be executed in the earpiece **201**, in the portable telecommunication device **210**, or through various other electronic devices and media within the network **200**. In one embodiment, raw or preprocessed data from the sensor module **201** is transmitted wirelessly to the telecommunication device **210**, and this device executes various algorithms to convert the raw sensor data (from one or more sensors) into a meaningful assessment for the user. In another embodiment these algorithms are executed within the earpiece **201** itself, without the need for processing in the telecommunication device **210**. The output from these algorithms can be viewed as charts, graphs, figures, photos, or other formats for the user to view and analyze. Preferably, these formats display various health factors over time with respect to a particular environment, with health factor intensity on the dependent axis and time or environmental factor intensity on the independent axis. However, virtually any relationship between the physiological data and environmental data can be processed by the algorithm, and these relationships can be quantitative, qualitative, or a combination of both.

[0085] One innovation involves applying the earpiece sensor module **201** towards a physical or mental health assessment method. An algorithm may combine data from health and environmental sensors **101, 102** towards generating a personal overall health assessment for the user, conditional to a particular environment. For example breathing rate, pulse rate, and core body temperature can be compared with ozone density in the air for generating an ozone-dependent personal health assessment. In another specific example of this innovation, information from the earpiece sensors **101, 102** can be used to monitor overall "mood" of a user in a particular

environment. More particularly, algorithmic processing and analyzing of data from sensors for core body temperature, heart rate, physical activity, and lighting condition can provide a personal assessment of overall mood conditional on external lighting conditions.

[0086] As previously mentioned, the ear is located at an ideal physiological position for monitoring a variety of health and environmental factors. Thus, the ear location can enable a variety of methodologies for physiological and environmental monitoring with an earpiece module **100**. In particular, because the ear canal is naturally designed for the transmission of audible sound, the ear canal facilitates methods for monitoring physiological processes by monitoring internal sounds. However, when extracting physiological information from the body, in a given external environment, environmental information is inevitably part of the extracted signal. This is because external energy, such as external audible noise, is entering the body. Thus, when listening to internal sounds, external sounds are also picked up. A methodology for cleaning up the signal such that it contains clearer information about physiology (as opposed to external environment) is provided by some embodiments of the present invention.

[0087] **Fig. 4** illustrates a physiological signal extraction methodology **400** for selectively monitoring internal physiological energies through an earpiece module **420** according to embodiments of the present invention. In the illustrated method, internal physiological energy is sensed by a sensor designated "Sensor-1" **401**. Sensor-1 generates an electrical signal in response to the physiological energy. One or more external sensors **402, 403, and 404** sense external energy from the environment in the vicinity of the earpiece module user and generate an electrical signal in response to the external energy. Though only one external sensor is needed, multiple sensors can be used to add sensing functionality, improve signal extraction, and/or increase the selectivity of sensing various energies. In **Fig. 4**, the external energy sensors **402, 403, 404** are shown collecting energy from different directions to emphasize that each sensor can be sensing the same type of energy but from a different direction, as this directional information can be useful for various assessments of the earpiece user. The energies described can be any physical energy, such as electrical, magnetic, electromagnetic, atomic, gravity, mechanical, acoustic, and the like. A signal processor **405** collects the electrical sensor responses and processes these signals into a signal that can be transmitted wirelessly through a transmitter/receiver **406** for communicating the information **407** telemetrically between the earpiece module **420** and a portable telecommunication device **210** (**Fig. 2**).

[0088] As with processor **103** of **Fig. 1**, the signal processor **405** of **Fig. 4** can be used to combine signals from the various sensors, compare similarities between the signals, and generate a new signal that contains cleaner physiological information than any of the original signals.

This can be done by converting the analog signals from the physiological sensors **401** and environmental sensors **402, 403, and 404** into digital signals and comparing the signals in, for example, a digital comparator to form a new signal that contains cleaner physiological information. (In some cases, an analog comparator technique can also be used if the signals are not digitized.) If these digitized signals are synchronized in time, a subtraction of environmental features from the signals can be realized by the comparator. Further, if algorithms are integrated into the signal processor **405**, comparisons can be made with respect to how external energy affects physiological energy in time.

[0089] An embodiment of the physiological signal extraction methodology **400** is presented in **Fig. 5** as an acoustical-cancellation physiological signal extraction methodology **500**. An earpiece module **517** (for example, with the functionality of earpiece module **100** of **Fig. 1**) is attached to the ear **506** with an ear attachment **505**. This earpiece module **517** is physically similar, if not identical, to the various examples shown in **Figs. 9-16**, discussed below. The earpiece module **517** contains at least one physiological acoustical sensor **501** pointed in the direction of the tympanic membrane **520** and at least one external acoustical sensor **502** pointing away from the body and towards the outside environment. To suppress the convolution of external and internal sounds, an acoustical buffer region **519** is placed between the two sensors **501, 502**. Environmental sounds **507** are sampled by the external acoustical sensor **502**, and physiological sounds **508** traveling through the ear canal **530** (and towards the earpiece **517**) are sampled by the physiological acoustical sensor **501**. Because the tympanic membrane and other body parts and tissues naturally vibrate in response to external sounds **507**, part of the physiological acoustical energy **508** is composed of environmental acoustical energy **507** as well as physiological sounds. These physiological sounds are referred to as "auscultatory" information. By comparing digitized signals from each acoustical sensor **501, 502**, the external energy **507** signatures can be at least partially removed from the auscultatory **508** signatures such that a new signal, containing cleaner physiological information, can be generated. For example, the sounds of external steps and human voices can be digitally removed or reduced from the final processed signal such that the final signal contains a cleaner representation of the internal sounds of pulse rate, breathing rate, swallowing rate, and other auscultatory information.

[0090] The acoustical sensors **501, 502** can contain any acoustical transducer, such as a microphone, piezoelectric crystal, vibrating membrane, magnetic recorder, and the like. Further, the acoustical sensors **501, 502** may contain a variety of layers for filtering sounds and promoting the directional extraction of sound. Additionally, various electrical filters, such as low-pass, highpass, band-pass, notch, and other filters, can be used to clean-up signals from each sensor **501, 502** to help remove

unwanted sounds or signatures. In some embodiments, the acoustical sensors **501, 502** are compact microphones, such as electric microphones or piezoelectric microphones, and the signals from these microphones are electrically filtered. The acoustical buffer region **519** can be any material that absorbs acoustical energy. In some embodiments, this material is soft, durable material, such as plastic, foam, polymer, or the like. In some embodiments, the acoustical buffer region **519** can be specially shaped to reflect or absorb sounds of certain frequencies through acoustical interference.

[0091] An example of how the auscultatory signal extraction technique **500** may be used is summarized in test data **800** set forth in **Fig. 8**. A small microphone was placed inside the ear of a test subject, and various sounds were recorded over time. In the test data **800**, the user was relaxing on a chair. The raw waveform **801** contains information from internal and external sounds. However, following digital filtering and noise cancellation, the final energy spectrum **802** and waveform **803** contain cleaner information about the test subject's pulse rate. In fact, the signature of each pulse can even be identified. In processing this signal, the noise reduction algorithm was selected by intelligently choosing a data segment dominated by external (environmental) acoustical energy, where physiological information was largely not present. Such intelligent algorithms can be integrated into a Bluetooth earpiece module for automatic auscultatory analysis for extracting physiological sounds from the body. Because the nature of external sounds and internal sounds are known by the placement of sensors **501, 502**, providing a basis for signal subtraction, the acoustical signal extraction innovation **500** can provide clean auscultatory data automatically in real-time.

[0092] Another embodiment of the signal extraction methodology **400** is presented in **Fig. 6**. The optical physiological signal extraction technique **600** is a method of extracting a variety of physiological information from the tympanic membrane **620** by locking-in to the vibrational frequency of the tympanic membrane **620**. In this method **600**, the earpiece module **614** contains at least one acoustical energy sensor **601** for measuring acoustical energy coming from the ear canal **630** and other neighboring organs and tissues. At least one optional external acoustical energy sensor **602** can be used for measuring environmental sounds in the vicinity of the earpiece user, as the combined signals from sensors **601, 602** can produce a cleaner signal for physiological monitoring. At least one optical emitter **624** is located in the earpiece for generating optical energy directed towards the tympanic membrane **620** through the ear canal **630**. This optical energy is absorbed, scattered, and reflected by the ear canal **630** and tympanic membrane **620**. In some cases, the optical energy induces fluorescence in the ear canal or tympanic membrane. In other cases, the optical energy experiences a change in polarization or other optical properties. In many cases, a change in more than one optical property (absorption, reflection, diffraction,

fluorescence, polarization, etc.) occurs. In any case, this resulting optical energy is referred to as the "secondary energy." The secondary energy is detected by at least one optical detector **625**, though more than one optical detector **625** may be utilized. As with the acoustical sensors **601**, **602**, the optical detector **625** converts incoming energy (in this case optical energy) into an electrical signal to be sent to a signal processor **405** (Fig. 4). The optical detector **625** may contain filters for selectively passing optical energy of physiological interest. A buffer region **619** is used to prevent external sound and light from convoluting the extraction of physiological information. In many cases, the optical energy generates a secondary response that is not optical in origin, such as a thermal response or biochemical response. In such case, at least one optical detector **625** may be replaced with at least one other type of sensor for sensing the non-optical secondary response.

[0093] Because the thin tympanic membrane **620** vibrates significantly in response to sound, whereas the other physiological ear features, such as the ear canal **630** and external ear **606** do not vibrate significantly, a method of extracting secondary optical signals scattered from the vibrating tympanic membrane **620** is provided. Acoustical information from the tympanic membrane vibrational response, collected by the acoustical sensor **601** (or a combination of sensors **601**, **602**), is processed by a signal processor **405**, and the secondary optical information from the tympanic membrane is collected by the optical detector(s) **625**. The signal processor compares digitized signals from these sensors in synchronized time, such that signals from the optical detector **625** containing frequency components characteristic of the tympanic membrane's vibrational response are selectively extracted to provide cleaner physiological information from the tympanic membrane. For example, the oxygen content of blood in the tympanic membrane can be monitored by the reflection of red and infrared light from the tympanic membrane, similar to pulse-oximetry. However, scattered optical energy from the ear canal may make it difficult to extract blood oxygen from the tympanic membrane, as the source of scattered light is unclear. The optical physiological signal extraction methodology **600** provides a means of locking-in to the tympanic membrane optical reflection signal through the tympanic membrane vibrational signal collected by the acoustical sensor **601** (or the combination of sensors **601**, **602**). The illustrated methodology **600** works because the thin tympanic membrane **620**, in response to sound, vibrates with substantially greater deflection than the ear canal, and thus primary and secondary light scattered from the tympanic membrane **620** is largely modulated by the frequency of sound reaching the tympanic membrane. This same technique **600** can be applied towards monitoring scattered optical energy from the vibrating bones of the ear, using electromagnetic wavelengths capable of passing through the tympanic membrane.

[0094] Another non-limiting embodiment of the optical physiological signal extraction methodology **600** of the present invention involves dosimetry. For example, the concentration of a drug and/or the performance of a drug can be monitored over time by characterizing the real-time fluorescence response of the drug, or intentional fluophores placed in the drug, via the tympanic membrane. In such case, the fluorescence response of the tympanic membrane can be extracted from optical noise through the illustrated methodology **600**. However, in this case the fluorescence response, as opposed to the reflectance response, is extracted from the tympanic membrane **620**.

[0095] In the optical physiological signal extraction methodology **600**, a variety of devices can be used for the optical source or optical sources **624**, such as a light-emitting diode (LED), a laser diode (LD), a miniature lamp (such as a miniature incandescent lamp, a miniature mercury lamp, or a miniature tungsten lamp), a light guide delivering light from an outside source (such as the sun or other light source), a multi-wavelength source, a microplasma source, an arc source, a combination of these sources, and the like. Special variants of light-emitting diodes, such as resonant-cavity light emitting diodes (RCLEDs), superluminescent LEDs (SLEDs), organic LEDs (OLEDs), and the like can also be applied.

[0096] In some embodiments of Fig. 6, coherent light can be used to monitor physiological processes. Monitoring vibrating membranes can be accomplished by using lasers and LDs such that coherent optical energy can directly interrogate the membrane and interference signals can be extracted. However, the signal extraction approach of Fig. 6 allows physiological signal extraction from the tympanic membrane with incoherent light-emitting diodes, which use less power, are more commercially available, and are more cost-effective than laser diodes. In fact, the scattered light from LEDs can be an advantage as scattered light may be necessary for reaching the tympanic membrane from outside of the ear canal. More specifically, earpiece module users may prefer to not have a tube stuck deep into the ear canal, and thus there may be no direct, unobstructed optical path to the tympanic membrane from outside of the ear.

[0097] It should be noted that in some cases the optical physiological signal extraction methodology **600** can be implemented without the optical emitter **624**. For example, the native IR blackbody radiation of the tympanic membrane, scattered in proportion to acoustical vibrational motion of the tympanic membrane, can be extracted using the approach **600** of Fig. 6 without the need of an optical emitter **624**. This may be accomplished by locking-in to the acoustically modulated blackbody IR radiation from the tympanic membrane, sensed by the photodetector **625**, through the signals received by the acoustic sensor **601** or **602**. The extracted blackbody radiation from the tympanic membrane can then be processed by a signal processor **103** to yield a resulting signal indicative of core body temperature. In this embodiment, the

photodetector **625** may be, for example, an IR sensor, an IR photodiode, an IR avalanche photodiode, an IR photoconductor, an I R-detecting field-effect transistor, a fast-response thermal sensor such as a pyroelectric sensor, or the like.

[0098] A specific pictorial example of the innovative optical physiological signal extraction methodology **600**, incorporating an LED-photodetector module **700**, is shown in **Fig. 7**. In the illustrated module **700**, at least one LED **724** generates at least one optical beam **713** directed towards the tympanic membrane **720** through the ear canal **730**. At least one photodetector **725** is positioned to receive scattered light **717** modulated by the tympanic membrane **720**. Inevitably, scattered light from the ear canal **730** not associated with the tympanic membrane will also reach the photodetector **725**. The optical physiological signal extraction methodology **600**, according to some embodiments of the present invention, can be used to reduce the impact of scattered light from the ear canal **730** and increase the impact of scattered light from the tympanic membrane **720**.

[0099] An optical reflector **727** may be used to steer the light from the LED **724** towards the tympanic membrane **720** and away from the photodetector **725**, preventing convolution and saturation by the optical source light **713**. The LED **724** and photodetector **725** are mounted onto a mounting board **726** in a discrete module, and this discrete module may be mounted to a larger board **710** for integration with circuitry in an earpiece sensor module **100**. Mounting of components to the board **726** and the board **726** to the larger board **710** can be accomplished, for example, by heating soldering bumps underneath the parts through standard electronic soldering techniques. The photodetector **724** can be any solid state device, such as a photodiode, an avalanche photodiode, a photoconductor, a photovoltaic, a photomultiplier, a FET photodetector, a photomultiplier tube, or the like. In some cases, the larger mounting board **710** may be connected to a detachable element, such as a cable, jack, fixture, or the like.

[0100] The active optical absorption region of the photodetector **725** may be covered by at least one optical filter for selectively passing light of interest. Light-guiding optics may also be integrated. Optical filters and light-guiding optics may also be applied to the LED source **724**. The LED **724** can be any optical wavelength from the deep-UV to the deep-IR. In some cases, the LED **724** can be replaced with a laser diode or other compact laser source, as long as electrical powering requirements are satisfied. In such case, the laser diode may need to be pulsed on a set interval to prevent a battery drain from continuous laser diode usage.

[0101] Referring back to **Fig. 4**, the directional external energy sensors **402**, **403**, and **404** can be useful for monitoring multiple sounds at once and deconvoluting interference from other sounds. For example, to monitor footsteps (pedometry), physical activity, and/or the impact on vital signs, signals from the sensors **401**, **402**, **403**,

and **404** can all be processed together, via the signal processor **405**, to generate meaningful information about each factor. More specifically, the sound of footsteps can be extracted from the final processed signal by deconvoluting directional sounds from above the earpiece user, through Sensor-3 **403**, and by deconvoluting directional sounds from the side of the earpiece user, through Sensor-2 **402**. In this manner, sounds from footsteps, coming primarily from below the user, measured through Sensor-4 **404**, and from inside the user, measured through Sensor-1 **401**, can be extracted from interfering sounds coming from other, non-relevant directions. According to some embodiments of the present invention, a person's vital signs can be extracted through the same methodology, but in this case, the sounds measured from at least one external energy sensor (Sensor-2, Sensor-3, or Sensor-4 **404**) are also deconvoluted from the final signal such that the final signal contains cleaner physiological information than that from Sensor-1 **401** alone. As a further example of the acoustical signal extraction methodology **500** of the present invention, the signal extraction technique can be used to extract acoustical signals associated with one or more of the following: yawning, swallowing, eating, masticating, sleeping, slurping, walking, running, physical activity, jogging, jumping, teeth grinding, jaw movements, a change in bite, changes in speech, changes in voice (volume, pitch, speed, inflammation of vocal chords, etc.), coughing, snoring, sneezing, laughing, eye muscle movements, crying, yelling, vocal stress, physical and psychological stress, stuttering, digestion, organ functioning, vital signs, pulse rate, breathing rate, cardiovascular performance, pulmonary performance, lung capacity, breathing volume, blood pressure, athletic performance, physiological or psychological stress indicators, the number of typed words on a keyboard or typing rate, personal habits (such as scratching, nail biting, saying "um," hair pulling, smoking, and the like), emotional states, muscle tension, and the like.

[0102] It should be clear that the general physiological signal extraction methodology **500** is also applicable in the reverse. Namely, the external environmental energy can be extracted from the convolution of external energy with physiological energy through the same basic process. In such case, the signal processor **405** subtracts signatures associated with internal physiological energy such that the new processed signal contains cleaner information about the environment. It should also be clear that any of the sensors **401**, **402**, **403**, and **404** can be composed of multiple sensors measuring multiple forms and expressions of various physical energies.

[0103] The earpiece modules described herein need not be embodied within headsets. For example, an earpiece module **100** according to embodiments of the present invention can be a hearing aid, an earplug, an entertaining speaker, the earpiece for an IPOD, Walkman, or other entertainment unit, a commercial headset for a phone operator, an earring, a gaming interface, or the like. The earpiece module **100** covers the broad realm

of earpieces, ear jewelry, and ear apparatuses used by persons for entertainment, hearing, or other purposes both inside and outside of health and environmental monitoring.

[0104] Moreover, two earpiece modules **100** may be utilized, one for each ear of a person, according to some embodiments of the present invention. Dual-ear analysis with two earpiece modules can be used, for example, to compare the core temperature of each tympanic membrane in order to gauge brain activity comparing each brain hemisphere. In another case, acoustical energy, including ultrasonic energy, can be passed from one earpiece module to the other, with acoustic absorption and reflection being used to gauge various physiological states. For example, this technique can be used to gauge hydration level in the head or brain by estimating the acoustical energy absorption rate and sound velocity through the head of the user.

[0105] A variety of earpiece styles, shapes, and architectures can be used for earpiece module **100** according to embodiments of the present invention. A non-limiting embodiment of the earpiece module is shown pictorially in **Fig. 9**. The illustrated earpiece **905** fits over the ear of a person and is held in place by an ear support **901** (also called the "earpiece attachment component" **105**). The illustrated earpiece module **905** also includes an earpiece body **902**, an earpiece fitting **908**, and an optional earlobe clip **904**. The earpiece may also contain an adjustable mouthpiece **1416** (**Fig. 14B**) and/or a pinna cover **1402** (**Figs. 14A-14B**) described below. The earpiece **905** connects with the ear canal of a person through an earpiece fitting **908** located on the backside **906** of the earpiece **905**. The earpiece fitting **908** transmits sound to the inner ear and eardrum. Health and environmental sensors are integrated primarily within or along the earpiece body **902**, including the earpiece backside **906**. However, an earlobe clip **904** can contain various health and environmental sensors as well. In some cases, health and environmental sensors can be integrated within or along the ear support **901**, the adjustable mouthpiece **1416**, the earpiece fitting **908**, or the pinna cover **1402**. Raw or processed data **903** from these sensors can be wirelessly transferred to a recording device or a portable telecommunication device **210** (**Fig. 2**). In some embodiments of the present invention, a recording device can be located within or about the earpiece **905** itself. In some cases, this recording device is flash memory or other digitized memory storage. The types of health and environmental factors which may be monitored have been previously described above for the earpiece module **100**.

[0106] It should be understood that the earpiece body **902** can be any shape and size suitable for supporting an earpiece fitting **1008**. In some cases, the earpiece body and earpiece fitting can be one and the same structure, such that the earpiece body-fitting is a small fitting inside the ear. In many cases, it is desirable to seal off or partially seal off the ear canal so as to prevent sounds

from entering or leaving the ear such that auscultatory signal can more easily be extracted from the ear canal through devices (such as microphones) in the earpiece body-fitting.

[0107] It should be noted that the invention is not limited to the exemplary earpiece **905** of **Fig. 9**. Other earpiece configurations are also capable of integrating health and environmental sensors for portable, noninvasive, real-time health monitoring according to embodiments of the present invention. For example, the earlobe clip **904** can be modified to reach other surfaces along or near a person's ear, head, neck, or face to accommodate electrical or optical sensing. Similarly, more than one clip may be integrated into the earpiece **905**. Sensors can be integrated into the earpiece-fitting **1008** as shown in the earpiece **1002** of **Fig. 10**. In such embodiments, the sensors may be integrated into a module **1009** in the earpiece-fitting **1008**. Environmental sensors are preferably located on the outside of the earpiece **1205** through a region on the earpiece frontside **1206** (as shown in **Fig. 12**). This allows access to air in the vicinity of the earpiece user. However, environmental sensors can be located anywhere along the earpiece module **905**.

[0108] **Fig. 12** illustrates details about the location of sensors in certain parts of an earpiece module **1205**, according to embodiments of the present invention. The ear support **1201** contains a pinna cover **1202** that may contain sensors for monitoring physiological and environmental factors. This structure is particularly useful for sensing methodologies which require energy to be transmitted through the thin layers of the pinna (the outer ear). Though any portion of the pinna can be covered and/or contacted, in some embodiments, the pinna cover **1202** overlaps at least a part of the helix or a part of the scapha of an ear. Likewise, an optical absorption detector, composed of an optical emitter and optical detector, can be integrated into the pinna cover **1202** for monitoring, for example, hydration, dosimetry, skin temperature, inductive galvanometry, conductive galvanometry, and the like.

[0109] Galvanometry, the measurement of electrical properties of the skin, can be measured inductively, through contactless electromagnetic induction without contacts, or conductively, with two, three, four, or more conductivity probes. Additionally, a 4-point conductivity probe technique, such as that used for measuring the conductivity of semiconductor wafers, can be applied. A variety of sensors can be integrated into the earpiece fitting **1208**. For example, a galvanometric device can be integrated into the surface **1209** of the earpiece fitting where the earpiece fitting touches the skin of the outer ear. Additionally, an inductive device, such as an inductive coil **1214**, can be integrated along the earpiece fitting body to measure movements of the tympanic membrane inductively. The inductive impedance can also be measured with the inductive coil **1214** or another inductive sensor, and this can be applied towards contactless galvanometry. The inductive coil **1214** can include one or more

coils arranged in any orientation, and a core material, such as an iron-containing material, may be used to improve the sensitivity of the response. In some cases, multiple coils may be used to facilitate the canceling of stray electromagnetic interference. Sensors can also be integrated into the end tip **1212** of the earpiece fitting **1208** to measure physiological properties deeper into the ear canal. For example, the optical module **700** of **Fig. 7** may be located in, at, or near the end tip region **1212** in a module **1213**. The sensors on the module **1213** in this region are carefully arranged so as not to prevent the transmission of sound (from the built-in communication module **107**) and to not be distorted during earpiece placement and removal. The end tip sensor module **1213** can contain several types of sensors for generating multiple types of energy and detecting multiple types of energy, and this module can be integrated into the speaker module (part of the communication module **107**) inside the earpiece fitting **1208** that is used for sound transmission to the user during telemetric conversations. In some cases, the speaker module can be used as a microphone to measure auscultatory signals from the body. This may be especially useful for measuring low frequency signals less than 1000 Hz. Employing the speaker as a microphone may require impedance matching to maximize the auscultatory signal extraction.

[0110] Alignment, placement, and arrangement of sensors, according to embodiments of the present invention, can be enabled or simplified by adopting a flexible circuitry configuration **1300**, such as that shown in **Fig. 13**. A flexible circuit board **1304** according to embodiments of the present invention can be made out of any stable flexible material, such as kapton, polymers, flexible ceramics, flexible glasses, rubber, and the like. A key requirement of the flexible material of the flexible circuit board **1304** is that it must be sufficiently electrically insulating and electrochemically inert. As with a standard rigid circuit board, a variety of sensors **1306** can be mounted on the flexible circuit board **1304**, and this board can be integrated into any part of the earpiece module **905** (**Fig. 9**). Flexible circuitry can be especially useful for odd-shaped components of the earpiece, such as the earpiece fitting **908**, ear support **901**, the earpiece clip **904**, the adjustable mouthpiece **1416**, and the pinna cover **1202/1402**. In some cases, flexible piezoelectric polymers, such as polyvinylidene fluoride may be useful for measuring body motion and auscultatory sounds from the body.

[0111] **Figs. 14A-14B** illustrate an embodiment **1400** of an earpiece module **1405** with an adjustable mouthpiece **1416** and a pinna cover **1402**. The earpiece **1400** contains a region where an adjustable mouthpiece **1416** can be swiveled, extended, pulled, extracted, flipped, or ejected towards the mouth. A microphone at the end of the mouthpiece **1416** can be used to improve personal communication through the earpiece **1400**. Sensors integrated into the mouthpiece **1416** can be used to monitor, for example, exhaled breath for respirometry and

inhalation/exhalation monitoring. Carbon dioxide, oxygen, nitrogen, water vapor, and other respired gases and vapors can be monitored, providing an overall assessment of health. Additionally, VOC's and other vapors exhaled by the breath can be monitored for diagnosing various disease states, such as diabetes, obesity, diet, metabolism, cancer, hepatic or renal health, organ functioning, alcoholism, halitosis, drug addiction, lung inflammation, voice analysis, voice distinction, and the like. The mouthpiece **1416** is in a retracted or stored position in **Fig. 14A** and is in an extended or operative position in **Fig. 14B**.

[0112] Another multifunctional earpiece module **1500**, according to embodiments of the present invention, is illustrated in **Fig. 15**. The illustrated earpiece module **1500** includes the embodiments described with respect to **Figs. 9** and **14A-14B**, such as a pinna cover **1502**, an ear support **1501**, a mouthpiece **1516**, an earpiece body **1505**, and the like. Additionally, the earpiece module **1500** may contain an extension **1511** with sensors for monitoring jaw motion, arterial blood flow near the neck, or other physiological and environmental factors near the jaw and neck region.

[0113] The person illustrated in **Fig. 15** is also wearing an earring monitor **1514** according to embodiments of the present invention. Because at least one portion of an earring may penetrate the skin, earring monitor **1514** may contain sensors and telemetric circuitry that provide access to various blood analytes through iontophoresis and electrochemical sensing that may not be easily accessible by the other portions of the earpiece module **1500**. Additionally, the earring may provide a good electrical contact for ECG or skin conductivity.

[0114] Embodiments of the present invention are not limited to earpiece modules. Other types of modules may be utilized that attach to other portions of a person's body. For example, a temple module **1600** having a similar design as the earpiece module design 100 can also be employed, as illustrated in **Fig. 16**. A temple module **1600** has the benefit of being close to physiological areas associated with stress, intracranial pressure, brain activity, and migraines. Additionally, a temple module can monitor physiological activity associated with the onset of a stroke, such as increased or decreased blood flow and/or oxygen flow to the brain.

[0115] **Fig. 19** illustrates a sensor module, according to embodiments of the present invention, integrated into a telemetric Bluetooth module. Though a Bluetooth module is used in this example, it should be understood that other telemetric modules can be used. Telemetric modules according to some embodiments of the present invention may operate in open architecture protocols, allowing multiple telemetric devices to communicate with each other. A Bluetooth module (including the sensor module) according to some embodiments of the present invention is integrated into a wearable earpiece module (*i.e.*, module **100** described above). The sensor module illustrated in **Fig. 19** contains one or more sensors, and

is mounted onto a Bluetooth module. In one embodiment, the sensor module is directly soldered onto the Bluetooth module. In another embodiment, the sensor module is elevated from the Bluetooth module with spacers, and a cable or electrical wires connect between the sensor module and the Bluetooth module. The module may be elevated in embodiments where the sensors need to be exposed to the environment. For example, the sensors may need to be exposed through the frontside region **1106** of an earpiece module **1105** (**Fig. 11**), and the Bluetooth module may fit too deeply into the earpiece module to provide sensor access to the external environment. In some cases, contact leads or vias may connect between the sensor module and an extended sensor or an additional sensor module. This allows the extended sensor or sensor module to be flexibly mounted anywhere inside, along, outside, or about the earpiece module **100**. Extended sensors can be especially useful for 4-point galvanometric monitoring of skin conductance, pulse oximetry, and volatile organic compound monitoring.

[0116] **Fig. 20** illustrates the power budget of a personal health and environmental monitor earpiece module, such as earpiece module **100**, incorporated into a Bluecore Bluetooth module, according to some embodiments of the present invention. As illustrated, the sensor components (*i.e.*, a body temperature sensor, 2-axis accelerometer, barometric pressure sensor, humidity sensor, ambient temperature sensor, and ambient lighting sensor) account for less than 16 mW of the total operating power of the Bluetooth-enabled earpiece module. The Bluecore Bluetooth operating power during transmission is approximately 65 mW. Combined together, the earpiece module, with all operating components, can operate with less than 100 mW of total operating power and provide a full day of sensing between recharges of typical batteries. Sensors other than these particular sensors, can also be included with minimal increase in operating power with respect to the Bluecore Bluetooth module. Pulsed sensing or "polling" of the sensors to read out data at certain intervals can further extend battery life.

[0117] Pulse oximetry is a standard noninvasive technique of estimating blood gas levels. Pulse oximeters typically employ 2 or more optical wavelengths to estimate the ratio of oxygenated to deoxygenated blood. Similarly, various types of hemoglobin, such as methemoglobin and carboxyhemoglobin can be differentiated by measuring and comparing the optical absorption at key red and near-infrared wavelengths. **Fig. 17** shows a transmittance pulse oximeter **1710** incorporated into an earpiece module (such as earpiece module **905** of **Fig. 9**) with the head **1707** of the earlobe clip containing an optical source **1708** and an optical detector **1709**. In general, the optical wavelengths from optical source **1708** pass through arteries or veins and are selectively absorbed by various blood metabolites, typically blood gas carriers such as hemoglobin. These metabolites can change color in response to the incorporation or removal of various blood gases, such as oxygen, carbon dioxide,

carbon monoxide, and other inhaled gases. The optical detector **1709** may contain optical filters to selectively detect light at key wavelengths relating to the presence or absence of the aforementioned optical absorption bands.

[0118] Though only two optical wavelengths are shown emanating from the source **1708**, several additional wavelengths can be incorporated and/or replace conventional wavelengths. For example, by adding additional visible and infrared wavelengths, myoglobin, methemoglobin, carboxyhemoglobin, bilirubin, SpCO₂, and blood urea nitrogen (BUN) can be estimated and/or monitored in real-time in addition to the conventional pulse oximetry SpO₂ measurement.

[0119] The optical source **1708** can include light-emitting diodes (LEDs), laser diodes (LDs), or other compact optical sources. In some cases, optical energies from the optical sources can be guided with waveguides, such as fiber optics. In some cases, ambient light, such as room light or solar radiation, may be sufficient for the optical source **1708**. In such case, waveguides may be used to couple ambient light towards the earlobe or other point of interest. Ambient light may be useful in that ambient light may represent a diffuse optical source that is largely independent of body position, such that motion artifacts associated with body motion may be lessened. The optical detectors **1709** can include photodiodes (PDs), avalanche photodiodes (APDs), photomultipliers, or other compact optical detectors.

[0120] **Fig. 18** shows a reflective pulse oximetry setup **1800** where reflected wavelengths **1816** are measured, as opposed to measuring transmitted wavelengths. In the illustrated embodiment, an optical source-detector assembly **1811** is integrated into an earlobe clip head **1807** to generate optical wavelengths **1815** and monitor the resulting reflected optical energy **1816**. The optical source-detector assembly **1811** contains one or more optical sources emitting one or more optical wavelengths, as well as one or more optical detectors detecting one or more optical wavelengths. The epidermis **1812**, dermis **1813**, and subcutaneous **1814** layers of skin tissue are shown in **Fig. 18** for reference.

[0121] The reflective pulse oximetry setup **1817** is also suitable for measuring fluorescence from various skin or blood analytes. For example, the optical sources and/or photodetectors may be selectively filtered to measure key fluorescence bands. A fluorescence approach can be applied to, for example, the real-time monitoring of cholesterol and lipids in the skin or blood. Though the optical techniques of **Fig. 17** and **Fig. 18** are shown primarily over the earlobe or skin, these techniques can be integrated with the optical physiological signal extraction technique **600**, described above with respect to **Fig. 6**, for measuring blood gas properties at or near the tympanic membrane.

[0122] Blood hydration can also be monitored optically, as water selectively absorbs optical wavelengths in the mid-IR and blue-UV ranges, whereas water can be more

transparent to the blue-green wavelengths. Thus, the same optical emitter/detector configuration used in earpiece pulse oximetry (**Figs. 17 and 18**) can be employed for hydration monitoring. However, mid-IR or blue optical emitters and detectors may be required. Additionally, monitoring the ratio of blue-green to other transmitted or reflected wavelengths may aid the real-time assessment of blood hydration levels. Blood hydration can also be monitored by measuring changes in capacitance, resistance, or inductance along the ear in response to varying water content in the skin tissues or blood. Similarly, hydration can be estimated by monitoring ions extracted via iontophoresis across the skin. Additionally, measuring the return velocity of reflected sound (including ultrasound) entering the head can be used to gauge hydration. These hydration sensors can be mounted anywhere within or along an earpiece. For example, with respect to the earpiece **905** of **Fig. 9**, hydration sensors can be mounted to a body **902** of the earpiece, the ear support **901**, the earpiece backside **906**, an earlobe clip, a pinna cover **1402**, an earpiece fitting **1208**, and the like. For monitoring hydration properties through the tympanic membrane, the earpiece tip **1212** of the earpiece fitting **1208** may be ideal for a sensor module (such as **1213**). It should be noted that other hydration sensors can also be incorporated into a module.

[0123] A variety of techniques can be used for monitoring blood metabolites via an earpiece module, such as earpiece module **100**. For example, glucose can be monitored via iontophoresis at the surface of the skin combined with enzyme detection. Blood urea nitrogen (BUN) can be monitored by monitoring UV fluorescence in blood (through the skin) or by monitoring visible and mid-IR light absorption using the pulse oximetry approach described above. Various ions such as sodium, potassium, magnesium, calcium, iron, copper, nickel, and other metal ions, can be monitored via selective electrodes in an earpiece module following iontophoresis through the skin. The optical physiological signal extraction approach **600** described above can be used to monitor glucose from the tympanic membrane by monitoring optical reflection and optical fluorescence from the tympanic membrane in response to IR and blue light.

[0124] Cardiopulmonary functioning can be evaluated by monitoring blood pressure, pulse, cardiac output, and blood gas levels via earpiece modules, and other monitoring apparatus in accordance with some embodiments of the present invention. Pulse rate and intensity can be monitored through pulse oximetry (described above) as well as by sensing an increase in oxygenated blood with time. Pulse rate and blood flow may also be assessed through impedance measurements via galvanometry near a blood vessel. Additionally, pulse rate and blood flow may be assessed through a fast-response thermal energy sensor, such as a pyroelectric sensor. Because moving blood may temporarily increase or decrease the localized temperature near a blood vessel, a pyroelectric sensor will generate an electrical signal that is propor-

tional to the total blood flow in time. Blood pressure can be monitored along the earlobe, for example. According to some embodiments of the present invention, a digital blood pressure meter is integrated into an earpiece module, such as earpiece **905** of **Fig. 9**. A compact clip, similar to **1707** of **Fig. 17**, containing actuators and sonic and pressure transducers, can be placed along the earlobe, and systolic and diastolic pressure can be measured by monitoring the pressure at which the well-known Korotkoff sound is first heard (systolic), then disappears (diastolic). This technique can also be used to monitor intracranial pressure and other internal pressures. Blood pressure may also be measured by comparing the time between pulses at different regions of the body. For example, sensors for monitoring pulse rate and blood volume can be located in front of the ear and behind the ear or at the earlobe, and the time between the detection of each pulse from each sensor, as well as the volume of blood passed, can be processed by the signal processor **103** into an indication of blood pressure. Electrodes within or about an earpiece can also be utilized to monitor blood gases diffused through the skin, giving an indication of blood gas metabolism. For example, a compact Severinghaus electrode can be incorporated within an earpiece module for the real-time monitoring of CO₂ levels in the blood, for example, through an earlobe connector, a sensor region of an earpiece fitting, or along or about an ear support. These Severinghaus-type electrodes can also be used to monitor other blood gases besides CO₂, such as oxygen and nitrogen.

[0125] Organ function monitoring includes monitoring, for example, the liver, kidneys, pancreas, skin, and other vital or important organs. Liver quality can be monitored noninvasively by monitoring optical absorption and reflection at various optical wavelengths. For example, optical reflection from white LEDs or selected visible-wavelength LEDs can be used to monitor bilirubin levels in the skin and blood, for a real-time assessment of liver health.

[0126] Monitoring neurological functioning can be accomplished via electrodes placed at the ear, near the ear, or along another surface of the body. When such electrodes are placed along the forehead, this process is described as electroencephalography, and the resulting data is called an electroencephalogram (EEG). These electrodes can be either integrated into an earpiece module or connected to an earpiece module, according to some embodiments of the present invention. For example, an earlobe clip (e.g., **904**, **Fig. 9**) can be modified to conform with EEG electrodes or other electrodes for measuring brain waves or neurological activity. For monitoring neurological functioning, a temple earpiece (e.g., **1600**, **Fig. 16**) may also be used. Electrodes may be positioned in a temple earpiece region near the temples of a user for direct contact with the skin. In some embodiments, direct contact is not necessary, and the neurological functioning can be monitored capacitively, inductively, electromagnetically, or a combination of these approaches. In some embodiments, brain waves may cou-

ple with low frequency acoustical sensors integrated into an earpiece module.

[0127] A person's body motion and head position can be monitored by integrating a motion sensor into an earpiece module (e.g., **905, Fig. 9**) Two such compact motion sensors include gyroscopes and accelerometers, typically mechanical or optical in origin. In some embodiments, an accelerometer may be composed of one or more microelectromechanical systems (MEMS) devices. In some embodiments, an accelerometer can measure acceleration or position in 2 or more axes. When the head is moved, a motion sensor detects the displaced motion from the origin. A head position monitor can be used to sense convulsions or seizures and relay this information wirelessly to a recording device. Similarly, head position monitoring may serve as a feedback mechanism for exercise and athletic training were head positioning with respect to the body is important. Additionally, the head position monitoring can be used to monitor when someone has fallen down or is not moving.

[0128] Body temperature, including core and skin temperature, can be monitored in real-time by integrating compact infrared sensors into an earpiece module, according to some embodiments of the present invention. Infrared sensors are generally composed of thermoelectric/pyroelectric materials or semiconductor devices, such as photodiodes or photoconductors. Thermistors, thermocouples, and other temperature-dependent transducers can also be incorporated for monitoring body temperature. These sensors can be very compact and thus can be integrated throughout an earpiece module. In some embodiments, these sensors may be mounted along the backside of an earpiece body, as illustrated in **Fig. 9**, where the earpiece connects with the ear canal. **Fig. 10** shows an embodiment of a compact sensor **1009**, such as a temperature sensor, incorporated into an earpiece fitting **1008** at the backside **906** of an earpiece body **902**. Because the earpiece fitting **1008** is in intimate or near-intimate contact with the ear canal, body temperature can be very accurately monitored. Signal extraction technique **600**, described above, may be utilized for monitoring core body temperature via the tympanic membrane.

[0129] In some embodiments of the present invention, a pedometer can be integrated into an earpiece module to measure the number of steps walked during a day. Pedometers that can be integrated into an earpiece module include, but are not limited to, mechanical pedometers (usually implementing a metallic ball or spring), microelectromechanical systems (MEMS) pedometers, inertial sensor pedometers, accelerometer-based pedometers, accelerometry, gyroscopic pedometers, and the like.

[0130] In some embodiments of the present invention, a pedometer for an earpiece module employs an acoustic sensor for monitoring the characteristic sounds of footsteps channeled along the ear canal. For example, an acoustic sensor can be integrated into an earpiece hous-

ing (e.g., **902, Fig. 9**) along the backside thereof (e.g., **906, Fig. 9**) and/or within an earpiece fitting thereof (e.g., **1008, Fig. 10**). The sounds generated from footsteps can be detected and analyzed with a signal processor (e.g., **405, Fig. 4**) using the approach described above (i.e., **500, Fig. 5**) to identify footstep sounds in the midst of convoluting physiological noise. In this embodiment, digitized electrical signals from footstep sounds from outside the body are compared with digitized electrical signals from footstep sounds traveling through the body (and ear canal), and only the spectral features associated with both types of digitized signals are amplified. This provides a new signal that contains cleaner information about footsteps. Better accuracy at discriminating a true step from other sounds or motions, such as driving in a car, can be determined by analyzing more than one sensor output through the methodology **400** described in **Fig. 4**.

[0131] Breathing characteristics can be monitored in a manner similar to that of acoustic pedometry (described above) in the auscultatory extraction methodology **500**. In some embodiments, an acoustic sensor in an earpiece module is used to sense sounds associated with breathing. Signal processing algorithms are then used to extract breathing sounds from other sounds and noise. This information is processed into a breathing monitor, capable of monitoring, for example, the intensity, volume, and speed of breathing. Another method of monitoring breathing is to employ pressure transducers into an earpiece module. Changes in pressure inside or near the ear associated with breathing can be measured directly and, through signal processing, translated into a breathing monitor. Similarly, optical reflection sensors can be used to monitor pressure in or near the ear by monitoring physical changes in the skin or tissues in response to breathing. For monitoring the physical changes of the tympanic membrane in response to breathing, and hence ascertaining breathing rate, the optical signal extraction approach **600** described above can be employed. At least one color sensor, or colormetric sensor, can be employed to monitor changes in color associated with breathing and other health factors. In the various embodiments described herein, the location of these acoustic sensors is in or near an earpiece fitting (e.g., **1008, Fig. 10**) and the sensor itself is preferably positioned in a manner similar to the sensor **1009** shown in **Fig. 10**.

[0132] It should be noted that some embodiments of the present invention incorporate health sensors that do not employ chemical or biological reagents for monitoring various health factors. This is because such sensors have traditionally required larger instrumentation (not suitable for portability) and/or disposable samplers (not acceptable to most end users). However, sensors employing chemical or biological reagents may be incorporated into earpiece modules, according to some embodiments of the present invention. For example, the diffusion of analyte through the skin can be monitored electrically or optically by selective binding to enzymes or

antibodies contained in the health sensors integrated into an earpiece module. In some cases, iontophoresis, agitation, heat, or osmosis may be required to pull ions from the skin or blood into the sensor region for monitoring health factors. In some cases, these analytes may be tagged with markers for electromagnetic, electrical, nuclear, or magnetic detection.

[0133] Caloric intake, physical activity, and metabolism can be monitored using a core temperature sensor, an accelerometer, a sound extraction methodology (e.g., **500, Fig. 5**) a pulse oximeter, a hydration sensor, and the like. These sensors can be used individually or in unison to assess overall caloric metabolism and physical activity for purposes such as diet monitoring, exercise monitoring, athletic training, or the like. For example, the sound extraction methodology **500** of **Fig. 5** can be used to extract sounds associated with swallowing, and this can give an indication of total food volume consumed. Additionally, a core temperature sensor, such as a thermopile, a pyroelectric sensor, a thermoelectric sensor, or a thermistor, or a tympanic membrane extraction technique (e.g., **600, Fig. 6**), can be used to assess metabolism. In one case, the core temperature is compared with the outdoor temperature, and an estimate of the heat loss from the body is made, which is related to metabolism.

[0134] Environmental temperature can be monitored, for example, by thermistor, thermocouple, diode junction drop reference, or the like. Electrical temperature measurement techniques are well known to those skilled in the art, and are of suitable size and power consumption that they can be integrated into a wireless earpiece module without significant impact on the size or functionality of the wireless earpiece module.

[0135] Environmental noise can be monitored, for example, by transducer, microphone, or the like. Monitoring of environmental noise preferably includes, but is not limited to, instantaneous intensity, spectral frequency, repetition frequency, peak intensity, commonly in units of decibels, and cumulative noise level exposures, commonly in units of decibel-hours. This environmental noise may or may not include noise generated by a person wearing an earpiece module. Sound made by a person wearing an earpiece module may be filtered out, for example, using analog or digital noise cancellation techniques, by directional microphone head shaping, or the like. The environmental noise sensor may or may not be the same sensor as that used for the intended purpose of wireless communication. In some embodiments, the environmental noise sensor is a separate sensor having broader audible detection range of noise level and frequency, at the possible sacrifice of audio quality.

[0136] Environmental smog includes VOC's, formaldehyde, alkenes, nitric oxide, PAH's, sulfur dioxide, carbon monoxide, olefins, aromatic compounds, xylene compounds, and the like. Monitoring of the aforementioned smog components can be performed using earpiece modules and other wearable apparatus, according

to embodiments of the present invention, in a variety of methods. All smog components may be monitored. Alternatively, single smog components or combinations of smog components may be monitored. Photoionization detectors (PID's) may be used to provide continuous monitoring and instantaneous readings. Other methods of detecting smog components according to embodiments of the present invention include, but are not limited to, electrocatalytic, photocatalytic, photoelectrocatalytic, colorimetric, spectroscopic or chemical reaction methods. Examples of monitoring techniques using the aforementioned methods may include, but are not limited to, IR laser absorption spectroscopy, difference frequency generation laser spectroscopy, porous silicon optical microcavities, surface plasmon resonance, absorptive polymers, absorptive dielectrics, and colorimetric sensors. For example, absorptive polymer capacitors inductors, or other absorptive polymer-based electronics can be incorporated into an earpiece module (e.g., **100, Fig. 1**) according to embodiments of the present invention. These polymers change size or electrical or optical properties in response to analyte(s) from the environment (such as those described above). The electrical signal from these absorptive polymer electronic sensors can be correlated with the type and intensity of environmental analyte. Other techniques or combinations of techniques may also be employed to monitor smog components. For example, a smog component may be monitored in addition to a reference, such as oxygen, nitrogen, hydrogen, or the like. Simultaneous monitoring of smog components with a reference analyte of known concentration allows for calibration of the estimated concentration of the smog component with respect to the reference analyte within the vicinity of an earpiece user.

[0137] In some embodiments of the present invention, environmental air particles can be monitored with a flow cell and a particle counter, particle sizer, particle identifier, or other particulate matter sensor incorporated as part of an earpiece module (e.g., **100, Fig. 1**) or externally attached to an earpiece module. Non-limiting examples of particles include oil, metal shavings, dust, smoke, ash, mold, or other biological contaminants such as pollen. In some embodiments of the present invention, a sensor for monitoring particle size and concentration is an optical particle counter. A light source is used (e.g., a laser or a laser diode), to illuminate a stream of air flow. However, a directional LED beam, generated by a resonant cavity LED (RCLED), a specially lensed LED, or an intense LED point source, can also be used for particle detection. The optical detector which is off-axis from the light beam measures the amount of light scattered from a single particle by refraction and diffraction. Both the size and the number of particles can be measured at the same time. The size of the monitored particle is estimated by the intensity of the scattered light. Additionally, particles can be detected by ionization detection, as with a commercial ionization smoke detector. In this case, a low-level nuclear radiation source, such as americium-241, may be

used to ionize particles in the air between two electrodes, and the total ionized charge is detected between the electrodes. As a further example, piezoelectric crystals and piezoelectric resonator devices can be used to monitor particles in that particles reaching the piezoelectric surface change the mass and hence frequency of electro-mechanical resonance, and this can be correlated with particle mass. If the resonators are coated with selective coatings, certain types of particles can attach preferentially to the resonator, facilitating the identification of certain types of particles in the air near a person wearing an earpiece module. In some embodiments, these resonators are solid state electrical devices, such as MEMS devices, thin film bulk acoustic resonators (FBARs), surface-acoustic wave (SAW) devices, or the like. These compact solid state components may be arrayed, each arrayed element having a different selective coating, for monitoring various types of particles.

[0138] In some embodiments of the present invention, environmental air pressure or barometric pressure can be monitored by a barometer. Non-limiting examples of barometric pressure measurement include hydrostatic columns using mercury, water, or the like, foil-based or semiconductor-based strain gauge, pressure transducers, or the like. In some embodiments of the present invention, semiconductor-based strain gauges are utilized. A strain gauge may utilize a piezoresistive material that gives an electrical response that is indicative of the amount of deflection or strain due to atmospheric pressure. Atmospheric pressure shows a diurnal cycle caused by global atmospheric tides. Environmental atmospheric pressure is of interest for prediction of weather and climate changes. Environmental pressure may also be used in conjunction with other sensing elements, such as temperature and humidity to calculate other environmental factors, such as dew point. Air pressure can also be measured by a compact MEMS device composed of a microscale diaphragm, where the diaphragm is displaced under differential pressure and this strain is monitored by the piezoelectric or piezoresistive effect.

[0139] In some embodiments of the present invention, environmental humidity, relative humidity, and dew point can be monitored by measuring capacitance, resistivity or thermal conductivity of materials exposed to the air, or by spectroscopy changes in the air itself. Resistive humidity sensors measure the change in electrical impedance of a hygroscopic medium such as a conductive polymer, salt, or treated substrate. Capacitive humidity sensors utilize incremental change in the dielectric constant of a dielectric, which is nearly directly proportional to the relative humidity of the surrounding environment. Thermal humidity sensors measure the absolute humidity by quantifying the difference between the thermal conductivity of dry air and that of air containing water vapor. Humidity data can be stored along with pressure monitor data, and a simple algorithm can be used to extrapolate the dew point. In some embodiments of the present invention, monitoring humidity is performed via spectroscopy.

The absorption of light by water molecules in air is well known to those skilled in the art. The amount of absorption at known wavelengths is indicative of the humidity or relative humidity. Humidity may be monitored with a spectroscopic method that is compatible with the smog monitoring spectroscopic method described above.

[0140] When environmental factors such as the aforementioned are monitored continuously in real-time, a user's total exposure level to an environmental factor can be recorded. When a representative volume of air a user has been exposed to is monitored or estimated, the volumetric concentration of the analytes can be calculated or estimated. In order to estimate the volume of air a person wearing the earpiece has been exposed to, a pedometer or accelerometer or air flow sensor can also be integrated into an earpiece module. Pedometers and accelerometers can be integrated into an earpiece module via mechanical sensors (usually implementing a mechanical-electrical switch), MEMS devices, and/or gyroscopic technologies. The technologies required for these types of pedometers and accelerators are well known to those skilled in the art. The incorporated pedometer or accelerometer (or more than one pedometer or accelerometer) is used to gage the distance a person has traveled, for use in the estimation of the volume of air to which a person has been exposed, and the subsequent estimate of the volumetric concentration of monitored analytes.

[0141] The health and environmental sensors utilized with earpiece modules and other wearable monitoring apparatus, according to embodiments of the present invention, can operate through a user-selectable switch on an earpiece module. However, health and environmental sensors can also be run automatically and independently of the person wearing the apparatus. In other embodiments, the person may control health and environmental monitoring through a device wirelessly coupled to an earpiece module, such as a portable telecommunication device (e.g., **210, Fig. 2**). For example, health and environmental sensors in or about an earpiece module can be controlled wirelessly through, for example, a cell phone, laptop, or personal digital assistant (PDA).

[0142] The earpiece module **100** may be configured such that user preferences can be "downloaded" wirelessly without requiring changes to the earpiece monitor hardware. For example, an earpiece concerned about a heart condition may wish to have the signal processor **103** focus on processing pulse signature, at the expense of ignoring other physiological or environmental parameters. The user may then use the portable telecommunication device **210** to download a specialized algorithm through the web. This may be accomplished through existing wireless infrastructure by text-messaging to a database containing the algorithm. The user will then have an earpiece module suited with analysis software specialized to the needs and desires of the user.

[0143] Health and environmental monitors, according to embodiments of the present invention, enable low-

cost, real-time personal health and environmental exposure assessment monitoring of various health factors. An individual's health and environmental exposure record can be provided throughout the day, week, month, or the like. Moreover, because the health and environmental sensors can be small and compact, the overall size of an apparatus, such as an earpiece, can remain lightweight and compact.

[0144] The foregoing is illustrative of the present invention and is not to be construed as limiting thereof. Although a few exemplary embodiments of this invention have been described, those skilled in the art will readily appreciate that many modifications are possible in the exemplary embodiments without materially departing from the teachings and advantages of this invention. Accordingly, all such modifications are intended to be included within the scope of this invention as defined in the claims. The invention is defined by the following claims, with equivalents of the claims to be included therein.

[0145] Some embodiments of the invention in its various aspects may be further understood by reference to the following numbered paragraphs:

1. A personal monitoring apparatus, comprising:

a housing configured to be attached to the body of a person;
 at least one physiological sensor supported by the housing, wherein each physiological sensor is configured to detect and/or measure physiological information from the person;
 at least one environmental sensor supported by the housing, wherein each environmental sensor is configured to detect and/or measure environmental conditions in a vicinity of the person;
 a signal processor supported by the housing and configured to receive and process signals produced by the physiological and environmental sensors; and
 a transmitter responsive to the signal processor that is configured to transmit physiological and environmental sensor signals as processed by the signal processor from the signal processor to a remote terminal.

2. The apparatus of paragraph 1, wherein the transmitter is configured to transmit signals from the signal processor to the remote terminal in real time.

3. The apparatus of paragraph 1, wherein the signal processor is configured to process signals produced by the physiological and environmental sensors into signals that can be heard and/or viewed by the person.

4. The apparatus of paragraph 1, wherein the signal processor is configured to selectively extract environmental effects from signals produced by a phys-

iological sensor.

5. The apparatus of paragraph 1, wherein the signal processor is configured to selectively extract physiological effects from signals produced by an environmental sensor.

6. The apparatus of paragraph 1, wherein a physiological sensor is oriented in a direction towards the person, wherein an environmental sensor is oriented in a direction away from the person, and wherein a buffer material is positioned between the physiological sensor and environmental sensors.

7. The apparatus of paragraph 6, wherein the buffer material is configured to selectively reflect and/or absorb energy emanating from the environment and/or the person.

8. The apparatus of paragraph 1, wherein the housing is configured to be attached to an ear of the person, wherein a physiological sensor is an acoustical sensor oriented in a direction towards a tympanic membrane of the ear and is configured to detect acoustical energy emanating from the tympanic membrane, wherein an environmental sensor is an acoustical sensor and is oriented in a direction away from the person, and wherein the processor is configured to utilize signals produced by the environmental sensor to extract environmental acoustical energy not emanating from the tympanic membrane from signals produced by the physiological sensor.

9. The apparatus of paragraph 8, further comprising an optical emitter supported by the housing that directs optical energy towards the tympanic membrane, and an optical detector supported by the housing that is configured to detect secondary optical energy emanating from the tympanic membrane.

10. The apparatus of paragraph 9, wherein the signal processor is configured to extract selected optical energy from the secondary optical energy emanating from the tympanic membrane.

11. The apparatus of paragraph 9, wherein the signal processor is configured to extract optical noise from the secondary optical energy emanating from the tympanic membrane.

12. The apparatus of paragraph 9, wherein the optical detector comprises a filter configured to pass secondary optical energy at selective wavelengths.

13. The apparatus of paragraph 8, further comprising an optical detector supported by the housing that is configured to detect acoustically modulated black-body IR radiation emanating from the tympanic

membrane.

14. The apparatus of paragraph 1, wherein the housing is configured to be attached to an ear of the person, and further comprising an optical emitter supported by the housing that directs optical energy towards the tympanic membrane, and wherein a physiological sensor comprises an optical detector configured to detect secondary optical energy emanating from the tympanic membrane.

15. The apparatus of paragraph 14, wherein the signal processor is configured to extract selected optical energy from the secondary optical energy emanating from the tympanic membrane.

16. The apparatus of paragraph 14, wherein the signal processor is configured to extract optical noise from the secondary optical energy emanating from the tympanic membrane.

17. The apparatus of paragraph 14, wherein the optical detector comprises a filter configured to pass secondary optical energy at selective wavelengths.

18. The apparatus of paragraph 1, wherein the housing is configured to be attached to an ear of the person, and wherein a physiological sensor comprises an optical detector that is configured to detect acoustically modulated blackbody IR radiation emanating from the tympanic membrane.

19. The apparatus of paragraph 1, wherein the signal processor utilizes one or more filters to process signals produced by the physiological and environmental sensors.

20. The apparatus of paragraph 1, further comprising a receiver configured to receive audio and/or video information from a remote terminal, and further comprising a communication module supported by the housing and that is configured to store and/or process and/or play audio and/or video information received from the remote terminal.

21. The apparatus of paragraph 1, further comprising a communication module supported by the housing and that is configured to alert the person when a physiological sensor detects certain physiological information from the person and/or when an environmental sensor detects certain environmental information from the vicinity of the person.

22. The apparatus of paragraph 21, wherein the communication module is configured to provide audible and/or visible alerts and/or physical alerts.

23. The apparatus of paragraph 21, wherein the

communication module is configured to audibly present vital sign information to the person.

24. The apparatus of paragraph 21, wherein the communication module is configured to store content generated by the person and/or by the at least one physiological and environmental sensors.

25. The apparatus of paragraph 1, wherein the transmitter is configured to transmit signals produced by the physiological and environmental sensors to a gaming device.

26. The apparatus of paragraph 1, further comprising an ear hook that extends from the housing and that is configured to attach the housing to an ear of a person.

27. The apparatus of paragraph 26, wherein the housing is configured to be positioned in adjacent contacting relationship with the temple of the person.

28. The apparatus of paragraph 26, further comprising a physiological sensor and/or an environmental sensor supported by the ear hook.

29. The apparatus of paragraph 26, wherein the hook comprises a pinna cover that is configured to contact a portion of the pinna of an ear, and wherein a physiological sensor and/or an environmental sensor is supported by the pinna cover.

30. The apparatus of paragraph 1, wherein the housing is an earring.

31. The apparatus of paragraph 1, further comprising an earring that is configured to be attached to an ear of a person, wherein the earring comprises an environmental sensor that is configured to detect and/or measure environmental conditions in a vicinity of the person, and wherein the signal processor is configured to receive and process signals produced by the earring environmental sensor.

32. The apparatus of paragraph 1, further comprising an earring that is configured to be attached to an ear of a person, wherein the earring comprises a physiological sensor that is configured to detect and/or measure physiological information from the person, and wherein the signal processor is configured to receive and process signals produced by the earring physiological sensor.

33. The apparatus of paragraph 1, further comprising an arm that extends from the housing and that supports one or more physiological sensors and/or environmental sensors.

34. The apparatus of paragraph 33, wherein the arm supports physiological sensors configured to detect and/or measure jaw motion and/or arterial blood flow near the neck of the person.

5

35. The apparatus of paragraph 1, wherein the housing is configured to be attached to an ear of the person, and further comprising an earpiece fitting configured to be inserted within the ear canal and having one or more physiological sensors supported thereby.

10

36. The apparatus of paragraph 1, further comprising a transmittance pulse oximeter and/or reflectance pulse oximeter supported by the housing.

15

37. The apparatus of paragraph 1, wherein the housing is configured to be attached to an ear of the person, and further comprising an earlobe clip extending from the housing, and wherein a transmittance pulse oximeter is supported by the earlobe clip.

20

38. The apparatus of paragraph 1, wherein the housing is configured to be attached to an ear of the person, and further comprising an earlobe clip extending from the housing, and wherein a reflectance pulse oximeter is supported by the earlobe clip.

25

39. The apparatus of paragraph 1, wherein the at least one physiological sensor comprises one or more sonic and pressure transducers supported by the housing that are configured to measure blood pressure of the person.

30

40. The apparatus of paragraph 1, wherein the at least one physiological sensor comprises electrodes configured to monitor neurological functions of the person.

35

41. The apparatus of paragraph 1, wherein the at least one physiological sensor comprises a motion sensor configured to detect body motion of the person.

40

42. The apparatus of paragraph 41, wherein the motion sensor comprises an accelerometer and/or gyroscope.

45

43. The apparatus of paragraph 1, wherein the at least one physiological sensor comprises a body temperature sensor.

50

44. The apparatus of paragraph 1, wherein the at least one environmental sensor comprises a colorimetric sensor that changes color in response to detecting one or more chemicals in the environment.

55

45. The apparatus of paragraph 1, wherein the at

least one environmental sensor comprises a pedometer.

46. The apparatus of paragraph 45, wherein the pedometer is an acoustic pedometer that detects sound generated by footsteps.

47. The apparatus of paragraph 1, wherein the at least one physiological sensor comprises an acoustic sensor that detects breathing.

48. The apparatus of paragraph 1, wherein the at least one physiological sensor is configured to measure caloric metabolism of the person.

49. The apparatus of paragraph 1, wherein the at least one physiological sensor comprises a body fat analyzer.

50. The apparatus of paragraph 1, wherein the at least one environmental sensor comprises an electromagnetic field (EMF) sensor that is configured to detect electromagnetic radiation spikes.

51. The apparatus of paragraph 1, further comprising an air sampling system supported by the housing that samples air in a vicinity of the person.

52. The apparatus of paragraph 1, wherein the at least one physiological sensor comprises an impedance plethysmograph.

53. The apparatus of paragraph 1, wherein the at least one environmental sensor comprises an ozone sensor or a carbon monoxide sensor.

54. The apparatus of paragraph 1, wherein the at least one physiological sensor comprises an ultraviolet (UV) light sensor.

55. The apparatus of paragraph 1, wherein the at least one physiological sensor is configured to detect drowsiness of the person, and further comprising an alarm configured to alert the person in response to the at least one physiological sensor detecting drowsiness.

56. The apparatus of paragraph 1, further comprising a recording device supported by the housing that is configured to record signals produced by the physiological and environmental sensors and/or signals processed by the signal processor.

57. The apparatus of paragraph 1, further comprising a user interface on the housing that provides user control over one or more of the physiological and/or environmental sensors.

58. The apparatus of paragraph 1, further comprising a remote device in wireless communication with the apparatus, wherein the remote device comprises a user interface that provides user control over one or more of the physiological and/or environmental sensors.

59. The apparatus of paragraph 1, further comprising a user interface that is configured to allow the person to store a time mark indicating a particular point in time.

60. The apparatus of paragraph 1, wherein the transmitter is configured to send a signal to the remote terminal when one or more of the physiological and/or environmental sensors are turned off.

61. The apparatus of paragraph 1, wherein the transmitter is configured to send a signal to the remote terminal when potentially erroneous data has been collected by one or more of the physiological and/or environmental sensors.

62. The apparatus of paragraph 1, wherein a physiological sensor is configured to detect damage to a portion of the body of the person.

63. The apparatus of paragraph 62, further comprising a communication module supported by the housing and that is configured to alert the person when a physiological sensor detects damage to a portion of the body of the person.

64. The apparatus of paragraph 1, wherein the housing comprises two portions, each configured to be attached to an ear of the person.

65. The apparatus of paragraph 1, wherein the at least one physiological sensor is configured to detect and/or measure one or more of the following types of physiological information: heart rate, pulse rate, breathing rate, blood flow, heartbeat signatures, cardio-pulmonary health, organ health, metabolism, electrolyte type and/or concentration, physical activity, caloric intake, caloric metabolism, physical and/or psychological stress levels and/or stress level indicators, drug dosage and/or dosimetry, physiological drug reactions, drug chemistry, biochemistry, position and/or balance, body strain, neurological functioning, brain activity, brain waves, blood pressure, cranial pressure, hydration level, auscultatory information, auscultatory signals associated with pregnancy, physiological response to infection, skin and/or core body temperature, eye muscle movement, blood volume, inhaled and/or exhaled breath volume, physical exertion, exhaled breath physical and/or chemical composition, the presence and/or identity and/or concentration of viruses and/or bac-

teria, foreign matter in the body, internal toxins, heavy metals in the body, anxiety, fertility, ovulation, sex hormones, psychological mood, sleep patterns, hunger and/or thirst, hormone type and/or concentration, cholesterol, lipids, blood panel, bone density, organ and/or body weight, reflex response, sexual arousal, mental and/or physical alertness, sleepiness, auscultatory information, response to external stimuli, swallowing volume, swallowing rate, sickness, voice characteristics, voice tone, voice pitch, voice volume, vital signs, head tilt, allergic reactions, inflammation response, autoimmune response, mutagenic response, DNA, proteins, protein levels in the blood, water content of the blood, pheromones, internal body sounds, digestive system functioning, cellular regeneration response, healing response, stem cell regeneration response

66. The apparatus of paragraph 1, wherein the at least one environmental sensor is configured to detect and/or measure one or more of the following types of environmental information: climate, humidity, temperature, pressure, barometric pressure, soot density, airborne particle density, airborne particle size, airborne particle shape, airborne particle identity, volatile organic chemicals (VOCs), hydrocarbons, polycyclic aromatic hydrocarbons (PAHs), carcinogens, toxins, optical radiation, X-rays, gamma rays, microwave radiation, terahertz radiation, ultraviolet radiation, infrared radiation, radio waves, atomic energy alpha particles, atomic energy beta-particles, gravity, light intensity, light frequency, light flicker, light phase, ozone, carbon monoxide, carbon dioxide, nitrous oxide, sulfides, airborne pollution, foreign material in the air, viruses, bacteria, signatures from chemical weapons, wind, air turbulence, sound and/or acoustical energy, ultrasonic energy, noise pollution, human voices, animal sounds, diseases expelled from others, exhaled breath and/or breath constituents of others, toxins from others, pheromones from others, industrial and/or transportation sounds, allergens, animal hair, pollen, exhaust from engines, vapors and/or fumes, fuel, signatures for mineral deposits and/or oil deposits, snow, rain, thermal energy, hot surfaces, hot gases, solar energy, hail, ice, vibrations, traffic, the number of people in a vicinity of the person, coughing and/or sneezing sounds from people in the vicinity of the person, loudness and/or pitch from those speaking in the vicinity of the person.

67. The apparatus of paragraph 1, wherein the housing is configured to be attached to an ear of a person, and further comprising a speaker, microphone, and transceiver supported by the housing, wherein the transceiver is electronically connected to the speaker and microphone and permits bidirectional wireless communications between the apparatus and a re-

remote terminal, and wherein the transceiver is electronically connected to the signal processor and is configured to transmit physiological and environmental sensor signals from the signal processor to the remote terminal.

5

68. The apparatus of paragraph 67, wherein the transceiver is a Bluetooth®, Wi-Fi, or ZigBee transceiver or is interoperable with multiple wireless communication protocols.

10

69. The apparatus of paragraph 67, further comprising an arm movably attached to the housing, wherein the microphone is supported by the arm, and wherein the arm is movable between a stored position and an extended, operative position.

15

70. The apparatus of paragraph 69, further comprising a physiological sensor and/or an environmental sensor supported by the arm.

20

71. The apparatus of paragraph 1, wherein the transmitter is configured to transmit signals from the signal processor to the remote terminal following a predetermined time interval.

25

72. The apparatus of paragraph 1, wherein the at least one physiological sensor and/or the at least one environmental sensor is configured to identify a person to whom the personal monitoring apparatus housing is attached.

30

73. The apparatus of paragraph 1, wherein the at least one physiological sensor and/or the at least one environmental sensor is configured to monitor physical aging rate.

35

74. The apparatus of paragraph 1, wherein the signal processor is configured to process information from the at least one physiological sensor and/or the at least one environmental sensor to assess aging rate.

40

75. The apparatus of paragraph 1, wherein the at least one environmental sensor is configured to assess aging rate, and wherein the at least one environmental sensor comprises a UV sensor or a pollution sensor.

45

76. The apparatus of paragraph 1, wherein the at least one physiological sensor is configured to assess aging rate, and wherein the at least one physiological sensor comprises a pulse rate sensor, a blood pressure sensor, an activity sensor, or a psychosocial stress sensor.

50

55

77. The apparatus of paragraph 1, wherein the at least one physiological and environmental sensors

are configured to monitor physical aging rate, wherein the at least one environmental sensor comprises a UV sensor or a pollution sensor, and wherein the at least one physiological sensor comprises a pulse rate sensor, a blood pressure sensor, an activity sensor, or a psychosocial stress sensor.

78. The apparatus of paragraph 1, wherein the apparatus is a hearing aid.

79. The apparatus of paragraph 1, wherein the at least one physiological sensor is configured to measure caloric consumption and/or calories burned by the person.

80. The apparatus of paragraph 1, further comprising memory supported by the housing, wherein the memory includes at least one algorithm, and wherein the signal processor is configured to process the at least one algorithm.

81. The apparatus of paragraph 80, wherein the at least one algorithm can be modified wirelessly via the transmitter.

82. The apparatus of paragraph 80, wherein the transmitter is configured to wirelessly upload an algorithm to the memory.

83. The apparatus of paragraph 80, wherein the at least one algorithm is configured to focus processing resources on at least one extraction of physiological or environmental information.

84. The apparatus of paragraph 1, further comprising a rechargeable power source that powers the at least one physiological sensor, the at least one environmental sensor, the signal processor, and the transmitter.

85. The apparatus of paragraph 1, wherein the at least one physiological sensor and/or the at least one environmental sensor is configured to be regenerated through a physical and/or chemical change.

86. The apparatus of paragraph 21, wherein the communication module communicates a treatment, therapy, or plan of action to the person upon detection of physiological or environmental concerns.

87. The apparatus of paragraph 1, further comprising an audible communicator supported by the housing that is configured to communicate therapeutic sounds to the person in response to physiological or psychosocial stress.

88. The apparatus of paragraph 1, further comprising a light source supported by the housing that is con-

figured to provide light therapy to the person in response to physiological or psychosocial stress.

89. The apparatus of paragraph 1, wherein the at least one physiological sensor includes multiple temperature sensors configured to measure core body temperature and skin temperature of the person.

90. The apparatus of paragraph 88, wherein the temperature sensors are configured to measure core body temperature from the tympanic membrane or ear canal and skin temperature from the skin of the ear canal or the skin of the outer ear.

91. A personal monitoring apparatus, comprising:

a wireless personal communicator configured to be attached to the ear of a person; and at least one physiological sensor associated with the wireless personal communicator that is configured to detect and/or measure physiological information from a person, wherein the wireless personal communicator is configured to transmit physiological sensor signals to a remote terminal.

92. A personal monitoring apparatus, comprising:

a wireless personal communicator configured to be attached to the ear of a person; and at least one environmental sensor associated with the wireless personal communicator that is configured to detect and/or measure environmental conditions in a vicinity of a person, wherein the wireless personal communicator is configured to transmit environmental sensor signals to a remote terminal.

Claims

1. A system for evaluating the cardiopulmonary functioning of a person, the system comprising:

a portable telecommunication device; and a sensor module configured to be worn by the person, the sensor module comprising:

at least one physiological sensor configured to sense one or more of the following types of physiological information generated by the person: pulse rate, blood flow, blood gas levels, body temperature, and blood pressure; at least one motion sensor configured to sense body motion of the person; a signal processor configured to process signals from the at least one physiological

sensor and the at least one motion sensor to generate an assessment of cardiopulmonary functioning of the person; and a transmitter in communication with the signal processor and configured to transmit signals from the signal processor to the portable telecommunication device; wherein the portable telecommunication device comprises a user interface configured to display signals from the signal processor.

2. The system of Claim 1, wherein the portable telecommunication device comprises at least one physiological sensor configured to sense one or more of the following types of physiological information generated by the person: pulse rate, blood flow, blood gas levels, body temperature, and blood pressure.

3. The system of Claim 1, wherein the sensor module comprises an earpiece module and wherein the at least one physiological sensor is configured to sense physiological information generated from an ear region of the person.

4. The system of Claim 1, wherein the at least one physiological sensor comprises a blood pressure sensor comprising an actuator and a pressure transducer.

5. The system of Claim 1, wherein the at least one physiological sensor comprises a blood pressure sensor comprising a pulse rate and/or blood volume sensor.

6. The system of Claim 1, further comprising a personal database and an anonymous database, wherein the personal database contains cardiopulmonary information for the person, and wherein the anonymous database contains cardiopulmonary information for multiple other persons, and wherein the anonymous database is publicly accessible through the Internet.

7. The system of Claim 1, wherein the sensor module comprises at least one environmental exposure sensor configured to sense environmental exposure information in the vicinity of an ear region of the person, and wherein the at least one signal processor is configured to remove environmental exposure information and/or motion information from signals generated by the at least one physiological sensor.

8. The system of Claim 7, further comprising a personal database and an anonymous database, wherein the personal database contains cardiopulmonary and environmental information for the person, and wherein the anonymous database contains cardiopulmonary and environmental information for multiple other persons, and wherein the anonymous database is publicly accessible through the Internet.

9. The system of Claim 6, wherein the portable telecommunication device comprises at least one signal processor configured to communicate with the personal and anonymous databases, to generate personalized cardiopulmonary statistics for the person from data in the personal database, and to generate cardiopulmonary statistics for multiple other persons from data in the anonymous database. 5
10. The system of Claim 9, wherein the portable telecommunication device at least one signal processor is configured to generate a comparison between cardiopulmonary functioning of the person and cardiopulmonary functioning of multiple other persons. 10
15
11. The system of Claim 1, wherein the at least one physiological sensor and/or the at least one motion sensor can be activated and deactivated via the portable telecommunication device user interface. 20
12. The system of Claim 1, further comprising:
at least one remote terminal;
wherein the at least one transmitter is configured to transmit at least one signal to the at least one a remote terminal; and 25
wherein the at least one signal processor is configured to focus processing resources on at least one type of physiological information in response to a specified preference through the at 30
least one remote terminal. 30
13. The system of Claim 12, wherein the specified preference is determined by the person or is determined automatically independently of the person. 35

40

45

50

55




FIG. 1




FIG. 2




FIG. 3




FIG. 4




FIG. 5




FIG. 6




FIG. 7




FIG. 8




FIG. 9




FIG. 10




FIG. 11






FIG. 12






FIG. 15




FIG. 16




FIG. 17




FIG. 18




FIG. 19




FIG. 20



EUROPEAN SEARCH REPORT

Application Number
EP 16 16 4775

5

10

15

20

25

30

35

40

45

50

55

DOCUMENTS CONSIDERED TO BE RELEVANT			
Category	Citation of document with indication, where appropriate, of relevant passages	Relevant to claim	CLASSIFICATION OF THE APPLICATION (IPC)
X	US 2001/049471 A1 (SUZUKI TAKUJI [JP] ET AL) 6 December 2001 (2001-12-06) * paragraphs [0052] - [0054], [0066] - [0070], [0115] - [0117], [0147] - [0148] *	1-13	INV. A61B5/00 A61B5/22
			TECHNICAL FIELDS SEARCHED (IPC)
			A61B
The present search report has been drawn up for all claims			
Place of search Munich		Date of completion of the search 1 September 2016	Examiner Martelli, Luca
<p>CATEGORY OF CITED DOCUMENTS</p> <p>X : particularly relevant if taken alone Y : particularly relevant if combined with another document of the same category A : technological background O : non-written disclosure P : intermediate document</p> <p>T : theory or principle underlying the invention E : earlier patent document, but published on, or after the filing date D : document cited in the application L : document cited for other reasons & : member of the same patent family, corresponding document</p>			

 1
EPO FORM 1503 03/02 (P04C01)

**ANNEX TO THE EUROPEAN SEARCH REPORT
ON EUROPEAN PATENT APPLICATION NO.**

EP 16 16 4775

5 This annex lists the patent family members relating to the patent documents cited in the above-mentioned European search report.
The members are as contained in the European Patent Office EDP file on
The European Patent Office is in no way liable for these particulars which are merely given for the purpose of information.

01-09-2016

Patent document cited in search report	Publication date	Patent family member(s)	Publication date
US 2001049471 A1	06-12-2001	JP 2001344352 A	14-12-2001
		US 2001049471 A1	06-12-2001
		US 2003194205 A1	16-10-2003
		US 2003195398 A1	16-10-2003
		US 2003204132 A1	30-10-2003

REFERENCES CITED IN THE DESCRIPTION

This list of references cited by the applicant is for the reader's convenience only. It does not form part of the European patent document. Even though great care has been taken in compiling the references, errors or omissions cannot be excluded and the EPO disclaims all liability in this regard.

Patent documents cited in the description

- US 90576107 P [0001]
- US 87612806 P [0001]
- US 87560606 P [0001]

专利名称(译)	用于健康和环境监测的遥测设备		
公开(公告)号	EP3081155A1	公开(公告)日	2016-10-19
申请号	EP2016164775	申请日	2007-12-07
[标]申请(专利权)人(译)	瓦倫賽爾公司		
申请(专利权)人(译)	VALENCELL INC.		
当前申请(专利权)人(译)	VALENCELL INC.		
[标]发明人	LEBOEUF STEVEN FRANCIS TUCKER JESSE BERKLEY AUMER MICHAEL EDWARD		
发明人	LEBOEUF, STEVEN FRANCIS TUCKER, JESSE BERKLEY AUMER, MICHAEL EDWARD		
IPC分类号	A61B5/00 A61B5/22		
CPC分类号	A61B5/0059 A61B5/0205 A61B5/021 A61B5/02438 A61B5/0816 A61B5/087 A61B5/11 A61B5/14546 A61B5/1455 A61B5/4064 A61B5/411 A61B5/415 A61B5/418 A61B5/6817 A61B5/6887 A61B2560 /0242 A61B5/222 G16H40/63 G16H40/67 G16H50/20 G16H50/30 A61B5/0002 A61B5/0013 A61B5 /0015 A61B5/0022 A61B5/0071 A61B5/0084 A61B5/01 A61B5/02055 A61B5/024 A61B5/02427 A61B5 /026 A61B5/029 A61B5/031 A61B5/04 A61B5/04001 A61B5/0476 A61B5/0496 A61B5/0533 A61B5 /1032 A61B5/1112 A61B5/1118 A61B5/112 A61B5/1126 A61B5/12 A61B5/14539 A61B5/14542 A61B5 /14551 A61B5/14552 A61B5/14556 A61B5/1477 A61B5/224 A61B5/4205 A61B5/4227 A61B5/4266 A61B5/4542 A61B5/4806 A61B5/4812 A61B5/4839 A61B5/4845 A61B5/4848 A61B5/486 A61B5/4866 A61B5/4872 A61B5/4875 A61B5/6803 A61B5/6815 A61B5/6816 A61B5/7203 A61B5/721 A61B5/7405 A61B5/742 A61B7/00 A61B7/04 A61M37/00 A61M2037/0007 A61N1/325 G01D11/00 G01N21/47 G01N21/59 G01N2201/021 G01N2201/0612 G01N2201/062		
优先权	60/875606 2006-12-19 US 60/876128 2006-12-21 US 60/905761 2007-03-08 US 11/811844 2007-06-12 US		
外部链接	Espacenet		

摘要(译)

提供了用于监测各种生理和环境因素的可穿戴设备。实时，无创的健康和环境监视器包括集成在小的低轮廓设备（例如听筒模块）内的多个紧凑传感器。收集生理和环境数据并将其无线传输到无线网络中，其中数据被存储和/或处理。

