



(12) **EUROPEAN PATENT APPLICATION**

(43) Date of publication:

10.07.2002 Bulletin 2002/28

(51) Int Cl.⁷: **A61B 5/16**, G06F 19/00

(21) Application number: **01204771.8**

(22) Date of filing: **10.12.2001**

(84) Designated Contracting States:

**AT BE CH CY DE DK ES FI FR GB GR IE IT LI LU
MC NL PT SE TR**

Designated Extension States:

AL LT LV MK RO SI

• **Patton, David L.**

Rochester, New York 14650-2201 (US)

• **Parks, Peter A.**

Rochester, New York 14650-2201 (US)

(30) Priority: **21.12.2000 US 746052**

(71) Applicant: **EASTMAN KODAK COMPANY**
Rochester, New York 14650 (US)

(74) Representative: **Parent, Yves et al**

KODAK INDUSTRIE,

Département Brevets,

CRT - Zone Industrielle

71102 Chalon-sur-Saône Cedex (FR)

(72) Inventors:

• **Blazey, Richard N.**

Rochester, New York 14650-2201 (US)

(54) **Reducing noise in a technique for diagnosing attention deficit hyperactivity disorder**

(57) A method of determining whether an individual has Attention Deficit Hyperactivity Disorder (ADHD) comprising: sampling the peripheral skin temperature of a human subject during a predetermined time interval when the subject is in an inactive state to provide a sampled peripheral skin temperature signal containing noise: modulating said sampled peripheral skin temper-

ature signal containing noise with a known reference signal to produce a modulated signal; inputting said modulated signal and said known reference signal to a lock-in amplifier to produce a sampled peripheral skin temperature signal free of said noise; and analyzing the sampled peripheral skin temperature signal for a pre-selected parameter to determine whether said predetermined parameter has a value indicative of ADHD.




FIG. 4a

100

Description

[0001] This invention relates in general to a technique for diagnosing and treating Attention Deficit Hyperactivity Disorder (ADHD) and more particularly to a technique for modifying a person's behavior using biofeedback and image modification.

[0002] ADHD is the most common neurobehavioral disorder of childhood as well as among the most prevalent health conditions affecting school-aged children. Between 4% and 12% of school age children (several millions) are affected. \$3 billion is spent annually on behalf of students with ADHD. Moreover, in the general population, 9.2% of males and 2.9% of females are found to have behavior consistent with ADHD. Upwards of 10 million adults may be affected.

[0003] ADHD is a difficult disorder to diagnose. The core symptoms of ADHD in children include inattention, hyperactivity, and impulsivity. ADHD children may experience significant functional problems, such as school difficulties, academic underachievement, poor relationships with family and peers, and low self-esteem. Adults with ADHD often have a history of losing jobs, impulsive actions, substance abuse, and broken marriages. ADHD often goes undiagnosed if not caught at an early age and affects many adults who may not be aware of the condition. ADHD has many look-alike causes (family situations, motivations) and co-morbid conditions (depression, anxiety, learning disabilities).

[0004] Diagnosis of ADHD involves a process of elimination using written and verbal tests. However, there is no one objective, independent valid test for ADHD. Various objective techniques have been proposed but have not yet attained acceptance. These include:

1. The eye problem called convergence insufficiency was found to be three times more common in children with ADHD than in other children by University of California, San Diego researchers.

2. Infrared tracking to measure difficult-to-detect movements of children during attention tests combined with functional MRI imaging of the brain were used by psychiatrists at McLean Hospital in Belmont, Massachusetts to diagnose ADHD in a small group of children (Nature Medicine, Vol. 6, No. 4, April 2000, Pages 470-473).

3. Techniques based on BEG biofeedback for the diagnoses and treatment of ADHD are described by Lubar (Biofeedback and Self-Regulation, Vol. 16, No. 3, 1991, Pages 201-225).

4. U.S. Patent 6,097,980, issued August 1, 2000, inventor Monastera et al, discloses a quantitative electroencephalographic process assessing ADHD.

5. U.S. Patent 5,913,310, issued June 22, 1999, inventor Brown, discloses a video game for the diagnosis and treatment of ADHD.

6. U.S. Patent 5,918,603, issued July 6, 1999, inventor Brown, discloses a video game for the diagnosis and treatment of ADHD.

7. U.S. Patent 5,940,801, issued August 17, 1999, inventor Brown, discloses a microprocessor such as a video game for the diagnosis and treatment of ADHD.

8. U.S. Patent 5,377,100, issued December 27, 1994, inventors Pope et al., discloses a method of using a video game coupled with brain wave detection to treat patients with ADHD.

9. Dr. Albert Rizzo of the Integrated Media Systems Center of the University of Southern California has used Virtual Reality techniques for the detection and treatment of ADHD.

10. U.S. Patent 6,053,739, inventors Stewart et al., discloses a method of using a visual display, colored visual word targets and colored visual response targets to administer an attention performance test.

11. U.S. Patent 5,377,100, issued December 27, 1994, inventors Patton et al., discloses a system and method of managing the psychological state of an individual using images.

[0005] There are several clinical biofeedback and physiology monitoring systems (e.g. Multi Trace, Bio Integrator). These systems are used by professional clinicians. A clinician monitors a patient's physiologic changes and accordingly uses different protocols. Some multimedia content (e.g. images, sound) can be used during the session to display a patient's pattern of physiologic reactivity and to help the patient in his/her task defined by the clinician. A good example is a session designed to help a patient to increase her/his hand temperature. A synthetic animation with the sun rising over the ocean can be used to show the patient's temperature. When the patient's temperature increases the sun is rising over the water horizon. When his/her temperature decreases the sun is moving behind the horizon. A clinician can help the patient with verbal instructions. Although skin temperature spectral characteristics have been shown to indicate stress-related changes of peripheral vasomotor activity in normal subjects (See: "Spontaneous skin temperature oscillations in normal human subjects", by: Shusterman et al., pp. 1173-1181), there has been no disclosure of the use of variations in skin-temperature response to assist in diagnosing ADHD. (See: Biofeedback and Self-Regulation, Vol. 20, No. 4, 1995).

[0006] PCT International Application WO 00/16687, published 30 March 2000, discloses a method and device for determining depth of anesthesia. A pattern of very low frequency oscillations in measured skin temperature is defined and analyzed. The frequency band width of a frequency domain analysis of the oscillatory pattern, or the correlation

between simultaneous oscillatory patterns measured at different physical locations, are used separately or fused to obtain an index of depth of anesthesia. There is no disclosure of the use of variations in skin temperature response to assist in diagnosing ADHD.

[0007] As discussed above, the primary method for diagnosing ADHD is the use of a bank of written and verbal assessment instruments designed to assess criteria established by American Medical Association (AMA) as described in the Diagnostic and Statistics manual - IV (DSM-IV) and administered by the school psychologist or other licensed practitioner. In some cases those individuals who meet DSM-IV criteria for ADHD diagnosis are prescribed a drug such as Ritalin. Behavioral observations of the patient while on Ritalin are conducted to assess the impact of prescribed medication.

[0008] U.S. Patent Application Serial No. 09/597,610, describes an apparatus and method of determining whether an individual has Attention Deficit Hyperactivity Disorder by analyzing physiologic reactivity patterns (lower average Mrange) when the subject is asked to sit quietly in a low stimulus environment for a short period of time.

[0009] There are many factors, which can contribute to a change in skin temperature variability besides ADHD. The largest potential source of error is stress due to causes other than the sensory deprivation included in the test. Other extraneous causes of reduced peripheral temperature variability (TV) might include disease states, room temperature variation, etc.

[0010] The primary feature of U.S. Patent Application Serial No. 09/597,610 is to diagnose subjects with ADHD. There is no attempt made to treat the condition once it has been diagnosed.

[0011] According to the present invention, there is provided a solution to the problems discussed above.

[0012] According to a feature of the present invention, there is provided a method of determining whether an individual has Attention Deficit Hyperactivity Disorder (ADHD) comprising: sampling the peripheral skin temperature of a human subject during a predetermined time interval when the subject is in an inactive state to provide a sampled peripheral skin temperature signal containing noise; modulating said sampled peripheral skin temperature signal containing noise with a known reference signal to produce a modulated signal; inputting said modulated signal and said known reference signal to a lock-in amplifier to produce a sampled peripheral skin temperature signal free of said noise; and analyzing the sampled peripheral skin temperature signal for a pre-selected parameter to determine whether said predetermined parameter has a value indicative of ADHD.

[0013] The invention has the following advantages.

1. A technique for diagnosing ADHD is provided which is simple, inexpensive, reliable and provides a level of accuracy improved over the prior art.
2. A technique for treating ADHD is provided.

[0014] Fig. 1 is a diagrammatic view illustrating an embodiment of the present invention.

[0015] Fig. 2 is a perspective view showing in greater detail the embodiment of Fig. 1.

[0016] Fig. 3 is a block diagram illustrating the function of a Lock-in Amplifier.

[0017] Figs. 4a and 4b are a block diagram of a system incorporating the present invention respectively in diagnosis and treatment modes.

[0018] Figs. 5, 6a and 6b are graphical views useful in explaining the present invention.

[0019] Fig. 7 is a diagrammatic view useful in explaining the present invention.

[0020] Fig. 8 is a diagrammatic view useful in explaining the present invention.

[0021] Figs. 9a and 9b are a block diagram of a system incorporating the present invention respectively in diagnosis and treatment modes.

[0022] Fig. 10 is a diagrammatic view useful in explaining the present invention.

[0023] Fig. 11 a is an image as it is displayed on a monitor in accordance with the present invention.

[0024] Fig. 11b is an image as it is displayed on a monitor in accordance with the present invention.

[0025] Fig. 11c is an image as it is displayed on a monitor in accordance with the present invention.

[0026] Fig. 11d is an image as it is displayed on a monitor in accordance with the present invention.

[0027] Fig. 11e is an image as it is displayed on a monitor in accordance with the present invention.

[0028] Fig. 11f is an image as it is displayed on a monitor in accordance with the present invention.

[0029] Fig. 12 is a graphical view useful in explaining the present invention.

[0030] According to the invention, it has been found that a signature of ADHD is hidden in fluctuation of the temperature of the skin as measured at the extremities such as at a fingertip. Biofeedback practitioners have long used measurement of hand temperature to help subjects manage their physiology by controlling blood flow to the extremities.

[0031] It is well known in the art that as person's stress level increases the blood vessels in the body contract as is evidenced by the fact a person's blood pressure increases as their level of stress increases. As the blood vessels in the body contract, blood flow is restricted. This is most evident in the extremities such as the fingers, because the blood vessels in the extremities are small and furthest from the heart. A direct result of decreased blood flow to the

blood vessels in the extremities is a decrease in the peripheral temperature of the extremities. Conversely, as a person's stress level decreases and one relax, is the blood vessels also relax and expand causing blood flow to increase. As the blood flow to the vessels in the extremities increases the peripheral temperature of the extremities increases. When a subject with ADHD is subjected to sensory deprivation such as being made to look at a blank screen or an obscured image, the lack of stimulation increases their level of anxiety and their stress level increases. As their stress level increases their blood vessels contract and the peripheral temperature of their extremities decreases. Conversely, as the screen or image they are viewing becomes less obscured or more interesting, thus decreasing their sensory deprivation, their level of anxiety and stress decreases, thus relaxing the blood vessels, increasing the blood flow and raising the temperature of their peripheral temperature of the extremities.

[0032] As shown in Fig. 1, a subject 10 is sitting on a chair 12 viewing a display device 14 wearing a set of earphones 30 connected via a wire not shown to a sound-generating device. In the embodiment shown the sound may be generated using an external CPU 44. The subject 10 is at rest in an inactive state viewing the display device 14. The subject's 10 skin temperature is measured via a finger temperature sensor module 22 mounted on the subject's finger on their left hand 15 connected via a wire 40 to an external CPU 44. In the embodiment shown the temperature sensor module 22 is connected to the external CPU 44, which can be used as the control and recording device portion.

[0033] Referring to Fig. 2, the analyzer 18 may be a stand-alone device having the temperature sensor module 22 as an integral part. The analyzer 18 has a display 26 (such as an OLED) or may be connected to an external display 14. The display 14 can be a monitor, television, palm pilot, or any other type of soft display or device with a soft display.

[0034] Referring again to Fig. 1, the subject's 10 skin temperature is measured by a temperature sensor module 23 mounted on the subject's right finger 16 connected via a wire to the external CPU 44. The subject's 10 temperature may be measured using either the finger tip 15 or the fingertip on the right hand 16 or fingertips on both hands. The external CPU 44 is connected to the display device 14. The earphone 30 may be used to block out ambient noise, to produce a white noise intended to reduce or eliminate the audio stimulus from the environment during the test or to obscure a sound related to an image shown on the display 14. The sound generated may be synchronized with what is appearing on the display 14.

[0035] Referring to Fig 2, there is shown an illustration of the analyzer 18 comprising temperature sensor modules 22 and 23, where the subject 10 inserts their left fingertip 15 in groove 17. The temperature sensor 22 can have an on/off switch 24, and a display 26. The temperature sensor module 22 can have an internal power supply, such as a battery 30, or an external low voltage power supply port 32 for an external low voltage power supply (not shown), such as used for a telephone. The temperature module 22 can be connected to the external CPU 44 via a cable 40 (such as an USB or RS 232 cable), or wireless-transmitting device such as a RF or IR link (not shown). A second temperature sensor module 23 can be connected to the external CPU 44 or the analyzer 18 via a cable 46. The second temperature sensor module 23 can be used to sample the skin temperature of the right hand. It should be understood that either temperature sensor module might be used on either hand. Analyzer 18 or CPU 44 applies the appropriate transforms to analyze the sampled temperatures and displays the results on the display 14 or 26. The results from the test can be stored in the CPU's memory (not shown) and can be transmitted via a transmission link such as the Internet to other locations.

[0036] Now referring to Fig. 3, there is provided a block diagram showing how a signal $S(t)$ 55 which is combined with a much larger noise $N(t)$ 60, can nevertheless be extracted by a lock-in amplifier if that signal is modulated with a known reference. An example is a light beam modulated by a chopper 65. The light is then incident on an electronic device 70 and an output electrical signal is collected. That electronic signal contains within it a signal synchronous with the light modulation, but at a level many orders of magnitude weaker than other components in the electronic device output (the Noise). When the output of the electronic device 70 and the reference signal 75 are fed to a lock-in amplifier 50, the signal can be extracted 80. Examples of lock-in amplifiers 50 are the Dual Phase Lock-in Amplifier Printed Circuit Model 5105 or the Dual Phase Wide Bandwidth DSP Lock-in Amplifier Model 7280 made by Perkin-Elmer Corp.

[0037] Referring now to Fig. 4a, analyzer module 18 includes analyzer circuit 100. The analyzer circuit 100 includes of a temperature sensor 102, lock-in amplifier 50, amplifier and signal conditioner 104, a switch 105 (shown in the diagnosis (D) position), analog to digital converter 106, digital signal analysis 108, display 110, battery 112, power switch 114 and power conversion and/or regulation 116. The circuit 100 can include a memory card slot 118 for receiving a memory card, which can provide system upgradability, and removable data export without compromising safety isolation.

[0038] Referring again to Fig. 1, the fingertip temperature is first recorded during an interval when the subject 10 has been asked to sit quietly for a given period of time, nominally about 10 minutes while viewing monitor 14. The monitor is either blank or the scene appearing on the monitor is obscured or distorted. The time period may be shorter or longer. The temperature data is sampled via a temperature sampling circuit 100 (shown in Fig. 4a) at a time interval Δt creating a list of N temperature samples, which are digitized by D/A 106 and which are stored. The N samples are divided into windows of m samples. The data from each window is then passed through a Fast Fourier Transform (FFT) algorithm in circuit 108 producing 2^{m-1} data points spaced equally in frequency space. The values are complex numbers having

form

$$\text{FFT}(f_n) = A(f_n) + B(f_n)i$$

where i is the $\sqrt{-1}$. The Phase $\Phi(f_n)$ can be found from the equation

$$\Phi(f_n) = \tan^{-1}\left(\frac{B(f_n)}{A(f_n)}\right) \quad (.00)$$

and the Magnitude $M(f_n)$ from

$$M(f_n) = \sqrt{B(f_n)^2 + A(f_n)^2} \quad (0.0)$$

[0039] Fig. 5 graphically illustrates the temperature signal during one window for a normal subject and a person diagnosed with ADHD.

[0040] Figs. 6a, 6b are graphically illustrates the magnitude transform for the data corresponding with a subject with ADHD and normal subject. The magnitude spectrum undergoes dramatic changes essentially changing from a hyperbolic curve to a flat response. These graphical illustrations as well as the following can be displayed on display 110 or on some other visual indication device.

[0041] The following is another feature of the present invention:

Raw Data

[0042] The raw data $T_{i,k}(t)$ is the temperature taken at a fingertip during the baseline period.

Windows

[0043] The data for each session were divided into a series of windows prior to performing the Fourier Transform operation. Call the window width w . For each window a FFT algorithm calculates the Fourier Transform $F(f)$. The Magnitude and Phase of this transform are defined as given above. The range of magnitude variation during a window is given below where $f_{\max}$ and $f_{\min}$ are the frequencies where the Magnitude is the greatest and the least respectively (note the dc component at frequency zero is excluded).

$$M_{\text{range}} = [M(f_{\max}) - M(f_{\min})]$$

Session Mean and Standard Deviation

[0044] The mean magnitude range for subject i during session k is found from equation 1.0. where m is the number of windows in the session.

$$\langle M_{i,k} \rangle = \frac{\sum_{j=1}^m [M(f_{\max})_j - M(f_{\min})_j]}{m} \quad (1.0)$$

[0045] And the corresponding standard deviation is:

$$< S_{i,k} > = \sqrt{\frac{\sum_{j=1}^m \{ [M(f_{\max})_j - M(f_{\min})_j] - < M_{i,k} > \}^2}{m-1}} \dots\dots\dots (1.1)$$

Determination Indicator

[0046] Positive diagnostic indicator is established based upon the chart of Fig. 7 by setting a threshold level (e.g., 3) for one of the parameters. Below that limit, the subject has a positive diagnostic indicator for ADHD. Above the limit, the subject has a negative diagnostic indicator for ADHD. This procedure can be improved by taking peripheral temperatures during different times of the day over a period of one or more days. Fig. 8 shows the results taken at different times of the day over a period of two days.

[0047] Referring to Fig. 9a, with switches 134 and 138 set to the diagnostic mode D, an image source 120 sends a digitized image to a video mixer 122 where it is mixed with varying amounts of obscuration from the video obscuration signal generator 124. The obscured image's signal is then fed to monitor 126. The amount of obscuration is synchronized to a reference supplied by signal generator 95, which may be any common waveform such as sine wave, square wave, ramp, triangle wave etc. Simultaneously, an audio source 128 may be fed through an audio obscuration generator 130 where it is mixed with audio noise or attenuated in proportion to and in synchronism with the reference signal. Both the visual and auditory stimuli supplied to the subject are modulated by the reference signal from the reference signal generator 95.

[0048] Referring now to Figs. 11a, b, c, d, e, and f, the technique previously described can be used to extract a subject's response to modulated sensory deprivation. By changing (Fig. 9a) the amount of obscuration of a stimulating image 200a, b, c, d, e, and f and/or an audio signal, modulation of the subject's physiology, as measured by variation of his/her peripheral temperature is created.

[0049] Referring to Fig. 4a, the peripheral temperature as measured by the temperature sensor 102, or a function derived from the subject's peripheral temperature, is fed from amplifier and signal conditioner 104 to the lock-in amplifier 50. The reference signal 75 is fed from the reference signal generator 95 (shown in Fig. 9a) to the lock-in amplifier 50 from point A. With switch 105 set in the diagnostic mode D the part of the subject's physiological response which is synchronous with the reference signal 75 is extracted by circuit 100, thus detecting a subject response which is directly correlated with the sensory deprivation signal and uncontaminated by other physiological responses.

[0050] Now referring to Fig. 10, the results are shown where a small modulation has been added to actual Mrange data for a subject. Fig. 10 shows the original signal (diamonds), the signal with the modulation added (triangles) and the signal that would be extracted (X's). Even though only a very small extracted signal (right hand axis) of the subject's temporal variation could be attributed to the sensory deprivation it is still detectable. In this example the reference-modulated component is a constant 0.3 units on a signal whose average value is about 5.0 or about 6%.

[0051] Referring to Fig. 1, an image 200a shown in Fig. 11a is displayed on the screen 14. As the subject concentrates on the image 200a the blood flow to the fingertip 15 and/or 16 increases causing the subject's peripheral temperature to change.

[0052] Referring to Fig. 4b, with switch 105 set in the treatment mode T the change in the subject's peripheral temperature is fed from the amplifier and signal conditioner 104 of circuit 100 at point B to the difference signal amplifier 132 shown in Fig. 9b. The change in the subject's peripheral temperature is also fed from the amplifier and signal conditioner 104 through the analog to digital converter 106, to the digital signal analysis 108 where the result is shown on display 110.

[0053] Now referring to Fig 9b, with switches 134 and 138 set in the treatment mode T the difference signal amplifier 132 compares signal B, which is a measure of the subjects peripheral temperature, to an adjustable reference voltage V_{ref} (131) which may be generated internally to 132 or supplied externally. The value of $R_{ef} V_{ref}$ is linearly related to the desired peripheral temperature. Suppose, for example, the subject's peripheral temperature was 72F. If the value V_{ref} was then set to correspond to a temperature of 90F, the difference amplifier output would then be proportional to the difference between these temperatures (18F).

[0054] The obscuration generators 124 and 130 would be so constructed that the amount of obscuration would be proportional to the size of the difference signal as shown in Fig. 12.

[0055] Now referring to Fig 12, the obscuration O shown on the ordinate is directly proportional to the difference voltage $\Delta = V - V_{ref}$ shown on the abscissa as indicated by the equation $O = k \cdot \Delta$

[0056] Thus, as the subject's peripheral temperature approached the reference temperature, the difference signal would also decrease causing a proportional decrease in the obscuration level. When the subject's temperature reached the reference setting of 90 degrees, the obscuration would vanish and the scene would be clearly visible and the audio clearly heard.

[0057] Referring to Figs. 9a and 9b, the switch 134 switches the input of the video obscuration signal generator 124 from the reference signal generator 95 to the difference signal amplifier 132. The image 136 can be the same as the image 200a shown in Fig. 11a. As previously described in Fig. 9a, the image 136 is modified in relationship to changes in the subject's 10 peripheral temperature. For example the image 200a can be a scene obscured by fog. As the subject concentrates on the image the fog begins to gradually disappear until the scene becomes clear as shown in Figs. 11a through 11f and images 200a through 200f respectively. This technique is used to train the subject 10 to modify his or her behavior. Likewise switch 138 can switch the input of the audio obscuration signal generator 130 from the reference signal generator 95 to the difference signal amplifier 132 causing the audio heard through the earphones 30 to be modified in relationship to the subject's 10 peripheral temperature. As in the case of the image the sound for example may be made louder or a distortion such as white noise may be reduced so the audio becomes clearer.

Claims

1. A method of determining whether an individual has Attention Deficit Hyperactivity Disorder (ADHD) comprising:
 - sampling the peripheral skin temperature of a human subject during a predetermined time interval when the subject is in an inactive state to provide a sampled peripheral skin temperature signal containing noise;
 - modulating said sampled peripheral skin temperature signal containing noise with a known reference signal to produce a modulated signal;
 - inputting said modulated signal and said known reference signal to a lock-in amplifier to produce a sampled peripheral skin temperature signal free of said noise; and
 - analyzing the sampled peripheral skin temperature signal for a pre-selected parameter to determine whether said predetermined parameter has a value indicative of ADHD.
2. The method of claim 1 wherein the skin temperature of at least one extremity of a human subject is sampled.
3. The method of claim 1 wherein the skin temperature of at least one finger of a human subject is sampled.






FIG. 1






FIG. 4a




FIG. 4b






FIG. 5






FIG. 7

DATE	TIME		
6/13/00	8:00 AM	2.8	0.65
6/13/00	12:00 NOON	2.7	0.67
6/13/00	5:00 PM	3.1	0.65
6/14/00	8:00 AM	2.9	0.65
6/14/00	12:00 NOON	2.8	0.66
6/14/00	5:00 PM	3.0	0.68

FIG. 8




FIG. 12




FIG. 9a




FIG. 9b




FIG. 10

200a



Fig. 11a

200b



Fig. 11b




Fig. 11c




Fig. 11d



Fig. 11e



Fig. 11f

专利名称(译)	减少用于诊断注意力缺陷多动障碍的技术中的噪音		
公开(公告)号	EP1221306A2	公开(公告)日	2002-07-10
申请号	EP2001204771	申请日	2001-12-10
[标]申请(专利权)人(译)	伊斯曼柯达公司		
申请(专利权)人(译)	伊士曼柯达公司		
当前申请(专利权)人(译)	麦克莱恩医院CORPORATION		
[标]发明人	BLAZEY RICHARD N PATTON DAVID L PARKS PETER A		
发明人	BLAZEY, RICHARD N. PATTON, DAVID L. PARKS, PETER A.		
IPC分类号	A61B5/01 A61B5/00 A61B5/16 A61B10/00 G06F19/00		
CPC分类号	A61B5/01 A61B5/168		
代理机构(译)	家长, YVES		
优先权	09/746052 2000-12-21 US		
其他公开文献	EP1221306A3		
外部链接	Espacenet		

摘要(译)

一种确定个体是否具有注意力缺陷多动障碍 (ADHD) 的方法, 包括 : 当受试者处于非活动状态时, 在预定时间间隔内对人类受试者的外周皮肤温度进行采样, 以提供包含噪声的采样的外周皮肤温度信号 : 用已知的参考信号调制包含噪声的所述采样的外围皮肤温度信号, 以产生调制信号;将所述调制信号和所述已知参考信号输入到锁定放大器, 以产生没有所述噪声的采样周边皮肤温度信号;分析采样的外周皮肤温度信号以获得预选参数, 以确定所述预定参数是否具有指示ADHD的值。

