



(11) **EP 1 523 934 B1**

(12) **EUROPEAN PATENT SPECIFICATION**

(45) Date of publication and mention of the grant of the patent:
08.12.2010 Bulletin 2010/49

(51) Int Cl.:
A61B 5/04 ^(2006.01) **A61B 5/05** ^(2006.01)
A61B 5/0205 ^(2006.01)

(21) Application number: **04104961.0**

(22) Date of filing: **11.10.2004**

(54) **Sensor arrangement**

Sensoranordnung

Agencement de capteur

(84) Designated Contracting States:
AT BE BG CH CY CZ DE DK EE ES FI FR GB GR HU IE IT LI LU MC NL PL PT RO SE SI SK TR

(30) Priority: **17.10.2003 US 688863**

(43) Date of publication of application:
20.04.2005 Bulletin 2005/16

(73) Proprietor: **GE Healthcare Finland Oy**
00510 Helsinki (FI)

(72) Inventors:
• **Hoskonen, Terho**
04430, Järvenpää (FI)
• **Kamppari, Lasse**
00280, Helsinki (FI)

- **Kymäläinen, Minna**
00250, Helsinki (FI)
- **Kall, Magnus**
02210, Espoo (FI)
- **Pesu, Leena**
00810 Helsinki (FI)

(74) Representative: **Valkeiskangas, Tapio Lassi**
Paavali
Kolster Oy Ab
Iso Roobertinkatu 23
P.O. Box 148
00121 Helsinki (FI)

(56) References cited:
WO-A-03/057030 **US-A- 4 595 013**
US-A- 4 595 018 **US-A1- 2003 009 096**
US-B1- 6 394 953

EP 1 523 934 B1

Note: Within nine months of the publication of the mention of the grant of the European patent in the European Patent Bulletin, any person may give notice to the European Patent Office of opposition to that patent, in accordance with the Implementing Regulations. Notice of opposition shall not be deemed to have been filed until the opposition fee has been paid. (Art. 99(1) European Patent Convention).

Description

[0001] The present invention relates to measuring anesthesia parameters from the head of a patient.

[0002] The parameters widely used in anesthesia are Entropy, which is derived from EEG and FEMG signals, and NMT and SpO₂. Currently the Entropy parameter is the only parameter, which is exclusively measured from the head of the patient. SpO₂ is sometimes measured from the ear if extremities cannot be used. So far NMT is mainly monitored from the hand. The parameters mentioned above can be described shortly as follows.

[0003] SpO₂ or pulse oximetry measures the oxygenation of the blood noninvasively. Blood absorbs red and infrared light differently depending on the oxygenation, ie. the colour of the blood varies with its oxygenation. By emitting red and infrared light through tissue and measuring the absorption of the two different wavelengths (red, about 660 nm and infrared, about 940 nm) the blood oxygenation can be calculated. There are two ways of doing this, transmission oximetry or reflectance oximetry. In transmission oximetry the emitter (two LEDs) and receiver (photodetector) are placed facing each other typically on each side of a finger, toe or earlobe. In reflectance oximetry the light is reflected below the tissue (eg. Chest, forehead or limbs) back to the same surface as the emitter. This way both the emitter and receiver can be placed on the same skin surface. These matters are described in "Chemical Biosensors", Peura, R.A., Webster J.G. (ed.), Medical Instrumentation: Application and Design. New York: Wiley, 1998, pp.469-472.

[0004] Neuro Muscular Transmission (NMT) is the transfer of an impulse between a nerve and a muscle in the neuromuscular junction. NMT can be blocked by neuromuscular blocking agents-drugs, which cause transient muscle paralysis and prevent the patient from moving and breathing spontaneously. Muscle relaxation is used during general anesthesia to enable endotracheal intubation and to provide the surgeon with optimal working conditions. The level of neuromuscular block is routinely measured by stimulating a peripheral nerve, usually in the hand, and by evaluating the muscle response. The muscle response can be measured either visually, by touching the hand, using a mechanical piezoelectric sensor or measuring the EMG response (ie. electrical muscle activity). These matters are described in "A Practical Guide to Monitoring: Neuromuscular Function", Sorin J. Brull et al, Datex-Ohmeda, 2002.

[0005] Neuromuscular transmission can also be measured from the face of the patient by stimulating the facial nerve and observing the response of the facial muscles. These matters are described in the article "Comparison of Neuromuscular Blockade in Upper Facial and Hypothenar Muscles", Paloheimo Markku P.J. et al, Journal of Clinical Monitoring, Vol 4, No 4, Little, Brown and Company, October 1988.

[0006] The entropy parameter is used to determine the level of hypnosis of an anesthetized patient. The Entropy

parameter is based on EEG and EMG signals measured from the forehead of the patient. The EEG signal represents brain activity whereas EMG represents muscle activity. Entropy could be described as the level of irregularity in the EEG and EMG signals. When the patient is awake, there is more brain and muscle activity whereas an anesthetized patient has less brain and muscle activity. These matters are described in the PCT-document WO 02/32305 A1.

[0007] As an examples of the prior art WO 03/057030 A, US 4 595 018 and US 2003/009096 can be mentioned.

[0008] A considerable problem in the operating rooms is the large amount of cables and hoses extending from the patient to a patient monitor and other devices connected to the patient. The amount of cables and hoses is due to the fact that traditionally separate sensors have been connected for example to a patient monitor using a cable of its own or a hose of its own. This principle leads to a considerable amount of cables and hoses, which may cause difficulties in the operating rooms particularly in extreme situations.

[0009] The object of the invention is to provide a sensor arrangement by which the problems of the prior art technique can be eliminated. This is obtained by the invention.

The basic idea of the invention is described in claim 1.

[0010] The sensor described herein provides a combination of the basic adequacy of anesthesia parameters into one compact sensor. The sensor gives a significant improvement to the current level of ergonomics and usability. When using the invention the user only has to attach one sensor instead of three separate sensors, Entropy, NMT and SpO₂. In addition all parameters are measured from the same area, the face of the patient. There is no need to attach any sensors on the hands of the patient, which would typically be the case for NMT and SpO₂. The user also only needs to connect one cable to the sensor since all parameters are connected through one connector. Depending on the sensor design, it might be necessary to use separate connectors for some of the parameters to meet patient leakage current and isolation requirements.

[0011] As told above a considerable problem in the operating rooms using the prior art technique is the large amount of cables and hoses extending from the patient to the patient monitor and other devices connected to the patient. The present invention eliminates or at least drastically reduces said problem by combining several parameters into one cable and thereby reducing the "cable clutter".

[0012] Currently the Entropy parameter is the only parameter, which is exclusively measured from the head of the patient. SpO₂ is sometimes measured from the ear if extremities cannot be used. So far NMT is mainly monitored from hand, but in fact the face offers a good alternative location for NMT measurement. Since Entropy can also be measured from the forehead of the patient, the head is a logical location for the combined sensor. The Entropy electrodes are located on the forehead and tem-

ple area.

[0013] Electrodes are also used for NMT stimulus and can also be used for NMT measurement (muscle response is measured by measuring the EMG response). To reduce the number of electrodes needed, some of the Entropy and NMT electrodes can be shared between the two parameters. The measurements can then be multiplexed to stimulate and measure potentials for the two different parameters. NMT can be measured either using a mechanical sensor sensing physical muscle movement or using electrodes measuring muscle activity electrically (EMG). Using a mechanical sensor requires a separate piezo-electric sensor over the muscle where the response is to be measured.

[0014] SpO₂ is typically measured from the extremities or from the ear. It is, however, possible to measure SpO₂ anywhere on the body where you can place an optical emitter and detector in such a fashion that the emitted light passes through oxygenated tissue. On the head of the patient such areas are the ears and the nose, and if the light is reflected off the skull, the forehead can be used as well.

[0015] All parameters in the combined adequacy of anesthesia sensor can be reliably recorded from the head of the patient enabling a compact sensor. It is also possible to evaluate the amount of pain experienced by the patient (analgesia) by monitoring the heartrate and the amplitude of the plethysmographic curve (signal obtained from the SpO₂ sensor). The analgesia parameter could also be derived from the SpO₂ signal without additional sensors.

[0016] In the following the invention will be described in greater detail by means of the examples shown in the drawings enclosed. The Figures 1 - 11 describe eleven different embodiments of the invention.

[0017] The first embodiment of the invention is described in Figure 1. The sensor arrangement shown in Figure 1 comprises an array of electrodes for measuring EEG, EMG and NMT. The electrodes are located on the face of the patient. Electrode 1 is located just posterior to the lower part of the pinna and electrode 2 is located just anterior to the tragus. Electrode 3 is located below the eye. Electrodes 4 and 5 have two alternative locations, a and b. If location b is used, electrode 4a is also used. Electrode 4a is located on the temple area between the corner of the eye and the hairline. Electrode 5a is located above the eye at the same level as electrode 6, which is located between the eyebrows of the patient at the center of the forehead, approximately 4 cm above the nose. Electrode 4b is located at either location F3 or F4 (left or right side) of the International 10-20 system. The International 10-20 system is described in "Monitoring in Anesthesia and Critical Care Medicine", Casey D. Blitt, Churchill Livingstone, 1985. Electrode 5b is located between electrode 4b and electrode 6.

[0018] It is very advantageous to place electrode 5b essentially in the middle of electrodes 4b and 6 so that the distances between electrode 5b and electrode 4b,

and electrode 5b and electrode 6 are essentially the same. In addition to these electrodes, a reflective optical sensor 7 for monitoring substances in tissues, e.g. SpO₂ is placed on the face of the patient, anywhere where suitable for the structure of the sensor, eg. but not limited to on the forehead above electrode 6. The optical sensor 7 comprises an emitter and a receiver located close to each other. The emitter comprises LEDs of different wavelengths and the receiver comprises a photodetector.

[0019] Electrodes 1 and 2 are the NMT stimulus electrodes, stimulating the facial nerve. Electrodes 4a and 6 are the NMT recording electrodes and electrode 5 (a or b) is the NMT grounding electrode. Electrodes 4 (a or b) and 6 also record EEG and EMG signals used e.g. to derive the Entropy parameter. Electrode 5 (a or b) is the reference electrode for the EEG and EMG measurement. The EEG and EMG measurement can be enhanced using electrode 3 e.g. but not limited to record eye movements. The EEG and EMG measurement can be done with or without electrode 3. The optical sensor measures e.g. the plethysmographic curve, the heartrate and the blood oxygen saturation.

[0020] The embodiment shown in Figure 1 comprises also a base element 9. The base element 9 can be made of any appropriate flexible material, for example of plastic material. The electrodes and sensors described above can be attached to the base element by using any appropriate method known per se.

[0021] All electrodes and sensors described above are connected to a single connector 10 attached to the base element 9 as shown in Figure 1. Instead of a single connector 10 a series of connectors may be used as told before.

[0022] The second embodiment is described in Figure 2. The sensor arrangement shown in Figure 2 comprises an array of electrodes for measuring EEG, EMG and NMT. The electrodes are located on the face of the patient. Electrode 1 is located just posterior to the lower part of the pinna and electrode 2 is located just anterior to the tragus. Electrode 3 is located below the eye. Electrodes 4 and 5 have two alternative locations, a and b. If location b is used, electrode 4a is also used. Electrode 4a is located on the temple area between the corner of the eye and the hairline. Electrode 5a is located above the eye at the same level as electrode 6, which is located between the eyebrows of the patient at the center of the forehead, approximately 4 cm above the nose. Electrode 4b is located at either location F3 or F4 (left or right side) of the International 10-20 system. Electrode 5b is located between electrode 4b and electrode 6.

[0023] It is very advantageous to place electrode 5b essentially in the middle of electrodes 4b and 6 so that the distances between electrode 5b and electrode 4b, and electrode 5b and electrode 6 are essentially the same. In addition to these electrodes, a transmission optical sensor 7 for monitoring substances in tissues, e.g. SpO₂ is placed on the nose of the patient. The optical sensor 7 comprises an emitter and a receiver located on

opposite sides of the nose. The emitter comprises LEDs of different wavelengths and the receiver comprises of a photodetector.

[0024] Electrodes 1 and 2 are the NMT stimulus electrodes, stimulating the facial nerve. Electrodes 4a and 6 are the NMT recording electrodes and electrode 5 (a or b) is the NMT grounding electrode. Electrodes 4 (a or b) and 6 also record EEG and EMG signals used e.g. to derive the Entropy parameter. Electrode 5 (a or b) is the reference electrode for the EEG and EMG measurement. The EEG and EMG measurement can be enhanced using electrode 3 e.g. but not limited to record eye movements. The EEG and EMG measurement can be done with or without electrode 3. The optical sensor measures e.g. plethysmographic curve, the heartrate and the blood oxygen saturation.

[0025] The embodiment shown in Figure 2 comprises also a base element 9. The base element 9 can be made of any appropriate flexible material, for example of plastic material. The electrodes and sensors described above can be attached to the base element by using any appropriate method known per se.

[0026] All electrodes and sensors described above are connected to a single connector 10 attached to the base element 9 as shown in Figure 2. Instead of a single connector 10 a series of connectors may be used as told before.

[0027] The third embodiment is described in Figure 3. The sensor arrangement shown in Figure 3 comprises an array of electrodes for measuring EEG, EMG and NMT. The electrodes are located on the face of the patient. Electrode 1 is located just posterior to the lower part of the pinna and electrode 2 is located just anterior to the tragus. Electrode 3 is located below the eye. Electrodes 4 and 5 have two alternative locations, a and b. If location b is used, electrode 4a is also used. Electrode 4a is located on the temple area between the corner of the eye and the hairline. Electrode 5a is located above the eye at the same level as electrode 6, which is located between the eyebrows of the patient at the center of the forehead, approximately 4 cm above the nose. Electrode 4b is located at either location F3 or F4 (left or right side) of the International 10-20 system. Electrode 5b is located between electrode 4b and electrode 6.

[0028] It is very advantageous to place electrode 5b essentially in the middle of electrodes 4b and 6 so that the distances between electrode 5b and electrode 4b, and electrode 5b and electrode 6 are essentially the same. In addition to these electrodes, a transmission optical sensor 7 for monitoring substances in tissues, e.g. SpO₂ is placed on the ear of the patient. The optical sensor 7 comprises an emitter and a receiver located on opposite sides of the auricle. The emitter comprises LEDs of different wavelengths and the receiver comprises a photodetector.

[0029] Electrodes 1 and 2 are the NMT stimulus electrodes, stimulating the facial nerve. Electrodes 4a and 6 are the NMT recording electrodes and electrode 5 (a or

b) is the NMT grounding electrode. Electrodes 4 (a or b) and 6 also record EEG and EMG signals used e.g. to derive the Entropy parameter. Electrode 5 (a or b) is the reference electrode for the EEG and EMG measurement.

5 The EEG and EMG measurement can be enhanced using electrode 3 e.g. but not limited to record eye movements. The EEG and EMG measurement can be done with or without electrode 3. The optical sensor measures e.g. the plethysmographic curve, the heartrate and the blood oxygen saturation.

10 **[0030]** The embodiment shown in Figure 3 comprises also a base element 9. The base element 9 can be made of any appropriate flexible material, for example of plastic material. The base element 9 can be formed and designed freely according to the existing need as shown in the Figures, ie. for example the base element 9 in Figure 3 is slightly different when compared to the base element 9 in Figure 1. The electrodes and sensors described above can be attached to the base element by using any appropriate method known per se.

15 **[0031]** All electrodes and sensors described above are connected to a single connector 10 attached to the base element 9 as shown in Figure 3. Instead of a single connector 10 a series of connectors may be used as told before.

20 **[0032]** The fourth embodiment is described in Figure 4. The sensor arrangement shown in Figure 4 comprises an array of electrodes for measuring EEG, EMG and for NMT stimulus. The electrodes are located on the face of the patient. Electrode 1 is located just posterior to the lower part of the pinna and electrode 2 is located just anterior to the tragus. Electrode 3 is located below the eye. Electrodes 4 and 5 have two alternative locations, a and b. Electrode 4a is located on the temple area between the corner of the eye and the hairline. Electrode 5a is located above the eye at the same level as electrode 6, which is located between the eyebrows of the patient at the center of the forehead, approximately 4 cm above the nose. Electrode 4b is located at either location F3 or F4 (left or right side) of the International 10-20 system. Electrode 5b is located between electrode 4b and electrode 6.

25 **[0033]** It is very advantageous to place electrode 5b essentially in the middle of electrodes 4b and 6 so that the distances between electrode 5b and electrode 4b, and electrode 5b and electrode 6 are essentially the same. In addition to these electrodes, a reflective optical sensor 7 for monitoring substances in tissues, e.g. SpO₂ is placed on the face of the patient, anywhere where suitable for the structure of the sensor, eg. but not limited to on the forehead above electrode 6. The optical sensor 7 comprises an emitter and a receiver located close to each other. The emitter comprises LEDs of different wavelengths and the receiver comprises a photodetector. A mechanical piezoelectric sensor 8 is located over either the procerus, frontalis, corrugator or orbicularismuscle or a combination of these.

30 **[0034]** Electrodes 1 and 2 are the NMT stimulus elec-

trodes, stimulating the facial nerve. Electrodes 4 (a or b) and 6 record EEG and EMG signals used e.g. to derive the Entropy parameter. Electrode 5 (a or b) is the reference electrode for the EEG and EMG measurement. The EEG and EMG measurement can be enhanced using electrode 3 e.g. but not limited to record eye movements. The EEG and EMG measurement can be done with or without electrode 3. The optical sensor measures e.g. the plethysmographic curve, the heartrate and the blood oxygen saturation. The mechanical piezoelectric sensor 8 records muscle response to NMT stimulus.

[0035] Also the embodiment shown in Figure 4 comprises according to the invention a base element 9. The base element 9 can be made of any appropriate flexible material, for example of plastic material. The electrodes and sensors described above can be attached to the base element by using any appropriate method known per se. As told before the form and the structure of the base element can be designed quite freely according to the existing need.

[0036] In this embodiment all electrodes and sensors described above are connected to a single connector 10 attached to the base element 9 in the same way as described in Figures 1 - 3. Instead of a single connector 10 a series of connectors may be used as told before.

[0037] The fifth embodiment is described in Figure 5. The sensor arrangement shown in Figure 5 comprises an array of electrodes for measuring EEG, EMG and for NMT stimulus. The electrodes are located on the face of the patient. Electrode 1 is located just posterior to the lower part of the pinna and electrode 2 is located just anterior to the tragus. Electrode 3 is located below the eye. Electrodes 4 and 5 have two alternative locations, a and b. Electrode 4a is located on the temple area between the corner of the eye and the hairline. Electrode 5a is located above the eye at the same level as electrode 6, which is located between the eyebrows of the patient at the center of the forehead, approximately 4 cm above the nose. Electrode 4b is located at either location F3 or F4 (left or right side) of the International 10-20 system. Electrode 5b is located between electrode 4b and electrode 6.

[0038] It is very advantageous to place electrode 5b essentially in the middle of electrodes 4b and 6 so that the distances between electrode 5b and electrode 4b, and electrode 5b and electrode 6 are essentially the same. In addition to these electrodes, a transmission optical sensor 7 for monitoring substances in tissues, e.g. SpO₂ is placed on the nose of the patient. The optical sensor 7 comprises an emitter and a receiver located on opposite sides of the nose. The emitter comprises LEDs of different wavelengths and the receiver comprises a photodetector. A mechanical piezoelectric sensor 8 is located over either the procerus, frontalis, corrugator or orbicularis muscle or a combination of these.

[0039] Electrodes 1 and 2 are the NMT stimulus electrodes, stimulating the facial nerve. Electrodes 4 (a or b) and 6 record EEG and EMG signals used e.g. to derive

the Entropy parameter. Electrode 5 (a or b) is the reference electrode for the EEG and EMG measurement. The EEG and EMG measurement can be enhanced using electrode 3 e.g. but not limited to record eye movements.

5 The EEG and EMG measurement can be done with or without electrode 3. The optical sensor measures e.g. the plethysmographic curve, the heartrate and the blood oxygen saturation. The mechanical piezoelectric sensor 8 records muscle response to NMT stimulus.

10 **[0040]** Also the embodiment shown in Figure 5 comprises according to the invention a base element 9. The base element 9 can be made of any appropriate flexible material, for example of plastic material. The electrodes and sensors described above can be attached to the base element by using any appropriate method known per se. As told before the form and the structure of the base element can be designed quite freely according to the existing need.

15 **[0041]** In this embodiment all electrodes and sensors described above are connected to a single connector 10 attached to the base element 9 in the same way as described in Figures 1 - 4. Instead of a single connector 10 a series of connectors may be used as told before in connection with the previous embodiments.

20 **[0042]** The sixth embodiment is described in Figure 6. The sensor arrangement shown in Figure 6 comprises an array of electrodes for measuring EEG, EMG and for NMT stimulus. The electrodes are located on the face of the patient. Electrode 1 is located just posterior to the lower part of the pinna and electrode 2 is located just anterior to the tragus. Electrode 3 is located below the eye. Electrodes 4 and 5 have two alternative locations, a and b. Electrode 4a is located on the temple area between the corner of the eye and the hairline. Electrode 5a is located above the eye at the same level as electrode 6, which is located between the eyebrows of the patient at the center of the forehead, approximately 4 cm above the nose. Electrode 4b is located at either location F3 or F4 (left or right side) of the International 10-20 system. Electrode 5b is located between electrode 4b and electrode 6.

25 **[0043]** It is very advantageous to place electrode 5b essentially in the middle of electrodes 4b and 6 so that the distances between electrode 5b and electrode 4b, and electrode 5b and electrode 6 are essentially the same. In addition to these electrodes, a transmission optical sensor 7 for monitoring substances in tissues, e.g. SpO₂ is placed on the ear of the patient. The optical sensor 7 comprises an emitter and a receiver located on opposite sides of either auricle. The emitter comprises LEDs of different wavelengths and the receiver comprises a photodetector. A mechanical piezoelectric sensor 8 is located over either the procerus, frontalis, corrugator or orbicularis muscle or a combination of these.

30 **[0044]** Electrodes 1 and 2 are the NMT stimulus electrodes, stimulating the facial nerve. Electrodes 4 (a or b) and 6 record EEG and EMG signals used e.g. to derive the Entropy parameter. Electrode 5 (a or b) is the refer-

ence electrode for the EEG and EMG measurement. The EEG and EMG measurement can be enhanced using electrode 3 e.g. but not limited to record eye movements. The EEG and EMG measurement can be done with or without electrode 3. The optical sensor measures e.g. the plethysmographic curve, the heartrate and the blood oxygen saturation. The mechanical piezoelectric sensor 8 records muscle response to NMT stimulus.

[0045] Also the embodiment shown in Figure 6 comprises according to the invention a base element 9. The base element 9 can be made of any appropriate flexible material, for example of plastic material. The electrodes and sensors described above can be attached to the base element by using any appropriate method known per se. As told before the form and the structure of the base element can be designed quite freely according to the existing need.

[0046] In this embodiment all electrodes and sensors described above are connected to a single connector 10 attached to the base element 9 in the same way as described in Figures 1 - 5. Instead of a single connector 10 a series of connectors may be used as told before in connection with the embodiments shown in Figures 1 - 5.

[0047] The seventh embodiment is described in Figure 7. The sensor arrangement shown in Figure 7 comprises an array of electrodes for measuring EEG, EMG and NMT. The electrodes are located on the face of the patient. Electrode 1 is located just posterior to the lower part of the pinna and electrode 2 is located just anterior to the tragus. Electrode 3 is located below the eye. Electrodes 4 and 5 have two alternative locations, a and b. If location b is used, electrode 4a is also used. Electrode 4a is located on the temple area between the corner of the eye and the hairline. Electrode 5a is located above the eye at the same level as electrode 6, which is located between the eyebrows of the patient at the center of the forehead, approximately 4 cm above the nose. Electrode 4b is located at either location F3 or F4 (left or right side) of the International 10-20 system. Electrode 5b is located between electrode 4b and electrode 6.

[0048] It is very advantageous to place electrode 5b essentially in the middle of electrodes 4b and 6 so that the distances between electrode 5b and electrode 4b, and electrode 5b and electrode 6 are essentially the same.

[0049] Electrodes 1 and 2 are the NMT stimulus electrodes, stimulating the facial nerve. Electrodes 4a and 6 are the NMT recording electrodes and electrode 5 (a or b) is the NMT grounding electrode. Electrodes 4 (a or b) and 6 also record EEG and EMG signals used e.g. to derive the Entropy parameter. Electrode 5 (a or b) is the reference electrode for the EEG and EMG measurement. The EEG and EMG measurement can be enhanced using electrode 3 e.g. but not limited to record eye movements. The EEG and EMG measurement can be done with or without electrode 3.

[0050] Also the embodiment shown in Figure 7 comprises according to the invention a base element 9. The

base element 9 can be made of any appropriate flexible material, for example of plastic material. The electrodes and sensors described above can be attached to the base element by using any appropriate method known per se.

5 As told before the form and the structure of the base element can be designed quite freely according to the existing need.

[0051] In this embodiment all electrodes and sensors described above are connected to a single connector 10 attached to the base element 9 in the same way as described in Figures 1 - 6. Instead of a single connector 10 a series of connectors may be used as told before in connection with the embodiments shown in Figures 1 - 6.

[0052] The eighth embodiment is described in Figure 8. The sensor arrangement shown in Figure 8 comprises an array of electrodes for measuring EEG, EMG and for NMT stimulus. The electrodes are located on the face of the patient. Electrode 1 is located just posterior to the lower part of the pinna and electrode 2 is located just anterior to the tragus. Electrode 3 is located below the eye. Electrodes 4 and 5 have two alternative locations, a and b. Electrode 4a is located on the temple area between the corner of the eye and the hairline. Electrode 5a is located above the eye at the same level as electrode 6, which is located between the eyebrows of the patient at the center of the forehead, approximately 4 cm above the nose. Electrode 4b is located at either location F3 or F4 (left or right side) of the International 10-20 system. Electrode 5b is located between electrode 4b and electrode 6.

[0053] It is very advantageous to place electrode 5b essentially in the middle of electrodes 4b and 6 so that the distances between electrode 5b and electrode 4b, and electrode 5b and electrode 6 are essentially the same. A mechanical piezoelectric sensor 8 is located over either the procerus, frontalis, corrugator or orbicularis muscle or a combination of these.

[0054] Electrodes 1 and 2 are the NMT stimulus electrodes, stimulating the facial nerve. Electrodes 4 (a or b) and 6 record EEG and EMG signals used e.g. to derive the Entropy parameter. Electrode 5 (a or b) is the reference electrode for the EEG and EMG measurements. The EEG and EMG measurement can be enhanced using electrode 3 e.g. but not limited to record eye movements. The EEG and EMG measurement can be done with or without electrode 3. The mechanical piezoelectric sensor 8 records muscle response to NMT stimulus.

[0055] Also the embodiment shown in Figure 8 comprises according to the invention a base element 9. The base element 9 can be made of any appropriate flexible material, for example of plastic material. The electrodes and sensors described above can be attached to the base element by using any appropriate method known per se. As told before the form and the structure of the base element can be designed quite freely according to the existing need.

[0056] In this embodiment all electrodes and sensors described above are connected to a single connector 10

attached to the base element 9 in the same way as described in connection with Figures 1 - 7 instead of a single connector 10 a series of connectors may be used as told before in connection with the embodiments shown in Figures 1 - 7.

[0057] The ninth embodiment is described in Figure 9. The sensor arrangement shown in Figure 9 comprises an array of electrodes for measuring EEG and EMG. The electrodes are located on the face of the patient. Electrode 1 is located below the eye. Electrodes 2 and 3 have two alternative locations, a and b. Electrode 2a is located on the temple area between the corner of the eye and the hairline. Electrode 3a is located above the eye at the same level as electrode 4, which is located between the eyebrows of the patient at the center of the forehead, approximately 4 cm above the nose. Electrode 2b is located at either location F3 or F4 (left or right side) of the International 10-20 system. Electrode 3b is located between electrode 2b and electrode 4.

[0058] It is very advantageous to place electrode 3b essentially in the middle of electrodes 2b and 4 so that the distances between electrode 3b and electrode 2b, and electrode 3b and electrode 4 are essentially the same. In addition to these electrodes, a reflective optical sensor 7 for monitoring substances in tissues, e.g. SpO₂ is placed on the face of the patient, anywhere where suitable for the structure of the sensor, for example on the forehead as shown in Figure 9. The optical sensor 7 comprises an emitter and a receiver located close to each other. The emitter comprises LEDs of different wavelengths and the receiver comprises a photodetector.

[0059] Electrodes 2 (a or b) and 4 record EEG and EMG signals used e.g. to derive the Entropy parameter. Electrode 3 (a or b) is the reference electrode for the EEG and EMG measurement. The EEG and EMG measurement can be enhanced using electrode 1 e.g. but not limited to record eye movements. The EEG and EMG measurement can be done with or without electrode 1. The optical sensor measures e.g. the plethysmographic curve, the heartrate and the blood oxygen saturation.

[0060] The embodiment shown in Figure 9 comprises also according to the invention a base element 9. The base element 9 can be made of any appropriate flexible material, for example of plastic material. The electrodes and sensors described above can be attached to the base element by using any appropriate method known per se. As told before the form and the structure of the base element can be designed quite freely according to the existing need.

[0061] In this embodiment all electrodes and sensors described above are connected to a single connector 10 attached to the base element 9 in the same way as described in connection with Figures 1 - 8. Instead of a single connector 10 a series of connectors may be used as told before in connection with the embodiments shown in Figures 1 - 8.

[0062] The tenth embodiment is described in Figure 10. The sensor arrangement shown in Figure 10 com-

prises an array of electrodes for measuring EEG and EMG. The electrodes are located on the face of the patient. Electrode 1 is located below the eye. Electrodes 2 and 3 have two alternative locations, a and b. Electrode 2a is located on the temple area between the corner of the eye and the hairline. Electrode 3a is located above the eye at the same level as electrode 4, which is located between the eyebrows of the patient at the center of the forehead, approximately 4 cm above the nose. Electrode 2b is located at either location F3 or F4 (left or right side) of the International 10-20 system. Electrode 3b is located between electrode 2b and electrode 4.

[0063] It is very advantageous to place electrode 3b essentially in the middle of electrodes 2b and 4 so that the distances between electrode 3b and electrode 2b, and electrode 3b and electrode 4 are essentially the same. In addition to these electrodes, a transmission optical sensor 7 for monitoring substances in tissues, e.g. SpO₂ is placed on the nose of the patient. The optical sensor 7 comprises an emitter and a receiver located on opposite sides of the nose. The emitter comprises LEDs of different wavelengths and the receiver comprises a photodetector.

[0064] Electrodes 2 (a or b) and 4 record EEG and EMG signals used e.g. to derive the Entropy parameter. Electrode 3 (a or b) is the reference electrode for the EEG and EMG measurement. The EEG and EMG measurement can be enhanced using electrode 1 e.g. but not limited to record eye movements. The EEG and EMG measurement can be done with or without electrode 1. The optical sensor measures e.g. the plethysmographic curve, the heartrate and the blood oxygen saturation.

[0065] As told in connection with the previous embodiments also the embodiment shown in Figure 10 comprises a base element 9. The base element 9 can be made of any appropriate flexible material, for example of plastic material. The electrodes and sensors described above can be attached to the base element by using any appropriate method known per se. As told before the form and the structure of the base element can be designed quite freely according to the existing need.

[0066] In the embodiment of Figure 10 all electrodes and sensors described above are connected to a single connector 10 attached to the base element 9 in the same way as described in connection with Figures 1 - 9. Instead of a single connector 10 a series of connectors may be used as told before in connection with the embodiments shown in Figures 1 - 9.

[0067] The eleventh embodiment is described in Figure 11. The sensor arrangement shown in Figure 11 comprises an array of electrodes for measuring EEG and EMG. The electrodes are located on the face of the patient. Electrode 1 is located below the eye. Electrodes 2 and 3 have two alternative locations, a and b. Electrode 2a is located on the temple area between the corner of the eye and the hairline. Electrode 3a is located above the eye at the same level as electrode 4, which is located between the eyebrows of the patient at the center of the

forehead, approximately 4 cm above the nose. Electrode 2b is located at either location F3 or F4 (left or right side) of the International 10-20 system. Electrode 3b is located between electrode 2b and electrode 4.

[0068] It is very advantageous to place electrode 3b essentially in the middle of electrodes 2b and 4 so that the distances between electrode 3b and electrode 2b, and electrode 3b and electrode 4 are essentially the same. In addition to these electrodes, a transmission optical sensor 7 for monitoring substances in tissues, e.g. SpO₂ is placed on the ear of the patient. The optical sensor 7 comprises an emitter and a receiver located on opposite sides of either auricle. The emitter comprises LEDs of different wavelengths and the receiver comprises a photodetector.

[0069] Electrodes 2 (a or b) and 4 record EEG and EMG signals used e.g. to derive the Entropy parameter. Electrode 3 (a or b) is the reference electrode for the EEG and EMG measurement. The EEG and EMG measurement can be enhanced using electrode 1 e.g. but not limited to record eye movements. The EEG and EMG measurement can be done with or without electrode 1. The optical sensor measures e.g. the plethysmographic curve, the heartrate and the blood oxygen saturation.

[0070] As told in connection with the previous embodiments also the embodiment shown in Figure 11 comprises a base element 9. The base element 9 can be made of any appropriate flexible material, for example of plastic material. The electrodes and sensors described above can be attached to the base element by using any appropriate method known per se. As told before the form and the structure of the base element can be designed quite freely according to the existing need.

[0071] In the embodiment of Figure 11 all electrodes and sensors described above are connected to a single connector 10 attached to the base element 9 in the same way as described in connection with Figures 1 - 10. Instead of a single connector 10 a series of connectors may be used as told before in connection with the embodiments shown in Figures 1 - 10.

[0072] In the embodiments shown in Figures 1 - 11 all electrodes and sensors are connected to a single connector 10 for connecting the sensor arrangement to a patient monitor. Said arrangement reduces the amount of cables needed between the patient and the patient monitor. As told above depending on the sensor design it might however be necessary to use separate connectors for some of the parameters, ie. for some of the electrodes used, to meet patient leakage current and isolation requirements. Said separate connectors can be arranged as a compact unit, in which the connectors are placed side by side for example.

[0073] The above embodiments of the invention are by no means intended to limit the invention, but the invention can be modified quite freely within the scope of the claims. Accordingly, it is clear that an embodiment of the invention or its details do not necessarily need to be just as described in the figures, but solutions of other

kinds are also possible.

Claims

1. Sensor arrangement for measuring anesthesia parameters from the head of a patient, the sensor arrangement comprising a base element (9) and an array of electrodes and an optical sensor (7) for monitoring substances in tissues, all electrodes and sensors (1-8) being connected to a single connector (10) or a series of connectors attached to the base element (9) for connecting the sensor arrangement to a patient monitor, **characterized in that** the array of electrodes comprises at least three electrodes (4a, 5a,6;2a.3a.4;4b,6,3;2b,4.1), the three electrodes being adapted to *measure EEG and EMG, the first (4a;2a) of the three electrodes being configured to be located on the temple area between the corner of the eye and the hairline, the second electrode (5a; 3a) of the three electrodes being configured to be located above the eye at the same level as the third electrode (6;4) of the three electrodes which is configured to be located between the eyebrows of the patient at the center of the forehead above the nose, and **in that** the sensor arrangement further comprises a mechanical NMT sensor (8), the mechanical NMT sensor (8) being a piezoelectric sensor located over either the procerus, frontalis, corrugator or orbicularis muscle or a combination of these to record the response to the NMT stimulus.
2. The arrangement of claim 1, **characterized in that** the third electrode is configured to be located about 4 cm above the nose, and the fourth electrode (3;1) of the array of electrodes is configured to be located below the eye for enhancing the EEG and EMC measurement.
3. The arrangement of claim 1, **characterized in that** the electrodes (4a, 6) are used to measure NMT response.
4. The arrangement of claim 1, **characterized in that** the first (4b;2b) of the three electrodes is located on location F2 or F4 of the International 10-20 system, the second electrode (6;4) of the three electrodes is located between the eyebrows of the patient at the center of the forehead, about 4 cm above the nose, and the fourth electrode (3;1) of the array of electrodes is located below the eye for enhancing the EEG and EMG measurement.
5. The arrangement of claim 4, **characterized in that** there is an additional electrode (4a) located on the temple area between the corner of the eye, and the additional electrode (4a) and the second (6) and the third electrodes (3) of the three electrodes are used

to measure NMT response.

6. The arrangement of claim 1, 2, 3, 4 or 5, **characterized in that** the optical sensor (7) for monitoring substances in tissues is attached to the forehead. 5
7. The arrangement of claim 1, 2, 3, 4 or 5, **characterized in that** the optical (7) sensor for monitoring substances in tissues is attached to the root of the nose. 10
8. The arrangement of claim 1, 2, 3, 4, or 5, **characterized in that** the optical sensor (7) for monitoring substances in tissues is attached to the ear. 15
9. The arrangement of claim 1, **characterized in that** the optical sensor (7) for monitoring substances in tissues is a SpO2 sensor. 20
10. The arrangement of claim 1, **characterized in that** the first and the electrode (1,2) of the array of electrodes are NMT stimulus electrodes located just posterior to the lower part of the pinna and just anterior to the tragus to stimulate the facial nerve. 25

Patentansprüche

1. Sensoranordnung zum Messen von Anästhesieparametern vom Kopf eines Patienten, welche Sensoranordnung ein Basiselement (9) und eine Gruppierung von Elektroden und einen optischen Sensor (7) zum Überwachen von Substanzen, in Geweben umfasst, wobei alle Elektroden und Sensoren (1 - 8) an einen einzelnen Anschluss (10) oder eine Serie von Anschlüssen angeschlossen sind, der/die an dem Basiselement (9) zum Anschließen der Sensoranordnung an einem Patientenmonitor befestigt ist/sind, **dadurch gekennzeichnet, dass** die Elektroden-Gruppierung mindestens drei Elektroden (4a,5a,6; 2a,3a,4; 4b,6,3; 2b,4,1) aufweist, welche drei Elektroden dazu bestimmt sind, ein EEG und EMG zu messen, wobei die erste (4a;2a) der drei Elektroden dazu bestimmt ist, im Schläfenbereich zwischen dem Eck des Auges und der Haaransatzlinie angeordnet zu werden, die zweite Elektrode (5a;3a) der drei Elektroden dazu bestimmt ist, oberhalb des Auges auf dem selben Niveau entsprechend der dritten Elektrode (6;4) der drei Elektroden angeordnet zu werden, die dazu bestimmt ist, zwischen den Augenbrauen des Patienten am Zentrum der Stirn oberhalb der Nase angeordnet zu werden, und dass die Sensoranordnung ferner einen mechanischen NMT-Sensor (8) aufweist, wobei der mechanische NMT-Sensor (8) ein piezoelektrischer Sensor ist, der entweder über dem Procerus-, dem Frontalis-, dem Corrugator- oder dem Orbicularis-Muskel oder einer Kombination dieser zur Aufnahme der Antwort auf

den NMT-Stimulus anzuordnen ist.

2. Anordnung nach Anspruch 1, **dadurch gekennzeichnet, dass** die dritte Elektrode dazu bestimmt ist, ca. 4 cm oberhalb der Nase angeordnet zu werden, und die vierte Elektrode (3; 1) der Elektroden-Gruppierung dazu bestimmt ist, unterhalb des Auges zur Erhöhung der EEG- und EMG-Messung angeordnet zu werden. 5
3. Anordnung nach Anspruch 1, **dadurch gekennzeichnet, dass** die Elektroden (4a,6) dazu verwendet werden, um eine NMT-Antwort zu messen. 10
4. Anordnung nach Anspruch 1, **dadurch gekennzeichnet, dass** die erste (4b;2b) der drei Elektroden auf der Platzierung F2 oder F4 des internationalen 10-20-Systems angeordnet ist, die zweite Elektrode (6;4) der drei Elektroden zwischen den Augenbrauen des Patienten am Zentrum der Stirn, ca. 4 cm oberhalb der Nase angeordnet ist, und die vierte Elektrode (3;1) der Elektroden-Gruppierung unterhalb des Auges zur Erhöhung der EEG- und EMG-Messung angeordnet ist. 15
5. Anordnung nach Anspruch 4, **dadurch gekennzeichnet, dass** eine zusätzliche Elektrode (4a) im Schläfenbereich zwischen dem Eck des Auges angeordnet ist, und die zusätzliche Elektrode (4a) und die zweite (6) und die dritte Elektrode (3) der drei Elektroden dazu verwendet werden, eine NMT-Anhvor zu messen. 20
6. Anordnung nach Anspruch 1, 2,3,4 oder 5, **dadurch gekennzeichnet, dass** der optische Sensor (7) zum Überwachen von Substanzen in Geweben an der Stirn festgelegt ist. 25
7. Anordnung nach Anspruch 1,2,3,4 oder 5, **dadurch gekennzeichnet, dass** der optische Sensor (7) zum Überwachen von Substanzen in Geweben an der Nasenwurzel festgelegt ist. 30
8. Anordnung nach Anspruch 1, 2, 3, 4 oder 5, **dadurch gekennzeichnet, dass** der optische Sensor (7) zum Überwachen von Substanzen in Geweben am Ohr festgelegt ist. 35
9. Anordnung nach Anspruch 1, **dadurch gekennzeichnet, daß** der optische Sensor (7) zum Überwachen von Substanzen in Geweben ein SpO2-Sensor ist. 40
10. Anordnung nach Anspruch 1, **dadurch gekennzeichnet, dass** die erste und die Elektrode (1, 2) der Elektroden-Gruppierung NMT-Stimulus-Elektroden sind, die unmittelbar hinter dem

unteren Teil der Ohrmuschel und unmittelbar vor dem Tragus zur Stimulierung des Gesichtsnervs angeordnet ist.

Revendications

1. Agencement de capteurs pour mesurer des paramètres d'anesthésie de la tête d'un patient, l'agencement de capteurs comportant un élément de base (9) et un réseau d'électrodes et un capteur optique (7) pour surveiller des substances dans des tissus, toutes les électrodes et les capteurs (1-8) étant connectés à un connecteur unique (10) ou à une série de connecteurs fixés à l'élément de base (9) pour connecter l'agencement de capteurs à un moniteur d'un patient, **caractérisé en ce que** le réseau d'électrodes comporte au moins trois électrodes (4a, 5a, 6 ; 2a, 3a, 4 ; 4b,6,3 ; 2b,4.1), les trois électrodes étant adaptées pour mesurer un électroencéphalogramme EEG et un électromyogramme EMG, la première (4a ; 2a) des trois électrodes étant configurée pour être positionnée sur la région temporale entre le coin de l'oeil et la ligne de tête, la deuxième électrode (5a ; 3a) des trois électrodes étant configurée pour être positionnée au-dessus de l'oeil au même niveau que la troisième électrode (6 ; 4) des trois électrodes qui est configurée pour être positionnée entre les sourcils du patient au centre du front au-dessus du nez, et **en ce que** l'agencement de capteurs comporte en outre un capteur NMT mécanique (8), le capteur NMT mécanique (8) étant un capteur piézo-électrique localisé soit sur le muscle procerus, frontalis, corrugator ou orbiculaire ou une combinaison de ceux-ci pour enregistrer la réponse au stimulus NMT. 5
2. Agencement selon la revendication 1, **caractérisé en ce que** la troisième électrode est configurée pour être positionnée environ 4 cm au-dessus du nez, et la quatrième électrode (3 ; 1) du réseau d'électrodes est configurée pour être positionnée au-dessous de l'oeil pour améliorer la mesure EEG et EMC. 10
3. Agencement selon la revendication 1, **caractérisé en ce que** les électrodes (4a, 6) sont utilisées pour mesurer une réponse NMT. 15
4. Agencement selon la revendication 1, **caractérisé en ce que** la première (4b ; 2b) des trois électrodes est positionnée sur un emplacement F2 ou F4 du système 10-20 international, la deuxième électrode (6 ; 4) des trois électrodes est positionnée entre les sourcils du patient au niveau du centre du front, environ 4 cm au-dessus du nez, et la quatrième électrode (3 ; 1) du réseau d'électrode est positionnée au-dessous de l'oeil pour améliorer la mesure EEG et EMG. 20
5. Agencement selon la revendication 4, **caractérisé en ce que** il existe une électrode supplémentaire (4a) positionnée sur la région temporale entre le coin de l'oeil, et l'électrode supplémentaire (4a) et la deuxième (6) et la troisième électrodes (3) des trois électrodes sont utilisées pour mesurer une réponse NMT. 25
6. Agencement selon la revendication 1, 2, 3, 4 ou 5, **caractérisé en ce que** le capteur optique (7) pour surveiller des substances dans des tissus est fixé au front. 30
7. Agencement selon la revendication 1, 2, 3, 4 ou 5, **caractérisé en ce que** le capteur optique (7) pour surveiller des substances dans des tissus est fixé à la base du nez. 35
8. Agencement selon la revendication 1, 2, 3, 4 ou 5, **caractérisé en ce que** le capteur optique (7) pour surveiller des substances dans des tissus est fixé à l'oreille. 40
9. Agencement selon la revendication 1, **caractérisé en ce que** le capteur optique (7) pour surveiller des substances dans des tissus est un capteur SpO2. 45
10. Agencement selon la revendication 1, **caractérisé en ce que** la première et la deuxième électrodes (1, 2) du réseau d'électrodes sont des électrodes de stimulus NMT positionnées juste après la partie inférieure du pavillon et juste avant le tragus pour stimuler le nerf facial. 50




Figure 1. The first embodiment.




Figure 2. The second embodiment.




Figure 3. The third embodiment.




Figure 4. The fourth embodiment.




Figure 5. The fifth embodiment.




Figure 6. The sixth embodiment.




Figure 7. The seventh embodiment.




Figure 8. The eighth embodiment.




Figure 9. The ninth embodiment.




Figure 11. The eleventh embodiment.

REFERENCES CITED IN THE DESCRIPTION

This list of references cited by the applicant is for the reader's convenience only. It does not form part of the European patent document. Even though great care has been taken in compiling the references, errors or omissions cannot be excluded and the EPO disclaims all liability in this regard.

Patent documents cited in the description

- WO 0232305 A1 [0006]
- WO 03057030 A [0007]
- US 4595018 A [0007]
- US 2003009096 A [0007]

Non-patent literature cited in the description

- Chemical Biosensors. Medical Instrumentation: Application and Design. Wiley, 1998, 469-472 [0003]
- **Paloheimo Markku P.J. et al.** Comparison of Neuromuscular Blockade in Upper Facial and Hypothenar Muscles. *Journal of Clinical Monitoring*, October 1988, vol. 4 (4 [0005]

专利名称(译)	传感器布置		
公开(公告)号	EP1523934B1	公开(公告)日	2010-12-08
申请号	EP2004104961	申请日	2004-10-11
申请(专利权)人(译)	INSTRUMENTARIUM CORPORATION		
当前申请(专利权)人(译)	GE HEALTHCARE芬兰OY		
[标]发明人	HOSKONEN TERHO KAMPPARI LASSE KYMALAINEN MINNA KALL MAGNUS PESU LEENA		
发明人	HOSKONEN, TERHO KAMPPARI, LASSE KYMÄLÄINEN, MINNA KALL, MAGNUS PESU, LEENA		
IPC分类号	A61B5/04 A61B5/05 A61B5/0205 A61B5/00 A61B5/0402 A61B5/0488 A61B5/11		
CPC分类号	A61B5/6841 A61B5/0059 A61B5/04001 A61B5/0402 A61B5/0488 A61B5/1106 A61B5/4821 A61B5/6814		
优先权	10/688863 2003-10-17 US		
其他公开文献	EP1523934A1		
外部链接	Espacenet		

摘要(译)

用于测量来自患者头部的麻醉参数的传感器装置，传感器装置包括基座元件（9）和电极阵列以及用于监测组织中物质的光学传感器（7）。在传感器布置中，所有电极和传感器连接到单个连接器（10）或连接到基座元件（9）的一系列连接器，用于将传感器装置连接到患者监视器。




Figure 1. The first embodiment.