



(11)

EP 3 231 360 A1

(12) **EUROPEAN PATENT APPLICATION**

(43) Date of publication:
18.10.2017 Bulletin 2017/42

(51) Int Cl.:
A61B 5/00 (2006.01) **A61F 2/46 (2006.01)**
A61F 2/38 (2006.01)

(21) Application number: **17173896.6**

(22) Date of filing: **24.03.2005**

(84) Designated Contracting States:
AT BE BG CH CY CZ DE DK EE ES FI FR GB GR HU IE IS IT LI LT LU MC NL PL PT RO SE SI SK TR

• **Liao, Yen-Shuo**
Warsaw, IN 46580 (US)

(30) Priority: **31.03.2004 US 813803**

(74) Representative: **Curran, Clair**
Urquhart-Dykes & Lord LLP
Arena Point
Merrion Way
Leeds LS2 8PA (GB)

(62) Document number(s) of the earlier application(s) in accordance with Art. 76 EPC:
05251831.3 / 1 586 287

(71) Applicant: **DePuy Products, Inc.**
Warsaw, IN 46581 (US)

Remarks:

This application was filed on 01.06.2017 as a divisional application to the application mentioned under INID code 62.

(72) Inventors:

• **DiSilvestro, Mark**
Fort Wayne, IN 46825 (US)

(54) **KNEE JOINT ENDOPROSTHESIS WITH AMBIENT CONDITION SENSING**

(57) A system for monitoring the ambient conditions of a mammalian joint, and particularly a joint that has been instrumented with a joint endoprosthesis includes a sensor supported by a component of the joint endoprosthesis. The system includes a transmission element that is also supported within the body of the patient, preferably within the endoprosthesis. The transmission element transmits a signal indicative of the sensed ambient condition within the instrumented joint. For example, the sensor can be a temperature sensor used to evaluate the temperature within a joint, such as a hip joint, during activity or exercise by the patient.




FIG. 7

EP 3 231 360 A1

Description

[0001] The present invention relates to orthopaedic components configured for implantation within a patient. In particular, the invention concerns systems and methods for evaluating the ambient conditions within a joint space.

[0002] Replacement of human joints, such as the knee, shoulder, elbow and hip, has become a more and more frequent medical treatment. Longer life spans mean that the joints endure more wear and tear. More sports activities mean greater likelihood of serious joint injuries. Treatment of injuries, wear and disease in human joints has progressed from the use of orthotics to mask the problem, to fusion of the joint, to the use of prostheses to replace the damaged joint component(s).

[0003] Joint endoprostheses have been developed to replace virtually every human joint. The efficacy and success of these orthopaedic components or implants has steadily increased over the years as improvements in materials, manufacturing and design are developed. New machining processes and material coatings have been developed that enhance the fixation of the implant within the natural bone of a patient. Alloys and ceramics have been developed that emulate the strength of natural bone, while still preserving the biomechanical attributes of the joint being repaired. Bearing surfaces have been improved to increase the bearing life.

[0004] In spite of these improvements in endoprosthesis design and in the surgical procedures to implant these joint components, it is still difficult to control or emulate the ambient conditions of an intact mammalian joint. For instance, any articulating endoprosthesis necessarily generates heat from friction between the moving components. Excessive temperatures can lead to boney and soft tissue damage and even necrosis in a joint. Materials choice and smooth machining techniques can greatly reduce the friction between articulating parts, but in spite of these efforts joint over-heating may be a problem.

[0005] In an ideally constructed endoprosthesis, friction may only become a problem as the bearing surfaces wear. Since the prosthetic bearing components are not regenerative, the surfaces of these components will inevitably wear, especially in an active patient. As the bearing surfaces wear and roughen, friction increases, which may result in a noticeable, and even dangerous, increase in joint temperature. An awareness of this ambient condition of the joint can be used to assist in diagnosis of early problems and to determine when a revision of the endoprosthesis will be necessary before the bone and surrounding soft tissue is damaged.

[0006] The present invention contemplates a system for monitoring the ambient conditions of a mammalian joint. The invention is particularly suited for use with a joint that has been replaced by an endoprosthesis. This invention is useful in joints that endure high loads over many cycles, such as the hip or knee, since these joints are especially susceptible to temperature increases due

to unresolved friction in the endoprosthesis.

[0007] In one aspect, the invention provides a joint endoprosthesis comprising:

5 a body configured to replace a portion of a mammalian joint;
at least one sensor supported by said body, said sensor adapted to sense an ambient condition of the mammalian joint and to generate a condition signal indicative of the sensed condition; and
10 a transmission element connected to said sensor to receive said condition signal and operable to transmit a signal indicative of said condition signal.

15 **[0008]** In another aspect, the invention provides a system for sensing a condition within a mammalian joint comprising:

an endoprosthesis including a body configured to replace a portion of the joint;
20 a sensor supported by said body, said sensor adapted to sense an ambient condition of the mammalian joint and to generate a condition signal indicative of the sensed condition;
25 a transmitter connected to said sensor to receive said condition signal and operable to transmit a transmission signal outside the joint indicative of said condition signal;
a receiver disposed outside the joint for receiving said transmission signal; and
30 translation circuitry for translating said transmission signal to a human sensible signal.

[0009] The sensor can be used in a method for determining a condition within a mammalian joint comprising the steps of:

introducing a sensor within the joint, the sensor adapted to sense an ambient condition of the joint and to generate a sensor signal indicative of the ambient condition;
40 coupling the sensor with a transmission element operable to transmit an information signal outside the joint in response to the sensor signal;
45 sensing the ambient condition within the joint; and transmitting the information signal.

[0010] The sensor can be used in a method for determining a condition within a mammalian joint comprising the steps of:

introducing a sensor within the joint, the sensor adapted to sense an ambient condition of the joint and to generate a sensor signal indicative of the ambient condition;
55 coupling the sensor with a transmission element operable to transmit an information signal outside the joint in response to the sensor signal;

sensing the ambient condition within the joint; and transmitting the information signal.

[0011] In one embodiment of the invention, the ambient condition is the temperature within the joint. In this embodiment, a temperature sensor is supported by a component of a joint endoprosthesis, such as an articulating component of the endoprosthesis. The temperature sensor communicates a signal indicative of the ambient temperature within the joint to a transmission element that is supported within the body of the patient. In a preferred embodiment, the transmission element is also supported within a component of the joint endoprosthesis.

[0012] The transmission element includes electrical or electronic elements operable to transmit a signal in relation to the temperature signal received from the temperature sensor. In one embodiment, the transmission element includes an antenna that transmits a signal outside the joint to a receiver. The receiver can include electrical or electronic elements that can translate the signal received from the transmission element into a human sensible format. For instance, the receiver can provide a visual display of the ambient temperature within the joint. Alternatively, or in addition, the receiver can issue an audible alarm if the sensed temperature exceeds a predetermined threshold. A memory component can be associated with the receiver to maintain a retrievable history of the temperature within the joint.

[0013] In certain embodiments, the temperature sensor and transmitter are disposed within corresponding cavities defined in the orthopaedic component. The cavity is potted with a biologically compatible material, such as a bone cement. Preferably, the depth of the cavity for the temperature sensor is adequate for a meaningful temperature reading within the joint. Moreover, the temperature sensor is most preferably situated as close to an articulating surface of the joint as possible, since friction generated by movement of this surface is a primary cause of deleterious temperature increases within the joint. For instance, where the joint endoprosthesis is a hip prosthesis, the temperature sensor can be disposed in the acetabular cup or in the femoral head, since these components include the articulating surface for the hip prosthesis.

[0014] The transmission element can be configured to simply transmit the temperature signal generated by the sensor, or it can be configured to analyse the temperature signal. In the former case, the analysis of the temperature signal can occur in the receiver. The temperature signal can be evaluated to determine whether a critical temperature condition exists. For instance, it is known that sustained temperatures above 44°C can cause necrosis of bone and soft tissues. The temperature signal can be first evaluated to determine whether the ambient temperature in the joint has reached this threshold temperature. It is contemplated that some conditioning of the temperature signal may be required. If the sensor is not in direct contact with the bone or surrounding soft tissue, any tem-

perature value is necessarily less than the ambient condition due to the thermal conductivity of the medium supporting the temperature sensor. The temperature signal can be conditioned to account for this temperature differential to produce an accurate estimate of the ambient temperature in the joint.

[0015] The analysis of the temperature signal is preferably performed over a period of time. This can provide information as to the period over which the sensed temperature has exceeded the temperature threshold. This time aspect of the analysis can be based on a time threshold, such as one minute of sustained temperature above the threshold. Alternatively, the analysis can be based on a time-temperature function in which the temperature threshold varies as a function of the length of time at that temperature. For example, ambient temperatures above 50°C may be indicative of a serious problem so the time limit at this temperature may be relatively short, say 30 seconds. On the other hand, an ambient temperature below the necrosis threshold temperature may be sustainable for several minutes before a problem is indicated. This time-temperature function can be applied through appropriate circuitry or through on-board software that applies an equation or utilizes a table look-up.

[0016] In accordance with certain features of the invention, the system component resident with the joint endoprosthesis includes a power source to drive the temperature sensor and the transmission element. The power source can be self-contained, such as a battery, which is disposed within a component of the endoprosthesis. The power source can be passive, such as a power coil that derives its power from electromagnetic coupling with an external coil. This passive power source approach can utilize technology commonly used for RFID tags. As with the RFID technology, the passive power source can also constitute an antenna for transmitting the temperature signal outside the joint. With the passive power source approach, an external power source driving the external coil may be carried by the patient in proximity to the endoprosthesis, or may be placed in proximity to the endoprosthesis by a caregiver at the point of care..

[0017] The present invention contemplates sensing other ambient conditions of an instrumented mammalian joint. For instance, the pH of the soft tissue or fluids within the joint can provide an indication of the health of the joint following implantation of an endoprosthesis. The pH can provide an indication of the presence of an infection in the joint before the infection is manifested by outwardly sensible symptoms, such as inflammation of the surrounding skin. Thus, the temperature sensor can be replaced by a pH sensor, where the pH sensor is positioned so that it is in contact with the tissue within the joint. A similar sensor can be used to detect the presence of specific genes, proteins, bacteria, chemicals or fluids within the joint. Sensors of this type can often be passive, meaning that a chemical reaction in the sensor generates an electrical current that can be sensed by a transmission element.

[0018] The present invention therefore provides a system that can sense ambient conditions within a mammalian joint. One benefit of this system is that it can detect potentially harmful conditions within the joint that could not otherwise be sensed. A further benefit of the invention is that it provides a mechanism for warning a patient or a surgeon of this potentially harmful condition in sufficient time to allow remedial or corrective action to be taken.

[0019] Embodiments of the invention will now be described by way of example with reference to the accompanying drawings, in which:

FIG. 1 is a cross-sectional view of a hip implant incorporating ambient condition sensing features of the present invention.

FIG. 2 is a side view of an endoprosthesis according to one embodiment of the present invention.

FIG. 3 is a block diagram of the components of the condition sensor system according to an embodiment of the invention for use with the endoprosthesis shown in FIG. 2.

FIGS. 4a and 4b are block diagrams of components for use with the components shown in the block diagram of FIG. 3.

FIG. 5 is a block diagram of an external device according to one aspect of the present invention.

FIG. 6 is a block diagram of an alternative external device according to the invention.

FIG. 7 is a front view of a knee endoprosthesis implementing the ambient condition sensing system of the present invention.

[0020] Referring to the drawings, FIG.1 shows a hip endoprosthesis 10 which includes an acetabular cup 12 fixed within the ilium I. The cup includes a liner 13 that provides a low-friction articulating surface. The endoprosthesis further includes a femoral component 14 that is fixed within the prepared proximal end of the femur F. In particular, the femoral component includes a stem 16 implanted within the intramedullary canal of the femur F. The stem terminates in a proximal body 18 from which extends a neck 19. The neck carries a femoral head 20 mounted thereon, being configured to articulate within the liner 13 of the acetabular cup to define an articulating contact surface 22.

[0021] As with any surface of contact between moving components, the joint contact 22 between the two primary components of the hip endoprosthesis 10 generate a certain amount of friction. This friction results in a temperature increase in the articulating components, especially the acetabular cup 12 and the femoral head 20. This temperature increase is dissipated into the surrounding bone and soft tissue, resulting in an increase in ambient temperature within the joint. Research has demonstrated that necrosis starts when mammalian tissue is maintained at 44 to 47°C for at least one minute [See, Eriksson et al. Scand J Plast. Reconstr. Surg. 1984; 18(3): 261-8].

[0022] In certain patient tests [see, Bergmann et al. Journal of Biomechanics 2001; 34: 421-428], a patient having a hip implant was instrumented with temperature sensors at various locations in the femoral head and stem. After over an hour of walking on a treadmill, the temperature at the centre of the head reached about 43°C. In a laboratory hip simulation [see, Lu et al. Proc. Instn. Mech. Engrs. 1997; [H], 211: 101-108], the temperature exceeded 50°C after about three hours of continuous simulated walking. Finite element analysis has demonstrated that for a 50°C temperature measured at the femoral head 0.5 mm to the articulating surface, the surface temperature could reach 100°C. Obviously, this temperature is well above the temperature at which tissue necrosis starts. Sustained ambient temperatures in this 100°C range can cause severe damage to the bones and surrounding tissue. Consequently, the studies suggested that patients with hip implants to avoid any strenuous activity that might result in dangerous temperature increases in the hip joint.

[0023] Not all activity levels lead to unhealthy temperatures in the instrumented joint. Rather than avoid physical activity altogether, it is preferable that a patient be permitted to engage in healthy exercise, such as walking. The present invention provides a system for monitoring the ambient temperature of the joint and issuing a warning when the temperature reaches a pre-determined threshold value. The patient can then stop or reduce the activity level until the temperature returns to an acceptable value.

[0024] Thus, in accordance with one aspect of the invention, a sensor 30 is supported by one of the components of the endoprosthesis 10. In the illustrated embodiment, the sensor is supported in the neck 19 of the proximal body 18. Alternatively, the sensor can be supported inside the femoral head, close to the articulating surface. The sensor may be situated as close as possible to the articulating contact surface 22 as possible to obtain a temperature reading that is as close as possible to the actual temperature at that contact surface. In the present embodiment the temperature is a miniature temperature sensor (such as ADT7516, Analog Devices, Inc., MA) or thermocouple capable of generating an electrical signal as a function of the ambient temperature. In a specific embodiment, the sensor can be a TD5A miniature temperature sensor sold by MicroSwitch Corp. This sensor is about 3.2 mm (0.125 inch) in height and width, and less than 2.5 mm (0.1 inch) in thickness. Other temperature sensors can be used, such as the TC40 thermocouple or the RTD Probe of Minco Products, Inc. The temperature sensor must be small enough to fit within the envelope of a joint component and be capable of providing fast response in a temperature range of 20 to 200°C.

[0025] In accordance with the preferred embodiment, the sensor 30 communicates via internal wiring 33 with a transmission element 35. The transmission element 35 is operable to receive the condition signals from the tem-

perature sensor 30 and transmit an output signal indicative of the condition signal. A power source 40 is electrically connected to the transmission element 35 and the sensor 30 to provide electrical power to both devices via wiring 37 (FIG. 2).

[0026] The power source 40 can be an active element, such as a battery, provided that it is suitably small to be supported within an implant component and sufficiently sealed against leakage of toxic materials. A lithium iodine cell available from Wilson Greatbatch Technologies can be used. The power source 40 can include a switch to conserve battery life. The switch can be inductively activated, such as by an electromagnetic wand passed outside the body adjacent the instrumented joint. The switch can be activated when the patient anticipates undertaking activity that will exercise the joint.

[0027] Alternatively, the power source 40 can constitute a passive power supply, such as the type of power supply used in RFID tags. This passive power source can be in the form of an inductive ferrite coil, such as the small wound coil available commercially from MicroHelix, Inc. of Portland, Oregon. An external electromagnetic device powers this passive power source.

[0028] Referring to FIG. 2, the layout of one embodiment of the invention is illustrated. In particular, the femoral component 14 can be formed with a number of cavities for receiving the elements of the temperature sensing system. Specifically, a cavity 24 can be defined in the neck 19 to receive the sensor 30. The dimensions of the cavity 24 preferably provide a close fit around the sensor. Moreover, the depth of the cavity 24 depends upon the nature of the sensor. In other words, if the sensor requires direct contact with the adjacent tissue, the depth of the channel 24 can be established to allow the sensor to be accessible on the outer surface of the implant. On the other hand, where the sensor is a temperature sensor, as discussed above, the sensor can be embedded within the cavity 24 below the surface of the implant. Most preferably, the temperature sensor is as close to the surface as possible, since its temperature response depends upon heat transmission through the implant into the cavity.

[0029] Similar cavities 25 and 26 are defined in the proximal body 18 to house the transmission element 35 and the power source 40, respectively. Wiring channels 27 and 28 pass between the cavities to receive wires 33 and 37, respectively, connected between the elements. The cavities are closed and the elements embedded within a suitable biocompatible material. In a preferred embodiment, bone cement is used to fill the cavities when the sensor 30, transmission element 35 and power supply 40 are housed therein.

[0030] The transmission element 35 can take on a variety of forms, all with the purpose of transmitting a signal indicative of the ambient condition within the joint. In a preferred embodiment, the transmission element is a modulator/transmitter that serves to convert the voltage signal received from the temperature sensor into a transmission signal, such as a radio-frequency wave (rf sig-

nal), transmitted to a receiver positioned outside the patient's body. Preferably, the transmission element 35 is arranged on a small printed circuit board, which can be of the type commercially available from Advanced Circuits of Aurora, Colorado. The particular layout and design of the circuit board will depend upon factors such as the type of electronic components used for the signal source and for modulating the sensor signal.

[0031] Suitable internal modulator/transmitters are commercially available from Texas Instruments in the form of electronic chips. While the specific characteristics of the internal modulator/transmitter may vary, the components must be appropriate for implantation within a patient, must transmit at a known frequency and should not consume excessive power. In addition, the transmitter component must be capable of transmitting an rf signal through the patient's body, as well as through the endoprosthesis and/or the potting surrounding the transmission element 35 within the cavity 25. In certain embodiments, the necessary transmission range is not very great, since the receiver will be carried on the patient's body (see below). However, it is contemplated that transmission element may be capable of longer range transmissions, such as to a remote receiver connected to a PC for use in analysing the ambient conditions within the joint. Various antenna configurations for the transmission element 35 are contemplated by the invention. For instance, the antenna can be situated at the distal end of the implant, where a material that does not impede or restrict the transmissions can replace the metal of the implant. In another configuration, a substantial portion of the implant itself can act as an antenna.

[0032] Block circuit diagrams of certain embodiments of the invention are shown in FIGS. 3, 4a and 4b. As depicted in FIG. 3, the temperature sensor 30 can operate as a variable resistor receiving an input voltage from the power source 40. The sensor 30 can be directly electrically connected to the power source or can be connected through the transmission element 25. The sensor 30 produces an output voltage V_{OUT} that is fed to a conditioning circuit 45. The conditioning circuit 45 can constitute the modulator discussed above that converts the voltage V_{OUT} to an rf signal. In this case, the output 46 is an rf signal that is transmitted by an antenna 48, depicted in FIG. 4a. The antenna 48 transmits a signal outside the joint to an external receiver. The transmitted signal or transmission in this embodiment is continuous so that the joint temperature can be continuously monitored.

[0033] In an alternative embodiment, a transmission is only if the sensed temperature exceeds a predetermined threshold. In this instance, the conditioning circuit 45 can provide its output 46 to a comparator circuit 50, as shown in FIG. 4b. This comparator circuit 50 can receive a reference voltage V_{REF} from the power source. In this case, the output signal 46 is a voltage, which can be the voltage V_{OUT} . The reference voltage V_{REF} can be calibrated to correspond to a threshold temperature as sensed by the temperature sensor. The reference volt-

age may not necessarily correspond to the actual temperature within the joint, since the temperature sensed by the sensor embedded within the implant body will depend upon the thermal conductivity of the potting material and/or implant material. Nevertheless, an anticipated sensor temperature can be calibrated to an ambient temperature within the joint, and this anticipated temperature translated to a reference voltage V_{REF} that would be generated by the sensor if it was exposed to the threshold temperature.

[0034] The output 51 of this comparator circuit can be fed to a transmitter 48. In this case, the comparator circuit 50 would include the modulator feature described above. As an adjunct or another alternative, the output 51 can be a voltage that is fed to an alarm 52 that is resident with the patient, but not necessarily directly associated with the endoprosthesis.

[0035] In the most preferred system, the conditioning circuitry 45 is directly coupled to the antenna 48 to continuously transmit a signal indicative of the temperature within the joint. This signal can be received by an external device, such as the devices 60 and 70 shown in FIGS. 5 and 6, respectively. The device 60 in FIG. 5 includes an antenna 62 for receiving the rf signal from the transmission element 35. A power supply 68 supplies power to the antenna, as well as to the other electrical components of the device 60. In addition, the power supply 68 can be configured to provide power to a passive power source 40 mounted within the implant. Thus, the power supply 68 can include a power transmission coil that creates an electromagnetic field intercepted by the passive power source 40. The power supply 68 and the passive power source 40 can utilize RFID tag technology. In some RFID tag systems, the power transmission and signal transmission functions are combined through load modulation. In some passive power systems, the power transmission occurs through dipole antenna transmissions from the external device, while the sensor signal is transmitted through backscatter modulation. The conditioning circuit 45 of the implanted portion of the inventive system can be modified to accomplish either of these forms of power and data transmission.

[0036] Returning to FIG. 5, the external device 60 can include an alarm 64 and/or a memory 66. The alarm 64 can provide a sensible signal, such as an audible or touch sensible signal. The alarm 64 can include a piezo-electric component that produces vibration that can be heard and/or felt. A suitable alarm can be the type used in cellular phones, provided that a sufficient power supply is available. The memory 66 can be configured to store a sampling of the received transmission to provide a history of the ambient conditions within the joint. This memory 66 can then be extracted by linking the external device 60 to a PC, for instance. This information can be used by medical personnel to track the response of the endoprosthesis and instrumented joint to exertion by the patient. In addition, analysis of this ambient condition history can diagnose potential problems with the implant or with

the patient's activity regimen.

[0037] In an alternative embodiment, an external device 70 includes an antenna 72 and analysis circuitry 74, as shown in FIG. 6. This analysis circuitry can evaluate the incoming ambient condition signal received by the antenna 72 and determine a course of action based on that signal. For instance, the analysis circuitry can include a comparator circuit, such as the circuit 50 shown in FIG. 4b, in which the received signal is compared to a threshold value. If the incoming signal exceeds the threshold value, the analysis circuit can send data to an on-board memory 78 and/or activate an alarm 76. The memory and alarm can be configured as described above. A power supply 80 provides power to all of the electronic components of the device 70, and can also serve as a power coil for a passive power source on the endoprosthesis. The analysis circuitry 74 may also provide a link to a visual display device 79. The device 79 can be part of the external device 70 or can be separate from the device and only operable when linked to the analysis circuit 74. In a preferred embodiment, the display device is an LED or LCD array that displays a visual symbol. In the case of a temperature sensor system, the array can display the ambient temperature within the joint. The display device 79 can also display alphanumeric messages indicative of the current condition within the joint, such as "NORMAL" or "WARNING".

[0038] The external devices 60 and 70 can be housed within a case and sized to be worn by the patient. For instance, the case housing either device can be strapped around the patient's thigh so that it will be maintained in close proximity to the temperature sensor 30 and transmission element 35. Alternatively, the external devices 60, 70 can be supported on a belt spanning the patient's waist. If the broadcast range of the transmission element is adequate, the external device can be carried anywhere on the person, much like a pager or cell phone.

[0039] It is contemplated that the present invention can be used in any mammalian joint, including human and animal joints. For instance, the system can be used with a knee endoprosthesis 85, as shown in FIG. 7. By way of background, a typical knee endoprosthesis includes a proximal tibial component 87 that is affixed to the tibia T, distal femoral component 89 that is mounted to the femur F, and an intermediate tibial bearing 91. The tibial bearing 91 and the distal femoral component 89 form the articulating interface 93 as the tibia T moves relative to the femur F. It is at this location that friction between the two components can increase the ambient temperature within the knee joint.

[0040] The proximal tibial component 87 includes a tibial temperature sensor 95 that is embedded within the component, preferably as close as possible to the articulating surface 93. The sensor is connected to a transmission element 97 that is embedded within the tibial component as well. The sensor 95 and transmission element 97 can be stacked within a bore defined in the proximal tibial component 87.

[0041] Alternatively, or additionally, a temperature sensor 99 can be disposed in the distal femoral component 89. Its associated transmission element 101 can be mounted within a bore defined in the distal end of the femur F, as shown in FIG. 7. The transmission elements 97 and 101 can be configured similar to the transmission element 35 discussed above. A power source, such as the power source 40, can also be provided with both transmission elements. The variation incorporating the sensor 99 illustrates that the ambient condition sensing system of the present invention can be mounted within the patient's natural bone.

[0042] The embodiments of the invention described above utilize a temperature sensor to ascertain the ambient temperature within the instrumented joint. Although a single sensor is described above, the implant or prosthetic joint can include several temperature sensors placed at strategic locations. The sensors can generate sensor signals with a particular signature to identify the location of the sensor.

[0043] The invention also contemplates a variety of condition sensors for evaluating other ambient conditions of the joint. For example, the sensor 30 can be a pH sensor to evaluate the acidic or alkaline characteristic of the joint environment. Deviation from an expected pH value may indicate a medical condition that requires attention, such as the presence of infection within the joint. A pH sensor must necessarily be in contact with the tissue surrounding the implant. In this case, the sensor can be flush mounted on an exposed surface of the implant. In the context of the hip implant, the sensor 30 can be moved from the neck 19 to the upper end of the proximal body 18 where it will contact the soft tissues and synovial fluid surrounding the implant. Alternatively, the sensor can be placed apart from the implant in contact with pertinent body tissues. For the knee implant, the sensor can be positioned on an exposed edge of the proximal tibial component 87.

[0044] The power requirements for the pH sensor may be different from a temperature sensor. Many pH sensors rely upon a chemical reaction to generate a current. One such pH sensor that is suited for biomedical applications is an iridium oxide based potentiometric electrode sold by SenslRox Inc. Other similar sensors can be utilized that sense the presence of certain chemicals.

[0045] In one application of the present invention, the ambient condition sensor is constantly operating throughout the life of the endoprosthesis. As explained above, an internal or external alarm can be provided to notify the patient of a potentially hazardous temperature level within the joint. Alternatively, an external receiver or reader can be provided to receive signals indicative of temperature or other ambient conditions (such as pH) within the joint.

[0046] As a further alternative, the sensor system can be used only for diagnostic purposes. In other word, the ambient condition sensor system is activated only intermittently, and more specifically, it is activated by a phy-

sician during a visit to evaluate the success of a newly implanted endoprosthesis. In this case, the power source 40 for the implanted system can be a passive system that is activated by the external device, as described above. The patient can undergo a treadmill evaluation, during which the physician monitors the joint temperature. Where the sensor is a pH sensor, the surgeon can simply activate the implant sensor and assess the transmitted pH data during the treadmill evaluation. In other protocols, a directly powered system can generate and store the condition data for later downloading by the surgeon.

[0047] In the embodiments described above, a single type of sensor is used to generate ambient condition data. Alternatively, several different sensors can be incorporated into the endoprosthesis. Each of the sensors can be provided with a unique signature so that the data transmitted from the system can be easily interpreted. For example, an endoprosthesis can be provided with a temperature sensor and a pH sensor.

[0048] Other types of sensors are also contemplated by the invention, where the sensors are capable of evaluating certain ambient conditions within a joint or in surrounding tissue of body spaces. For instance, the sensor can respond to the presence of a particular gene, protein, chemical, bacteria or similar biological substance. A sensor can also be provided that senses the presence of non-biological chemicals or materials. The nature of the ambient condition will determine the type of sensor and the nature of the information obtained about the endoprosthesis and its surroundings.

[0049] The invention also provides a joint prosthesis and system for sensing a condition within a mammalian joint having features which are set out in the following numbered clauses:

Clause 1: A joint endoprosthesis comprising:

a body configured to replace a portion of a mammalian joint;
 at least one sensor supported by said body, said sensor adapted to sense an ambient condition of the mammalian joint and to generate a condition signal indicative of the sensed condition;
 and
 a transmission element connected to said sensor to receive said condition signal and operable to transmit a signal indicative of said condition signal.

Clause 2: The joint endoprosthesis of clause 1, wherein said sensor is a temperature sensor and the ambient condition is temperature.

Clause 3: The joint endoprosthesis of clause 1, wherein said sensor is a pH sensor and the ambient condition is pH.

Clause 4: The joint endoprosthesis of clause 1, wherein said sensor is configured to determine the presence of a biological material.

Clause 5: The joint endoprosthesis of clause 1, wherein said sensor is a configured to sense the presence of a pre-determined liquid.

Clause 6: The joint endoprosthesis of clause 1, wherein said body is a component of a joint prosthesis selected from the group of a hip prosthesis, a knee prosthesis, a shoulder prosthesis and an elbow prosthesis.

Clause 7: The joint endoprosthesis of clause 1, wherein said transmission element includes an alarm.

Clause 8: The joint endoprosthesis of clause 1, wherein said transmission element includes a transmitter supported by said body and configured to transmit a signal to a receiver located outside the joint indicative of said condition signal.

Clause 9: The joint endoprosthesis of clause 8, wherein said transmission element includes an antenna and a power source providing power to said antenna.

Clause 10: The joint endoprosthesis of clause 1, further comprising a power source supported by said body and connected to provide power to said sensor and said communication element.

Clause 11: The joint endoprosthesis of clause 10, wherein said power source is a passive power source.

Clause 12: A system for sensing a condition within a mammalian joint comprising:

- an endoprosthesis as claimed in clause 1,
- a transmitter connected to said sensor to receive said condition signal and operable to transmit a transmission signal outside the joint indicative of said condition signal;
- a receiver disposed outside the joint for receiving said transmission signal; and
- translation circuitry for translating said transmission signal to a human sensible signal.

Clause 13: The system for determining a condition within a mammalian joint of clause 12 wherein said translation circuitry includes an alarm, which is preferably configured to produce an audible signal or a vibration.

Clause 14: The system for sensing a condition within

a mammalian joint of clause 12, wherein said translation circuitry includes a display configured to produce a visually sensible signal.

Claims

1. A knee endoprosthesis comprising:
 - a component configured to replace a portion of a mammalian knee joint;
 - at least one sensor supported by the component, the sensor being adapted to sense an ambient condition of the joint and to generate a condition signal indicative of the sensed condition; and
 - a transmission element connected to the sensor to receive the condition signal from the sensor and operable to transmit a transmission signal indicative of the condition signal.
2. The knee endoprosthesis of claim 1, in which the component of the knee prosthesis is a proximal tibial component having an articulating surface which can articulate against a corresponding surface of a distal femoral component, and in which the sensor is embedded within the proximal tibial component close to the articulating surface.
3. The knee endoprosthesis of claim 2, in which the proximal tibial component includes a bore, the sensor and transmission element being stacked within the bore.
4. The knee endoprosthesis of claim 1 or 2, in which the component of the knee prosthesis is a distal femoral component having an articulating surface which can articulate against a corresponding surface of a proximal tibial component, and in which the sensor is embedded within the distal femoral component close to the articulating surface.
5. The knee endoprosthesis of claim 1, in which the sensor is a temperature sensor and the ambient condition is temperature.
6. The knee endoprosthesis of claim 1, in which the sensor is a pH sensor and the ambient condition is pH.
7. The knee endoprosthesis of claim 1, in which the sensor is configured to sense the presence of at least one of a biological material or a pre-determined liquid.
8. The knee endoprosthesis of claim 1, in which the transmission element includes an alarm.

9. The knee endoprosthesis of claim 1, in which the transmission element includes a transmitter supported by the component and configured to transmit a signal to a receiver located outside the joint indicative of the condition signal. 5
10. The knee endoprosthesis of claim 1, in which the transmission element includes an antenna and a power source providing power to the antenna. 10
11. The knee endoprosthesis of claim 1, further comprising a power source supported by the component and connected to provide power to the sensor and the communication element. 15
12. The knee endoprosthesis of claim 10, in which the power source is a passive power source.
13. A system for sensing a condition within a mammalian knee joint comprising: 20
- a knee endoprosthesis as claimed in claim 1;
 - a transmitter connected to the sensor to receive the condition signal and operable to transmit a transmission signal out of the joint indicative of the condition signal; 25
 - a receiver disposed outside the joint for receiving the transmission signal,
 - and
 - translation circuitry for translating the transmission signal to a signal that can be sensed by humans. 30
14. The system for sensing a condition within a mammalian knee joint of claim 13, in which the translation circuitry includes an alarm, which is preferably configured to produce an audible signal or vibration. 35
15. The system for sensing a condition within a mammalian knee joint of claim 13, in which the translation circuitry includes a display configured to produce a visually sensible signal. 40

45

50

55




FIG. 1




FIG. 2




FIG. 3




FIG. 4a




FIG. 4b



EUROPEAN SEARCH REPORT

Application Number
EP 17 17 3896

5

10

15

20

25

30

35

40

45

50

55

DOCUMENTS CONSIDERED TO BE RELEVANT			
Category	Citation of document with indication, where appropriate, of relevant passages	Relevant to claim	CLASSIFICATION OF THE APPLICATION (IPC)
X	US 5 360 016 A (KOVACEVIC NEBOJSA [US]) 1 November 1994 (1994-11-01) * column 3, lines 51-61 * * column 4, lines 24-49 * * column 6, lines 1-6, 21-46 * * figures 1-3, 11 *	1-4,9, 13,15 6,8,14	INV. A61B5/00 A61F2/46 A61F2/38
X	US 2004/019382 A1 (AMIROUCHE FARID [US] ET AL) 29 January 2004 (2004-01-29) * paragraphs [0028] - [0031], [0034], [0035], [0039], [0042], [0043] * * figures 1-3, 5 * * claims 33, 36 *	1-3,9, 11,13,15	
X	US 2002/024450 A1 (TOWNSEND CHRISTOPHER P [US] ET AL) 28 February 2002 (2002-02-28) * paragraphs [0028] - [0031], [0052] - [0054] * * figures 1a, 1b, 4 *	1,2,5,7, 9-13,15	
Y	US 6 447 448 B1 (ISHIKAWA AKIRA [US] ET AL) 10 September 2002 (2002-09-10) * column 8, lines 14-19 * * figures 4A, 6 *	6	TECHNICAL FIELDS SEARCHED (IPC) A61B A61F
Y	US 2003/176783 A1 (HU QINGMAO [SG]) 18 September 2003 (2003-09-18) * paragraphs [0049], [0050], [0055] * * figure 1 *	8,14	
The present search report has been drawn up for all claims			
Place of search The Hague		Date of completion of the search 4 September 2017	Examiner Trattner, Barbara
CATEGORY OF CITED DOCUMENTS X : particularly relevant if taken alone Y : particularly relevant if combined with another document of the same category A : technological background O : non-written disclosure P : intermediate document		T : theory or principle underlying the invention E : earlier patent document, but published on, or after the filing date D : document cited in the application L : document cited for other reasons & : member of the same patent family, corresponding document	

EPO FORM 1503 03/02 (P04C01)

ANNEX TO THE EUROPEAN SEARCH REPORT
ON EUROPEAN PATENT APPLICATION NO.

EP 17 17 3896

5 This annex lists the patent family members relating to the patent documents cited in the above-mentioned European search report.
The members are as contained in the European Patent Office EDP file on
The European Patent Office is in no way liable for these particulars which are merely given for the purpose of information.

04-09-2017

Patent document cited in search report	Publication date	Patent family member(s)	Publication date
US 5360016 A	01-11-1994	US 5197488 A	30-03-1993
		US 5360016 A	01-11-1994
		WO 9217113 A1	15-10-1992

US 2004019382 A1	29-01-2004	AU 2003228341 A1	08-10-2003
		EP 1487385 A2	22-12-2004
		JP 2005520630 A	14-07-2005
		US 2004019382 A1	29-01-2004
		US 2009299483 A1	03-12-2009
		US 2012290088 A1	15-11-2012
US 2002024450 A1	28-02-2002	WO 03079940 A2	02-10-2003
		US 2002024450 A1	28-02-2002
		US 2009112523 A1	30-04-2009
US 6447448 B1	10-09-2002	US 2010165593 A1	01-07-2010
		AU 2400200 A	31-07-2000
		US 6447448 B1	10-09-2002
US 2003176783 A1	18-09-2003	WO 0038570 A1	06-07-2000
		CA 2416139 A1	10-01-2002
		EP 1296608 A1	02-04-2003
		JP 2004507288 A	11-03-2004
		US 2003176783 A1	18-09-2003
		US 0202028 A1	10-01-2002

EPO FORM P0459

For more details about this annex : see Official Journal of the European Patent Office, No. 12/82

REFERENCES CITED IN THE DESCRIPTION

This list of references cited by the applicant is for the reader's convenience only. It does not form part of the European patent document. Even though great care has been taken in compiling the references, errors or omissions cannot be excluded and the EPO disclaims all liability in this regard.

Non-patent literature cited in the description

- **ERIKSSON et al.** *Scand J Plast. Reconstr. Surg.*, 1984, vol. 18 (3), 261-8 **[0021]**
- **BERGMANN et al.** *Journal of Biomechanics*, 2001, vol. 34, 421-428 **[0022]**
- **LU et al.** *Proc. Instn. Mech. Engrs.*, 1997, vol. 211, 101-108 **[0022]**

专利名称(译)	膝关节内置假体与环境条件感测		
公开(公告)号	EP3231360A1	公开(公告)日	2017-10-18
申请号	EP2017173896	申请日	2005-03-24
[标]申请(专利权)人(译)	德普伊产品公司		
申请(专利权)人(译)	DePuy公司PRODUCTS, INC.		
当前申请(专利权)人(译)	DePuy公司PRODUCTS, INC.		
[标]发明人	DISILVESTRO MARK LIAO YEN SHUO		
发明人	DISILVESTRO, MARK LIAO, YEN-SHUO		
IPC分类号	A61B5/00 A61F2/46 A61F2/38 A61B5/01 A61B5/07 A61B17/00 A61B17/56 A61F2/00 A61F2/02 A61F2/30 A61F2/32 A61F2/34 A61F2/36 A61F2/40 A61F2/42 A61F2/48 A61F2/76 G08B1/08		
CPC分类号	A61B5/0008 A61B5/01 A61B5/076 A61B5/14539 A61B5/4528 A61B2017/00084 A61F2/0095 A61F2/32 A61F2/34 A61F2/36 A61F2/3662 A61F2/367 A61F2/38 A61F2/3804 A61F2/3859 A61F2/389 A61F2/40 A61F2/4657 A61F2002/30326 A61F2002/30449 A61F2002/30589 A61F2002/30593 A61F2002/30668 A61F2002/3067 A61F2002/30698 A61F2002/30878 A61F2002/30884 A61F2002/30892 A61F2002/3611 A61F2002/3625 A61F2002/3631 A61F2002/3647 A61F2002/365 A61F2002/4661 A61F2002/4672 A61F2002/4674 A61F2002/4696 A61F2002/48 A61F2002/481 A61F2002/482 A61F2002/488 A61F2220/005 A61F2250/0001 A61F2250/0002 A61F2250/0037 A61F2250/008 Y10S128/903		
优先权	10/813803 2004-03-31 US		
外部链接	Espacenet		

摘要(译)

用于监测哺乳动物关节的环境条件的系统，特别是已经装配有关节内置假体的关节，包括由关节内置假体的部件支撑的传感器。该系统包括传输元件，该传输元件也支撑在患者体内，优选地在内置假体体内。传输元件在仪表化关节内传输指示所感测的环境条件的信号。例如，传感器可以是温度传感器，用于在患者的活动或锻炼期间评估关节内的温度，例如髌关节。

