



(51) International Patent Classification:

A61B 5/00 (2006.01) G06F 19/00 (2011.01)
A61B 5/021 (2006.01)

(21) International Application Number:

PCT/US2017/042221

(22) International Filing Date:

14 July 2017 (14.07.2017)

(25) Filing Language:

English

(26) Publication Language:

English

(30) Priority Data:

62/365,815 22 July 2016 (22.07.2016) US
15/649,438 13 July 2017 (13.07.2017) US

(71) Applicant: EDWARDS LIFESCIENCES CORPORATION [US/US]; One Edwards Way, Irvine, CA 92614 (US).

(72) Inventors: AL HATIB, Feras; Edwards Lifesciences, One Edwards Way, Legal Department, Irvine, CA 92614 (US).
JIAN, Zhongping; Edwards Lifesciences, One Edwards Way, Legal Department, Irvine, CA 92614 (US).

(74) Agent: CRAPENHOFT, Michael et al.; Edwards Lifesciences, One Edwards Way, Irvine, CA 92614 (US).

(81) Designated States (unless otherwise indicated, for every kind of national protection available): AE, AG, AL, AM,

AO, AT, AU, AZ, BA, BB, BG, BH, BN, BR, BW, BY, BZ, CA, CH, CL, CN, CO, CR, CU, CZ, DE, DJ, DK, DM, DO, DZ, EC, EE, EG, ES, FI, GB, GD, GE, GH, GM, GT, HN, HR, HU, ID, IL, IN, IR, IS, JO, JP, KE, KG, KH, KN, KP, KR, KW, KZ, LA, LC, LK, LR, LS, LU, LY, MA, MD, ME, MG, MK, MN, MW, MX, MY, MZ, NA, NG, NI, NO, NZ, OM, PA, PE, PG, PH, PL, PT, QA, RO, RS, RU, RW, SA, SC, SD, SE, SG, SK, SL, SM, ST, SV, SY, TH, TJ, TM, TN, TR, TT, TZ, UA, UG, US, UZ, VC, VN, ZA, ZM, ZW.


(84) Designated States (unless otherwise indicated, for every kind of regional protection available): ARIPO (BW, GH, GM, KE, LR, LS, MW, MZ, NA, RW, SD, SL, ST, SZ, TZ, UG, ZM, ZW), Eurasian (AM, AZ, BY, KG, KZ, RU, TJ, TM), European (AL, AT, BE, BG, CH, CY, CZ, DE, DK, EE, ES, FI, FR, GB, GR, HR, HU, IE, IS, IT, LT, LU, LV, MC, MK, MT, NL, NO, PL, PT, RO, RS, SE, SI, SK, SM, TR), OAPI (BF, BJ, CF, CG, CI, CM, GA, GN, GQ, GW, KM, ML, MR, NE, SN, TD, TG).

Published:

— with international search report (Art. 21(3))

(54) Title: MEAN ARTERIAL PRESSURE (MAP) DERIVER PREDICTION OF FUTURE HYPOTENSION

Fig. 1



(57) Abstract: There are provided systems and methods for performing mean arterial pressure (MAP) derived prediction of future hypotension. Such a system includes a hardware unit including a hardware processor and a system memory, a hypotension prediction software code stored in the system memory, and a sensory alarm. The hardware processor is configured to execute the hypotension prediction software code to receive MAP data of the living subject, and to transform the MAP data to one or more parameters predictive of a future hypotension event of the living subject. The hardware processor is further configured to execute the hypotension prediction software code to determine a risk score of the living subject corresponding to the probability of the future hypotension event based on at least some of the one or more parameters, and to invoke the sensory alarm if the risk score of the living subject satisfies a predetermined risk criteria.

- 1 -

MEAN ARTERIAL PRESSURE (MAP) DERIVED PREDICTION OF FUTURE HYPOTENSION

5

BACKGROUND

Hypotension, or low blood pressure, can be a harbinger of serious medical complications, and even mortality, for patients undergoing surgery and those acutely or critically ill patients receiving treatment in an intensive care unit (ICU). The dangers associated with the occurrence of hypotension in a patient are due both to the potential injury caused by the hypotension itself and to the many serious underlying medical disorders that the occurrence of hypotension may signify.

In and of itself, hypotension in surgical patients or critically ill patients is a serious medical condition. For example, in the operating room (OR) setting, hypotension during surgery is associated with increased mortality and organ injury. Even short durations of extreme hypotension during surgery are associated with acute kidney injury and myocardial injury. Among critically ill patients, in-hospital mortality may be nearly doubled for patients experiencing hypotension after emergency intubation. For surgical patients and seriously ill patients alike, hypotension, if not corrected, can impair organ perfusion, resulting in irreversible ischemic damage, neurological deficit, cardiomyopathy, and renal impairment.

In addition to posing serious risks to surgical patients and critically ill patients in its own right, hypotension can be a symptom of one or more other

- 2 -

serious underlying medical conditions. Examples of underlying conditions for which hypotension may serve as an acute symptom include sepsis, myocardial infarction, cardiac arrhythmia, pulmonary embolism, hemorrhage, dehydration, anaphylaxis, acute reaction to medication, hypovolemia, insufficient cardiac output, and vasodilatory shock. Due to its association with such a variety of serious medical conditions, hypotension is relatively common, and is often seen as one of the first signs of patient deterioration in the OR and ICU. For instance, hypotension is seen in up to approximately thirty-three percent of surgeries overall, and up to eighty-five percent in high risk surgeries. Among ICU patients, hypotension occurs in from approximately twenty-four percent to approximately eighty-five percent of all patients, with the eighty-five percent occurrence being seen among critically ill patients.

Conventional patient monitoring for hypotension in the OR and ICU settings can include continuous or periodic blood pressure measurement. However, such monitoring, whether continuous or periodic, typically provides no more than a real-time assessment. As a result, hypotension in a surgical patient or critically ill patient is usually detected only after it begins to occur, so that remedial measures and interventions cannot be initiated until the patient has entered a hypotensive state. Although, as noted above, extreme hypotension can have potentially devastating medical consequences quite quickly, even relatively

- 3 -

mild levels of hypotension can herald or precipitate cardiac arrest in patients with limited cardiac reserve.

In view of the frequency with which hypotension is observed to occur in the OR and ICU settings, and due to the serious and sometimes immediate
5 medical consequences that can result when it does occurs, a solution enabling prediction of a future hypotension event, before its occurrence, is highly desirable.

SUMMARY

There are provided systems and methods for performing mean arterial pressure (MAP) derived prediction of future hypotension, substantially as shown
10 in and/or described in connection with at least one of the figures, and as set forth more completely in the claims.

- 4 -

BRIEF DESCRIPTION OF THE DRAWINGS

Figure 1 shows a diagram of an exemplary system for performing mean arterial pressure (MAP) derived prediction of future hypotension, according to one implementation;

5 Figure 2A shows an exemplary implementation for non-invasively detecting arterial pressure at an extremity of a living subject;

Figure 2B shows an exemplary implementation for performing minimally invasive detection of arterial pressure of a living subject;

Figure 3 shows an exemplary system and a computer-readable non-
10 transitory medium including instructions enabling performance of MAP derived prediction of future hypotension;

Figure 4 is a flowchart presenting an exemplary method for use by a monitoring and evaluation system to perform MAP derived prediction of future hypotension; and

15 Figure 5 shows a trace of an arterial pressure waveform including exemplary indicia corresponding to the probability of future hypotension in a living subject.

- 5 -

DETAILED DESCRIPTION

The following description contains specific information pertaining to implementations in the present disclosure. One skilled in the art will recognize that the present disclosure may be implemented in a manner different from that specifically discussed herein. The drawings in the present application and their accompanying detailed description are directed to merely exemplary implementations. Unless noted otherwise, like or corresponding elements among the figures may be indicated by like or corresponding reference numerals. Moreover, the drawings and illustrations in the present application are generally not to scale, and are not intended to correspond to actual relative dimensions.

The present application discloses systems and methods for performing mean arterial pressure (hereinafter “MAP”) derived prediction of future hypotension. By transforming MAP data of a living subject to one or more parameters predictive of a future hypotension event of the living subject, the present application discloses a solution enabling determination of a risk score corresponding to the probability that the future hypotension event will occur. In addition, by receiving and transforming the MAP data of the living subject on an ongoing basis, the solution disclosed by the present application enables substantially continuous hypotension risk monitoring of the living subject. Moreover, by invoking a sensory alarm if the risk score of the living subject satisfies a predetermined risk criteria, the present application discloses a solution

- 6 -

that provides an early warning of a future hypotension event of the living subject, thereby advantageously enabling health care workers to prepare a timely and effective intervention.

Figure 1 shows a diagram of an exemplary system for performing MAP
5 derived prediction of future hypotension, according to one implementation. Monitoring and evaluation system 102 is implemented within patient care environment 100, which may be an intensive care unit (ICU) or operating room (OR), for example. As shown in Figure 1, in addition to monitoring and evaluation system 102, patient care environment 100 includes patient 130
10 (hereinafter “living subject 130”), and healthcare worker 150 (hereinafter “user 150”) trained to utilize monitoring and evaluation system 102.

As further shown in Figure 1, monitoring and evaluation system 102 includes system processor 106, implemented as a hardware processor, and system memory 108 storing hypotension prediction software code 110 for processing
15 MAP data 112. Monitoring and evaluation system 102 also includes display 126 providing user interface 120. As will be discussed in greater detail below, user interface 120 is configured to receive inputs 152 from user 150, and to provide sensory alarm 128 if a risk score predictive of a future hypotension event of living subject 130 satisfies a predetermined risk criteria. Also shown in Figure 2 are
20 analog-to-digital converter 122 (hereinafter “ADC 122”) and digital-to-analog converter 124 (hereinafter “DAC 124”) used by monitoring and evaluation system

- 7 -

102 to process data associated with determination and display of the hypotension risk score of living subject 130.

In addition, Figure 1 shows exemplary hemodynamic sensor 140 attached to living subject 130. It is noted that hemodynamic sensor 140 may be a non-invasive or minimally invasive sensor attached to living subject 130. In one implementation, as represented in Figure 1, hemodynamic sensor 140 may be attached non-invasively at an extremity of living subject 130, such as a wrist or finger of living subject 130. Although not explicitly shown in Figure 1, in other implementations, hemodynamic sensor 140 may be attached non-invasively at an ankle or toe of living subject 130. Figure 1 further shows hemodynamic signals 142 received by monitoring and evaluation system 102, which may include signals corresponding to the arterial pressure of living subject 130. Monitoring and evaluation system 102 and hemodynamic sensor 140 may be configured such that hemodynamic signals 142 may be received by monitoring and evaluation system 102 wirelessly, or via a wired connection with hemodynamic sensor 140.

System processor 106 is configured to execute hypotension prediction software code 110 to receive MAP data 112 of living subject 130. System processor 106 is further configured to execute hypotension prediction software code 110 to transform MAP data 112 to one or more parameters predictive of a future hypotension event by living subject 130. For example, hypotension prediction software code 110 may transform MAP data 112 to one or more

- 8 -

parameters predictive of a hypotension event by living subject 130 occurring in the next approximately one to five minutes, or up to approximately thirty minutes in the future.

System processor 106 is also configured to execute hypotension prediction software code 110 to determine a risk score of living subject 130 corresponding to the probability of the future hypotension event based on at least some, i.e., at least a subset, of the one or more parameters derived from MAP data 112. In addition, system processor 106 is configured to execute hypotension prediction software code 110 to invoke sensory alarm 128 if the risk score of living subject 130 satisfies a predetermined risk criteria.

In various implementations, sensory alarm 128 may be implemented as one or more of a visual alarm, an audible alarm, and a haptic alarm. For example, when implemented to provide a visual alarm, sensory alarm 128 may be invoked as flashing and/or colored graphics shown by user interface 120 on display 126, and/or may include displaying the risk score via user interface 120 on display 126. When implemented to provide an audible alarm, sensory alarm 128 may be invoked as any suitable warning sound, such as a siren or repeated tone. Moreover, when implemented to provide a haptic alarm, sensory alarm 128 may cause hardware unit 104 to vibrate or otherwise deliver a physical impulse perceptible to user 150.

- 9 -

It is noted that the risk score of living subject 130 is determined based on parameters derived from MAP data 112 of living subject 130, which in turn is determined based on hemodynamic signals 142 of living subject 130 received from hemodynamic sensor 140. Consequently, according to the inventive
5 concepts disclosed by the present application, hardware processor 106 of monitoring and evaluation system 102 is configured to execute hypotension prediction software code 110 to determine the risk score of living subject 130 without comparison with data corresponding to hypotension in other living subjects. In other words, hypotension prediction software code 110 determines
10 the risk score of living subject 130 based on parameters derived from MAP data 112 without reference to a hypotension patient database storing information regarding hypotension in patients other than living subject 130.

In addition to the functionality described above, in some implementations, hardware processor 106 may be configured to execute hypotension prediction
15 software code 110 to identify a most probable cause of the future hypotension event of living subject 130. For example, based on indicia included in hemodynamic signals 142, hypotension prediction software code 110 may be able to identify poor vascular tone, low blood volume, or reduced cardiac contractility, to name a few exemplary causes, as a most probable cause of a predicted future
20 hypotension event. Furthermore, in some implementations, hardware processor 106 may be configured to execute hypotension prediction software code 110 to

- 10 -

recommend a medical intervention for preventing the future hypotension event of living subject 130. With respect to the first and second example causes of hypotension identified above, administration of a vasoconstrictor may be recommended if poor vascular tone is detected, while administration of saline or whole blood may be recommend if low blood volume is identified as a most probable cause of the predicted future hypotension event. In one implementation, system 102 may automatically administer the medical intervention for preventing the future hypotension event of living subject 130. For example, in response to detecting a future hypotension event, system 102 may transmit a signal causing an administration of a vasoconstrictor if poor vascular tone is detected or causing an administration of saline or whole blood if low blood volume is identified as the issue.

Referring to Figure 2A, Figure 2A shows an exemplary implementation for sensing arterial pressure non-invasively at an extremity of a living subject. Patient care environment 200A, in Figure 2A, shows system 202 including hypotension prediction software code 210 receiving MAP data 212 of living subject 230. As further shown by Figure 2A, the arterial pressure of living subject 230 is detected non-invasively at finger 232 of living subject 230 using hemodynamic sensing cuff 240a. Also shown in Figure 2A are ADC 222 of system 202, and hemodynamic signals 242 received by system 202 from hemodynamic sensing cuff 240a.

- 11 -

Living subject 230, hemodynamic signals 242, and hemodynamic sensing cuff 240a correspond respectively in general to living subject 130, hemodynamic signals 142, and hemodynamic sensor 140, in Figure 1, and may share any of the characteristics attributed to those corresponding features in the present application. Moreover, system 202 including ADC 222 and hypotension prediction software code 210 receiving MAP data 212, in Figure 2A, corresponds in general to monitoring and evaluation system 102 including ADC 122 and hypotension prediction software code 110 receiving MAP data 112, in Figure 1, and may share any of the characteristics attributed to that corresponding feature in the present application.

According to the implementation shown in Figure 2A, hemodynamic sensing cuff 240a is designed to sense an arterial pressure of living subject 230 non-invasively at finger 232 of living subject 230. Moreover, as shown in Figure 2A, hemodynamic sensing cuff 240a may take the form of a small, lightweight, and comfortable hemodynamic sensor suitable for extended wear by living subject 230. It is noted that although hemodynamic sensing cuff 240a is shown as a finger cuff, in Figure 2A, in other implementations, hemodynamic sensing cuff 240a may be suitably adapted as a wrist, ankle, or toe cuff for attachment to living subject 230.

It is further noted that the advantageous extended wear capability described above for hemodynamic sensing cuff 240 when implemented as a finger cuff may

- 12 -

also be attributed to wrist, ankle, and toe cuff implementations. As a result, hemodynamic sensing cuff 240a may be configured to provide substantially continuous beat-to-beat monitoring of the arterial pressure of living subject 230 over an extended period of time, such as minutes or hours, for example.

5 Continuing to Figure 2B, Figure 2B shows an exemplary implementation for performing minimally invasive detection of arterial pressure of a living subject. Patient care environment 200B, in Figure 2B, shows system 202 including hypotension prediction software code 210 receiving MAP data 212 of living subject 230. As further shown by Figure 2B, the arterial pressure of living
10 subject 230 is detected via minimally invasive hemodynamic sensor 240b. Also shown in Figure 2B are ADC 222 of system 202, and hemodynamic signals 242 received by system 202 from hemodynamic sensing cuff 240b.

It is noted that the features shown in Figure 2B and identified by reference numbers identical to those shown in Figure 2A correspond respectively to those
15 previously described features, and may share any of the characteristics attributed to them above. It is further noted that hemodynamic sensor 240b corresponds in general to hemodynamic sensor 140, in Figure 1, and may share any of the characteristics attributed to that corresponding feature in the present application.

According to the implementation shown in Figure 2B, hemodynamic
20 sensor 240b is designed to sense an arterial pressure of living subject 230 in a minimally invasive manner. For example, hemodynamic sensor 240b may be

- 13 -

attached to living subject 230 via a radial arterial catheter inserted into an arm of living subject 230. Alternatively, and although not explicitly represented in Figure 2B, in another implementation, hemodynamic sensor 240b may be attached to living subject 230 via a femoral arterial catheter inserted into a leg of living
5 subject 230. Like non-invasive hemodynamic sensing cuff 240a, in Figure 2A, minimally invasive hemodynamic sensor 240b, in Figure 2B, may be configured to provide substantially continuous beat-to-beat monitoring of the arterial pressure of living subject 230 over an extended period of time, such as minutes or hours, for example.

10 Moving now to Figure 3, Figure 3 shows an exemplary system and a computer-readable non-transitory medium including instructions enabling performance of MAP derived prediction of future hypotension. System 302, in Figure 3, includes hardware unit 304 including processor 304, memory 306, and display 326. Display 326 may take the form of a liquid crystal display (LCD), a
15 light-emitting diode (LED) display, an organic light-emitting diode (OLED) display, or another suitable display screen that performs a physical transformation of signals to light. System 302 including hardware unit 304 having processor 306 and memory 308 corresponds in general to monitoring and evaluation system 102 including hardware unit 104 having system processor 106 and system memory
20 108, and may share any of the characteristics attributed to that corresponding

- 14 -

feature in the present application. That is to say, system 302 may be configured to provide user interface 120 and/or sensory alarm 128 using display 326.

Also shown in Figure 3 is computer-readable non-transitory medium 314 having hypotension prediction software code 310 stored thereon. The expression
5 “computer-readable non-transitory medium,” as used in the present application, refers to any medium, excluding a carrier wave or other transitory signal, that provides instructions to processor 306 of system 302. Thus, a computer-readable non-transitory medium may correspond to various types of media, such as volatile media and non-volatile media, for example. Volatile media may include dynamic
10 memory, such as dynamic random access memory (dynamic RAM), while non-volatile memory may include optical, magnetic, or electrostatic storage devices. Common forms of computer-readable non-transitory media include, for example, optical discs, RAM, programmable read-only memory (PROM), erasable PROM (EPROM), and FLASH memory.

15 According to the implementation shown in Figure 3, computer-readable non-transitory medium 314 provides hypotension prediction software code 310 for execution by processor 306 of system 302. Hypotension prediction software code 310, when executed by processor 306, instantiates a hypotension prediction software code corresponding to hypotension prediction software code 110/210, in
20 Figure 1/2, and capable of performing all of the operations performed by that corresponding feature and described in the present application.

- 15 -

Example implementations of the present inventive concepts will be further described below with reference to Figure 4 and Figure 5. Figure 4 presents flowchart 460 outlining an exemplary method for use by a monitoring and evaluation system to perform MAP derived prediction of future hypotension, while Figure 5 shows a trace of an arterial pressure waveform including exemplary indicia corresponding to the probability of future hypotension in a living subject. The method outlined in flowchart 400 can be performed using hypotension prediction software code 110/210/310 described above.

Flowchart 460 begins with receiving, by hypotension prediction software code 110/210/310 executed by processor 106/306, MAP data 112/212 of living subject 130/230 (action 462). As used herein, the expression “MAP data” refers to data utilized to determine the mean arterial pressure or MAP of a living subject, as well as data derived from predictive indicia and enabling prediction of future hypotension in the living subject based on the MAP of the living subject. For example, MAP data 112/212 may be extracted and/or processed from hemodynamic signals 142/242 received by system 102/202/302 from hemodynamic sensor 140/240a/240b.

In one implementation, for example, hemodynamic sensor 140/240a/240b may be used to sense an arterial pressure of living subject 130/230 at an extremity of living subject 130/230, and to determine a central arterial pressure of living subject 130/230 based on the sensed arterial pressure. System 102/202/302 may

- 16 -

be configured to receive the determined central arterial pressure of living subject 130/230 as hemodynamic signals 142/242, which, in various implementations, may be received as analog signals or digital signals. In implementations in which hemodynamic signals 142/242 are received as analog signals, system 102/202/302
5 utilizes ADC 122 to convert hemodynamic signals 142/242 into digital data including MAP data 112/212. It is noted that in other implementations, system 102/202/302 can be configured to determine the central arterial pressure of living subject 130/230 based on the arterial pressure sensed by hemodynamic sensor 140/240a/240b.

10 Referring to diagram 500, in Figure 5, MAP data 112/212 may include various indicia predictive of future hypotension in living subject 130/230 and derived from arterial pressure waveform 580, which may be a central arterial pressure waveform of living subject 130/230, for example. Diagram 500 shows exemplary indicia 582, 584, 586, and 588, corresponding respectively to the start
15 of a heartbeat, the maximum systolic pressure marking the end of systolic rise, the presence of the dicrotic notch marking the end of systolic decay, and the diastole of the heartbeat of living subject 130/230. Also shown by diagram 500 is exemplary slope 590 of arterial pressure waveform 580. It is noted that slope 590 is merely representative of multiple slopes that may be measured at multiple
20 locations along arterial pressure waveform 580.

- 17 -

In addition to the indicia 582, 584, 586, and 588 of arterial pressure waveform 580 per se, the behavior of arterial pressure waveform 580 during the intervals between those indicia may also be used as indicia predictive of future hypotension for living subject 130/240. For example, the interval between the
5 start of the heartbeat at indicia 582 and the maximum systolic pressure at indicia 584 marks the duration of the systolic rise (hereinafter “systolic rise 582-584”). The systolic decay of arterial pressure waveform 580 is marked by the interval between the maximum systolic pressure at indicia 584 and the dicrotic notch at indicia 586 (hereinafter “systolic decay 584-586”). Together, systolic rise 582-
10 584 and systolic decay 584-586 mark the entire systolic phase (hereinafter “systolic phase 582-586”), while the interval between the dicrotic notch at indicia 586 and the diastole at indicia 588 mark the diastolic phase of arterial pressure waveform 580 (hereinafter “diastolic phase 586-588”).

Also of potential diagnostic interest is the behavior of arterial pressure
15 waveform 580 in the interval from the maximum systolic pressure at indicia 584 to the diastole at indicia 588 (hereinafter “interval 584-588”), as well as the behavior of arterial pressure waveform 580 from the start of the heartbeat at indicia 582 to the diastole at indicia 588 (hereinafter “heartbeat interval 582-588”). The behavior of arterial pressure waveform 580 during intervals: 1)
20 systolic rise 582-584, 2) systolic decay 584-586, 3) systolic phase 582-586, 4) diastolic phase 586-588, 5) interval 584-588, and 6) heartbeat interval 582-588

- 18 -

may be determined by measuring the area under the curve of arterial pressure waveform 580 and the standard deviation of arterial pressure waveform 580 in each of those intervals, for example. The respective areas and standard deviations measured for intervals 1, 2, 3, 4, 5, and 6 above (hereinafter “intervals 1-6”) may
5 serve as additional indicia predictive of future hypotension for living subject 130/240.

As noted above, MAP data 112/212 may include any or all of indicia 582, 584, 586, 588, and 590, as well as the respective areas and standard deviations measured for intervals 1-6 of arterial pressure waveform 580, and may be utilized
10 to determine MAP itself, or to enable prediction of future hypotension in living subject 130/230 based on MAP. With respect to determination of MAP itself, as known in the art, MAP may be determined from the following equation:

$$\text{MAP} = (\text{CO} * \text{SVR}) + \text{CVP} \quad (\text{Equation 1})$$

where CO is cardiac output, SVR is systemic vascular resistance, and CVP is
15 central venous pressure. However, MAP may also be approximately determined using systolic pressure (SP) and diastolic pressure (DP), corresponding respectively to maximum systolic pressure 584 and pressure at diastole 588. According to such an approximate determination, MAP may be expressed as:

$$\text{MAP (approximately)} = \text{DP} + 1/3(\text{SP} - \text{DP}) \quad (\text{Equation 2})$$

20 Thus, in one implementation, MAP data 112/212 may include at least data corresponding to indicia 584 and 588 for generating an approximate determination

- 19 -

of MAP. However, in other implementations, MAP data 112/212 may include data extracted and/or processed from hemodynamic signals 142/242 and corresponding to the cardiac output (CO), systemic vascular resistance (SVR), and central venous pressure (CVP) of living subject 130/230.

5 Flowchart 460 continues with transforming, by hypotension prediction software code 110/210/310 executed by processor 106/306, MAP data 112/212 to at least one parameter predictive of a future hypotension event of living subject 130/230 (action 464). For example, in one implementation, MAP itself may be a single parameter sufficient to predict a future hypotension event of living subject
10 130/230. Specifically, in one implementation, a future hypotension event by living subject 130/230 may be predicted based on MAP by the following equation:

$$\text{Risk Score} = 1/(1 + e^{-((a * \text{MAP}) + b)}) \quad (\text{Equation 3})$$

where Risk Score corresponds to the probability of a future hypotension event of
15 living subject 130/230, and “a”, MAP itself, and “b”, are parameters predictive of such a hypotensive event. It is noted that in some implementations, the parameters “a” and “b” may be predetermined and fixed, while in other implementations, “a” and “b” may be variables that are determined on a case-by-case basis and may be obtained from the transformation of MAP data 112/212
20 performed as action 464.

- 20 -

Flowchart 460 continues with determining, by hypotension prediction software code 110/210/310 executed by processor 106/306, the risk score for living subject 130/230, e.g., Risk Score above (action 466). As noted above, the risk score for living subject 130/230 may be determined using Equation 3. In
5 some implementations, the risk score may be expressed as a fraction, as represented by Equation 3. However, in some implementations, the risk score may be converted to a percentage risk score between zero percent and one hundred percent.

It is emphasized that the risk score of living subject 130/230 is determined
10 based on parameters derived from MAP data 112/212 of living subject 130/230, which in turn is determined based on hemodynamic signals 142/242 of living subject 130/230 received from hemodynamic sensor 140/240a/240b. Consequently, according to the inventive concepts disclosed by the present application, hardware processor 106/306 is configured to execute hypotension
15 prediction software code 110/210/310 to determine the risk score of living subject 130/230 without comparison with data corresponding to hypotension in other living subjects. That is to say, hypotension prediction software code 110/210/310 determines the risk score of living subject 130/230 based on parameters derived from MAP data 112/212 without reference to a hypotension patient database
20 storing information regarding hypotension in patients other than living subject 130/230.

- 21 -

Flowchart 460 can conclude with invoking, by hypotension prediction software code 110/210/310 executed by processor 106/306, sensory alarm 128 if the risk score of living subject 130/230 satisfies a predetermined risk criteria (action 468). As shown in Figure 1, for example, hypotension prediction software
5 code 110/210/310 may be configured to provide an output to user interface 120 on display 126/326 for displaying the risk score of living subject 130/230, and/or for invoking sensory alarm 128. As further shown in Figure 1, in some implementations, the output of hypotension prediction software code 110/210/310 may be processed using DAC 124 to convert digital signals into analog signals for
10 presentation via user interface 120.

The predetermined risk criteria may be based on the value of the risk score, on the trend of the risk score over a time interval, or both. For example, where the risk score is expressed as a percentage between zero and one hundred, having the risk score exceed a threshold of eighty-five percent, for instance, may cause
15 sensory alarm 128 to be invoked immediately. Alternatively, or in addition, a lower risk score may cause sensory alarm 128 to be invoked if it exceeds a predetermined threshold over the entirety of a predetermined time period.

Thus, for example, while a risk score of eighty five percent may cause sensory alarm 128 to be invoked immediately, a risk score of eighty percent may
20 cause sensory alarm 128 to be invoked after several seconds at that level, such as ten to thirty seconds in which the risk score is continuously between eighty and

- 22 -

eighty five percent, for example. By analogy, a still lower risk score may cause sensory alarm 128 to be invoked if that risk score is maintained continuously for one or more minutes. In yet another implementation, the risk score may cause sensory alarm 128 to be invoked if it meets or exceeds a predetermined value a
5 predetermined number of times over a predetermined time period. For example, having the risk score exceed seventy five percent three times over a five minute interval may cause sensory alarm 128 to be invoked.

As noted above by reference to Figure 1, sensory alarm 128 may be implemented as one or more of a visual alarm, an audible alarm, and a haptic
10 alarm. For example, when implemented to provide a visual alarm, sensory alarm 128 may be invoked as flashing and/or colored graphics shown by user interface 120 on display 126, and/or may include displaying the risk score via user interface 120 on display 126/326. When implemented to provide an audible alarm, sensory alarm 128 may be invoked as any suitable warning sound, such as a siren or
15 repeated tone. Moreover, when implemented to provide a haptic alarm, sensory alarm 128 may cause hardware unit 104/304 to vibrate or otherwise deliver a physical impulse perceptible to user 150.

Although not included among the actions outlined by flowchart 460, in some implementations, the present method may include identifying, by
20 hypotension prediction software code 110/210/310 executed by processor 106/306, a most probable cause of the future hypotension event of living subject

- 23 -

130/230. For example, and as noted above, based on indicia included in hemodynamic signals 142, hypotension prediction software code 110/210/310 may be used to identify poor vascular tone, low blood volume, or reduced cardiac contractility, to name a few exemplary causes, as a most probable cause of a
5 predicted future hypotension event.

In addition, in some implementations, the present method may include recommending, by hypotension prediction software code 110/210/310 executed by processor 106/306, a medical intervention for preventing the future hypotension event of living subject 130/230. With respect to poor vascular tone
10 or low blood volume, for example, administration of a vasoconstrictor may be recommended if poor vascular tone is detected, while administration of saline or whole blood may be recommend if low blood volume is identified as a most probable cause of the predicted future hypotension event.

Thus, by transforming MAP data of a living subject to one or more
15 parameters predictive of a future hypotension event of the living subject, the present application discloses a solution enabling determination of a risk score corresponding to the probability that the future hypotension event will occur. In addition, by receiving and transforming the MAP data of the living subject on an ongoing basis, the solution disclosed by the present application enables
20 substantially continuous hypotension risk monitoring of the living subject. Moreover, by invoking a sensory alarm if the risk score of the living subject

- 24 -

satisfies a predetermined risk criteria, the present application discloses a solution that provides an early warning of a future hypotension event of the living subject, thereby advantageously enabling health care workers to prepare a timely and effective intervention.

5 From the above description it is manifest that various techniques can be used for implementing the concepts described in the present application without departing from the scope of those concepts. Moreover, while the concepts have been described with specific reference to certain implementations, a person of ordinary skill in the art would recognize that changes can be made in form and
10 detail without departing from the scope of those concepts. As such, the described implementations are to be considered in all respects as illustrative and not restrictive. It should also be understood that the present application is not limited to the particular implementations described herein, but many rearrangements, modifications, and substitutions are possible without departing from the scope of
15 the present disclosure.

- 25 -

CLAIMS

What is claimed is:

1. A system for monitoring and evaluation of a living subject, the
5 system comprising:
 - a hardware unit including a hardware processor and a system memory;
 - a hypotension prediction software code stored in the system memory;
 - a sensory alarm;wherein the hardware processor is configured to execute the hypotension
10 prediction software code to:
 - receive a mean arterial pressure (MAP) data of the living
subject;
 - transform the MAP data to at least one parameter predictive
of a future hypotension event of the living subject;
 - 15 determine a risk score of the living subject corresponding to
the probability of the future hypotension event based on at least a
subset of the at least one parameter; and
 - invoke the sensory alarm if the risk score of the living subject
satisfies a predetermined risk criteria.

- 26 -

2. The system of claim 1, wherein the hardware processor is configured to execute the hypotension prediction software code to determine the risk score of the living subject without comparison with data corresponding to hypotension in other living subjects.

5

3. The system of claim 1, wherein the hardware processor is further configured to execute the hypotension prediction software code to invoke the sensory alarm by displaying the risk score of the living subject via a display of a user interface on a display connected to the hardware unit.

10

4. The system of claim 1, wherein the hardware processor is further configured to execute the hypotension prediction software code to identify a most probable cause of the future hypotension event.

15

5. The system of claim 4, wherein the hardware processor is further configured to execute the hypotension prediction software code to recommend a medical intervention for preventing the future hypotension event.

6. The system of claim 1, wherein the system is further configured to determine the MAP data based on hemodynamic signals of the living subject received from a sensor attached to the living subject.

20

- 27 -

7. The system of claim 6, wherein the hemodynamic signals are obtained non-invasively.

5 8. The system of claim 6, wherein the hemodynamic signals are obtained non-invasively at an extremity of the living subject.

9. A method for use by a system for monitoring and evaluation of a living subject, the system including a hardware processor and a hypotension prediction software code stored in a system memory, the method comprising:

10 receiving, by the hypotension prediction software code executed by the hardware processor, a mean arterial pressure (MAP) data of the living subject;

transforming, by the hypotension prediction software code executed by the hardware processor, the MAP data to at least one parameter predictive of a future hypotension event of the living subject;

15 determining, by the hypotension prediction software code executed by the hardware processor, a risk score of the living subject corresponding to the probability of the future hypotension event, based on at least a subset of the at least one parameter; and

20

- 28 -

invoking, by the hypotension prediction software code executed by the hardware processor, a sensory alarm of the system if the risk score of the living subject satisfies a predetermined risk criteria.

5 10. The method of claim 9, wherein determining the risk score of the living subject is performed without comparison with data corresponding to hypotension in other living subjects.

 11. The method of claim 9, wherein invoking the sensory alarm of the system comprises displaying the risk score of the living subject via a user
10 interface on a display of the system.

 12. The method of claim 9, further comprising identifying, by the hypotension prediction software code executed by the hardware processor, a most probable cause of the future hypotension event.

15

 13. The method of claim 12, further comprising recommending, by the hypotension prediction software code executed by the hardware processor, a medical intervention for preventing the future hypotension event.

- 29 -

14. The method of claim 9, further comprising determining the MAP data based on hemodynamic signals of the living subject received from a sensor attached to the living subject.

5 15. A computer-readable non-transitory medium having stored thereon instructions, which when executed by a hardware processor, instantiate a method comprising:

receiving a mean arterial pressure (MAP) data of a living subject;

transforming the MAP data to at least one parameter predictive of a future
10 hypotension event of the living subject;

determining a risk score of the living subject corresponding to the probability of the future hypotension event based on at least a subset of the at least one parameter; and

invoking a sensory alarm if the risk score of the living subject satisfies a
15 predetermined risk criteria.

16. The computer-readable non-transitory medium of claim 15, wherein determining the risk score of the living subject is performed without comparison with data corresponding to hypotension in other living subjects.

- 30 -

17. The computer-readable non-transitory medium of claim 15, further comprising displaying the risk score of the living subject via a user interface.

18. The computer-readable non-transitory medium of claim 15, further
5 comprising identifying a most probable cause of the future hypotension event.

19. The computer-readable non-transitory medium of claim 18, further comprising recommending a medical intervention for preventing the future hypotension event.

10

20. The computer-readable non-transitory medium of claim 15, further comprising determining the MAP data based on hemodynamic signals of the living subject received from a sensor attached to the living subject.


Fig. 1



Fig. 2A**Fig. 2B**


Fig. 3



Fig. 4

Fig. 5

INTERNATIONAL SEARCH REPORT

International application No.
PCT/US2017/042221**A. CLASSIFICATION OF SUBJECT MATTER****A61B 5/00(2006.01)i, A61B 5/021(2006.01)i, G06F 19/00(2011.01)i**

According to International Patent Classification (IPC) or to both national classification and IPC

B. FIELDS SEARCHED

Minimum documentation searched (classification system followed by classification symbols)

A61B 5/00; G06F 17/60; G06T 11/20; A61B 5/0402; A61B 5/021; G06F 19/00

Documentation searched other than minimum documentation to the extent that such documents are included in the fields searched

Korean utility models and applications for utility models

Japanese utility models and applications for utility models

Electronic data base consulted during the international search (name of data base and, where practicable, search terms used)

eKOMPASS(KIPO internal) & Keywords: health, monitoring, GUI, display, hypotension, probability, MAP, alarm

C. DOCUMENTS CONSIDERED TO BE RELEVANT

Category*	Citation of document, with indication, where appropriate, of the relevant passages	Relevant to claim No.
Y	US 2015-0116333 A1 (ABBOTT DIABETES CARE INC.) 30 April 2015 See paragraphs [55]-[76], [279] and claim 13.	1-20
Y	WO 2016-022989 A2 (THE GENERAL HOSPITAL CORPORATION) 11 February 2016 See paragraphs [39], [114] and figures 1-21.	1-20
Y	WO 2015-183689 A1 (ROCHE DIABETES CARE, INC. et al.) 03 December 2015 See paragraph [41], claim 1 and figure 2.	2, 7, 8, 10, 16
A	WO 2004-034898 A2 (PHILIPS INTELLECTUAL PROPERTY & STANDARDS GMBH et al.) 29 April 2004 See claims 1-21 and figure 3.	1-20
A	US 2005-0187796 A1 (ROSENFELD et al.) 25 August 2005 See claims 1-6 and figure 19.	1-20



Further documents are listed in the continuation of Box C.



See patent family annex.

* Special categories of cited documents:

"A" document defining the general state of the art which is not considered to be of particular relevance

"E" earlier application or patent but published on or after the international filing date

"L" document which may throw doubts on priority claim(s) or which is cited to establish the publication date of another citation or other special reason (as specified)

"O" document referring to an oral disclosure, use, exhibition or other means

"P" document published prior to the international filing date but later than the priority date claimed

"T" later document published after the international filing date or priority date and not in conflict with the application but cited to understand the principle or theory underlying the invention

"X" document of particular relevance; the claimed invention cannot be considered novel or cannot be considered to involve an inventive step when the document is taken alone

"Y" document of particular relevance; the claimed invention cannot be considered to involve an inventive step when the document is combined with one or more other such documents, such combination being obvious to a person skilled in the art

"&" document member of the same patent family

Date of the actual completion of the international search

21 September 2017 (21.09.2017)

Date of mailing of the international search report

21 September 2017 (21.09.2017)

Name and mailing address of the ISA/KR

International Application Division

Korean Intellectual Property Office

189 Cheongsa-ro, Seo-gu, Daejeon, 35208, Republic of Korea



Facsimile No. +82-42-481-8578

Authorized officer

KIM, Yeon Kyung

Telephone No. +82-42-481-3325



INTERNATIONAL SEARCH REPORT

Information on patent family members

International application No.

PCT/US2017/042221

Patent document cited in search report	Publication date	Patent family member(s)	Publication date
US 2015-0116333 A1	30/04/2015	EP 2473422 A1 IL 216631 A US 2011-0193704 A1 US 2013-0338465 A1 US 2014-0347186 A1 US 2016-0058345 A1 US 2017-0000426 A1 US 2017-086756 A1 US 8514086 B2 US 8816862 B2 US 9186113 B2 US 9226714 B2 US 9549694 B2 WO 2011-026053 A1	11/07/2012 29/02/2012 11/08/2011 19/12/2013 27/11/2014 03/03/2016 05/01/2017 30/03/2017 20/08/2013 26/08/2014 17/11/2015 05/01/2016 24/01/2017 03/03/2011
WO 2016-022989 A2	11/02/2016	EP 3195067 A2 US 2017-235917 A1 WO 2016-022989 A3	26/07/2017 17/08/2017 07/04/2016
WO 2015-183689 A1	03/12/2015	EP 3154419 A1 US 2015-0347698 A1 US 2016-0378937 A1 US 9465917 B2	19/04/2017 03/12/2015 29/12/2016 11/10/2016
WO 2004-034898 A2	29/04/2004	AU 2003-263554 A1 EP 1553870 A2 JP 2006-502781 A US 2006-0167362 A1 US 7572230 B2 WO 2004-034898 A3	04/05/2004 20/07/2005 26/01/2006 27/07/2006 11/08/2009 15/07/2004
US 2005-0187796 A1	25/08/2005	AU 2000-57640 A1 AU 2000-57640 B2 CA 2378005 A1 CA 2378005 C EP 1200924 A2 EP 1200924 B1 EP 2040188 A1 JP 09-045616 A JP 4056571 B2 US 2004-0111296 A1 US 2005-0037554 A1 US 2005-0159987 A1 US 2005-0177400 A1 US 2005-0203777 A1 US 2006-0017563 A1 US 2006-0022834 A1 US 2006-0025657 A1 US 2006-0064324 A1	09/01/2001 31/07/2003 28/12/2000 01/11/2005 02/05/2002 09/04/2014 25/03/2009 14/02/1997 05/03/2008 10/06/2004 17/02/2005 21/07/2005 11/08/2005 15/09/2005 26/01/2006 02/02/2006 02/02/2006 23/03/2006

INTERNATIONAL SEARCH REPORT

Information on patent family members

International application No.

PCT/US2017/042221

Patent document cited in search report	Publication date	Patent family member(s)	Publication date
		US 2006-0071797 A1	06/04/2006
		US 2006-0085227 A1	20/04/2006
		US 2006-0085229 A9	20/04/2006
		US 2006-0122869 A9	08/06/2006
		US 2006-0161459 A9	20/07/2006
		US 2006-0271407 A1	30/11/2006
		US 2006-0271408 A1	30/11/2006
		US 2006-0271409 A1	30/11/2006
		US 2006-0271410 A1	30/11/2006
		US 2009-0216564 A1	27/08/2009
		US 2009-0259495 A1	15/10/2009
		US 6804656 B1	12/10/2004
		US 6830617 B1	14/12/2004
		US 7256708 B2	14/08/2007
		US 7307543 B2	11/12/2007
		US 7315825 B2	01/01/2008
		US 7321862 B2	22/01/2008
		US 7395216 B2	01/07/2008
		US 7403902 B2	22/07/2008
		US 7411509 B2	12/08/2008
		US 7433827 B2	07/10/2008
		US 7454359 B2	18/11/2008
		US 7454360 B2	18/11/2008
		US 7467094 B2	16/12/2008
		US 7475019 B2	06/01/2009
		US 7650291 B2	19/01/2010
		US 7837792 B2	23/11/2010
		US 7991625 B2	02/08/2011
		US 8170887 B2	01/05/2012
		US 8175895 B2	08/05/2012
		US 8326649 B2	04/12/2012
		US 8401874 B2	19/03/2013
		WO 00-79466 A2	28/12/2000
		WO 00-79466 A3	19/07/2001

专利名称(译)	平均动脉压 (MAP) 推测预测未来的低血压		
公开(公告)号	EP3487389A4	公开(公告)日	2019-07-17
申请号	EP2017831605	申请日	2017-07-14
[标]申请(专利权)人(译)	爱德华兹生命科学公司		
申请(专利权)人(译)	爱德华生命科学公司		
当前申请(专利权)人(译)	爱德华生命科学公司		
[标]发明人	AL HATIB FERAS JIAN ZHONGPING		
发明人	AL HATIB, FERAS JIAN, ZHONGPING		
IPC分类号	A61B5/00 A61B5/021 G06F19/00		
CPC分类号	A61B5/02108 A61B5/02241 A61B5/6826 A61B5/7267 A61B5/7275 A61B5/742 A61B5/746 A61B2505/01 A61B2505/03 A61B2505/05 G16H40/63 G16H50/30 G16H50/50		
优先权	62/365815 2016-07-22 US 15/649438 2017-07-13 US		
其他公开文献	EP3487389A1		
外部链接	Espacenet		

摘要(译)

提供了用于执行平均动脉压 (MAP) 导出的对未来低血压的预测的系统和方法。这种系统包括硬件单元，其包括硬件处理器和系统存储器，存储在系统存储器中的低血压预测软件代码，以及感官警报。硬件处理器被配置为执行低血压预测软件代码以接收活体的MAP数据，并将MAP数据变换为预测活体的未来低血压事件的一个或多个参数。硬件处理器还被配置为执行低血压预测软件代码，以基于一个或多个参数中的至少一些参数确定与未来低血压事件的概率对应的活体的风险评分，并且如果是，则调用感觉警报。生活受试者的风险评分满足预定的风险标准。