

(19) World Intellectual Property Organization
International Bureau



(43) International Publication Date
16 June 2005 (16.06.2005)

PCT

(10) International Publication Number
WO 2005/053527 A1

(51) International Patent Classification⁷: **A61B 5/00**

LR, LS, LT, LU, LV, MA, MD, MG, MK, MN, MW, MX, MZ, NA, NI, NO, NZ, OM, PG, PH, PL, PT, RO, RU, SC, SD, SE, SG, SK, SL, SY, SZ, TJ, TM, TN, TR, TT, TZ, UA, UG, UZ, VC, VN, YU, ZA, ZM, ZW only: **KONINKLIJKE PHILIPS ELECTRONICS N. V.** [NL/NL]; Groenewoudseweg 1, NL-5621 BA Eindhoven (NL).

(21) International Application Number:
PCT/IB2004/052511

(22) International Filing Date:
23 November 2004 (23.11.2004)

(25) Filing Language: English

(72) Inventor; and
(75) Inventor/Applicant (for US only): **NEUMANN, Rolf** [DE/DE]; c/o Philips Intellectual Property &, Standards GmbH Weisshausstr. 2, 52066 Aachen (DE).

(26) Publication Language: English

(30) Priority Data:
03104501.6 2 December 2003 (02.12.2003) EP

(74) Agents: **VOLMER, Georg** et al.; Philips Intellectual Property &, Standards GmbH Weisshausstr. 2, 52066 Aachen (DE).


(71) Applicant (for DE only): **PHILIPS INTELLECTUAL PROPERTY & STANDARDS GMBH** [DE/DE]; Stein-damm 94, 20099 Hamburg (DE).

(81) Designated States (unless otherwise indicated, for every kind of national protection available): AE, AG, AL, AM, AT, AU, AZ, BA, BB, BG, BR, BW, BY, BZ, CA, CH, CN, CO, CR, CU, CZ, DE, DK, DM, DZ, EC, EE, EG, ES, FI, GB, GD, GE, GH, GM, HR, HU, ID, IL, IN, IS, JP, KE, KG, KP, KR, KZ, LC, LK, LR, LS, LT, LU, LV, MA, MD, MG, MK, MN, MW, MX, MZ, NA, NI, NO, NZ, OM, PG, PH, PL, PT, RO, RU, SC, SD, SE, SG, SK, SL, SY, TJ, TM,

(71) Applicant (for AE, AG, AL, AM, AT, AU, AZ, BA, BB, BE, BG, BR, BW, BY, BZ, CA, CH, CN, CO, CR, CU, CY, CZ, DK, DM, DZ, EC, EE, EG, ES, FI, GB, GD, GE, GH, GM, HR, HU, ID, IL, IN, IS, JP, KE, KG, KP, KR, KZ, LC, LK,

[Continued on next page]

(54) Title: MEDICAL MEASURING DEVICE



(57) Abstract: The invention relates to a medical measuring device (10) comprising at least one measuring apparatus (12, 14), which has at least one sensor (16, 18) for generating a measuring signal of a patient (20, 22). A measuring data detection device (24) is also provided, which is designed to exchange measuring signals with the at least one measuring apparatus (12, 14) via an, in particular, wireless communication route (24, 26). The at least one measuring apparatus (12, 14) is designed to signal the quality of the measuring signals.

WO 2005/053527 A1



TN, TR, TT, TZ, UA, UG, US, UZ, VC, VN, YU, ZA, ZM, ZW.

SI, SK, TR), OAPI (BF, BJ, CF, CG, CI, CM, GA, GN, GQ, GW, ML, MR, NE, SN, TD, TG).

(84) Designated States (*unless otherwise indicated, for every kind of regional protection available*): ARIPO (BW, GH, GM, KE, LS, MW, MZ, NA, SD, SL, SZ, TZ, UG, ZM, ZW), Eurasian (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM), European (AT, BE, BG, CH, CY, CZ, DE, DK, EE, ES, FI, FR, GB, GR, HU, IE, IS, IT, LU, MC, NL, PL, PT, RO, SE,

Published:

— *with international search report*

For two-letter codes and other abbreviations, refer to the "Guidance Notes on Codes and Abbreviations" appearing at the beginning of each regular issue of the PCT Gazette.

Medical measuring device

The invention relates to a medical measuring device according to claim 1.

Instead of stationary and large measuring apparatuses, small and mobile
5 apparatuses are used more and more frequently in the medical sector, which can be carried by
patients and therefore allow greater freedom of movement. An autonomous ECG recorder is
known, for example, from US 5,433,209 and is designed as a portable apparatus allowing
leads-off detection and alarm actuation on the portable apparatus which is implemented
automatically according to a fixed sequence once the apparatus has been switched on.

10 Mobile devices of this type are generally optimized with respect to a small size
and low power consumption. They therefore do not generally have detailed displays, but only
small displays designed for the basic functions such as on/off or the battery status.

Devices of this type are increasingly no longer used as autonomous units, but
as remote units for measuring data detection in a distributed measuring and measuring data
15 detection system. These units then communicate with a stationary apparatus via a generally
wireless communication connection, via which measuring signals are transmitted from a
remote unit or a measuring apparatus to the stationary apparatus or the measuring data
detection device.

20 However, when sensors of the remote units are placed on the body of a patient,
medical staff cannot generally see a stationary apparatus with its detailed displays located in
another room. Therefore they have no information about the correct placing on the body of
the patient with respect to good quality of the measuring signals. For this purpose, the staff
have to go to the stationary apparatus once the sensors have been placed and check the
measuring signal quality. However, this is very time-consuming.

25 A further problem is that directly after the placing of sensors of a remote unit,
the measuring signal quality is frequently very good but some time later deteriorates. It is
therefore generally necessary for medical staff to check the measuring signal quality from
time to time at the stationary apparatus. However, this is also very time-consuming.

An object of the present invention is therefore to propose a medical measuring device which is easier for medical staff to handle than the devices described at the outset, in particular requiring less time for monitoring.

5 This object is achieved by a medical measuring device with the features of claim 1. Further configurations emerge from the dependent claims.

An essential concept of the invention consists in signaling the measuring signal quality from a sensor directly at the measuring apparatus, to which the sensor is connected. Medical staff are therefore spared the time-consuming checking of the quality of
10 the measuring signals at a central unit like the measuring data detection device.

The invention relates to a medical measuring device with at least one measuring apparatus which has at least one sensor for generating a measuring signal of a patient, and a measuring data detection device, which is designed to exchange the measuring signal with the at least one measuring apparatus via an, in particular, wireless communication
15 route, wherein the at least one measuring apparatus is designed to signal the quality of the measuring signal.

The at least one measuring apparatus is designed, in particular, to signal the quality of the measuring signal acoustically, for example by a short audio signal, when the signal quality is poor. The audio signal can thus be changed depending on the signal quality,
20 for example it may be repeated very often in the case of very poor signal quality. Typically no audio signal is sounded when the signal quality is adequate or good.

Alternatively or in addition, the at least one measuring apparatus can be designed to signal the quality of the measuring signal optically, for example by a display with LEDs or on an LCD.

25 The at least one measuring device is preferably a light means with different colors, each color being associated with a predetermined range of a signal quality and activated when the quality of the measuring signal is in the corresponding, predetermined range.

The light means may also be, for example, a three-colored LED, three
30 different colors being provided for a range of poor quality, a range of medium and a range of high quality. Red may be, for example, poor, yellow medium and green good signal quality.

The at least one measuring apparatus is preferably designed to signal the quality of the measuring signal automatically. In this case no activation of a signalization of the measuring signal quality is necessary by medical staff.

The at least one measuring apparatus may be designed, for example, to signal the quality of the measuring signal when it is placed on a patient at another measuring site. In other words, it is triggered automatically when the measuring site is changed and signals the signal quality.

5 In addition or also alternatively, the at least one measuring apparatus can be designed to signal the quality of the measuring signal, if a substantial change in the quality of the measuring signal is detected, for example when a patient has removed one or more sensors.

10 The at least one measuring apparatus can also be designed to signal the quality of the measuring signal on demand, for example by pressing a button on the measuring apparatus or by a corresponding demand from the measuring data detection device.

In a simple embodiment, the at least one measuring apparatus is designed to signal the quality of the measuring signal in such a way that falling below a predetermined signal quality is signaled. In other words there is a threshold value in the form of the
15 predetermined signal quality. The falling below of the threshold value can be detected by a comparator in the measuring apparatus and trigger or activate signaling.

For preferred application areas in the medical sector, the at least one measuring apparatus is designed to signal the quality of the measuring signal on the basis of an evaluation of one or more parameters such as the perfusion index, transmission level,
20 interference level, the signal form or the like.

The at least one measuring apparatus is preferably a pulsoximeter, an ECG recorder and/or ultrasound measuring head.

25 Further advantages of the application possibilities of the present invention emerge from the following description of an embodiment of the invention with the single drawing.

30 The single Figure of the drawing shows a medical measuring device 10 in the form of a distributed medical measuring system with measuring apparatuses 12 and 14 and a central measuring data detection device 24 which is used for storing and displaying medical measuring data and for central control of the measuring apparatus 12 and 14.

The measuring data detection device 24 comprises an LCD display screen 38 for displaying medical measuring data. The medical measuring data comprise, for example, a curve pattern 42 and numerical values 40 for measuring values. The measuring data detection device 24 has various operating elements 46 for adjusting measuring parameters, the display on the screen 38 and functions of this type of the measuring data detection device 24.

The measuring device 12 is a portable ECG measuring apparatus which has a plurality of ECG electrodes 16 as sensors. As shown in the Figure, a patient 20 carries the ECG measuring apparatus 12 on his upper body, on which the ECG electrodes 16 are fastened. The ECG measuring device 12 has an ECG recorder for recording the ECG signals picked up via the ECG sensor 16. It also comprises a radio unit, with which it can build up a radio communication connection 26 with the measuring data detection device 24 for transmitting measuring signals.

To facilitate the correct placing of the ECG electrodes 16 on the upper body of the patient 20 for medical staff, the ECG measuring apparatus 12 has a three-colored LED 34 and a loudspeaker 30. The LED 34 and the loudspeaker 30 are used for optical or acoustic signaling of the quality of measuring signals which are captured via the ECG electrodes 16.

When the ECG measuring apparatus 12 detects that no measuring signal with adequate quality can be received via the ECG electrodes 16, it switches the color of the LED 34 to red to display a poor or lesser signal quality. Furthermore, an acoustic signal in the form of a short periodic audio signal sounds over the loudspeaker 30 for as long as the signal quality is not adequate.

The signal quality is checked fully automatically in the ECG measuring apparatus 12, as soon as it is switched on. It is also possible to start a test of the signal quality by actuating a signal quality test button 36 on the ECG measuring apparatus 12. This may be carried out, for example, by the patient 20 himself. When the signal quality is adequate, the ECG measuring device 12 transmits measuring signals of the ECG electrodes 16 via the radio communication connection 26 to the measuring data detection device 24 which shows the signals received, for example in the form of the curve pattern 42 on the large LCD display screen 38 and records the course of the measuring signals.

The measuring apparatus 14 is a pulsoximeter and connected to a pulsoximeter sensor 18, in which one finger 22 of the patient is located. The measuring signals of the sensor 18 are transmitted to the pulsoximeter measuring apparatus 14. The measuring apparatus comprises a comparator for comparing the signal quality of the measuring signals received with the predetermined threshold value for a predetermined signal quality. When the

signal quality received is less than the predetermined threshold value, the comparator output signal activates an LED 32 and an audio signal generator which controls the loudspeaker 28 with an audio signal. In this case, there is therefore optical and acoustic signaling that the quality of the signal of the pulsoximeter sensor 18 is not adequate to ensure reliable recording
5 in the measuring data detection device 24.

The signal quality can then be changed by the patient or medical staff by changing the position of the pulsoximeter sensor 18 in order to receive an adequate signal quality. When the signal quality is adequate, the measuring signals are transmitted from the pulsoximeter measuring apparatus 14 via a radio communication connection 26 to the
10 measuring data detection device 24 which displays the measuring signals received in the form of numerical values on the screen 38 and records them.

LIST OF REFERENCE NUMERALS:

	10	medical measuring device
	12	ECG measuring apparatus
	14	pulsoximeter
	16	ECG electrodes
5	18	pulsoximeter sensor
	20	patient
	22	finger of a patient
	24	measuring data detection device
	26	radio communication connection
10	28, 30	loudspeaker
	32, 34	LED
	36	signal quality test button
	38	LCD display screen
	40	numerical values
15	42	curve pattern
	46	operating elements

CLAIMS:

1. A medical measuring device (10) comprising at least one measuring apparatus (12, 14), which has at least one sensor (16, 18) for generating a measuring signal of a patient (20, 22) and a measuring data detection device (24) which is designed to exchange measuring signals with the at least one measuring apparatus (12, 14) via an, in particular, wireless communication route (24, 26), wherein the at least one measuring apparatus (12, 14) is designed to signal the quality of the measuring signals.
5
2. A medical measuring device as claimed in claim 1, characterized in that the at least one measuring apparatus (12, 14) is designed to signal the quality of the measuring signals acoustically (28, 30).
10
3. A medical measuring device as claimed in claim 1 or 2, characterized in that the at least one measuring apparatus is designed to signal the quality of the measuring signals optically (32, 34).
15
4. A medical measuring device as claimed in claim 3, characterized in that the at least one measuring apparatus has a light means (32, 34) with different colors, each color being associated with a predetermined range of a signal quality and activated when the quality of the measuring signals is in the correspondingly predetermined range.
20
5. A medical measuring device as claimed in claim 4, characterized in that three different colors are provided for a range of poor quality, a range of medium and a range of high quality of the measuring signals.
- 25 6. A medical measuring device as claimed in any one of the preceding claims, characterized in that the at least one measuring apparatus (12, 14) is designed to signal the quality of the measuring signals automatically.

7. A medical measuring device as claimed in claim 6, characterized in that the at least one measuring apparatus (12, 14) is designed to signal the quality of the measuring signals when it is placed on a patient at another measuring site.
- 5 8. A medical measuring device as claimed in claim 6 or 7, characterized in that the at least one measuring apparatus (12, 14) is designed to signal the quality of the measuring signals, when a substantial change in the quality of the measuring signals is detected.
- 10 9. A medical measuring device as claimed in any one of the preceding claims, characterized in that the at least one measuring apparatus (12, 14) is designed to signal the quality of the measuring signals on demand (36).
10. A medical measuring device as claimed in any one of the preceding claims,
15 characterized in that the at least one measuring apparatus (12, 14) is designed to signal the quality of the measuring signals in such a way that falling below a predetermined signal quality is signaled.
11. A medical measuring device as claimed in any one of the preceding claims,
20 characterized in that the at least one measuring apparatus (12, 14) is designed to signal the quality of the measuring signals on the basis of an evaluation of one or more parameters such as perfusion index, transmission level, interference level, the signal form or the like.
12. A medical measuring device as claimed in any one of the preceding claims,
25 characterized in that the at least one measuring apparatus is a pulsoximeter (14, 18), an ECG recorder (12, 16) and/or ultrasound measuring head.

1/1




Fig. 1

INTERNATIONAL SEARCH REPORT

International Application No
PCT/IB2004/052511

A. CLASSIFICATION OF SUBJECT MATTER
IPC 7 A61B5/00

According to International Patent Classification (IPC) or to both national classification and IPC

B. FIELDS SEARCHED
Minimum documentation searched (classification system followed by classification symbols)
IPC 7 A61B

Documentation searched other than minimum documentation to the extent that such documents are included in the fields searched

Electronic data base consulted during the international search (name of data base and, where practical, search terms used)
EPO-Internal

C. DOCUMENTS CONSIDERED TO BE RELEVANT

Category °	Citation of document, with indication, where appropriate, of the relevant passages	Relevant to claim No.
X	US 6 415 166 B1 (BRASHEARS MICHAEL K ET AL) 2 July 2002 (2002-07-02) column 3, line 6 - line 12 column 4, line 33 - line 48	1,3,6-8, 10-12
A	column 5, line 63 - column 6, line 3	4,5
X	US 2003/120164 A1 (RYZIN PATRICK A VAN ET AL) 26 June 2003 (2003-06-26) paragraphs '0029!, '0048!, '0081!	1,3,6-8, 10-12
A		4,5
X	US 2002/161291 A1 (CAROTHERS DON ET AL) 31 October 2002 (2002-10-31) paragraph '0084! paragraph '0085!, first sentence figure 1c	1,3,9, 11,12
	----- -/--	

Further documents are listed in the continuation of box C. Patent family members are listed in annex.

° Special categories of cited documents :

A document defining the general state of the art which is not considered to be of particular relevance

E earlier document but published on or after the international filing date

L document which may throw doubts on priority claim(s) or which is cited to establish the publication date of another citation or other special reason (as specified)

O document referring to an oral disclosure, use, exhibition or other means

P document published prior to the international filing date but later than the priority date claimed

T later document published after the international filing date or priority date and not in conflict with the application but cited to understand the principle or theory underlying the invention

X document of particular relevance; the claimed invention cannot be considered novel or cannot be considered to involve an inventive step when the document is taken alone

Y document of particular relevance; the claimed invention cannot be considered to involve an inventive step when the document is combined with one or more other such documents, such combination being obvious to a person skilled in the art.

& document member of the same patent family

Date of the actual completion of the international search 17 January 2005	Date of mailing of the international search report 24/01/2005
---	---

Name and mailing address of the ISA European Patent Office, P.B. 5818 Patentlaan 2 NL - 2280 HV Rijswijk Tel. (+31-70) 340-2040, Tx. 31 651 epo nl, Fax: (+31-70) 340-3016	Authorized officer Knüpling, M
--	--

INTERNATIONAL SEARCH REPORT

International Application No
PC., -B2004/052511

C.(Continuation) DOCUMENTS CONSIDERED TO BE RELEVANT

Category °	Citation of document, with indication, where appropriate, of the relevant passages	Relevant to claim No.
X	US 5 170 791 A (BOOS ANDREAS ET AL) 15 December 1992 (1992-12-15) column 2, line 21 - line 26 column 3, line 49 - line 64	1,3-8, 10-12
A	US 2002/035315 A1 (BREED DIVYA S ET AL) 21 March 2002 (2002-03-21) paragraph '0090!	1,2

INTERNATIONAL SEARCH REPORT

 Int. Patent Application No
 PCT/JP2004/052511

Patent document cited in search report		Publication date	Patent family member(s)	Publication date
US 6415166	B1	02-07-2002	US 2004102687 A1	27-05-2004
US 2003120164	A1	26-06-2003	DE 10259780 A1 FR 2834628 A1 JP 2003220045 A	03-07-2003 18-07-2003 05-08-2003
US 2002161291	A1	31-10-2002	US 6770028 B1 US 6584336 B1 EP 1309270 A1 WO 0215781 A1 US 2002140675 A1 US 2003197679 A1 AU 2859600 A CA 2358454 A1 EP 1148809 A1 JP 2002535026 T WO 0042911 A1	03-08-2004 24-06-2003 14-05-2003 28-02-2002 03-10-2002 23-10-2003 07-08-2000 27-07-2000 31-10-2001 22-10-2002 27-07-2000
US 5170791	A	15-12-1992	NONE	
US 2002035315	A1	21-03-2002	US 6606511 B1 EP 1389945 A2 JP 2004528913 T WO 02091918 A2 US 2004133087 A1 EP 1139858 A1 JP 2002534146 T WO 0040147 A1	12-08-2003 25-02-2004 24-09-2004 21-11-2002 08-07-2004 10-10-2001 15-10-2002 13-07-2000

专利名称(译)	医疗测量设备		
公开(公告)号	EP1691677A1	公开(公告)日	2006-08-23
申请号	EP2004799213	申请日	2004-11-23
[标]申请(专利权)人(译)	皇家飞利浦电子股份有限公司		
申请(专利权)人(译)	飞利浦知识产权及标准部GMBH 皇家飞利浦电子N.V.		
当前申请(专利权)人(译)	飞利浦知识产权及标准部GMBH 皇家飞利浦电子N.V.		
[标]发明人	NEUMANN ROLF PHILIPS INT PROP & STANDARDS GMBH		
发明人	NEUMANN, ROLF PHILIPS INT. PROP. &, STANDARDS GMBH		
IPC分类号	A61B5/00 A61B5/0404 A61B8/00		
CPC分类号	G06F11/0784 A61B5/0002 A61B5/0404 A61B5/1455 A61B5/7221 A61B8/00 G16H40/63		
优先权	2003104501 2003-12-02 EP		
外部链接	Espacenet		

摘要(译)

本发明涉及一种医疗测量装置 (10) , 其包括至少一个测量装置 (12,14) , 该测量装置具有至少一个传感器 (16,18) , 用于产生患者 (20,22) 的测量信号。还提供了测量数据检测装置 (24) , 其设计用于通过特别是无线通信路径 (24,26) 与至少一个测量装置 (12,14) 交换测量信号。至少一个测量装置 (12,14) 设计用于发信号通知测量信号的质量。