

(19)



(11)

EP 2 336 845 B1

(12)

EUROPEAN PATENT SPECIFICATION

(45) Date of publication and mention of the grant of the patent:
17.02.2016 Bulletin 2016/07

(51) Int Cl.:
G06F 1/32 (2006.01) A61B 5/00 (2006.01)

(21) Application number: **11158725.9**

(22) Date of filing: **27.09.2007**

(54) **Sensor device with persistent low power beacon**

Sensorvorrichtung mit Bake mit durchgehend niedriger Leistung

Dispositif capteur avec une balise persistante à basse puissance

(84) Designated Contracting States:
AT BE BG CH CY CZ DE DK EE ES FI FR GB GR HU IE IS IT LI LT LU LV MC MT NL PL PT RO SE SI SK TR

(30) Priority: **28.09.2006 US 529046**

(43) Date of publication of application:
22.06.2011 Bulletin 2011/25

(60) Divisional application:
15199548.7

(62) Document number(s) of the earlier application(s) in accordance with Art. 76 EPC:
07852437.8 / 2 076 828

(73) Proprietor: **NIKE Innovate C.V.**
Beaverton, OR 97005-6453 (US)

(72) Inventor: **Blackadar, Thomas, P.**
Natick, MA 01760 (US)

(74) Representative: **McCartney, Jonathan William et al**
Haseltine Lake LLP
Redcliff Quay
120 Redcliff Street
Bristol BS1 6HU (GB)

(56) References cited:
TW-U- M 273 770 US-A1- 2006 035 590
US-B1- 6 334 848

EP 2 336 845 B1

Note: Within nine months of the publication of the mention of the grant of the European patent in the European Patent Bulletin, any person may give notice to the European Patent Office of opposition to that patent, in accordance with the Implementing Regulations. Notice of opposition shall not be deemed to have been filed until the opposition fee has been paid. (Art. 99(1) European Patent Convention).

Description

FIELD

[0001] This application relates generally to power management of remote sensor devices.

BACKGROUND

[0002] Some remote sensor devices are capable of communicating a signal to a primary device indicating when the remote device is low on power. Upon receiving such a signal, the primary device may warn its user that the remote device is low on power, and thus enable the user to recharge or replace the battery of the remote device before the remote device actually runs out of power. One example of such a system is a computer that employs wireless user input (UI) devices, such as a wireless mouse or keyboard. When such UI devices are low on power, a signal is communicated to the computer's processor indicating the low power condition, and the computer then displays a message to the user warning of the same. If the user subsequently fails to replace or recharge the battery promptly, the remote device continues to operate normally until it has completely run out of power. At such time, the remote device becomes incapable not only of performing its intended function but also of informing the primary device of the reason it has become inoperable.

[0003] US Patent Application No. US2006/0226999 discloses a wireless input device with a low voltage mandatory alert function, including: a battery for supplying power for the wireless input device; a microcontroller for handling the input signals of the wireless input device. The device is characterized in that the microcontroller is used for detecting the voltage of the battery; when the voltage is lowered to the lower limit voltage, the wireless input device can no longer operate. US Patent Application No. US2006/0226999 claims priority from TW 273770Y.

SUMMARY

[0004] According to one aspect of the present invention, a method involves a first device comprising a sensor configured to sense a stimulus experienced by the first device, a controller configured to process data received from the sensor and thereby obtain processed sensor data, a transmitter configured to wirelessly transmit the processed data from the first device to a second device, and a battery configured to supply power to at least the controller and the transmitter. The first device is operated in a first operational mode in which the sensor, the controller, and the transmitter are used at least occasionally to obtain and transmit processed data to the second device. When it is determined that the battery is in a low power condition, the first device is operated in a second operational mode wherein the sensor, controller, and

transmitter are not used to obtain and transmit processed sensor data to the second device, but wherein the first device at least occasionally transmits a signal to the second device that indicates a low power condition of the battery.

[0005] According to another aspect, an apparatus comprises a sensor, a controller, a transmitter, and a battery. The sensor is configured to sense a stimulus experienced by the apparatus. The controller is configured to process data received from the sensor and thereby obtain processed sensor data. The transmitter is configured to wirelessly transmit the processed sensor data from the apparatus to another device. The battery is configured to supply power to at least the controller and the transmitter. The apparatus is configured to operate in a first operational mode when a determination is made that the battery is not in a low power condition, and to operate in a second operational mode when a determination is made that the battery is in a low power condition. In the first operational mode, the sensor, the controller, and the transmitter are used at least occasionally to obtain and transmit processed sensor data to the other device. In the second operational mode, the sensor, controller, and transmitter do not obtain and transmit processed sensor data to the other device, but the apparatus at least occasionally transmits a signal to the other device that indicates a low power condition of the battery.

[0006] According to another aspect, a method involves use of a first device comprising a sensor configured to sense a stimulus experienced by the first device, a controller configured to process data received from the sensor and thereby obtain processed sensor data, a transmitter configured to wirelessly transmit the processed data from the first device to a second device, a receiver configured to receive data transmitted wirelessly from the second device to the first device, and a battery configured to supply power to at least the controller, the transmitter, and the receiver. The first device is operated in a first operational mode in which the sensor, the controller, and the transmitter are used at least occasionally to obtain and transmit processed data to the second device, and in which the receiver is used at least occasionally to receive data transmitted wirelessly from the second device. When it is determined that the battery is in a low power condition, the first device is operated in a second operational mode wherein the receiver is not used to receive data transmitted wirelessly from the second device, but wherein the transmitter is used at least occasionally to transmit a signal to the second device that indicates a low power condition of the battery.

BRIEF DESCRIPTION OF THE DRAWINGS

[0007]

Fig. 1 is a block diagram of an illustrative embodiment of a remote sensor apparatus; and Figs. 2-4 are flow charts showing examples of rou-

times that may be executed by the controller shown in Fig. 1.

DETAILED DESCRIPTION

[0008] In some embodiments, upon detecting a "low power" condition of a remote sensor device, the mode of operation of the remote device may be changed so as to substantially reduce its rate of power consumption. The remote device may then be allowed to perform only a limited set of functions, and may continue to transmit a "low power" signal to a primary device for an extended period of time in spite of its decreased functionality. In certain embodiments, the remote device may be configured so that the only function it performs while in its "low power" mode of operation is the transmission of a signal to the primary device informing the primary device of its "low power" condition. In some embodiments, the capacity or usage of the battery may additionally be monitored to determine when the battery is soon to be in a "low power" condition and a signal is transmitted indicating such to be the case, thus enabling the user to be warned that the battery is "running low and needs to be replaced soon," or to be provided with some similar message or indication. Should the user fail to replace the battery before the "low power" condition is actually reached, the device will not simply cease working, but will change modes of operation so as to substantially reduce its power consumption and will continue to inform the user of the "lower power" condition of the battery. Accordingly, unlike with prior art remote sensor devices that cease all operations after they run out of power, a user of a device like that disclosed herein will not be left guessing as to whether the system including the remote device ceased working because the remote device ran out of power or because of some other reason, such as failure of one or more other components of the remote device or failure of one or more components of the receiving device.

[0009] Fig. 1 is a block diagram of an example of a remote sensor device 100 that may be employed in connection with certain embodiments of the invention. As shown, the device 100 may include a controller 102, a sensor 104, a battery 106, a memory 108, a transmitter 110, an antenna 112, and a battery monitoring unit 114. A remote sensor device 100 configured generally as shown in Fig. 1 can be configured in any of a number of ways and can be used for any of a number of purposes, and the invention is not limited to any particular type of device or use thereof. In certain embodiments, for example, the remote sensor device 100 may comprise an ambulatory device that is mounted on or within a shoe or otherwise supported by a person to monitor activity of the person while he or she is walking or running or is otherwise in locomotion on foot. Examples of such devices are disclosed, for example, in U.S. Patent Nos. 6,611,789; 6,305,221; 6,301,964; 6,298,413; 6,032,108; 6,018,705; 5,955,667; 4,578,769; and 4,371,945, the entire contents of each of which is incorporated herein by

reference. Alternatively, the remote sensor device 100 may comprise, for example, a wireless mouse or a wireless keyboard for a computer, or any other device capable of sensing one or more stimuli and communicating data concerning a sensed stimulus to another device via a wireless communications link.

[0010] The sensor 104 may comprise any device that is capable of sensing an external stimulus, and the invention is not limited to the use of any particular type of sensor. It may, for example, comprise an accelerometer such as that disclosed in U.S. Patent No. 6,336,365, which is incorporated herein by reference in its entirety, or may comprise any of the sensors disclosed in U.S. Pat. Nos. 6,611,789; 6,305,221; 6,301,964; 6,298,413; 6,032,108; 6,018,705; 5,955,667; 4,578,769; and 4,371,945. Alternatively, it may comprise, as but a few examples, another type of accelerometer, a vibration sensor, a temperature sensor, a humidity sensor, a light sensor, an audio detector, an electrical or magnetic field sensor, etc. Any number of sensors of the same type, or any combination of different types of sensors may be employed in various embodiments. It should be appreciated that the sensor 104 may additionally comprise certain signal processing elements, e.g., one or more amplifiers, buffers, filters, etc., arranged to condition a signal generated by a transducer, e.g., an accelerometer such as that disclosed in U.S. Patent No. 6,336,365, prior to providing the signal to the controller 102.

[0011] The controller 102 may, for example, comprise one or more processors capable of receiving and processing data from the sensor 104. Any type or number of controllers may be employed and the invention is not limited to the use of a controller of any particular type or configuration. As shown in Fig. 1, the controller 102 may have an associated memory 108 in which data and instructions accessed by the controller 102 may be stored to enable the controller 102 to execute various routines. The memory 108 may be embodied either separately or integrally with the controller 102. Examples of routines that may be performed by the controller 102 in connection with certain embodiments of the invention are described below in connection with Figs. 2-4.

[0012] The transmitter 110 and associated antenna 112 may take on any of numerous forms and may be employed, for example, to wirelessly transmit processed data from the sensor to another device, e.g., a wristwatch, a portable music player, a computer, etc. In some embodiments, a receiver (not shown) may additionally be employed in the device 100 to receive incoming wireless signals, or a transceiver, that can both transmit and receive wireless signals, may instead be used.

[0013] The battery 106 may be responsible for supplying power to all of the components in the remote device 100. It may take on any of numerous forms, and the invention is not limited to the use of a battery of any particular type or configuration. The specific type and energy capacity of the battery may be chosen based on the application at hand. In an embodiment in which the battery

is used to power a shoe-mounted remote sensor device that is used to monitor performance parameters of a user in locomotion on foot, the battery may, for example, be a CR2032 Lithium coin cell having a capacity of 200 milliamp hours (mAh).

[0014] The battery monitoring unit 114 may comprise any known device or circuit capable of monitoring the remaining capacity of the battery 106. Such devices and the techniques they employ are well understood in the art and thus will not be described herein. As discussed in more detail below, in some embodiments, a "low power" condition of the battery 106 may be determined not by directly monitoring a state of the battery, but rather based upon monitoring or estimating the cumulative power consumption of the components in the device 100. Accordingly, at least in some embodiments, a battery monitoring unit 114 like that shown would not be required.

[0015] Fig. 2 shows an illustrative example of a routine 200 that may be executed by the controller 102 shown in Fig. 1. As noted above, instructions for the routine 200 may, for example, be stored in the memory 108 associated with the controller 102. As shown, the routine 200 may begin at a step 202 wherein the controller is "initialized." Such initialization may occur, for example, when a new battery 106 is installed in the device 100, in response to a user command, or by some other mechanism.

[0016] After initialization, the routine 200 proceeds to steps 204 and 206, wherein one or more sensors and controllers are placed in an "active" mode to enable them to perform their data accumulation and processing functions. In some embodiments, for example, an accelerometer and a processor may be caused to begin actively accumulating and analyzing data concerning footsteps taken by a user in locomotion on foot. It should be appreciated, however, that in certain embodiments, the step 204 may involve the activation of one or more signal processing elements, e.g., amplifiers, buffers, filters, etc., associated with a transducer (not shown) in addition to or in lieu of activating the transducer itself. It should further be appreciated that, in some embodiments a sensor may be employed that does not itself consume power, and the step 204 may thus be omitted in such embodiments.

[0017] After "activating" the sensor 104 (if necessary) and the controller 102, the routine 200 proceeds to a step 208, wherein data accumulated by the sensor may be processed in an appropriate fashion. As discussed in more detail below, in connection with the step 208, processed data from the sensor 104 may be transmitted wirelessly to another device via the transmitter 110 and antenna 112 of the device 100.

[0018] At the step 210, the routine 200 next determines whether any new data is being accumulated by the sensor 104. Such a determination may, for example, involve an assessment of whether the sensor 104 has ceased generating a signal or data for more than a particular period of time, e.g., several seconds. When it is deter-

mined that the sensor has ceased accumulating data, the routine 200 proceeds to steps 212 and 214, wherein the one or more sensors and controllers may be taken out of their "active" mode and placed in a "sleep" mode for power preservation purposes. As noted above, in embodiments in which the sensor 104 does not require power in order to be "active," the step 212 may be omitted.

[0019] After placing the device 100 in a "sleep" mode, the routine 200 waits at a step 216 until a determination is made that the device should "wake up" to begin actively processing and accumulating data once again. The determination of whether and when to wake up may be made, for example, by monitoring an output of the sensor 104 (or a transducer included therein) for activity, in a response to a user input, e.g., depression of a "start" button, or by any other mechanism. In embodiments in which a sensor is used to monitor locomotion of a person on foot, the "wake up" determination 216 may be made, for example, by employing a low-power comparator (not shown) to monitor the output of a transducer. In embodiments in which an accelerometer that does not consume power, e.g., the accelerometer disclosed in U.S. Pat. No. 6,336,365, is employed as the transducer, the power consumption of the device 100 in the "sleep" mode may thus be substantially limited to only the power consumption of such a comparator. It should be appreciated that in addition to such an automated "wake up" function, the device 100 may additionally or alternatively comprise one or more user input devices, e.g., switches or pushbuttons, that may be manipulated to cause the device 100 to "wake up." Furthermore, one or more user input devices may additionally or alternatively be provided that can be manipulated to cause the device 100 to be put into a "sleep" mode, or even to cause the device to be powered down completely so that even the automated "wake up" function is disabled until further user input is provided.

[0020] Referring again to Fig. 2, when at the step 210 (discussed above) it is determined that new data is being accumulated by the sensor 104, the routine 200 proceeds to a step 218, wherein it is determined whether the battery 106 is in a "low power" condition, e.g., by determining whether the capacity of the battery 106 has been depleted below a particular level. When, it is determined that the battery is not in a "low power" condition, the routine 200 returns to the step 208, wherein the sensor data continues to be accumulated and processed. When, it is determined that the battery 106 is in a "low-power" condition, however, the routine 200 proceeds to a step 220, wherein the device is placed in a "life support mode" (discussed in more detail below in connection with Fig. 4.) In alternative embodiments, the step 218 may additionally or alternatively be performed at other points in the routine 200, and it is not critical that it be performed immediately after determining whether new sensor data is being accumulated. For example, in some embodiments, the step 218 may additionally or alternatively be performed immediately after the step 206 and/or between

the steps 208 and 210.

[0021] The determination of whether the battery 106 is in a "low power" condition may be made in any of a number of ways, and the invention is not limited to any particular technique or mechanism for making such a determination. In some embodiments, the remaining capacity of the battery 106 may be measured directly by the battery monitoring unit 114 capacity monitoring techniques that may be employed by the battery monitoring unit are well known in the art and thus will not be described in further detail. The determination of whether the battery 106 is in a "low power" condition may thus be made by evaluating whether the measured remaining capacity is below a particular threshold. In other embodiments, the controller 102 or some other device may additionally or alternatively track the cumulative power consumption of the various components in the device 100, or estimate such consumption based on cumulative time of use in various modes, and the determination of whether the battery 106 is in a "low power" condition may thus be made by evaluating whether the determined total power usage since installation of a new battery is above a particular threshold.

[0022] No matter how the "low power" determination is made, a threshold level may be set that allocates the total power capacity of the battery 106 between a first period in which the device 100 is in its "operational mode" and a second, subsequent period during which the device 100 is in its "life support mode," so as to achieve desired operational objectives. For instance, if it is desired that the device 100 be capable of transmitting a "life support beacon" once every hour for a period of two years after the primary functionality of the device has been shut down, then the threshold level may be set accordingly. The portion of the total capacity of the battery 106 that is to be used for "life support" may be calculated, for example, by multiplying the desired total number of "life support beacons" by the power consumed by each beacon transmission. The allocation of the total capacity of the battery may also, of course, take into account the desired lifetime of the device 100 in its "operational mode."

[0023] It should be appreciated that, in addition to determining whether the "low power" condition discussed above has been reached, the capacity or usage of the battery may additionally be monitored to determine when the battery is soon to be in the "low power" condition. This may be achieved, for example, by employing the same technique used to monitor for the "low power" condition, but using a slightly higher or lower threshold. When such a determination is made, a signal may be transmitted via the transmitter 110 and antenna 112 that informs the primary device that the battery 106 is running low and needs to be replaced. The message or indication provided to the user as a result of such a signal may either be the same as that provided in response to the low power beacon, or may be a different message. For example, in response to a signal indicating the battery is approaching

the "low power" condition, a message may be displayed informing the user the battery is "running low," whereas in response to a signal indicating the "low power" condition has already been reached, the message may inform the user that the battery is "out of power."

[0024] Fig. 3 shows an illustrative example of the routine 208 (Fig. 2) that may be employed by a device that senses activity of a person in locomotion on foot, for example, by employing one or more accelerometers to monitor motion of the person. In the illustrative example shown, the routine 208 begins at a step 302, wherein "foot contact times" of a person, i.e., amounts of time during in which a person's foot is on the ground during respective footsteps taken by the person, are determined by examining the output of the sensor 104. Based on the measured foot contact times, the routine 208 may then calculate performance parameters such as pace, distance traveled, speed, etc., (step 304), and subsequently transmit such information to another device via the transmitter 110 and antenna 112 (step 306). The routine 208 shown in Fig. 3 is, of course, but only one example of a routine that may employed to accumulate, process, and transmit sensor data to another device. Other examples of additional or alternative routines that may be employed in connection with various embodiments of the invention are disclosed in U.S. Patent Nos. 6,611,789; 6,305,221; 6,301,964; 6,298,413; 6,032,108; 6,018,705; 5,955,667; 4,578,769; and 4,371,945, discussed above. A radio transmission protocol such as that disclosed in U.S. Patent No. 7,187,924, or any other suitable protocol, may be employed to communicate data and/or commands between the device 100 and the other device. In some embodiments, a routine 208 such as that illustrated in Fig. 3 will be performed only when the device 100 is in its "operational mode," and may, for example, require the battery 106 to supply approximately two milliamps of current to the various components of the device 100.

[0025] Fig. 4 shows an illustrative example of a routine that may be employed when the device 100 is placed in a "life support mode" (step 200 in Fig. 2). In the example shown, the only activity for which the device 100 is allowed to consume power is to transmit a "life support beacon," e.g., a signal indicating that the device has run out of power, at least occasionally. Such a "life support" routine may, for example, require the battery 106 to supply approximately 6 micro-amps of current to the various components of the device 100. It should be appreciated, however, that the device 100 may alternatively be configured so that some additional level of activity beyond the transmission of a "life support beacon" may be permitted. All that is important is that the modality of the device 100 be changed in some way so that certain power-consuming activities cease when the device 100 enters the "life support mode." In some embodiments, when the device 100 is placed in its "life support mode," the modality of the radio transmission protocol employed by the device 100 may also be changed so as to further minimize its power consumption. For example, in embodi-

ments in which a two-way radio transmission protocol is employed to wirelessly communicate data between the device 100 and another device when the device 100 is in its "operational mode," the device 100 may further conserve power by switching to a one-way radio transmission protocol, e.g., to allow only the transmission of a "life-support beacon" but not the receipt of incoming messages, upon entering its "life support mode."

[0026] In the example of Fig. 4, the routine 220 first involves de-activating the sensor 104 and/or the processor 102 (steps 402 and 404) so that the controller 102 ceases processing data accumulated by the sensor 104 and transmitting processed sensor data via the transmitter 110 and antenna 112. In the example shown, the controller 102 may be deactivated except to the extent necessary to transmit a life support beacon each time the device 100 "wakes up" for such a purpose. As noted above, some embodiments may employ a sensor 104 that need not be deactivated, and the step 402 need not be employed in such circumstances.

[0027] The "wake up" step 408 may involve, for example, waking up once every minute, once every ten minutes, once every hour, etc., with a period depending upon the type of sensor that is employed and the use to which it is being put. Additionally or alternatively, the step 408 may involve sensing an external stimulus, for example, sensing motion that indicates that perhaps a user is attempting to put the device to use. In some embodiments, for example, an output of an accelerometer may be monitored to determine whether the signal exceeds a certain threshold. In certain such embodiments, power consumption in the "life support mode" may be limited significantly by basing the wake up decision in whole or in part upon the output of a low-power comparator that compares the output of an accelerometer such as that disclosed in U.S. Pat. No. 6,336,365 to a threshold voltage.

[0028] The step 408 may additionally or alternatively involve the manipulation of a user input mechanism, e.g., a pushbutton, that may cause the device to transmit a beacon upon activation of the mechanism, or may simply allow the device to "wake up" in response to a sensed stimulus and/or periodically (as discussed above), for some period of time after the mechanism has been activated. In some embodiments, a low-power receiver may additionally or alternatively be used to determine whether and when another device is attempting to communicate with the remote device 100, and the "life support beacon" may be transmitted upon detection of such a communication attempt. Any combination of the above techniques may also be employed. For example, the device may attempt to send a message once every minute during time periods after a pushbutton has been depressed or after a determination is made that the device 100 is in motion.

[0029] Having described several embodiments of the invention in detail, various modifications and improvements will readily occur to those skilled in the art. Such modifications and improvements are intended to be with-

in the scope of the invention. Accordingly, the foregoing description is by way of example only, and is not intended as limiting. The invention is limited only as defined by the following claims and the equivalents thereto.

Claims

1. A method, comprising steps of:

(a) providing a first device comprising a sensor configured to sense a stimulus experienced by the first device, a controller configured to receive data from the sensor, a transceiver configured to wirelessly transmit the data from the first device to a second device, and a battery configured to supply power to at least the controller and the transceiver;

(b) operating the first device in a first operational mode;

(c) determining whether the battery is in a low power condition;

(d) when it is determined that the battery is in a low power condition, operating the first device in a second operational mode, wherein certain power-consuming activities cease when the first device enters the second operational mode; and

(e) when an external stimulus sensed by the first device exceeds a threshold, operating the first device to transmit a signal to the second device that indicates a low power condition of the battery.

2. The method of claim 1, wherein the sensor further comprises at least one of the following transducers: an accelerometer, a vibration sensor, a temperature sensor, a humidity sensor, a light sensor, an audio detector, an electrical or magnetic field sensor, and the external stimulus comprises an output of the at least one transducer.

3. The method of claim 2, wherein the sensor further comprises a signal processing element arranged to condition data from the at least one transducer prior to the sensor providing the data to the controller.

4. The method of claim 2 or 3, wherein the sensor further comprises an accelerometer and a low-power comparator configured to compare the output of the accelerometer to a threshold voltage, and transmission of the signal to the second device that indicates a low power condition of the battery is performed in dependence in whole or in part upon the output of the low-power comparator.

5. The method of claim 2 or 3, wherein the sensor further comprises an accelerometer and the first device is configured to use the accelerometer to determine

- a foot contact times value relating to a wearer of the first device.
6. The method of claim 5, wherein the first device is further configured to calculate a performance parameter value based on the determined foot contact times value.
7. The method of any preceding claim, wherein the first device is configured to receive an input from a user of the first device involving manipulation of a user input mechanism, the first device being arranged to transmit a signal to the second device that indicates a low power condition of the battery in response to the input,
8. The method of claim 1, wherein the external stimulus is motion that indicates that a user is attempting to put the first device to use.
9. The method of any preceding claim, wherein the determining whether the battery is in the low power condition comprises a determination selected from the group consisting of: whether the remaining capacity of the battery is below a particular value, whether the first device has consumed more than a particular amount of power from the battery, an estimation of cumulative power consumption of various components in the first device, an estimation of cumulative time of use in one or more operational modes, or whether a determined total power usage since an installation of a new battery is above a particular threshold.
10. An apparatus, comprising:
- a sensor configured to sense a stimulus experienced by the apparatus;
 - a controller configured to receive data from the sensor;
 - a transceiver configured to wirelessly transmit the sensor data from the apparatus to a second device and receive data from the second device; and
 - a battery configured to supply power to at least the controller and the transceiver;
- wherein the apparatus is configured to operate in a first operational mode when a determination is made that the battery is not in a low power condition, and to operate in a second operational mode when a determination is made that the battery is in a low power condition wherein certain power-consuming activities cease when the apparatus enters the second operational mode, and when an external stimulus sensed by the apparatus exceeds a threshold, to operate to transmit a signal to the second device that indicates a low power condition of the battery.
11. The apparatus of claim 10, wherein the sensor further comprises at least one of the following transducers: an accelerometer, a vibration sensor, a temperature sensor, a humidity sensor, a light sensor, an audio detector, an electrical or magnetic field sensor, and the external stimulus comprises an output of the at least one transducer.
12. The apparatus of claim 11, wherein the sensor further comprises a signal processing element arranged to condition data from the at least one transducer prior to the sensor providing the data to the controller.
13. The apparatus of claim 11 or 12, wherein the sensor further comprises an accelerometer and a low-power comparator configured to compare the output of the accelerometer to a threshold voltage, and transmission of the signal to the second device that indicates a low power condition of the battery is performed in dependence in whole or in part upon the output of the low-power comparator.
14. The apparatus of claim 11 or 12, wherein the sensor further comprises an accelerometer and the apparatus is configured to use the accelerometer to determine a foot contact times value relating to a wearer of the first device.

Patentansprüche

1. Verfahren, welches folgende Schritte umfasst:

- (a) Bereitstellen eines ersten Gerätes, welches einen Sensor, der zum Abtasten eines Stimulus, der durch das erste Gerät wahrgenommen wird, konfiguriert ist, einen Controller, der zum Empfangen von Daten von dem Sensor konfiguriert ist, einen Sendeempfänger, der zum drahtlosen Übertragen der Daten von dem ersten Gerät an ein zweites Gerät konfiguriert ist, und eine Batterie, die zum Bereitstellen von Energie an mindestens den Controller und den Sendeempfänger konfiguriert ist, umfasst;
- (b) Betreiben des ersten Gerätes in einem ersten Betriebsmodus;
- (c) Bestimmen, ob sich die Batterie in einem Niedrigenergiezustand befindet;
- (d) wenn bestimmt wird, dass sich die Batterie in einem Niedrigenergiezustand befindet, Betreiben des ersten Gerätes in einem zweiten Betriebsmodus, wobei bestimmte stromverbrauchende Aktivitäten wegfallen, wenn das erste Gerät in den zweiten Betriebsmodus schaltet; und
- (e) wenn ein externer Stimulus, der durch das erste Gerät erfasst wird, eine Schwelle über-

- steigt, Betreiben des ersten Gerätes zum Übertragen eines Signals an das zweite Gerät, das einen Niedrigenergiezustand der Batterie anzeigt.
2. Verfahren nach Anspruch 1, wobei der Sensor ferner mindestens einen der folgenden Messumformer umfasst: einen Beschleunigungsmesser, einen Vibrationssensor, einen Temperatursensor, einen Feuchtigkeitssensor, einen Lichtsensor, einen Audiodektor, einen elektrischen oder magnetischen Feldsensor, und der externe Stimulus eine Ausgabe des mindestens einen Messumformers umfasst.
 3. Verfahren nach Anspruch 2, wobei der Sensor ferner ein Signalverarbeitungselement umfasst, dass zum Konditionieren von Daten von dem mindestens einen Messumformer, bevor der Sensor die Daten an den Controller bereitstellt, geeignet ist.
 4. Verfahren nach Anspruch 2 oder 3, wobei der Sensor ferner einen Beschleunigungsmesser und einen Niedrigenergiekomparator umfasst, der zum Vergleichen der Ausgabe des Beschleunigungsmessers mit einer Schwellenspannung konfiguriert ist, und die Übertragung des Signals an das zweite Gerät, das einen Niedrigenergiezustand der Batterie anzeigt, erfolgt komplett oder teilweise in Abhängigkeit von der Ausgabe des Niedrigenergiekomparators.
 5. Verfahren nach Anspruch 2 oder 3, wobei der Sensor ferner einen Beschleunigungsmesser umfasst und das erste Gerät zum Verwenden des Beschleunigungsmessers zum Bestimmen eines Fußkontaktzeiten-Wertes in Bezug auf einen Träger des ersten Gerätes konfiguriert ist.
 6. Verfahren nach Anspruch 5, wobei das erste Gerät ferner zum Berechnen eines Leistungsparameterwertes auf der Grundlage des bestimmten Fußkontaktzeiten-Wertes konfiguriert ist.
 7. Verfahren nach einem der vorhergehenden Ansprüche, wobei das erste Gerät zum Empfangen einer Eingabe von einem Benutzer des ersten Gerätes, welche eine Manipulation eines Benutzereingabemechanismus beinhaltet, konfiguriert ist, wobei das erste Gerät zum Übertragen eines Signals an das zweite Gerät, das als Reaktion auf die Eingabe einen Niedrigenergiezustand der Batterie anzeigt, geeignet ist.
 8. Verfahren nach Anspruch 1, wobei der externe Stimulus eine Bewegung ist, die anzeigt, dass ein Benutzer versucht, das erste Gerät anzuwenden.
 9. Verfahren nach einem der vorhergehenden Ansprüche, wobei das Bestimmen, ob sich die Batterie in dem Niedrigenergiezustand befindet, eine Bestimmung ausgewählt aus der Gruppe bestehend aus Folgenden umfasst: ob die verbleibende Kapazität der Batterie unter einem bestimmten Wert liegt, ob das erste Gerät mehr als eine bestimmte Energiemenge aus der Batterie verbraucht hat, eine Schätzung des kumulativen Energieverbrauchs verschiedener Komponenten in dem ersten Gerät, eine Schätzung einer kumulativen Zeit der Verwendung in einem oder mehreren Betriebsmodi, oder ob eine bestimmte Gesamtenergienutzung seit einer Installation einer neuen Batterie über einer bestimmten Schwelle liegt.
 10. Vorrichtung, welche Folgendes umfasst:
 - einen Sensor, der zum Abtasten eines Stimulus, der durch die Vorrichtung wahrgenommen wird, konfiguriert ist;
 - einen Controller, der zum Empfangen von Daten von dem Sensor konfiguriert ist;
 - einen Sendeempfänger, der zum drahtlosen Übertragen der Sensordaten von der Vorrichtung an ein zweites Gerät und Empfangen von Daten von dem zweiten Gerät konfiguriert ist; und
 - eine Batterie, die zum Bereitstellen von Energie an mindestens den Controller und den Sendeempfänger konfiguriert ist;
 - wobei die Vorrichtung zum Arbeiten in einem ersten Betriebsmodus, wenn eine Bestimmung erfolgt, dass sich die Batterie nicht in einem Niedrigenergiezustand befindet, und zum Arbeiten in einem zweiten Betriebsmodus, wenn eine Bestimmung erfolgt, dass sich die Batterie in einem Niedrigenergiezustand befindet, wobei bestimmte stromverbrauchende Aktivitäten weggelassen, wenn die Vorrichtung in den zweiten Betriebsmodus schaltet, und wenn ein externer Stimulus, der durch die Vorrichtung erfasst wird, eine Schwelle übersteigt, zum Arbeiten zum Übertragen eines Signals an das zweite Gerät, das einen Niedrigenergiezustand der Batterie anzeigt, konfiguriert ist.
 11. Vorrichtung nach Anspruch 10, wobei der Sensor ferner mindestens einen der folgenden Messumformer umfasst: einen Beschleunigungsmesser, einen Vibrationssensor, einen Temperatursensor, einen Feuchtigkeitssensor, einen Lichtsensor, einen Audiodektor, einen elektrischen oder magnetischen Feldsensor, und der externe Stimulus eine Ausgabe von dem mindestens einen Messumformer umfasst.
 12. Vorrichtung nach Anspruch 11, wobei der Sensor ferner ein Signalverarbeitungselement umfasst, das zum Konditionieren von Daten von dem mindestens

einen Messumformer, bevor der Sensor die Daten an den Controller bereitstellt, geeignet ist.

13. Vorrichtung nach Anspruch 11 oder 12, wobei der Sensor ferner einen Beschleunigungsmesser und einen Niedrigenergiekomparator, der zum Vergleichen der Ausgabe des Beschleunigungsmessers mit einer Schwellenspannung konfiguriert ist, umfasst, und die Übertragung des Signals an das zweite Gerät, das einen Niedrigenergiezustand der Batterie anzeigt, erfolgt komplett oder teilweise in Abhängigkeit von der Ausgabe des Niedrigenergiekomparators.
14. Vorrichtung nach Anspruch 11 oder 12, wobei der Sensor ferner einen Beschleunigungsmesser umfasst und die Vorrichtung zur Verwendung des Beschleunigungsmessers zum Bestimmen eines Fußkontaktzeiten-Wertes in Bezug auf einen Träger des ersten Gerätes konfiguriert ist.

Revendications

1. Procédé comprenant les étapes suivantes :

(a) la fourniture d'un premier dispositif comprenant un capteur configuré pour détecter un stimulus subi par le premier dispositif, un dispositif de commande configuré pour recevoir des données en provenance du capteur, un émetteur-récepteur configuré pour transmettre en mode sans fil les données du premier dispositif à un second dispositif, et une batterie configurée pour alimenter au moins le dispositif de commande et l'émetteur-récepteur ;

(b) le fonctionnement du premier dispositif dans un premier mode de fonctionnement ;

(c) la détermination si oui ou non la batterie est dans une condition de basse puissance ;

(d) s'il est déterminé que la batterie est dans une condition de basse puissance, le fonctionnement du premier dispositif dans un second mode de fonctionnement, dans lequel certaines activités consommant de la puissance cessent lorsque le premier dispositif entre dans le second mode de fonctionnement ; et

(e) lorsqu'un stimulus externe détecté par le premier dispositif dépasse un seuil, le fonctionnement du premier dispositif pour transmettre un signal au second dispositif qui indique une condition de basse puissance de la batterie.

2. Procédé selon la revendication 1, dans lequel le capteur comprend au moins l'un des émetteurs-récepteurs suivants : un accéléromètre, un capteur de vibration, un capteur de température, un capteur d'humidité, un capteur de lumière, un détecteur de sons,

un capteur de champ électrique ou magnétique, et le stimulus externe comprend une sortie d'au moins un émetteur-récepteur.

3. Procédé selon la revendication 2, dans lequel le capteur comprend en outre un élément de traitement de signal conçu pour conditionner des données provenant du ou des émetteur(s)-récepteur(s) avant la fourniture des données au dispositif de commande par le capteur.
4. Procédé selon la revendication 2 ou 3, dans lequel le capteur comprend en outre un accéléromètre et un comparateur à basse puissance configuré pour comparer la sortie de l'accéléromètre à une tension de seuil, et une transmission du signal au second dispositif qui indique qu'une condition de basse puissance de la batterie est mise partiellement ou totalement en oeuvre en fonction de la sortie du comparateur à basse puissance.
5. Procédé selon la revendication 2 ou 3, dans lequel le capteur comprend en outre un accéléromètre et le premier dispositif est configuré pour utiliser l'accéléromètre pour déterminer une valeur de nombres de contact avec le pied par rapport à un porteur du premier dispositif.
6. Procédé selon la revendication 5, dans lequel le premier dispositif est en outre configuré pour calculer une valeur de paramètre de performance sur la base de la valeur de nombres de contact avec le pied déterminée.
7. Procédé selon une quelconque revendication précédente, dans lequel le premier dispositif est configuré pour recevoir une entrée en provenance d'un utilisateur du premier dispositif impliquant la manipulation d'un mécanisme d'entrée d'utilisateur, le premier dispositif étant agencé pour transmettre un signal au second dispositif qui indique une condition de basse puissance de la batterie en réponse à l'entrée.
8. Procédé selon la revendication 1, dans lequel le stimulus externe est un mouvement qui indique qu'un utilisateur tente d'utiliser le premier dispositif.
9. Procédé selon une quelconque revendication précédente, dans lequel la détermination si oui ou non la batterie est dans la condition de basse puissance comprend une détermination sélectionnée parmi le groupe composé des déterminations suivantes : si oui ou non la capacité restante de la batterie est inférieure à une valeur particulière, si oui ou non le premier dispositif a consommé une quantité de puissance supérieure à une quantité de puissance particulière provenant de la batterie, une estimation de

la consommation de puissance cumulée de divers composants dans le premier dispositif, une estimation du temps d'utilisation cumulé dans un ou plusieurs modes de fonctionnement, ou si oui ou non une consommation de puissance totale déterminée depuis une installation d'une nouvelle batterie est supérieure à un seuil particulier.

10. Appareil comprenant :

un capteur configuré pour détecter un stimulus subi par l'appareil ;

un dispositif de commande configuré pour recevoir des données en provenance du capteur ;

un émetteur-récepteur configuré pour transmettre en mode sans fil les données de capteur provenant de l'appareil à un second dispositif et recevoir des données du second dispositif ; et une batterie configurée pour alimenter au moins le dispositif de commande et l'émetteur-récepteur ;

dans lequel l'appareil est configuré pour fonctionner dans un premier mode de fonctionnement lorsqu'il est déterminé que la batterie n'est pas dans une condition de basse puissance, et pour fonctionner dans un second mode de fonctionnement lorsqu'il est déterminé que la batterie est dans une condition de basse puissance dans laquelle certaines activités consommant de la puissance cessent lorsque l'appareil entre dans le second mode de fonctionnement, et lorsqu'un stimulus externe détecté par l'appareil dépasse un seuil, pour fonctionner pour transmettre un signal au second dispositif qui indique une condition de basse puissance de la batterie.

11. Appareil selon la revendication 10, dans lequel le capteur comprend en outre au moins l'un des émetteurs-récepteurs suivants : un accéléromètre, un capteur de vibration, un capteur de température, un capteur d'humidité, un capteur de lumière, un détecteur de sons, un capteur de champ électrique ou magnétique, et le stimulus externe comprend une sortie du ou des émetteur(s)-récepteur(s).

12. Appareil selon la revendication 11, dans lequel le capteur comprend en outre un élément de traitement de signal conçu pour conditionner des données provenant du ou des émetteur(s)-récepteur(s) avant la fourniture des données au dispositif de commande par le capteur.

13. Appareil selon la revendication 11 ou 12, dans lequel le capteur comprend en outre un accéléromètre et un comparateur à basse puissance configuré pour comparer la sortie de l'accéléromètre à une tension de seuil, et une transmission du signal au second dispositif qui indique qu'une condition de basse puis-

sance de la batterie est mise partiellement ou totalement en oeuvre en fonction de la sortie du comparateur à basse puissance.

14. Appareil selon la revendication 11 ou 12, dans lequel le capteur comprend en outre un accéléromètre et l'appareil est configuré pour utiliser l'accéléromètre pour déterminer une valeur de nombres de contact avec le pied par rapport à un porteur du premier dispositif.

10

15

20

25

30

35

40

45

50

55




FIG. 1




FIG. 2




Fig. 3




Fig. 4

REFERENCES CITED IN THE DESCRIPTION

This list of references cited by the applicant is for the reader's convenience only. It does not form part of the European patent document. Even though great care has been taken in compiling the references, errors or omissions cannot be excluded and the EPO disclaims all liability in this regard.

Patent documents cited in the description

- US 20060226999 A [0003]
- TW 273770 Y [0003]
- US 6611789 B [0009] [0010] [0024]
- US 6305221 B [0009] [0010] [0024]
- US 6301964 B [0009] [0010] [0024]
- US 6298413 B [0009] [0010] [0024]
- US 6032108 A [0009] [0010] [0024]
- US 6018705 A [0009] [0010] [0024]
- US 5955667 A [0009] [0010] [0024]
- US 4578769 A [0009] [0010] [0024]
- US 4371945 A [0009] [0010] [0024]
- US 6336365 B [0010] [0019] [0027]
- US 7187924 B [0024]

专利名称(译)	具有持久低功率信标的传感器设备		
公开(公告)号	EP2336845B1	公开(公告)日	2016-02-17
申请号	EP2011158725	申请日	2007-09-27
[标]申请(专利权)人(译)	耐克国际有限公司		
申请(专利权)人(译)	NIKE INTERNATIONAL LTD		
当前申请(专利权)人(译)	NIKE INNOVATE C.V.		
[标]发明人	BLACKADAR THOMAS P		
发明人	BLACKADAR, THOMAS, P.		
IPC分类号	G06F1/32 A61B5/00		
CPC分类号	G06F1/3203 A61B5/11 A61B2560/0204 A61B2560/0209 G01C22/006		
优先权	11/529046 2006-09-28 US		
其他公开文献	EP2336845A1		
外部链接	Espacenet		

摘要(译)

一种公开的方法涉及提供第一设备，该第一设备包括：传感器，被配置为感测由第一设备经历的刺激；控制器，被配置为处理从传感器接收的数据，从而获得处理的传感器数据；发送器，被配置为从处理器无线地发送处理的数据。第一设备到第二设备，以及电池，被配置为至少向控制器和发射器供电。第一设备在第一操作模式下操作，其中传感器，控制器和发射器至少偶尔用于获得并将处理后的数据发送到第二设备。当确定电池处于低功率状态时，第一设备以第二操作模式操作，其中传感器，控制器和发射器不用于获取处理的传感器数据并将其传输到第二设备，但是其中第一设备至少偶尔向第二设备发送指示电池的低功率状态的信号。




FIG. 1