



(11)

EP 3 505 068 A1

(12)

EUROPEAN PATENT APPLICATION
published in accordance with Art. 153(4) EPC

(43) Date of publication:

03.07.2019 Bulletin 2019/27

(21) Application number: **17853365.9**

(22) Date of filing: **15.09.2017**

(51) Int Cl.:

A61B 8/00 (2006.01)	A61G 15/00 (2006.01)
A61G 15/02 (2006.01)	A61B 5/00 (2006.01)
A61B 8/08 (2006.01)	A61B 8/14 (2006.01)
A61B 5/01 (2006.01)	A61B 5/103 (2006.01)

(86) International application number:

PCT/KR2017/010147

(87) International publication number:

WO 2018/056651 (29.03.2018 Gazette 2018/13)

(84) Designated Contracting States:

**AL AT BE BG CH CY CZ DE DK EE ES FI FR GB
GR HR HU IE IS IT LI LT LU LV MC MK MT NL NO
PL PT RO RS SE SI SK SM TR**

Designated Extension States:

BA ME

Designated Validation States:

MA MD

(30) Priority: **23.09.2016 US 201662398689 P**

12.09.2017 US 201715702167

(71) Applicant: **Samsung Medison Co., Ltd.**

Hongcheon-gun, Gangwon-do 25108 (KR)

(72) Inventors:

- **PARK, Dai-un**
Hongcheon-gun
Gangwon-do 25108 (KR)
- **WOO, Kyeong-gu**
Hongcheon-gun
Gangwon-do 25108 (KR)
- **MOON, Jun-pil**
Hongcheon-gun
Gangwon-do 25108 (KR)


(74) Representative: **Jacobs, Bart et al**

Arnold & Siedsma
Bezuidenhoutseweg 57
2594 AC The Hague (NL)

(54) **MEDICAL DIAGNOSIS DEVICE AND MEDICAL DIAGNOSIS METHOD USING SAME**

(57) Provided are a medical diagnosis apparatus and a medical diagnosis method using the same. According to an embodiment, the medical diagnosis apparatus may include: a main body; a chair unit movably supported by the main body and on which an object is positioned; a diagnosis part that is movably connected to the main body and is spaced apart from the chair unit by a preset first distance in one plane; a controller configured to generate a control signal for moving the diagnosis part according to preset information; and a first driving device configured to generate a driving force for moving the diagnosis part according to the control signal.

FIG. 2



Description

TECHNICAL FIELD

[0001] The present disclosure relates to a medical diagnosis apparatus including an ultrasound probe for providing an ultrasound image and a medical chair unit and a medical diagnosis method.

BACKGROUND ART

[0002] Ultrasound diagnosis apparatuses transmit an ultrasound signal generated by a transducer of a probe to an object and receive information about a signal reflected from the object, thereby obtaining an image of an internal part of the object (e.g., soft tissue or blood flow) in a non-invasive manner.

[0003] Because ultrasound diagnosis apparatuses are compact, affordable, display images in real-time, and are highly safe for a fetus due to lack of radiation exposure compared to other types of imaging diagnosis apparatuses such as an X-ray diagnostic apparatus, a computerized tomography (CT) scanner, a magnetic resonance imaging (MRI) apparatus, a nuclear medicine diagnostic apparatus, etc., such ultrasound diagnosis apparatuses have been widely used for medical diagnosis.

[0004] An ultrasound diagnosis apparatus includes a medical chair unit on which a probe and an object can be positioned. In obstetrical and gynecological diagnosis during which ultrasound probes are widely used, an external condition of a pregnant woman corresponding to an object rapidly changes, and according to a change in a diagnostic posture of the pregnant woman due to changes in an external appearance of the pregnant woman and diagnostic items, relative positions of a medical chair on which the pregnant woman is seated for obstetrical or gynecological examination, a probe holder for holding probes, and a diagnosis part also need to be changed.

DESCRIPTION OF EMBODIMENTS

TECHNICAL PROBLEM

[0005] Provided is a medical diagnosis apparatus including an accessory unit of which a position and a form automatically or manually change according to body information of an object and medical information of the object.

[0006] Provided is also a medical diagnosis apparatus including an accessory unit of which a position is automatically controlled such that interference with an object may not occur according to a diagnostic mode for the object.

SOLUTION TO PROBLEM

[0007] According to an aspect of the present disclo-

sure, a medical diagnosis apparatus may include: a main body; a chair unit movably supported by the main body and on which an object is positioned; a diagnosis part that is movably connected to the main body and is spaced apart from the chair unit by a preset first distance in one plane; a controller configured to generate a control signal for moving the diagnosis part according to preset information; and a first driving device configured to generate a driving force for moving the diagnosis part according to the control signal.

[0008] The chair unit and the diagnosis part may be spaced apart from each other by a preset first height along a direction perpendicular to the one plane.

[0009] The medical diagnosis apparatus may further include: a first sensor configured to detect a position of the diagnosis part, which varies depending on the driving force generated by the first driving device; and a first limit switch configured to stop the first driving device as the diagnosis part and the chair unit are arranged adjacent to each other with a distance or height therebetween that is less than or equal to the preset first distance or the preset first height.

[0010] The first distance that is a distance between a center line in a longitudinal direction of the chair unit and a center line of the diagnosis part extending in a direction parallel to the center line may be in a range of 40 cm to 90 cm.

[0011] The chair unit may include an upper body support, a seat, and a leg rest sequentially arranged in one direction and connected to one another, and the first height between the seat and a lower end of the diagnosis part may be in a range of 5 cm to 70 cm.

[0012] The medical diagnosis apparatus may further include a storage storing first body information of the object and an input interface configured to input identification information of the object, the first body information of the object may be identified by the identification information of the object, and the identification information of the object may be at least one of name information of the object, fingerprint information of the object, face information of the object, and an identification code corresponding to the object.

[0013] When the medical diagnosis apparatus is an obstetrical and gynecological diagnosis apparatus, the first body information of the object may be at least one of a gestational age, the number of fetuses, a fetal position, a weight, a height, a body temperature, an examination history, and a medical history.

[0014] The medical diagnosis apparatus may further include a first connector that connects the diagnosis part to the main body and is configured such that the diagnosis part is movable with respect to the main body, and the first connector may include: a first engaging member rotatably coupled to the main body; a first arm that extends in one direction and is hinged with the first engaging member; a second engaging member rotatably coupled to the first arm; a second arm that extends in one direction and is hinged with the second engaging member; and a

connection member having one end coupled to the diagnosis part and the other end hinged to the second arm.

[0015] The first driving device may be a traction motor, and the first sensor may include an encoder configured to detect a driving state of the traction motor.

[0016] The medical diagnosis apparatus may further include: an ultrasound diagnosis device including at least one ultrasound probe and a probe holder that is movably connected to the main body; and a second driving device configured to generate a driving force for moving the ultrasound diagnosis device, and the ultrasound diagnosis device may be spaced apart from the chair unit by a preset second distance in one plane, and the controller may generate a control signal for moving the ultrasound diagnosis device according to preset information.

[0017] The chair unit and the ultrasound diagnosis device may be spaced apart from each other by a preset second height along a direction perpendicular to the one plane.

[0018] The medical diagnosis apparatus may further include: a second sensor configured to detect a position of the ultrasound diagnosis device, which varies depending on the driving force generated by the second driving device; and a second limit switch configured to stop the second driving device as the diagnosis part and the chair unit are arranged adjacent to each other with a distance or a height therebetween that is less than or equal to the preset second distance or the preset second height.

[0019] The second distance that is a distance between the center line in the longitudinal direction of the chair unit and a center line of the probe holder extending in a direction parallel to the center line may be in a range of 35 cm to 85 cm.

[0020] The chair unit may include an upper body support, a seat, and a leg rest sequentially arranged in one direction and connected to one another, and the second height between the seat and a lower end of the probe holder may be in a range of 5 cm to 70 cm.

[0021] The medical diagnosis apparatus may further include a probe sensor configured to detect a state in which the at least one ultrasound probe has been held on the probe holder.

[0022] According to another aspect of the present disclosure, a medical diagnosis method may include: acquiring first body information of an object; generating a control signal for a chair unit, an ultrasound diagnosis device, and a diagnosis part based on the first body information of the object; changing, according to the control signal, the chair unit, the ultrasound diagnosis device, and the diagnosis part from an initial state to a diagnostic state; receiving diagnosis completion information; and changing the chair unit, the ultrasound diagnosis device, and the diagnosis part from the diagnostic state to the initial state.

[0023] The medical diagnosis method may further include: detecting positions of the ultrasound diagnosis device and the diagnosis part that vary depending on driving forces generated by first and second driving devices; and

stopping driving by the first and second driving devices when a distance or height between the chair unit and either the ultrasound diagnosis device or the diagnosis part is in a range that is less than or equal to a predetermined range.

[0024] The medical diagnosis method may further include inputting identification information of the object, the first body information of the object may be acquired based on the identification information of the object, and the identification information of the object may be at least one of name information of the object, fingerprint information of the object, face information of the object, and an identification code corresponding to the object.

[0025] When the medical diagnosis method is an obstetrical and gynecological diagnosis method, the first body information of the object may be at least one of a gestational age, the number of fetuses, a weight, a height, a body temperature, a medical history, and a fetal position.

[0026] When at least one ultrasound probe included in the ultrasound diagnosis device, is held on a probe holder for a certain period of time, the diagnosis completion information may be input.

25 ADVANTAGEOUS EFFECTS OF DISCLOSURE

[0027] According to an embodiment, a medical diagnosis apparatus allows a form of an accessory unit to automatically change according to body information and medical information of an object, thereby increasing user convenience and minimizing diagnosis time.

[0028] Furthermore, according to an embodiment, a medical diagnosis apparatus allows a position of an accessory unit to be automatically controlled such that interference with an object may not occur according to a diagnostic mode for the object, thereby improving safety of the object and user convenience and preventing damage to the medical diagnosis apparatus.

40 BRIEF DESCRIPTION OF DRAWINGS

[0029] These and/or other aspects will become more readily appreciated from the following description of the embodiments, taken in conjunction with the accompanying drawings, in which reference numerals denote structural elements.

FIG. 1 is a block diagram of a configuration of a medical diagnosis apparatus according to an embodiment.

FIG. 2 is a perspective view of a medical diagnosis apparatus according to an embodiment.

FIG. 3 is a block diagram of a configuration of a driver and a controller according to an embodiment.

FIG. 4A is a plan view of a medical diagnosis apparatus according to an embodiment.

FIG. 4B is a side view of a medical diagnosis apparatus according to an embodiment.

FIG. 5A is a perspective view of a first connector according to an embodiment.

FIG. 5B is an exploded perspective view of a first connector according to an embodiment.

FIG. 5C is a schematic diagram of a rotation axis and a limit switch according to an embodiment.

FIG. 5D is a plan view of a first connector according to an embodiment.

FIG. 5E is a side view of a first connector according to an embodiment.

FIG. 6 is a flowchart of a diagnosis method using a medical diagnosis apparatus, according to an embodiment.

FIGS. 7A through 7C are respectively a perspective view, a side view, and a plan view of a medical diagnosis apparatus that is in an initial state, according to an embodiment.

FIGS. 8A through 8C are respectively a perspective view, a side view, and a plan view of a medical diagnosis apparatus that is in a first diagnostic state, according to an embodiment.

FIGS. 9A and 9B are respectively a perspective view and a plan view of a medical diagnosis apparatus that is in a second diagnostic state, according to an embodiment.

FIGS. 10A through 10C are respectively a perspective view, a side view, and a plan view of a medical diagnosis apparatus that is in a third diagnostic state, according to an embodiment.

MODE OF DISCLOSURE

[0030] The present specification describes principles of the present disclosure and sets forth embodiments thereof to clarify the scope of the present disclosure and to allow those of ordinary skill in the art to implement the embodiments. The present embodiments may have different forms and should not be construed as being limited to the descriptions set forth herein.

[0031] Like reference numerals refer to like elements throughout. The present specification does not describe all components in the embodiments, and common knowledge in the art or the same descriptions of the embodiments will be omitted below. The term "part" or "portion" used herein may be implemented using hardware or software, and according to embodiments, a plurality of "parts" or "portions" may be formed as a single unit or element, or one "part" or "portion" may include a plurality of units or elements. Hereinafter, the operating principles and embodiments of the present disclosure will be described in detail with reference to the accompanying drawings.

[0032] Furthermore, in the present specification, an "object" may be a target to be imaged and include a patient, a pregnant woman, a fetus, or a part thereof. For example, the object may include a part of an organ in a pregnant woman's body, a fetus, or a phantom.

[0033] Throughout the specification, a "user" may be, but is not limited to, a medical expert, e.g., a medical

doctor, a nurse, a medical laboratory technologist, a medical imaging expert, etc.

[0034] Throughout the specification, an "ultrasound image" refers to an image of an object, which is formed by processing ultrasound signals transmitted to and reflected from the object.

[0035] Embodiments will be described more fully hereinafter with reference to the accompanying drawings.

[0036] FIG. 1 is a block diagram of a configuration of a medical diagnosis apparatus 1 according to an embodiment. FIG. 2 is a perspective view of a medical diagnosis apparatus according to an embodiment.

[0037] Referring to FIGS. 1 and 2, the medical diagnosis apparatus 1 according to the embodiment may include an ultrasound diagnosis device 30, a main body 25, a diagnosis part 20 that may be used by a user to manipulate the medical diagnosis apparatus 1 for diagnosing an object, and a chair part 40 in which the object may be positioned. Hereinafter, while an obstetrical and gynecological diagnosis apparatus has been described as an example of the medical diagnosis apparatus 1, embodiments of the present disclosure are not limited thereto, and the technical idea of the present specification may be applied to another medical diagnosis apparatus 1 including the diagnosis part 20, the ultrasound diagnosis device 30, and the chair part 40 that are arranged to be separated from one another.

[0038] According to an embodiment, the diagnosis part 20 may include an image processor 230 for processing a received signal into an image, a display 240 for outputting the image, a storage 255, a communicator 260, and an input interface 270.

[0039] The image processor 230 generates an ultrasound image by using ultrasound data generated by an ultrasound receiver 322.

[0040] The display 240 may display a generated ultrasound image and various pieces of information processed by the medical diagnosis apparatus 1. The display 240 may include one or a plurality of displays, e.g., a first display for a user and a second display for an object, according to its implemented configuration. In this case, the display may be combined with a touch panel to form a touch screen.

[0041] The storage 255 may store various data or programs for driving and controlling the medical diagnosis apparatus 1, input and/or output ultrasound data, obtained ultrasound images, identification (ID) information and body information of an object, ID information and body information of a user, etc.

[0042] In the present specification, ID information of an object or user means at least one of all types of information used to identify the object or individual user, such as a name, a resident registration number, a birth date, a personal ID number, a personal ID code, and biometric recognition information such as a face, an iris, a fingerprint, etc. Furthermore, in the present specification, body information of an object means all pieces of body information of the object for medical treatment, such as a

pregnant woman's gestational age, the number of fetuses, a fetal position, a pregnant woman's weight, stature, body temperature, examination history, medical history, etc. Furthermore, in the present specification, a user's body information means all pieces of user's body information needed during diagnosis, such as an operator's operating posture, stature (a height and a sitting height), arm length, gaze position, etc.

[0043] According to an embodiment, the medical diagnosis apparatus 1 may include the communicator 260 and may be connected to external apparatuses (e.g., central servers, medical apparatuses, portable devices such as smartphones, tablet PCs, wearable devices, etc.) via the communicator 260.

[0044] The communicator 260 may include at least one element capable of communicating with the external apparatuses, for example, at least one of a local area communication module, a wired communication module, and a wireless communication module.

[0045] For example, the communicator 260 may transmit ID information of an object and a user to an external apparatus such as a central server, and the external apparatus may transmit data related to body information of the object and the user, corresponding to the received ID information of the object and the user, to the controller 250 so that the controller 250 may control the medical diagnosis apparatus 1 according to the received data related to body information of the object and the user. The external apparatus may include a recording medium having recorded thereon the data related to body information of the object and the user.

[0046] The input interface 270 may receive a user input for controlling the medical diagnosis apparatus 1. For example, the user may input to the input interface 270 ID information of the object, ID information of the user, or a manipulation signal for adjusting a position of the chair part 40 that will be described below. In this case, the user input may include, but is not limited to, an input of manipulating a button, a key pad, a mouse, a trackball, a jog switch, a knob, etc., an input of touching a touch pad or touch screen, a voice input, a motion input, an input of biometric information, etc.

[0047] According to an embodiment, the main body 25 may include the controller 250 for controlling the medical diagnosis apparatus 1 and support the diagnosis part 20, the ultrasound diagnosis device 30, and the chair part 40.

[0048] The controller 250 may control all operations of the medical diagnosis apparatus 1 and flow of signals between the internal components of the medical diagnosis apparatus 1. The controller 250 may include a memory storing data or programs for performing functions of the medical diagnosis apparatus 1 and a processor processing the programs or data. Furthermore, the controller 250 may control an operation of the medical diagnosis apparatus 1 by receiving a control signal from the input interface 270 or an external apparatus.

[0049] According to an embodiment, the ultrasound diagnosis device 30 may include an ultrasound probe 310

and an ultrasound transceiver 320 for transmitting or receiving ultrasound waves. The ultrasound probe 310 may include a plurality of transducers. The plurality of transducers may transmit ultrasound signals to an object in response to transmitting signals applied by a transmitter 321 included in the ultrasound transceiver 320. The plurality of transducers may receive ultrasound signals reflected from the object to generate reception signals. In this case, the ultrasound probe 310 may be formed integrally with the medical diagnosis apparatus 1, or may be separate from the medical diagnosis apparatus 1 but be connected thereto by wire or wirelessly. In addition, the medical diagnosis apparatus 1 may include one or a plurality of ultrasound probes 310 according to its implemented configuration.

[0050] According to an embodiment, the ultrasound diagnosis device 30 may further include a probe holder 330 for holding the ultrasound probe 310 in addition to the ultrasound probe 310 and the ultrasound transceiver 320. The user may use the ultrasound probe 310 to diagnose an object and place the ultrasound probe 310 on the probe holder 330 after diagnosis is stopped or completed.

[0051] The probe holder 330 may further include a probe detector 331 for detecting whether the ultrasound probe 310 has been held on the probe holder 330. The probe detector 331 may be located on at least one inner wall of the probe detector 330, but is not limited thereto. For example, the probe detector 331 may be a weight sensor for sensing a weight of the ultrasound probe 310, a micro switch or piezoelectric sensor pressed by the ultrasound probe 310, an optical sensor, or the like. For example, when the probe detector 331 detects that the ultrasound probe 310 has been held on the probe holder 330 for a certain period of time, e. g., for sixty (60) seconds or more, it may be recognized that diagnosis with regard to the object is completed.

[0052] According to an embodiment, the chair part 40 may include a chair unit 400 in which the object may be positioned and one or more object sensors 41 capable of acquiring body information of the object. The chair unit 400 is sufficiently long so that the object may be positioned therein. A length direction of the chair unit 400 is parallel to a length direction or height direction of the object. The chair unit 400 may be supported to be fixed to the floor or be movable. For example, the chair unit 400 may move vertically to allow the object to ascend or descend or may be inclined to adjust a diagnosis angle with respect to the object.

[0053] According to an embodiment, the chair unit 400 may include a seat 410 and an upper body support 420 with a slope adjustable with respect to the seat 410. The seat 410 may support a lower body of the object while the upper body support 420 supports an upper body of the object. The upper body support 420 may include a head support 420-1 for supporting a head of the object. The head support 420-1 may be detachably fixed to the upper body support 420, and may be detached from the

upper body support 420 according to a diagnostic state. The chair unit 400 may further include a leg rest 430 on which legs of the object rest. According to an embodiment, the leg rest 430 may include a first rest 431 and a second rest 432 capable of respectively supporting the right and left legs. However, the chair unit 400 is not limited thereto, and may also be applied to a support capable of supporting an object, such as a chair having a different shape or a bed.

[0054] According to an embodiment, the user may adjust, according to a diagnostic state of the object, an angle of the upper body support 420 with respect to the seat 410 or an angle of the leg rest 430 with respect to the seat 410. Furthermore, the first and second rests 431 and 432 included in the leg rest 430 may be adjusted at various angles to be separated from each other according to a diagnostic state of the object.

[0055] The object sensor 41 is a sensing device capable of detecting a state of the object positioned on the chair unit 400. For example, the object sensor 41 may include a weight sensor capable of measuring in real-time measurement information of the object, such as a weight of the object, a temperature sensor capable of detecting a change in a temperature of the object, a time sensor capable of detecting and calculating a sitting duration of time, or an operation sensor capable of detecting a sudden change in a sitting state of the object. Accordingly, the object sensor 41 may detect measurement information of the object and a sudden change in a sitting state of the object, which occurs during a diagnostic process, and transmit the measurement information of the object, position movement information of the object, etc. to the controller 250.

[0056] Referring back to FIG. 1, according to an embodiment, a driver 50 may generate a driving force capable of moving and changing the shapes of the diagnosis part 20, the ultrasound diagnosis device 30, and the chair part 40 according to a control signal from the controller 250. When the object is a pregnant woman carrying a fetus, her external appearance rapidly changes according to the growth of the fetus, and diagnostic items also change according to the growth of the fetus. When a diagnostic posture of the pregnant woman changes due to the changes in the external appearance of the pregnant woman and diagnostic items, a shape of the chair part 40 in which the pregnant woman is positioned to receive an obstetric or gynecological diagnosis has to be changed, and positions of the diagnosis part 20 and the ultrasound diagnosis device 30 need to be changed to provide the user with usage convenience. Generation of a control signal for controlling the driver 50 according to the body information of the object and the body information of the user and automatic movement of the diagnosis part 20, the ultrasound diagnosis device 30, and the chair part 40 according to a diagnostic state of the object based on the control signal will be described in more detail below.

[0057] FIG. 3 is a block diagram of a configuration of

a driver and a controller according to an embodiment. FIG. 4A is a plan view of a medical diagnosis apparatus according to an embodiment. FIG. 4B is a side view of a medical diagnosis apparatus according to an embodiment.

[0058] According to an embodiment, the user may perform diagnosis using the medical diagnosis apparatus 1 by being located adjacent to the upper or lower body of the object according to preset information such as body information of the object, a diagnostic state of the object, a user input, and preset state information. Thus, to improve usage convenience of the user, positions of the diagnosis part 20 and the ultrasound diagnosis device 30 used by the user need to be changed according to preset information.

[0059] According to an embodiment, when the object, the diagnosis part 20, and the ultrasound diagnosis device 30 are arranged within a predetermined range such that they interfere with one another, this arrangement may cause damage to the object. Thus, when the diagnosis part 20 and the ultrasound diagnosis device 30 are arranged within a predetermined range from the object, it is needed to physically or controllably stop movement of the diagnosis part 20 and the ultrasound diagnosis device 30. An embodiment to be described below presents the technical idea in which when the diagnosis part 20 and the ultrasound diagnosis device 30 are arranged adjacent to the object positioned on the chair unit 400, operations of a first driving device 511 and a second driving device 521 configured to generate driving forces for respectively driving the diagnosis part 20 and the ultrasound diagnosis device 30 may be stopped controllably or physically by using first and second limit switches 513 and 514.

[0060] Referring to FIGS. 2 and 3, according to an embodiment, the driver 50 may include a first driving unit 510 for moving the diagnosis part 20, a second driving unit 520 for moving the ultrasound diagnosis device 30, and a third driving unit 530 for moving the chair part 40.

[0061] According to an embodiment, the first driving unit 510 may include the first driving device 511 that is positioned between the diagnosis part 20 and the main body 25 to transmit a driving force to a first connector 21 connecting between the diagnosis part 20 and the main body 25, a first sensor 512 capable of detecting a position of the diagnosis part 20 by sensing a driving state of the first driving device 511, and the first limit switch 513 capable of stopping driving by the first driving device 511 in a critical condition.

[0062] The first driving device 511 is a driving motor capable of generating a driving force that is transmitted to the first connector 21. For example, the first driving device 511 may be a traction motor including a stator and a rotor located at a central part of the stator. When the first driving device 511 is a traction motor, it is possible to continuously check a driving force that is provided to the first connector 21 by detecting a position of a magnet included in a rotor and the number of rotations of a rotor

core in the rotor via the first sensor 512 as described below. However, in the present specification, the first driving device 511 is not limited to a traction motor and may be any driving device capable of transmitting a driving force to the first connector 21 while continuously checking the driving force that is transmitted to the first connector 21.

[0063] The first sensor 512 is a position sensor capable of detecting a position of the diagnosis part 20, which varies depending on a driving force generated by the first driving device 511. For example, the first sensor 512 may include an optical encoder consisting of a light source such as light emitting diode (LED) and a light-receiver such as a photo diode, a photo transistor or a photo resistor, or may include a magnetic encoder consisting of a permanent magnet and a magnetic field sensor such as a hall sensor or magneto resistive (MR) sensor. When the first sensor 512 includes an encoder, the first sensor 512 may detect a change in the position of the diagnosis part 20 due to the first driving device 511 by sensing a driving state of the first driving device 511, which is transmitted to the first connector 21, and transmitting the driving state to the controller 250. However, in the specification, the first sensor 512 is not limited to an optical or magnetic encoder, and may be any sensor capable of continuously identifying the position of the diagnosis part 20 that varies depending on a driving force generated by the first driving device 511.

[0064] The first limit switch 513 is a control device capable of outputting a control signal corresponding to on/off states of the first driving device 511 according to a position of the diagnosis part 20 detected by the first sensor 512. For example, when the first sensor 512 is implemented as a traction motor, the first sensor 512 may detect a position of a magnet included in a rotor and the number of rotations of a rotor core in the rotor. In this case, for example, a threshold position of the magnet in the rotor and a threshold rotation number of the rotor core therein may be preset in the first limit switch 513. When the first sensor 512 detects that the position of the magnet in the rotor and the number of rotations of the rotor core therein respectively reach their threshold values, the first limit switch 513 may forcibly stop an operation of the first driving device 511. Accordingly, generation of a driving force by the first driving device 511 may be stopped, movement of the first connector 21 that receives a driving force from the first driving device 511 may be stopped, and relative positions of the diagnosis part 20 and the main body 25 connected by the first connector 21 may be fixed.

[0065] According to an embodiment, the second driving unit 520 may include a second driving device 521 that is positioned between the ultrasound diagnosis device 30 and the main body 25 to transmit a driving force to a second connector 31 connecting between the ultrasound diagnosis device 30 and the main body 25, a second sensor 522 capable of detecting a change in a position of the ultrasound diagnosis device 30 due to a driving

force generated by the second driving device 521, and a second limit switch 523 capable of stopping driving by the second driving device 521 in a critical condition. Because the second driving unit 520 has substantially the same configuration as the first driving unit 510, a detailed description thereof will be omitted here for convenience.

[0066] Referring to FIGS. 4A and 4B, the diagnosis part 20 and the ultrasound diagnosis device 30 may be arranged in different directions with respect to the chair unit 400. However, embodiments of the present disclosure are not limited thereto, and the diagnosis part 20 and the ultrasound diagnosis device 30 may be arranged in the same direction with respect to the chair unit 400 or may be formed integrally with each other. For example, a probe holder may be provided on one side 22 of the diagnosis part 20 as shown in FIG. 2, and accordingly, the ultrasound probe 310 may also be placed on the one side 22 of the diagnosis part 20.

[0067] According to an embodiment, the diagnosis part 20, the ultrasound diagnosis device 30, and the chair unit 400 may move to specific positions where user convenience may be provided according to a diagnostic mode, as described below with reference to FIGS. 7A through 10C. In this case, when the diagnosis part 20 or the ultrasound diagnosis device 30 interfere with a body of the object positioned on the chair unit 400 for examination, such interference may unintentionally cause damage to the body of the object and the medical diagnosis apparatus 1. Thus, the diagnosis part 20 and the ultrasound diagnosis device 30 may be arranged to be spaced apart from the chair unit 400 by more than a predetermined range such that they may not interfere with the body of the object.

[0068] For example, when the diagnosis part 20 and the ultrasound diagnosis device 30 are arranged in different directions with respect to the chair unit 400 as shown in FIG. 4A, the diagnosis part 20 may be spaced apart from a center line O along a length direction of the chair unit 400 by a first distance T_1 between the center line O and a center line M_1 of the diagnosis part 20 extending along a direction parallel to the center line O, e. g., by a distance of 40 cm to 90 cm, according to a diagnostic state of the object. For example, in this case, a width W_2 of the diagnosis part 20 perpendicular to the center line O may be in a range of 30 cm to 60 cm, while a width W_1 of the chair unit 400 perpendicular to the center line O may be in a range of 40 cm to 110 cm. Although FIG. 4A shows the width W_1 of the chair unit 400 measured with respect to the seat 410, embodiments of the present disclosure are not limited thereto, and the width W_1 of the chair unit 400 may be a distance between two ends of the first and second rests 431 and 432 according to positions of the diagnosis part 20 and the ultrasound diagnosis device 30, which vary depending on a diagnostic state of the object. The probe holder 330 included in the ultrasound diagnosis device 30 may also be spaced apart from the center line O along the length direction of the chair unit 400 by a second distance T_2 between the

center line O and a center line M_2 of the probe holder 330 extending along a direction parallel to the center line O, e. g., by a distance of 35 cm to 85 cm, according to a diagnostic state of the object. For example, in this case, a width W_3 of the probe holder 330 perpendicular to the center line O may be in a range of 20 cm to 40 cm, while the width W_1 of the chair unit 400 perpendicular to the center line O may be in a range of 40 cm to 110 cm.

[0069] Furthermore, as shown in FIG. 4B, the diagnosis part 20 may be arranged such that a lower end of the diagnosis part 20 is spaced apart from the seat 410 included in the chair unit 400 by a first height h_1 in a Z-axis direction, e. g., by a height of 5 cm to 70 cm, according to a diagnostic state of the object. The probe holder 330 included in the ultrasound diagnosis device 30 may also be arranged such that a lower end of the probe holder 330 is spaced apart from the seat 410 included in the chair unit 400 by a second height h_2 in the Z-axis direction, e. g., by a height of 5 cm to 70 cm, according to a diagnostic state of the object.

[0070] According to an embodiment, the diagnosis part 20 and the ultrasound diagnosis device 30 may receive driving forces respectively from the first and second driving device 511 and 521 shown in FIG. 3 so as to move. Thus, states in which the first and second driving devices 511 and 521 generate driving forces may respectively be set to correspond to ranges of the predetermined distances T_1 and T_2 and predetermined heights h_1 and h_2 such that the diagnosis part 20 and the ultrasound diagnosis device 30 may not interfere with the chair unit 400 and the body of the object. When the first and second sensors 512 and 522 detect that positions of the diagnosis part 20 and the ultrasound diagnosis device 30 respectively deviate from the ranges of the predetermined distances T_1 and T_2 and predetermined heights h_1 and h_2 , which are set such that the diagnosis part 20 and the ultrasound diagnosis device 30 may not interfere with the chair unit 400 and the body of the object, the first and second limit switches 513 and 523 may respectively forcibly stop driving operations by the first and second driving devices 511 and 521, and accordingly, may prevent damage to the body of the object and the medical diagnosis apparatus 1 due to interference between the object and the diagnosis part 20 and the ultrasound diagnosis device 30.

[0071] FIG. 5A is a perspective view of a first connector according to an embodiment. FIG. 5B is an exploded perspective view of the first connector according to an embodiment. FIG. 5C is a schematic diagram of a rotation axis and a limit switch according to an embodiment. FIG. 5D is a plan view of a first connector according to an embodiment. FIG. 5E is a side view of a first connector according to an embodiment.

[0072] As described above, according to an embodiment, the diagnosis part 20 and the ultrasound diagnosis device 30 may move to specific positions according to diagnostic states. The driver 50 shown in FIG. 1 may generate driving forces according to a control signal re-

ceived from the controller 250 and respectively transmit the driving forces to the first and second connectors 21 and 31, each being implemented as a plurality of link parts, such that the diagnosis part 20 and the ultrasound diagnosis device 30 may be automatically arranged at predetermined diagnostic positions corresponding to each diagnostic state.

[0073] According to an embodiment, as shown in FIGS. 5A and 5B, the first connector 21 may include a first engaging member 2010 coupled to the main body 25 to be rotatable around a first rotation axis 2011 and a first arm 2012 hinged with the first engaging member 2010, a second engaging member 2014 coupled to one end of the first arm 2012 to be rotatable around a second rotation axis 2013 and a second arm 2015 hinged with the second engaging member 2014, and a connection member 2016 having one end coupled to the diagnosis part 20 and the other end hinged to one end of the second arm 2015 and connecting the diagnosis part 20 to the second arm 2015.

[0074] Referring to FIG. 5D, the diagnosis part 20 may be connected to the main body 25 by the first and second arms 2012 and 2015. For example, the first arm 2012 may be rotatably coupled to the main body 25 due to the first rotation axis 2011, and thus, may move in an XY plane to be rotatable about the first rotation axis 2011 with respect to the main body 25. Furthermore, the second arm 2015 may be rotatably coupled to the first arm 2012 due to the second rotation axis 2013, and thus, may move in the XY plane to be rotatable about the second rotation axis 2013 with respect to the first arm 2012. Accordingly, the diagnosis part 20 connected to the main body 25 by the first and second arms 2012 and 2015 may move freely with respect to the main body 25 in one plane (the XY plane).

[0075] According to an embodiment, the first and second arms 2012 and 2015 may each receive a driving force from the first driving device 511 of FIG. 3 for rotational movement. In this case, when the first sensor 512 detects that a position of the diagnosis part 20 connected to the first and second arms 2012 and 2015 deviates from a range of the predetermined distance T_1 from the chair unit 400, the first limit switch 513 may forcibly stop driving by the first driving device 511.

[0076] For example, as shown in FIG. 5C, driving by the first driving device 511 may be forcibly stopped by the first limit switch 513 capable of limiting rotation of the second rotation axis 2013. According to an embodiment, one or a plurality of first limit switches 513 may be arranged on a path of rotation of the second rotation axis 2013 in order to limit a range of rotation of the second rotation axis 2013, and may contact a damper fixedly attached to the second rotation axis 2013 to limit rotation of the second rotation axis 2013 and thus rotation of the second arm 2015 connected to the second rotation axis 2013, thereby preventing interference between the diagnosis part 20 and the object. However, a configuration of a limit switch is not limited thereto, and the limit switch

may be implemented as a control member capable of limiting rotations of the first and second rotation axes 2011 and 2013 with respect to the first and second arms 2012 and 2015 when the first and second arms 2012 and 2015 move beyond their movable ranges.

[0077] Referring to FIGS. 5B and 5E, according to an embodiment, the diagnosis part 20 may be connected to the main body 25 by the first and second arms 2012 and 2015 and the connection member 2016. For example, the first arm 2012 may be hinged to the main body 25, and the second arm 2015 may be hinged to the first arm 2012 and the connection member 2016. Accordingly, the second arm 2015 may move up and down with respect to the first arm 2012 along the Z-axis direction. Thus, the diagnosis part 20 connected to the main body 25 by the first and second arms 2012 and 2015 and the connection member 2016 may move up and down with respect to the main body 25 along the Z-axis direction. In this case, when the second arm 2015 rotates such that the diagnosis part 20 moves up and down outside a range of the predetermined first height h_1 as shown in FIG. 4B, the first limit switch 513 may forcibly stop driving by the first driving device 511 to thereby prevent interference between the object and the diagnosis part 20. Because the second connector 31 for connecting the ultrasound diagnosis device 30 to the main body 25 has substantially the same configuration as the first connector 21, a detailed description thereof will be omitted here for convenience.

[0078] FIG. 6 is a flowchart of a diagnosis method using a medical diagnosis apparatus, according to an embodiment. FIGS. 7A through 7C are respectively a perspective view, a side view, and a plan view of a medical diagnosis apparatus that is in an initial state, according to an embodiment. FIGS. 8A through 8C are respectively a perspective view, a side view, and a plan view of a medical diagnosis apparatus that is in a first diagnostic state, according to an embodiment. FIGS. 9A and 9B are respectively a perspective view and a plan view of a medical diagnosis apparatus that is in a second diagnostic state, according to an embodiment. FIGS. 10A through 10C are respectively a perspective view, a side view, and a plan view of a medical diagnosis apparatus that is in a third diagnostic state, according to an embodiment.

[0079] Referring to FIG. 6, in operation S110, ID information of an object is input via the input interface 270 included in the diagnosis part 20. For example, as described above ID information of the object means at least one of all types of information used to identify the object, such as a name, a resident registration number, a birth date, a personal ID number, a personal ID code, and biometric recognition information such as a face, an iris, a fingerprint, etc.

[0080] In operation S120, first body information of the object is acquired using the ID information of the object input via the input interface 270. According to an embodiment, the controller 250 may acquire first body information of the object corresponding to the ID information of

the object and which is stored in the storage 255 or an external apparatus by using the ID information of the object input via the input interface 270. In this case, the first body information of the object may be stored in the storage 255 included in the diagnosis part 20 or the external apparatus capable of performing communication via the communicator 260. In this case, the first body information of the object means all pieces of prestorable body information of the object for obstetrical and gynecological treatment, such as a pregnant woman's gestational age, the number of fetuses, a fetal position, a pregnant woman's weight, stature, body temperature, examination history, medical history, etc.

[0081] In operation S140, a control signal for moving the chair unit 400, the diagnosis part 20, and the ultrasound diagnosis device 30 is generated based on the acquired first body information of the object. According to an embodiment, the controller 250 may identify a diagnostic state of the object and body information thereof by using the acquired first body information of the object. In this case, the chair unit 400, the ultrasound diagnosis device 30, and the diagnosis part 20 may be changed according to a diagnostic state of the object and body information thereof, and the controller 250 generates a control signal that may be used to generate a driving force for changing the shapes of and moving the chair unit 400, the ultrasound diagnosis device 30, and the diagnosis part 20

[0082] In operation S150, the chair unit 400, the diagnosis part 20, and the ultrasound diagnosis device 30 are changed from an initial state to a diagnostic state based on a control signal generated by the controller 250. According to an embodiment, the driver 50 may generate a driving force according to a control signal generated by the controller 250 to change the chair unit 400, the diagnosis part 20, and the ultrasound diagnosis device 30 from an initial state to a diagnostic state. For example, the chair unit 400, the diagnosis part 20, and the ultrasound diagnosis device 30 may be changed from an initial state to first through third diagnostic states according to body information of the object such as a gestational age.

[0083] According to an embodiment, in an initial state, the chair unit 400 may have a structure that makes it easy for the object to sit thereon as shown in FIGS. 7A through 7C. For example, in the initial state, the upper body support 420 may be arranged to have a first angle α of 90° to 120° with respect to the seat 410 in a counterclockwise direction. Furthermore, in this case, the leg rest 430 may be arranged to have a second angle β of 240° to 360° with respect to the seat 410 in a clockwise direction. Furthermore, the ultrasound diagnosis device 30 and the diagnosis part 20 may be each arranged adjacent to the seat 410 such that they do not interfere with the object while the object is sitting on the chair unit 400 due to operations of the first and second driving devices 511 and 521. In this case, when the distances T_1 and T_2 or heights h_1 and h_2 between the chair unit 400 and either the diagnosis part 20 or the ultrasound diagnosis device

30 exceed a predetermined range indicated in FIG. 4A or 4B, the first or second limit switch 513 and 523 may stop driving by the first or second driving device 511 or 521.

[0084] Furthermore, according to an embodiment, in a first diagnostic state, when the object, i.e., a pregnant woman, is in an early stage (10 weeks or less of pregnancy), the chair unit 400 may have a structure for diagnosing a lower body part of the object as shown in FIGS. 8A through 8C. For example, in the first diagnostic state, the upper body support 420 may be tilted to lie flat with respect to the seat 410, i.e., to have a first angle α of 180° with respect to the seat 410. However, embodiments of the present disclosure are not limited thereto, and the upper body support 420 may be tilted at a first angle α , e.g., at an angle of 110° to 180° , with respect to the seat 410 when needed during a diagnostic process. Furthermore, the leg rest 430 may be arranged to have a second angle β of 120° to 180° with respect to the seat 410 in a clockwise direction. Furthermore, the seat 410 may be tilted to have an angle of 0° to 20° with respect to the ground.

[0085] Furthermore, in this case, the chair unit 400 may be arranged to be raised from or lowered to the ground according to a user's height and a diagnosis type. Furthermore, for example, the ultrasound diagnosis device 30 and the diagnosis part 20 may be raised from or lowered to the ground according to a user's height or a diagnosis type, and may be arranged adjacent to the leg rest 430 by moving away from the seat 410 based on a user's arm length and a diagnosis type, thereby maximizing usage convenience of the user. Furthermore, the diagnosis part 20 and the ultrasound diagnosis device 30 may be each arranged adjacent to the leg rest 430 due to the first and second driving devices 511 and 521, thereby providing user convenience in the first diagnostic state. In this case, when the diagnosis part 20 and the ultrasound diagnosis device 30 are arranged adjacent to the chair unit 400 within a predetermined range, the first or second limit switch 513 or 523 may stop driving by the first or second driving device 511 or 521 in substantially the same manner as in the initial state, and thus, a description thereof will be omitted here.

[0086] Furthermore, according to an embodiment, in a second diagnostic state, when the object, i.e., the pregnant woman, is in a middle stage (10 to 30 weeks of pregnancy), the chair unit 400 may have a structure for diagnosing an abdominal part of the object as shown in FIGS. 9A and 9B. For example, in the second diagnostic state, the seat 410, the upper body support 420, and the leg rest 430 may be arranged in one plane. In other words, the upper body support 420 may be tilted to lie flat with respect to the seat 410, i.e., to have a first angle α of 180° with respect to the seat 410. However, embodiments of the present disclosure are not limited thereto, and the upper body support 420 may be tilted at a first angle α , e.g., at an angle of 110° to 180° , with respect to the seat 410 when needed during a diagnostic process.

Because matters related to raising and lowering of the chair unit 400 and movements of the diagnosis part 20 and the ultrasound diagnosis device 30 based on a user's height and a diagnosis type are substantially the same as those in the first diagnostic state, detailed descriptions thereof will be omitted here. Furthermore, the diagnosis part 20 may be located adjacent to the seat 410 due to the first driving device 511, and the ultrasound diagnosis device 30 may be located adjacent to the leg rest 430 due to the second driving device 521, thereby providing user convenience in the second diagnostic state. In this case, when the diagnosis part 20, the ultrasound diagnosis device 30, and the chair unit 400 are arranged adjacent to one another within a predetermined range, the first or second limit switch 513 or 523 may stop driving by the first or second driving device 511 or 521 in substantially the same manner as in the initial state, and thus, descriptions thereof will be omitted here.

[0087] In addition, according to an embodiment, in a third diagnostic state, when the object, i.e., the pregnant woman, is in a late stage (30 weeks or more of pregnancy), the chair unit 400 may have a structure for diagnosing an abdominal part of the object as shown in FIGS. 10A through 10C. When the pregnant woman enters the late stage of pregnancy, it may be hard for her to lie flat on her back due to a fetal weight. Thus, the upper body support 420 needs to move relative to the seat 410 by taking into account diagnostic convenience for the object. For example, in the third diagnostic state, the upper body support 420 may be tilted to have a first angle α of 110° to 170° with respect to the seat 410 in a counterclockwise direction. Furthermore, the leg rest 430 may be arranged in the same plane as the seat 410. Because matters related to raising and lowering of the chair unit 400 and movements of the diagnosis part 20 and the ultrasound diagnosis device 30 based on a user's height and a diagnosis type are substantially the same as those in the first diagnostic state, detailed descriptions thereof will be omitted here. Furthermore, the diagnosis part 20 and the ultrasound diagnosis device 30 may be each arranged adjacent to the leg rest 430 due to the first and second driving devices 511 and 521, thereby providing user convenience in the third diagnostic state. In this case, when the diagnosis part 20, the ultrasound diagnosis device 30, and the chair unit 400 are arranged adjacent to one another within a predetermined range, the first or second limit switch 513 or 523 may stop driving by the first or second driving device 511 or 521 in substantially the same manner as in the initial state, and thus, descriptions thereof will be omitted here.

[0088] In operation S160, positions of the diagnosis part 20 and the ultrasound diagnosis device 30, which vary depending on driving forces generated by the first and second driving devices 511 and 521, are detected. For example, as shown in FIG. 3, the first sensor 512 may detect a position of the diagnosis part 20, which varies depending on a driving force generated by the first driving device 511, and the second sensor 522 may de-

tect a position of the ultrasound diagnosis device 30, which varies depending on a driving force generated by the second driving device 521.

[0089] In operation S165, it may be determined, based on the detected positions of the diagnosis part 20 and the ultrasound diagnosis device 30, whether a distance or height between the chair unit 400 and either the diagnosis part 20 or the ultrasound diagnosis device 30 is in a range that is less than or equal to a predetermined range. For example, when a distance or height between the chair unit 400 and either the diagnosis part 20 or the ultrasound diagnosis device 30 is in a range that is less than or equal to a predetermined range, interference may occur between the object and the diagnosis part 20 and the ultrasound diagnosis device 30 and cause damage to the object and the medical diagnosis apparatus 1. For example, to prevent such damage to the object and the medical diagnosis apparatus 1, the first and second sensors 512 and 522 may continuously detect driving states of the first and second driving devices 511 and 521, respectively.

[0090] In operation S167, when the distance or height between the chair unit 400 and either the diagnosis part 20 or the ultrasound diagnosis device 30 is in a range that is less than or equal to the predetermined range, driving by the first and second driving devices 511 and 521 may be stopped. For example, when driving states of the first and second driving devices 511 and 521 reach preset threshold values such that a range of a distance or height between the chair unit 400 and either the diagnosis part 20 or the ultrasound diagnosis device 30 is narrowed down to less than or equal to the predetermined range, the first and second limit switches 513 and 523 shown in FIG. 3 may be respectively used to forcibly stop driving by the first and second driving devices 511 and 521.

[0091] In operation S170, when diagnosis of the object by a user is completed, diagnosis completion information is input. According to an embodiment, when diagnosis of the object by the user is completed, the user may hold the ultrasound probe 310 on the probe holder 330. When the probe sensor 331 detects that the ultrasound probe 310 has been held on the probe holder 330 for a certain period of time, it may be recognized that the diagnosis of the object is completed, and diagnosis completion information indicating that the diagnosis of the object is completed may be input. However, embodiments of the present disclosure are not limited thereto, and the diagnosis completion information may be directly input by the user via the input interface 270.

[0092] In operation S180, when the diagnosis completion information is input, the chair unit 400, the diagnosis part 20, and the ultrasound diagnosis device 30 are changed from a diagnostic state to an initial state based on a control signal generated by the controller 250. According to an embodiment, the driver 50 may generate a driving force according to a control signal generated by the controller 250 to change the chair unit 400, the

diagnosis part 20, and the ultrasound diagnosis device 30 from the diagnostic state to the initial state.

[0093] While medical diagnosis apparatuses and medical diagnosis methods using the same have been particularly shown and described with reference to embodiments thereof, it will be understood by those of ordinary skill in the art that the above-described embodiments are merely examples and are intended to cover various changes in form and details and other equivalent embodiments. Accordingly, the true scope of technical protection of the present disclosure will be defined by the technical spirit of the following claims.

Claims

1. A medical diagnosis apparatus comprising:

- a main body;
- a chair unit movably supported by the main body and on which an object is positioned;
- a diagnosis part that is movably connected to the main body and is spaced apart from the chair unit by a preset first distance in one plane;
- a controller configured to generate a control signal for moving the diagnosis part according to preset information; and
- a first driving device configured to generate a driving force for moving the diagnosis part according to the control signal.

2. The medical diagnosis apparatus of claim 1, wherein the chair unit and the diagnosis part are spaced apart from each other by a preset first height along a direction perpendicular to the one plane.

3. The medical diagnosis apparatus of claim 2, further comprising:

- a first sensor configured to detect a position of the diagnosis part, which varies depending on the driving force generated by the first driving device; and
- a first limit switch configured to stop the first driving device as the diagnosis part and the chair unit are arranged adjacent to each other with a distance or height therebetween that is less than or equal to the preset first distance or the preset first height.

4. The medical diagnosis apparatus of claim 1, wherein the first distance that is a distance between a center line in a longitudinal direction of the chair unit and a center line of the diagnosis part extending in a direction parallel to the center line is in a range of 40 cm to 90 cm.

5. The medical diagnosis apparatus of claim 2, wherein

the chair unit comprises an upper body support, a seat, and a leg rest sequentially arranged in one direction and connected to one another, and wherein the first height between the seat and a lower end of the diagnosis part is in a range of 5 cm to 70 cm.

6. The medical diagnosis apparatus of claim 1, wherein the preset information comprises first body information of the object,
the medical diagnosis apparatus further comprising:

a storage storing the first body information of the object; and
an input interface configured to input identification information of the object,
wherein the first body information of the object is identified by the identification information of the object, and the identification information of the object is at least one of name information of the object, fingerprint information of the object, face information of the object, and an identification code corresponding to the object.

7. The medical diagnosis apparatus of claim 6, wherein when the medical diagnosis apparatus is an obstetrical and gynecological diagnosis apparatus, the first body information of the object is at least one of a gestational age, the number of fetuses, a fetal position, a weight, a height, a body temperature, an examination history, and a medical history.

8. The medical diagnosis apparatus of claim 1, further comprising a first connector that connects the diagnosis part to the main body and is configured such that the diagnosis part is movable with respect to the main body,
wherein the first connector comprises:

a first engaging member rotatably coupled to the main body;
a first arm that extends in one direction and is hinged with the first engaging member;
a second engaging member rotatably coupled to the first arm;
a second arm that extends in one direction and is hinged with the second engaging member;
and
a connection member having one end coupled to the diagnosis part and the other end hinged to the second arm.

9. The medical diagnosis apparatus of claim 3, wherein the first driving device is a traction motor, and the first sensor comprises an encoder configured to detect a driving state of the traction motor.

10. The medical diagnosis apparatus of claim 1, further

comprising:

an ultrasound diagnosis device comprising at least one ultrasound probe and a probe holder that is movably connected to the main body; and a second driving device configured to generate a driving force for moving the ultrasound diagnosis device,
wherein the ultrasound diagnosis device is spaced apart from the chair unit by a preset second distance in one plane, and the controller is further configured to generate a control signal for moving the ultrasound diagnosis device according to preset information.

11. The medical diagnosis apparatus of claim 10, wherein the chair unit and the ultrasound diagnosis device are spaced apart from each other by a preset second height along a direction perpendicular to the one plane.

12. The medical diagnosis apparatus of claim 11, further comprising:

a second sensor configured to detect a position of the ultrasound diagnosis device, which varies depending on the driving force generated by the second driving device; and
a second limit switch configured to stop the second driving device as the diagnosis part and the chair unit are arranged adjacent to each other with a distance or a height therebetween that is less than or equal to the preset second distance or the preset second height.

13. The medical diagnosis apparatus of claim 10, wherein the second distance that is a distance between the center line in the longitudinal direction of the chair unit and a center line of the probe holder extending in a direction parallel to the center line is in a range of 35 cm to 85 cm.

14. The medical diagnosis apparatus of claim 11, wherein the chair unit comprises an upper body support, a seat, and a leg rest sequentially arranged in one direction and connected to one another, and wherein the second height between the seat and a lower end of the probe holder is in a range of 5 cm to 70 cm.

15. The medical diagnosis apparatus of claim 10, further comprising a probe sensor configured to detect a state in which the at least one ultrasound probe has been held on the probe holder.

FIG. 1




FIG. 2




FIG. 3




FIG. 4A




FIG. 4B




FIG. 5A




FIG. 5B




FIG. 5C




FIG. 5D




FIG. 5E




FIG. 6




FIG. 7A




FIG. 7B




FIG. 7C




FIG. 8A




FIG. 8B




FIG. 8C




FIG. 9A




FIG. 9B




FIG. 10A




FIG. 10B





FIG. 10C



INTERNATIONAL SEARCH REPORT

International application No.

PCT/KR2017/010147

A. CLASSIFICATION OF SUBJECT MATTER

A61B 8/00(2006.01)ii

According to International Patent Classification (IPC) or to both national classification and IPC

B. FIELDS SEARCHED

Minimum documentation searched (classification system followed by classification symbols)

A61B 8/00; A61G 15/02; A61B 1/045; A61C 19/00; A61G 15/14; G01N 29/24

Documentation searched other than minimum documentation to the extent that such documents are included in the fields searched

Korean Utility models and applications for Utility models: IPC as above

Japanese Utility models and applications for Utility models: IPC as above

Electronic data base consulted during the international search (name of data base and, where practicable, search terms used)

eKOMPASS (KIPO internal) & Keywords: pregnant woman, medical examination table, chair, move, adjustment, ultrasonic waves, probe

C. DOCUMENTS CONSIDERED TO BE RELEVANT

Category*	Citation of document, with indication, where appropriate, of the relevant passages	Relevant to claim No.
X	JP 2011-036589 A (GC CORP.) 24 February 2011 See paragraphs [10], [18]-[36] and figures 1-4.	1-2,4-5
Y		3,6-15
Y	JP 2011-072418 A (GC CORP.) 14 April 2011 See paragraphs [29]-[36] and figures 1-3.	3,8-9,12
Y	KR 10-2005-0119921 A (YUN MIN ACE MANUFACTURING CO.) 22 December 2005 See paragraphs [62], [63] and figure 3.	6-7
Y	JP 2011-182978 A (WASEDA UNIV. et al.) 22 September 2011 See paragraphs [17]-[19], [27]-[30] and figure 1.	10-15
Y	KR 10-2014-0046754 A (SAMSUNG MEDISON CO., LTD.) 21 April 2014 See paragraphs [18]-[21] and figures 1, 2.	15
A	KR 10-2015-0052673 A (SAMSUNG MEDISON CO., LTD.) 14 May 2015 See claims 1-11 and figures 1-3.	1-15

☐ Further documents are listed in the continuation of Box C.☒ See patent family annex.

* Special categories of cited documents:

"A" document defining the general state of the art which is not considered to be of particular relevance

"E" earlier application or patent but published on or after the international filing date

"L" document which may throw doubts on priority claim(s) or which is cited to establish the publication date of another citation or other special reason (as specified)

"O" document referring to an oral disclosure, use, exhibition or other means

"P" document published prior to the international filing date but later than the priority date claimed

"T" later document published after the international filing date or priority date and not in conflict with the application but cited to understand the principle or theory underlying the invention

"X" document of particular relevance; the claimed invention cannot be considered novel or cannot be considered to involve an inventive step when the document is taken alone

"Y" document of particular relevance; the claimed invention cannot be considered to involve an inventive step when the document is combined with one or more other such documents, such combination being obvious to a person skilled in the art

"&" document member of the same patent family

Date of the actual completion of the international search

22 DECEMBER 2017 (22.12.2017)

Date of mailing of the international search report

22 DECEMBER 2017 (22.12.2017)

Name and mailing address of the ISA/KR

Korean Intellectual Property Office
Government Complex-Daejeon, 189 Seonsa-ro, Daejeon 302-701,
Republic of Korea

Facsimile No. +82-42-481-8578

Authorized officer

Telephone No.

INTERNATIONAL SEARCH REPORT
Information on patent family members

International application No.

PCT/KR2017/010147

Patent document cited in search report	Publication date	Patent family member	Publication date
JP 2011-036589 A	24/02/2011	NONE	
JP 2011-072418 A	14/04/2011	JP 5557499 B2	23/07/2014
KR 10-2005-0119921 A	22/12/2005	KR 10-2005-0118542 A WO 2005-120331 A1	19/12/2005 22/12/2005
JP 2011-182978 A	22/09/2011	NONE	
KR 10-2014-0046754 A	21/04/2014	KR 10-1560222 B1 US 2014-0107487 A1 WO 2014-058272 A1	14/10/2015 17/04/2014 17/04/2014
KR 10-2015-0052673 A	14/05/2015	KR 10-1562211 B1	21/10/2015

专利名称(译)	医疗诊断装置和使用其的医疗诊断方法		
公开(公告)号	EP3505068A4	公开(公告)日	2019-07-03
申请号	EP2017853365	申请日	2017-09-15
[标]申请(专利权)人(译)	三星麦迪森株式会社		
申请(专利权)人(译)	三星MEDISON CO. , LTD.		
当前申请(专利权)人(译)	三星MEDISON CO. , LTD.		
[标]发明人	PARK DAI UN WOO KYEONG GU MOON JUN PIL		
发明人	PARK, DAI-UN WOO, KYEONG-GU MOON, JUN-PIL		
IPC分类号	A61B8/00 A61G15/00 A61G15/02 A61B5/00 A61B8/08 A61B8/14 A61B5/01 A61B5/103		
CPC分类号	A61B5/01 A61B5/103 A61B5/1072 A61B5/1172 A61B5/1176 A61B5/4306 A61B5/4362 A61B5/70 A61B8/08 A61B8/0866 A61B8/14 A61B8/40 A61B8/4209 A61B8/4218 A61B8/4433 A61B8/461 A61B8 /585 A61B50/10 A61B2503/02 A61G13/0009 A61G15/005 A61G15/02 A61G15/12 A61G2203/30 A61G5/128		
代理机构(译)	JACOBS , BART		
优先权	62/398689 2016-09-23 US 15/702167 2017-09-12 US		
其他公开文献	EP3505068A1		
外部链接	Espacenet		

摘要(译)

提供一种医疗诊断设备和使用该医疗诊断设备的医疗诊断方法。根据实施例，医疗诊断设备可包括：主体;椅子单元，由主体可移动地支撑，物体放置在该椅子单元上;诊断部分，其可移动地连接到主体并且在一个平面中与椅子单元隔开预设的第一距离;控制器，用于根据预设信息生成用于移动诊断部的控制信号;第一驱动装置，用于根据控制信号产生用于移动诊断部的驱动力。