

(19)



(11)

EP 3 071 285 B1

(12)

EUROPEAN PATENT SPECIFICATION

(45) Date of publication and mention of the grant of the patent:
03.06.2020 Bulletin 2020/23

(51) Int Cl.:
A61M 25/14 (2006.01) A61N 1/04 (2006.01)
A61N 1/36 (2006.01) A61N 1/05 (2006.01)
A61B 5/00 (2006.01) A61B 5/042 (2006.01)
A61B 5/0245 (2006.01)

(21) Application number: **14864542.7**

(22) Date of filing: **21.11.2014**

(86) International application number:
PCT/IB2014/002937

(87) International publication number:
WO 2015/075548 (28.05.2015 Gazette 2015/21)

(54) APPARATUS FOR ASSISTED BREATHING BY TRANSVASCULAR NERVE STIMULATION

VORRICHTUNG FÜR UNTERSTÜTZTE ATMUNG DURCH TRANSVASKULÄRE NERVENSTIMULATION

APPAREIL D'ASSISTANCE RESPIRATOIRE PAR STIMULATION NERVEUSE TRANSVASCULAIRE

(84) Designated Contracting States:
AL AT BE BG CH CY CZ DE DK EE ES FI FR GB GR HR HU IE IS IT LI LT LU LV MC MK MT NL NO PL PT RO RS SE SI SK SM TR

(30) Priority: **22.11.2013 US 201361907993 P**

(43) Date of publication of application:
28.09.2016 Bulletin 2016/39

(73) Proprietor: **Lungpacer Medical Inc. Burnaby BC V5A 4N6 (CA)**

(72) Inventors:

- **THAKKAR, Viral Burnaby, BC V3J 1B4 (CA)**
- **HOFFER, Joaquin Andres Anmore, BC V3H 5E9 (CA)**

- **TRAN, Bao Dung Vancouver, BC V5N4J5 (CA)**
- **EVANS, Douglas Downingtown, PA 19335 (US)**
- **NASH, John Chester Spring, PA 19425 (US)**
- **REYNOLDS, Steven Campbell North Vancouver, BC V7L 3Y7 (CA)**

(74) Representative: **Cabinet Beau de Loménie 158, rue de l'Université 75340 Paris Cedex 07 (FR)**

(56) References cited:

WO-A1-2008/092246	WO-A1-2009/006337
WO-A1-2013/131187	US-A- 5 411 025
US-A1- 2010 036 451	US-A1- 2013 116 743
US-A1- 2013 116 743	

EP 3 071 285 B1

Note: Within nine months of the publication of the mention of the grant of the European patent in the European Patent Bulletin, any person may give notice to the European Patent Office of opposition to that patent, in accordance with the Implementing Regulations. Notice of opposition shall not be deemed to have been filed until the opposition fee has been paid. (Art. 99(1) European Patent Convention).

DescriptionTechnical Field

[0001] Embodiments of this disclosure relate to medical apparatus and particularly to apparatus applicable for the restoration, enhancement, or modulation of diminished neurophysiological functions. Specific embodiments provide apparatus for stimulating the diaphragm muscle to assist breathing by transvascular electrical stimulation of nerves.

Background

[0002] Electrical stimulation of nerves is widely applied in the treatment of a range of conditions and may be applied to control muscle activity or to generate sensations. Nerves may be stimulated by placing electrodes in, around, or near the nerves and activating the electrodes by means of an implanted or external source of electricity.

[0003] The phrenic nerves normally transmit signals from the brain that cause the contractions of the diaphragm necessary for breathing. However, various conditions can prevent appropriate signals from being delivered to the phrenic nerves. These include:

- permanent or temporary injury or disease affecting the spinal cord or brain stem;
- Amyotrophic Lateral Sclerosis (ALS);
- decreased day or night ventilatory drive (e.g. central sleep apnea, Ondine's curse); and
- decreased ventilatory drive while under the influence of anesthetic agents and/or mechanical ventilation.

These conditions affect a significant number of people.

[0004] Intubation and positive pressure mechanical ventilation (MV) may be used for periods of several hours or several days, sometimes weeks, to help critically ill patients breathe while in intensive care units (ICU). Some patients may be unable to regain voluntary breathing and thus require prolonged or permanent mechanical ventilation. Although mechanical ventilation can be initially lifesaving, it has a range of significant problems and/or side effects. Mechanical ventilation:

- often causes ventilator-induced lung injury (VILI) and alveolar damage which can lead to accumulation of fluid in the lungs and increased susceptibility to infection (ventilator-associated pneumonia; VAP);
- commonly requires sedation to reduce discomfort and anxiety in acutely intubated patients;
- causes rapid atrophy of the disused diaphragm muscle (ventilator-induced diaphragm dysfunction, VIDD);
- can adversely affect venous return because the lungs are pressurized and the diaphragm is inactive;
- interferes with eating and speaking;

- requires apparatus that is not readily portable; and
- increases the risk of dying if the patient fails to regain normal breathing and becomes ventilator-dependent.

[0005] A patient who is sedated and connected to a mechanical ventilator cannot breathe normally because the central neural drive to the diaphragm and accessory respiratory muscles is suppressed. Inactivity leads to muscle disuse atrophy and an overall decline in well-being. Diaphragm muscle atrophy occurs rapidly and can be a serious problem to the patient. According to a published study in organ donor patients (Levine et al., New England Journal of Medicine, 358: 1327-1335, 2008) after only 18 to 69 hours of mechanical ventilation, all diaphragm muscle fibers had shrunk on average by 52-57%. Muscle fiber atrophy results in muscle weakness and increased fatigability. Therefore, ventilator-induced diaphragm atrophy could cause a patient to become ventilator-dependent. It has been reported that over 840,000 ICU patients in the United States, Europe and Canada become ventilator dependent every year.

[0006] There remains a need for cost-effective, practical, surgically simple and minimally invasive apparatus and methods that may be applied to stimulate breathing. There is also a need for apparatus and methods for facilitating patients on MV to regain the capacity to breathe naturally and to be weaned from MV. US 2013/0116743 A1 discloses a system controlling respiration depth or respiration rate, the system including a catheter according to the preamble of claim 1. US 2010/0036451 A1 discloses electrode structures for transvascular nerve stimulation.

SUMMARY

[0007] The invention is defined in claim 1. Further aspects and preferred embodiments are defined in the appended claims. Aspects, embodiments and examples of the present disclosure which do not fall under the scope of the appended claims do not form part of the invention and are merely provided for illustrative purposes. Furthermore, the methods presented in the present description are provided for illustrative purposes only and do not form part of the present invention. Embodiments of the present disclosure relate to, among other things, medical apparatus and methods for nerve stimulation. Specific embodiments provide apparatus for stimulating breathing by transvascular electrical stimulation of nerves. Each of the embodiments disclosed herein may include one or more of the features described in connection with any of the other disclosed embodiments. The catheter according to the invention is defined in claim 1.

[0008] In one embodiment, a catheter may include an elongated tubular member including a first aperture and a second aperture each in an exterior wall of the elongated tubular member; a first electrode located within the elongated tubular member and positioned relative to the

first aperture so that electrical energy associated with the first electrode travels to or from the exterior of the elongated tubular member through the first aperture; and a second electrode located within the elongated tubular member and positioned relative to the second aperture so that electrical energy associated with the second electrode travels to or from the exterior of the elongated tubular member through the second aperture.

[0009] The catheter may additionally or alternatively include one or more of the following features: a plane that is perpendicular to the longitudinal axis of the catheter may pass through both the first and second apertures; a plane that is perpendicular to the longitudinal axis of the catheter and that passes through the first aperture does not pass through the second aperture; a line parallel to the longitudinal axis of the catheter may pass through both the first and second apertures; the catheter may further include a third aperture and a fourth aperture each in the exterior wall of the elongated tubular member located proximate to a distal end of the catheter, and the first and second apertures may be located proximal to the third and fourth apertures, a third electrode located within the elongated tubular member and positioned relative to the third aperture so that electrical energy associated with the third electrode travels to or from the exterior of the elongated tubular member through the third aperture, and a fourth electrode located within the elongated tubular member and positioned relative to the fourth aperture so that electrical energy associated with the fourth electrode travels to or from the exterior of the elongated tubular member through the fourth aperture; a plane crossing a longitudinal axis of the catheter may pass through both the first and second electrodes to define a cross-sectional area of the catheter, and the cross-sectional area does not include any other electrodes; the first and second electrodes may be bipolar electrodes configured to stimulate a nerve; the first and second apertures and the first and second electrodes may be arranged such that activation of the first and second electrodes creates an electrical field extending radially outwards from only a portion of a circumference of the catheter; and the catheter may further include a first electrode assembly extending through a first lumen of the catheter and a second electrode assembly extending through a second lumen of the catheter, and the first electrode assembly may include the first electrode and the second electrode assembly may include the second electrode.

[0010] In another embodiment, a catheter may include an elongated tubular member including a first plurality of apertures in an exterior wall of the elongated tubular member and a second plurality of apertures in the exterior wall, wherein the second plurality of apertures may be located distal to the first plurality of apertures such that a longitudinal distance between a most distal aperture of the first plurality of apertures and a most proximal aperture of the second plurality of apertures is greater than a longitudinal distance between adjacent apertures of the first plurality of apertures and a longitudinal distance be-

tween adjacent apertures of the second plurality of apertures; a plurality of proximal electrodes located within the elongated tubular member, wherein each of the plurality of proximal electrodes may be positioned radially inward of a corresponding one of the first plurality of apertures; and a plurality of distal electrodes located within the elongated tubular member, wherein each of the plurality of distal electrodes may be positioned radially inward of a corresponding one of the second plurality of apertures.

[0011] The catheter may additionally or alternatively include one or more of the following features: the first plurality of apertures may include at least three apertures, and the second plurality of apertures may include at least three apertures; the first plurality of apertures may be arranged in two rows extending in a proximal-distal direction along the catheter; the second plurality of apertures may be arranged in two rows extending in a proximal-distal direction along the catheter, and lines parallel to a longitudinal axis of the catheter and passing through the two rows of the second plurality of apertures do not pass through the two rows of the first plurality of apertures; the first plurality of apertures may include pairs of apertures, and each pair of apertures may be arranged such that a plane passing through the centers of the pair of apertures forms an acute angle with respect to a plane passing perpendicular to a longitudinal axis of the catheter; the first plurality of apertures may include pairs of apertures, and each pair of apertures may be arranged such that a plane passing through the centers of the two apertures is perpendicular to a longitudinal axis of the catheter; a pair of the plurality of proximal electrodes may include bipolar electrodes configured to stimulate a first nerve, and a pair of the plurality of distal electrodes includes bipolar electrodes configured to stimulate a second nerve; bipolar electrode pairs of the plurality of proximal electrodes may be configured to be selectively activated to create an electrical field extending radially outwards from only a portion of a circumference of a longitudinal section of the catheter that includes the proximal electrodes, and bipolar electrode pairs of the plurality of distal electrodes may be configured to be selectively activated to create an electrical field extending radially outwards from only a portion of the circumference of a longitudinal section of the catheter that includes the distal electrodes; the catheter may further include a first electrode assembly and a second electrode assembly; each of the first and second electrode assemblies may include half of the plurality of proximal electrodes; the catheter may further include a third electrode assembly and a fourth electrode assembly; each of the third and fourth electrode assemblies may include half of the plurality of distal electrodes; the catheter may include a first lumen, a second lumen, a third lumen, and a fourth lumen; the first electrode assembly may be located within the first lumen, the second electrode assembly may be located within the second lumen, the third electrode assembly may be located within the third lumen, and the fourth

electrode assembly may be located within the fourth lumen; and each of the proximal and distal electrodes may be electrically coupled to a distal end of an elongated conductive member.

[0012] In yet another embodiment, a catheter may include an elongated member; a proximal set of electrodes positioned along a first longitudinal portion of the elongated member to at least one of emit or receive electrical energy to or from an exterior of the elongated member along only a portion of a circumference of the first longitudinal portion; and a distal set of electrodes positioned along a second longitudinal portion of the elongated member to at least one of emit or receive electrical energy to or from an exterior of the elongated member along only a portion of a circumference of the second longitudinal portion. The proximal and distal sets of electrodes may be positioned such that the proximal set of electrodes is configured to stimulate a patient's left phrenic nerve and the distal set of electrodes is configured to stimulate the patient's right phrenic nerve.

[0013] The catheter may additionally or alternatively include one or more of the following features: each of the proximal and distal electrodes may include a conductive tubular member; each of the proximal and distal electrodes may include an arcuate member having an inner wall and an outer wall; each of the proximal and distal electrodes may be electrically coupled to an elongated conductive member that extends proximally from the electrode; the proximal and distal electrodes may be electrically coupled to the distal ends of the elongated conductive members; at least one of the proximal and distal electrodes may include conductive ink printed on an exterior of the elongated member; the elongated member of the catheter may include a first lumen, a second lumen, a third lumen, and a fourth lumen; a first plurality of the proximal set of electrodes may be supported by a first elongated tubular member within the first lumen; a second plurality of the proximal set of electrodes may be supported by a second elongated tubular member within the second lumen; a first plurality of the distal set of electrodes may be supported by a third elongated tubular member within the third lumen; and a second plurality of the distal set of electrodes may be supported by a fourth elongated tubular member within the fourth lumen; at least one of the proximal and distal electrodes may include a conductive member fixed to an exterior of the elongated member; the catheter may further include a steering mechanism adapted to deflect a distal end of the elongated member; the catheter may further include a ribbon cable having a plurality of elongated conductive members; and a proximal portion of the catheter may include a first cross-sectional shape, and a distal portion of the catheter may include a second cross-sectional shape different than the first cross-sectional shape.

[0014] Further aspects of the disclosures and features of example embodiments are illustrated in the appended drawings and/or described in the text of this specification and/or described in the accompanying claims. It may be

understood that both the foregoing general description and the following detailed description are exemplary and explanatory only and are not restrictive of the invention, as claimed.

BRIEF DESCRIPTION OF THE DRAWINGS

[0015] The accompanying drawings, which are incorporated in and constitute a part of this specification, illustrate non-limiting exemplary embodiments of the present disclosure and together with the description serve to explain the principles of the disclosure.

FIGs. 1A, 1B, and 1C illustrate various views of a catheter having windows that may align with nerve-stimulating electrodes within the catheter, according to an exemplary embodiment.

FIG. 2 is a cross-sectional view of the catheter shown in FIG. 1, showing lumen locations that may receive nerve-stimulating electrodes, according to an exemplary embodiment.

FIG. 3A illustrates an electrode assembly that may be applied for stimulating a left phrenic nerve; FIG. 3B illustrates a cross-sectional view of an electrode shown in FIG. 3A; FIG. 3C illustrates an electrode assembly that may be applied for stimulating a right phrenic nerve; and FIG. 3D illustrates a cross-sectional view of an electrode shown in FIG. 3C, according to exemplary embodiments.

FIG. 4A illustrates a catheter; FIG. 4B illustrates an electrode assembly that may be positioned in the proximal end of the catheter of FIG. 4A and may be applied for stimulating a left phrenic nerve; FIG. 4C illustrates an electrode assembly that may be positioned in the distal end of the catheter of FIG. 4A and may be applied for stimulating a right phrenic nerve; and FIG. 4D illustrates a cross-sectional view of the catheter of FIG. 4A, with the electrode assemblies of FIG. 4B and 4C shown within the lumens of the catheter, according to exemplary embodiments.

FIG. 5 illustrates the anatomy of selected nerves and blood vessels in a person's neck and upper torso.

FIG. 6A illustrates electrical field lines produced by a catheter and electrode pair, according to an exemplary embodiment. FIG. 6B illustrates the electrical field lines of an exemplary prior art electrode.

FIG. 7A illustrates a catheter having leads sewn into the catheter shaft; FIG. 7B illustrates an electrode assembly that may be inserted into the catheter of FIG. 7A; FIG. 7C illustrates a partial longitudinal cross section of a distal electrode of FIG. 7A; and FIG. 7D illustrates a transverse cross-sectional view of a proximal electrode pair of FIG. 7A showing the inner lumens of the catheter, according to exemplary embodiments.

FIG. 8A illustrates a catheter having electrodes that are printed directly onto the exterior of the catheter; FIG. 8B illustrates an exploded view of distal elec-

trodes of the catheter of FIG. 8A; FIG. 8C illustrates an exploded view of proximal electrodes of the catheter of FIG. 8A; and FIG. 8D illustrates a transverse cross-sectional view of an electrode pair of FIG. 8A, according to exemplary embodiments.

FIG. 9A illustrates a catheter; FIG. 9B illustrates proximal and distal electrode assemblies that may be inserted into lumens of the catheter of FIG. 9A; FIG. 9C illustrates an exploded view of the distal electrode assemblies shown in FIG. 9B; FIG. 9D illustrates an exploded view of the proximal electrode assemblies shown in FIG. 9B; and FIG. 9E illustrates a transverse cross-sectional view of the catheter of FIG. 9A, according to exemplary embodiments.

FIGs. 10A and 10B illustrate views of a catheter having electrodes that are adhered directly onto the exterior of the catheter; FIG. 10C illustrates an exploded view of electrodes shown in FIG. 10A; FIG. 10D illustrates a transverse, cross-sectional view of a single electrode; and FIG. 10E illustrates a transverse, cross-sectional view of an electrode pair of FIG. 10A, according to exemplary embodiments.

FIG. 11A illustrates a catheter; FIG. 11B illustrates proximal and distal electrode assemblies held together by injection molding, according to a first exemplary embodiment; FIG. 11C illustrates an exploded view of the distal electrodes shown in FIG. 11B; FIG. 11D illustrates electrode assemblies held together by injection molding, according to a second exemplary embodiment; FIG. 11E illustrates an exploded view of the distal electrodes shown in FIG. 11D; and FIG. 11F illustrates a transverse, cross-sectional view of the catheter of FIG. 11A, showing the catheter lumens and electrode assemblies of FIG. 11B within the lumens.

FIG. 12A illustrates a catheter; FIG. 12B illustrates a perspective view of a distal electrode assembly; FIG. 12C illustrates a perspective view of a proximal electrode assembly; FIG. 12D illustrates a side view of the distal electrode assembly of FIG. 12B; FIG. 12E illustrates a side view of the proximal electrode assembly of FIG. 12C; FIG. 12F illustrates a transverse cross-sectional view of a distal electrode of FIG. 12D; FIG. 12G illustrates a transverse cross-sectional view of a proximal electrode of FIG. 12E; FIG. 12H illustrates a transverse cross-sectional view of the catheter of FIG. 12A with two distal electrode assemblies of FIG. 12B within the catheter lumens; FIG. 12I illustrates a transverse cross-sectional view of the catheter of FIG. 12A with two proximal electrode assemblies of FIG. 12C within the catheter lumens; FIG. 12J illustrates the view of FIG. 12H with ECG wires through a central lumen of the catheter; and FIG. 12K illustrates the view of FIG. 12I with ECG wires through a central lumen, according to exemplary embodiments.

FIG. 13A illustrates a catheter; FIG. 13B illustrates a perspective view of a distal electrode assembly

having arcuate electrodes; FIG. 13C illustrates a perspective view of a proximal electrode assembly having arcuate electrodes; FIG. 13D illustrates a side view of the distal electrode assembly of FIG. 13B; FIG. 13E illustrates a side view of the proximal electrode assembly of FIG. 13C; FIG. 13F illustrates a transverse cross-sectional view of a distal electrode of FIG. 13D; FIG. 13G illustrates a transverse cross-sectional view of a proximal electrode of FIG. 13E; FIG. 13H illustrates a transverse cross-sectional view of the catheter of FIG. 13A with two distal electrode assemblies of FIG. 13B within the catheter lumens; FIG. 13I illustrates a transverse cross-sectional view of the catheter of FIG. 13A with two proximal electrode assemblies of FIG. 13C within the catheter lumens; FIG. 13J illustrates the view of FIG. 13H with ECG wires through a central lumen of the catheter; and FIG. 13K illustrates the view of FIG. 13I with ECG wires through a central lumen, according to exemplary embodiments.

FIG. 14 illustrates individually shielded ECG wires, according to an exemplary embodiment.

FIGs. 15A, 15B, and 15C illustrate various views of a steering mechanism for steering a distal catheter tip, according to an exemplary embodiment.

FIG. 16A illustrates a catheter having a steering mechanism that includes a stiffening element and two pull wires that are adhered within a central lumen of the catheter; FIG. 16B illustrates a transverse cross-section of the catheter of FIG. 16A showing the steering mechanism in a central lumen; FIG. 16C illustrates a side view of the steering mechanism; FIG. 16D illustrates a longitudinal cross-sectional view of the distal portion of the catheter of FIG. 16A showing an exploded view of the steering mechanism; and FIG. 16E illustrates an exploded view of a portion of the steering mechanism shown in FIG. 16D, according to exemplary embodiments.

FIGs. 17A and 17B illustrate a steering mechanism that includes two hypodermic tubes with laser cut portions to help direct bending, according to an exemplary embodiment.

FIG. 18A illustrates a catheter having a steering mechanism that includes diametric lumens, each with a pull wire; FIG. 18B illustrates the pull wires of the steering mechanism; FIG. 18C illustrates a transverse cross-sectional view of the catheter of FIG. 18A; FIG. 18D illustrates a longitudinal cross-sectional view of the distal portion of the catheter of FIG. 18A showing the steering mechanism; and FIG. 18E illustrates an exploded view of a portion of the steering mechanism shown in FIG. 18D, according to exemplary embodiments.

FIG. 19A illustrates a catheter having a steering mechanism that includes a single push/pull wire inserted through a hypodermic tube/compression coil and adhered within a central lumen; FIG. 19B illustrates the steering mechanism; FIG. 19C illustrates

a transverse cross-sectional view of the catheter of FIG. 19A; FIG. 19D illustrates a longitudinal cross-sectional view of the distal portion of the catheter of FIG. 19A showing the steering mechanism; and FIG. 19E illustrates an exploded view of a portion of the steering mechanism shown in FIG. 19D, according to exemplary embodiments.

FIGs. 20A, 20B, and 20C illustrate catheters having different window alignments, according to exemplary embodiments.

FIG. 21 illustrates a dorsal view of human blood vessels and left and right phrenic nerves, with a pre-shaped catheter inserted within the blood vessels, according to an exemplary embodiment.

FIG. 22A illustrates a catheter having longitudinal slots along its length; and FIG. 22B illustrates a cross-sectional view of the catheter of FIG. 22A, according to an exemplary embodiment.

FIG. 23A illustrates a catheter having longitudinal slots along a portion of its length; and FIG. 23B illustrates a cross-sectional view of the catheter of FIG. 23A, according to an exemplary embodiment.

FIG. 24A illustrates electrode assemblies within the catheter of either FIGs. 22A-22B or 23A-23B, with a sleeve shown covering a portion of the catheter; and FIG. 24B illustrates a cross-sectional view of FIG. 24A, according to an exemplary embodiment.

FIG. 25A illustrates a side view of a ribbon wire catheter with an inner catheter core and an outer insulation jacket; FIG. 25B illustrates a perspective view of the catheter of FIG. 25A; and FIG. 25C illustrates a cross-sectional view of the catheter of FIG. 25A, according to an exemplary embodiment.

FIG. 26A illustrates electrodes attached to a ribbon wire catheter; FIG. 26B illustrates a cross-sectional view of a proximal electrode pair of the catheter of FIG. 26A; FIG. 26C illustrates a cross-sectional view of a distal electrode pair of the catheter of FIG. 26A; FIG. 26D illustrates the ribbon wire catheter of FIG. 26A, shown attached to a guidewire lumen and in a closed position; FIG. 26E illustrates the ribbon wire catheter of FIG. 26D in an open position; FIG. 26F illustrates the ribbon wire catheter of FIG. 26D in relation to a vessel wall and target nerve; FIG. 26G illustrates a perspective view of the ribbon wire catheter of FIG. 26A in an open position; and FIG. 26H illustrates the ribbon wire catheter of FIG. 26G with a pull wire, according to exemplary embodiments.

DETAILED DESCRIPTION

[0016] Throughout the following description, specific details are set forth to provide a more thorough understanding to persons skilled in the art. The following description of examples of the technology is not intended to be exhaustive or to limit the system to the precise forms of any example embodiment. Accordingly, the description and drawings are to be regarded in an illustrative,

rather than a restrictive, sense.

General Overview

[0017] In general, embodiments of this disclosure relate to medical devices and methods for electrically stimulating a patient's nerves. In one embodiment, the patient's nerves may be stimulated to activate the diaphragm to restore or control breathing.

[0018] The medical devices described herein may include several components, including a catheter having an elongated tubular member and one or more electrode assemblies, a signal generator to provide stimulation energy to the electrode assemblies, and one or more sensors to sense the condition of the patient and adjust the stimulation signals. The medical devices may further include a steering mechanism. Various embodiments of catheters are disclosed, including windowed catheters, multi-lumen catheters, and ribbon catheters. In addition, various embodiments of electrode assemblies are disclosed, which may be used alone, in combination with other electrode assemblies, and with any of the disclosed elongated tubular members that form the outer portion of the catheters. The term "catheter" may be used herein to refer to the elongated tubular member of the catheter or to the assembled catheter as a whole, which may include electrode assemblies, a steering mechanism, and any other components within or coupled to the elongated tubular member. Several types of steering mechanisms are also described.

[0019] The different embodiments of the various medical device components (e.g., catheters, electrode assemblies, steering mechanisms, etc.) may be combined and used together in any logical arrangement. Furthermore, individual features or elements of any described embodiment may be combined with or used in connection with the individual features or elements of other embodiments. The various embodiments may further be used in different contexts than those specifically described herein. For example, the disclosed electrode structures may be combined or used in combination with various deployment systems known in the art for various diagnostic and/or therapeutic applications.

[0020] During use, the medical devices (e.g., a catheter with one or more electrode assemblies) may be inserted into a patient's blood vessels such that the electrode assemblies are near the patient's nerves. The electrode assemblies may then be used for transvascular electrical stimulation of the patient's nerves. The disclosed devices may be optimized for rapid, temporary deployment in a patient and easy removal from the patient. The disclosed devices may be used, for example, for restoring breathing, treating conditions such as disuse muscle atrophy and chronic pain, or for any other procedures involving nerve stimulation. The disclosed devices may be used to treat acute or chronic conditions.

Medical Device Overview: Catheter and Electrode Assemblies

[0021] Referring to FIGs. 1-6B, an overview of an exemplary embodiment of a medical device and a method of use will be described. Later drawings will be referenced to describe additional or alternative embodiments of the various medical device components.

[0022] FIGs. 1A, 1B, and 1C illustrate various views of a catheter 10 according to an exemplary embodiment. In FIGs. 1A, 1B, and 1C, the catheter 10 is shown in a different rotational position around a longitudinal axis A-A through the catheter 10. The catheter 10 may include an elongated tubular member made of extruded polyurethane (or any other suitable biocompatible material). As can be seen in FIG. 1A, the catheter 10 may include a row of distal windows 16, which may be aligned along a longitudinal axis near a distal end 12 of the catheter 10. The catheter 10 may further include a second row of distal windows 16, which can be partially seen in FIG. 1C. At a position 14 on the catheter 10 proximal to windows 16 (in some cases at the proximal end of the catheter 10), the catheter 10 may similarly include two rows of proximal windows 18. These windows will be referred to herein as "proximal windows 18" to distinguish the proximal set of windows 18 from the distal set of windows 16. In other embodiments, the catheter 10 may include three or more rows of distal windows 16 or three or more rows of proximal windows 18. The proximal windows 18 may have the same or different structural features as the distal windows 16. A section of the catheter 10 between the proximal windows 18 and the distal windows 16 may be free of windows.

[0023] In one embodiment, the catheter 10 includes six distal windows 16 and twelve proximal windows 18. However, in other embodiments, the catheter 10 may include fewer or more proximal or distal windows. For example, in other embodiments, the catheter 10 may include two, four, eight, ten, twelve, or more distal windows 16, and/or two, four, six, eight, ten, or more than twelve proximal windows 18. The distal windows 16 and proximal windows 18 may be configured in pairs such that the catheter 10 has an even number of distal windows 16 and an even number of proximal windows 18. However, the number of windows 16 or 18 may also be an odd number.

[0024] The windows 16, 18 may be cut (e.g. by a laser, manual skive, drill, punch, etc.) through the exterior wall of catheter 10, or the windows may be formed by any other suitable method, such as during an extrusion process or other manufacturing process. The windows 16, 18 may be elongated along the longitudinal axis A-A. They may have a rectangular, oval, square, or any other shape. The windows 16, 18 may be apertures configured to allow electrical signals to travel from an interior lumen of the catheter 10 to the exterior of the catheter 10. In an additional or alternative embodiment, the windows 16, 18 may be covered by a material that allows electrical signals to

pass through. As can be seen in the figures, the proximal windows 18 may be rotationally offset from the distal windows 16. In other words, in one embodiment, a straight line drawn proximally through a row of distal windows 16 does not pass through a row of proximal windows 18. In other embodiments, one or more rows of proximal windows 18 may be aligned with a corresponding row of distal windows 16.

[0025] The dimensions of catheter 10 may be customized in accordance with the anatomy of a particular patient. However, in some embodiments, the length of the section of the catheter 10 that includes the proximal windows 18 may be 10cm or less, between 3-5cm, or between 1-3cm. The distance between two adjacent proximal windows 18 (whether the windows are longitudinally adjacent or adjacent on the same row of windows) may be 5cm or less, 3cm or less, or may be around 1cm. The length of the section of the catheter 10 that includes the distal windows 16 may be 6cm or less, between 2-4cm, or between 1-2cm. The distance between two adjacent distal windows 16 (whether longitudinally adjacent or adjacent on the same row of windows) may be 5cm or less, 3cm or less, or may be around 1cm. The length of the section of the catheter between proximal windows 18 and distal windows 16, which may be free of windows, may be 12cm or less, 10cm or less, or 8cm or less. The windows 16, 18 may have a length of 6mm or less, 5mm or less, 4mm or less, 3mm or less, 2mm or less, or 1mm or less. In one embodiment, the windows may have a length that is less than the length of corresponding electrodes that are electrically exposed through the windows. It should be understood that the above catheter dimensions are exemplary only, and the catheter 10 may have dimensions that vary from the above ranges and specific measurements.

[0026] FIG. 2 illustrates a cross-sectional view along plane II-II (see FIG. 1A) of catheter 10. The interior of catheter 10 may include one or more lumens. In one embodiment, the catheter 10 may include six lumens 20, 22, 24, 26, 28, 30, although the catheter 10 may include fewer or more lumens. The lumens 20, 22, 24, and 26 may be electrode assembly lumens used to receive electrode assemblies described in further detail below. In one embodiment, proximal windows 18 may create a pathway between the interior of lumens 20, 22 and the exterior of catheter 10. Thus, lumens 20, 22 may receive electrodes that align with the proximal windows 18 shown in FIGs. 1A-1C. Similarly, distal windows 16 may create a pathway between the interior of lumens 24, 26 and the exterior of catheter 10, and lumens 24, 26 may receive electrodes that align with the distal windows 16 shown in FIGs. 1A-1C. Lumens 20, 22 may therefore be proximal electrode assembly lumens, and lumens 24, 26 may be distal electrode assembly lumens. As will be described in greater detail below, the proximal electrode assemblies placed in lumens 20, 22 may be used to stimulate a patient's left phrenic nerve, and the distal electrode assemblies placed in lumens 24, 26 may be used to stimulate a pa-

tient's right phrenic nerve. Lumen 28 may receive a guidewire, and lumen 30 may receive a steering mechanism, other instruments, wires, or may be used to transport fluid to or from a working site.

[0027] FIG. 3A illustrates an exemplary embodiment of a proximal electrode assembly 32, and FIG. 3B illustrates a cross-sectional view of a single electrode 36 along plane IIIB-IIIB of FIG. 3A. In one embodiment, the proximal electrode assembly 32 may include six proximal electrodes 36. Similarly, FIG. 3C illustrates an exemplary embodiment of a distal electrode assembly 34, and FIG. 3D illustrates a cross-sectional view of a single electrode 38 along plate IIID-IIID of FIG. 3C. The distal electrode assembly 34 may include three distal electrodes 38. The two electrode assemblies 32 and 34 may differ from one another in terms of number of electrodes, structural features of the electrodes, and structural features of the assembly as a whole.

[0028] A proximal electrode assembly 32 may be held within one of proximal electrode assembly lumens 20, 22 of catheter 10, and a second proximal electrode assembly 32 may be held within the other of proximal electrode assembly lumens 20, 22 of catheter 10. Similarly, distal electrode assembly 34 may be held within one of distal electrode assembly lumens 24, 26 of catheter 10, and a second distal electrode assembly 34 may be held within the other of distal electrode assembly lumens 24, 26 of catheter 10. This combination of two proximal electrode assemblies 32 and two distal electrode assemblies 34 within the lumens of catheter 10 may allow the twelve proximal electrodes 36 to align with the twelve proximal windows 18 and the six distal electrodes 38 to align with the six distal windows 16.

[0029] FIGs. 3A and 3B will be referenced to describe proximal electrode assembly 32 in greater detail. Individual electrical leads 44 may be coiled together to form cable 40 of the proximal electrode assembly 32. Each lead 44 may include an elongated conductive member 45 and may be surrounded by a layer of non-conductive material 46. In one embodiment, the lead 44 may be a wire, the elongated conductive member 45 may include strands of stainless steel or another conductive material, and the non-conductive material 46 may be a layer of insulation. The leads 44 may deliver electrical or other signals to and from the electrodes 36.

[0030] In one embodiment, the cable 40 may include seven leads 44. Of these seven leads 44, six may be individually de-insulated at certain locations (e.g., underneath electrodes 36, as shown in FIG. 3B) to expose the conductive member 45 underneath. A conductive connector 42, which may be thin, flexible, and made of stainless steel or another conductive material, may be joined (e.g. mechanically, adhesive, micro-welded, etc.) to the exposed conductive member 45 and wrapped transversely around the cable 40. The conductive connector 42 may provide a contact surface between the exposed conductive member 45 and an electrode 36. In one embodiment, the electrode 36 may be a platinum-10% irid-

ium (or any other suitable implantable electrode material like stainless steel, platinum, titanium nitride, coated stainless steel, etc.) ring electrode, which is crimped (or adhered, microwelded) to the exterior of the conductive connector 42 and cable 40. The seventh insulated lead 44 shown in the center of FIG. 3B may help support and stiffen the cable 40. The seventh lead 44 also may be used to carry other types of signals, for example signals from a sensor or ECG signals. In total, as noted above, two seven-lead proximal electrode assemblies may be inserted into the lumens 20, 22 of catheter 10.

[0031] Referring to FIGs. 3C and 3D, cable 48 of a distal electrode assembly 34 may include three electrical leads 44, which may be constructed in a similar manner as described in connection with the proximal electrode assembly 32. Three electrodes 38 may be mounted to conductive connectors 42, which are connected to exposed conductive members 45 of corresponding leads 44. In additional or alternative embodiments, partial or semi-circular electrodes may be used instead of ring electrodes 36, 38. The number of lumens within catheter 10, number of cables 40, 48, the number of electrodes 36, 38 on each cable 40, 48, respectively, and the distance between electrodes 36, 38, along with other structural features, may be varied to fit particular applications.

[0032] In one embodiment, any of the proximal electrodes 36 or the distal electrodes 38 may be used to measure electrical signals or other data from within the patient's body. In other words, in addition or alternatively to emitting or receiving electrical energy to produce a localized current for nerve stimulation, the electrodes may serve as sensors that receive electrical or other types of information from the patient.

[0033] FIGs. 4A-4D illustrate how multiple electrode assemblies 32, 34 may be within the lumens of catheter 10. A catheter 10 is depicted in FIG. 4A, two proximal electrode assemblies 32 are depicted in FIG. 4B, and two distal electrode assemblies 34 are depicted in FIG. 4C. The two proximal electrode assemblies 32 may be placed within lumens 20, 22 of catheter 10 such that the electrodes 36 align with proximal windows 18. Similarly, the two distal electrode assemblies 34 may be placed within lumens 24, 26 of catheter 10 such that the electrodes 38 align with distal windows 16 (not shown in FIG. 4A). Once aligned, the electrode assemblies 32, 34 may be fixed (e.g. with adhesive or by any other structure or method) within their respective catheter lumens. FIG. 4D illustrates a cross-section of catheter 10, taken along plane IVD-IVD of FIG. 4A, that shows the catheter with two proximal electrode assemblies 32 and two distal electrode assemblies 34 within lumens 20, 22, 24, 26 of catheter 10.

[0034] Referring to FIG. 5, a medical device 50 may include a catheter 10 having two proximal electrode assemblies 32 and two distal electrode assemblies 34. The electrode assemblies 32, 34 may be within the elongated tubular member of catheter 10 such that electrodes 36 are exposed through proximal windows 18 and elec-

trodes 38 are exposed through distal windows 16. The cables 40, 48 formed of electrical leads 44 may exit through the proximal end of the catheter 10 and may be attached (e.g. by solder, crimp, PCB, etc.) to connectors 52, 54.

[0035] To assemble medical device 50, the electrode assemblies 32, 34, which may include leads 44 and electrodes 36, 38, may be introduced into one or more lumens through lumen openings at either the proximal end or distal end of catheter 10. For example, the leads 44 may be inserted into a proximal end of the catheter 10 and threaded or pulled through one or more lumens until electrodes 36, 38 are located at predetermined locations in a more distal portion of the catheter 10. Portions of the catheter wall may be removed, either before or after insertion of the electrode assemblies 32, 34, to create windows 18, 16. Windows 18, 16 may expose the electrodes, allowing for a conductive path between the electrodes 36, 38 and the blood vessel lumen in which the medical device 50 may be placed.

[0036] Referring still to FIG. 5, in an exemplary method of use, the medical device 50 may be used for transvascular stimulation of nerves in the neck and/or chest of a human or other mammal (e.g., a pig, a chimpanzee). FIG. 5 illustrates the anatomy of selected nerves and blood vessels in the neck and chest of a human and, in particular, the relative locations of the left phrenic nerve (PhN) 56, right phrenic nerve 58, vagus nerves (VN) (not shown), external or internal jugular veins (JV) 60, brachiocephalic veins (BCV) 62, superior vena cava (SVC) 64, and left subclavian vein (LSV) 66.

[0037] The medical device 50 may be used to rhythmically activate the diaphragm by inserting the catheter 10, with one or more electrode assemblies 32, 34, percutaneously into central veins of a patient. Percutaneous insertion of the catheter 10 may be accomplished by the Seldinger technique, in which a guide wire is inserted through a hypodermic needle into a vein. The distal tip of the catheter is then passed over the guide wire and advanced into the vein. The shape and mechanical properties of the catheter may be designed to urge the catheter 10 to gently hug the vein wall in regions adjacent to the right and left phrenic nerves, as shown in FIG. 5.

[0038] In the embodiment of FIG. 5, the medical device 50 may be inserted into the left subclavian vein 66 and advanced into the superior vena cava 64. In another configuration, not shown, the medical device 50 may be inserted into the left jugular vein and advanced into the superior vena cava 64. The catheter 10 may be inserted in a minimally-invasive way and may be temporarily placed into, and thus removable from, the patient. In one embodiment, the windows 18 are oriented such that, when the catheter is inserted into the left subclavian vein 66, the six pairs of windows 18 are directed posteriorly towards the left phrenic nerve 56 and the three pairs of distal windows 16 are directed laterally towards the right phrenic nerve 58.

[0039] In one embodiment, the electrode assemblies

34 may include electrodes 38 arranged and oriented to most effectively stimulate a nerve extending parallel to the catheter 10 (e.g., the right phrenic nerve 58 in FIG. 5), and the electrode assemblies 32 may include electrodes 36 arranged and oriented to most effectively stimulate a nerve extending at transverse or right angles to the catheter 10 (e.g., the left phrenic nerve 56 in FIG. 5). In an additional or alternative embodiment, the electrode assemblies 34 may include electrodes 38 arranged and oriented to most effectively stimulate a nerve extending at transverse or right angles to the catheter 10, and the electrode assemblies 32 may include electrodes arranged and oriented to most effectively stimulate a nerve extending parallel to the catheter 10. In the embodiments described above, the electrodes 38 of the electrode assemblies 34 have been placed in a more distal location along catheter 10 than the electrodes 36 of electrode assemblies 32. However, in other embodiments, the electrode assemblies 32 may be arranged within the catheter 10 such that their electrodes 36 are more distal than the electrodes 38 of the electrode assemblies 34. In this alternative embodiment, the windows 16, 18 of the catheter 10 may be configured to accommodate the alternative placement of the electrode assemblies 32, 34.

[0040] Once the catheter is fully inserted into the patient, various pairs of bipolar electrode combinations can be tested to locate nerves of interest and to determine which electrodes most effectively stimulate the nerves of interest. For example, in one embodiment, testing may be done to locate the right phrenic nerve 58 and to determine which pair of electrodes 38 (out of the distal set of electrodes 38) most effectively stimulate the right phrenic nerve 58. Similarly, testing may be done to locate the left phrenic nerve 56 and to determine which pair of electrodes 36 (out of the proximal set of electrodes 36) most effectively stimulate the left phrenic nerve 56. As a non-limiting example, testing could involve the use of a signal generator to systematically send electrical impulses to selected electrodes. By observing the patient's condition or by using sensors, the ideal electrode pairs may be identified.

[0041] FIG. 6A illustrates a cross-sectional view of catheter 10 along the plane VIA-VIA shown in FIG. 4A and will be referenced to describe selective activation of a pair of electrodes for stimulating a nerve. The electrodes of FIG. 6A may be any electrode pair located at any location along catheter 10, and the nerve 56 may be any nerve located parallel, transverse, or at any other orientation with respect to catheter 10. However, for ease of description, proximal electrodes 36 and left phrenic nerve 56 are referenced in connection with FIG. 6A, even though left phrenic nerve 56 is shown transverse to catheter 10 in FIG. 5. Although not shown in FIG. 6A, a pair of distal electrodes 38 also may be selectively activated to stimulate the right phrenic nerve 58.

[0042] During "selective activation," an electrical potential may be created between a pair of selected bipolar electrodes, such as between a first electrode 36' and a

second electrode 36". The first electrode 36' may be aligned with a first window 18', and the second electrode 36" may be aligned with a second window 18". The arrangement of the first and second electrodes 36', 36" and the first and second windows 18', 18" may create an electrical field 68 in the vicinity of first and second windows 18', 18". The first and second electrodes 36', 36" may be selected to effectively target a nerve, such as the left phrenic nerve 56 shown in FIG. 6A or another nerve near the electrodes 36', 36". The windows 18', 18" and the resulting electrical field 68 may therefore be oriented to-

wards the left phrenic nerve 56 or other target nerve. **[0043]** During nerve stimulation, electrical current flows from one of the electrodes 36', 36" to the other of the electrodes 36', 36", flowing through the windows 16', 16" and through the blood and surrounding tissues. The catheter 10 with windows 16', 16" therefore acts as an insulative barrier that constrains and focuses the electrical field 68, rather than allowing the electrical field 68 to expand radially outwards in all directions. The focused electrical field allows target nerve stimulation at lower energy levels and avoids stimulating unwanted nerves or other structures. In some embodiments, the stimulation current may be between 10 - 6000nC (nanocoulombs) or between 50-500nC.

[0044] FIG. 6B illustrates an exemplary prior art nerve stimulation device 70 that may be used to stimulate a nerve 78. The prior art device 70 may include lead wires 72 and an electrode 74. The device 70 may be inserted into a blood vessel 76, and an electrical field 80 may be created around the device 70. As can be seen in FIG. 6B, the electrical field 80 may be created around the circumference of the device 70. Although it may target a nerve 78, the electrical field is not confined to a specific location and therefore may also target other anatomical structures within the patient. Thus, in general, the windows 16, 18 of catheter 10 may allow the use of lower and safer electrical currents to activate the phrenic nerves 56, 58 and prevent overstimulation or unwanted activation of nearby structures such as other nerves, muscles, or the heart.

Electrode Assembly Embodiments

[0045] FIGs. 7A-13K illustrate additional or alternative embodiments of electrodes and electrode assemblies that may be used with any of the catheters described herein. The below embodiments may be variations of the electrode assemblies and electrodes described previously. Therefore, features not mentioned may be unchanged or logical modifications of the above-described embodiments. For ease of reference, proximal electrodes 36, proximal electrode assemblies 32, distal electrodes 38, and distal electrode assemblies 34 of each embodiment will be referred to using the same reference numerals as used above, even though some features of these components may be modified in the below embodiments.

Bare/Sewn Wires

[0046] Referring to FIGs. 7A-7D, the layer of non-conductive material 46 may be removed from portions of leads 44 to expose the underlying conductive member 45. FIG. 7A illustrates a catheter 10, and FIG. 7B illustrates a proximal electrode assembly 32. The exposed conductive members 45 (straight or coiled for increased surface area) of leads 44 may be positioned within windows 16 or 18 of the catheter 10 and, in some embodiments, may extend radially out of the windows 16, 18. In another embodiment, as shown in FIG. 7C, the conductive member 45 may pass out of a lumen of the catheter 10 through an aperture in the catheter outer wall, travel in a proximal-distal direction, and then pass back through another aperture in the outer wall of catheter 10. The portion of the conductive member 45 that forms an electrode 36, 38 may be the distal end of a lead 44. The insulated leads 44 may additionally or alternatively be sewn into the catheter 10, leaving the exposed conductive member 45 on the exterior of the catheter 10 and the remaining insulated lead 44 inside a catheter lumen. FIG. 7D illustrates a cross-section of catheter 10 through a pair of proximal electrodes 36 that include exposed conductive members 45.

[0047] In some embodiments, a conductive member, such as an electrode described in connection with FIGs. 10A-10E, may be fixed (e.g., with adhesive, heat fusion, etc.) to the exterior of catheter 10 and in electrical contact (e.g., mechanically, microwelded) with the exposed conductive member 45. Fixing such a conductive member to the exposed conductive member 45 may increase certain electrical properties of the electrode, such as conductivity and surface area, relative to an electrode that only includes the exposed conductive member 45. Examples of conductive member material include platinum, platinum iridium, gold, stainless steel, titanium nitride, MP35N, palladium, etc.

Printed Electrodes

[0048] FIG. 8A illustrates a catheter having electrodes and leads that are printed directly onto the exterior of catheter 10. FIG. 8B illustrates an exploded view of distal electrodes 38 of the catheter 10, FIG. 8C illustrates an exploded view of proximal electrodes 36 of catheter 10, and FIG. 8D illustrates a transverse cross-sectional view of a proximal electrode pair 36 taken along plane VIIIID-VIIIID of FIG. 8C. Electrodes 36, 38 may be formed by conductive inks (such as silver flakes or carbon flakes suspended in polymer). These conductive inks may be deposited and adhered directly onto the catheter 10 and sealed, except for the exposed electrodes 36, 38, with an outer polyurethane or other flexible insulative film. The exposed electrodes 36, 38 also may be coated (e.g., with titanium nitride) for purposes such as one or more of: enhancing electrical properties, such as conductivity and surface area; providing corrosion resistance; and reduc-

ing the potential for formation of silver oxide which could be toxic. As can be seen in FIG. 8C, the conductive ink trace of distal electrodes 38 may travel proximally along catheter 10 past the proximal electrodes 36.

[0049] The use of printed electrodes may reduce the overall complexity of the design while maximizing the useable catheter lumen space, without changing the catheter profile or flexibility too drastically. However, in some embodiments, the profile of the catheter may be reduced because of the space saved by using electrodes printed on the exterior of the catheter. In an additional or alternative embodiment, one or several catheter lumens may be used for fluid delivery, blood sampling, or central venous pressure monitoring. In another additional or alternative embodiment, several of the catheter lumens, such as lumens 20, 22, 24, 26 may be eliminated since there are no catheter assemblies as described in connection with other embodiments. Thus, in one embodiment, the catheter 10 may include only lumen 28 and lumen 30. If the catheter 10 with printed electrodes includes fewer than the six lumens shown in FIG. 2, for example, its cross-sectional area may be reduced, one or more of the fewer lumens may be made larger to accommodate larger tools or other objects, or one or more smaller lumens may be added to accommodate tools or other objects.

Electrode-Supporting Catheters

[0050] FIGs. 9A-9E illustrate electrodes 36, 38 supported by catheters 94, 96 that may be placed within a lumen of catheter 10. In this embodiment, proximal electrodes 36 may be joined by an electrode catheter 94, and distal electrodes 38 may be joined by an electrode catheter 96. The catheters 94, 96 may be elongated tubular members that include a non-conductive material. The electrodes 36, 38 may be crimped onto the catheters 94, 96 and may be electrically connected to conductive members 45 of leads 44 through the walls of the electrode catheters 94, 96. The catheters 94, 96 may have cross-sectional areas that are smaller than the cross-sectional areas of their respective lumens of catheter 10 so that catheters 94, 96 may be inserted into the lumens of catheter 10. When catheters 94, 96 are inserted into catheter 10, the electrodes 36, 38 may be aligned with windows 18, 16 of catheter 10 and fixed in place, similar to other embodiments. Although not shown in FIG. 9E, leads 44 may travel in a proximal-distal direction through the electrode catheters 94, 96.

[0051] In an additional or alternative embodiment, one or more catheters having a single electrode 36 or 38, or a pair of bipolar electrodes, may be inserted into a lumen of catheter 10 during a procedure (i.e., while catheter 10 is within a patient's vascular system) and advanced to various windows 18, 16 until optimal locations are found. By doing so, less material may be used, which may drive down the cost of production of the medical device 50.

Exterior Electrodes

[0052] FIGs. 10A-10E illustrate electrodes 36, 38 on the exterior of a catheter 10. In the embodiment of FIGs. 10A-10E, electrodes 36, 38 may be connected (microwelded, etc.) to a lead 44 and may be fixed (e.g., crimped, adhered, etc.) onto the exterior of catheter 10. The lead 44 may be inserted through the wall of the catheter 10 (e.g., through a window 16, 18) and into a lumen within the catheter 10.

[0053] In other embodiments, one or more ring electrodes may be fixed to the exterior of the catheter 10. To facilitate directional targeting of one or more nerves, an insulative coating may be applied to cover a portion of the electrodes.

Injection Molding

[0054] FIGs. 11A-11F illustrate an embodiment in which the manufacturing process of electrode assemblies 32, 34 may include injection molding. To obtain the electrode configuration shown in FIGs. 11B and 11C, electrodes 36, 38 may be individually attached to leads 44 by injection molding, with the electrodes 36, 38 in electrical contact with conductive members 45. The molding process may form a covering 98 around each lead 44. The covering 98 may include a non-conductive material, such as plastic. The electrodes 36, 38 may be flat, semi-circular, or any other suitable shape. Similarly, the covering 98 may form any shape around the leads 44, such as the shape shown in FIG. 11F.

[0055] In another embodiment, shown in FIGs. 11D and 11E, the electrodes 36, 38 and bundle of leads 44 may be placed within an injection molding jig that injects material, such as plastic, around the bundle of leads 44 to anchor the electrodes in place, forming a covering 98 but in one embodiment leaving at least a portion of the electrodes 38 exposed. In some embodiments, the electrodes may be covered by a thin layer of polymer, which may be removed in a subsequent step. In the embodiment of FIG. 11C, the covering 98 may be placed in the longitudinal vicinity of the electrodes and might only surround a single lead, and thus may be referred to as "partial." In the embodiment of FIG. 11E, the covering 98 may cover a larger longitudinal portion of the underlying leads 44 and may surround multiple leads, and thus may be referred to as "full." Once each electrode 38 is anchored to the leads 44, the electrode assemblies 32, 34 may be inserted into the lumens of catheter 10 and aligned with windows 18, 16.

Electrodes Supported by Tubular Members

[0056] FIGs. 12A-12K illustrate yet another embodiment of electrode assemblies 32, 34. In this embodiment, tubular members 100 may support the distal ends 102 of leads 44 and hold the distal ends 102 adjacent to electrodes 36, 38.

[0057] FIG. 12A illustrates a catheter 10; FIG. 12B illustrates a perspective view of a distal electrode assembly 34; FIG. 12C illustrates a perspective view of a proximal electrode assembly 32; FIG. 12D illustrates a side view of the distal electrode assembly 34 of FIG. 12B; FIG. 12E illustrates a side view of the proximal electrode assembly 32 of FIG. 12C; FIG. 12F illustrates a transverse cross-sectional view of a distal electrode 38 of FIG. 12D; FIG. 12G illustrates a transverse cross-sectional view of a proximal electrode 36 of FIG. 12E; FIG. 12H illustrates a transverse cross-sectional view of the catheter of FIG. 12A with two distal electrode assemblies 34 of FIG. 12B within the catheter lumens; FIG. 12I illustrates a transverse cross-sectional view of the catheter 10 of FIG. 12A with two proximal electrode assemblies 32 of FIG. 12C within the catheter lumens; FIG. 12J illustrates the view of FIG. 12H with ECG wires through a central lumen of the catheter 10; and FIG. 12K illustrates the view of FIG. 12I with ECG wires through a central lumen of catheter 10.

[0058] FIGs. 12B-12G illustrate the proximal and distal electrodes 36, 38 of the proximal and distal electrode assemblies 32, 34, respectively. As can be seen in the figures, electrode assemblies 32, 34 include leads 44, similar to other embodiments. As shown most clearly in FIGs. 12F and 12G, the distal portions 102 of leads 44 may include exposed conductive members 45 and may be attached by welding or any other method to the exterior of a tubular member 100 and to the interior of electrodes 36, 38. The tubular member 100 may be 1-6mm in length, 2-4mm in length, and in one embodiment about 3mm in length, although the tubular member 100 may be any other suitable length. The tubular member 100 may be a stainless steel hypodermic tube. (In FIGs. 12B-12E, tubular members 100 are not shown and would be all or mostly covered by electrodes 36, 38. Distal portions 102 of leads 44 are labeled in FIGs. 12D and 12E to show their general location, although they are underneath electrodes 36, 38.) As can also be seen in FIGs. 12F and 12G, the distal portions 102 of leads 44 may cause the electrodes 36, 38 to protrude radially outward.

[0059] Each lead 44 may travel proximally through any electrodes 38, 36 that are positioned more proximally than the electrode to which the distal end 102 of that lead is attached. For example, referring to FIG. 12B, the lead 44 that is attached to the most distal electrode 38 of the distal electrode assembly 34 may travel proximally through the other two electrodes 38 and through all six proximal electrodes 36. Referring to FIG. 12C, the lead 44 attached to the most distal electrode 36 may travel proximally through each of the other five electrodes 36.

[0060] In one embodiment, the distal electrode assembly 34 may include three leads 44 - one for each electrode 38. Similarly, the proximal electrode assembly 32 may include six leads 44 - one for each electrode 36. As the leads 44 of each electrode assembly 32, 34 join together, the leads may be coiled to form cables 48, 40. At more distal locations, cable 48 (formed of leads 44 from distal

electrode assembly 34), may include one or two leads. At more proximal locations, such as proximal to the most proximal electrode 38, cable 48 may include three leads 44. Similarly, at more distal locations, cable 40 (formed of leads from proximal electrode assembly 32), may include one, two, three, four, or five leads. At more proximal locations, such as proximal to the most proximal electrode 36, cable 40 may include six leads 44.

[0061] FIGs. 12H and 12I illustrate cross-sectional views with the electrode assemblies 34, 32 within lumens of the catheter 10. Although the lumens of catheter 10 illustrated in FIGs. 12H and 12I may be shaped differently than in FIG. 2, the catheter 10 may still include lumens 20, 22 configured to receive proximal electrode assemblies 32, lumens 24, 26 configured to receive distal electrode assemblies 34, a lumen 28 configured to receive a guidewire, and a lumen 30 configured to receive a steering mechanism or other structures. As can be seen in FIGs. 12H, distal electrodes 38 may be aligned with distal windows 16. FIG. 12I illustrates proximal electrodes 36 aligned with proximal windows 18. The leads 44 from distal electrode assemblies 34 can be seen in the cross-sectional view of FIG. 12I because the leads 44 may travel proximally through lumens 24, 26.

[0062] FIGs. 12J and 12K are similar to the views shown in FIGs. 12H and 12I, except FIGs. 12J and 12K illustrate two electrocardiography (ECG) conductive members 104 within lumen 30. ECG conductive members 104 may be coupled to one or more ECG electrodes 106 (see FIG. 12A and FIG. 14) located at a distal end of catheter 10, for sensing ECG signals of a patient.

[0063] One benefit of the embodiments of FIGs. 12A-12K is that each electrode 36, 38 may be movable with respect to other electrodes 36, 38. Although the electrodes 36, 38 are connected by leads 44, the leads 44 typically are flexible. Therefore, when placing electrode assemblies 32, 34 within catheter 10 during manufacture of the medical device 50, this embodiment allows each electrode 36, 38 to be positioned within its respective window 18, 16 at least partially independently of other electrodes. Independent positioning of the electrodes may allow positioning errors to be minimized, as opposed to embodiments in which electrodes 36, 38 are fixed to other electrodes by a catheter or other rigid structure.

Arcuate Electrodes

[0064] FIGs. 13A-13K illustrate an embodiment that is similar to the embodiment shown in FIGs. 12A-12K. Similar features from the embodiment of FIGs. 12A-12K will not be repeated here. The main difference between the embodiment of FIGs. 13A-13K and the embodiment of FIGs. 12A-12K is that each of the electrodes 36, 38 of FIGs. 13A-13K may form an arcuate shape that functions to hold and contact the distal ends 102 (including exposed conductive members 45) of leads 44. The proximal and distal assemblies 32, 34 of FIGs. 13A-13K may or may not include tubular members 100.

[0065] As shown in FIGs. 13F and 13G, each of the electrodes 36, 38 may be C-shaped and may have an outer wall 108 and an inner wall 110. The outer wall 108 and the inner wall 110 of an electrode may sandwich the exposed conductive member 45 at the distal end 102 of a lead 44.

Electrocardiography Electrodes

[0066] FIG. 14 illustrates two ECG electrodes 106 and their associated components. As with all other features in this application, the ECG electrodes 106 may be used with any of the other embodiments described herein. The ECG electrodes 106 may be located at a distal end of a catheter 10 (see FIG. 12A). In one embodiment, the catheter 10 may include two ECG electrodes 106, although in some embodiments the catheter 10 may include one electrode 106 or more than two electrodes 106. A conductive member 104, which may be insulated, may connect each electrode 106 to an ECG system located outside of the patient. The ECG conductive members 104 may be braided or twisted together and may be surrounded by a non-conductive layer 105 (also shown in FIGs. 12J and 12K).

[0067] The electrodes 106 may monitor a patient's heart rate. Heart rate monitoring may be beneficial during use of medical device 50 to alert a medical practitioner to changes in the patient's heart rate. Changes in the patient's heart rate may be caused by the medical device 50 stimulating certain nerves or by unintentional stimulation of the patient's heart. Heart rate monitoring also may be relied on to achieve steady recruitment of a nerve. For example, the catheter 10 may move when a patient's heart beats, causing fluctuations in nerve stimulation. If the patient's heart rate is known, the electrical potential created between a pair of bipolar nerve-stimulating electrodes can be adjusted in real time to deliver a constant charge to the nerve.

Steering Mechanisms

[0068] A variety of steering mechanism may be included in a medical device 50 to help control positioning of catheter windows 16, 18, and thus electrodes 38, 36, within a blood vessel. A steering mechanism may be located within a central lumen 30 of catheter 10 or within other lumens of the catheter 10. It may be beneficial to position at least some electrodes 36, 38 in close proximity to each target nerve, as having electrodes situated close to the nerve can reduce the amount of current shunted through the blood and thus may reduce the electrical current needed to activate the nerve.

[0069] Several factors may help position the proximal windows 18 in a desired location within a blood vessel. For example, the typical subclavian vein penetration angle and the shape and elasticity of catheter 10 may combine to position the proximal windows 18 along a posterior wall of the subclavian vein, in close proximity to the left

phrenic nerve, which normally descends dorsal to the left subclavian vein.

[0070] To ensure that the distal portion of the catheter 10, including windows 16 and their associated electrodes 38, is positioned in a desired location with respect to the right phrenic nerve, the medical device 50 may include stiffening elements and steering mechanisms. In one embodiment, the stiffening elements and steering mechanisms may help position the distal set of electrodes 38 against a lateral wall of the superior vena cava, close to the right phrenic nerve.

Turn Member Steering Mechanism

[0071] Referring to FIGs. 15A-15C, a steering mechanism 112 may include a single pre-shaped elongated member 114, such as a wire or tube (i.e. stainless steel, nitinol, hypodermic tube, etc.) to steer the catheter 10. The elongated member 114 may include a handle 120, a proximal portion 116 coupled to the handle 120, and a distal portion 118 that is bent with respect to the proximal portion 116. When the proximal portion 116 is turned via the handle 120, the distal portion 118 may correspondingly turn into a variety of positions and may function to position the distal end of catheter 10.

[0072] FIGs. 15A-15C illustrate the elongated member 114 in three different positions: a first position indicated by distal portion 118a, a second position indicated by distal portion 118b, and a third position indicated by distal portion 118c. FIG. 15A illustrates a front view of the steering mechanism 112 in three different positions, FIG. 15B illustrates a top view of steering mechanism 112 in three different positions, and FIG. 15C illustrates a view from the distal end of the steering mechanism 112 to the proximal end of the steering mechanism 112 when the steering mechanism 112 is in three different positions.

[0073] Elongated member 114 may be stiff enough to ensure that the distal portion of the catheter 10, which includes the distal electrodes 38, is placed against the vessel wall. The elongated member 114 also may be stiff enough to transmit steering torque from the proximal handle 120 to the distal portion 118.

Control Member Steering Mechanisms

[0074] Referring to FIGs. 16A-16E, another embodiment of steering mechanism 112 may include one or more control members 122. In one embodiment, the control members 122 may be pulled or pushed to bend or deflect a portion of catheter 10. The control members 122 may be surrounded by and may slide longitudinally relative to one or more tubular members 124, such as hypodermic tubes or compression coils. The tubular members 124 may be flexible. The steering mechanism 112 of this embodiment may further include a stiffening element 126, such as a tube or rod, which may be attached (e.g., by weld, adhesive, etc.) to the tubular members 124.

[0075] The embodiment of FIGs. 16A-16E may allow bidirectional steering of catheter 10. At a proximal end of the steering mechanism 112, a handle (not shown) may facilitate pulling or pushing of the control members 122 relative to their corresponding tubular members 124. As shown in FIG. 16C, the distal end of the steering assembly 112 may include gaps 128 between tubular members 124. The gaps 128 may facilitate bending of the distal end of the catheter 10. Once assembled, the steering mechanism 112 may be adhered within the central lumen 30 or another lumen of the catheter 10.

[0076] Referring to FIGs. 17A and 17B, in an additional or alternative embodiment, tubular members 124 may include narrowed portions 130. The narrowed portions 130 may replace the gaps 128 or may be used in combination with gaps 128 to provide the desired flexibility. The narrowed portions 130 may be formed using a laser or by any other method.

[0077] Referring to FIGs. 18A-18E, in yet another embodiment of steering mechanism 112, control members 122 may be located in separate lumens 132, 134 within catheter 10. Similar to the embodiment of FIGs. 16A-16E, the control members 122 may be surrounded by one or more tubular members 124, which may be hypodermic tubes or compression coils. In one embodiment, each tubular member 124 does not surround a distal end portion of its respective control member 122. The distal end portion of the control member 122 may therefore be fixed to the distal end of its corresponding lumen 132, 134. A distal end portion of each tubular member 124 also may be fixed to its respective lumen 132, 134 at a position more proximal than the fixed portion of the control member 122. A gap extending longitudinally along the lumen may be left between the fixed portion of the control member 122 and the fixed portion of its corresponding tubular member 124 such that, when the control member 122 is pulled or pushed relative to its tubular member 124, deflection of the catheter 10 occurs within the gapped space.

[0078] In yet another embodiment, referring to FIGs. 19A-19E, steering mechanism 112 may include a single control member 122. The control member 122 may be surrounded by a tubular member 124 and may be pushed or pulled relative to the tubular member 124 to deflect the distal end of catheter 10. A distal portion of the control member 122 may be fixed within the distal end of lumen 30, or another lumen of catheter 10, and the tubular member 124 may be fixed to a more proximal location within lumen 30. Again, a gap may be formed between the fixed portion of control member 122 and the fixed portion of tubular member 124 to control the deflection locations of the catheter 10. In one embodiment, the control member 122 may be pulled to deflect the catheter tip in one direction and pushed to deflect the catheter tip in the other, opposite direction.

[0079] In some embodiments, any of the steering mechanisms described above may include a balloon, which may be inflated to assist in urging the distal portion

of the catheter 10 and the distal electrodes 38 against the superior vena cava lateral wall. The balloon may be attached to a side of the catheter opposite the windows corresponding to distal electrodes 38. Upon inflation of the balloon, electrodes 38 may be urged towards a wall of the superior vena cava.

Catheter Embodiments

10 Catheter Window Arrangements

[0080] Referring to FIGs. 20A-20C, the windows 16, 18 of catheter 10 may have a variety of alternative configurations. For example, instead of being aligned as shown in FIG. 1, windows 16 may be offset from other windows 16, and windows 18 may be offset from other windows 18 with respect to a proximal-distal line 136 on the exterior surface of catheter 10 or with respect to a circumferential line 138 around the circumference of catheter 10. For example, windows 16 may be offset from each other if the more proximal window 16 does not lie on the same proximal-distal line 136 drawn through the center of the most distal window 16. Each window 18 of FIGs. 20B and 20C may be offset from other windows 18 with respect to circumferential lines 138 drawn through the center of windows 18. Embodiments of catheter 10 include windows 16, 18 with any configuration of offset and non-offset windows. As noted earlier, the set of windows 16 or rows of windows 16 may be offset from the set of windows 18 or rows of windows 18 with respect to a proximal-distal line 136.

[0081] In addition to electrode proximity to the nerves, electrode configuration relative to the nerve, as determined by windows 16, 18, may reduce the amount of electrical current required to stimulate nerve axons. Nerve axons may require lower activation currents when the electrodes and the direction of current flow are parallel to or along the nerve, thus producing a longitudinal transmembrane depolarization of sufficient magnitude to initiate action potentials. The direction the nerve courses is not exactly known and can vary from one individual to another.

[0082] Providing a plurality of different possible electrode configurations permits selection of sets of electrodes to be used for nerve stimulation in an individual. Using proximal electrodes 36 as an example, electrode pairs may be arranged in a straight line (e.g., along circumferential line 138 as in FIG. 20A), staggered (e.g., FIG. 20B), or angled (e.g., FIG. 20c) along a circumference of the catheter 10 to ensure that the nerves may be effectively stimulated. Referring to FIG. 20A, the circumferential line 138 may pass through (or over) the center of two electrodes, or the circumferential line 138 may pass through (or over) other portions of the two electrodes (e.g., the pair of electrodes may be slightly offset). Referring to FIG. 20B, staggered electrode pairs may be arranged such that the longitudinal distance (along a proximal-distal line parallel to the longitudinal axis of

catheter 10) between longitudinally adjacent electrodes (such as between electrodes 18a and 18b), is approximately equal to the longitudinal distances between other pairs of longitudinally adjacent electrodes, such as 18b and 18c. Referring to FIG. 20C, angled pairs of electrodes may be arranged such that planes passing through the center of the pairs of electrodes do not form a right angle with respect to the longitudinal axis of the catheter 10. Thus, the staggered electrode embodiment of FIG. 20B is a subset of the angled electrode embodiment of FIG. 20C, and the embodiment of FIG. 20A in which a circumferential line 138 passes through or over non-center portions of electrode pairs also may be considered to include angled electrode pairs. The electrode configuration may be varied along the catheter 10 to account for the anatomical differences found among different patients. Selecting appropriate electrode pairs can provide effective nerve stimulation despite these differences.

Pre-Shaped Catheter

[0083] FIG. 21 illustrates a medical device 50 having a pre-shaped catheter 10, with electrodes 36, 38 according to any embodiments disclosed herein. The pre-shaped catheter 10 may have arcuate, coiled, s-shaped, u-shaped, or any other pre-shaped portions. The pre-shaped catheter 10 may help ensure that the electrodes 36, 38 are in close contact with the vessel wall and thus closer to the phrenic nerve or other nerves, even in individuals where the right phrenic nerve may course more anteriorly or posteriorly than normal.

[0084] The pre-shaping of the catheter 10 may be accomplished, for example, by a stiffening element inserted within the catheter lumens, or pre-shaped during the manufacturing process. The pre-shaped catheter 10 may be flexible but may have some stiffness and may tend to return to its pre-shaped configuration. When inserted over a stiffer guidewire, the catheter 10 may straighten for the ease of insertion. When the guidewire is taken out, the catheter 10 may return to its pre-shaped form.

Catheter with Elongated Openings

[0085] Referring to FIGs. 22A-24B, in additional or alternative embodiments, the catheter 10 may include elongated openings 140 along the its exterior. The elongated openings 140 may connect the exterior of the catheter 10 to an interior lumen and may be referred to as slits or channels. As shown in FIGs. 22A-22B, the elongated openings 140 may extend along the full length of the catheter 10. Additionally or alternatively, as shown in FIGs. 23A-23B, the elongated openings 140 may extend along part of the length of the catheter 10. As shown in FIGs. 24A and 24B, the elongated openings 140 may additionally or alternatively be covered by a sleeve 142.

[0086] Threading electrode assemblies 32, 34 through the lumens of catheter 10 during assembly of medical device 50 may present challenges due to the length of

the lumens and their small diameter. In the embodiments of FIGs. 22A-24B, the electrode assemblies 32, 34 may be inserted into one or more lumens of catheter 10 through elongated openings 140. The ability to access the lumens of the catheter 10 from locations radially outside of the lumens, rather than from the proximal and distal ends of the lumens, may simplify installation of electrical leads 44 and other components of the medical device 50 during the manufacturing process.

[0087] The elongated openings 140 may be created during an initial extrusion or molding process to form catheter 10 or may be created during a later step. Some non-limiting examples of suitable polymers for the first extrusion or molding are: low and high-density thermoplastic polyurethanes such as polyester, polyether, and polycarbonate-based varieties; polycarbonate-based polyurethanes; and polyamides (nylon) and polyamide block copolymers (PEBA).

[0088] As shown in FIGs. 24A and 24B, after the electrode assemblies 32, 34 are installed in the lumens of catheter 10, an outer sleeve 142 may be threaded over the catheter 10 to secure the wire assemblies within the lumens. The outer sleeve 142 may be a polymeric tubular sleeve and may be formed by extrusion. The inner diameter of the outer sleeve 142 may be large enough to slide over the outside of the catheter 10 but may be small enough to retain the electrode assemblies 32, 34 within the lumens of the catheter 10 after it has been slid over the catheter 10. The outer sleeve 142 may extend in a proximal-distal direction along a desired length of the catheter 10.

[0089] The outer sleeve 142 may be formed of a thin, thermoplastic material such as, but not limited to, polyamide, polyether block amide, polyurethane, silicone rubber, nylon, polyethylene, fluorinated hydrocarbon polymers, etc. Examples of polymer materials suitable for use in the sleeve are commercially available under the trademarks PEBAX™ and PELLETHANE™.

[0090] The outer sleeve 142 may be thermally bonded or otherwise mechanically attached to the catheter 10 by any of a number of methods. In one such method, a tubular member, which may be formed by extrusion, may be placed over and around both the catheter 10 and the outer sleeve 142. The tubular member may be shrinkable to compress against the outer sleeve 142. For example, the tubular member may comprise heat shrink tubing. The heat shrink tubing can be formed of one or more layers depending upon the desired properties. As an example, heat-shrink tubing from Parker TexLoc (Fort Worth, TX) has two layers for electrical insulation. Tex-flour fluoropolymer double-shrink heat shrinkable tubing has an outer layer of PTFE heat shrink with an inner layer of FEP tubing. When using double shrink tubing, the catheter 10 may be encapsulated by the FEP tubing as the PTFE shrinks, melting the FEP and creating a waterproof protective covering which is desirable for a variety of applications including RF and electrical stimulation devices.

[0091] Thermal energy then may be applied to the heat

shrink tubing to compress the heat shrink tubing around the outer sleeve 142 and the catheter 10. Contraction of the heat shrink tubing provides a compressive force directed radially inward on the outer sleeve 142. The compressive force exerted by the heat shrink tubing helps secure the outer sleeve 142 to the catheter 10.

[0092] At the same time, or in a later step, thermal energy (e.g. RF heating, electromagnetic induction heating, etc.) may be applied to the assembly comprising the heat shrink tubing, the outer sleeve 142, and the catheter 10. The thermal energy may be sufficient to elevate the temperature of the assembly in order to induce bonding of the outer sleeve 142 to the catheter 10. The combination of the compressive force generated by the heat shrink tubing and the thermal energy heating the materials above their respective melt temperatures will serve to bond the outer sleeve 142 and the catheter 10 together. The thermal energy is typically not high enough to create a bond between the heat shrink tubing and the polymeric sleeve nor is it high enough to damage the integrity of the catheter assembly.

[0093] The heat shrink tubing may then be removed from the assembly comprising the catheter 10 (which is received inside the outer sleeve 142). A slit, notch, perforations, or other weakened regions may be used to assist with the removal of the heat shrink tubing from the assembly. In some cases, the shrink tubing may be constructed of a biocompatible material such as EPTFE and can be left on the catheter assembly.

[0094] Within lumens of catheter 10 according to any embodiments disclosed herein, it may be desirable to insert a support structure, such as a polytetrafluoroethylene (e.g., Teflon) coated mandrel, which may provide interior support to maintain the structure of the catheter 10 and preserve the patency of the longitudinal lumen throughout the manufacturing process. The support structure can later be removed by pulling it through either the distal or proximal openings in the lumen. In some cases the support structure can be stretched and elongated, thereby reducing its cross-sectional area, prior to removal.

[0095] One or more outer sleeves 142 of different materials, thicknesses, or material properties (e.g. durometer) can be used at various locations along the length of catheter 10 to alter various physical properties (e.g. stiffness, torqueability, friction, etc.) at specific locations along the length of the finished catheter. For example, a flexible sleeve 142 could be utilized at the distal portion of the catheter 10 to allow the tip of the catheter 10 to more easily track along a guidewire. A more rigid sleeve 142 could be used at the proximal portion of the catheter 10 to allow for more pushability or torqueability when grasping the distal end of the catheter 10. Adjacent sleeves 142 could be butt-welded or otherwise coupled end-to-end during the final forming process. Lap-joints or scarf joints may optionally be used to form a smoother transition between adjacent sleeves 142.

[0096] Other elements or structures may be incorpo-

rated into the catheter 10 construction using the assembly method described above. As one example, to help provide a desirable shape or contour to the distal end of the catheter 10, a shaping element may be inserted into one of the elongated openings 140, or into an enclosed lumen, at a desired location along the first extrusion. The shaping element may be formable or pre-formed to impart a desired configuration (e.g. a desired curvature) to the catheter 10. The shaping element may be pre-formed or formed to cause the catheter 10 to curve in a plane having a desired angular relationship, such as, for example, to aid in positioning electrodes 36, 38 of the medical device 50.

[0097] The shaping element may be resiliently flexible. In some embodiments, the shaping element may comprise a predetermined length of e.g. nitinol wire, ribbon, spring, etc. In some embodiments, the shaping element may comprise a temperature-dependent shape-memory material such as a shape-memory alloy. In some embodiments, the shaping element may be constructed to assume a desired shape after the catheter 10 has entered the body of a patient. For example, body heat may cause a shape-memory shaping element to change to a desired shaped configuration, or an external source of energy (e.g. an electrical current) may be applied to cause a shape change of a shaping element by a thermal or other mechanism. In some embodiments the shaping element becomes more curved upon actuation.

Alternative Lead Embodiments

[0098] Referring to FIGs. 25A-26H, in an additional or alternative embodiment, one or all of the electrode leads 44 may be embedded in a flexible ribbon cable 144. The ribbon cable 144 may include multiple insulated leads 44 connected along their lengths to form a single planar structure. The planar structure may be flexible to form other shapes. Similar to other leads 44 described herein, the leads 44 of the ribbon cable 144 may include an elongated conductive member 45 surrounded by a layer of non-conductive material 46, such as insulation.

[0099] In the embodiment of FIGs. 25A-25C, the ribbon cable 144 may be closed as a flexible cylinder (e.g., formed around a mandrel and the approximated ribbon edges fixed with adhesive along the length). This design may allow any of the leads 44 to be deinsulated at a point along the catheter length and attached to an electrode 36, 38, such as, for example, a flexible foil electrode or an electrode formed according to any of the embodiments described herein. Two proximal electrodes 36 of the ribbon cable embodiment may be seen in the cross-section of FIG. 25C and will be described in greater detail below. The exterior elongated tubular member of catheter 10 may be formed around the ribbon cable 144 using the heat shrink method previously described to form a smooth electrically-insulating wall. Individual electrodes 36, 38 may be exposed through windows 18, 16 formed in the catheter 10, similar to other embodiments.

[0100] An advantage of the embodiment of FIGs. 25A-25C is that a larger portion of the entire catheter 10 cross-section may be available for guide wire and/or fluid lumen(s). As shown in FIG. 25C, the ribbon cable 144 may be supported by a support catheter 146, which may include the lumens described in connection with other embodiments or may include the guidewire lumen 28 and the delivery lumen 148 shown in FIG. 25C. Another advantage of the embodiment of FIGs. 25A-25C is its simplicity and ease of fabrication.

[0101] FIGs. 26A-26H illustrate use of ribbon cable 144 in greater detail. Referring to FIG. 26B, proximal electrodes 36 may contact leads 44 within ribbon cable 144. Referring to FIG. 26C, distal electrodes 38 may contact different leads 44 within ribbon cable 144. The ribbon cable 144 may be held temporarily in a cylindrical form with a weak adhesive (such as an adhesive that dissolves in contact with blood, such as e.g., sucrose). As shown in FIGs. 26D and 26E, a guide wire lumen 30 or other lumens may be permanently attached to the ribbon cable 144 (for example using a strong biocompatible adhesive). The ribbon cable 144 and any support catheter 146 may be wrapped in a thin electrically-insulating covering to form catheter 10 (for example by sliding the assembly into a sleeve 142 and using the previously described heat-shrink method or the like). A seam may be opened (e.g. using a knife or laser) directly over the ribbon cable 144 seam to transition the ribbon cable 144 from the closed position shown in FIG. 26D to the open position shown in FIG. 26E. An adhesive may be used to transition the ribbon cable 144 from the position shown in FIG. 26E to the position shown in FIG. 26D. As in other embodiments, windows 16, 18 may be formed in the exterior covering of the catheter 10 to reveal electrodes 36, 38 at their desired locations.

[0102] A catheter 10 having a ribbon cable 144 may be introduced into a blood vessel of the body of a subject in its closed configuration (see FIG. 26D). Once inside the vessel, the adhesive may dissolve in a matter of several minutes and the ribbon cable 144 may be free to deploy into a nearly flat configuration, which may be its preferred state due to the natural elasticity of the ribbon cable 144. Optionally, two control members 150, such as Nitinol or other springy metal wires, or pull wires, may be embedded along the edges of the ribbon cable 144, and their natural elasticity and/or operation may contribute to the desired open configuration shown in FIG. 26E.

[0103] Referring to FIG. 26F, the natural elasticity of the ribbon cable 144 and/or the control members 150 may contribute to urge the ribbon cable 144 toward the vessel wall in such a way that the electrodes are proximate to the vessel wall in the vicinity of a target nerve, such as right phrenic nerve 58. With this design, one or more of the catheter electrodes 36, 38 exposed through windows 18, 16 is likely to be in very close proximity to the target nerve and may afford highly selective recruitment of the nerve with very low current or charge delivery. Furthermore, this design provides effective insulation of

the electrodes 36, 38 from the blood in the vessel, thus minimizing current spread to unwanted regions and maximizing recruitment selectivity of the target nerve.

[0104] FIG. 26G is an isometric view of a catheter 10 having a ribbon cable 144 intended for deployment inside a vessel. In this embodiment, the proximal portion of the catheter 10 may have a near-circular, tubular cross-section in regions where the ribbon cable 144 is adhered with permanent adhesive that will not dissolve in blood. In contrast, the distal portions of the catheter 10 are shown in FIG. 26G to have opened into the open ribbon cable configuration where the attachment of ribbon edges was temporary and the adhesive was dissolved once inside the blood vessel lumen. It is further seen in FIG. 26G that the distal portion of the catheter having a ribbon cable 144 may naturally adopt a corkscrew (or "helical") configuration, the dimensions of which are determined by the properties of the control members 150 embedded along the ribbon cable edges. One configuration may be a corkscrew section of approximately 20 mm diameter and approximately 30 mm length. Such a configuration may ensure that some of the distal wires are in close proximity with, for example, the target right phrenic nerve 58 coursing on the outside of the superior vena cava 64 (not shown in Fig. 24G but shown in Fig. 21).

[0105] FIG. 26H illustrates a control member 152 that can be used to restrict the total length of the distal coiled portion of the catheter 10 having a ribbon cable 144. The control member 152 may be attached to a point near the distal end of the catheter 10 and may run freely through a lumen inside the proximal portion of the catheter, crossing to outside the patient where the proximal end of the pull wire can be controlled by the practitioner. By pulling on the control member 152, the catheter 10 having a ribbon cable 144 may be controlled to open maximally inside the SVC, ensuring that the ribbon surface is completely deployed against the vessel wall.

Medical Device Having a Barometer

[0106] The medical device 50 may include barometric correction that allows the device 50 to operate at different altitudes, since a patient receiving electrical stimulation phrenic-nerve pacing of the diaphragm may need to breathe a constant oxygen supply, but the density of air declines with altitude. The natural correction is for the patient to breathe more deeply and/or more rapidly to compensate. The medical device 50 or the catheter 10 may include a gauge (e.g. a barometer) that measures atmospheric pressure in order to compensate for altitude changes. High altitude performance is especially valuable to the military, any other agency transporting injured people (ski resorts, mountain climbers) and more generally, any patient who requires pacing and needs to travel in an aircraft.

Medical Device Equipped with Electronic Chip

[0107] The medical device 50 or the catheter 10 may be equipped with an electronic chip that stores information about the catheter 10 and/or its usage. The chip may be, for example, provided in a hub of the catheter 10. In one embodiment, when the catheter 10 is coupled to a controller, the controller may read the chip and send signals to the electrodes 36, 38 only if the chip has the correct encryption and/or makes a correct response etc. The chip may store information such as one or a plurality of the catheter serial number; size (length and/or diameter); lot number; batch number; date manufactured; electrode arrangement; electrode interconnection information (pin-outs for a connector connected to the electrodes by conductors in the catheter); etc. The controller may accept algorithm upgrades that only apply to certain serial numbers or catheter types determined with reference to the information stored in the chip.

Other Alternative Embodiments and Interpretation of Terms

[0108] As noted earlier, any of the components and features of any of the embodiments disclosed herein may be combined and used in any logical combinations with any of the other components and features disclosed herein. However, for the sake of example, some ways in which the described example embodiments may be varied include:

- different numbers of electrodes;
- different electrode configurations;
- different electrode fixing (crimp, adhesive, microwave, etc.);
- different electrode shape (round, oval, circular, rectangular, etc.);
- different electrode material;
- different electrode surface areas;
- different electrode spacing;
- different number or shapes of lumens;
- different window shape/dimensions;
- different catheter profile (e.g., +/- 9Fr);
- different catheter length; and/or
- different steering mechanism.

[0109] Unless the context clearly requires otherwise, throughout the description and the claims:

- "comprise," "comprising," and the like are to be construed in an inclusive sense, as opposed to an exclusive or exhaustive sense; that is to say, in the sense of "including, but not limited to";
- "connected," "coupled," or any variant thereof, means any connection or coupling, either direct or indirect, between two or more elements; the coupling or connection between the elements can be physical, logical, or a combination thereof;

- "herein," "above," "below," and words of similar import, when used to describe this specification, shall refer to this specification as a whole, and not to any particular portions of this specification;
- "or," in reference to a list of two or more items, covers all of the following interpretations of the word: any of the items in the list, all of the items in the list, and any combination of the items in the list; and
- the singular forms "a," "an," and "the" also include the meaning of any appropriate plural forms.

[0110] Words that indicate directions such as "vertical," "transverse," "horizontal," "upward," "downward," "forward," "backward," "inward," "outward," "left," "right," "front," "back," "top," "bottom," "below," "above," "under," and the like, used in this description and any accompanying claims (where present), depend on the specific orientation of the apparatus described and illustrated. The subject matter described herein may assume various alternative orientations. Accordingly, these directional terms are not strictly defined and should not be interpreted narrowly.

[0111] Specific examples of systems, methods and apparatus have been described herein for purposes of illustration. These are only examples. The technology provided herein can be applied to systems other than the example systems described above. Many alterations, modifications, additions, omissions, and permutations are possible within the practice of this invention. This invention includes variations on described embodiments that would be apparent to the skilled addressee, including variations obtained by: replacing features, elements and/or acts with equivalent features, elements and/or acts; mixing and matching of features, elements and/or acts from different embodiments; combining features, elements and/or acts from embodiments as described herein with features, elements and/or acts of other technology; and/or omitting combining features, elements and/or acts from described embodiments.

[0112] It is therefore intended that the following appended claims and claims hereafter introduced are interpreted to include all such modifications, permutations, additions, omissions, and sub-combinations as may reasonably be inferred. The scope of the claims should not be limited by the preferred embodiments set forth in the examples, but should be given the broadest interpretation consistent with the description as a whole.

Claims

1. A catheter (10), comprising:
 - an elongated member;
 - a plurality of proximal windows (18) on the catheter (10) positioned along a first longitudinal portion of the elongated member;
 - a proximal set of electrodes comprising a plu-

rality of proximal electrodes (36) aligned with the proximal windows (18) to at least one of emit or receive electrical energy to or from an exterior of the elongated member; and

a plurality of distal windows (16) on the catheter (10) positioned along a second longitudinal portion of the elongated member;

a distal set of electrodes distal to the proximal set of electrodes, the distal set of electrodes comprising a plurality of distal electrodes (38) aligned with the distal windows (16) to at least one of emit or receive electrical energy to or from an exterior of the elongated member;

wherein the proximal and distal sets of electrodes are positioned such that the proximal set of electrodes is configured to stimulate a patient's left phrenic nerve and the distal set of electrodes is configured to stimulate the patient's right phrenic nerve,

characterized in that

the plurality of proximal windows (18) are positioned such that the proximal electrodes (36) at least one of emit or receive electrical energy to or from an exterior of the elongated member along only a portion of a circumference of the first longitudinal portion,

the plurality of distal windows (16) are positioned such that the distal electrodes (38) at least one of emit or receive electrical energy to or from an exterior of the elongated member along only a portion of a circumference of the second longitudinal portion,

wherein a row of the plurality of proximal electrodes (36) is exposed along a first line at a surface of the elongated member and parallel to a longitudinal axis (A-A) of the catheter (10),

wherein a row of the plurality of distal electrodes (38) is exposed along a second line at the surface of the elongated member and parallel to a longitudinal axis (A-A) of the catheter (10), and

wherein the first longitudinal portion of the elongated member is without electrodes exposed along the second line, and the second longitudinal portion of the elongated member is without electrodes exposed along the first line.

2. The catheter (10) of claim 1, wherein each of the proximal and distal electrodes includes a conductive tubular member.
3. The catheter (10) of claim 1 or 2, wherein each of the proximal and distal electrodes includes an arcuate member having an inner wall and an outer wall.
4. The catheter (10) of any one of claims 1 to 3, wherein each of the proximal and distal electrodes is electrically coupled to an elongated conductive member that extends proximally from the electrode.

5. The catheter (10) of any one of claim 1 to 3, wherein the proximal and distal electrodes are electrically coupled to the distal ends of the elongated conductive members.

6. The catheter (10) of any one of claims 1 to 5, wherein at least one of the proximal and distal electrodes includes conductive ink printed on an exterior of the elongated member.

7. The catheter (10) of any one of claims 1 to 6, wherein the elongated member of the catheter includes a first lumen (20), a second lumen (22), a third lumen (24), and a fourth lumen (26); a first plurality of the proximal set of electrodes is supported by a first elongated tubular member within the first lumen (20); a second plurality of the proximal set of electrodes is supported by a second elongated tubular member within the second lumen (22); a first plurality of the distal set of electrodes is supported by a third elongated tubular member within the third lumen (24); and a second plurality of the distal set of electrodes is supported by a fourth elongated tubular member within the fourth lumen (26).

8. The catheter (10) of any one of claims 1 to 7, wherein at least one of the proximal and distal electrodes includes a conductive member fixed to an exterior of the elongated member.

9. The catheter (10) of any one of claims 1 to 8, further comprising a steering mechanism adapted to deflect a distal end of the elongated member.

10. The catheter (10) of any one of claims 1 to 9, further comprising a ribbon cable (144) having a plurality of elongated conductive members.

11. The catheter (10) of any one of claims 1 to 10, wherein a proximal portion of the catheter (10) includes a first cross-sectional shape, and a distal portion of the catheter includes a second cross-sectional shape different than the first cross-sectional shape.

12. The catheter (10) of any one of claims 1 to 11, wherein the proximal set of electrodes is fixed relative to a lumen of the catheter (10) and the distal set of electrodes is fixed relative to a lumen of the catheter (10).

13. The catheter (10) of any one of claims 1 to 12, wherein the proximal set of electrode includes two proximal electrode assemblies (32, 36) within first lumens of the catheter (10), and the distal set of electrodes includes two distal electrode assemblies (34, 38) within second lumens of the catheter (10).

14. The catheter (10) of any one of claims 1 to 13, wherein the first longitudinal portion of the elongated mem-

ber is without stimulation electrodes exposed along the second line, and the second longitudinal portion of the elongated member is without stimulation electrodes exposed along the first line.

15. The catheter (10) of any one of claims 1 to 14, wherein each of the plurality of proximal electrodes (36) and the plurality of distal electrodes (38) is arranged in two rows extending in a proximal-distal direction along the catheter (10), and lines parallel to the longitudinal axis (A-A) of the catheter (10) and passing through the two rows of the plurality of distal electrodes (38) do not pass through the two rows of the plurality of proximal electrodes (36).

Patentansprüche

1. Katheter (10), umfassend:

ein langgestrecktes Element,
 eine Vielzahl von proximalen Fenstern (18) auf dem Katheter (10), die entlang eines ersten Längsabschnitts des langgestreckten Elements angeordnet sind,
 einen proximalen Satz von Elektroden, der eine Vielzahl von mit den proximalen Fenstern (18) ausgerichteten proximalen Elektroden (36) umfasst, um elektrische Energie an eine Außenseite des langgestreckten Elements zumindest zu senden oder von dieser zu empfangen, und eine Vielzahl von distalen Fenstern (16) auf dem Katheter (10), die entlang eines zweiten Längsabschnitts des langgestreckten Elements angeordnet sind,
 einen distalen Satz von Elektroden, der distal zu dem proximalen Satz von Elektroden ist, wobei der distale Satz von Elektroden eine Vielzahl von mit den distalen Fenstern (16) ausgerichteten distalen Elektroden (38) umfasst, um elektrische Energie an eine Außenseite des langgestreckten Elements zumindest zu senden oder von dieser zu empfangen,
 wobei der proximale und der distale Satz von Elektroden derart positioniert sind, dass der proximale Satz von Elektroden so konfiguriert ist, dass er den linken Nervus phrenicus eines Patienten stimuliert, und der distale Satz von Elektroden so konfiguriert ist, dass er den rechten Nervus phrenicus des Patienten stimuliert,
dadurch gekennzeichnet, dass
 die Vielzahl von proximalen Fenstern (18) derart positioniert sind, dass die proximalen Elektroden (36) elektrische Energie an eine Außenseite des langgestreckten Elements entlang nur eines Teils eines Umfangs des ersten Längsabschnitts zumindest senden oder von dieser empfangen,

die Vielzahl von distalen Fenstern (16) derart positioniert sind, dass die distalen Elektroden (38) elektrische Energie an eine Außenseite des langgestreckten Elements entlang nur eines Teils eines Umfangs des zweiten Längsabschnitts zumindest senden oder von dieser empfangen,
 wobei eine Reihe der Vielzahl von proximalen Elektroden (36) entlang einer ersten Linie an einer Oberfläche des langgestreckten Elements und parallel zu einer Längsachse (A-A) des Katheters (10) freiliegt,
 wobei eine Reihe der Vielzahl von distalen Elektroden (38) entlang einer zweiten Linie an einer Oberfläche des langgestreckten Elements und parallel zu einer Längsachse (A-A) des Katheters (10) freiliegt, und
 wobei der erste Längsabschnitt des langgestreckten Elements ohne Elektroden ist, die entlang der zweiten Linie freiliegen, und der zweite Längsabschnitt des langgestreckten Elements ohne Elektroden ist, die entlang der ersten Linie freiliegen.

2. Katheter (10) nach Anspruch 1, wobei jede der proximalen und distalen Elektroden ein leitendes röhrenförmiges Element umfasst.
3. Katheter (10) nach Anspruch 1 oder 2, wobei jede der proximalen und distalen Elektroden ein bogenförmiges Element, das eine Innenwand und eine Außenwand aufweist, umfasst.
4. Katheter (10) nach einem der Ansprüche 1 bis 3, wobei jede der proximalen und distalen Elektroden elektrisch mit einem langgestreckten leitenden Element, das sich proximal von der Elektrode erstreckt, gekoppelt ist.
5. Katheter (10) nach einem der Ansprüche 1 bis 3, wobei die proximalen und distalen Elektroden elektrisch mit den distalen Enden der langgestreckten leitenden Elemente gekoppelt sind.
6. Katheter (10) nach einem der Ansprüche 1 bis 5, wobei mindestens eine der proximalen und distalen Elektroden leitfähige Tinte umfasst, die auf eine Außenseite des langgestreckten Elements gedruckt ist.
7. Katheter (10) nach einem der Ansprüche 1 bis 6, wobei das langgestreckte Element des Katheters ein erstes Lumen (20), ein zweites Lumen (22), ein drittes Lumen (24) und ein viertes Lumen (26) umfasst, wobei eine erste Vielzahl des proximalen Satzes von Elektroden von einem ersten langgestreckten röhrenförmigen Element innerhalb des ersten Lumens (20) getragen wird, eine zweite Vielzahl des proximalen Satzes von Elektroden durch ein zweites lang-

gestrecktes röhrenförmiges Element innerhalb des zweiten Lumens (22) getragen wird, eine erste Vielzahl des distalen Satzes von Elektroden durch ein drittes langgestrecktes röhrenförmiges Element innerhalb des dritten Lumens (24) getragen wird, und eine zweite Vielzahl des distalen Satzes von Elektroden durch ein viertes langgestrecktes röhrenförmiges Element innerhalb des vierten Lumens (26) getragen wird.

8. Katheter (10) nach einem der Ansprüche 1 bis 7, wobei mindestens eine der proximalen und distalen Elektroden ein leitfähiges Element umfasst, das an einer Außenseite des langgestreckten Elements befestigt ist.
9. Katheter (10) nach einem der Ansprüche 1 bis 8, ferner umfassend einen Lenkungsmechanismus, der eingerichtet ist, ein distales Ende des langgestreckten Elements abzulenken.
10. Katheter (10) nach einem der Ansprüche 1 bis 9, ferner umfassend ein Flachbandkabel (144), das eine Vielzahl von langgestreckten leitfähigen Elementen aufweist.
11. Katheter (10) nach einem der Ansprüche 1 bis 10, wobei ein proximaler Abschnitt des Katheters (10) eine erste Querschnittsform umfasst und ein distaler Abschnitt des Katheters eine zweite Querschnittsform umfasst, die sich von der ersten Querschnittsform unterscheidet.
12. Katheter (10) nach einem der Ansprüche 1 bis 11, wobei der proximale Satz von Elektroden relativ zu einem Lumen des Katheters (10) fixiert ist und der distale Satz von Elektroden relativ zu einem Lumen des Katheters (10) fixiert ist.
13. Katheter (10) nach einem der Ansprüche 1 bis 12, wobei der proximale Satz von Elektroden zwei proximale Elektrodenanordnungen (32, 36) innerhalb erster Lumen des Katheters (10) umfasst und der distale Satz von Elektroden zwei distale Elektrodenanordnungen (34, 38) innerhalb zweiter Lumen des Katheters (10) umfasst.
14. Katheter (10) nach einem der Ansprüche 1 bis 13, wobei der erste Längsabschnitt des langgestreckten Elements ohne Stimulationselektroden ist, die entlang der zweiten Linie freiliegen, und der zweite Längsabschnitt des langgestreckten Elements ohne Stimulationselektroden ist, die entlang der ersten Linie freiliegen.
15. Katheter (10) nach einem der Ansprüche 1 bis 14, wobei jede der Vielzahl von proximalen Elektroden (36) und der Vielzahl von distalen Elektroden (38) in

zwei Reihen angeordnet ist, die sich in einer proximal-distalen Richtung entlang des Katheters (10) erstrecken, und wobei Linien, die parallel zu der Längsachse (A-A) des Katheters (10) verlaufen und durch die zwei Reihen der Vielzahl von distalen Elektroden (38) verlaufen, nicht durch die zwei Reihen der Vielzahl von proximalen Elektroden (36) verlaufen.

10 Revendications

1. Cathéter (10) comprenant :

un élément allongé ;

une pluralité de fenêtres proximales (18) sur le cathéter (10) positionnées le long d'une première partie longitudinale de l'élément allongé ;

un ensemble proximal d'électrodes comprenant une pluralité d'électrodes proximales (36) alignées avec les fenêtres proximales (18) pour réaliser au moins l'une parmi l'émission ou la réception de l'énergie électrique vers ou depuis un extérieur de l'élément allongé ; et

une pluralité de fenêtres distales (16) sur le cathéter (10) positionnées le long d'une seconde partie longitudinale de l'élément allongé ;

un ensemble distal d'électrodes à distance de l'ensemble proximal d'électrodes, l'ensemble distal d'électrodes comprenant une pluralité d'électrodes distales (38) alignées avec les fenêtres distales (16) pour réaliser au moins l'une parmi l'émission ou la réception de l'énergie électrique vers ou depuis un extérieur de l'élément allongé ;

dans lequel les ensembles proximal et distal d'électrodes sont positionnées de sorte que l'ensemble proximal d'électrodes est configuré pour stimuler le nerf phrénique gauche d'un patient et l'ensemble distal d'électrodes est configuré pour stimuler le nerf phrénique droit du patient,

caractérisé en ce que

la pluralité de fenêtres proximales (18) sont positionnées de sorte que les électrodes proximales (36) réalisent au moins l'une par l'émission ou la réception de l'énergie électrique vers ou depuis un extérieur de l'élément allongé uniquement le long d'une partie d'une circonférence de la première partie longitudinale,

la pluralité de fenêtres distales (16) sont positionnées de sorte que les électrodes distales (38) réalisent au moins l'une parmi l'émission ou la réception de l'énergie électrique vers ou depuis un extérieur de l'élément allongé uniquement le long d'une partie d'une circonférence de la seconde partie longitudinale,

dans lequel une rangée de la pluralité d'électrodes proximales (36) est exposée le long d'une première ligne au niveau d'une surface de l'élé-

- ment allongé et parallèle à un axe longitudinal (A-A) du cathéter (10), dans lequel une rangée de la pluralité d'électrodes distales (38) est exposée le long d'une seconde ligne au niveau de la surface de l'élément allongé et parallèle à un axe longitudinal (A-A) du cathéter (10), et dans lequel la première partie longitudinale de l'élément allongé est sans électrodes exposées le long de la seconde ligne, et la seconde partie longitudinale de l'élément allongé est sans électrodes exposées le long de la première ligne.
2. Cathéter (10) selon la revendication 1, dans lequel chacune des électrodes proximales et distales comprend un élément tubulaire conducteur.
 3. Cathéter (10) selon la revendication 1 ou 2, dans lequel chacune des électrodes proximales et distales comprend un élément arqué ayant une paroi interne et une paroi externe.
 4. Cathéter (10) selon l'une quelconque des revendications 1 à 3, dans lequel chacune des électrodes proximales et distales est électriquement couplée à un élément conducteur allongé qui s'étend de manière proximale à partir de l'électrode.
 5. Cathéter (10) selon l'une quelconque des revendications 1 à 3, dans lequel les électrodes proximales et distales sont électriquement couplées aux extrémités distales des éléments conducteurs allongés.
 6. Cathéter (10) selon l'une quelconque des revendications 1 à 5, dans lequel au moins l'une des électrodes proximales et distales comprend une encre conductrice imprimée sur un extérieur de l'élément allongé.
 7. Cathéter (10) selon l'une quelconque des revendications 1 à 6, dans lequel l'élément allongé du cathéter comprend une première lumière (20), une deuxième lumière (22), une troisième lumière (24) et une quatrième lumière (26) ; une première pluralité de l'ensemble proximal d'électrodes est supportée par un premier élément tubulaire allongé à l'intérieur de la première lumière (20) ; une seconde pluralité de l'ensemble proximal d'électrodes est supportée par un deuxième élément tubulaire allongé à l'intérieur de la deuxième lumière (22) ; une première pluralité de l'ensemble distal d'électrodes est supportée par un troisième élément tubulaire allongé à l'intérieur de la troisième lumière (24) ; et une seconde pluralité de l'ensemble distal d'électrodes est supportée par un quatrième élément tubulaire allongé à l'intérieur de la quatrième lumière (26).
 8. Cathéter (10) selon l'une quelconque des revendications 1 à 7, dans lequel au moins l'une des électrodes proximales et distales comprend un élément conducteur fixé sur un extérieur de l'élément allongé.
 9. Cathéter (10) selon l'une quelconque des revendications 1 à 8, comprenant en outre un mécanisme de direction adapté pour dévier une extrémité distale de l'élément allongé.
 10. Cathéter (10) selon l'une quelconque des revendications 1 à 9, comprenant en outre un câble ruban (144) ayant une pluralité d'éléments conducteurs allongés.
 11. Cathéter (10) selon l'une quelconque des revendications 1 à 10, dans lequel une partie proximale du cathéter (10) comprend une première forme transversale, et une partie distale du cathéter comprend une seconde forme transversale différente de la première forme transversale.
 12. Cathéter (10) selon l'une quelconque des revendications 1 à 11, dans lequel l'ensemble proximal d'électrodes est fixe par rapport à une lumière du cathéter (10) et l'ensemble distal d'électrodes est fixe par rapport à une lumière du cathéter (10).
 13. Cathéter (10) selon l'une quelconque des revendications 1 à 12, dans lequel l'ensemble proximal d'électrodes comprend deux ensembles d'électrodes proximales (32, 36) à l'intérieur des premières lumières du cathéter (10), et l'ensemble distal d'électrodes comprend deux ensembles d'électrodes distales (34, 38) à l'intérieur des deuxièmes lumières du cathéter (10).
 14. Cathéter (10) selon l'une quelconque des revendications 1 à 13, dans lequel la première partie longitudinale de l'élément allongé est sans électrodes de stimulation exposées le long de la seconde ligne, et la seconde partie longitudinale de l'élément allongé est sans électrodes de stimulation exposées le long de la première ligne.
 15. Cathéter (10) selon l'une quelconque des revendications 1 à 14, dans lequel chacune de la pluralité d'électrodes proximales (36) et de la pluralité d'électrodes distales (38) est agencée dans deux rangées s'étendant dans une direction proximale - distale le long du cathéter (10) et des lignes parallèles à l'axe longitudinal (A-A) du cathéter (10) et passant par les deux rangées de la pluralité d'électrodes distales (38) ne passent pas par les deux rangées de la pluralité d'électrodes proximales (36).




FIG. 1A



FIG. 1B




FIG. 1C




FIG. 2




FIG. 3A




FIG. 3B




FIG. 3C




FIG. 3D




FIG. 4A




FIG. 4B




FIG. 4C




FIG. 4D




FIG. 5




FIG. 6A








FIG. 6B






FIG. 8A




FIG. 8B




FIG. 8C




FIG. 8D




FIG. 9A




FIG. 9B




FIG. 9C




FIG. 9D




FIG. 9E






FIG. 10C




FIG. 10D




FIG. 10E




FIG. 11A




FIG. 11B




FIG. 11C




FIG. 11D




FIG. 11E




FIG. 11F




FIG. 12A




FIG. 12B




FIG. 12C




FIG. 12D




FIG. 12E




FIG. 12F




FIG. 12G




FIG. 12H




FIG. 12I




FIG. 12J




FIG. 12K




FIG. 13A




FIG. 13B




FIG. 13C




FIG. 13D




FIG. 13E




FIG. 13F




FIG. 13G




FIG. 13H




FIG. 13I




FIG. 13J




FIG. 13K




FIG. 14




FIG. 15A




FIG. 15B





















FIG. 15C












FIG. 20A




FIG. 20B



FIG. 20C






FIG. 21








FIG. 24A










FIG. 24B








FIG. 26D




FIG. 26E




FIG. 26F




FIG. 26G




FIG. 26H

REFERENCES CITED IN THE DESCRIPTION

This list of references cited by the applicant is for the reader's convenience only. It does not form part of the European patent document. Even though great care has been taken in compiling the references, errors or omissions cannot be excluded and the EPO disclaims all liability in this regard.

Patent documents cited in the description

- US 20130116743 A1 [0006]
- US 20100036451 A1 [0006]

Non-patent literature cited in the description

- **LEVINE et al.** *New England Journal of Medicine*, 2008, vol. 358, 1327-1335 [0005]

专利名称(译)	通过经血管神经刺激辅助呼吸的装置和方法		
公开(公告)号	EP3071285A1	公开(公告)日	2016-09-28
申请号	EP2014864542	申请日	2014-11-21
申请(专利权)人(译)	西门菲沙大学		
当前申请(专利权)人(译)	西门菲沙大学		
[标]发明人	THAKKAR VIRAL HOFFER JOAQUIN ANDRES TRAN BAO DUNG EVANS DOUGLAS NASH JOHN REYNOLDS STEVEN CAMPBELL		
发明人	THAKKAR, VIRAL HOFFER, JOAQUIN ANDRES TRAN, BAO DUNG EVANS, DOUGLAS NASH, JOHN REYNOLDS, STEVEN CAMPBELL		
IPC分类号	A61M25/14 A61N1/04 A61N1/36 A61B5/00 A61B5/0245 A61B5/042 A61N1/05		
CPC分类号	A61B5/0245 A61B5/0422 A61B5/6852 A61B2562/043 A61N1/05 A61N1/0551 A61N1/3601 A61N1/3611 A61N1/36185 A61M25/00 A61M25/0029 A61M25/0147 A61M2025/0034		
优先权	61/907993 2013-11-22 US		
其他公开文献	EP3071285A4 EP3071285B1		
外部链接	Espacenet		

摘要(译)

导管可包括用于经血管神经刺激的电极。电极可以位于导管的内腔中并且与导管的外壁中的孔对准。电极可产生聚焦电场以刺激一根或多根神经。在一个实施例中，导管可以包括一组近端电极和一组远端电极，并且近端电极可以刺激患者的左神经，而远端电极可以刺激患者的右神经。