



(11) **EP 1 857 045 B1**

(12) **EUROPEAN PATENT SPECIFICATION**

(45) Date of publication and mention
of the grant of the patent:
26.01.2011 Bulletin 2011/04

(51) Int Cl.:
A61B 5/00 (2006.01)

(21) Application number: **07107810.9**

(22) Date of filing: **09.05.2007**

(54) **Portable body fat measurement device, method and medium, using side-view light sources**

Tragbares Körperfett-Messgerät, -verfahren und medium mit Seitenansicht-Lichtquellen

Dispositif portable de mesure des graisses corporelles, procédé et support utilisant des sources lumineuses latérales

(84) Designated Contracting States:
AT DE FR GB NL

(30) Priority: **19.05.2006 KR 20060044953**

(43) Date of publication of application:
21.11.2007 Bulletin 2007/47

(73) Proprietor: **Samsung Electronics Co., Ltd.**
Suwon-si
Gyeonggi-do 443-742 (KR)

(72) Inventors:
• **Hwang, In Duk**
Jangan-gu, Suwon-si
440-705, Gyeonggi-do (KR)

• **Shin, Kun Soo**
Bundang-dong, Bundang-gu, Seongnam-si
463-748 Gyeonggi-do (KR)

(74) Representative: **D'Halleweyn, Nele Veerle Trees**
Gertrudis
Arnold & Siedsma
Sweelinckplein 1
2517 GK The Hague (NL)

(56) References cited:
EP-A- 1 396 227 EP-A- 1 520 514
EP-A- 1 634 533 EP-A1- 0 819 970
EP-A2- 1 852 059 WO-A-01/28416
US-B1- 6 285 904

Note: Within nine months of the publication of the mention of the grant of the European patent in the European Patent Bulletin, any person may give notice to the European Patent Office of opposition to that patent, in accordance with the Implementing Regulations. Notice of opposition shall not be deemed to have been filed until the opposition fee has been paid. (Art. 99(1) European Patent Convention).

EP 1 857 045 B1

Description

[0001] One or more embodiments of the present invention relate to a portable body fat measurement device according to the preamble of claim 1, method, according to the preamble of claim 12 and medium according to the preamble of claim 16, using side-view light sources and an optical sensor module, and more particularly to a portable body fat measurement device, method and medium which can irradiate an output light from the side-view light sources to a measurement point for body fat measurement, and calculate body fat information by using a light scattered at the measurement point.

[0002] EP 1 634 533 discloses an optical fat measuring apparatus wherein at least one of the light source section and the light receiving section is arranged plurally.

[0003] EP 1 396 227 discloses a similar embodiment with a light source constituted by a measuring light source element and a correcting light source element.

[0004] Maintaining health and achieving beauty is a priority for many consumers. Accordingly, there is currently a trend to seek a healthy lifestyle. The amount of body fat is one criteria used to estimate an individual's health. There are various methods of measuring the amount of body fat.

[0005] Methods for measuring body fat ratio include a body average density measurement employing underwater weighing, a skinfold test measuring the thickness of fat at a specific point of the body, applying a weak electrical current to the body and measuring the body's impedance, and using a table of values to measure the body fat ratio based on waist size. Problems associated with these methods include inaccuracy and the need for complicated equipment.

[0006] Currently, body fat measurement techniques also include using measuring light from a body to readily and accurately measuring body fat. Such body fat measurement device using light operates based on the principal that backward scattering occurs when a light emitted from a light source is used to irradiate a measurement point of a body. An optical detector is used to measure the amount of body fat by measuring a scattered optical signal.

[0007] A general issue with such body fat measurement devices, using backscattered light, is that the light source is generally too big to be incorporated into a portable device. Moreover, when the device is miniaturized, accuracy of the body fat measurement device may not be guaranteed because the accuracy of the body fat measurement device depends on an irradiated dimension of the light, and on an optical volume. Accordingly, a portable body fat measurement device that can readily and accurately measure body fat thickness is needed.

[0008] One or more embodiments of the present invention provide a portable body fat measurement device, method and medium, which can more accurately measure body fat by minimizing a measurement error caused by hemoglobin. For example, a signal requesting a

change of the measurement point may be output in an image output unit and sound output unit when body fat is measured by irradiating a measurement point of a user to indicate when a blood vessel is located beneath the measurement point.

[0009] Therefor the invention relates to an optical sensor module according to claim 1, a portable body fat measurement device according to claim 6, a method for measuring body fat according to claim 12, and a computer readable medium according to claim 16.

[0010] One or more embodiments of the present invention also provide a portable body fat measurement device, method and medium, that may also be installed within portable devices, e.g., a mobile terminal and the like, by minimizing thickness of an optical sensor module installed in the portable body fat measurement device.

[0011] One or more embodiments of the present invention also provides a portable body fat measurement device, method and medium, that can accurately measure body fat by using a small optical sensor having a comparatively small cross-section, by adopting an optical element, e.g., a prism sheet and a diffusion plate.

[0012] Additional aspects and/or advantages of the invention will be set forth in part in the description which follows and, in part, will be apparent from the description, or may be learned by practice of the invention.

[0013] According to one or more embodiments of the present invention, there is provided a portable body fat measuring device as defined in claim 6, including a light source unit having at least two side-view light sources and a light guiding efficiency optical element to guide an optical signal generated from the at least two side-view light sources to a measuring point at which body fat is measured, an optical detection unit to detect a scattered optical signal, generated by a scattering of the optical signal irradiated to the measuring point, and to transform the scattered optical signal into an electrical signal, and an electrical signal calculation unit to calculate body fat information based on the electrical signal.

[0014] According to one or more embodiments of the present invention, there is provided an optical sensor module for a portable body fat measuring device, as defined in claim 1, the optical sensor module including a light source unit having at least two side-view light sources and a light guiding efficiency optical element to guide an optical signal generated from the at least two side-view light sources to a body fat measuring point at which body fat is measured, and an optical detection unit to detect a scattered optical signal, generated by scattering of the optical signal generated from the at least two side-view light sources to a body fat measuring point at which body fat is measured, and an optical detection unit to detect a scattered optical signal, generated by scattering of the optical signal irradiated to the measuring point, to transform the scattered optical signal into an electrical signal, and to forward the electrical signal to an electrical signal calculation unit.

[0015] According to one or more embodiments of the

present invention, there is provided a method for measuring body fat, as defined in claim 12, using a portable light source unit having at least two side-view light sources and a light guiding efficiency optical element including guiding at least one light beam generated from the at least two side-view light sources to irradiate a measuring point, detecting scattered light, generated by a scattering of the at least one light beam after being irradiated to the measuring point transforming the scattered light into an electrical signal, and calculating body fat information based on the electrical signal.

BRIEF DESCRIPTION OF THE DRAWINGS

[0016] These and/or other aspects and advantages of the present invention will become apparent and more readily appreciated from the following detailed description, taken in conjunction with the accompanying drawings of which:

FIG. 1 illustrates a configuration of a portable body fat measurement device, according to one or more embodiments of the present invention;

FIG. 2 illustrates a lateral face of an optical sensor module, according to one or more embodiments of the present invention; and

FIG. 3 illustrates a top view of an optical sensor module, according to one or more embodiments of the present invention.

DETAILED DESCRIPTION OF EMBODIMENTS

[0017] Reference will now be made in detail to embodiments of the present invention, examples of which are illustrated in the accompanying drawings, wherein like reference numerals refer to the like elements throughout. Embodiments are described below in order to explain the present invention by referring to the figures.

[0018] A body fat measurement apparatus, according to an embodiment of the present invention, may be designed to have a stand-alone configuration, or the apparatus may be installed in a portable device such as a mobile communication device, a personal digital assistant (PDA), a portable game device, an MP3 player, a personal multimedia player (PMP), a digital multimedia broadcasting (DMB) device, a blood sugar measurement device, a grip power exercise device, a notebook computer, etc., for example, noting that alternative embodiments are equally available.

[0019] Further, measurement techniques described herein are not limited to a human body. The portable body fat measurement device, according to one or more embodiments of the present invention, may be used for at least all organisms having a subcutaneous fat layer between skin and muscle, for example.

[0020] FIG. 1 illustrates a configuration of a portable body fat measurement device according to one or more embodiments of the present invention.

[0021] The portable body fat measurement device may include, for example, an optical sensor module 110, an electrical signal calculation unit 120 and an output unit 130. The optical sensor module 110 may include, also as an example, an optical power control unit 111, a light source unit 112 and an optical detection unit 113. The electrical signal unit 120 may include, similarly as an example, a signal amplification unit 121, a body fat information calculation unit 122 and an output control unit 123, with output unit 130, potentially also includes a display unit 131 and a sound output unit 132.

[0022] The light source unit 112 of the optical sensor module 110 may have at least two side-view light sources and a light guiding efficiency optical element guiding an optical signal generated from the side-view light sources to a body fat measurement point.

[0023] The light source unit 112 may include, for example, the light guiding efficiency optical element, e.g., a light emitting diode (LED), a light guide plate, and/or an optical fiber. Here, the light guiding efficiency optical element may guide light generated in the side-view light sources to vertically irradiate a body at the measurement point, using a predetermined dimension. The side-view light sources may be embodied using a luminous element, e.g., an LED, located in the light guiding efficiency optical element. For such an embodiment, the configuration and shape of the side-view light sources included in a light source unit 112 will be described in greater detail below with reference to FIG. 3.

[0024] FIG. 3 illustrates a top view of an optical sensor module of a portable body fat measurement device, according to one or more embodiments of the present invention.

[0025] Referring to FIGS. 1 and 3, a top view of an optical sensor module includes, for example, a light source unit 112 and a light detection unit 113 of the optical sensor module 110. According to one or more embodiments of the present invention, the optical sensor may include at least two of the light source unit 112, i.e., the optical sensor may include at least two of the light source unit 112 for measuring body fat thickness. In another embodiment, the optical sensor may include at least three of the light source unit 112 for more accurate measurements the body fat thickness. As the quantity of the light source unit 112 increases, a scattered light reference, which may be used to measure the body fat at a measurement point, may increase. This may improve the accuracy of the measurements.

[0026] As an example, in FIG. 3, three light source units, i.e., a light source S1, a light source S2, and a light source S3 are installed.

[0027] Referring to FIG. 3, the light source units S1, S2, and S3 may include side-view light sources 324, 325 and 326, and light guiding efficiency optical elements 321, 322 and 323. Specifically, as an example, one of the light source units S1, S2, and S3 may be installed along a lateral face of the light guiding efficiency optical elements 321, 322 and 323, noting that additional light

source units may further be installed along the lateral face of the light guiding efficiency optical elements 321, 322 and 323.

[0028] An installation quantity and position of the side-view light sources 324, 325 and 326 may be embodied using various methods. The side-view light sources 324, 325 and 326 may be embodied with a luminous element, e.g., with the LED example described above.

[0029] The light guiding efficiency optical elements 321, 322 and 323 receive light from the side-view light sources 324, 325 and 326 and may guide the emitted light to be emitted via a top surface of the light guiding efficiency optical elements 321, 322 and 323. Specifically, light may be radiated in the same dimension as the top surface of the light guiding efficiency optical elements 321, 322 and 323.

[0030] The light guiding efficiency optical elements 321, 322 and 323 may include a prism sheet to increase the forward luminance of light reflected via the prism sheet. Here, light having a predetermined angle may exclusively be transmitted, for example, and all light radiated at all other angles may be reflected to increase forward luminance.

[0031] In addition, the light guiding efficiency optical elements 321, 322 and 323 may include a diffusion plate, i.e. the diffusion plate may be provided along the top surface of the light guiding efficiency optical elements 321, 322 and 323, so that uniform luminance according to a viewing angle may be achieved. The diffusion plate may be embodied, for example, in a polyethylene terephthalate (PET), a poly carbonate (PC), or the like. In another embodiment, a particle coating film for scattering light may also be formed on a top surface of the light guiding efficiency optical elements 321, 322 and 323, e.g., provided with the diffusion plate.

[0032] As illustrated, the light source units S1, S2 and S3, including the side-view light sources 324, 325 and 326 and the light guiding efficiency optical elements 321, 322 and 323, may be spaced apart from the optical detection unit 310 by a predetermined distance, e.g., the light source unit S1 may be separated from the optical detection unit 310 by a distance 3D1, the light source unit S2 may be separated from the optical detection unit 310 by a distance 3D2, and the light source unit S3 may be separated from the optical detection unit 310 by a distance 3D3. The distances 3D1, 3D2 and 3D3 between each of the light source units S1, S2, and S3, respectively, and the optical detection unit 310, may be variously designed according to a threshold value for measurable body fat at a measurement point. Namely, when the distance is larger, the threshold value of the measurable body fat at the measurement point becomes comparatively larger.

[0033] Also, an optical power or light strength output from the side-view light sources 324, 325, and 326 of each of the light source units may be designed to increase as the distances 3D1, 3D2, and 3D3 from the optical detection unit 310 increase. Namely, the optical power may

be established to correspond to the respective powers of the side-view light source 326 of the optical source S3, the side-view light source 325 of the optical source S2 and the side-view light source 324 of the optical source S1. The setting of the optical power may be controlled by the optical power control unit 111, for example. In one embodiment, light output from each of the side-view light sources 324, 325, and 326 may be made identical to any of the other light sources.

[0034] In another embodiment, the light source units S1, S2, and S3 including the side-view light sources 324, 325, and 326 and the light guide plate may be designed to have a thickness of less than approximately 1.5 mm. This facilitates installation in a portable device, for example. As described above, a slimmer light source unit capable of outputting a sufficient optical power may be provided by establishing at least two side-view light sources in a peripheral of the light guiding efficiency optical elements 321, 322 and 323, e.g., in an array type. Accordingly, depending on the environment, the optical sensor module 110, according to one or more embodiments of the present invention, may be optimized for installation in a mobile terminal where an acceptable component thickness is extremely limited, due to the density of components within the mobile device.

[0035] Referring back to FIG. 1, such an optical power control unit 111 may control the light power generated by controlling current supplied to the at least two side-view light sources. As described above, the operational current supplied to the at least two side-view light sources may be controlled so as to increase the optical power in proportion to the distance of a side-view light source from the optical detection unit 113.

[0036] The optical detection unit 113 may receive at least two scattered lights at the measurement point to transform into an electrical signal. Namely, the optical detection unit 113 may receive light scattered from inside a body as a result of the measurement point being irradiated. In one embodiment, the optical detection unit 113 may include an optical-electrical transducer element to transform the optical signal into the electrical signal.

[0037] The electrical signal calculation unit 120 may calculate body fat data at the measurement point by reviewing the corresponding electrical signal. As an example only, the electrical signal calculation unit 120 may include a signal amplification unit 121, a body fat information calculation unit 122 and an output control unit 123.

[0038] The signal amplification unit 121 may receive and amplify the electrical signal, e.g., transformed in the optical detection unit 113, and forward/transmit the signal to the body fat information calculation unit 122.

[0039] The body fat information calculation unit 122 may use the amplified electrical signal to calculate body fat information at the measurement point. The body fat information calculation unit 122 may further calculate thickness of the body fat from a intensity of scattered light backscattered from a body. The body fat ratio may also be calculated as a percentage, or a weight of the body

fat may be calculated via a predetermined lookup table, which will be described below by referring to FIG. 2.

[0040] FIG. 2 illustrates, as an example only, a lateral face of an optical sensor module of a portable body fat measurement device according to one or more embodiments of the present invention.

[0041] As described, the light source unit 230 may include at least one side-view light sources 231, 232 and 233, a prism sheet 240 and a diffusion plate 250. For example, in FIG. 2, a light source unit 230 may have three side-view light sources 231, 232 and 233, a prism sheet 240 and a diffusion plate 250.

[0042] Each of the side-view light sources 231, 232 and 233 may be separated from the optical detection unit 210 by a certain distance. The optical power control unit 111 of FIG. 1 may further control a value of the operation current supplied to each of the light sources. Such control compensates for the fact that an irradiated optical power may increase, as a distance from the optical detection unit 210 increases. Namely, as illustrated in FIG. 2, the current supplied to the side-view light source 233 may be greater than corresponding a current supplied to the side-view light source 232, and current supplied to the side-view light source 232 may be greater than corresponding current supplied to the side-view light source 231.

[0043] In this case, the intensity of scattered light, radiated from the side-view light source 233, scattered from a body and received by the optical detection unit 210, is smaller than the intensity of scattered light received by the optical detection unit from the side-view light source 232. Similarly, the intensity of scattered light corresponding to the side-view light source 232, is smaller than the intensity of scattered light corresponding to the side-view light source 231. Specifically, intensity of scattered light, reflected in different directions in different layers, e.g., layer 270 between a fat layer and a muscle layer, may be varied. Therefore the body fat information calculation unit 122 may calculate body fat information at the measurement point by calculating the intensity of scattered light corresponding to the each of the light sources.

[0044] The optical detection unit 210 detects scattered light, generated from each of the side-view light sources 231, 232 and 233, irradiated and scattered into the body. The illustrated three solid lines in FIG. 2 indicate optical signals that have been generated by each of the side-view light sources 231, 232 and 233 to irradiate a measurement point on a body. The optical signals, generated by each of the side-view light sources 231, 232 and 233, are scattered into the body and subsequently detected by the optical detection unit 210.

[0045] Here, an optical cut-off unit 220 is provided to prevent the lights, illustrated as a dotted line in FIG. 2 and generated by each of the side-view light sources 231, 232 and 233, from being directly detected in the optical detection unit 210 without first being irradiated and scattered into the body. Such direct radiation may cause an inaccurate measurement in one or more em-

bodiments of the present invention.

[0046] The intensity of the scattered light, generated in the side-view light sources 231, 232 and 233, decreases in proportion to the distance the scattered light travels inside the body. Also, the intensity of the scattered light tends to be reduced significantly as the scattered light passes through the layer 260 between the skin and the fat and the layer 270 between the fat and the muscle. In this case, information about the scattered light may be gained by sequentially extinguishing each of the side-view light sources 231, 232 and 233. Various body fat information, e.g. thickness of body fat, a body fat ratio, weight of the body fat and the like, may be calculated from the information gained by sequentially extinguishing each of the side-view light sources 231, 232 and 233.

[0047] Referring back to FIG. 1, an output control unit 123 controls the body fat information to be displayed or played via the output unit 130. For example, the output unit 130 may display or play the body fat information via a display unit 131 or a sound output unit 132. Alternatively, output and/or display embodiments are equally available.

[0048] Here, when the electrical signal transformed by the signal amplification unit 121 meets a predetermined value, e.g. is less than or equal to the predetermined value, the output control unit 123 may generate a message, requesting a user to change the measurement point. The message may be displayed and/or played via the output unit 130, for example. Specifically, as only an example, when the body fat information calculation unit 122 is not able to calculate body fat thickness because the electrical signal is weak, the output control unit 123 may provide the user with a message, requesting the user to change the measurement point, via the output unit 130.

[0049] Referring to FIG. 2, when a blood vessel 280 is located at or near the measurement point, the electrical signal may be weak. Blood flowing through the blood vessel 280 includes hemoglobin. A property of hemoglobin causes it to absorb scattered light. Due to hemoglobin's absorption of scattered light, when a measurement point is at or near a blood vessel, the intensity of scattered light received by the optical detection unit 210 decreases, possibly resulting in inaccurate body fat measurements.

[0050] Accordingly, when a value of the electrical signal meets a predetermined value, e.g. is less than or equal to the predetermined value, the output control unit 123 may provide the user with a message requesting the user to change the measurement point. The message may be displayed in a display unit 131, for example, using a type of a short message service (SMS). The message may also be played via the output unit 132 as audio sound, such as an alarm signal or a voice message, for example.

[0051] According to one or more embodiments of the present invention, to improve accuracy when scattered light is absorbed by hemoglobin, at least any one of the

at least two side-view light sources may output a light having a wavelength of approximately 600 nm through 800 nm, which provides comparatively greater absorption for hemoglobin.

[0052] When at least any one of the side-view light sources radiates light having a wavelength of approximately 600 nm through 800 nm, the optical detection unit 210 may more accurately detect a signal when it is located above a blood vessel. The optical detection unit 210 may then request a user to change the measurement point. Namely, according to one or more embodiments of the present invention, a plurality of light sources may radiate light having a wavelength of approximately 600 nm through 950 nm, and more specifically at least one of the plurality of light sources may irradiate a light having a wavelength of approximately 600 nm through 800 nm, to more accurately detect a signal when the optical detection unit 210 is located above a blood vessel. Here, alternative embodiments are equally available.

[0053] Thus, according to one or more embodiments of the present invention, a measurement error when measuring body fat thickness may be minimized by preventing a portable body fat measurement device 100 from being located above a blood vessel.

[0054] In addition to this discussion, embodiments of the present invention can also be implemented through computer readable code/instructions in/on a medium, e.g., a computer readable medium, to control at least one processing element to implement any above described embodiment. The medium can correspond to any medium/media permitting the storing and/or transmission of the computer readable code.

[0055] The computer readable code can be recorded/transferred on a medium in a variety of ways, with examples of the medium including magnetic storage media (e.g., ROM, floppy disks, hard disks, etc.), optical recording media (e.g., CD-ROMs, or DVDs), and storage/transmission media such as carrier waves, as well as through the Internet, for example. Here, the medium may further be a signal, such as a resultant signal or bit stream, according to embodiments of the present invention. The media may also be a distributed network, so that the computer readable code is stored/transferred and executed in a distributed fashion. Still further, as only an example, the processing element could include a processor or a computer processor, and processing elements may be distributed and/or included in a single device.

[0056] Also, according to one or more embodiments of the present invention, a portable body fat measurement device, method and medium, that can more accurately measure body fat by minimizing a measurement error caused by hemoglobin is provided. In an example, a signal for requesting a user to change a measurement point is output to one or both of an image output unit and a sound output unit when a blood vessel is located beneath the measurement point.

[0057] Accordingly, according to one or more embodiments of the present invention, a portable body fat meas-

urement device, method and medium, having an optical sensor module of limited thickness is provided, thus facilitating installation in portable devices, e.g. a mobile terminal, with minimal space availability.

[0058] Further, according to one or more embodiments of the present invention, a portable body fat measurement device, method and medium, is provided that can accurately measure body fat using an optical sensor with a comparatively smaller cross-section, by adopting an optical element, e.g. a prism sheet and a diffusion plate.

[0059] Although a few embodiments of the present invention have been shown and described, the present invention is not limited to the described embodiments.

Claims

1. Optical sensor module (110) for a portable body fat measuring device, the optical sensor module comprising:

a light source unit (112;230; S1, S2, S3) having at least two side-view light sources (231,232,233; 324,325,326) and a light guiding efficiency optical element (321,322,323) having a top surface and a lateral face for guiding an optical signal generated from the at least two side-view light sources through the top surface to a body fat measuring point at which body fat is measured, said at least two side-view light sources being installed along the lateral face; and

an optical detection unit (113;210;310) for detecting a scattered optical signal, generated by scattering of the optical signal generated from the at least two side-view light sources and irradiated to the measuring point, for transforming the scattered optical signal into an electrical signal, and for forwarding the electrical signal to an electrical signal calculation unit, **characterized in that** the at least two side-view light sources (324,325,326) emit a light having an identical wavelength, while separated from the optical detection unit with different distances, and **in that** the module further comprises:

an optical power control unit configured to control a value of an operational current supplied to each of the light sources so as to increase the optical power in proportion to the distance of a side-view source from the optical detection unit.

2. Optical sensor module according to claim 1, **characterized in that**, the light source unit (112) further comprises a light collective optical element comprising a prism sheet.

3. Optical sensor module according to any of the previous claims, **characterized in that**, the light source unit further comprises a scattered optical element comprising a diffusion plate.
4. Optical sensor module according to any of the previous claims, **characterized in that**, the light guiding efficiency optical element comprises a light guide or an optical fiber, and the side-view light source comprises a luminous element including a light emitting diode (LED) located in the light guiding efficiency optical element.
5. Optical sensor module according to any of the previous claims, **characterized in that**, the electrical signal calculation unit calculates body fat information at the measuring point.
6. Portable body fat measuring device comprising:
 - an optical sensor module according to any of the previous claims; and
 - an electrical signal calculation unit (120) to calculate body fat information based on the electrical signal.
7. Device of claim 6, **characterized in that** the electrical signal calculation unit (120) comprises:
 - a signal amplification unit (121) to amplify the electrical signal transformed from the optical detection unit (113);
 - a body fat information calculation unit (122) to calculate the body fat information from the amplified electrical signal; and
 - an output control unit (123) to control an output of the body fat information to an output device (130).
8. Device of claim 7, the electrical signal having an intensity, **characterized in that**, the output control unit (123) controls output of a message to request changing the measuring point via the output device (130), when the intensity of the electrical signal transformed in the optical detection unit meets a predetermined value.
9. Device according to any of the claims 6-8, **characterized in that**, the light source unit outputs an optical signal having a wavelength of approximately 600 to 800 nm.
10. Device according to any of the claims 6-9, **characterized in that**, the device further comprises:
 - a light cut-off unit to prevent the optical signal from being directly radiated into the optical detection unit (113).

11. Device according to any of the claims 6-10, **characterized in that**, the portable body fat measuring device is any one of a mobile terminal, a personal digital Assistant (PDA), a portable game device, an MP3 player, a personal multimedia player (PMP), a digital multimedia broadcasting terminal (DMB) terminal, a portable blood sugar measuring device, and a grip power exercise device.
12. Method for measuring body fat using a portable light source unit (112) having at least two side-view light sources and a light guiding efficiency optical element having a top surface and a lateral face, said at least two side-view light sources being installed along the lateral face, the method comprising:
 - guiding at least one light beam generated from the at least two side-view light sources through the top surface to irradiate a measuring point; detecting scattered light, generated by a scattering of the at least one light beam generated from the at least two side-view light sources, after being irradiated to the measuring point; transforming the scattered light into an electrical signal; and
 - calculating body fat information based on the electrical signal, **characterized by**:
 - controlling the at least two side-view light sources to respectively emit a light having an identical wavelength by controlling an operation current supplied to the at least two-side view light sources;
 - separating the at least two side-view light sources from an optical detector by different distances; and
 - increasing a power of the light output from the portable light source unit as a distance between the optical detector and the at least two side-view light sources increases..
13. Method of claim 12, **characterized in that**, the calculating comprises:
 - amplifying the electrical signal transformed from the scattered light;
 - calculating body fat information from the amplified electrical signal; and
 - controlling the output of the body fat information to an output device.
14. Method of any of the claims 12-13, **characterized in that**, the method further comprises directing a message to request changing the measuring point when a value of the electrical signal transformed in the optical detector meets a predetermined value.
15. Method of any of the claims 12-14, **characterized**

in that, the method further comprises preventing the scattered light from being radiated directly into the optical detector.

16. Medium comprising computer readable code to control at least one processing element to implement the method of any of the claims 12-15.

Patentansprüche

1. Optisches Sensormodul (110) für ein tragbares Körperfett-Messgerät, wobei das optische Sensormodul umfasst:

eine Lichtquelleneinheit (112; 230; S1, S2, S3) mit zumindest zwei seitlichen (side-view) Lichtquellen (231, 232, 233; 324, 325, 326) und einem optischen Lichtleiteffizienzelement (321, 322, 323), das eine obere Fläche und eine Seitenfläche aufweist, um ein von den zumindest zwei seitlichen Lichtquellen erzeugtes optisches Signal durch die obere Fläche zu einem Körperfett-Messpunkt, an dem Körperfett gemessen wird, zu leiten, wobei die zumindest zwei seitlichen Lichtquellen entlang der Seitenfläche angebracht sind; und

eine optische Erfassungseinheit (113; 210; 310) zum Erfassen eines gestreuten optischen Signals, das erzeugt wird durch Streuen des von den zumindest zwei seitlichen Lichtquellen erzeugten und zum Messpunkt gestrahlten optischen Signals, zum Umwandeln des gestreuten optischen Signals in ein elektrisches Signal, und zum Weiterleiten des elektrischen Signals an eine Berechnungseinheit für das optische Signal, **dadurch gekennzeichnet, dass** die zumindest zwei seitlichen Lichtquellen (324, 325, 326) ein Licht mit identischer Wellenlänge aussenden, während sie von der optischen Erfassungseinheit mit unterschiedlichen Abständen getrennt sind, und dass das Modul weiterhin umfasst:

eine Einheit zur Steuerung der optischen Leistung, die ausgebildet ist, um einen Wert eines jeder der Lichtquellen zugeführten Betriebsstroms zu regeln, um die optische Leistung im Verhältnis zur Entfernung einer seitlichen Lichtquelle von der optischen Erfassungseinheit zu erhöhen.

2. Optisches Sensormodul nach Anspruch 1, **dadurch gekennzeichnet, dass** die Lichtquelleneinheit (112) weiterhin ein optisches Lichtempfangselement umfasst, das ein flächiges Prismenteil umfasst.
3. Optisches Sensormodul nach einem der vorstehenden Ansprüche, **dadurch gekennzeichnet, dass**

die Lichtquelleneinheit weiterhin ein optisches Streuelement umfasst, das eine Diffusionsplatte umfasst.

4. Optisches Sensormodul nach einem der vorstehenden Ansprüche, **dadurch gekennzeichnet, dass** das optische Lichtleiteffizienzelement einen Lichtleiter oder eine optische Faser umfasst, und die seitliche Lichtquelle ein Leuchtelement umfasst, das eine lichtemittierende Diode (LED) beinhaltet, die sich im optischen Lichtleiteffizienzelement befindet.

5. Optisches Sensormodul nach einem der vorstehenden Ansprüche, **dadurch gekennzeichnet, dass** die Berechnungseinheit für das elektrische Signal Körperfettinformationen am Messpunkt berechnet.

6. Tragbares Körperfett-Messgerät, umfassend:

ein optisches Sensormodul nach einem der vorstehenden Ansprüche; und
eine Berechnungseinheit (120) für ein elektrisches Signal, um Körperfettinformationen auf Grundlage des elektrischen Signals zu berechnen.

7. Gerät nach Anspruch 6, **dadurch gekennzeichnet, dass** die Berechnungseinheit (120) für das elektrische Signal umfasst:

eine Signalverstärkungseinheit (121), um das von der optischen Erfassungseinheit (113) umgewandelte elektrische Signal zu verstärken;
eine Körperfettinformationen-Berechnungseinheit (122), um die Körperfettinformationen aus dem verstärkten elektrischen Signal zu berechnen; und
eine Ausgabesteuerungseinheit (123), um eine Ausgabe der Körperfettinformationen an eine Ausgabereinrichtung (130) zu steuern.

8. Gerät nach Anspruch 7, wobei das elektrische Signal eine Intensität aufweist, **dadurch gekennzeichnet, dass** die Ausgabesteuerungseinheit (123) die Ausgabe einer Nachricht steuert, um via die Ausgabereinrichtung (130) zu einer Veränderung des Messpunkts aufzufordern, wenn die Intensität des in der optischen Erfassungseinheit umgewandelten elektrischen Signals einem vorgegebenen Wert entspricht.

9. Gerät nach einem der Ansprüche 6 - 8, **dadurch gekennzeichnet, dass** die Lichtquelleneinheit ein optisches Signal mit einer Wellenlänge von annähernd 600 bis 800 nm ausgibt.

10. Gerät nach einem der Ansprüche 6 - 9, **dadurch gekennzeichnet, dass** das Gerät weiterhin um-

fasst:

eine Lichtsperrereinheit, um zu verhindern, dass das optische Signal direkt in die optische Erfassungseinheit (113) gestrahlt wird.

11. Gerät nach einem der Ansprüche 6 - 10, **dadurch gekennzeichnet, dass** das tragbare Körperfett-Messgerät beliebig ein mobiles Endgerät, ein persönlicher digitaler Assistent (PDA), ein tragbares Spielgerät, ein MP3-Spieler, ein persönliches multimediales Abspielgerät (PMP: Personal Multimedia Player), ein Endgerät für digitale multimediale Übertragung (DMB: Digital Multimedia Broadcasting), ein tragbares Blutzuckermessgerät oder ein Greifstärketrainingsgerät ist.

12. Verfahren zur Messung von Körperfett mittels einer tragbaren Lichtquelleneinheit (112) mit zumindest zwei seitlichen (side-view) Lichtquellen und einem optischen Lichteiteffizienzelement, das eine obere Fläche und eine Seitenfläche aufweist, wobei die zumindest zwei seitlichen Lichtquellen entlang der Seitenfläche angebracht sind, das Verfahren umfassend:

Leiten zumindest eines Lichtstrahls, erzeugt von den zumindest zwei seitlichen Lichtquellen, durch die obere Fläche, um einen Messpunkt zu bestrahlen;

Erfassen von gestreutem Licht, das erzeugt wird, indem der zumindest eine Lichtstrahl, erzeugt von den zumindest zwei seitlichen Lichtquellen, gestreut wird, nachdem er zum Messpunkt gestrahlt worden ist;

Umwandeln des gestreuten Lichts in ein elektrisches Signal; und

Berechnen von Körperfettinformationen auf Grundlage des elektrischen Signals, **gekennzeichnet durch:**

Steuern der zumindest zwei seitlichen Lichtquellen, damit sie jeweils Licht mit identischer Wellenlänge aussenden, **durch** Regeln eines Betriebsstroms, der den zumindest zwei seitlichen Lichtquellen zugeführt wird;

Trennen der zumindest zwei seitlichen Lichtquellen von einer optischen Erfassungseinrichtung um unterschiedliche Abstände; und

Erhöhen einer Leistung der Lichtausgabe aus der tragbaren Lichtquelleneinheit mit zunehmendem Abstand zwischen der optischen Erfassungseinrichtung und den zumindest zwei seitlichen Lichtquellen.

13. Verfahren nach Anspruch 12, **dadurch gekennzeichnet,**

zeichnet, dass das Berechnen umfasst:

Verstärken des aus dem gestreuten Licht umgewandelten elektrischen Signals;
Berechnen von Körperfettinformationen aus dem verstärkten elektrischen Signal; und
Steuern der Ausgabe der Körperfettinformationen an eine Ausgabeeinrichtung.

14. Verfahren nach einem der Ansprüche 12 - 13, **dadurch gekennzeichnet, dass** das Verfahren weiterhin das Zuleiten einer Nachricht umfasst, um zu einer Veränderung des Messpunkts aufzufordern, wenn ein Wert des in der optischen Erfassungseinrichtung umgewandelten elektrischen Signals einem vorgegebenen Wert entspricht.

15. Verfahren nach einem der Ansprüche 12 - 14, **dadurch gekennzeichnet, dass** das Verfahren weiterhin umfasst zu verhindern, dass das gestreute Licht direkt in die optische Erfassungseinrichtung gestrahlt wird.

16. Medium, das computerlesbaren Code umfasst, um zumindest ein Verarbeitungselement zu steuern, um das Verfahren nach einem der Ansprüche 12 - 15 zu implementieren.

Revendications

1. Module de captage optique (110) pour un dispositif portable de mesure de la graisse corporelle, le module de captage optique comprenant :

une unité de source lumineuse (112 ; 230 ; S1, S2, S3) possédant au moins deux sources lumineuses latérales (231, 232, 233 ; 324, 325, 326) et un élément optique à guidage efficace de la lumière (321, 322, 323) présentant une surface supérieure et une face latérale destinée au guidage d'un signal optique généré par les au moins deux sources lumineuses latérales à travers la surface supérieure vers un point de mesure de la graisse corporelle auquel est mesurée la graisse corporelle ; lesdites au moins deux sources lumineuses latérales étant installées le long de la face latérale ; et
une unité de détection optique (113 ; 210 ; 310) destinée à détecter un signal optique dispersé, généré par la dispersion du signal optique généré par les au moins deux sources lumineuses latérales et rayonné jusqu'au point de mesure, destinée à transformer le signal optique dispersé en un signal électrique, et à transmettre le signal électrique à une unité de calcul de signal électrique,

caractérisé en ce que les au moins deux sour-

ces lumineuses latérales (324, 325, 326) émettent une lumière de longueurs d'onde identiques, tout en étant séparées de l'unité de détection optique selon des distances différentes, et **en ce que** le module comprend en outre :

une unité de commande de la puissance optique configurée pour commander la valeur d'un courant fonctionnel fourni à chacune des sources lumineuses de manière à accroître la puissance optique proportionnellement à la distance existant entre une source latérale et l'unité de détection optique.

2. Module de captage optique selon la revendication 1, **caractérisé en ce que** l'unité de source lumineuse (112) comprend en outre un élément optique collecteur de lumière comprenant une feuille prismatique.
3. Module de captage optique selon l'une quelconque des revendications précédentes, **caractérisé en ce que** l'unité de source lumineuse comprend en outre un élément optique de dispersion comprenant une plaque de diffusion.
4. Module de captage optique selon l'une quelconque des revendications précédentes, **caractérisé en ce que** l'élément optique à guidage efficace de la lumière comprend un guide de lumière ou une fibre optique, et la source lumineuse latérale comprend un élément luminescent, tel qu'une diode électroluminescente (DEL), situé dans l'élément optique à guidage efficace de la lumière.
5. Module de captage optique selon l'une quelconque des revendications précédentes, **caractérisé en ce que** l'unité de calcul de signal électrique calcule les données relatives à la graisse corporelle au niveau du point de mesure.
6. Dispositif portable de mesure de la graisse corporelle comprenant :
 - un module de captage optique selon l'une quelconque des revendications précédentes ; et
 - une unité de calcul de signal électrique (120) destinée à calculer les données relatives à la graisse corporelle en fonction du signal électrique.
7. Dispositif selon la revendication 6, **caractérisé en ce que** l'unité de calcul de signal électrique (120) comprend :
 - une unité d'amplification de signal (121) destinée à amplifier le signal électrique transformé à

partir de l'unité de détection optique (113) ;
 une unité de calcul de données relatives à la graisse corporelle (122) destinée à calculer les données relatives à la graisse corporelle à partir du signal électrique amplifié ; et
 une unité de commande de sortie (123) destinée à commander une émission des données relatives à la graisse corporelle auprès d'un dispositif de sortie (130) .

8. Dispositif selon la revendication 7, le signal électrique possédant une intensité, **caractérisé en ce que** l'unité de commande de sortie (123) commande la sortie d'un message demandant le changement du point de mesure via le dispositif de sortie (130), lorsque l'intensité du signal électrique transformé dans l'unité de détection optique satisfait une valeur prédéterminée.
9. Dispositif selon l'une quelconque des revendications 6 à 9, **caractérisé en ce que** l'unité de source lumineuse émet un signal optique possédant une longueur d'onde d'environ 600 à 800 nm.
10. Dispositif selon l'une quelconque des revendications 6 à 9, **caractérisé en ce que** le dispositif comprend en outre :
 - une unité de coupure de la lumière destinée à empêcher le signal optique d'être directement rayonné dans l'unité de détection optique (113).
11. Dispositif selon l'une quelconque des revendications 6 à 10, **caractérisé en ce que** le dispositif portable de mesure de la graisse corporelle est compris parmi : un terminal mobile, un assistant numérique personnel (PDA), un dispositif de jeu portable, un lecteur MP3, un lecteur multimédia personnel (PMP), un terminal de diffusion multimédia numérique (DMB), un dispositif portable de mesure de la glycémie, et un dispositif d'exercice de la force de préhension (« grip power »).
12. Procédé de mesure de la graisse corporelle utilisant une unité de source lumineuse portable (112) possédant au moins deux sources lumineuses latérales et un élément optique à guidage efficace de la lumière présentant une surface supérieure et une face latérale, lesdites au moins deux sources lumineuses latérales étant installées le long de la face latérale, le procédé comprenant :
 - le guidage d'au moins un rayon lumineux généré par les au moins deux sources lumineuses latérales à travers la surface supérieure afin d'irradier un point de mesure ;
 - la détection de la lumière dispersée, générée par la dispersion de l'au moins un rayon lumi-

neux généré par les au moins deux sources lumineuses latérales, après son rayonnement vers le point de mesure ;
la transformation de la lumière dispersée en un signal électrique ; et
le calcul de données relatives à la graisse corporelle en fonction du signal électrique, **caractérisé par** :

5

la commande des au moins deux sources lumineuses latérales de sorte qu'elles émettent une lumière ayant des longueurs d'ondes identiques grâce à la commande d'un courant fonctionnel fourni auxdites au moins deux sources lumineuses latérales ;
la réalisation d'une séparation entre les au moins deux sources lumineuses latérales et un détecteur optique selon des distances différentes ; et
l'accroissement d'une puissance de la lumière émise par l'unité de source lumineuse portable à mesure que s'accroît la distance séparant le détecteur optique et les au moins deux sources lumineuses latérales.

10

15

20

25

13. Procédé selon la revendication 12, caractérisé en ce que l'étape de calcul comprend :

l'amplification du signal électrique transformé à partir de la lumière dispersée ;
le calcul des données relatives à la graisse corporelle à partir du signal électrique amplifié ; et
la commande de l'émission des données relatives à la graisse corporelle auprès d'un dispositif de sortie.

30

35

14. Procédé selon l'une quelconque des revendications 12 à 13, caractérisé en ce que le procédé comprend en outre la production d'un message demandant le changement du point de mesure lorsqu'une valeur du signal électrique transformé dans le détecteur optique satisfait une valeur prédéterminée.

40

15. Procédé selon l'une quelconque des revendications 12 à 14, caractérisé en ce que le procédé comprend en outre l'empêchement pour la lumière dispersée d'être rayonnée directement dans le détecteur optique.

45

16. Support comprenant un code lisible par ordinateur destiné à commander au moins un élément de traitement informatique afin de mettre en oeuvre le procédé selon l'une quelconque des revendications 12 à 15.

50

55

FIG. 1




FIG. 2





FIG. 3



REFERENCES CITED IN THE DESCRIPTION

This list of references cited by the applicant is for the reader's convenience only. It does not form part of the European patent document. Even though great care has been taken in compiling the references, errors or omissions cannot be excluded and the EPO disclaims all liability in this regard.

Patent documents cited in the description

- EP 1634533 A [0002]
- EP 1396227 A [0003]

专利名称(译)	便携式人体脂肪测量装置，方法和介质，使用侧视光源		
公开(公告)号	EP1857045B1	公开(公告)日	2011-01-26
申请号	EP2007107810	申请日	2007-05-09
[标]申请(专利权)人(译)	三星电子株式会社		
申请(专利权)人(译)	SAMSUNG ELECTRONICS CO., LTD.		
当前申请(专利权)人(译)	SAMSUNG ELECTRONICS CO., LTD.		
[标]发明人	HWANG IN DUK SHIN KUN SOO		
发明人	HWANG, IN DUK SHIN, KUN SOO		
IPC分类号	A61B5/00		
CPC分类号	A61B5/0059 A61B5/1075 A61B5/4872		
优先权	1020060044953 2006-05-19 KR		
其他公开文献	EP1857045A1		
外部链接	Espacenet		

摘要(译)

一种便携式人体脂肪测量装置，方法和介质，其能够通过使用具有相对小的横截面的小型光学传感器来精确地测量体脂肪。该装置包括具有至少两个侧视光源的光源单元和用于将从至少两个侧视光源产生的光信号引导到测量点的光导效率光学元件，用于检测的光学检测单元散射的光信号，由照射到测量点的光信号的散射产生，并将散射的光信号转换成电信号；电信号计算单元，用于根据电信号计算体脂肪信息。

