

(19)



(11)

EP 2 313 003 B1

(12)

EUROPEAN PATENT SPECIFICATION

(45) Date of publication and mention of the grant of the patent:
03.08.2016 Bulletin 2016/31

(51) Int Cl.:
A61B 5/07 (2006.01) A61B 5/00 (2006.01)
G05F 1/00 (2006.01)

(21) Application number: **09807292.9**

(86) International application number:
PCT/US2009/053721

(22) Date of filing: **13.08.2009**

(87) International publication number:
WO 2010/019778 (18.02.2010 Gazette 2010/07)

(54) **INGESTIBLE CIRCUITRY**

EINNEHMBARER SCHALTKREIS

CIRCUITS POUVANT ÊTRE INGÉRÉS

(84) Designated Contracting States:
AT BE BG CH CY CZ DE DK EE ES FI FR GB GR HR HU IE IS IT LI LT LU LV MC MK MT NL NO PL PT RO SE SI SK SM TR

- **SNYDER, Eric**
South San Francisco 94080 (US)
- **COSTELLO, Benedict**
Berkeley
CA 94703 (US)

(30) Priority: **13.08.2008 US 88355 P**

(43) Date of publication of application:
27.04.2011 Bulletin 2011/17

(74) Representative: **Keane, David Colman et al**
Murgitroyd & Company
Scotland House
165-169 Scotland Street
Glasgow G5 8PL (GB)

(73) Proprietor: **Proteus Digital Health, Inc.**
Redwood City, CA 94065 (US)

(72) Inventors:
• **HAFEZI, Hooman**
Redwood City
CA 94065 (US)

(56) References cited:
EP-A2- 1 534 054 WO-A2-2006/116718
US-A1- 2002 026 111 US-A1- 2003 195 403
US-A1- 2007 142 721

Note: Within nine months of the publication of the mention of the grant of the European patent in the European Patent Bulletin, any person may give notice to the European Patent Office of opposition to that patent, in accordance with the Implementing Regulations. Notice of opposition shall not be deemed to have been filed until the opposition fee has been paid. (Art. 99(1) European Patent Convention).

EP 2 313 003 B1

Description**BACKGROUND**

5 **[0001]** Ingestible devices that include electronic circuitry have been proposed for use in a variety of different medical applications, including both diagnostic and therapeutic applications.

[0002] Examples of such ingestible devices are ingestible electronic capsules which collect data as they pass through the body, and transmit the data to an external receiver system. An example of this type of electronic capsule is disclosed in U.S. Patent No. 5,604,531 Iddan et al., which describes what is called an in vivo video camera. The swallowable capsule includes a camera system and an optical system for imaging an area of interest onto the camera system. The transmitter transmits the video output of the camera system and the reception system receives the transmitted video output. U.S. Patent No. 7,009,634 also issued to Iddan et al discloses an ingestible imaging device that obtains images from within body lumens or cavities. The electronic circuit components of the device are enclosed by an inert indigestible housing (e.g. glass housing) that passes through the body internally. U.S. Patent No. 6,800,060 issued to Marshall discloses an ingestible data recorder capsule medical device. The electronic circuits of the disclosed device (e.g. sensor, recorder, etc.) are housed in a capsule made of inert materials, and therefore ingestible and passable through the digestive tract without being consumed by the body.

[0003] In these devices, the electronic circuits are protected in a housing or capsule that prevents damage to the device's electronic circuits during the process of ingestion and elimination in the human body.

20 **[0004]** Recently, U.S. Patent Application Publication No. 2007/0008113 by Spoonhauer et al. disclosed fragile radio frequency identification (RFID) tags for use in drug ingestion monitoring applications. The RFID tags disclosed in this application are simple antenna structures that are configured to break down during transit through the body.

[0005] In certain instances, more complex circuitry suitable for use in ingestible devices is needed.

25 **[0006]** WO 2006/116718 A2, discloses a Pharma-Informatics system for the automatic identification of ingestion or other actual, physical administration of a pharmaceutical material.

SUMMARY

30 **[0007]** The present invention provides for robust ingestible circuitry, where the components of the ingestible circuitry are ingestible, and in some instances digestible. As the ingestible circuitry is made up of ingestible, and even digestible, components, the ingestible circuitry results in little, if any, unwanted side effects, even when employed in chronic situations. The ingestible circuitry is particularly suited for use in signal identifiers, e.g., as may be found in ingestible event markers (IEMs), which include pharma-informatics enabled compositions.

[0008] A method according to the invention is defined in claim 1.

35 **[0009]** Embodiments of ingestible circuitry include a solid support of an ingestible material, which support has on a surface thereof one or more electronic components. Components that may be present on the surface of the support may vary, and include but are not limited to: logic and/or memory elements, e.g., in the form of an integrated circuit; a power device, e.g., battery, fuel cell or capacitor; an effector, e.g., sensor, stimulator, etc.; a signal transmission element, e.g., in the form of an antenna, electrode, coil, etc.; a passive element, e.g., an inductor, resistor, etc. The one or more components on the surface of the support may be laid out in any convenient configuration. Where two or more components are present on the surface of the solid support, interconnects may be provided. All of the components and the support of the ingestible circuitry are ingestible, and in certain instances digestible.

BRIEF DESCRIPTION OF THE FIGURES

45 **[0010]**

FIG. 1 shows diagrammatically an ingestible identifier that includes ingestible circuitry.

FIGS. 2A to 2D provide views of assembly of an ingestible identifier that includes ingestible circuitry.

50 **FIGS. 3A and 3B** provide views of assembly of an ingestible identifier that includes ingestible circuitry.

FIG. 4 provides a view of assembly of an ingestible identifier that includes ingestible circuitry.

FIG. 5 provides a view of assembly of an ingestible identifier that includes ingestible circuitry.

FIGS. 6A and 6B provide views of assembly of an ingestible identifier that includes ingestible circuitry

FIGS. 7A to 7B provide views of a bifurcated laminate process employed to fabricate devices according to one embodiment of the invention.

55

DETAILED DESCRIPTION

[0011] The present invention provides for ingestible circuitry, where the components of the circuitry are ingestible, and in some instances digestible. As the ingestible circuitry is made up of ingestible, and even digestible, components, the ingestible circuitry results in little, if any, unwanted side effects, even when employed in chronic situations.

[0012] Embodiments of ingestible circuitry include a solid support of an ingestible material, which support has on a surface thereof one or more electronic components. Components that may be present on the surface of the support may vary, and include but are not limited to: logic and/or memory elements, e.g., in the form of an integrated circuit; a power device, e.g., battery, fuel cell or capacitor; an effector, e.g., sensor, stimulator, etc.; a signal transmission element, e.g., in the form of an antenna, electrode, coil, etc.; a passive element, e.g., an inductor, resistor, etc. The one or more components on the surface of the support may be laid out in any convenient configuration. Where two or more components are present on the surface of the solid support, interconnects may be provided.

[0013] The ingestible circuitry is particularly suited for use in signal identifiers, e.g., as may be found in ingestible event markers and pharma-informatics enabled compositions. One example includes use of the ingestible circuitry in association with a specific pharmaceutical product, such as a pill, to determine when a patient takes the pharmaceutical product. As the pill is consumed, the ingestible circuit is activated and generates a signal that is detected thereby signifying that the pharmaceutical product has been taken by a patient.

INGESTIBLE CIRCUITRY AND FABRICATION THEREOF

[0014] As summarized above, the present invention provides ingestible circuitry. Ingestible circuitry includes a solid support fabricated from an ingestible material, and one or more electronic components displayed on a surface thereof. Where two or more components are present on a given solid support, conductive interconnecting elements are also present that electrically couple the two or more components. A variety of different types of components may be present on the support, as reviewed in greater detail below. In addition, one or more optional elements, such as a protective layer, etc., may be provided.

[0015] Ingestible circuitry can be a standalone unit or it can be incorporated into another structure, e.g., an ingestible identifier, such as may be found in an ingestible event marker, including a pharma-informatics enabled pharmaceutical composition.

[0016] As summarized above, circuitry of the disclosure is ingestible, where the disparate components of the circuitry are fabricated from ingestible materials. In certain embodiments, one or more of the ingestible materials of the circuits are digestible materials. As such, the amounts of the materials are below chronic ingestion limits if the circuitry is present in a device that is going to be ingested chronically. If the circuitry is incorporated into a device that is going to be ingested less frequently, materials may be chosen based on the anticipated dosage schedule.

[0017] As reviewed above, elements of the ingestible circuitry include a solid support, one or more electronic components, and interconnects, among other elements.

[0018] The solid support is the structure on which all of the components are present. The solid support is fabricated from an ingestible material, where the material is a dielectric or insulating material. It can be fabricated from a variety of materials. Materials that provide mechanical strength and may be employed as an insoluble component of the solid support include, but are not limited to: Ethyl cellulose (e.g. Hercules Aqualon or Dow Ethocel), cellulose acetate, Agar, Gelatin. Insoluble materials of interest include ethylcellulose, a copolymer of acrylic acid and methacrylic acid esters, having from about 5 to 10% functional quaternary ammonium groups, polyethylene, polyamide, polyvinylchloride, polyvinyl acetate and any mixtures thereof. Fillers, such as, starch, glucose, lactose, inorganic salts such as sodium or potassium chloride, carbonates, bicarbonates, sulfates, nitrates, silicates (e.g., magnesium silicate) and alkali metals phosphates and oxides (e.g., titanium dioxide, magnesium oxide), may also be present. Soluble materials that may be employed, e.g., as disintegrating agents, in the solid support include, but are not limited to: Hydroxypropyl cellulose, hydroxyethylcellulose, carboxymethylcellulose, croscarmellose, hypromellose, hydroxypropyl methyl cellulose, methyl cellulose, Polysaccharides (starch, different sugars); Polyvinyl alcohol; Gums (guar, xanthan, acacia); Alginates (sodium or calcium alginate); povidone; etc. Also of interest are Plasticizing agents, e.g., Dibutyl sebacate, triacetin, triethyl citrate, polyethylene glycol, polyethylene oxide. Soluble materials of interest include proteins, polysaccharides, polyacrylates, hydrogels, polyvinyl alcohol, polyvinyl pyrrolidone, and derivatives of such polymers. In certain embodiments, plasticizers may be present, where plasticizers make it easier to process and modulate the strength so that it is not stiff and brittle. Also of interest are surfactants. Environmentally sensitive materials may also be present in the support, such as environmentally sensitive polymers, e.g., temperature sensitive polymers, pH sensitive polymers (e.g., Polymethacrylates (e.g. Degussa Eudragit®)), oxygen sensitive polymers, enzyme sensitive polymers (e.g., Starch, Chitosan, etc.), that will make it insoluble in certain physiological locations, such as the stomach, and soluble in other physiological locations, such as the intestine. Embodiments of such supports are supports that retain their shape in the stomach and then fall apart upon entry/transit through the intestine. Also present may be foaming agents, e.g., sodium carbonate, swelling

agents, e.g., hydrogel polymers, or cross linking agents, e.g., glutaraldehyde. In certain embodiments, the support is fabricated from a foodstuff which has suitable properties. Foodstuffs of interest include, but are not limited to: soy, whey, wheat gluten, rice starch, tapioca starch, rice paper, nori, corn chips, potato, pasta, filo, fruit roll-ups, haw flakes, crackers, gelatin and gummy. The solid supports can be fabricated via any convenient protocol, such as through deposition via a number of methods such as solvent cast, or melt extrusion.

[0019] Also present in ingestible circuitry is one or more conductive elements which serve to interconnect two or more distinct components on a surface(s) of the support. In certain embodiments, this conductive element, e.g., interconnect or wire, is a thin layer or strip of a homogenous conductive and ingestible material, such as gold, silver, graphite, titanium, copper, etc. The material making up the conductive element may be any material whose total amount is below chronic ingestion limits (i.e., how often one is ingesting the ingestible device) where the conductivity is within a desired range. Table 1 below provides examples of ranges.

Table 1

Metal	Resistivity (Ωm)	Dimension		
		Length	Width	Thickness
Cu	1.68×10^{-8}	1 cm	100 μm	1 μm
Mg	4.39×10^{-8}	1 cm	100 μm	10 μm
Au	2.21×10^{-8}	1 cm	100 μm	100 μm
Ag	1.59×10^{-8}	1 cm	10 μm	1 μm
Fe	9.61×10^{-8}	1 cm	100 μm	0.1 μm

[0020] The conductive elements (i.e., interconnects) can be deposited on a surface of the support to provide interconnection between two or more components as a homogeneous layer, for example a layer of gold. Any convenient deposition protocol may be employed, such as but not limited to: evaporation, plating, electrolysis plating, galvanic deposition, screen or ink jet printing, or other thin layer deposition techniques. Alternatively, a lamination method may be employed, where various elements are positioned as sheets. In yet other embodiments, a decal transfer process may be employed, where each of the distinct elements is on a separate backing layer. The distinct elements are transferred to the solid support, and then the backing layer is removed. With each of the above protocols, a patterning technique may be employed. The choice of patterning technique will depend on the choice of deposition process and the dimensional control required of the final pattern, for example evaporation or plating is very compatible with photo lithography. For laminate protocols, laser patterning might be employed, e.g., where a layer is deposited and the unwanted portions are cut out. In certain embodiments, purely additive techniques, such as ink jet or screen printing, are employed.

[0021] Instead of having a conductive element fabricated from a homogenous material, the conductive element can be a heterogenous material that is a paste or an ink. For example, a suspension of a conductive filler of the conductive materials, e.g., gold, silver, graphite, etc., with an ingestible binder material, such as a polymer, a thermoset or thermoplastic polymer, may be employed. This heterogenous material can contain other polymeric components such as plasticizers, surfactants to make the ink and the paste flow better, be more processable etc. In yet other embodiments, the conductive element is an isotropic conductive film, e.g., a film of inert particles, such as of a material like glass, that have been coated with a conductive material, e.g., a metal.

[0022] Electrical connection between the conductive element and components on the support may be achieved in a number of different ways. For example, interconnects and various components may be positioned on a surface of the solid support, and a layer of conductive material that covers the disparate components and conductive elements can be deposited in a manner that provides the desired connection. Alternatively, ingestible conductive glues, pastes and adhesives may be employed. In certain embodiments, of interest is the use of a combination of two (or more) glues, where one of the glues provides for desired conductive properties and one of the glues provides mechanical strength. In addition, mechanical attachment protocols such as pressing different components together, e.g., where the components have suitable shape interfaces that make it easier for them to bond under mechanical force, pressure, and temperature, may be employed. Also of interest is laser welding, sonic welding, etc. The components can be immobilized relative to a surface of the solid support by mechanically holding the components on to the solid support, e.g., via deposition of a conductive overlay, as reviewed above, by way of a glue, such as a thermoplastic glue that physically holds items in place or thermosetting glue that is cross linked. Lasers may be employed with mixtures of some metals or conductive elements and locally sintered to make an electrical contact at the sintered point (e.g., where the laser removes or densifies an organic material in a binder, leaving a more thermally stable conductive material behind).

[0023] In addition to the above components, the ingestible circuitry also includes one or more electronic components.

Electrical components of interest include, but are not limited to: logic and/or memory elements, e.g., in the form of an integrated circuit; a power device, e.g., battery, fuel cell or capacitor; an effector, e.g., sensor, stimulator, etc.; a signal transmission element, e.g., in the form of an antenna, electrode, coil, etc.; a passive element, e.g., an inductor, resistor, etc.

[0024] The various components may be produced on a surface of a solid support using a variety of different protocols.

For example, where the components are electrode elements that make up a battery which is activated upon contact with stomach fluid, e.g., as described below, the battery components can be deposited directly onto the solid support. For example, a magnesium layer can be evaporated onto a surface of the solid support, where the solid support is fabricated from a material(s) that withstands the temperature and pressure that occurs during that deposition process. The different components of the electrodes can be deposited onto a conductor layer that is then attached to the solid support. For example, one can have a thin sheet of gold, and a layer of CuCl can be deposited onto the gold, with the resultant product being attached to the solid support. The different layers can also be deposited via an ink or a paste. For example, a structure of CuCl deposited on gold can be broken up into small particles, and an ink material can be fabricated from the particles. The resultant ink material can be used to either print or silk screen the desired electrode pattern onto the solid support. Also of interest are protocols that employ screen printing or ink jet printing techniques. In yet other embodiments, an unpatterned slurry is deposited. In yet other embodiments, "roll-to-roll" or "continuous web" protocols are employed.

[0025] In certain embodiments, the ingestible circuitry includes a coating layer. The purpose of this coating layer can vary, e.g., to protect the circuitry, the chip and/or the battery, or any components during processing, during storage, or even during ingestion. For example, one may not desire the circuitry to be exposed to the body fluids after it is ingested.

In such instances, it may be desirable to only have the battery and transmit antennas be exposed to body fluids, with the rest of the circuitry being protected. In such instances, a coating on top of the circuitry that is ingestible but does not dissolve until the device is finished doing its transmission may be provided. Also of interest are coatings that are designed to protect the ingestible circuitry during storage, but dissolve immediately during use. For example, coatings that dissolve upon contact with an aqueous fluid, e.g., stomach fluid. Also of interest are protective processing coatings that are employed to allow the use of processing steps that would otherwise damage certain components of the device. For example, in embodiments where a chip with battery material deposited on the top and bottom is produced, the product needs to be diced. However, the dicing process can scratch off the battery material, and also there might be liquid involved which would cause the battery materials to discharge or dissolve. In such instances, a protective coating on the battery that prevents mechanical or liquid contact with the battery component during processing can be employed. Another purpose of the edible coatings would be to control the activation of the device. For example, an edible coating that sits on the battery electrodes and takes a certain period of time, e.g., five minutes, to dissolve upon contact with stomach fluid may be employed. The coating can also be an environmentally sensitive coating, e.g., a temperature or pH sensitive coating, or other chemically sensitive coating that provides for dissolution in a controlled fashion and allows one to activate the device when desired. Coatings that survive the stomach but dissolve in the intestine are also of interest, e.g., where one desires to delay activation until the device leaves the stomach. An example of such a coating is a polymer that is insoluble at low pH, but becomes soluble at a higher pH. Also of interest are pharmaceutical formulation protective coatings, e.g., a gel cap liquid protective coating that prevents the circuit from being activated by liquid of the gel cap.

[0026] Another component present in certain embodiments of the ingestible circuit is an activation mechanism, e.g., where the activation mechanism is distinct from the power source (e.g., battery). An example of such an alternative activation element is a patch of circuit that closes upon contact with fluid and activates the device. Another example is the reactive removal of a patch of the circuit that, before it is removed, keeps the circuit from operating.

[0027] As indicated above, ingestible circuitry devices may be fabricated in a variety of different ways. Any of a variety of different protocols may be employed in manufacturing the circuitry structures and components thereof. For example, molding, deposition and material removal, e.g., planar processing techniques, such as Micro-Electro-Mechanical Systems (MEMS) fabrication techniques, including surface micromachining and bulk micromachining techniques, may be employed. Deposition techniques that may be employed in certain embodiments of fabricating the structures include, but are not limited to: electroplating, cathodic arc deposition, plasma spray, screen or ink jet printing, sputtering, e-beam evaporation, physical vapor deposition, chemical vapor deposition, plasma enhanced chemical vapor deposition, etc. Material removal techniques included, but are not limited to: reactive ion etching, anisotropic chemical etching, isotropic chemical etching, sacrificial lift-off etching, planarization, e.g., via chemical mechanical polishing, laser ablation, electronic discharge machining (EDM), etc. Also of interest are lithographic protocols. Of interest in certain embodiments is the use of planar processing protocols, in which structures are built up and/or removed from a surface or surfaces of an initially planar substrate using a variety of different material removal and deposition protocols applied to the substrate in a sequential manner. Illustrative fabrication methods of interest are described in greater detail in PCT application serial nos. PCT/US2006/016370; PCT/US2007/022257; PCT/US2007/082563; PCT/US2008/052845; PCT/US2008/053999; and PCT/US2008/077753.

[0028] In certain embodiments, of interest is a bifurcated laminate process for preparing a device made up of ingestible

circuitry. In this bifurcated laminate process, a laminate component is made separate from a circuitry component, allowing greater freedom in terms of processing protocols than may be employed to fabricate the disparate components together, since protocols may be employed to fabricate a first component that cannot be used to fabricate the other, and vice versa. In such bifurcated laminate protocols, the circuitry and laminate components are combined into a single device following separate fabrication of the two components. To combine the two components, any convenient protocol may be employed. In certain embodiments, the circuitry component is fixed into receiving feature of the laminate component, and fixed in place with a suitable adhesive, such as a conductive adhesive. An example of the use of this protocol for the fabrication of an ingestible event marker according to an embodiment of the invention is provided below in connection with a description of FIGS. 7A to 7B.

[0029] In FIG. 7A, an initial laminate sheet which includes battery elements and a virtual dipole element (e.g., skirt) of an ingestible event marker is shown being prepared using a "continuous web" or "roll-to-roll process". The initial laminate sheet is characterized by having exposed battery layers, e.g., upper and lower exposed battery layers, and includes a first battery layer **708**, e.g., CuCl layer (e.g., produced by evaporation, electrodeposition, slurry deposition, silkscreen, or inkjet, etc.), a second virtual dipole layer **710** positioned on top of the battery layer (i.e., skirt), a third current collector layer **712**, e.g., Au, Cu, or graphite, etc., which may be a sheet or printed on the skirt, on top of the virtual dipole layer, and a fourth battery layer **714**, e.g., Mg foil. Where desired, one or more of the layers can be made separately before lamination, so each process need not be compatible with all the layers e.g., current collector can be graphite-based, made with a high temperature process, which may be incompatible with processes and/or materials used to fabricate the other layers. Layers may be glued together with edible, cellulose adhesive or other safe pressure sensitive adhesives (including but not limited to, silicon materials, etc.).

[0030] Fabricated separate from the laminate component is the circuitry component. The circuitry component may be fabricated using any convenient protocol, e.g., as summarized above.

[0031] Next, a hole or passage **720** configured to receive the circuitry component (e.g., integrated circuit (IC)) is punched in the resultant laminate component **722** to receive the circuitry component **724**, as shown in FIG. 7B. The circuitry component is then positioned in the passageway and fixed in place with a conductive adhesive **726**, e.g., as shown in FIG. 7B. A variety of conductive adhesives may be employed, e.g., a polymer filled with conductive particles or a reactive (2-part) glue. The conductivity of the adhesive may be moderate. Where desired, the adhesive can be covered with a final layer of insulating adhesive.

[0032] In a variation of the above protocol, a pre-punched lower laminate is employed. In this embodiment, the IC is placed onto a pre-punch hole, where prior to placement, the sheet may be covered with a pressure sensitive adhesive material that is removed prior to chip placement during punching but is removed prior to chip placement. A second laminate is applied over the top of the chips and then opened, e.g., with a laser, over the chips and the top conductor (e.g., battery material) is additively applied, e.g., by screen printing. A final non-conductive layer, such as treated paper or plastic, is used in a roll-to-roll process after this step to isolate the two sides of the battery before the IEMs are finally punched out of the roll for assembly into tablets or capsules.

[0033] Finally, a disc shaped device **740**, e.g., shown by dashed lines in FIG. 7B, is punched out to produce the desired IEM.

[0034] The above bifurcated laminate protocol finds use in, among other applications, fabricating IEMs that have a virtual dipole, e.g., as described in greater detail in pending United States Provisional Application Serial No. 60/975,108 titled "Virtual Dipole Signal Amplification For Pharma-Informatics System" and filed on September 25, 2007.

DEVICES COMPRISING INGESTIBLE CIRCUITRY

[0035] Ingestible circuitry of the invention finds use in a variety of different types of devices. One example of a device that can include ingestible circuitry of the invention is an ingestible identifier. Ingestible identifiers are described in PCT application serial no. PCT/US2006/016370 published as WO/2006/116718; PCT application serial no. PCT/US2007/082563 published as WO/2008/052136; PCT application serial no. PCT/US2007/024225 published as WO/2008/063626; PCT application serial no. PCT/US2007/022257 published as WO/2008/066617; PCT application serial no. PCT/US2008/052845 published as WO/2008/095183; PCT application serial no. PCT/US2008/053999 published as WO/2008/101107; PCT application serial no. PCT/US2008/056296 published as WO/2008/112577; PCT application serial no. PCT/US2008/056299 published as WO/2008/112578; PCT application serial no. PCT/US2008/077753 published as WO2009/042812; PCT application serial no. PCT/US2008/085048 published as WO 2009/070773; and PCT application serial no. PCT/US2009/36231; as well as pending United States application serial nos. 12/126,792 and 12/126,798.

[0036] An example of such an ingestible identifier is an identifier that includes battery. The battery includes, when completed, a cathode, an anode, and an electrolyte, where the electrolyte component is provided by a physiological fluid, e.g., stomach acid. When the identifier is ingested and reaches the stomach, the cathode and anode are exposed to stomach fluid. The stomach fluid (either by itself or when combined with a dried conductive precursor medium com-

ponent of the identifier, e.g., as described in pending PCT application serial no: PCT/ US2007/082563 acts as the electrolyte component of the battery. Completion of the battery powers the circuitry of the identifier which, in turn broadcasts a detectable signal.

[0037] Identifiers of interest include two dissimilar electrochemical materials which constitute the two electrodes (e.g., anode and cathode) of the battery. When the electrode materials are exposed and come into contact with the body fluid, such as stomach acid or other types of fluid (either alone or in combination with a dried conductive medium precursor), a potential difference, that is, a voltage, is generated between the electrodes as a result of the respective oxidation and reduction reactions incurred to the two electrode materials. A voltaic cell, or battery, can thereby be produced. Accordingly, in embodiments of the invention, such batteries are configured such that when the two dissimilar materials are exposed to the target site, e.g., the stomach, the digestive tract, etc., during the physical and chemical erosion of the composition in which the signal generation element is present, a voltage is generated. The two dissimilar materials in an electrolyte are at different potentials. As an example, copper and zinc when put into a cell have different potentials. Similarly, gold and magnesium have different potentials. As a result, a potential difference between the two dissimilar materials is generated.

[0038] In certain of these embodiments, the battery power source may be viewed as a power source that exploits electrochemical reaction in an ionic solution such as gastric fluid, blood, or other bodily fluids and some tissues. **FIG. 1** provides a diagrammatic representation of an ingestible identifier **10** having a battery that is completed by stomach fluid. First and second electrode materials (**12** and **13**) are present in an ionic solution **16** (which may be made up of target site fluid alone or target site fluid combined with a dried conductive medium precursor). This configuration creates a low voltage (V-) and a high voltage (V+) as applied to an electronic circuit **14**. The polarity of the electrodes are determined by the connection needs of the electronic circuit **14** and the design as illustrated is just one embodiment. Thus, it will be apparent to one skilled in the art that the scope of the present invention includes reversal of the polarity of the electrodes, such that electrode 13 represents the low voltage and electrode 12 represents high voltage. The two outputs of that electronic circuit **14** are E0 **11** and E1 **15**, which are the signal-transmission electrodes on the top surface.

[0039] Electrodes **12** and **13** can be made of any two materials appropriate to the environment in which the identifier **10** will be operating. The active materials are any pair of materials with different electrochemical potentials, as long as they are ingestible, e.g., as described above. For instance, in some embodiments where ionic solution **16** comprises stomach acids, electrodes **12** and **13** may be made of a noble metal (e.g., gold, silver, platinum, palladium or the like) so that they do not corrode prematurely. Suitable materials are not restricted to metals, and in certain embodiments the paired materials are chosen from metals and non-metals, e.g., a pair made up of a metal (such as Mg) and a salt (such as CuCl or CuI). With respect to the active electrode materials, any pairing of substances - metals, salts, or intercalation compounds - with suitably different electrochemical potentials (voltage) and low interfacial resistance are suitable.

[0040] Materials and pairings of interest include, but are not limited to those reported in Table 2 below.

TABLE 2		
	Anode	Cathode
Metals	Magnesium, Zinc Sodium (†), Lithium (†) Iron and alloys thereof	
Salts		Copper salts: iodide, chloride, bromide, sulfate, formate, (other anions possible) Fe ³⁺ salts: e.g. orthophosphate, pyrophosphate, (other anions possible) Oxygen or hydrogen (††) on platinum, gold or other catalytic surfaces
Intercalation compounds	Graphite with Li, K, Ca, Na, Mg	Vanadium oxide Manganese oxide

† Protected anodes: certain high energy anode material such as Li, Na, and other alkali metals are unstable in their pure form in the presence of water or oxygen. These may however be used in an aqueous environment if stabilized. One example of this stabilization is the so-called "protected lithium anode" developed by Polyplus Corporation (Berkeley, CA), where a polymer film is deposited on the surface of lithium metal to protect it from rapid oxidation and allow its use in aqueous environment or air ambient. (Polyplus has IP pending on this).

†† Dissolved oxygen can also serve as a cathode. In this case, the dissolved oxygen in the bodily fluids would be reduced to OH⁻ at a suitable catalytic surface such as Pt or gold. Also of interest dissolved hydrogen in a hydrogen reduction reaction.

[0041] In certain embodiments, one or both of the metals may be doped with a non-metal, e.g., to enhance the voltage output of the battery. Non-metals that may be used as doping agents in certain embodiments include, but are not limited to: sulfur, iodine and the like.

[0042] In certain embodiments, the electrode materials are cuprous iodine (CuI) or cuprous chloride as the cathode and magnesium (Mg) metal or magnesium alloy as the anode. Embodiments of the present invention use electrode materials that are not harmful to the human body.

[0043] In certain embodiments, the batteries have a small form factor. Batteries may be about 20 mm³ or smaller, e.g., about 10 mm³ or smaller, such as 1.0 mm³ or smaller, including 0.1 mm³ or smaller, including 0.02 mm³ or smaller. In certain embodiments, the battery element is dimensioned to have a width ranging from about 0.01 mm to about 100 mm, e.g., from about 0.1 mm to about 20 mm, including from about 0.5 mm to about 2 mm; a length ranging from about 0.01 mm to about 100 mm, e.g., from about 0.1 mm to about 20 mm, including from about 0.5 mm to about 2 mm, and a height ranging from about 0.01 mm to about 10 mm, e.g., from about 0.05 mm to about 2 mm, including from about 0.1 mm to about 0.5 mm.

[0044] The ingestible identifier 10 uses the voltage potential difference to power up electronic circuit 14. In one embodiment, the electronic circuit 14 modulates conductance to create a unique and identifiable current signature.

[0045] In certain embodiments, the battery has a laminate structure. As indicated above, a laminate process may be employed to fabricate ingestible circuitry in accordance with the invention. An example of such a laminate process is illustrated in FIGS. 2A to 2D. In FIG. 2A, structure 21 is made up of circular metallic foil 22, e.g., gold, and has patterned areas of an electrode material, such as CuCl, patterned on its surface in the form of four distinct quadrants 24. The CuCl regions 24 may be produced on the surface of the foil via any convenient protocol, such as evaporation. Also shown is area 26 which lacks electrode material and is configured to receive an integrated circuit. In FIG. 2B, structure 21 placed onto solid support 23, which support is made of an ingestible material, e.g., as described above. Structure 21 may be placed onto support 23 in a manner such that the two components are stably associated with each other, e.g., by press-fitting the structure 21 onto support 23 or gluing structure 21 onto support 23, among other ways to immobilize structure 21 onto support 23. While the sequence shown in FIGS. 2A and 2B illustrate a protocol in which structure 21 is produced before placement on support 23, in another embodiment the metallic foil 22 is first placed on support 23. Following placement of metallic foil 22 on support 23, the patterned areas of electrode material 24 are produced on the surface of metallic foil 22. In FIG. 2C, integrated circuit 25 is positioned in area 26 and connected to metallic foil 22. Finally, in FIG. 2D, a cover layer 27 (e.g., fabricated from the same material as the support) having electrode cutout areas 28 is stably positioned (e.g., with an ingestible adhesive) over structure 21 to produce a final ingestible circuit device that includes a solid support, an integrated circuit and four distinct surface electrodes. In this structure, the metallic foil layer 22 serves as the conductive interconnect between the different electronic components, i.e., the integrated circuit and electrodes, that are positioned on the surface of the support.

[0046] FIG. 3A illustrates another embodiment of a laminate process that may be employed to construct an ingestible circuit device of the invention. In FIG. 3A, structure 30 has been produced by first providing a release layer 31 on a backing layer 32. Metallic layer (e.g., gold) 33 has been deposited on the surface of release layer 31. Next, electrode material 34, e.g., CuCl, is deposited on surface of metallic layer 33. Finally, insulating layer 35 is positioned over electrode layer 34, which insulating layer may have cutout regions (not shown), e.g., as described in connection with the description of FIGS. 2A to 2D.

[0047] In FIG. 3B, an integrated circuit 36 having a layer of a second electrode material 37, e.g., Mg, on a surface thereof, is positioned in ingestible support 38. To assemble the final device, the release layer 31 and backing layer 32 are removed from structure 30, providing exposed metallic layer 33. This exposed metallic layer 33 is then positioned over circuit 36 and support 38 to yield the final desired device.

[0048] FIG. 4 illustrates a transfer protocol that may be employed to fabricate ingestible circuits in accordance with the invention. In FIG. 4, a circuit structure 40 that includes integrated circuit 41 connected to five different electrodes 42 via interconnecting conductive lines 43 is first produced on a removable backing 44. After production of circuit structure 40, backing 44 is removed and the circuit structure 44 is positioned on the surface of ingestible support 45. The protocol illustrated in FIG. 4 may be employed in processes where parameters of circuit structure production (e.g., chemicals, temperatures, pressures) are incompatible with the solid support material.

[0049] FIG. 5 illustrates a variation in which a conductive ink is employed to provide conductive interconnects between different components of an ingestible circuit device. In the device shown in FIG. 5, ingestible support 51 has displayed on its surface four different electrodes (made up of electrode material) 52. Positioned at a center region of support 51 are four contact pads 53. Interconnecting each electrode to a contact pad is a line of conductive ink material 54. To complete the structure, an integrated circuit is bonded to pads 53 and then a layer of protection material is positioned over the surface leaving exposed electrode elements, analogous to that shown in FIG. 2D.

[0050] In certain instances, laser patterning may be employed during fabrication of ingestible circuits of the invention, e.g., as illustrated in FIGS. 6A and 6B. In FIG. 6A, a blanket (i.e., non-patterned) layer of metal 61 is deposited on a surface of an ingestible support 62. Positioned on a portion of metal layer 61 is integrated circuit 63. Next, laser patterning

is employed to remove portions of metal layer **61** to produce antenna structure **64** and **65** on surface of support **62**.

[0051] Ingestible identifiers that include ingestible circuitry of the invention find use in a variety of different applications. One application of interest is the use of the ingestible identifiers as ingestible event markers (IEMs). Ingestible event markers can be used in both therapeutic and non-therapeutic applications, and are described in PCT application serial no. PCT/US2006/016370 published as WO/2006/116718; PCT application serial no. PCT/US2007/082563 published as WO/2008/052136; PCT application serial no. PCT/US2007/024225 published as WO/2008/063626; PCT application serial no. PCT/US2007/022257 published as WO/2008/066617; PCT application serial no. PCT/US2008/052845 published as WO/2008/095183; PCT application serial no. PCT/US2008/053999 published as WO/2008/101107; PCT application serial no. PCT/US2008/056296 published as WO/2008/112577; PCT application serial no. PCT/US2008/056299 published as WO/2008/112578; PCT application serial no. PCT/US2008/077753 published as WO2009/042812; PCT application serial no. PCT/US2008/085048 published as WO 2009/070773; and PCT application serial no. PCT/US2009/36231; as well as pending United States application serial nos. 12/126,792 and 12/126,798.

[0052] The disclosure of these ingestible event markers and applications for the same therein is specifically incorporated herein by reference. Therapeutic applications of ingestible identifiers are embodiments where, at least in some instances, the identifier is associated with a pharmaceutical composition. Medical embodiments of the present invention provide the clinician an important new tool in their therapeutic armamentarium: automatic detection and identification of pharmaceutical agents actually delivered into the body. The applications of this new information device and system are multi-fold. Applications include, but are not limited to: (1) monitoring patient compliance with prescribed therapeutic regimens; (2) tailoring therapeutic regimens based on patient compliance; (3) monitoring patient compliance in clinical trials; (4) monitoring usage of controlled substances; and the like. Each of these different illustrative applications is reviewed in greater detail in PCT application serial no. PCT/US2006/016370 published as WO/2006/116718; PCT application serial no. PCT/US2007/082563 published as WO/2008/052136; PCT application serial no. PCT/US2007/024225 published as WO/2008/063626; PCT application serial no. PCT/US2007/022257 published as WO/2008/066617; PCT application serial no. PCT/US2008/052845 published as WO/2008/095183; PCT application serial no. PCT/US2008/053999 published as WO/2008/101107; PCT application serial no. PCT/US2008/056296 published as WO/2008/112577; PCT application serial no. PCT/US2008/056299 published as WO/2008/112578; PCT application serial no. PCT/US2008/077753 published as WO2009/042812; PCT application serial no. PCT/US2008/085048 published as WO 2009/070773; and PCT application serial no. PCT/US2009/36231; as well as pending United States application serial nos. 12/126,792 and 12/126,798.

[0053] It is to be understood that this invention is not limited to particular embodiments described, as such may vary. It is also to be understood that the terminology used herein is for the purpose of describing particular embodiments only, and is not intended to be limiting, since the scope of the present invention will be limited only by the appended claims.

[0054] Where a range of values is provided, it is understood that each intervening value, to the tenth of the unit of the lower limit unless the context clearly dictates otherwise, between the upper and lower limit of that range and any other stated or intervening value in that stated range, is encompassed within the invention. The upper and lower limits of these smaller ranges may independently be included in the smaller ranges and are also encompassed within the invention, subject to any specifically excluded limit in the stated range. Where the stated range includes one or both of the limits, ranges excluding either or both of those included limits are also included in the invention.

[0055] Unless defined otherwise, all technical and scientific terms used herein have the same meaning as commonly understood by one of ordinary skill in the art to which this invention belongs. Although any methods and materials similar or equivalent to those described herein can also be used in the practice or testing of the present invention, representative illustrative methods and materials are now described.

[0056] The citation of any publication is for its disclosure prior to the filing date and should not be construed as an admission that the present invention is not entitled to antedate such publication by virtue of prior invention. Further, the dates of publication provided may be different from the actual publication dates which may need to be independently confirmed.

[0057] It is noted that, as used herein and in the appended claims, the singular forms "a", "an", and "the" include plural referents unless the context clearly dictates otherwise. It is further noted that the claims may be drafted to exclude any optional element. As such, this statement is intended to serve as antecedent basis for use of such exclusive terminology as "solely," "only" and the like in connection with the recitation of claim elements, or use of a "negative" limitation.

[0058] As will be apparent to those of skill in the art upon reading this disclosure, each of the individual embodiments described and illustrated herein has discrete components and features which may be readily separated from or combined with the features of any of the other several embodiments without departing from the scope of the present invention. Any recited method can be carried out in the order of events recited or in any other order which is logically possible.

[0059] Although the foregoing invention has been described in some detail by way of illustration and example for purposes of clarity of understanding, it is readily apparent to those of ordinary skill in the art in light of the teachings of this invention that certain changes and modifications may be made thereto without departing from scope of the appended claims.

[0060] Accordingly, the preceding merely illustrates the principles of the invention. It will be appreciated that those skilled in the art will be able to devise various arrangements which, although not explicitly described or shown herein, embody the principles of the invention and are included within its scope. Furthermore, all examples and conditional language recited herein are principally intended to aid the reader in understanding the principles of the invention and the concepts contributed by the inventors to furthering the art, and are to be construed as being without limitation to such specifically recited examples and conditions. The scope of the present invention, therefore, is not intended to be limited to the exemplary embodiments shown and described herein. Rather, the scope of present invention is embodied by the appended claims.

Claims

1. A method of producing an identifier to indicate the presence of conducting fluid, the method comprising:
 - laminating a non-conducting element between first and second dissimilar materials to create a support (722), wherein the first and second dissimilar materials generate a voltage potential when in contact with a conducting fluid;
 - removing a portion of the first and second dissimilar materials from the perimeter of the support (722) to expose the non-conducting element and to create a skirt (710);
 - securing a circuit within a hole formed in the support (722) using a conductive adhesive (726), wherein the circuit is electrically coupled to each of the first and second dissimilar materials; and
 - activating the circuit that controls the flow of current between the first and second dissimilar materials through the conducting fluid to indicate the presence of the conducting fluid.
2. The method of claim 1 further comprising creating a voltaic cell through oxidation and reduction reactions that occur when the first and second dissimilar materials are in contact with the conducting fluid.
3. The method of claim 2 further comprising producing a unique current signature that uniquely identifies the identifier.
4. The method of claim 1 wherein the conducting fluid is a physiological fluid.
5. The method of claim 1 further comprising securing the identifier to a pharmaceutical product to produce a tagged product such that activation of the circuit is an indication that the pharmaceutical product of the tagged product is in contact with physiological fluid.
6. The method of Claim 5 further comprising sealing the tagged product with a coating such that the tagged product is sealed from the physiological fluid for a predefined period of time until the coating is dissolved by the physiological fluid to allow the tagged product to reach a target site at which time the tagged product is exposed to the physiological fluid.
7. The method of claim 1, wherein the support comprises a current collector layer (712) between the non-conducting element and at least one of the first and second dissimilar materials.
8. The method of claim 1, further comprising punching the hole through the support to receive the circuit within the hole.

Patentansprüche

1. Ein Verfahren zum Erzeugen eines Identifikators, um das Vorhandensein eines leitenden Fluids anzuzeigen, wobei das Verfahren Folgendes beinhaltet:
 - Laminieren eines nicht leitenden Elements zwischen einem ersten und einem zweiten nicht artgleichen Material eines Trägers (722), wobei das erste und das zweite nicht artgleiche Material ein Spannungspotential generieren, wenn sie mit einem leitenden Fluid in Kontakt sind;
 - Entfernen eines Teils des ersten und des zweiten nicht artgleichen Materials von dem Umfang des Trägers (722), um das nicht leitende Element freizulegen und eine Randleiste (710) zu schaffen;
 - Sichern einer Schaltung innerhalb eines in dem Träger (722) ausgebildeten Lochs unter Verwendung von leitendem Klebstoff (726), wobei die Schaltung elektrisch mit jedem von dem ersten und dem zweiten nicht

artgleichen Material verbunden ist; und

Aktivieren der Schaltung, die den Stromfluss zwischen dem ersten und dem zweiten nicht artgleichen Material durch das leitende Fluid steuert, um das Vorhandensein des leitenden Fluids anzuzeigen.

- 5 2. Verfahren gemäß Anspruch 1, das weiterhin das Schaffen eines galvanischen Elements durch Oxidations- und Reduktionsreaktionen, die auftreten, wenn das erste und das zweite nicht artgleiche Material mit dem leitenden Fluid in Kontakt sind, beinhaltet.
- 10 3. Verfahren gemäß Anspruch 2, das weiterhin das Erzeugen einer eindeutigen Stromsignatur, die den Identifikator eindeutig identifiziert, beinhaltet.
4. Verfahren gemäß Anspruch 1, wobei das leitende Fluid ein physiologisches Fluid ist.
- 15 5. Verfahren gemäß Anspruch 1, das weiterhin das Sichern des Identifikators an einem pharmazeutischen Erzeugnis zum Erzeugen eines markierten Erzeugnisses beinhaltet, sodass die Aktivierung der Schaltung ein Anzeichen dafür ist, dass das pharmazeutische Erzeugnis des markierten Erzeugnisses mit dem physiologischen Fluid in Kontakt ist.
- 20 6. Verfahren gemäß Anspruch 5, das weiterhin das Abdichten des markierten Erzeugnisses mit einer Beschichtung beinhaltet, sodass das markierte Erzeugnis gegenüber dem physiologischen Fluid für eine vorher festgelegte Zeitspanne abgedichtet ist, bis die Beschichtung von dem physiologischen Fluid aufgelöst wird, um zu ermöglichen, dass das markierte Erzeugnis eine Zielstelle erreicht, zu welchem Zeitpunkt das markierte Erzeugnis dem physiologischen Fluid ausgesetzt wird.
- 25 7. Verfahren gemäß Anspruch 1, wobei der Träger eine Stromkollektorschicht (712) zwischen dem nicht leitenden Element und mindestens einem von dem ersten und dem zweiten nicht artgleichen Material beinhaltet.
8. Verfahren gemäß Anspruch 1, das weiter das Stanzen des Lochs durch den Träger beinhaltet, um die Schaltung innerhalb des Lochs aufzunehmen.

30

Revendications

- 35 1. Une méthode de production d'un identificateur pour indiquer la présence de fluide conducteur, la méthode comprenant :
- 40 la disposition en strate d'un élément non conducteur entre des premier et deuxième matériaux dissemblables pour créer un support (722), les premier et deuxième matériaux dissemblables générant un potentiel de tension quand ils sont en contact avec un fluide conducteur ;
le retrait d'une portion des premier et deuxième matériaux dissemblables du périmètre du support (722) pour exposer l'élément non conducteur et pour créer une jupe (710) ;
la fixation d'un circuit au sein d'un trou formé dans le support (722) à l'aide d'un adhésif conducteur (726), le circuit étant couplé électriquement à chacun des premier et deuxième matériaux dissemblables ; et
l'activation du circuit qui contrôle le flux de courant entre les premier et deuxième matériaux dissemblables à travers le fluide conducteur pour indiquer la présence du fluide conducteur.
- 45 2. La méthode de la revendication 1 comprenant en outre la création d'une cellule voltaïque par le biais de réactions d'oxydation et de réduction qui ont lieu quand les premier et deuxième matériaux dissemblables sont en contact avec le fluide conducteur.
- 50 3. La méthode de la revendication 2 comprenant en outre la production d'une signature de courant unique qui identifie l'identificateur de manière unique.
4. La méthode de la revendication 1 dans laquelle le fluide conducteur est un fluide physiologique.
- 55 5. La méthode de la revendication 1 comprenant en outre la fixation de l'identificateur à un produit pharmaceutique pour produire un produit marqué de sorte que l'activation du circuit est une indication que le produit pharmaceutique du produit marqué est en contact avec le fluide physiologique.

EP 2 313 003 B1

6. La méthode de la revendication 5 comprenant en outre l'étanchéification du produit marqué avec un revêtement de sorte que le produit marqué est étanche au fluide physiologique pendant une période de temps prédéfinie jusqu'à ce que le revêtement soit dissous par le fluide physiologique pour permettre au produit marqué d'atteindre un site cible, moment auquel le produit marqué est exposé au fluide physiologique.

5
7. La méthode de la revendication 1, dans laquelle le support comprend une couche de collecteur de courant (712) entre l'élément non conducteur et au moins un des premier et deuxième matériaux dissemblables.

10
8. La méthode de la revendication 1, comprenant en outre la perforation du trou à travers le support pour recevoir le circuit au sein du trou.

15

20

25

30

35

40

45

50

55




FIG. 1




FIG. 2A




FIG. 2B




FIG. 2C




FIG. 2D




FIG. 3A




FIG. 3B




FIG. 4




FIG. 5




FIG. 6B




FIG. 6A




FIG. 7A




FIG. 7B

REFERENCES CITED IN THE DESCRIPTION

This list of references cited by the applicant is for the reader's convenience only. It does not form part of the European patent document. Even though great care has been taken in compiling the references, errors or omissions cannot be excluded and the EPO disclaims all liability in this regard.

Patent documents cited in the description

- US 5604531 A, Iddan [0002]
- US 7009634 B [0002]
- US 6800060 B [0002]
- US 20070008113 A, Spoonhauer [0004]
- WO 2006116718 A2 [0006]
- US 2006016370 W [0027] [0035] [0051] [0052]
- US 2007022257 W [0027] [0035] [0051] [0052]
- US 2007082563 W [0027] [0035] [0036] [0051] [0052]
- US 2008052845 W [0027] [0035] [0051] [0052]
- US 2008053999 W [0027] [0035] [0051] [0052]
- US 2008077753 W [0027] [0035] [0051] [0052]
- US 60975108 B [0034]
- WO 2006116718 A [0035] [0051] [0052]
- WO 2008052136 A [0035] [0051] [0052]
- US 2007024225 W [0035] [0051] [0052]
- WO 2008063626 A [0035] [0051] [0052]
- WO 2008066617 A [0035] [0051] [0052]
- WO 2008095183 A [0035] [0051] [0052]
- WO 2008101107 A [0035] [0051] [0052]
- US 2008056296 W [0035] [0051] [0052]
- WO 2008112577 A [0035] [0051] [0052]
- US 2008056299 W [0035] [0051] [0052]
- WO 2008112578 A [0035] [0051] [0052]
- WO 2009042812 A [0035] [0051] [0052]
- US 2008085048 W [0035] [0051] [0052]
- WO 2009070773 A [0035] [0051] [0052]
- US 200936231 W [0035] [0051] [0052]
- US 12126792 B [0035] [0051] [0052]
- US 12126798 B [0035] [0051] [0052]

专利名称(译)	可吸收电路		
公开(公告)号	EP2313003B1	公开(公告)日	2016-08-03
申请号	EP2009807292	申请日	2009-08-13
[标]申请(专利权)人(译)	普罗秋斯生物医学公司		
申请(专利权)人(译)	PROTEUS生物医学, INC.		
当前申请(专利权)人(译)	PROTEUS数字医疗, INC.		
[标]发明人	HAFEZI HOOMAN SNYDER ERIC COSTELLO BENEDICT		
发明人	HAFEZI, HOOMAN SNYDER, ERIC COSTELLO, BENEDICT		
IPC分类号	A61B5/07 A61B5/00 G05F1/00		
CPC分类号	A61K9/0097 A23P20/20 A61B5/0031 A61B5/06 A61B5/073 A61B5/42 A61B5/4833 A61B5/4839 A61B5/6861 A61B5/6871 A61B5/6873 A61J3/007 A61J3/06 A61J2200/30 A61J2205/60 A61K9/4825 A61K9/4833 G01N33/15 H01M6/00 H05K13/00 Y10S128/903 Y10T29/49108 Y10T29/49124		
优先权	61/088355 2008-08-13 US		
其他公开文献	EP2313003A2 EP2313003A4		
外部链接	Espacenet		

摘要(译)

本发明提供了可用于可摄取组合物的安全可靠的电子电路。本发明的可摄取电路包括固体支持物;导电元件;和电子元件。每个支撑件, 导电元件和电子元件由可摄取材料制成。可摄取的电路可用于各种不同的应用, 包括作为可摄取标识符的组分, 例如可在可摄取事件标记物中找到的, 例如, 启用药物信息学的药物组合物。




FIG. 1