

(19)



(11)

EP 2 593 002 B1

(12)

EUROPEAN PATENT SPECIFICATION

(45) Date of publication and mention of the grant of the patent:
07.06.2017 Bulletin 2017/23

(51) Int Cl.:
A61B 5/00 ^(2006.01) **A61B 5/0478** ^(2006.01)
A61B 5/0408 ^(2006.01)

(21) Application number: **11730665.4**

(86) International application number:
PCT/EP2011/061618

(22) Date of filing: **08.07.2011**

(87) International publication number:
WO 2012/007384 (19.01.2012 Gazette 2012/03)

(54) **TEXTILE ELECTRODE**

TEXTILE ELEKTRODE

ÉLECTRODE TEXTILE

(84) Designated Contracting States:
AL AT BE BG CH CY CZ DE DK EE ES FI FR GB GR HR HU IE IS IT LI LT LU LV MC MK MT NL NO PL PT RO RS SE SI SK SM TR

- **DELIEGE, Benjamin**
B-4800 Verviers (BE)

(30) Priority: **13.07.2010 EP 10169351**

(74) Representative: **Pronovem**
Office Van Malderen
Parc d'affaires Zénobe Gramme- bâtiment K
Square des Conduites d'Eau 1-2
4020 Liège (BE)

(43) Date of publication of application:
22.05.2013 Bulletin 2013/21

(73) Proprietor: **CECOTEPE asbl**
4100 Seraing (BE)

(56) References cited:
WO-A1-2008/022482 **WO-A2-2007/092290**
WO-A2-2008/109699 **WO-A2-2009/013704**
US-A- 3 989 035 **US-A- 4 444 194**
US-A1- 2007 078 324 **US-A1- 2008 154 111**
US-A1- 2009 076 362 **US-A1- 2009 105 577**

(72) Inventors:
• **NINANE, Christian**
B-4020 Liège (BE)

Note: Within nine months of the publication of the mention of the grant of the European patent in the European Patent Bulletin, any person may give notice to the European Patent Office of opposition to that patent, in accordance with the Implementing Regulations. Notice of opposition shall not be deemed to have been filed until the opposition fee has been paid. (Art. 99(1) European Patent Convention).

EP 2 593 002 B1

Description**Field of the Invention**

- 5 **[0001]** The present invention is related to a textile electrode for measuring an electrical signal from a body part.
[0002] Another aspect of the invention is related to a clothing comprising such an electrode.

State of the Art

- 10 **[0003]** Medical electrodes are known in the art. Usually, those electrodes comprise a metallic surface in close contact with the skin. They are fixed on the skin by means of an adhesive, and the impedance between the skin and the metallic surface is reduced by the use of a conductive gel, for example silver gel or the use of a sponge-like material filled with an aqueous solution containing an electrolyte. Such type of electrodes is for example disclosed in document US 3,845,757. Such type of electrodes will be referred hereafter as standard medical electrodes, or prior art medical electrodes.
- 15 **[0004]** Prior art medical electrodes suffer several drawbacks. For example, particular care is to be taken to obtain good adhesion between the skin and the electrode (i.e. the skin should be shaved and cleaned). In order to avoid failure of the adhesive, for example, the conductive gel should not contaminate the adhesive surface, as it can inhibit the adhesion. Finally, the use of such electrode is somewhat uncomfortable. This is particularly true for long term measurement, for example in the field of sleepiness studies.
- 20 **[0005]** WO-A-01/02052 discloses a garment, adapted to be used as a medical electrode. The garment comprises a tubular body, which comprises at least two different zones. One of these zones is an electrically conductive zone, to be used as the electrode surface of the medical electrode. Another zone is an elastic zone, which comprises electrically non-conductive yarns. This elastic zone assures the position of the electrically conductive zone on the corpus on which the medical electrode is to be used.
- 25 **[0006]** It is known that the contact electrical resistance between such textile based electrode and the skin of a wearer to which the electrode is applied is high enough to render detection of electrical signals difficult. The contact electrical resistance in that case is further negatively impacted by the wearer movements, reducing the signal-to-noise ratio. This can be partly reduced by the presence of moisture, due either to perspiration in case of measurements during sport exercise, or to the addition of a conductive gel applied on the electrode.
- 30 **[0007]** Unfortunately, perspiration is not always present, and the addition of gel has only a transient effect, as the gel solvent has a tendency to evaporate. The disclosed electrode is therefore not suitable for measuring small electrical signals such as EEG, in a long term experiment and more particularly with patient at rest. On the one hand, such EEG measurements are key data in the study for example of sleepiness, wherein, on the other hand, the modification of the comfort of the sleeper should be as small as possible.
- 35 **[0008]** Document WO 2004/058346 discloses an electrode arrangement wherein the conductive contact with the skin is obtained with a moisture impermeable electrode, thereby maximising the appearance of perspiration and reducing contact resistance. Again, due to its rigidity, this electrode is a bit uncomfortable and not suitable for a user at rest or relaxed, or in skin parts producing a small amount of perspiration such as the human head in normal rest conditions where the patient is not stressed.
- 40 **[0009]** US2009076362 discloses a textile electrode comprising a fabric absorbent electrically isolating material to be in contact with the skin and that becomes conductive upon being wet.

Aims of the Invention

- 45 **[0010]** The present invention aims to provide a textile electrode that overcomes the drawbacks of prior art.
[0011] More particularly, the present invention aims to provide a textile electrode able to measure small electrical signals such as EEG signals in long term experiment, preferably lasting more than 12 hours.
[0012] Furthermore, the present invention aims to provide a textile electrode complying with usual sleeping conditions.

Summary of the Invention

- 50 **[0013]** The present invention is related to a textile electrode for measuring an electrical signal from a body according to claim 1.
[0014] According to particular preferred embodiments, the invention further discloses at least one or a suitable combination of the following features:
- 55
- the water vapour transmission rate of the vapour barrier sheet material is lower than 100 g/m².day;
 - the water vapour transmission rate of the vapour barrier sheet material is lower than 50 g/m².day;

- the textile contact is impregnated with a conductive gel;
- the absorbent material is impregnated with the conductive gel, or with a solvent of the conductive gel;
- an outer electrical contact is connected to the conductive textile contact and located on the external side of said barrier sheet material;
- 5 - the vapour barrier sheet material comprises a polymeric layer;
- the polymeric layer comprises a polymer selected from the group consisting of PEEK, polyimide, polyamide-imide, polyethersulfone, polysulfone, liquid crystalline polymers, polyester and their blends;
- the polymeric layer comprises a polymer selected from the group consisting of EPDM, ethylene vinyl acetate, SIS, SEBS, ethylene-propylene-rubber, synthetic or natural rubber, their copolymers and their blends;
- 10 - the vapour barrier sheet material further comprises a metallic or a metal oxide layer;
- an electrical circuit is printed onto said metallic layer;
- the textile electrode further comprises electronic devices for treating, in use, the signal induced by said body part;
- said electronic devices comprise amplification means and/or wireless communication means;
- the vapour barrier sheet material is flexible;
- 15 - the barrier sheet material is attached on the textile support by means of an adhesive and/or by sewing it along its perimeter on the textile support.

[0015] Another aspect of the invention is related to a clothing comprising at least one electrode according to the invention.

20 [0016] Preferably, the clothing of the invention is suitable for disposing said electrode in contact with the head of a patient.

[0017] The present invention is also related to the use of a clothing according the invention for measuring an EEG signal or an EMG signal.

25 **Brief Description of the Drawing**

[0018]

30 Fig. 1 schematically represents a cross-section view of an example of a textile electrode according to the present invention.

Fig. 2 schematically represents an example of a clothing (head band) including textile electrodes according to the invention.

Fig. 3 represents a picture of an electrode according to the invention.

35 Fig. 4 schematically represents the experimental testing setup of an example of textile electrode according to the invention.

Fig. 5 represents a comparison of the impedance of an electrode according to the invention and a prior art medical electrode respectively, as a function of frequency.

Fig. 6 represents weight loss measurement of different electrode arrangements (gel solvent losses).

40 **Figure keys**

[0019]

- 45 1. Electrode
- 2. Textile support
- 3. Conductive textile contact
- 4. Liquid absorbing material
- 5. Electrical wire
- 6. Outer electrical contact
- 50 7. Barrier sheet material
- 8. Clothing
- 9. Connection wires
- 10. EEG interface
- 11. Patient's head
- 55 12. AC Voltage source
- 13. Oscilloscope
- 14. Resistance

Detailed Description of the Invention

5 [0020] The electrode of the present invention comprises a conductive textile 3, for example made of conductive silver thread, for providing a contact with the skin. When placed on the skin, and due to its softness, such a contact improves the comfort of the wearer in comparison to rigid contacts.

[0021] In order to dispose the contact in the right place on a body part where an electrical signal has to be measured, the conductive contact is supported by a textile 2. In order to improve the comfort of the device, and improve the stability of the obtained contact, support textile has preferably elastic properties. This can be obtained for example by the use of a knitted jersey, using conventional fibres.

10 [0022] In order to increase the electrical contact between the skin and the conductive textile, the conductive textile is preferably impregnated by a conductive gel or a conductive liquid. As such liquid or gel are generally volatile, the impregnation is usually performed just before use. The use of such liquids or gels reduces the contact impedance of the electrode in such a way that very small electrical signals, such as those measured in EEG, can be easily measured.

15 [0023] In order to reduce the evaporation of the gel solvent, which degrades the quality of the electrical contact, a moisture barrier sheet material 7 is applied on the back side of the textile support 2. It was then discovered that the latter considerably reduces the evaporation of the conductive gel or gel solvent, thereby improving the possible time of continuous measurement. Such moisture barrier sheet material would advantageously extend on a surface a bit larger than the underlying conductive textile contact 3, in order to minimise the solvent evaporation. A barrier sheet having dimensions 10% to 20% larger than the contact is a good compromise between evaporation reduction and comfort improvement.

20 [0024] Preferably, the barrier sheet material has a water vapour transmission rate (WVTR), also called moisture vapour transmission rate (MVTR), lower than about 100 g/m².day, more preferably lower than about 50 g/m².day, ideally lower than about 25 g/m².day. WVTR in the present invention is measured according to ASTM E-96-92.

[0025] Advantageously, the support textile 2 is hydrophobic, in order to reduce lateral migration of the liquid by capillarity.

25 [0026] To further improve the possible continuous measurement time, an additional quantity of conductive gel or gel solvent can advantageously be stored in an intermediate absorbing layer 4. This layer can be either a sponge-like material or, preferably, an additional textile layer. This additional textile layer can preferably be obtained by 3 dimensional weaving. Advantageously, this absorbing layer is hydrophilic, in order to store a high quantity of solvent, thereby increasing the possible measurement time. Such an electrode is represented in fig. 1.

30 [0027] This additional layer can also improve the electrical contact by having the sensing surface on a protrusion standing out of the textile surface.

[0028] Advantageously, the barrier sheet material will exhibit elastomeric properties, in order to reduce the impact on the mechanical properties of the device. This can be obtained by the use of polymers selected from the group consisting of EPDM, ethylene vinyl acetate, SIS, SEBS, ethylene-propylene-rubber, synthetic or natural rubber, their copolymers and their blends. Alternatively, the barrier sheet material can comprise a polymer selected from the group consisting of PEEK, polyimide, polyamide-imide, polyethersulfone, polysulfone, liquid crystalline polymers such as those commercialised under the tradename Vectra®, polyester and their blends. These last polymers are suitable as the supporting layer for making flexible printed circuit board.

35 [0029] In order to increase its barrier properties, the barrier sheet material is advantageously a multilayer film comprising a vapour barrier material. Preferably, at least one layer of said multilayer film is a metallic or metal oxide layer.

40 [0030] More preferably, the outer layer (the layer on the side opposed to the textile on which the barrier sheet is fixed) is a metallic layer. This metallic layer, additionally to the barrier improvement, may advantageously be used to produce a printed circuit board on the back side of the electrode. In that case, the metallic area left after printing will reduce the effective area available for water vapour transmission, reducing the total evaporation rate of the electrode.

45 [0031] In order to simplify the connection of the electrode 1 to an acquisition device 10, an outer electrical contact 6 can be available on the back side of the moisture barrier sheet material 7. This contact can be connected to the conductive textile contact 3 by means of an electrical wire 5. The connection between the contact 6 and the acquisition device 10 can then be assured by means of a wire 9, or any other communication means.

50 [0032] Preferably, the barrier sheet material comprises on its back side a printed circuit board (PCB), more preferably, a flexible PCB. This permits to provide an electronic circuit directly placed on the electrode. For example, the circuit may comprise amplification means such as a differential amplifier closest to the contact. This proximity may reduce the noise level, thereby improving the signal-to-noise ratio. In a particular embodiment, the electrode may be reduced to this mere circuit but with the disadvantage that the textile sensation is much more comfortable for the skin and that the textile structure is more favourable for the gel repartition.

55 [0033] The electrode of the present invention can advantageously be integrated in a wearable clothing 8, as schematically represented in fig. 2. Preferably, said clothing 8 exhibits high elasticity, in order to regulate the pressure applied between the conductive textile 3 and the body part. This clothing 8 can advantageously comprise further elements, such as accumulators, signal recorder and/or wireless communication devices, so that no wire has to be connected to external devices upon use, thereby further improving the comfort of the wearer.

[0034] All those advantages render the clothing of the present invention particularly adapted to EEG measurements in sleepiness studies, particularly by reducing the sleeper perturbation arising from the different connections to external devices needed in such experiment. In such studies, minimum measurement time and user comfort are key parameters. For that reason, the electrodes of the present invention may advantageously be integrated in a bonnet or a hat-like clothing.

[0035] The clothing of the present invention may also be advantageously for use in paediatric studies.

[0036] It is also to be noticed that the gel impregnation is easier in the electrode of the invention and may be performed by an untrained user without risk, contrary to prior art medical electrodes wherein bad positioning of the gel may reduce the adhesion of the electrode. In the electrode of the invention, this adhesion and the resulting quality contact is better secured by the elastic pressure applied by the elasticity of the textile used.

Example

[0037] Three examples of electrodes according to the invention have been produced, and their performance has been compared with standard medical electrodes. Fig. 3 represents a picture of one of those electrodes.

[0038] As seen in fig. 3, the textile contacts are integrated in jersey textile. The textile structure is, from skin contact to outer side: conductive textile/support textile/barrier sheet material.

[0039] The conductive textile is a double knitted jersey incorporating polyamide fibres coated with silver (Shieldex 235/34dtex 2ply HC). The supporting textile is an interlock polyester jersey, acting also as an isolating layer. And, finally, the barrier sheet layer is a dielectric polyimide (Kapton™) film of 50 μm, with a superimposed copper layer of 35 μm (PCB flex). The PCB sheet is extending 0.5 cm away from the limits of the subjacent contact area.

[0040] According to WVTR reported in the literature, 50 μm Kapton films have a WVTR of lower than about 27 g/m².day (largest reported value). This value is further reduced by the presence of the metalized area left by the PCB, a 35 μm copper layer being considered as an absolute barrier layer.

[0041] The conductive gel is a silver containing gel, commercialised under the tradename "Brygel ECG ". The latter is a commonly used gel in the field of EEG measurement.

[0042] Two electrodes are integrated in the support, which has the shape of an elastic band, having a tuneable length. The general electric setup is represented in fig. 4. The distance between the electrodes is approximately 11 cm and the electrodes are maintained on the forehead of a patient with a constant pressure. An additional ground electrode is placed on the wearer skin. A sinusoidal signal of 5 Vpp is injected from the AC voltage source 12 in the first electrode. At the output of the second electrode a resistance 14 is placed having a magnitude order similar to that of the impedance to be measured. Measurements are performed with an oscilloscope 13.

[0043] When conductive gel is used in the impedance measurement, about 0.5 g is deposited directly on the contact before the measurement.

[0044] In all impedance measurements, a quasi static impedance has been measured by means of a 10 Hz signal. In order to evaluate the noise level, the 50 Hz signal arising from the electric distribution system has been measured.

[0045] Three textile electrodes dimensions have been used, having respectively 1, 2 and 4 square cm. The impedance has been measured on both dry electrodes, and on electrodes with gel. The results obtained by those electrodes have been compared with a prior art medical electrode having a gel contact area of about 2 square cm and a metallic electrode of 0.8 square cm. No measurements were performed on dry prior art medical electrodes. The results are summarised in table 1.

Table 1

	Prior art medical electrode	Textile 1 cm ²	Textile 2 cm ²	Textile 4 cm ²
Dry electrode 10 Hz	-	505 kΩ	-	40.4 kΩ
With Gel 10 Hz	10 kΩ	47 kΩ	-	7.4 kΩ
With gel, 100 Hz	8.9 kΩ	21.45 kΩ	13.5 kΩ	6.2 kΩ
1 kHz with gel	4.2 kΩ	5.6 kΩ	3.7 kΩ	1.6 kΩ
10 kHz with gel	0.832 kΩ	0.654 kΩ	0.54 kΩ	0.33 kΩ

[0046] The results in table 1 show that all the proposed surfaces are acceptable, with a surface of 3.25 square cm for obtaining the properties closest to the prior art medical electrodes (usual standard).

[0047] The noise arising from 50 Hz electric distribution has also been estimated. Table 2 summarise the (unwanted) 50 Hz measured voltage amplitude of the raw signal component (units: volt).

Table 2

	Prior art medical electrode	Textile 1 cm ²	Textile 4 cm ²
Dry electrode	-	0.156	0.064
With Gel	0.03	0.052	0.016

[0048] Figure 5 represents the impedance variation of the textile electrode of a 4 square cm conductive textile contact according to the invention (curve A) compared to the impedance of the prior art medical electrode (curve B), over a large range of frequencies. These results demonstrate the ability of such electrode to record electrical signal over a wide frequency range. By means of the embedded electronics as described above, the direct impedance of the electrode according the invention can even be reduced as compared with the prior art medical electrode, with a noise level also reduced.

[0049] Figure 6 represents the weight loss of different electrode setups as a function of time. In all cases, about 1 g of conductive gel has been deposited on the electrode, and each electrode has been disposed on a moisture impermeable surface. Curve C represents the weight loss in the case of a textile electrode without a moisture barrier sheet material on the back side. Curve D represents the case when the back side barrier sheet material is adhesively positioned by means of glue on almost the entire surface of the barrier sheet material. Curve E represents the weight loss in the case of a conductive textile electrode with a moisture barrier sheet material sewed on the back side of the electrode. In E, the sewed area is located in the perimeter of the barrier film. In order to mechanically secure the electrode of the invention, the use of both adhesive bonding and sewing the perimeter is preferred. One sees that the variation of the weight of gel with time is much stronger in the case of an electrode without a moisture barrier sheet (curve C). The difference between curves D and E is that, in the bonded case, the meshes are maintained much more tight, which further reduces the loss of gel moisture. Qualitatively, for the two electrodes with moisture barrier, the remaining gel is of similar aspect as the gel initially deposited. In the case without moisture barrier, the gel becomes dry and sticky.

Claims

1. Textile electrode (1) for measuring an electrical signal from a body part, said electrode comprising, successively from the side to be applied on the body part to the outside:
 - a conductive textile contact (3) adapted to be applied to said body part;
 - a textile support (2) for supporting said textile contact (3);
 - a vapour barrier sheet material (7) able to reduce, in use, evaporation of liquid from said textile electrode (1);
 - an absorbent material (4) able to store a liquid or a gel, **characterised in that** said absorbent material is disposed between said conductive textile (3) and said textile support (2).
2. Textile electrode according to claim 1 wherein the water vapour transmission rate of the vapour barrier sheet material is lower than 100 g/m².day, preferably lower than 50 g/m².day.
3. Textile electrode (1) according to any of the preceding claims, wherein said textile contact (3) is impregnated with a conductive gel.
4. Textile electrode according to any of the previous claims, wherein said absorbent material (4) is impregnated with the conductive gel, or with a solvent of the conductive gel.
5. Textile electrode according to any of the previous claims, wherein an outer electrical contact (6) is connected to the conductive textile contact (3) and located on the external side of said barrier sheet material.
6. Textile electrode according to any of the preceding claims, wherein the vapour barrier sheet material (7) comprises a polymeric layer.
7. Textile electrode according to claim 6, wherein the polymeric layer comprises a polymer selected from the group consisting of PEEK, polyimide, polyamide-imide, polyethersulfone, polysulfone, liquid crystalline polymers, polyester and their blends.

EP 2 593 002 B1

8. Textile electrode according to claim 6, wherein the polymeric layer comprises a polymer selected from the group consisting of EPDM, ethylene vinyl acetate, SIS, SEBS, ethylene-propylene-rubber, synthetic or natural rubber, their copolymers and their blends.
- 5 9. Textile electrode according to any of claims 6 to 8, wherein the vapour barrier sheet material further comprises a metallic or a metal oxide layer.
10. Textile electrode according to claim 9, wherein an electrical circuit is printed onto said metallic layer (7).
- 10 11. Textile electrode according to claim 10, further comprising electronic devices for treating, in use, the signal induced by said body part.
12. Textile electrode according to claim 11, wherein said electronic devices comprise amplification means and/or wireless communication means.
- 15 13. Clothing comprising at least one electrode (1) according to any of the previous claims.
14. Clothing according to claim 13, wherein said clothing is suitable for disposing said electrode (1) in contact with the head (11) of a patient.
- 20

Patentansprüche

- 25 1. Textile Elektrode (1) zum Messen eines elektrischen Signals von einem Körperteil, wobei die Elektrode aufeinanderfolgend von der Seite, die auf den Körperteil angebracht werden soll, nach außen Folgendes umfasst:
- einen leitenden textilen Kontakt (3), der angepasst ist, um auf den Körperteil angebracht zu werden;
 - einen textilen Träger (2), um den textilen Kontakt (3) zu tragen;
 - ein Dampfbarrieren-Blattmaterial (7), das dazu in der Lage ist, bei der Verwendung eine Verdampfung von Flüssigkeit aus der textilen Elektrode (1) zu reduzieren;
 - ein absorbierendes Material (4), das dazu in der Lage ist, eine Flüssigkeit oder ein Gel zu speichern, **dadurch gekennzeichnet, dass** das absorbierende Material zwischen dem leitenden Textil (3) und dem textilen Träger (2) angeordnet ist.
- 30
- 35 2. Textile Elektrode nach Anspruch 1, wobei die Wasserdampf-Übertragungsrate des Dampfbarrieren-Blattmaterials geringer als 100 g/m² pro Tag, vorzugsweise geringer als 50 g/m² pro Tag ist.
3. Textile Elektrode (1) nach einem der vorhergehenden Ansprüche, wobei der textile Kontakt (3) mit einem leitenden Gel imprägniert ist.
- 40 4. Textile Elektrode nach einem der vorhergehenden Ansprüche, wobei das absorbierende Material (4) mit dem leitenden Gel oder mit einem Lösemittel des leitenden Gels imprägniert ist.
- 45 5. Textile Elektrode (1) nach einem der vorhergehenden Ansprüche, wobei ein äußerer elektrischer Kontakt (6) mit dem leitenden textilen Kontakt (3) verbunden ist und sich auf der äußeren Seite des Barrieren-Blattmaterials befindet.
6. Textile Elektrode (1) nach einem der vorhergehenden Ansprüche, wobei das Dampfbarrieren-Blattmaterial (7) eine polymere Schicht umfasst.
- 50 7. Textile Elektrode nach Anspruch 6, wobei die polymere Schicht ein Polymer umfasst, ausgewählt aus der Gruppe, bestehend aus PEEK, Polyimid, Polyamid-imid, Polyethersulfon, Polysulfon, flüssigen kristallinen Polymeren, Polyester und ihren Mischungen.
- 55 8. Textile Elektrode nach Anspruch 6, wobei die polymere Schicht ein Polymer umfasst, ausgewählt aus der Gruppe, bestehend aus EPDM, Ethylvinylacetat, SIS, SEBS, Ethylen-Propylen-Gummi, synthetischem oder natürlichem Gummi, ihren Copolymeren und ihren Mischungen.
9. Textile Elektrode nach einem der Ansprüche 6 bis 8, wobei das Dampfbarrieren-Blattmaterial weiter eine metallische

oder Metalloxid-Schicht umfasst.

10. Textile Elektrode nach Anspruch 9, wobei eine elektrische Schaltung auf die Metallschicht (7) gedruckt ist.

5 11. Textile Elektrode nach Anspruch 10, weiter umfassend elektronische Vorrichtungen zur Behandlung bei Verwendung des Signals, das durch den Körperteil induziert wird.

12. Textile Elektrode nach Anspruch 11, wobei die elektronischen Vorrichtungen Amplifizierungsmittel und/oder drahtlose Kommunikationsmittel umfassen.

10 13. Kleidung, umfassend mindestens eine Elektrode (1) nach einem der vorhergehenden Ansprüche.

14. Kleidung nach Anspruch 13, wobei die Kleidung dazu geeignet ist, die Elektrode (1) in Kontakt mit dem Kopf (11) des Patienten anzuordnen.

15

Revendications

20 1. Electrode textile (1) pour mesurer un signal électrique provenant d'une partie de corps, ladite électrode comprenant, successivement en partant du côté devant être appliqué sur la partie de corps vers l'extérieur :

- un contact textile conducteur (3) adapté pour être appliqué à ladite partie de corps ;
- un support textile (2) pour supporter ledit contact textile (3) ;
- un matériau de feuille formant barrière à la vapeur (7) capable de réduire, en cours d'utilisation, l'évaporation de liquide à partir de ladite électrode textile (1) ;
- un matériau absorbant (4) capable de stocker un liquide ou un gel, **caractérisé en ce que** ledit matériau absorbant est disposé entre ledit textile conducteur (3) et ledit support textile (2).

25

30 2. Electrode textile selon la revendication 1, dans laquelle la vitesse de transmission de vapeur d'eau du matériau de feuille formant barrière à la vapeur est inférieure à 100 g/m² par jour, de préférence, inférieure à 50 g/m² par jour.

3. Electrode textile (1) selon l'une quelconque des revendications précédentes, dans laquelle ledit contact textile (3) est imprégné d'un gel conducteur.

35 4. Electrode textile selon l'une quelconque des revendications précédentes, dans laquelle ledit matériau absorbant (4) est imprégné du gel conducteur, ou d'un solvant du gel conducteur.

40 5. Electrode textile selon l'une quelconque des revendications précédentes, dans laquelle un contact électrique externe (6) est connecté au contact textile conducteur (3) et placé sur le côté externe dudit matériau de feuille barrière.

6. Electrode textile selon l'une quelconque des revendications précédentes, dans laquelle le matériau de feuille formant barrière à la vapeur (7) comprend une couche polymère.

45 7. Electrode textile selon la revendication 6, dans laquelle la couche polymère comprend un polymère choisi dans le groupe constitué de PEEK, de polyimide, de polyamide-imide, de polyéthersulfone, de polysulfone, de polymères cristallins liquides, de polyester et de leurs mélanges.

50 8. Electrode textile selon la revendication 6, dans laquelle la couche polymère comprend un polymère choisi dans le groupe constitué d'EPDM, d'éthylène-acétate de vinyle, de SIS, de SEBS, de caoutchouc éthylène-propylène, de caoutchouc synthétique ou naturel, de leurs copolymères et de leurs mélanges.

9. Electrode textile selon l'une quelconque des revendications 6 à 8, dans laquelle le matériau de feuille formant barrière à la vapeur comprend en outre une couche métallique ou d'oxyde de métal.

55 10. Electrode textile selon la revendication 9, dans laquelle un circuit électrique est imprimé sur ladite couche métallique (7).

11. Electrode textile selon la revendication 10, comprenant en outre des dispositifs électroniques servant à traiter, en

cours d'utilisation, le signal induit par ladite partie de corps.

12. Electrode textile selon la revendication 11, dans laquelle lesdits dispositifs électroniques comprennent des moyens d'amplification et/ou des moyens de communication sans fil.

5

13. Vêtement comprenant au moins une électrode (1) selon l'une quelconque des revendications précédentes.

14. Vêtement selon la revendication 13, dans lequel ledit vêtement est adapté pour disposer ladite électrode (1) en contact avec la tête (11) d'un patient.

10

15

20

25

30

35

40

45

50

55




Figure 1




Figure 2




Figure 3




Figure 4




Figure 5




Figure 6

REFERENCES CITED IN THE DESCRIPTION

This list of references cited by the applicant is for the reader's convenience only. It does not form part of the European patent document. Even though great care has been taken in compiling the references, errors or omissions cannot be excluded and the EPO disclaims all liability in this regard.

Patent documents cited in the description

- US 3845757 A [0003]
- WO 0102052 A [0005]
- WO 2004058346 A [0008]
- US 2009076362 A [0009]

专利名称(译)	纺织电极		
公开(公告)号	EP2593002B1	公开(公告)日	2017-06-07
申请号	EP2011730665	申请日	2011-07-08
[标]申请(专利权)人(译)	CECOTEPE ASBL		
申请(专利权)人(译)	CECOTEPE ASBL		
当前申请(专利权)人(译)	CECOTEPE ASBL		
[标]发明人	NINANE CHRISTIAN DELIEGE BENJAMIN		
发明人	NINANE, CHRISTIAN DELIEGE, BENJAMIN		
IPC分类号	A61B5/00 A61B5/0478 A61B5/0408		
CPC分类号	A61B5/04085 A61B5/0478 A61B5/4806 A61B5/6803 A61B5/6804		
优先权	2010169351 2010-07-13 EP		
其他公开文献	EP2593002A1		
外部链接	Espacenet		

摘要(译)

本发明涉及一种用于测量来自身体部位的电信号的纺织电极(1)，所述电极包括从待施加在身体部分上的一侧到外部的连续：导电织物触点(3)适用于所述身体部位；用于支撑所述织物触点(3)的织物支撑件(2)；一种蒸汽阻挡片材料(7)，其能够在使用中减少来自所述纺织电极(1)的液体的蒸发。




Figure 1




Figure 2