



(19) **United States**

(12) **Patent Application Publication**
Takahashi et al.

(10) **Pub. No.: US 2003/0018274 A1**

(43) **Pub. Date: Jan. 23, 2003**

(54) **HEART RATE MONITOR AND HEART RATE MEASURING METHOD**

(52) **U.S. Cl. 600/500**

(76) **Inventors: Yoshikazu Takahashi, Gunma-ken (JP); Wayne Baker, Shrewsbury, NJ (US); Hajime Shiogai, Gunma-ken (JP); Shinji Koshino, Gunma-ken (JP); Shintaro Mitsuhashi, Gunma-ken (JP)**

(57) **ABSTRACT**

Correspondence Address:
VENABLE
P.O. Box 34385
Washington, DC 20043-9998 (US)

Accurate occurrences of pulsation per unit time, that is, a heart rate is measured with a burden on a subject person being reduced to be very small and without being susceptible to body vibrations accompanying exercise. A heart rate monitor is produced, in which a light-emitting element 11 and a light-receiving element 12 are fitted to a head of a human body, light from the light-emitting element 11 is reflected at or transmitted through a subcutaneous artery 4 and/or blood running in the subcutaneous artery, the reflected or transmitted light is detected at the light-receiving element 12, and by using a CPU 14, the pulsation of the subcutaneous artery 4 and/or a change in bloodstream running in the subcutaneous artery 4 is measured from a change in intensity of the light detected at the light-receiving element 12, a pulse rate of the change in the bloodstream per unit time is calculated from this measured value, and the calculated pulse rate of the change in the bloodstream per unit time is regarded as a heart rate.

(21) **Appl. No.: 10/185,718**

(22) **Filed: Jul. 1, 2002**

(30) **Foreign Application Priority Data**

Jul. 19, 2001 (JP) 2001-219993

Publication Classification

(51) **Int. Cl.⁷ A61B 5/02**




FIG.1




FIG.2




FIG.3




FIG.4




FIG.5




FIG.6




FIG.7




FIG.8




FIG.9





FIG.10



HEART RATE MONITOR AND HEART RATE MEASURING METHOD

BACKGROUND OF THE INVENTION

[0001] 1. Field of the Invention

[0002] The present invention relates to a heart rate monitor for measuring the heart rate of a subject person while doing exercise such as running, jogging and walking, while doing light exercise, or during medical treatment.

[0003] It should be noted that the heart rate in this invention means "occurrences of pulse per unit time".

[0004] 2. Description of the Related Art

[0005] As a method of measuring a heart rate, there are conventionally a method of detecting an electrocardiographic signal from electrodes attached to an area near a heart as disclosed in Japanese Patent Application Laid-open No. 60-116325, a method of optically detecting a pulse rate from a blood vessel of a lobe as disclosed in Japanese Patent Application Publication No. 61-43057, a method of detecting pressure pulsation by mechanical vibration from an artery near a body surface as disclosed in U.S. Pat. No. 4,038,976, and a method in combination with a hemodynamometer as disclosed in Japanese Patent Application Laid-open No. 4-279146.

[0006] However, the prior arts described above have the following problems to be solved.

[0007] Specifically, at first, in the method of detecting an electrocardiographic signal from electrodes attached to an area near a heart, it is necessary to fix the electrodes for detecting an electrocardiographic signal in contact with the skin of a thorax, and thus a band with a stretching properties, wound around the thorax is usually used. For this reason, a subject person has to be naked temporarily so that this band can be attached to him or her, and the chest is secured with such strength as to prevent this band from falling off, which sometimes gives a feeling of strain to the subject person if it is attached to him or her for a long period of time. Further, even if a heart rate is measured by the electrocardiographic signal collected at the thorax, in order to transmit it to the subject person, it is necessary to provide a display unit at a wrist or the like and send a signal to the wrist from the thorax by means such as radio.

[0008] Next, in the method of optically detecting a pulse rate from a blood vessel of a lobe, if a subject person does hard exercise such as running, there is the possibility of a measurement error occurring when the pulse rate is optically detected under the influence of body vibrations.

[0009] Even if the pulse rate is to be measured at a blood vessel where arteriovenous anastomosis exists as the blood vessel of a lobe, the aforementioned arteriovenous anastomosis has the function of adjusting bloodstream based on correlation between outside temperature and body heat, and therefore the bloodstream is decreased by this adjustment function to make the measurement difficult in some cases.

[0010] Further, in the method of detecting pressure pulsation by mechanical vibration from an artery near a body surface, body vibration has more influence than in the aforementioned method of optically detecting a pulse rate,

and there is the possibility that a measurement error becomes large especially in the pulse rate detection during exercise.

[0011] In addition to it, in the method of performing detection in combination of a hemodynamometer, measurement can be made comparatively easily because a pulse rate is detected by an optical method or the like while a blood vessel is pressed with a cuff or the like. However, the burden that a measured region is pressed by the cuff or the like is imposed on the subject person during measurement.

[0012] In blood pressure measurement, the measurement is finished in a short time, and it is allowable that the measured region is pressed during that time. However, since heart rate measurement continues for a long time and measurement is needed during exercise, it is not preferable that the measured region is pressed by a cuff or the like.

[0013] The present invention is made in the aforementioned background, and is to provide a heart rate monitor, which imposes a very small burden on a subject person, is less susceptible to body vibrations accompanying exercise, and can measure the accurate occurrences of pulse per unit time, that is, a heart rate.

SUMMARY OF THE INVENTION

[0014] In order to solve the above-described disadvantage, trials and errors were repeated about taking out an accurate heart rate, with a burden on a subject person and a hindrance to exercise being made the smallest necessary limit, even under body vibrations of a subject person, and as a result, the present inventors have reached the following knowledge.

[0015] Specifically, in order to take out a heart rate with a burden on a subject person and a hindrance to exercise being made the smallest necessary limit even under the body vibrations of the subject person, it is preferable to reflect or transmit light at or through a blood vessel and/or blood, and thereafter detect the light.

[0016] Next, in order to collect an accurate heart rate, a thick artery in which arteriovenous anastomosis does not adjust bloodstream is preferable as a blood vessel at which the heart rate is taken out.

[0017] The present inventors have completed the invention of a heart rate monitor which can measure an accurate heart rate with a burden on a subject person and a hindrance to exercise being made the smallest necessary limit based on the above-described knowledge.

[0018] Specifically, a first aspect of the invention is a heart rate monitor comprising a light-emitting element, a light-receiving element, and a CPU, with

[0019] light from the aforesaid light-emitting element being reflected at or transmitted through blood running in a blood vessel,

[0020] the aforesaid light-receiving element detecting the reflected or transmitted light,

[0021] the aforesaid CPU measuring a change in bloodstream running in the vessel from a change in intensity of the light detected at the aforesaid light-receiving element, and

- [0022] the aforesaid CPU calculating a pulse rate of the change in bloodstream per unit time from the measured value, and regarding the calculated pulse rate of the change in the bloodstream per unit time as a heart rate, and is characterized in that
- [0023] the aforesaid light-emitting element and the aforesaid light-receiving element are fitted to a head of a human body having a space of 4 mm to 10 mm between them, and
- [0024] light with a wavelength of 900 nm to 1200 nm emitted by the aforesaid light-emitting element is reflected at or transmitted through a subcutaneous artery and/or blood running in the subcutaneous artery and is detected at the aforesaid light-receiving element.
- [0025] A second aspect of the invention is the heart rate monitor according to claim 1, characterized by further comprising a display unit for displaying the calculated heart rate, and characterized in that
- [0026] the aforesaid display unit transmits the calculated heart rate to a measuring person and/or a subject person by means of a display, a voice, radio, and/or bone conduction.
- [0027] A third aspect of the invention is the heart rate monitor according to claim 1 or claim 2, characterized by further comprising a storage device for storing the calculated heart rate.
- [0028] A fourth aspect of the invention is the heart rate monitor according to any one of claim 1 through claim 3, characterized by further comprising a head band fitted to a head of a human body, and characterized in that
- [0029] the aforesaid light-emitting element, the aforesaid light-receiving element, the aforesaid CPU, and the aforesaid display unit are attached to the aforesaid head band.
- [0030] A fifth aspect of the invention is the heart rate monitor according to any one of claim 1 through claim 3, characterized by further comprising an eyeglass frame fitted to a head of a human body, and characterized in that
- [0031] the aforesaid light-emitting element, the aforesaid light-receiving element, the aforesaid CPU and the aforesaid display unit are attached to the aforesaid eyeglass frame.
- [0032] A sixth aspect of the invention is the heart rate monitor according to any one of claim 1 through claim 3, characterized by further comprising a sun visor fitted to a head of a human body, and characterized in that
- [0033] the aforesaid light-emitting element, the aforesaid light receiving element, the aforesaid CPU and the aforesaid display unit are attached to the aforesaid sun visor.
- [0034] A seventh aspect of the invention is the heart rate monitor according to any one of claim 1 through claim 3, characterized by further comprising a container engaged in an ear pinna of a human body, and characterized in that
- [0035] the aforesaid light-emitting element, the aforesaid light-receiving element, the aforesaid CPU and the aforesaid display unit are attached to the aforesaid container.
- [0036] An eighth aspect of the invention is a method of measuring a heart rate comprising the steps of
- [0037] fitting a light-emitting element and a light-receiving element to a human body,
- [0038] reflecting or transmitting light emitted by the aforesaid light-emitting element at or through blood running in a blood vessel and detecting it at the aforesaid light-receiving element,
- [0039] measuring a change in bloodstream running in the blood vessel from a change in intensity of the light detected at the aforesaid light-receiving element, and
- [0040] calculating a pulse rate of the change in bloodstream per unit time from the calculated value and regarding the calculated pulse rate of the change in blood stream per unit time as a heart rate, and is characterized in that
- [0041] the aforesaid light-emitting element and the aforesaid light-receiving element are fitted to a head of a human body with a space of 4 mm to 10 mm between them, and
- [0042] light with a wavelength of 900 nm to 1200 nm emitted by the aforesaid light-emitting element is reflected at or transmitted through a subcutaneous artery and/or blood running in the subcutaneous artery and is detected at the aforesaid light receiving element.

BRIEF DESCRIPTION OF THE DRAWINGS

- [0043] FIG. 1 is a schematic diagram of a section in a surface of a head of a subject person;
- [0044] FIG. 2 is a circuit block diagram of a heart rate monitor according to an embodiment;
- [0045] FIG. 3 is a perspective view of a fitting example of the heart rate monitor according to the embodiment to a subject person;
- [0046] FIG. 4 is a perspective view of a fitting example of the heart rate monitor according to the embodiment to the subject person;
- [0047] FIG. 5 is a perspective view of a fitting example of the heart rate monitor according to the embodiment to the subject person;
- [0048] FIG. 6 is a perspective view of a fitting example of the heart rate monitor according to the embodiment to the subject person;
- [0049] FIG. 7 is a perspective view of a fitting example of the heart rate monitor according to the embodiment to the subject person;
- [0050] FIG. 8 is a perspective view of a fitting example of the heart rate monitor according to the embodiment to the subject person;
- [0051] FIG. 9 is an example of the heart rate monitor according to the embodiment fitted to an ear of the subject person; and

[0052] FIG. 10 is a schematic view of a cross section of an ear region of the subject person in the fitting example shown in FIG. 9.

DETAILED DESCRIPTION OF THE PREFERRED EMBODIMENT

[0053] A preferred embodiment of the present invention will be explained in detail below.

[0054] First, as described above, in order to take a heart rate with a burden on a subject person and hindrance to exercise being reduced to the minimum necessary amount, it is preferable to reflect or transmit light at or through a blood vessel and/or blood and thereafter detect the light. In order to take an accurate heart rate, a thick artery for which arteriovenous anastomosis does not adjust bloodstream is preferable as a blood vessel from which the heart rate is taken.

[0055] However, since a thick artery of a human body is not normally located near a body surface, the accurate heart rate cannot be taken even if light is emitted from the body surface to try to detect the light after reflected or transmitted at or through the artery in a non-pressed state.

[0056] Here, a first conception of the present inventors is that they paid attention to a subcutaneous artery at a head of a human body as a blood vessel where the heart rate is taken. Normally, thick arteries are located in a deep inside of a human body as described above, but in the head, they are located comparatively near the body surface.

[0057] Specifically, thick arteries exist in soft tissue between cranial bones and a skin, and less fat tissue causing a hindrance to measurement exists in the soft tissue irrespective of physique of subject persons.

[0058] More preferably, the most stable spot in a human body during exercise such as running is a head of a human body. This is considered to protect the brain from shock during exercise, and as a place where data is stably taken from a human body during the exercise, the head is also the most suitable place.

[0059] To be additionally preferable, functional parts for transmitting a heart rate obtained by processing the obtained data to a subject person are reduced in size and weight as a result of improvement in electronics. Since the obtained heart rate is transmitted to eyes or ears of the subject person by means of light or voice, if the data is taken at the head, a heart rate monitor with everything being integrated and excellent in operability can be realized.

[0060] Next, a second conception of the present inventors is that they found out an optimal wavelength of light of a light-emitting element and an optimal distance between the light-emitting element and a light-receiving element.

[0061] Specifically, light with a wavelength of 900 nm to 1200 nm, more preferably, 950 nm to 1050 nm, penetrates in a human body favorably and is modulated by the movement of an artery and bloodstream. Further, the distance between the light-emitting element and the light receiving element is made to be 4 mm to 10 mm, more preferably, 7 mm to 9 mm, whereby the aforementioned modulated light can be favorably detected.

[0062] Preferred embodiments of the present invention will be explained in more detail below with reference to the drawings.

[0063] FIG. 1 is a schematic diagram of a section in a surface of a head of a subject person.

[0064] Soft tissue 2 exists between cranial bones 1 and a skin 3, and for example, an artery 4 such as a supraorbital artery and a vein 5, and a capillary vessel 6 exist in the soft tissue, and a light-emitting element 11 and a light-receiving element 12 are provided on the skin 3.

[0065] Blood runs in the artery 4, the vein 5 and the capillary vessel 6, and the artery 4 especially pulsates in accordance with a heart rate.

[0066] The light-emitting element 11 is preferably an infrared LED or the like generating light having a wavelength of 900 nm to 1200 nm, more preferably, 950 nm to 1050 nm. This is because the infrared light with the wavelength is hardly absorbed in body tissue and transmits through the soft tissue 2 to reach the artery 4 and the like, whereby it is modulated and reflected, and can be detected at the light receiving element 12. It should be noted that as the light-receiving element 12, a photo transistor or the like can be appropriately used.

[0067] Further, it is preferable that the light-emitting element 11 and the light-receiving element 12 are placed on the skin 3 with a space of 4 mm to 10 mm, more preferably, 7 mm to 9 mm between them.

[0068] This is because it is preferable that the space between both the elements is small in order to detect the light emitted from the light-emitting element 11 and reflected at the artery 4 by the light-receiving element 12, but it is difficult to place both the elements directly above the artery 4 or in the state in which both the elements straddle the artery 4 for each measurement, and further the location of the artery 4 differs a little among individuals and the like. Therefore, when the light-emitting element 11 and the light-receiving element 12 have the space of 4 mm to 10 mm, more preferably, 7 mm to 9 mm, the light reflected from the artery 4 can be received with stability. Further, it is also preferable to increase the number of the light-receiving elements to be two or more and provide them around the light-emitting element 11 as a center to thereby efficiently and stably receive the reflected light from the artery 4 and perform comparative processing of signals from a plurality of the light-receiving elements, thereby making the constitution in which an influence of outer light is cancelled.

[0069] In addition to the above, an artery near an external auditory meatus can be used as placement positions for the light-emitting element 11 and the light-receiving element 12.

[0070] This makes the constitution in which light is emitted to a superficial temporal artery existing in this region and the reflected or transmitted light is detected, and it is possible to adopt the constitution in which the light-emitting element 11 and the light-receiving element 12 are placed at the superficial temporal artery side in an external ear with a space being provided between them as described above, or to adopt the constitution in which the light-emitting element 11 is placed inside the external auditory meatus and the light-receiving element 12 is placed at a side across the superficial temporal artery.

[0071] FIG. 2 is a circuit block diagram in a heart rate monitor 10 according to the present invention.

[0072] Light generated from the light-emitting element **11** is pulsation-modulated and reflected at an artery of a human body, and is detected by the light-receiving element **12** to be an electric signal. The obtained electric signal is appropriately amplified in an amplifier **13** to enter a CPU **14**. At this time, it is a preferable constitution that the light-emitting element **11** is not lit all the time but lit in a pulse form to save electric power, thereby increasing the life of a battery in the heart rate monitor **10**.

[0073] The CPU **14** compares a signal sent to the light-emitting element **11** and the modulated electric signal detected at the light-receiving element **12**, then cancels a disturbance factor such as outer light, and measures pulsation of a subcutaneous artery and/or a change in bloodstream in the subcutaneous artery. Subsequently, the CPU **14** calculates the pulse rate in the change of bloodstream per unit time from the measured pulse rate and the like, and this is regarded as a heart rate.

[0074] Further, the CPU **14** converts the calculated heart rate into a numerical value, and transmits it to the subject person and/or a measuring person via a display unit.

[0075] As a concrete transmitting method, it is preferable to transmit the calculated heart rate to the subject person and the like by optically displaying it on a display **15**, by converting the heart rate in the numerical form into a synthetic voice and running it into an earphone **16**, by running the heart rate in the synthetic voice to a bone conduction element **17** and/or the like.

[0076] Further, as necessary, the constitution in which the data of the heart rate is transmitted from a transmitter **18** by radio or the like and received by a receiver at the measuring person may be suitable.

[0077] In addition, it is a preferable constitution that the CPU **14** is provided with a data storage device **19**.

[0078] By adopting this constitution, a heart rate measurement value within a desired period of time can be temporarily stored in the data storage device **19**. By reading and analyzing the temporarily stored data by a computer or the like, it is made possible to obtain data contributing to the grasp of capacity of locomotion, physical condition and the like of a subject person without being limited by a measuring time.

[0079] FIG. 3 through FIG. 7 show examples of devices of the heart rate monitor **10** having the aforementioned constitution and examples of fitting them to a subject person.

[0080] (Fitting Example 1)

[0081] FIG. 3 shows an example in which the heart rate monitor **10**, the display **15** and the earphone **16** are placed at a head band **31** wound around a head of a human body.

[0082] In this example, if the heart rate monitor **10** is placed at a brow, a supraorbital artery or the like can be used as an artery at which the heart rate is detected, and if it is placed at a temporal region, a superficial temporal artery, zygomatico-orbital artery or the like can be used.

[0083] The display **15** using liquid crystal or the like as a display unit may be used, but it is also a preferable constitution that with use of a head mount display, the displayed numerical value is transmitted to a subject person in a virtual

reality form as if it were, for example, 50 cm ahead of him or her while the display itself actually exists near his or her eyes.

[0084] In this example, the display **15** and the earphone **16** are both provided, but the constitution in which either one is used may be suitable.

[0085] (Fitting Example 2)

[0086] FIG. 4 shows an example in which the heart rate monitor **10** and the bone conduction element **17** are placed at the head band **31** as shown in FIG. 3.

[0087] The bone conduction element **17** transmits a synthetic voice signal from the CPU **14** as a vibration, and therefore a subject person can hear the synthetic voice even if there is noise around him or her.

[0088] If this constitution is adopted, the heart rate monitor **10** and the bone conduction element **17** can be both placed on the head band **31**, which can provide a simple design and is preferable in handling.

[0089] (Fitting Example 3)

[0090] FIG. 5 shows an example in which the heart rate monitor **10** and the transmitter **18** are placed on the head band **31** as shown in FIG. 3.

[0091] The transmitter **18** transmits a heart rate signal from the CPU to the receiver by radio.

[0092] The constitution in which the heart rate signal received at the receiver can be, for example, further stored, printed, displayed and analyzed can be provided. In order to feed back the data to the subject person, the constitution using an optical display or a synthetic voice is preferable.

[0093] If this constitution is adopted, the heart rate monitor **10** and the transmitter **18** can be both placed on the head band **31**, which can provide a simple design, and is preferable in handling.

[0094] Here, the aforementioned (Fitting example 2) and (Fitting example 3) are the fitting examples suitable for heart rate measurement on the occasion of doing sports such as, for example, swimming, athletic sports, and a ball game, which give a shock to a head or require vigorous motions.

[0095] It is a preferable constitution that the head band **31** provided with the heart rate monitor **10** and the like is integrated with, for example, a swimming cap to further reduce a burden on a subject person, for the heart rate measurement on the occasion of swimming.

[0096] (Fitting Example 4)

[0097] FIG. 6 is an example in which the heart rate monitor **10** and the display unit are placed at an eyeglass frame **32**.

[0098] In this example, the heart rate monitor **10** is placed at a temple part of the eyeglass frame **32**, and therefore a superficial temporal artery, a zygomatico-orbital artery and the like can be used as an artery at which the heart rate is detected. As the display unit, the display **15** using liquid crystal or the like as in the example shown in FIG. 3 may be used, but the constitution in which a head mount display is used is also preferable.

[0099] It goes without saying that the earphone 16 and/or the bone conduction element 17 can be used.

[0100] (Fitting Example 5)

[0101] FIG. 7 is an example in which the heart rate monitor 10 and the display unit are placed at a sun visor 33.

[0102] In this example, the heart rate monitor 10 is placed at a brow region or temporal region with use of the sun visor 33, and therefore a supraorbital artery, a superficial temporal artery, a zygomatico-orbital artery and the like can be used as an artery at which the heart rate is detected. As the display unit, the display 15 using liquid crystal or the like as in the example shown in FIG. 3 may be used, but the constitution in which a head mound display is used is also preferable.

[0103] It goes without saying that the earphone 16 and/or the bone conduction element 17 can be used.

[0104] (Fitting Example 6)

[0105] FIG. 8 is an example in which the heart rate monitor 10 itself is shaped into an ear attachment set and is engaged in an ear pinna.

[0106] In this example, the light-emitting element 11 is placed in an external auditory meatus 7 as shown in FIG. 9 and FIG. 10.

[0107] Here, FIG. 9 is a perspective view showing the situation in which the light-emitting element 11 and the light-receiving element 12 of the heart rate monitor 10 are placed with a posterior auricular artery 8 between them, and FIG. 10 is a schematic diagram of a cross section of the aforementioned light-emitting element 11 and the light-receiving element 12 being placed with the posterior auricular artery 8 between them.

[0108] As is obvious from FIG. 10, light emitted from the light-emitting element 11 is transmitted through the posterior auricular artery 8 to reach the light-receiving element 12. The heart rate can be obtained from the light reaching the light-receiving element 12.

[0109] When the light-emitting element 11 and the light-receiving element 12 are placed with the posterior auricular artery 8 between them, if the light-emitting element 11 is placed at a side of an external auditory meatus 7, a preferable constitution that is not susceptible to outer light is obtained.

[0110] Here, it is also a preferable constitution that the form of the ear attachment set is suitably designed to attach and integrate the light-emitting element 11, the light-receiving element 12, the CPU 14 and the earphone 16 inside a container of an ear attachment set to thereby reduce a burden on a subject person.

[0111] It is also a preferable constitution that a synthetic voice signal from the CPU 14 is transmitted to the subject person with use of the bone conduction element 17 integrated with the ear attachment set.

[0112] In the above-described fitting examples 1 through 6, it is also a preferable constitution that the data storage device 19 is provided in the CPU 14 as described above.

[0113] As described in detail thus far, the present invention has the object of measuring accurate occurrences of pulsation per unit time, that is, the heart rate, with a burden on a subject person being reduced to be very small, and

without being susceptible to body vibrations accompanying exercise, and is to provide a heart rate monitor comprising a light-emitting element, a light-receiving element, and a CPU, with

[0114] light from the aforesaid light-emitting element being reflected at or transmitted through blood running in a blood vessel,

[0115] the aforesaid light-receiving element detecting the reflected or transmitted light,

[0116] the aforesaid CPU measuring a change in bloodstream running in the blood vessel from a change in intensity of the light detected at said light-receiving element, and

[0117] the aforesaid CPU calculating a pulse rate of the change in the bloodstream per unit time from the measured value, and regarding the calculated pulse rate of the change in the bloodstream per unit time as a heart rate, and is characterized in that

[0118] the aforesaid light-emitting element and the aforesaid light-receiving element are fitted to a human head having a space of 4 mm to 10 mm between them, and

[0119] light with a wavelength of 900 nm to 1200 nm emitted by the aforesaid light-emitting element is reflected at or transmitted through a subcutaneous artery and/or blood running in the subcutaneous artery and is detected at the aforesaid light-receiving element.

[0120] As a result, it becomes possible to measure an accurate heart rate with a burden on a subject person and a hindrance to exercise being the minimum necessary amount.

What is claimed is:

1. A heart rate monitor comprising a light-emitting element, a light-receiving element, and a CPU,

light from said light-emitting element being reflected at or transmitted through blood running in a blood vessel,

said light-receiving element detecting the reflected or transmitted light,

said CPU measuring a change in bloodstream running in the blood vessel from a change in intensity of the light detected at said light-receiving element, and

said CPU calculating a pulse rate of the change in the bloodstream per unit time from the measured value, and regarding the calculated pulse rate of the change in the bloodstream per unit time as a heart rate,

wherein said light-emitting element and said light-receiving element are fitted to a human head having a space of 4 mm to 10 mm between them, and

wherein light with a wavelength of 900 nm to 1200 nm emitted by said light-emitting element is reflected at or transmitted through a subcutaneous artery and/or blood running in the subcutaneous artery and is detected at said light-receiving element.

2. The heart rate monitor according to claim 1, further comprising:

a display unit for displaying the calculated heart rate, wherein said display unit transmits the calculated heart rate to a measuring person and/or a subject person by means of an optical display, a voice, radio, and/or bone conduction.

3. The heart rate monitor according to claim 1 or claim 2, further comprising:

a storage device for storing the calculated heart rate.

4. The heart rate monitor according to any one of claim 1 through claim 3, further comprising:

a head band fitted to a head of a human body, wherein said light-emitting element, said light-receiving element, said CPU, and said display unit are attached to said head band.

5. The heart rate monitor according to any one of claim 1 through claim 3, further comprising:

an eyeglass frame fitted to a head of a human body, wherein said light-emitting element, said light-receiving element, said CPU and said display unit are attached to said eyeglass frame.

6. The heart rate monitor according to any one of claim 1 through claim 3, further comprising:

a sun visor fitted to a head of a human body, wherein said light-emitting element, said light receiving element, said CPU and said display unit are attached to said sun visor.

7. The heart rate monitor according to any one of claim 1 through claim 3, further comprising:

a container engaged in an ear pinna of a human body, wherein said light-emitting element, said light-receiving element, said CPU and said display unit are attached to said container.

8. A method of measuring a heart rate comprising the steps of:

fitting a light-emitting element and a light-receiving element to a human body;

reflecting or transmitting light emitted by said light-emitting element at or through blood running in a blood vessel and detecting it at said light-receiving element; measuring a change in bloodstream running inside the blood vessel from a change in intensity of the light detected at said light-receiving element; and

calculating a pulse rate of the change in the bloodstream per unit time from the measured value and regarding the calculated pulse rate of the change in the blood stream per unit time as a heart rate,

wherein said light-emitting element and said light-receiving element are fitted to a head of a human body with a space of 4 mm to 10 mm between them, and

wherein light with a wavelength of 900 nm to 1200 nm emitted by said light-emitting element is reflected at or transmitted through a subcutaneous artery and/or blood running in the subcutaneous artery and is detected at said light receiving element.

* * * * *

专利名称(译)	心率监测器和心率测量方法		
公开(公告)号	US20030018274A1	公开(公告)日	2003-01-23
申请号	US10/185718	申请日	2002-07-01
[标]申请(专利权)人(译)	高桥YOSHIKAZU BAKER WAYNE SHIOGAI HAJIME 越野SHINJI 三桥SHINTARO		
申请(专利权)人(译)	高桥YOSHIKAZU BAKER WAYNE SHIOGAI HAJIME 越野SHINJI 三桥SHINTARO		
当前申请(专利权)人(译)	高桥YOSHIKAZU BAKER WAYNE SHIOGAI HAJIME 越野SHINJI 三桥SHINTARO		
[标]发明人	TAKAHASHI YOSHIKAZU BAKER WAYNE SHIOGAI HAJIME KOSHINO SHINJI MITSUHASHI SHINTARO		
发明人	TAKAHASHI, YOSHIKAZU BAKER, WAYNE SHIOGAI, HAJIME KOSHINO, SHINJI MITSUHASHI, SHINTARO		
IPC分类号	A61B5/0245 A61B5/00 A61B5/02		
CPC分类号	A61B5/0059 A61B5/6814 A61B5/6816		
优先权	2001219993 2001-07-19 JP		
其他公开文献	US6783501		
外部链接	Espacenet USPTO		

摘要(译)

每单位时间准确出现脉动，即，心率是在对象人的负担减小到非常小并且不易受到伴随运动的身体振动的情况下测量的。产生心率监测器，其中发光元件11和光接收元件12装配到人体的头部，来自发光元件11的光在皮下动脉4处反射或透射。和/或在皮下动脉中运行的血液，在光接收元件12处检测反射或透射的光，并且通过使用CPU 14，皮下动脉4的脉动和/或皮下运动的血流的变化。根据在光接收元件12处检测到的光强度的变化来测量动脉4，根据该测量值计算每单位时间血流变化的脉搏率，并计算所述变化的脉搏率。每单位时间的血流被视为心率。

