



US009149186B2

(12) **United States Patent**  
**Grayzel et al.**

(10) **Patent No.:** **US 9,149,186 B2**  
(45) **Date of Patent:** **Oct. 6, 2015**

(54) **CONFIGURATION OF CABLES FOR  
MONITORING SYSTEMS**

(76) Inventors: **Joseph Grayzel**, Englewood, NJ (US);  
**Jeffrey Grayzel**, Morristown, NJ (US)

(\*) Notice: Subject to any disclaimer, the term of this  
patent is extended or adjusted under 35  
U.S.C. 154(b) by 24 days.

(21) Appl. No.: **13/337,034**

(22) Filed: **Dec. 23, 2011**

(65) **Prior Publication Data**

US 2012/0165621 A1 Jun. 28, 2012

**Related U.S. Application Data**

(60) Provisional application No. 61/426,806, filed on Dec.  
23, 2010.

(51) **Int. Cl.**

**A61B 5/00** (2006.01)

**A61B 5/0428** (2006.01)

**A61B 5/0205** (2006.01)

**A61B 5/021** (2006.01)

(52) **U.S. Cl.**

CPC ..... **A61B 5/00** (2013.01); **A61B 5/04286**  
(2013.01); **A61B 5/021** (2013.01); **A61B**  
**5/02055** (2013.01); **A61B 2562/221** (2013.01);  
**A61B 2562/225** (2013.01); **A61B 2562/247**  
(2013.01)

(58) **Field of Classification Search**

CPC ..... **A61B 2562/221**; **A61B 5/0205**  
See application file for complete search history.

(56) **References Cited**

**U.S. PATENT DOCUMENTS**

3,492,987 A \* 2/1970 Parker ..... 600/21  
4,224,936 A \* 9/1980 Cox ..... 600/21  
4,280,507 A \* 7/1981 Rosenberg ..... 600/508

4,353,372 A \* 10/1982 Ayer ..... 600/393  
4,367,728 A \* 1/1983 Mutke ..... 600/21  
4,485,806 A \* 12/1984 Akers ..... 600/21  
4,768,241 A \* 9/1988 Beney ..... 5/600  
4,981,139 A \* 1/1991 Pfohl ..... 600/484  
5,131,854 A \* 7/1992 Jose et al. .... 439/86  
5,491,299 A \* 2/1996 Naylor et al. .... 174/36  
5,626,151 A \* 5/1997 Linden ..... 128/897  
5,950,625 A \* 9/1999 Bongiovanni et al. .... 128/845  
5,975,081 A \* 11/1999 Hood et al. .... 128/845  
6,247,963 B1 \* 6/2001 Rattner ..... 439/502  
6,833,506 B2 \* 12/2004 Wechsler ..... 174/113 R  
6,870,109 B1 \* 3/2005 Villarreal ..... 174/102 R

(Continued)

**OTHER PUBLICATIONS**

Siegel JD, Rhinehart E, Jackson M, Chiarello L, and the Healthcare  
Infection Control Practices Advisory Committee, "2007 Guideline  
for Isolation Precautions: Preventing Transmission of Infectious  
Agents in Healthcare Settings", p. 1-225.\*

*Primary Examiner* — William Thomson


*Assistant Examiner* — Marie Archer

(57)

**ABSTRACT**

A physical configuration of cables connecting a monitoring  
apparatus to a human patient, where said patient and his  
immediate surroundings define a potentially infectious con-  
taminated zone. The configuration provides for the monitor  
and main trunk cable to lie outside of the contamination zone,  
and one or more serial cables connect to the trunk cable and  
enter the contamination zone to provide contact with the  
patient. This physical configuration prevents contamination  
of the monitor and trunk cable, so they may be reused on  
successive patients, while lightweight and inexpensive serial  
cables contacting the patient and his contamination zone may  
be disposable. Examples of monitoring various physiological  
variables are provided to exemplify the universal concept of  
such physical configuration. Adaptation for wireless trans-  
mission is also described.

**25 Claims, 10 Drawing Sheets**




(56)


**References Cited**


U.S. PATENT DOCUMENTS


|           |      |         |               |           |              |      |         |                |          |
|-----------|------|---------|---------------|-----------|--------------|------|---------|----------------|----------|
| 6,971,985 | B2 * | 12/2005 | Perlatti      | 600/21    | 8,375,572    | B2 * | 2/2013  | Lind et al.    | 29/825   |
| 7,521,634 | B2 * | 4/2009  | Clem et al.   | 174/113 R | 2004/0074212 | A1 * | 4/2004  | Yachi et al.   | 55/385.2 |
| 8,070,508 | B2 * | 12/2011 | Flagler       | 439/470   | 2006/0178030 | A1 * | 8/2006  | Lund et al.    | 439/287  |
| 8,076,580 | B2 * | 12/2011 | Kolasa et al. | 174/105 R | 2006/0247487 | A1 * | 11/2006 | Arts et al.    | 600/21   |
| 8,089,001 | B2 * | 1/2012  | Wang          | 174/110 R | 2007/0056593 | A1 * | 3/2007  | Kubicko et al. | 128/846  |
|           |      |         |               |           | 2007/0156005 | A1 * | 7/2007  | Baum           | 588/249  |
|           |      |         |               |           | 2007/0260133 | A1 * | 11/2007 | Meyer          | 600/393  |
|           |      |         |               |           | 2012/0071740 | A1 * | 3/2012  | Kaestle        | 600/323  |


\* cited by examiner


**FIG. 1**

**FIG. 2**

**FIG. 3**

**FIG. 4**

**FIG. 5**

**FIG. 6**








FIG. 7



**FIG. 8**



**FIG. 9**

**FIG. 10A****FIG. 10B**

1

## CONFIGURATION OF CABLES FOR MONITORING SYSTEMS

### RELATED APPLICATIONS

This application claims the benefit of U.S. Provisional Application No. 61/426,806 filed Dec. 23, 2010

### FIELD

The invention generally relates to apparatus and configurations of apparatus for use in patient monitoring systems.

### BACKGROUND

Ill patients require surveillance of essential information relating to the patient's condition. Such information may relate to physiologic or anatomic functions or status. Apparatus which perform this surveillance function are referred to as monitoring systems. The most common signal employed for continuous surveillance is the electrocardiogram (ECG). Other physiologic functions that can be monitored include, but are not limited to temperature, blood pressure, respiration, blood oximetry, cardiac bio-impedance, and others. The system comprises an electronic monitor console connected to one or more cables, which terminate with a sensor device interfaced with the patient.

The most common location for the electronic monitor console is at the patient's bedside, but the patient may reside on a reclining chair, stretcher, gurney, operating-room table, or other similar modality, with the electronic monitor console similarly nearby. Often the patient can reach out and touch the electronic monitor console. One or more cables connect the electronic console to the patient to convey information from the patient. Such cables are most often electrical/electronic lines, but may also be pneumatic, hydraulic, or fiber-optic, consistent with the information being conveyed from patient to electronic console. Henceforth, in the description below, the term cable shall be broadly defined as the means of conveying such signals from the patient to the monitor console. Thus, the term cable could mean an electrical cable, a pneumatic cable, a fiber-optic cable, or other, depending on the application.

The modality that will be employed as the paradigm for initial description of a system configuration is the ECG, followed by analogous applications to temperature and blood pressure. The ECG is a wave-form depicting the time-varying difference in electrical potential between two points on the surface of the skin. Electrical connection to the skin is provided by a conductive electrode connected to a conductive wire; the simplest arrangement consists of the two active electrodes whose potential difference is to be measured, and a third electrode serving as a ground or reference electrode. This arrangement provides one ECG signal or lead; each additional lead requires an additional electrode with attached conductive wire. Since it is often desirable to monitor several ECG leads, it is common to have four or more electrodes with wires grouped as a packaged assembly.

To limit and control the transfer of infectious agents within the hospital environment, these electrodes with attached wires are frequently discarded after each patient use, since they are considered to be contaminated by the patient and not suitable for transfer to another ill individual. Being disposable, the electrode-wire assembly employs wires of minimal length which lie entirely on the patient or on his bed. Hereafter, we may refer to such wires as serial wires, since they are in series with the trunk cable, which then extends to the input

2

connector of the electronic monitoring console. Thus, a bundled group of wires may constitute a cable and be denoted as the serial cable, so named as it is in series with the trunk cable. A connecting means, such as a metallic pin, located at the proximal end of each wire within the serial cable, couples to a multiple-input yoke at the distal end of a permanent trunk cable. Other connecting means may be possible. Of note, the terms proximal and distal are referenced to the electronic monitor console, proximal being closer to the console and distal being further away, in the direction of the patient.

The trunk cable extends all the way to the electronic monitor console to which it couples via a substantial multiple-conductor connector. Thus, the trunk cable contains multiple shielded wire conductors within its entire length and terminates in a multiple pin-receptive yoke at its distal end, and a substantial multiple-conductor connector at its proximal end, which is inserted into the input receptacle of the monitor console. Parenthetically, it is again noted that cables which are pneumatic, hydraulic, fiber-optic, or of a non-electronic nature will require respectively-appropriate connectors.

The trunk-cable is a relatively expensive component of the monitoring system and is not considered a disposable item, but is reused continuously through the sequence of patients to be interfaced with the monitor over time. The trunk-cable conspicuously reaches from the monitor console to the patient's bed, is contacted frequently by the patient, his bedclothes and linens, and is also handled frequently by caregivers at the patient's bedside. Thus, the trunk-cable is exposed directly to multiple sources of microbial contamination, and can transmit same to the subsequent sequence of patients for whom the monitoring system is employed.

Nosocomial infections are a major cause of in-hospital morbidity and responsible for large increases in hospital costs, for which reimbursement is not given. Hence, hospitals have intensely addressed causes of such hospital-acquired infection and have identified potential culprits. Among such sources of contamination and transmission of microbes are trunk-cables for ECG and trunk-cables for other monitored parameters, such as previously mentioned temperature, blood pressure, respiration, blood oximetry, bio-impedance, and others. Many hospitals attempt to reduce the virulence of trunk-cables by frequent wiping with anti-microbial disinfectants, but microbial cultures of trunk-cables have revealed such cleansing to be of limited value and not adequate for the objective. Hence, contamination of trunk cables remains a serious problem, contributing to the transmission of infective agents from one patient to another.

### OBJECTS

It is an object of the present application to minimize or eliminate the role of trunk-cables as a discernable vehicle for the inter-patient transmission of infective agents, such as bacteria and fungi.

It is a further object of the present application to reduce hospital morbidity resulting from transmission of nosocomial infection by monitoring systems.

It is a further object of the present application to reduce hospital costs resulting from transmission of nosocomial infection by monitoring systems.

It is yet another object of the application to provide a monitoring system wherein the monitor console and trunk cable reside completely outside the infectious zone.

It is still another object of the application to provide a trunk cable of a length such that when its proximal end is attached

to the monitor console, its length is insufficient to allow its distal end to reach the perimeter of the infectious zone surrounding a patient.

It is yet another object of the application to provide a serial cable that is disposable.

It is still another object of the application to provide an intermediate cable to be used when the length of the serial cable is insufficient to have its proximal end extend beyond the perimeter of the infectious zone when its distal end is coupled to the patient.

It is yet another object of the application to provide for wireless transmission of information from a transmitter located inside or outside of the infectious zone to a receiver located outside the infectious zone.

It is still another object of the application to provide a method for preventing the transfer of infective agents along a series of patients successively utilizing the same monitoring system.

### SUMMARY

The present application describes spatial configurations of the monitor console and its associated cables which run from the monitor console to the patient. The patient's bed and a defined zone surrounding the bed are susceptible to contamination by the patient, and together are denoted hereafter as the Infectious Zone. The configuration described herein reduces or prevents contamination of the trunk cable, which is the expensive and reused portion among the group of cables. This is accomplished by locating the monitor console outside the infectious zone, and attaching thereto a short trunk cable whose length is not sufficient to reach the boundary of the infectious zone, thereby preventing the usual physical contact leading to contamination. The serial cable connected between the trunk cable and patient is made sufficiently long so that it extends from the trunk cable located outside the infectious zone to the patient's corpus. Thus, only the serial cable is susceptible to contamination, and it is made to be disposable and discarded. Compared to present-art cable systems, the trunk cables described herein are generally shorter than present trunk cables, and the serial cables described herein are generally longer than present-art serial cables. Both the trunk cable and the monitor console as described herein are always located outside the infectious zone.

The foregoing configuration for a monitoring system, consisting of both monitor console and trunk cable lying outside the infectious zone, and the serial cable will be described in detail for several monitoring modes, namely ECG, temperature, and blood pressure. It will then be evident to one skilled in the art the manner of applying the described system configurations to any other physiological parameter amenable to monitoring.

A second configuration is presented as follows. In the first configuration the serial cable extends from the patient to a point outside the infectious zone where it connects to the trunk cable. In the second configuration this primary serial cable remains short, not extending outside the infectious zone, and a second serial cable named the Intermediate Cable, extends from the proximal terminus of the primary serial cable to the distal end of the trunk cable lying outside of the infectious zone. This configuration enables present-day cables to remain unchanged, utilizing the existing short serial cable, while the intermediate cable continues to a point outside the infectious zone. This second configuration also accomplishes the desired result, namely avoiding contamina-

tion of the console monitor and the non-disposable trunk cable, both of which reside outside the perimeter of the infectious zone.

The first and second configurations described above may be modified by the addition of wireless transmission of the patient's physiologic signals from the patient to the monitor. A wireless transmitter may be attached to the proximal end of a short or long serial cable, or to the proximal end of an intermediate cable. Alternatively, the transmitter may be incorporated directly into the proximal end of a short or long serial cable, or to the proximal end of an intermediate cable. Alternatively, the transmitter and the sensor may be integrated, in which case neither a serial cable nor an intermediate cable is necessary. A wireless receiver may be attached to or incorporated into the distal end of the trunk cable. Alternatively, a receiver may be connected directly to the monitor or incorporated into the monitor and contained within the monitor's enclosure.

For the case where a short serial cable is employed, this arrangement does present the additional problem caused by the transmitter residing inside the infectious zone, since the transmitter is often costly and usually not treated as disposable. In the case where the transmitter will be reused, it would be advantageous for the transmitter to be enclosed within a disposable container which protects it from contamination. This is easily accomplished, for example, with a clear plastic bag-like envelope with a sealable opening, which maintains the cleanliness of the transmitter, yet permits it to be easily removed from the container or bag for subsequent use. A clear plastic material permits RF transmission, optical transmission, infra-red transmission, and other modalities through its protective envelope. Other types of containers could also be designed, including those that are more substantial, such as a plastic enclosure, and amenable to sterilization. The addition of wireless transmission may also be incorporated into other configurations described within this specification.

The configurations described above and in detail below may be advantageously applied to other monitoring systems to capture any information relating to a patient's condition that is amenable to patient monitoring.

In yet another configuration, the elimination of sequential infectious contamination by a reusable cable of a monitoring system employed among a series of patients may also be accomplished by sheathing or otherwise entirely enclosing the reusable trunk cable from its proximal to distal end in a covering, which herein will be referred to as a sheath. Such a sheath could be inexpensive and disposable after each patient use. This is advantageously accomplished by a lightweight flexible tubular structure, such as a thin-walled impermeable plastic tube or envelope, preferably transparent so that proper disposition of the cable within the plastic tube can be observed at all times. Alternatively, the sheath could be made from a polymeric film. It would be desirable that the sheath be capable of assuming a collapsed or compacted form, which can be expanded longitudinally to the full length of the trunk cable. For example, the thin-walled envelope could possess a series of radially-oriented pleats, analogous to pleats on an accordion, which would permit the envelope to be compressed into a compact structure for packaging, shipping and handling, and then be expanded longitudinally over and around the trunk cable along its full length. An alternate structure for the sheath would be a telescopic disposition of the sheath with adjacent lengths folded sequentially within one another. This structure would also be initially compact, and then expanded longitudinally to envelop the entire length of the trunk cable. A third structure, less ordered than the foregoing, would simply be a thin-walled tubular plastic film

crumpled along its axis. In some configurations the sheath would extend to a point that would encompass the proximal end of the serial cable or the wireless receiver if one is being utilized. In yet other configurations the sheath may extend even further and may be of a length to reach from the monitor console to the patient.

Since it is desirable to have the trunk cable sealed and isolated within the sheath, the ends of the sheath would comprise a means to seal it around the cable or the connector. The open ends may be occluded with a partition, generally perpendicular to the long axis of the sheath. Such an occlusive end-member is advantageously composed of an elastic material, such as a latex-like rubber or a compressible sponge. The elastic end-partition would possess a central slit or puncture through which the cable could be inserted into the sheath, yet the elastic end-partition would recoil snugly around the cable in a conforming manner to provide a sufficiently tight seal around the end of the cable to prevent entry of contaminants. Other means of sealing the end of the sheath are also contemplated. To further accomplish the objective of a contaminant-free cable, the interior of the sheath could possess an antimicrobial chemical or other active substance, such as an interior coating to the sheath, or dispersion in powder form, or a liquid impregnated into the end-partition which is wiped along the cable as it is inserted into the sheath.

The foregoing configurations enable methods of reducing the transmission of infection from patient to patient amongst a series of patients successively utilizing the same monitoring system. Such methods include the steps of assessing the infectious zone and defining its perimeter; placing the monitor console outside said perimeter; attaching the proximal end of the trunk cable to the monitor console and placing the entirety of the trunk cable in a position outside of the infectious zone; connecting the trunk cable distal end to the serial cable proximal end such that both ends are positioned outside the perimeter of said infectious zone; extending the serial cable distal end into the infectious zone; coupling the sensor device located at the distal end of the serial cable to the patient; if necessary due to insufficient combined length of the trunk cable and the serial cable, attaching an intermediate cable to both the serial cable proximal end and the trunk cable distal end to complete a transmission pathway for the patient information to be transmitted from the patient to the monitor console. In yet another configuration, the intermediate cable can be replaced by a wireless transmission device. In yet another configuration, the trunk cable and/or serial cable and/or intermediate cable is encased in a sheath that is deployed over the cable, where said sheath is comprised of an impervious material constituting an effective barrier against microbial agents.

#### BRIEF DESCRIPTION OF THE DRAWINGS

The accompanying drawings which are incorporated in and constitute part of this specification, illustrate some, although not all, possible system configurations.

FIG. 1 depicts a present-art system configuration for ECG monitoring

FIG. 2 depicts a present-art system configuration for temperature monitoring.

FIG. 3 depicts a present-art system configuration for blood-pressure monitoring.

FIG. 4 depicts a configuration as applied to ECG monitoring.

FIG. 5 depicts a configuration as applied to temperature monitoring.

FIG. 6 depicts a configuration as applied to blood-pressure monitoring.

FIG. 7 depicts a configuration as applied to ECG monitoring.

FIG. 8 depicts a configuration as applied to temperature monitoring.

FIG. 9 depicts a configuration as applied to blood-pressure monitoring.

FIGS. 10A-10B depicts configurations of a sheath for encasing the cables.

#### DETAILED DESCRIPTION

FIG. 1 depicts a present-art monitoring system for the ECG. The patient **101** is shown supine on bed **104** or analogous surface for repose or transport. Outside and beyond the perimeter **104** of the bed, dashed lines **107** demarcate the outer boundary or perimeter of the infectious zone, which is beyond the patient's reach. Electronic monitor console **110** is shown outside the infectious zone, although it is frequently positioned at the patient's bedside and within reach of the patient, hence within the infectious zone. Present-art practice generally locates the monitor console according to physical constraints of the available space and operator convenience, without attention to issues of contamination by the patient. Trunk Cable **112** is shown connected to the console by connector **113** at its proximal end, and possesses a connector or yoke **114** at its distal end. Three conductive wires **117** comprise the serial cable shown herein, but more elaborate serial cables contain additional electrical wires to enable multiple ECG leads (waveforms). Each conductive wire comprising the serial cable terminates at its distal end in a conductive electrode **121** which is conductively coupled to the skin surface. Other types of conductive couplings may be used, not shown, such as subcutaneous or intravascular. The proximal end of the serial cable connects to the yoke **114** of the trunk cable, such connection shown herein by pin connectors **116**, though other types of connectors may be employed. The present-art system configuration shown in FIG. 1 makes evident the ease of frequent contamination of the trunk cable and its yoke connector by the patient, bedclothes, and other personal sundries residing with the patient. The serial cable is generally disposable.

FIG. 2 depicts a present-art monitoring system for body temperature, showing the patient **201**, the perimeter **204** of the bed, and the outer boundary or perimeter **207** of the infectious zone. Electronic monitor console **210** is shown outside the infectious zone and engages input connector **213** on the proximal end of the trunk cable **212**. The distal end of the trunk cable possesses connector **214** which couples to connector **216** on the proximal end of serial cable **217**, possessing the requisite number of conductors to convey the signal representing body temperature. The distal end of the serial cable connects to the temperature sensor **222**, such as thermistor or thermocouple, shown in the axilla of the patient. FIG. 2, in a manner analogous to FIG. 1, shows the consistent contamination of the trunk cable by the patient and his intimate physical environment.

FIG. 3 depicts a present-art monitoring system for non-invasive blood pressure measurement, showing the patient **301**, the perimeter of the bed **304**, and the perimeter **307** of the infectious zone. Electronic monitor console **310** is shown outside the infectious zone and receives pneumatic input connector **313** on the proximal end of the pneumatic trunk cable **312** (tubular trunk line). The distal end of the tubular pneumatic trunk line possesses connector **314**, which couples pneumatically to connector **316** on the proximal end of the

pneumatic serial cable **317**, the serial tubular line to inflatable blood-pressure cuff **323**. The electronic console contains an air pump to inflate the cuff, a valve to gradually bleed air from the cuff after adequate inflation, a pressure sensor to measure air pressure within the tubular lines and cuff, and algorithms for controlling the operation of the system and for computing blood pressure from the pulsating pressure fluctuations which occur during deflation of the pressurized cuff. This method is well-known to those skilled in the art, and further details are not herein provided. While disposable blood pressure cuffs are now available, but not always employed, their serial pneumatic line **317** is always short, and connector **316** lies within the infectious zone, as does its mating connector **314**; the pneumatic trunk cable **312** extending to the monitor console **310** is extensively within the bed and infectious zone.

FIG. 4 depicts the first configuration applied to ECG monitoring, showing the patient **401**, the perimeter **404** of the bed, and the perimeter **407** of the infectious zone. Electronic monitor console **410** is located outside the infectious zone, and receives connector **413** from the proximal end of trunk cable **426**. Trunk cable **426** lies entirely outside the infectious zone, as does the connector or yoke **414** at its distal end. Thus, the trunk cable is not subject to direct contamination by the patient or his intimate environment. Pin connectors **416**, affixed to the proximal end of serial cable **418**, also lie outside the infectious zone, but serial cable **418** enters the infectious zone and extends to the patient, where ECG electrodes **421** at the distal ends of the serial cable's wires are conductively coupled to the patient. Compared to present art as shown in FIG. 1, the configuration as drawn in FIG. 4 shows the trunk cable to be shorter and the disposable serial cable to be longer than present art.

FIG. 5 depicts the first configuration applied to monitoring of temperature, showing patient **501**, the perimeter **504** of the bed, and the perimeter **507** of the infectious zone. Electronic monitor console **510** is located outside the infectious zone, and receives connector **513** from the proximal end of trunk cable **526**. Trunk cable **526** lies entirely outside the infectious zone, as do connector **513** at its proximal end and connector **514** at its distal end. Thus, the trunk cable is not subject to direct contamination by the patient or his intimate environment. Connector **516** at the proximal end of serial cable **518** also lies outside the infectious zone, but serial cable **518** enters the infectious zone and extends to the patient, where temperature sensor **522** at the distal end resides in the patient's axilla. Compared to present art as drawn in FIG. 2, the configuration as drawn in FIG. 5 shows the trunk cable to be shorter and the disposable serial cable to be longer than present art.

FIG. 6 depicts the first configuration applied to monitoring of blood pressure, showing patient **601**, the perimeter **604** of the bed, and the perimeter **607** of the infectious zone. Electronic monitor console **610** is located outside the infectious zone, and receives connector **613** from the proximal end of pneumatic trunk cable **626**. Trunk cable **626** lies entirely outside the infectious zone, as does pneumatic connector **614** at its distal end. Thus, pneumatic trunk cable **626** is not subject to direct contamination by the patient or his intimate environment. Pneumatic connector **616** at the proximal end of serial pneumatic cable **618** also lies outside the infectious zone; serial pneumatic cable **618** enters the infectious zone and extends to the patient, where blood-pressure cuff **623** at the distal end is wrapped around the patient's arm. Compared to present art as drawn in FIG. 3, the configuration as drawn in FIG. 6 shows the pneumatic trunk cable to be shorter and the disposable serial pneumatic cable to be longer than present art.

FIG. 7 depicts the second configuration applied to ECG monitoring, showing patient **701**, the perimeter **704** of the bed, and the perimeter **707** of the infectious zone. Electronic monitor console **710** is located outside the infectious zone, and receives connector **713** from the proximal end of trunk cable **726**. Trunk cable **726** lies entirely outside the infectious zone **707**, as does yoke connector **714** at its distal end. Thus, trunk cable **726** is not subject to direct contamination by the patient or his intimate environment. Pin connectors **715** are affixed to the proximal end of an intermediate cable **733**, and also lie outside the infectious zone, while intermediate cable **733** enters the infectious zone and extends to the proximal end of the serial cable **717**. Pin-receptive connectors **734** at the distal end of the intermediate cable mate with pin connectors **716** at the proximal end of the serial cable. The distal ends of wires comprising the serial cable terminate in conductive electrodes **721** which are conductively coupled to the patient. In this second configuration, both the serial cable and the intermediate cable are disposable. This permits use of serial cables as presently manufactured, which are not sufficiently long to reliably extend outside the infectious zone, while the intermediate cable of simple structure and inexpensive serves as an extension line for the serial cable and reaches outside the infectious zone to the yoke connector **714** of the trunk cable **726**. Essentially, serial cable **717** linked to intermediate cable **733** replaces serial cable **418** of FIG. 4.

FIG. 8 depicts the second configuration applied to monitoring of temperature, showing patient **801**, the perimeter **804** of the bed, and the perimeter **807** of the infectious zone. Electronic monitor console **810** is located outside the infectious zone, and receives connector **813** from the proximal end of trunk cable **826**. Trunk cable **826** lies entirely outside the infectious zone **807**, as does connector **814** at its distal end. Thus, trunk cable **826** and its connectors are not subject to direct contamination by the patient or his intimate environment. Mating connector **815** is affixed to the proximal end of an intermediate cable **833**, and also lies outside the infectious zone, while intermediate cable **833** enters the infectious zone and extends to the proximal end of the serial cable **817**. At the distal end of intermediate cable **833**, receptive connector **834** mates with connector **816** at the proximal end of serial cable **817**. The distal end of serial cable **817** connects to the temperature sensor, which is shown nestled in the patient's axilla. In this second configuration for temperature monitoring, both serial cable **817** and intermediate cable **833** are disposable. Essentially, serial cable **817** linked to intermediate cable **833** replaces serial cable **518** of FIG. 5.

FIG. 9 depicts the second configuration applied to monitoring of blood pressure, showing patient **901**, the perimeter **904** of the bed, and the perimeter **907** of the infectious zone. Electronic monitor console **910** is located outside the infectious zone, and receives pneumatic connector **913** from the proximal end of pneumatic trunk cable **926**. Trunk cable **926** lies entirely outside the infectious zone **907**, as does pneumatic connector **914** at its distal end. Thus, pneumatic trunk cable **926** and its connectors are not subject to direct contamination by the patient or his intimate environment. Mating connector **915** is affixed to the proximal end of an intermediate pneumatic cable **933**, and also lies outside the infectious zone, while intermediate pneumatic cable **933** enters the infectious zone and extends to the proximal end of the serial cable **917**. At the distal end of intermediate pneumatic cable **933**, receptive pneumatic connector **934** mates with pneumatic connector **916** at the proximal end of serial pneumatic cable **917**. The distal end of pneumatic serial cable **917** connects to the blood pressure cuff **923**, which is wrapped around the patient's arm. In this second configuration for monitoring

of blood pressure, both serial pneumatic cable **917** and intermediate pneumatic cable **933** are disposable. Essentially, serial pneumatic cable **917** linked to intermediate pneumatic cable **933** replaces serial pneumatic cable **618** of FIG. 6. Present-day disposable blood-pressure cuffs generally possess a short length of pneumatic cable (tubing) permanently affixed thereto, which would serve as the serial pneumatic cable **917** of the present FIG. 9.

FIGS. **10A-10B** depicts sheaths primarily used for encasing the trunk cable of the monitoring system, and could also be used for the other cables as well. FIG. **10A** is a longitudinal section along the central axis showing an configuration having a pleated sheath with end-partitions. The pleated sheath **1080** is generally shown, with radially-oriented pleats **1081**, end-partition **1082** possessing apertures **1083a** and **1083b** through both of which the cable is inserted, and then one end-partition is slidably drawn along the entire length of the cable. At the trunk cable's proximal end the connector protrudes slightly to enable connection to the monitor console; at the distal end the trunk cable may protrude sufficiently to allow connection of the serial cable, and the region of such connection may then be inserted inside the sheath so that the trunk cable at its distal end is fully protected by the sheath. As previously described, the distal end of the trunk cable and its mating to the proximal end of the serial cable, or the proximal end of the intermediate cable in the second configuration, are always maintained outside of the infectious zone, and this is maintained during disposition of the sheath around and over said cables.

FIG. **10B** is a longitudinal section along the central axis of another configuration depicting a sheath with a compact telescopic form, which may be drawn along the entire length of the trunk cable and connections made as described above for a pleated sheath. The telescopic sheath **1090** is generally shown, with overlying folds **1091**, end-partition **1092** possessing apertures **1093a** and **1093b**.

The apertures **1083** and **1093**, if true voids in the material of the end-partition, are smaller than the diameter of the cable so that the end-partition snugly surrounds the cable and seals it from the external environment. Alternatively, the aperture may be replaced by a slit which is parted to insert the cable. End-partitions **1082** and **1092** are advantageously elastic or compliant materials to perform the function of a seal around the cable. If the material comprising the end-partition is sponge-like, it may be impregnated with an antimicrobial, which would be wiped along the cable during insertion as the end-partition is drawn along the entire length of the cable.

The sheath material may be made of any number of elastomeric materials, and may or may not incorporate an antimicrobial agent. Alternatively, the anti-microbial agent may be applied to the inner and/or outer surfaces of the sheath material.

While the two configurations of a sheath depicted herein show the sheath material in a folded manner in order to reduce the space needed to package the component, an alternative means of collapsing the sheath may be to simply bundle or bunch the material together.

Other configurations for the sheath (not shown) may consist of other means for enclosing each end of the sheath to capture it against the cable or the connector. In one configuration an adhesive material may be applied to the end of the sheath, which is then compressed against the cable or connector. Alternatively, the ends may be made with an elastic band or other cinching means which can cinch down against the cable or the connector.

Yet other configurations of the sheath may provide sufficient material to allow the sheath to extend over multiple

cables of the monitoring system. In this configuration the sheath would extend into the infectious zone. It may also be made of sufficient length to reach from the monitor to the patient along the entire length of multiple cables.

While preferred configurations have been described with particularity and with reference to the drawings, modifications and variations of the foregoing will be apparent to those of skill in the art utilizing the techniques disclosed herein. It is, therefore, to be understood that such configurations are illustrative and not limiting on the scope of the present application and that the application encompasses such modifications and variations.

What is claimed is:

1. A monitoring system for transmission of information from a patient residing within an infectious zone to a monitor console using a cable assembly, said monitoring system comprising:

A monitor console to process and/or display said information from said patient; and

A cable assembly comprising a trunk cable and a serial cable;

Said trunk cable being of a first length and comprising a proximal end and a distal end, said proximal end adapted to interface with said monitor console, said distal end comprising a connector, said first length defined as the distance from said proximal end to said distal end;

Said serial cable being of a second length and comprising a proximal end and a distal end, said proximal end comprising a connector, said distal end comprising at least one sensor device adapted to interface with said patient and capture said information from said patient, said second length defined as the distance from said proximal end to said distal end;

wherein said trunk cable distal end connector and said serial cable proximal end connector are each adapted to couple to one another;

wherein said cable assembly comprising said serial cable connector coupled to said trunk cable connector is configured to transmit said information from said patient to said monitor console when said sensor device is interfaced with said patient and said trunk cable is interfaced with said monitor console;

wherein said patient resides within and is surrounded by an infectious zone having an outer boundary demarcated by a perimeter located beyond the reach of any portions of said patient's body;

wherein the location of said perimeter is defined by said patient's caregiver;

wherein said monitor console resides entirely outside said perimeter of said infectious zone, said monitor console being located a distance from said perimeter, said distance being of a third length;

wherein said first length is less than said third length such that when said trunk cable proximal end is interfacing with said monitor console said trunk cable distal end connector cannot contact said perimeter of said infectious zone; and

wherein the combination of said serial cable coupled to said trunk cable together has a total length equal to or greater than a distance from said sensor device interfacing with said patient to said monitor console.

2. The system of claim 1 wherein said sensor device is of a type to capture said information related to at least one of the functions of electrocardiogram, heart rate, respiration, temperature, blood pressure, bio-impedance, blood oxygen,

## 11

ultrasound, electro-encephalography, pulse-oximetry and generates a signal to be transmitted along said cable assembly to said monitor.

3. The system of claim 1 wherein said serial cable is disposable.

4. The system of claim 1 wherein said serial cable and said trunk cable are electrical cables.

5. The system of claim 1 wherein said serial cable and said trunk cable are pneumatic cables and said sensor is adapted to interface with said patient's respiratory system.

6. The system of claim 1 wherein said serial cable and said trunk cable are fiber-optic cables.

7. The system of claim 1 wherein said serial cable and said trunk cable are filled with a fluid.

8. The system of claim 1 further comprising a sheath adapted to be disposed over said trunk cable and/or said serial cable;

wherein said trunk cable and/or said serial cable are encased in said sheath.

9. The cable assembly of claim 1 wherein said at least one sensor device is adapted to couple to said serial cable distal end.

10. The cable assembly of claim 1 further comprising an intermediate cable being of a fourth length and comprising a proximal end and a distal end, said proximal end comprising a connector and said distal end comprising a connector, said fourth length defined as the distance from said proximal end to said distal end;

wherein said intermediate cable proximal end connector and said trunk cable distal end connector are each adapted to couple to one another;

wherein said intermediate cable distal end connector and said serial cable proximal end connector are each adapted to couple to one another;

wherein said cable assembly comprising said serial cable coupled to said intermediate cable and said intermediate cable coupled to said trunk cable is configured to transmit said information from said patient to said monitor console when said sensor device is interfaced with said patient and said trunk cable is interfaced with said monitor console;

wherein said second length is less than the distance from said sensor device interfacing with said patient to said trunk cable distal end connector such that said serial cable proximal end connector cannot extend to a position to be able to couple to said trunk cable distal end connector; and

wherein the combination of said serial cable coupled to said intermediate cable and said intermediate cable coupled to said trunk cable together has a total length equal to or greater than the distance from said sensor device to said monitor console.

11. The apparatus of claim 10 wherein said second length is less than the distance from said sensor device interfacing with said patient to said perimeter such that said serial cable proximal end connector cannot extend beyond said perimeter of said infectious zone.

12. A monitoring system for transmission of electrocardiographic signals from a patient residing within an infectious zone to a monitor console using a cable assembly, said monitoring system comprising:

A monitor console to process and/or display said signals from said patient; and

A cable assembly comprising of a trunk cable and a serial cable;

said trunk cable being of a first length and comprising a proximal end and a distal end, said proximal end adapted

## 12

to interface with said monitor console, said distal end comprising a connector, said first length defined as the distance from said proximal end to said distal end;

said serial cable being of a second length and comprising a proximal end and a distal end, said proximal end comprising a connector, said distal end comprising at least one electrode adapted to interface with said patient and capture said electrocardiographic signals from said patient, said second length defined as the distance from said proximal end to said distal end;

wherein said trunk cable distal end connector and said serial cable proximal end connector are each adapted to couple to one another;

wherein said cable assembly comprising said serial cable connector coupled to said trunk cable connector is configured to transmit said electrocardiographic signals from said patient to said monitor console when said electrode is interfaced with said patient and said trunk cable is interfaced with said monitor console;

wherein said patient resides within and is surrounded by an infectious zone having an outer boundary demarcated by a perimeter located beyond the reach of any portions of said patient's body;

wherein the location of said perimeter is defined by said patient's caregiver;

wherein said monitor console resides entirely outside said perimeter of said infectious zone, said monitor console being located a distance from said perimeter, said distance being of a third length;

wherein said first length is less than said third length such that when said trunk cable proximal end is interfacing with said monitor console said trunk cable distal end connector cannot contact said perimeter of said infectious zone; and

wherein the combination of said serial cable coupled to said trunk cable together has a total length equal to or greater than a distance from said electrode interfacing with said patient to said monitor console.

13. The cable assembly of claim 12 further comprising an intermediate cable being of a fourth length and comprising a proximal end and a distal end, said proximal end comprising a connector and said distal end comprising a connector, said fourth length defined as the distance from said proximal end to said distal end;

wherein said intermediate cable proximal end connector and said trunk cable distal end connector are each adapted to couple to one another;

wherein said intermediate cable distal end connector and said serial cable proximal end connector are each adapted to couple to one another;

wherein said cable assembly comprising said serial cable coupled to said intermediate cable and said intermediate cable coupled to said trunk cable is configured to transmit said electrocardiographic signals from said patient to said monitor console when said electrode is interfaced with said patient and said trunk cable is interfaced with said monitor console;

wherein said second length is less than the distance from said electrode interfacing with said patient to said trunk cable distal end connector such that said serial cable proximal end connector cannot extend to a position to be able to couple to said trunk cable distal end connector, and

wherein the combination of said serial cable coupled to said intermediate cable and said intermediate cable coupled to said trunk cable together has a total length

## 13

equal to or greater than the distance from said electrode interfacing with said patient to said monitor console.

14. The apparatus of claim 13 wherein said second length is less than the distance from said electrode interfacing with said patient to said perimeter such that said serial cable proximal end connector cannot extend beyond said perimeter of said infectious zone.

15. The cable assembly of claim 12 wherein said at least one electrode is adapted to couple to said serial cable distal end.

16. A method of preventing the transfer of infective agents along a series of patients utilizing a monitoring system, said monitoring system to be subsequently used consecutively amongst said series of patients, comprising:

Defining an infectious zone surrounding said patient that is contaminated with infective agents, said infectious zone having an outer boundary demarcated by a perimeter located beyond the reach of any portions of said patient's body and where the location of said perimeter is defined by said patient's caregiver;

Deploying a monitor console configured to process and/or display information conveyed from said patient, and placing said monitor console outside of said perimeter of said infectious zone such that it resides a distance from said perimeter, said distance defined by a third length;

Deploying a cable assembly comprising a trunk cable and a serial cable, said trunk cable being of a first length and comprising a proximal end adapted to interface with said monitor console and a distal end comprising a connector, said first length defined as the distance from said proximal end to said distal end,

said serial cable being of a second length and comprising a proximal end and a distal end, said proximal end comprising a connector and a said distal end comprising a sensor device adapted to interface with said patient, said second length defined as the distance from said proximal end to said distal end,

said trunk cable distal end connector and said serial cable proximal end connector adapted to couple to one another;

wherein said first length is less than said third length such that when said trunk cable proximal end is interfacing with said monitor console, said trunk cable distal end connector cannot contact said perimeter of said infectious zone, and

wherein the combination of said serial cable coupled to said trunk cable together has a total length equal to or greater than a distance from said sensor device interfacing with said patient to said monitor console;

Connecting said patient to said monitor console through said cable assembly;

wherein said connecting said patient comprises the steps of:

- (1) Interfacing said trunk cable proximal end to said monitor console and placing the entirety of said trunk cable in a position outside said perimeter of said infectious zone;
  - (2) Coupling said trunk cable distal end connector to said serial cable proximal end connector such that both connectors are positioned outside said perimeter of said infectious zone;
  - (3) Extending said serial cable distal end into said infectious zone to reach said patient; and
  - (4) Interfacing said sensor device to said patient so that information can be acquired from said patient and transmitted to said monitor console;
- Monitoring said patient for a period of time;

## 14

Disconnecting said patient from said monitor console by decoupling said serial cable proximal end connector from said trunk cable distal end connector while maintaining the trunk cable outside said perimeter of said infectious zone, thereby keeping said trunk cable and said monitor console free from contamination and preventing said transfer of said infective agents to a subsequent patient in said series of patients.

17. The method of claim 16 further comprising a sheath adapted to be disposed over a said trunk cable such that said trunk cable is encased in said sheath, wherein said step of connecting said patient to said monitor further comprises the step of disposing said sheath over said trunk cable.

18. The method of claim 17 wherein said sheath has a length greater than said trunk cable and said step of disposing said sheath over said trunk cable further comprises extending said sheath distally over a portion of said serial cable.

19. A monitoring system for transmission of information from a patient residing within an infectious zone to a monitor console using a cable assembly, said monitoring system comprising:

A monitor console to process and/or display said information from said patient; and

A cable assembly comprising a trunk cable, an intermediate cable, and a serial cable;

said trunk cable being of a first length and comprising a proximal end and a distal end, said proximal end adapted to interface with said monitor console, said distal end comprising a connector, said first length defined as the distance from said proximal end to said distal end;

said intermediate cable being of a second length and comprising a proximal end and a distal end, said proximal end comprising a connector and said distal end comprising a connector, said second length defined as the distance from said proximal end to said distal end; and

said serial cable being of a third length and comprising a proximal end and a distal end, said proximal end comprising a connector, said distal end comprising at least one sensor device adapted to interface with said patient and capture said information from said patient, said third length defined as the distance from said proximal end to said distal end;

wherein said trunk cable distal end connector and said intermediate cable proximal end connector are each adapted to couple to one another;

wherein said intermediate cable distal end connector and said serial cable proximal end connector are each adapted to couple to one another;

wherein said cable assembly comprising said serial cable coupled to said intermediate cable and said intermediate cable coupled to said trunk cable is configured to transmit said information from said patient to said monitor console when said sensor device is interfaced with said patient and said trunk cable is interfaced with said monitor console;

wherein said patient resides within and is surrounded by an infectious zone having an outer boundary demarcated by a perimeter located beyond the reach of any portions of said patient's body;

wherein the location of said perimeter is defined by said patient's caregiver;

wherein said monitor console resides entirely outside of said perimeter, said monitor console being located a distance from said perimeter, said distance being of a fourth length;

wherein said first length is less than said fourth length such that when said trunk cable proximal end is interfacing

15

with said monitor console said trunk cable distal end connector cannot contact said perimeter of said infectious zone;

wherein said third length is less than the distance from said sensor device interfacing with said patient to said trunk cable distal end connector such that said serial cable proximal end connector cannot extend to a position to be able to couple to said trunk cable distal end connector; and

wherein the combination of said serial cable coupled to said intermediate cable and said intermediate cable coupled to said trunk cable together has a total length equal to or greater than a distance from said sensor device interfacing with said patient to said monitor console.

20. The cable assembly of claim 19 wherein said at least one sensor device is adapted to couple to said serial cable distal end.

21. The system of claim 19 further comprising a sheath adapted to be disposed over a said trunk cable and/or said intermediate cable and/or said serial cable;

wherein said trunk cable and/or said intermediate cable and/or said serial cable are encased in said sheath.

22. The apparatus of claim 19 wherein said third length is less than the distance from said sensor device interfacing with said patient to said perimeter such that said serial cable proximal end connector cannot extend beyond said perimeter of said infectious zone.

23. A method of preventing the transfer of infective agents along a series of patients utilizing monitoring system, said monitoring system to be subsequently used consecutively amongst said series of patients, comprising:

Defining an infectious zone surrounding said patient that is contaminated with infective agents, said infectious zone having an outer boundary demarcated by a perimeter located beyond the reach of any portions of said patient's body and where the location of said perimeter is defined by said patient's caregiver;

Deploying a monitor console configured to process and/or display information conveyed from said patient, and placing said monitor console outside of said perimeter of said infectious zone such that it resides a distance from said perimeter, said distance defined by a fourth length;

Deploying a cable assembly comprising a trunk cable, an intermediate cable, and a serial cable,

said trunk cable being of a first length and comprising a proximal end adapted to interface with said monitor console and a distal end comprising a connector, said first length defined as the distance from said proximal end to said distal end,

said intermediate cable being of a second length and comprising a proximal end and a distal end, said proximal end comprising a connector and said distal end comprising a connector, said second length defined as the distance from said proximal end to said distal end;

said serial cable being of a third length and comprising a proximal end and a distal end, said proximal end comprising a connector and said distal end comprising at least one sensor device adapted to interface with said

16

patient, said third length defined as the distance from said proximal end to said distal end;

said trunk cable distal end connector and said intermediate cable proximal end connector adapted to couple to one another; and

said intermediate cable distal end connector and said serial cable proximal end connector adapted to couple to one another;

wherein said first length is less than said fourth length such that when said trunk cable proximal end is interfacing with said monitor console, said trunk cable distal end connector cannot contact said perimeter of said infectious zone; and

wherein the combination of said serial cable coupled to said intermediate cable and said intermediate cable coupled to said trunk cable together has a total length equal to or greater than a distance from said sensor device interfacing with said patient to said monitor console;

Connecting said patient to said monitor console through said cable assembly;

wherein said connecting said patient comprises the steps of:

- (1) Interfacing said trunk cable proximal end to said monitor console and placing the entirety of said trunk cable in a position outside said perimeter of said infectious zone;
- (2) Coupling said trunk cable distal end connector to said intermediate cable proximal end connector such that both connectors are positioned outside said perimeter of said infectious zone;
- (3) Interfacing said sensor device with said patient; and
- (4) Extending said intermediate cable distal end towards said patient and coupling it to said serial cable proximal end connector such that said patient is connected to said monitor console so that information can be acquired from said patient and transmitted to said monitor console;

Monitoring said patient for a period of time;

Disconnecting said patient from said monitor console by decoupling said intermediate cable proximal end connector from said trunk cable distal end connector while maintaining said trunk cable outside said perimeter of said infectious zone, thereby keeping said trunk cable and said monitor console free from contamination and preventing said transfer of said infective agents to a subsequent patient in said series of patients.

24. The method of claim 23 further comprising a sheath adapted to be disposed over said trunk cable and/or said intermediate cable such that said trunk cable and/or said intermediate cable is encased in said sheath, wherein said step of connecting said patient to said monitor further comprises the step of disposing said sheath over said trunk cable and/or said intermediate cable.

25. The method of claim 23 wherein said third length is less than the distance from said sensor device interfacing with said patient to said perimeter such that said serial cable proximal end connector cannot extend beyond said perimeter of said infectious zone.

\* \* \* \* \*

|                |                                                                                                                                                                      |         |            |
|----------------|----------------------------------------------------------------------------------------------------------------------------------------------------------------------|---------|------------|
| 专利名称(译)        | 用于监控系统的电缆配置                                                                                                                                                          |         |            |
| 公开(公告)号        | <a href="#">US9149186</a>                                                                                                                                            | 公开(公告)日 | 2015-10-06 |
| 申请号            | US13/337034                                                                                                                                                          | 申请日     | 2011-12-23 |
| [标]申请(专利权)人(译) | GRAYZEL JOSEPH<br>GRAYZEL JEFFREY                                                                                                                                    |         |            |
| 申请(专利权)人(译)    | GRAYZEL JOSEPH<br>GRAYZEL JEFFREY                                                                                                                                    |         |            |
| 当前申请(专利权)人(译)  | GRAYZEL , JOSEPH<br>GRAYZEL , JEFFREY                                                                                                                                |         |            |
| [标]发明人         | GRAYZEL JOSEPH<br>GRAYZEL JEFFREY                                                                                                                                    |         |            |
| 发明人            | GRAYZEL, JOSEPH<br>GRAYZEL, JEFFREY                                                                                                                                  |         |            |
| IPC分类号         | A61B5/00 A61B5/0428 A61B5/0205 A61B5/021                                                                                                                             |         |            |
| CPC分类号         | A61B5/00 A61B5/04286 A61B5/021 A61B5/02055 A61B2562/221 A61B2562/225 A61B2562/247<br>A61B5/002 A61B5/0402 A61B5/0476 A61B8/00 A61B2562/222 A61B2562/223 A61B2562/224 |         |            |
| 审查员(译)         | THOMSON , WILLIAM                                                                                                                                                    |         |            |
| 助理审查员(译)       | ARCHER , MARIE                                                                                                                                                       |         |            |
| 优先权            | 61/426806 2010-12-23 US                                                                                                                                              |         |            |
| 其他公开文献         | US20120165621A1                                                                                                                                                      |         |            |
| 外部链接           | <a href="#">Espacenet</a> <a href="#">USPTO</a>                                                                                                                      |         |            |

#### 摘要(译)

连接监测设备与人类患者的电缆的物理配置，其中所述患者及其周围环境限定潜在的传染性污染区域。该配置使监视器和主干线电缆位于污染区域之外，并且一个或多个串行电缆连接到干线电缆并进入污染区域以提供与患者的接触。这种物理配置可以防止监视器和干线电缆的污染，因此它们可以在连续的患者身上重复使用，而接触患者及其污染区的轻便且廉价的串行电缆可以是一次性的。提供监视各种生理变量的示例以举例说明这种物理配置的通用概念。还描述了对无线传输的适应。

