



US006385821B1

(12) **United States Patent**
Modgil et al.

(10) **Patent No.:** **US 6,385,821 B1**
(45) **Date of Patent:** **May 14, 2002**

- (54) **APPARATUS FOR SECURING AN OXIMETER PROBE TO A PATIENT**
- (75) Inventors: **Onkar S. Modgil**, Plano, TX (US);
Christopher G. Chin, Grenada Hills, CA (US)
- (73) Assignee: **UDT Sensors, Inc.**, Hawthorne, CA (US)
- (*) Notice: Subject to any disclaimer, the term of this patent is extended or adjusted under 35 U.S.C. 154(b) by 0 days.

4,114,838 A	9/1978	Knauf	
4,530,350 A	7/1985	Brown et al.	
4,825,879 A	5/1989	Tan et al.	128/633
4,865,038 A	9/1989	Rich et al.	128/633
4,926,501 A	5/1990	Goosen	
5,131,118 A	7/1992	Breeher	
5,147,216 A	9/1992	Shotey	
5,209,230 A	5/1993	Swedlow et al.	128/633
5,339,810 A	8/1994	Ivers et al.	128/633
5,368,025 A	11/1994	Young et al.	128/633
5,437,275 A	8/1995	Amundsen et al.	128/633
5,715,535 A	2/1998	Hamilton et al.	
5,742,945 A	4/1998	Lindaman	
5,830,136 A	11/1998	Delonzor et al.	600/323
RE36,000 E	12/1998	Swedlow et al.	128/633
5,919,133 A	7/1999	Taylor et al.	
5,925,027 A	7/1999	Schmitz	

- (21) Appl. No.: **09/506,467**
- (22) Filed: **Feb. 17, 2000**

- (51) **Int. Cl.⁷** **A44B 21/00**
- (52) **U.S. Cl.** **24/306; 24/304**
- (58) **Field of Search** 24/442, 306, 304,
24/16 R, DIG. 11; 128/880, DIG. 15, DIG. 26;
439/369, 371; 137/375; 600/322, 323, 340,
344, 379, 384, 386


- (56) **References Cited**
U.S. PATENT DOCUMENTS
- 2,253,108 A 8/1941 Casey, Jr.
- 2,985,552 A 5/1961 Watanabe
- 3,232,289 A 2/1966 Zimmerman

Primary Examiner—James R. Brittain
(74) *Attorney, Agent, or Firm*—Lyon & Lyon LLP

(57) **ABSTRACT**

A strap or fastener for removably securing an oximeter probe to the appendage of a patient. The strap is made of an elastic material that wraps around the outside of the oximeter probe and is secured to the oximeter probe by attachment mechanisms such as Velcro that can be readjusted after initial application without producing excessive stress on the spring hinge of the oximeter probe.

16 Claims, 5 Drawing Sheets






FIG. 1






FIG. 2






FIG. 5




FIG. 6




FIG. 7




FIG. 8




FIG. 9




FIG. 10




FIG. 11




FIG. 12

APPARATUS FOR SECURING AN OXIMETER PROBE TO A PATIENT

BACKGROUND OF THE INVENTION

The present invention relates to medical sensors for detecting physiological functions and, in particular, to an apparatus for securing an oximeter probe to an appendage of a patient.

Pulse oximetry is a non-invasive medical technique useful for measuring certain vascular conditions. A pulse oximetry system comprises a sensor appliance containing a light source, such as an L.E.D., and a light sensor, such as a photodetector, and is mounted to the finger, toe or earlobe of a patient. The oximetry sensor emits light, which is scattered through a portion of the patient's tissue where blood perfuses the tissue and the light sensor photoelectrically senses the absorption of light in such tissue. The measurement of light absorbed is used to evaluate various characteristics of a patient such as oxygen saturation of hemoglobin in arterial blood, the volume of individual blood pulsations supplying the tissue, and the rate of blood pulsations corresponding to each heartbeat of a patient.

One kind of commonly used oximetry probe **110** is illustrated in FIGS. **1** and **2**. The probe **110** comprises first and second outer shells **112**, **114**, a spring hinge **116** at the distal end of the probe **110**, first and second extending tabs **118**, **120**, first and second inner pads **122**, **124**, and a cord **128** connected to the proximal end of the probe. FIG. **1** depicts the oximeter probe **110** in use. The first and second outer shells **112**, **114** are separated by forcing the first and second extending tabs **118**, **120** toward one another. The patient's finger or other appendage is then slipped between the first and second inner pads **122**, **124**. On the exposed faces of the first and second inner pads **122**, **124** are the photoemitter and photodetector used to measure various vascular conditions of the patient. The data from the photodetector is then transmitted to an attached console electrical cord **128**.

The spring hinge **116** is soft because excessive pressure on the finger can distort pulsations in the finger's blood supply. As a result, oximetry sensors frequently fall off the patient's finger when the patient is allowed to move unrestrained.

To prevent excessive movement of a finger to which the probe **110** is attached, medical personnel may secure the hand or arm to the patient's bed or a stationary object located nearby. A patient would be allowed to move the arm and hand more freely so that discomfort to the patient is avoided. To allow for the patient to move freely while not compromising the security of the oximeter probe **110** upon the finger, an additional means of securing the probe **110** to the patient is necessary.

Further, even small movements by the patient can cause differential motion between the oximeter probe **110** and the patient because the physical construction of the sensors renders them bulky and difficult to securely fasten to a patient's appendage. Such differential motion causes the signal received by the light sensor to be distorted, resulting in inaccurate measurements of the amount of blood constituent being evaluated.

In practice, reusable oximeter probes are frequently secured to the patient's appendage using adhesive tape. This method requires that the adhesive tape be applied such that sufficient pressure is applied to the patient's finger to securely fasten the oximeter probe **110**, but not so much that vasoconstriction occurs. If the practitioner creates too much

or too little pressure during the initial application of the adhesive tape, it becomes necessary to remove the adhesive tape from the body of the oximeter probe **110** and replace it in a different position. Such readjustment is made difficult by the bond between the tape and the shell of the oximeter probe **110**. In addition, the residual adhesive remaining on the shell increases risk of contamination. Further, if the tape is in contact with both the patient's skin and the oximeter probe **110**, removal of the adhesive tape from the patient's skin can cause irritation, especially when the patient's skin is particularly sensitive due to trauma or age.

Often, when adhesive tape is used to secure an oximeter probe to the appendage of the patient, the adhesive tape stresses the structure of the oximeter probe. Such distortion occurs if the adhesive tape is not applied with substantially equal pressure on both side openings of the oximeter probe. The undue stress on the spring mechanism that results from such distortion shortens the useful life span of the oximeter probe. Additionally, use of adhesive tape to secure the oximeter probe to the patient also decreases the useful life span of the oximeter probe by making sterilization of the oximeter probe after each use difficult because of adhesive build up. When adhesive tape is removed from the oximeter probe, residue of the adhesive remains on the shell of the probe. Removing the residue may require vigorous scrubbing and/or use of abrasive cleaning agents.

Another concern when securing an oximeter probe to a patient is ensuring that ambient light does not interfere with the signal being received by the photodetector. Outside light is easily scattered and transmitted within the tissue toward the photodetector because skin tissue is translucent. This ambient light causes interference with the signal detected at the photodetector.

Further, vasoconstriction may also be caused by exposure of the appendage to the often cool outside air. Low temperature induced vasoconstriction and the resultant decrease in blood supply may significantly affect the performance of the oximeter probe. Conventional attempts to alleviate the problem of low temperature vasoconstriction include using an integral heater with the sensor and periodic massaging. Heaters, however, must be well regulated to avoid overheating. Furthermore, they increase the complexity of the sensor and can be costly. Periodic massaging can be effective, but usually requires removal of the probe while the appendage is massaged. After some massaging of the appendage to stimulate blood flow to it, the probe is reapplied and measurement resumed. It would be desirable to employ a less complex, passive means for retaining body heat that does not interrupt the measurement process.

SUMMARY OF THE INVENTION

The present invention is preferably a strap for securing an oximeter probe to an appendage of a patient. The strap is preferably made of elastic material and may be removably secured to the outside of an oximeter probe to allow for readjustment of the strap after initial application without producing excessive stress on the spring hinge of the oximeter probe.

In one embodiment, the strap is preferably a patch of material comprising a body, a tab located at a proximal end of the body and connected to the body of the strap by a narrow neck, an attachment mechanism for securing the body of the strap about an oximeter probe, and another attachment mechanism for securing the tab about the cord of an oximeter probe. Preferably, at a distal end of the body of the strap is a flap which has a slit through which the

extending flap of the top shell of the oximeter probe may be placed to prevent excessive longitudinal movement of the strap.

In another embodiment of the present invention, the strap is preferably a patch of material comprising a body, a tab located at a proximal end of the body and connected to the body of the strap by a narrow neck, one attachment mechanism for securing the body of the strap, a second attachment mechanism for securing the tab and a third attachment mechanism preferably substantially perpendicular to the first and second attachment mechanisms for preventing excessive longitudinal movement of the strap.

In yet another embodiment of the strap, the strap preferably comprises two flaps connected by a neck, one of the flaps having a tab. The strap is secured to the oximeter probe by placing the flaps on opposing sides of the oximeter probe and placing the neck along the spring hinge at the distal end of the oximeter probe. An attachment mechanism is wrapped around the strap enclosing the body of the oximeter probe to secure the probe to an appendage of a patient while a second attachment mechanism is wrapped around the tab of the strap enclosing the cord neck of the oximeter probe to prevent excessive longitudinal movement of the strap.

In yet another embodiment of the present invention the strap is preferably conformed as a sock which, in use, is slipped over the oximeter probe. The strap further comprises two attachment mechanisms. One attachment mechanism is wrapped around the strap about the body of the oximeter probe so that the spring hinge is appropriately compressed on the appendage of the patient. The other is wrapped around the strap enclosing the cord neck of the oximeter probe.

For a fuller understanding of the nature of the present invention, reference should be made to the ensuing detailed description taken in conjunction with the accompanying drawings.

BRIEF DESCRIPTION OF THE DRAWINGS

In the drawings:

FIG. 1 is a perspective view from the proximal end of an oximeter probe.

FIG. 2 is a perspective view from the distal end of an oximeter probe.

FIG. 3 is a perspective view of a preferred embodiment of the oximeter probe strap according to the present invention.

FIG. 4 is a perspective view, from the proximal end of the oximeter probe, of the strap depicted in FIG. 3 in use.

FIG. 5 is a perspective view of a second preferred embodiment of the oximeter probe strap according to the present invention.

FIG. 6 is a perspective view, from the proximal end of the oximeter probe, of the strap depicted in FIG. 5 in use.

FIG. 7 is a perspective view, from the distal end of the oximeter probe, of the strap depicted in FIG. 5 in use.

FIG. 8 is a perspective view of a third preferred embodiment of the oximeter probe strap according to the present invention.

FIG. 9 is a perspective view, from the proximal end of the oximeter probe, of the strap depicted in FIG. 8 in use.

FIG. 10 is a perspective view, from the distal end of the oximeter probe, of the strap depicted in FIG. 8 in use.

FIG. 11 is a perspective view of a fourth preferred embodiment of the oximeter probe strap according to the present invention.

FIG. 12 is a perspective view, from the distal end of the oximeter probe, of the strap depicted in FIG. 11 in use.

DETAILED DESCRIPTION OF THE PREFERRED EMBODIMENTS

FIGS. 1 and 2 illustrate a reusable oximeter probe 110 commonly used in the medical industry. FIG. 1 is a per-

spective view taken from the proximal end of the oximeter probe 110 while attached to a patient. FIG. 2 depicts the oximeter probe 110 from the distal end in its neutral position.

The oximeter probe 110 comprises a first and second outer shell 112, 114, a spring hinge 116 at the distal end of the probe, first and second extending tabs 118, 120, first and second inner pads 122, 124, a cord sleeve 126, and a cord 128. FIG. 1 depicts the oximeter probe in use. The first and second outer shells 112, 114 are separated by pressing the first and second extending tabs 118, 120 toward one another. The patient's finger or other appendage is then slipped between the first and second inner pads 122, 124. On the inside faces of the first and second inner pads 122, 124 are a photoemitter and a photodetector (not shown) used to measure various vascular conditions of the patient. The data from the photodetector is then transmitted to an attached console via the cord 128.

FIG. 3 is a perspective view of a preferred embodiment of an oximeter probe strap comprising a body 202, a tab 206 located at the proximal end of the body 202, a first attachment mechanism 210 for securing the body 202 of the strap 200, and a second attachment mechanism 214 for securing the tab 206. The tab 206 is preferably connected to the body 202 of the strap 200 by a preferably narrow strip 204, the body 202, tab 206, and strip 204 preferably constituting a single patch of elastic material.

The strap may also include a flap 218 at the end opposing the strip 204, the flap 218 having a slit 216 through which the extending tab 118 of the top shell 112 of the oximeter probe 110 may be placed, as shown in FIG. 4. It is preferable that the strap 200 include the flap 218 with the slit 216 so that longitudinal movement of the strap 200 along the hard outer shells 112, 114 of the oximeter probe 110 may be minimized.

The strap 200 preferably has a total length (from proximal to distal end) of approximately 3.0 inches. The width of the body 202 preferably is approximately 3.5 inches and the width of the tab 206 preferably is approximately 1.25 inches. The body 202 and the tab 206 constitute one patch of elastic material that is preferably composed of a foam laminate with brushed nylon that is hook engagable.

As illustrated in FIG. 4, on a surface of the body 202 of the strap 200 is the first attachment mechanism 210 for securing the strap 200 about the oximeter probe 110 such that the spring hinge 116 of the oximeter probe 110 is appropriately compressed to maintain secure contact between the inner surfaces 122, 124 of the oximeter probe 110 and the appendage of the patient. The first attachment mechanism 210 preferably is comprised of a patch of hook material, such as Velcro, which may be adhesively laminated 210 to the material of the strap 200 as shown in FIG. 3. Alternatively, the first attachment mechanism 210 may be comprised of adhesive strip or a patch of hook material separate from the strap 200.

On a surface of the tab 206 is a second attachment mechanism 214 for holding the strap 200 about the cord sleeve 126 of the oximeter probe 110. Like the first attachment mechanism 210, the second attachment mechanism 214 preferably comprises a patch of hook material, such as Velcro, which may be adhesively laminated 212 to the tab 206 as shown in FIG. 3. Alternatively, the second attachment mechanism 214 may constitute an adhesive strip or a patch of hook material separate from the strap 200.

In use, after the patient's appendage is secured in the probe 110, the body 202 of the strap 200 may be placed over

the top portion of the hard shell **112** of the oximeter probe **110** with the extending tab **118** of the top portion of the hard shell placed through the slit **216** in the flap **218** of the strap **200**. The first attachment mechanism **210** may be wrapped around the outer surface of the body **202** of the strap **200** enclosing the upper and lower hard shells **112**, **114** of the oximeter probe **110**. The second attachment mechanism **214** may be wrapped around the tab **206**, enclosing the cord sleeve **126** of the oximeter probe **110**.

When hook material is used for the first and second attachment mechanisms **210**, **212**, the attachment mechanisms can be secured directly to the elastic material that constitutes the strap **200**. When adhesive strips are used for the attachment mechanisms **210**, **212** the strips may be placed around the entire circumference so that the opposing ends of the adhesive strips overlap to allow for a secure bond. Using hook material as the attachment mechanism may be preferred over an adhesive strip because it may facilitate to a greater degree readjustment of the first attachment mechanism **210** about the strap **200** and the oximeter probe **110**.

The combination of the slit **216** in the body **202** of the strap **200** and the second attachment mechanism **214** wrapped around the tab **206** enclosing the cord sleeve **126** prevents excessive longitudinal movement of the strap **200** along the hard shells **112**, **114** of the oximeter probe **110**. Likewise, the attachment mechanism **210** of the body **202** of the strap **200** holds the oximeter probe **110** securely to the appendage of the patient by reinforcing the spring action of the spring hinge **116**.

FIGS. 5-7 illustrate an alternative preferred embodiment of an oximeter probe strap. FIG. 5 is a perspective view of a strap **300** alone. FIG. 6 depicts the strap **300** in use as viewed from the proximal end of the oximeter probe **110**. FIG. 7 shows the strap **300** in use as viewed from the distal end of the oximeter probe **110**. As shown in FIG. 5, strap **300** is illustrated to have some of the same components as strap **200**. Numbers with identical second and third digits represent corresponding components.

The body **312** of the strap **300** preferably does not have a slit **216** as does the strap **200** depicted in FIG. 3. Instead, a third attachment mechanism **318** is attached to the body **302** of the strap **300** such that it preferably wraps around the distal end of the oximeter probe **110** and is attached to the opposite side of the body **302** of the strap **300** as shown in FIGS. 6-7.

The attachment mechanisms **310**, **314**, **318** are preferably comprised of a patch of hook material, such as Velcro, which may be adhesively laminated **308**, **312**, **316** to the material of the strap **300** as shown in FIG. 5. Alternatively, the attachment mechanisms **310**, **314**, **318** are comprised of an adhesive strip or a patch of hook material separate from the strap **300**.

Referring to FIGS. 6-7, the body **302** of the strap **300** is placed over the top portion of the hard shell **112** of the oximeter probe **110**. The first attachment mechanism **310** may be wrapped around the outer surface of the body **302** of the strap enclosing the upper and lower hard shells **112**, **114** of the oximeter probe **110**. The second attachment mechanism **314** of the tab **306** may be wrapped around the tab **306**, enclosing the cord sleeve **126** of the oximeter probe **110**. As illustrated in FIGS. 6-7, the third attachment mechanism **318** is attached **316** to the body **302** of the strap **300**, wrapped around the distal end of the oximeter probe **110** and attached to the body **302** of the strap **300** on the opposite side of the probe **110**.

The second attachment mechanism **314** may be placed around the tab **306** enclosing the cord sleeve **126** and the third attachment mechanism **318** may be placed around the distal end of the oximeter probe **110** to prevent excessive longitudinal movement of the strap **300** along the hard shells **112**, **114** of the oximeter probe **110**. Likewise, the first attachment mechanism **310** of the body **302** of the strap **300** holds the oximeter probe securely to the appendage of the patient by reinforcing the spring action of the spring hinge **116**.

Another preferred embodiment is shown in FIGS. 8-10. This embodiment of the oximeter probe strap **400** is comprised of a first flap **402A** and a second flap **402B**, a tab **406**, a connecting neck **418**, a first attachment mechanism **410** and a second attachment mechanism **414**. The first flap **402A** and the second flap **402B** are at opposite ends of the neck portion **418** of the strap **400**. The first attachment mechanism **410** attaches to the first flap **402A** and the second attachment mechanism attaches to the tab **406**.

In use, the first flap **402A** of the strap **400** is placed along the side of the oximeter probe **110** where the upper and lower shells **112**, **114** meet. The neck **418** of the strap **400** wraps around the distal end of the oximeter probe **110** and the second flap **402B** is placed along the side of the oximeter probe **110** where the upper and lower shells **112**, **114** meet, opposite the first flap **402A**. The first attachment mechanism **410** is wrapped around the surface of the first and second flaps **402A**, **402B**, such that the spring hinge **116** of the oximeter probe **110** is secured in an appropriately compressed position. The second attachment mechanism **414** is wrapped around the surface of the tab **406** enclosing the cord sleeve **126** of the oximeter probe **110**.

The first and second attachment mechanisms **410**, **414** preferably are comprised of a patch of hook material, such as Velcro, which may be adhesively laminated **408**, **412** to the material of the strap **400** as shown in FIG. 8. Alternatively, the first and second attachment mechanisms **408**, **412** are comprised of an adhesive strip or a patch of hook material separate from the strap **400**. If an adhesive strip is used, it is preferably wrapped completely around the surface of the strap **400** such that opposing ends of the adhesive strip overlap to ensure a secure bond. The use of hook material for the first and second attachment mechanisms **410**, **414** is preferred to facilitate readjustment of the attachment mechanisms **410**, **414**.

Another preferred embodiment is shown in FIGS. 11-12. This embodiment of the oximeter probe strap **500** is preferably comprised of at least one patch of fabric **502** in a sock-like apparatus with an opening **530**, a first attachment mechanism **510** and a second attachment mechanism **514**.

FIG. 12 depicts the strap **500** in use. The strap **500** may be slid over the oximeter probe **110** such that the body of the probe enclosing the patient's appendage is inside the fabric **502** and the cord **128** exits the strap **500** through the strap opening **530**. The first attachment mechanism **510** may be wrapped around the surface of the fabric **502** as a girth enclosing the first and second outer shells **112**, **114**, the spring hinge **116** and the first and second extending tabs **118**, **120** of the oximeter probe strap **110** such that the spring hinge **116** of the oximeter probe **110** is secured in an appropriately compressed position about the patient's appendage. The second attachment mechanism **514** is wrapped around the fabric **502** enclosing the cord sleeve **126** of the oximeter probe **110**.

The first and second attachment mechanisms **510**, **514** preferably are comprised of a patch of hook material, such

7

as Velcro, which may be adhesively laminated **508, 512** to the material of the strap **502** as shown in FIG. **11**. Alternatively, the first and second attachment mechanisms **508, 512** are comprised of an adhesive strip or a patch of hook material separate from the strap **500**. If an adhesive strip is used, it is preferably wrapped completely around the surface of the strap **500** such that opposing ends of the adhesive strip overlap to ensure a secure bond. The use of hook material for the first and second attachment mechanisms **510, 514** is preferred to facilitate readjustment of the attachment mechanisms **510, 514**.

As will be understood by those skilled in the art, the present invention may be embodied in other specific forms without departing from the essential characteristics thereof. Accordingly, the foregoing description is illustrative of the invention, but not limiting to the scope of the invention, which is set forth in the following claims.

What is claimed is:

1. A strap for an oximeter probe, comprising:
 - a patch comprising a body and a tab, the tab being connected by a strip to the body;
 - a first attachment mechanism for removably securing said body to outer shells of the oximeter probe; and
 - a second attachment mechanism for removably securing said tab to a cord of the oximeter probe;
 wherein said patch includes a flap opposing the strip, the flap having a slit configured for insertion of an extending tab of the oximeter probe.
2. The strap of claim **1** wherein said first attachment mechanism is substantially parallel to said second attachment mechanism.
3. The strap of claim **1**, said patch comprising an elastic hook engagable material.
4. The strap of claim **3**, said elastic hook engagable material being foam laminate having a brushed nylon surface.
5. The strap of claim **1** wherein said patch of material is approximately 3.0 inches from the proximal end to a distal end, said body portion is approximately 3.5 inches wide and said tab is approximately 1.25 inch wide.

8

6. The strap of claim **1**, said first and second attachment mechanisms comprising hook material.

7. The strap of claim **1**, said first and second attachment mechanisms comprising hooked material and at least one of the attachment mechanisms being adhesively laminated to said patch.

8. The strap of claim **1** wherein said first and second attachment mechanisms are adhesive strips.

9. A strap for an oximeter probe, comprising:

a patch comprising a body and a tab, the tab being connected by a strip to the body;

a first attachment mechanism for removably securing said body to outer shells of the oximeter probe;

a second attachment mechanism for removably securing said tab to a cord of the oximeter probe; and

a third attachment mechanism substantially perpendicular to said first and second attachment mechanisms for removably securing said body to the oximeter probe.

10. The strap of claim **9** wherein said first attachment mechanism is substantially parallel to said second attachment mechanism.

11. The strap of claim **9**, said patch comprising an elastic hook engagable material.

12. The strap of claim **11**, said elastic hook engagable material being foam laminate having a brushed nylon surface.

13. The strap of claim **9** wherein said patch of material is approximately 3.0 inches from the proximal end to a distal end, said body portion is approximately 3.5 inches wide and said tab is approximately 1.25 inch wide.

14. The strap of claim **9**, said first and second attachment mechanisms comprising hook material.

15. The strap of claim **9**, said first and second attachment mechanisms comprising hooked material and at least one of the attachment mechanisms being adhesively laminated to said patch.

16. The strap of claim **9** wherein said first and second attachment mechanisms are adhesive strips.

* * * * *

专利名称(译)	用于将血氧计探针固定到患者的装置		
公开(公告)号	US6385821	公开(公告)日	2002-05-14
申请号	US09/506467	申请日	2000-02-17
[标]申请(专利权)人(译)	UDT传感器		
申请(专利权)人(译)	UDT传感器, INC.		
当前申请(专利权)人(译)	OSI光电, INC.		
[标]发明人	MODGIL ONKAR S CHIN CHRISTOPHER G		
发明人	MODGIL, ONKAR S. CHIN, CHRISTOPHER G.		
IPC分类号	A61B5/00 A44B21/00		
CPC分类号	A61B5/14552 A61B5/6826 A61B5/6838 A61B5/6833 Y10T24/33 Y10T24/2708		
外部链接	Espacenet USPTO		

摘要(译)

一种带或紧固件，用于将血氧计探针可拆卸地固定到患者的附肢上。带子由弹性材料制成，其围绕血氧计探头的外部并且通过诸如Velcro的附接机构固定到血氧计探针，所述附接机构可以在初始应用之后重新调整，而不会在血氧计探针的弹簧铰链上产生过大的应力。

