



US009693697B2

(12) **United States Patent**
Tal et al.

(10) **Patent No.:** **US 9,693,697 B2**
(45) **Date of Patent:** **Jul. 4, 2017**

(54) **HAND-HELD DEVICE HAVING HEALTH MONITORING CAPABILITIES**

(56) **References Cited**

U.S. PATENT DOCUMENTS

(76) Inventors: **Benny Tal**, Ashkelon (IL); **Yair Tal**, Matan (IL); **Assaf Pressman**, Lehavim (IL)

4,995,399 A 2/1991 Hayashi
5,217,013 A * 6/1993 Lewis et al. 600/342
(Continued)

(*) Notice: Subject to any disclaimer, the term of this patent is extended or adjusted under 35 U.S.C. 154(b) by 99 days.

FOREIGN PATENT DOCUMENTS

EP 0821910 2/1998
EP 1407713 4/2004

(Continued)

(21) Appl. No.: **13/433,608**

(22) Filed: **Mar. 29, 2012**

OTHER PUBLICATIONS

(65) **Prior Publication Data**

US 2013/0261414 A1 Oct. 3, 2013

Frei et al.; Least squares acceleration filtering for the estimation of signal derivatives and sharpness at extrema [and application to biological signals]; IEEE Transactions on Biomedical Engineering, Jan. 1, 1999 Institute of Electrical and Electronics Engineers—ISSN 0018-9294; vol. 46, Nr:8, pp. 971-977; Jan. 1, 1999.

(Continued)

(51) **Int. Cl.**

A61B 5/00 (2006.01)
A61B 5/1455 (2006.01)

(Continued)

Primary Examiner — Eric Winakur

Assistant Examiner — Chu Chuan (JJ) Liu

(74) *Attorney, Agent, or Firm* — Morgan Lewis & Bockius LLP

(52) **U.S. Cl.**

CPC **A61B 5/02427** (2013.01); **A61B 5/0245** (2013.01); **A61B 5/0404** (2013.01); **A61B 5/0452** (2013.01); **A61B 5/14552** (2013.01); **A61B 2560/0462** (2013.01); **A61B 2560/0468** (2013.01); **A61B 2562/0209** (2013.01); **A61B 2562/0233** (2013.01); **A61B 2562/046** (2013.01); **A61B 2562/166** (2013.01)

(57)


ABSTRACT

A method, a computer readable media and a hand-held device, the hand-held device may include a first sensor that is positioned such as to be contacted by a first hand of a user when the user holds the hand-held device; a second sensor that is positioned such as to be contacted by a second hand of the user when the user holds the hand-held device; wherein at least one sensor of the first sensor and the second sensor is a hybrid sensor that comprises an electrode, an illumination element and a light detector; and a health monitoring module arranged to process detections signals from the electrode and from the light detector such as to provide processed signals that are indicative of a state of the user.

(58) **Field of Classification Search**

CPC **A61B 5/1455**; **A61B 5/14551**; **A61B 5/0452**; **A61B 5/0006**; **A61B 5/021**; **A61B 5/022**; **A61B 5/02255**; **A61B 5/0002**; **A61B 5/0059**; **A61B 5/145**
USPC **600/301**, **309**, **310**, **316**, **323**, **344**, **473**, **600/476**, **509**, **485**
See application file for complete search history.

26 Claims, 15 Drawing Sheets



(51) **Int. Cl.**

A61B 5/024 (2006.01)
A61B 5/0404 (2006.01)
A61B 5/0245 (2006.01)
A61B 5/0452 (2006.01)

FOREIGN PATENT DOCUMENTS

EP	1977688	10/2008
EP	2347706	7/2011
EP	2425768	3/2012
EP	2540221	1/2013
WO	WO03039326	5/2003
WO	WO 03039326	5/2003
WO	WO 2010087986	8/2010
WO	WO 2011060220	5/2011

(56)

References Cited

U.S. PATENT DOCUMENTS

5,218,962 A * 6/1993 Mannheimer A61B 5/14542
 600/331
 5,316,008 A 5/1994 Suga
 6,327,495 B1 * 12/2001 Iwabuchi A61B 5/0002
 600/485
 6,330,464 B1 * 12/2001 Colvin et al. 600/316
 6,334,065 B1 * 12/2001 Al-Ali et al. 600/323
 6,549,756 B1 * 4/2003 Engstrom A61B 5/02438
 600/509
 6,725,072 B2 * 4/2004 Steuer et al. 600/310
 6,801,648 B2 * 10/2004 Cheng A61B 5/14546
 356/342
 7,029,447 B2 4/2006 Rantala
 2002/0133066 A1 * 9/2002 Miller et al. 600/322
 2004/0015091 A1 * 1/2004 Greenwald et al. 600/513
 2004/0034294 A1 * 2/2004 Kimball et al. 600/323
 2004/0117212 A1 6/2004 Kong et al.
 2005/0261593 A1 11/2005 Zhang et al.
 2006/0009698 A1 1/2006 Banet
 2006/0211922 A1 * 9/2006 Al-Ali et al. 600/310
 2007/0106335 A1 * 5/2007 Dal Molin et al. 607/36
 2007/0185393 A1 8/2007 Zhou
 2007/0276262 A1 * 11/2007 Banet et al. 600/323
 2008/0238695 A1 10/2008 Yanai
 2008/0249382 A1 10/2008 Oh et al.
 2008/0275317 A1 11/2008 Cho
 2009/0216132 A1 8/2009 Orbach
 2009/0326395 A1 12/2009 Watson
 2010/0056880 A1 * 3/2010 Cho et al. 600/301
 2010/0081946 A1 4/2010 Garudadri et al.
 2010/0160793 A1 6/2010 Lee
 2010/0160798 A1 6/2010 Banet
 2010/0222652 A1 9/2010 Cho
 2010/0241011 A1 9/2010 McCombie et al.
 2011/0112382 A1 5/2011 Li et al.
 2011/0190600 A1 8/2011 McKenna et al.
 2012/0016210 A1 1/2012 Kim
 2012/0071734 A1 3/2012 Shimuta et al.
 2013/0005303 A1 1/2013 Song et al.

OTHER PUBLICATIONS

A h-Shirt-Based Body Sensor Network for Cuffless Calibration and Estimation of Arterial Blood Pressure; W. B. Gu Dept. of Electron. Eng., Chinese Univ. of Hong Kong, Hong Kong, China C. C. Y. Poon ; M. Y. Sy ; H. K. Leung ; Y. P. Liang ; Y. T. Zhang; 2009 Sixth International Workshop on Wearable and Implantable Body Sensor Networks; Jun. 3-5, 2009; Publisher: IEEE; pp. 151-155.
 Is pulse transit time a good indicator of blood pressure changes during short physical exercise in a young population? Jorge Proença, Department of Informatics, Engineering, Science and Technology Faculty of the University of Coimbra, Pólo II, Portugal; Jens Muehlsteff ; Xavier Aubert ; Paulo Carvalho; 2010 Annual International Conference of the IEEE Engineering in Medicine and Biology; Publisher:IEEE; Date of Conference: Aug. 31 2010-Sep. 4, 2010; pp. 598-601.
 (Pearson) correlation coefficient r, 2016, Penn State.
 Chua C., Heneghan C.; Continuous Blood Pressure Monitoring using ECG and Finger Photoplethysmogram; 2006 Proceedings of the 28th IEEE, EMBS Annual International Conference, 5117-5120.
 Seo S.; A Review and Comparison of Methods for Detecting Outliers in Univariate Data Sets 2006; University of Pittsburgh.
 European Patent Application No. 13161973.6, European Search Report dated Jun. 3, 2013, 3 pages.
 European Patent Application No. 13161973.6, European Search Report dated Sep. 18, 2014 3 pages.
 European Patent Application No. 13161973.6, Extended European Search Report dated Jun. 18, 2013, 9 pages.
 European Patent Application No. 13161986.8, Extended European Search Report, dated Jul. 1, 2013, 10 pages.
 European Patent Application No. 13161986.8, European Search Report, dated Sep. 4, 2015, 3 pages.
 European Patent Application No. 13161986.8, European Search Report, dated Nov. 26, 2014, 3 pages.

* cited by examiner




FIG. 1A




FIG. 1B




FIG. 1C




FIG. 2A




FIG. 2B




FIG. 3A




FIG. 3B




FIG. 3C




FIG. 4A




FIG. 4B




FIG. 4C




FIG. 5A




FIG. 5B




FIG. 5C






FIG. 6



700

FIG. 7



800

Fig. 8




FIG. 9




FIG. 10




FIG. 11




FIG. 12




FIG. 13

HAND-HELD DEVICE HAVING HEALTH MONITORING CAPABILITIES

BACKGROUND OF THE INVENTION

Modern health monitors are expected to be cheap, reliable and small as possible.

There is a growing need to provide a health monitor that can overcome ambient noises, can operate with low signal to noise ratio and be relatively cheap and compact.

SUMMARY OF THE INVENTION

According to an embodiment of the invention there may be provided a hand-held device that may include (a) a first sensor that may be positioned such as to be contacted by a first hand of a user when the user holds the hand-held device; (b) a second sensor that may be positioned such as to be contacted by a second hand of the user when the user holds the hand-held device. At least one sensor of the first sensor and the second sensor may be a hybrid sensor that comprises an electrode, an illumination element and a light detector. The hand-held device may also include (c) a health monitoring module arranged to process detections signals from the electrodes and from the light detector such as to provide processed signals that are indicative of a state of the user.

The hybrid sensor may include an electrode that defines a light illumination aperture and a light collection aperture. The illumination element may be arranged to direct light towards the user through the light illumination aperture. The light detector may be arranged to detect light from the user that passes through the light collection aperture.

The hybrid sensor may include an electrode that defines a light illumination aperture and multiple light collection apertures. The illumination element may be arranged to direct light towards the user through the light illumination aperture. At least one light detector may be arranged to detect light from the user that passes through the multiple light collection apertures.

The light illumination aperture may be positioned between a pair of light collection apertures.

The at least one light detector may be shielded by an apertured shield.

The hybrid sensor may include multiple illumination elements and multiple light detectors that are spaced apart from each other.

The electrode, the light detector and the illumination element may be proximate to each other. The distance between these elements can be few millimeters, can be smaller than few centimeters, and the like.

The hand-held device may include a third sensor that may be positioned such as to be contacted by the first or second hand of the user when the user holds the hand-held device.

The third sensor may be a hybrid sensor.

The third sensor may be positioned at a first side of the hand-held device while the first and second sensors are positioned at a second side of the hand-held device, the second side may be opposite to the first side.

The third sensor may be positioned such as to be contacted by a thumb of one of the hands of the user while the first and second sensors are positioned such as to be contacted by index fingers of the user.

The hand-held may include a fourth sensor that may be positioned such as to be contacted by the hand of the user that differs from a hand of the user that contacts the third sensor or is the same hand that contacts the third sensor.

The health monitoring module may be arranged to perform a common noise rejection algorithm on detection signals received from electrodes of multiple sensors out of the first, second and third sensors.

The health monitoring module may be arranged to perform the common noise rejection algorithm on detection signals received from electrodes of the first, second and third sensors.

The electrode may include a conductive portion and at least one additional portion.

The additional portion may be nonconductive.

The additional portion may be (for example—at least three times) thicker than the conductive portion. The thickness of the conductive portion can be defined as a thickness of a conductor (such as a conductive plate) that is expected to be contacted by the user.

The health monitoring module may be arranged to process detection signals from the light detector to provide an indication about a blood oxygen saturation level of the user.

The health monitoring module may be arranged to process detection signals from the electrode to provide an indication about an electrical activity of a heart of the user.

The health monitoring module may be arranged to process detection signals from the light detector to provide an indication about an electrical activity of a heart of the user.

The health monitoring module may be arranged to correlate between the detection signals of the light detector and of the electrode to provide an indication about an electrical activity of a heart of the user.

The health monitoring module may be arranged to process the detection signals of the light detector to define a processing window for processing the detection signals of the electrode.

The health monitoring module may be arranged to process the detection signals of the light detector to support the detection of a QRS complex; define an expected timing of a detection of a QRS complex in the detection signals of the electrode; and search for the QRS complex in detection signals of the electrode that are detected in proximity to the expected timing of detection.

The health monitoring module may be arranged to activate the illumination element and the light detector of the hybrid sensor while collecting detection signals from the electrode.

The health monitoring module may be arranged to ignore detection signals from the electrode while measuring a blood oxygen saturation of the user. The blood oxygen saturation can be learnt from a Pulse Plethysmography detected by the health monitoring module.

A method for monitoring a state of a user can be provided. The method may include: (a) receiving detection signals from multiple sensors; wherein the multiple sensors comprise a first sensor that may be positioned such as to be contacted by a first hand of a user when the user holds the hand-held device and a second sensor that may be positioned such as to be contacted by a second hand of the user when the user holds the hand-held device; wherein at least one sensor of the first sensor and the second sensor may be a hybrid sensor that comprises an electrode, an illumination element and a light detector; and (b) processing, by a health monitoring module, the detections signals from at least the electrode and from the light detector such as to provide processed signals that are indicative of a state of the user.

BRIEF DESCRIPTION OF THE DRAWINGS

The subject matter regarded as the invention is particularly pointed out and distinctly claimed in the concluding

portion of the specification. The invention, however, both as to organization and method of operation, together with objects, features, and advantages thereof may best be understood by reference to the following detailed description when read with the accompanying drawings in which:

FIGS. 1A-1C illustrate hand-held devices according to various embodiments of the invention;

FIGS. 2A-2B illustrate hand-held devices according to various embodiments of the invention;

FIGS. 3A-3B illustrate hand-held devices according to various embodiments of the invention;

FIG. 3C illustrates a portion of the hand-held device of any of FIGS. 1A-1C, 2A-2B and 3A-3B, according to an embodiment of the invention;

FIGS. 4A-4C illustrate a hybrid sensor according to various embodiments of the invention;

FIGS. 5A-5C illustrate a hybrid sensor according to various embodiments of the invention;

FIG. 6 is a timing diagram according to an embodiment of the invention;

FIG. 7 illustrates a method according to an embodiment of the invention;

FIG. 8 illustrates a method according to an embodiment of the invention;

FIG. 9 illustrates a PPG signal and a filtered PPG signal using a finite impulse response filter according to an embodiment of the invention;

FIG. 10 illustrates an ECG signal according to an embodiment of the invention;

FIG. 11 illustrates a sequence of detection time for QRS complexes according to an embodiment of the invention;

FIG. 12 illustrates an example of a RR sequence and an estimated RR sequence according to an embodiment of the invention; and

FIG. 13 illustrates an ECG signal and PPG signal according to an embodiment of the invention.

It will be appreciated that for simplicity and clarity of illustration, elements shown in the figures have not necessarily been drawn to scale. For example, the dimensions of some of the elements may be exaggerated relative to other elements for clarity. Further, where considered appropriate, reference numerals may be repeated among the figures to indicate corresponding or analogous elements.

DETAILED DESCRIPTION OF THE DRAWINGS

The subject matter regarded as the invention is particularly pointed out and distinctly claimed in the concluding portion of the specification. The invention, however, both as to organization and method of operation, together with objects, features, and advantages thereof, may best be understood by reference to the following detailed description when read with the accompanying drawings.

In the following detailed description, numerous specific details are set forth in order to provide a thorough understanding of the invention. However, it will be understood by those skilled in the art that the present invention may be practiced without these specific details. In other instances, well-known methods, procedures, and components have not been described in detail so as not to obscure the present invention.

The following abbreviations and terms are used in this specification:

HR	Heart Rate
BE	Backend of a hand-held device. It can be a server which among other tasks runs the algorithm on data which was sent from the hand-held device.

-continued

QRS	A waveform presented in an ECG during ventricular depolarization
RR interval	Distance (time) between sequential QRS complexes - two consecutive R waves
PTT	Pulse Transient Time. Time between the occurrence of the QRS complex and the corresponding PPG pulse.
Tachycardia	A rapid heart rate, especially one above 100 beats per minute in an adult

There is provided a compact, cheap and resilient hand-held device that has health monitoring capabilities. The hand-held device can include one or more sensors that are integrated with a smart phone, a media player, a game console, a communication device, a mobile phone, a palm computer and the like.

The device is hand-held in the sense that it can be held by one or two hands of a user. The user can hold the hand-held device with one hand, the device can be attached to a user or to another user accessory but the user can be requested to hold the hand-held device by one or two hands when performing at least one medical examination.

The shape of the hand-held device can be rectangular (as illustrated in FIGS. 1A-1B, 2A-2B and 3A-3B) but can have other shapes such as an oval shape, elliptical shape, a polygon shape and the like.

The hand-held device can include multiple medical sensors that may include electrodes, optical elements, infra-red elements, chemical sensors and the like. One or more of these sensors can be a hybrid sensor that can include different types of sensing elements such as electrodes and light sensing elements.

FIGS. 1A, 1B, 1C, 2A, 2B, 3A and 3C illustrate various examples of hand-held devices 20 that are contacted by users. The following table illustrates the mapping between fingers and sensors (30, 40, 40', 50, 50' 50") that should be contacted by the user, according to various embodiments of the invention.

FIG.	Second hand 19			
	First hand 18		2nd	2nd
	1st index finger 12	1st thumb 13	index finger 14	thumb 15
1A	40		30	
1B	40	50	30	
1C		30	50	40
2A	40	50	30	60
2B	40	30	50, 50'	
3A	40, 40'	50, 50', 50"	30	60
3B		30	50, 50'	40

FIG. 1A illustrates a hand-held device 20 that is being held by two hands (18 and 19) of a user. The hand-held device 20 may include: (a) a first sensor 40 that is positioned such as to be contacted by a first hand 18 of a user when the user holds the hand-held device 20; (b) a second sensor 30 that is positioned such as to be contacted by a second hand 19 of the user when the user holds the hand-held device; and (c) a health monitoring module 90 arranged to process detections signals from the electrodes and from the light detector such as to provide processed signals that are indicative of a state of the user. The health monitoring module 90 can perform the entire processing, can perform a partial processing and then send (or assist in sending) the partially processed signals to another entity (such as the main processor of the hand held device, a remote processing entity, a medical hub, a hospital etc) to be further processed. The health monitoring module 90 can be dedicated for medical

processing or can be also allocated to other tasks. The health monitoring module **90** can be a general purpose processor or a digital signals processor, it can control the functionality of the hand-held device **20**.

Either one of the first sensor **40** and the second sensor **30** can be placed on (or embedded with) an edge or a surface of the hand-held device **20** so that once the user touches that edge or surface, the user may touch the first sensor **40**.

FIGS. **1A** and **1B** illustrate the first sensor **40** and the second sensor **30** as belonging to a top side of the hand-held device **20** while FIG. **1C** illustrates the first sensor **40** and the second sensor **30** as belonging to a bottom side of the hand-held device **20**.

The first and second sensors **40** and **30** can be located at the same side of the hand-held device **20**, can be positioned at different sides and even opposite sides of the hand-held device **20**. For example, first sensor **40** can be positioned at a top side of the hand-held device **20** while the second sensor **30** can be positioned at a bottom side, a sidewall, a back side or even at the front panel of the hand-held device **20**.

FIG. **1A** also illustrates the hand-held device **20** as including a man machine interface (MMI) element **80**. This MMI element **80** can be a screen, a keyboard, a microphone, a loudspeaker, a touch screen and the like. This MMI element **80** can be much bigger than is being illustrated in FIG. **1A**. It can span across the entire (or almost entire) hand held device **20**. Yet according to another embodiment of the invention one or more sensor is connected to the application processor of the hand held device.

The MMI element **80** can provide to the user instructions to be followed during the medical test. For example, the MMI element can **80** request a user to contact one or more sensors, to limit the movement of the user, to change position or try to clean an electrode if it is detected that a certain electrode does not receive goon enough (too noisy or too weak) signals, and the like. The MMI element **80** can display or otherwise make the user aware of the outcome of the medical evaluation.

At least one sensor out of the first sensor **40** and the second sensor **30** can be a hybrid sensor that may include an electrode, an illumination element and a light detector. Non-limiting examples of a hybrid sensor (denoted **70**) are shown in FIGS. **4A-4C** and **5A-5C**.

According to an embodiment of the invention the hand-held device **20** can include more than two sensors. It can include for example, a third sensor such as third sensor **50** of FIGS. **1B** and **1C**, **2A**, **2b**, **3A** and **3B**.

Yet for another example, the hand-held device **20** can include a fourth sensor, such as fourth sensor **60** of FIGS. **2A**, **3A** and **50'** of FIG. **3B**.

Yet for a further example, the hand-held device **20** can include a fifth sensor, such as fifth sensor **40'** of FIG. **3A**, can include a sixth sensor such as sixth sensor **50'** of FIG. **3A** and can include a seventh sensor such as seventh sensor **50''** of FIG. **3A**.

The number of sensors of the hand-held device can exceed seven.

The sensors can be positioned such that each sensor is touched by a different finger of the user (as illustrated in FIGS. **1A**, **1B**, **1C**, **2A**, **2B**) although multiple sensors can be positioned such as to be touched by the same finger of the user (as illustrated in FIGS. **3A** and **3B**). The number of sensors that can be touched by the same finger can be two, three or more.

FIG. **3C** illustrates a portion of the hand-held device of any of FIGS. **1A-1C**, **2A-2B** and **3A-3B**, according to an embodiment of the invention. FIG. **3A** illustrates that a

sensor (such as second sensor **30**) is coupled to the health processing module **90** via analog circuits such as amplifier **92**, mixed signal circuits such as analog to digital converter (ADC) **94** and memory unit **96**. Electrical detection signals from an electrode of the second sensor **30** are amplified to amplifier **92** to provide amplified detection signals. The amplified detection signals can converted to digital detection signals that can be stored in memory unit **96** and/or processed by health monitoring module **90**.

FIGS. **4A** and **4B** are top and side views of a hybrid sensor **70** according to an embodiment of the invention.

The hybrid sensor **70** includes an electrode **120** that has apertures—light illumination apertures **110(1)-110(K)** and light collection apertures **100(1)-100(N)**. The user, or more specifically a finger of the user that touches the electrode (or is positioned above these apertures) is illuminated by light generated by illumination elements **210(1)-210(K)** and directed through the light illumination apertures **110(1)-110(K)**. Light (scattered and/or reflected) from the finger passes through the light collection apertures **100(1)-100(N)** and is detected by light detectors **200(1)-200(N)**. **N** and **K** are positive integers. **N** may differ from **K** but **N** may be equal **K**.

The electrode **120** is illustrated as including a conductive portion **120(1)** that is supported by another portion **120(2)**.

While FIGS. **4A** and **4C** illustrate a linear array of illumination elements and light detectors it is noted that the light detectors and light detectors can be arranged in other manners—for example, as a rectangular array—as illustrated by the two row array of FIG. **4A**.

It is noted that the illumination elements and the light detectors can be arranged in an interleaved manner (as illustrated in FIGS. **4A**, **4B**, **5A**, **5B**, and **5C**) but can be arranged in other manners.

It is noted that unwanted artifacts and signal noises can be reduced by either one of using electrodes with low impedance, shielding power and signal lines and raising the input impedance of the amplifier.

Light from an illumination element can be collected by one or more light detectors. FIGS. **5A-5C** illustrate a pair of light detectors per a single illumination element but the ratio can differ from 1:2. If there are more than one illumination elements then the number of light detectors associated with a single illumination element can differ from one illumination element to the other or can be equal to each other.

FIGS. **5A-5C** provide a top view, an exploded view and a cross sectional view of a hybrid sensor **70** according to an embodiment of the invention.

The hybrid sensor **70** includes: (a) a conductive portion **310** of an electrode, (b) an additional portion **320** of the electrode, (c) protective shields **331** and **332**, (d) illumination element **350**, (e) light detectors **340** and **360**, and (f) electrical circuit **370**.

The electrical circuit **370** can be a rigid or flexible electrical board that provides electrical connectivity (for power supply, control signals and communications) to the illumination element **350** and to light detectors **340** and **360**. The electrical circuit **370** can be connected to a power supply source and to the health monitoring processor.

The conductive portion of the electrode **310** is positioned above other parts of the hybrid sensor **70**. It has an upper surface **311** that defines a light illumination aperture **313** that is positioned between two light collection apertures **312** and **314**. The upper surface **311** is connected to four supporting legs, each supporting leg is conductive and include a vertical plate **315** and a horizontal plate **316**. The horizontal plate **316** can be connected to the board **371** of the electrical

circuit 370. The electrical circuit 370 can have slits in which each leg can be inserted so that the horizontal plate 316 can be positioned below the board 317 and can be used for assisting in fastening the elements of the hybrid sensor 70 to each other.

The additional portion 320 of the electrode can provide mechanical support to the conductive portion 310 and can define spaces (322, 323 and 324) that are positioned below apertures 312, 313 and 314 and allow light to be directed towards the user (through space 323) and be collected (via spaces 322 and 324).

The additional portion can be made of non-conductive material.

Protective shields 331 and 332, and light detectors 340 and 360 can be placed within spaces 322 and 324 while illumination element 350 can be placed within space 323.

Each one of light detectors 340 and 360 and illumination element 350 can conductors (such as 342, 352 and 362) to provide electrical connectivity with conductors (372, 373 and 374) of the board 371.

The hand-held device 20 can activate one sensor or multiple sensors and can correlate or otherwise use detections signals from one sensor to evaluate detection signals from another sensor. For example, the electrode 310 can provide signals that are characterized by a low signal to noise ratio and thus various waveforms such as the QRS complex can be hard to detect. The light detector 350 can sense light that is indicative of a movement of the blood vessels of the user that corresponds to the QRS complex and this detection can be used for defining a time window in which to search for the QRS complex at the signals of the electrode. The time window is time shifted from the appearance of the QRS complex at the light detector signal due to a known delay between the generation of the RQS complex pulse and appearance of a movement that reflects the QRS complex at the hand of the user.

FIG. 6 is a timing diagram according to an embodiment of the invention. The x-axis represents the passage of time.

The health monitoring module receives and processes signals from an electrodes and from a light detector of a hybrid sensor such as hybrid sensor 70.

The health monitoring module detects that at a first point in time 401 a movement of a blood vessel responsive to a QRS complex occurred—based on processing detection signals from the light detectors. The health monitoring module can then define a first window 501 for searching for electrical signals (from the electrode) that represent the QRS complex. The first window 501 precedes first point in time 401 by a known delay that represents an expected timing relationship between a detection of a QRS complex by the electrode and the detection of a movement representative of a QRS complex by the light detector. The health monitoring module can also define a second window 502 base don the first detection (at time 401) and an estimated heart rate of the user or based upon a second point in time 402 in which another movement representative of a QRS complex is detected.

FIG. 7 is a flow chart of a method 700 according to an embodiment of the invention.

Method 700 for monitoring a state of a user may start by stage 710 of receiving detection signals from multiple sensors; wherein the multiple sensors comprise a first sensor that is positioned such as to be contacted by a first hand of a user when the user holds the hand-held device and a second sensor that is positioned such as to be contacted by a second hand of the user when the user holds the hand-held device; wherein at least one sensor of the first sensor and the

second sensor is a hybrid sensor that comprises an electrode, an illumination element and a light detector.

Stage 710 may be followed by stage 720 of processing, by a health monitoring module, the detections signals from at least the electrode and from the light detector such as to provide processed signals that are indicative of a state of the user.

The hand-held device 20 that executes method 700 can be any of the mentioned above hand-held devices.

For example, stage 710 can include at least one of the following:

1. Receiving detection signals from a hybrid sensor that includes an electrode that defines a light illumination aperture and a light collection aperture; wherein the illumination element is arranged to direct light towards the user through the light illumination aperture; and wherein the light detector is arranged to detect light from the user that passes through the light collection aperture.
2. Receiving detection signals from a hybrid sensor that includes an electrode that defines a light illumination aperture and multiple light collection apertures; wherein the illumination element is arranged to direct light towards the user through the light illumination aperture; and wherein at least one light detector is arranged to detect light from the user that passes through the multiple light collection apertures.
3. Receiving detection signals from a hybrid sensor that includes a light illumination aperture that is positioned between a pair of light collection apertures.
4. Receiving detection signals from a hybrid sensor that includes at least one light detector that is shielded by an apertured shield.
5. Receiving detection signals from a hybrid sensor that includes multiple illumination elements and multiple light detectors that are spaced apart from each other.
6. Receiving detection signals from a hybrid sensor that includes an electrode, a light detector and an illumination element that are proximate to each other.
7. Receiving detection signals from a third sensor that is positioned such as to be contacted by the first or second hand of the user when the user holds the hand-held device. The third sensor can be a hybrid sensor or can differ from a hybrid sensor.
8. Receiving detection signals from a third sensor that is positioned at a first side of the hand-held device while the first and second sensors are positioned at a second side of the hand-held device, the second side is opposite to the first side.
9. Receiving detection signals from a third sensor that is positioned such as to be contacted by a thumb of one of the hands of the user while the first and second sensors are positioned such as to be contacted by index fingers of the user.
10. Receiving detection signals from a fourth sensor that is positioned such as to be contacted by the hand of the user that differs from a hand of the user that contacts the third sensor.
11. Receiving detection signals from a hybrid sensor that includes an electrode that includes a conductive portion and at least one additional portion. The additional portion may be insulating or partially conductive. The additional portion may be thicker (for example—at least three times thicker) than conductive portion.

For example, stage **720** can include at least one of the following:

1. Performing, by the health monitoring module, a common noise rejection algorithm on detection signals received from electrodes of multiple sensors out of the first, second and third sensors.
2. Performing, by the health monitoring module, the common noise rejection algorithm on detection signals received from electrodes of the first, second and third sensors.
3. Processing, by the health monitoring module, detection signals from the light detector to provide an indication about a blood oxygen saturation level of the user.
4. Processing, by the health monitoring module, detection signals from the electrode to provide an indication about an electrical activity of a heart of the user.
5. Processing, by the health monitoring module, detection signals from the light detector to provide an indication about an electrical activity of a heart of the user.
6. Correlating, by the health monitoring module, between the detection signals of the light detector and of the electrode to provide an indication about an electrical activity of a heart of the user.
7. Processing, by the health monitoring module, the detection signals of the light detector to define a processing window for processing the detection signals of the electrode.
8. Processing, by the health monitoring module, the detection signals of the light detector to detect a QRS complex; defining an expected timing of a detection of a QRS complex in the detection signals of the electrode; and searching for the QRS complex in detection signals of the electrode that are detected in proximity to the expected timing of detection.

Method **700** can include stage **730** of controlling the operation of the electrode and of the illumination elements. Stage **730** may include activating the illumination element and the light detector of the hybrid sensor while collecting detection signals from the electrode. Stage **730** may include ignoring detection signals from the electrode while measuring a blood oxygen saturation of the user.

FIG. **8** illustrates method **800** according to an embodiment of the invention.

Method **800** may start by stage **810** of processing, by a health monitoring module, detection signals of a light detector of a hybrid sensor to detect a blood vessel movement representative of a QRS complex. The hybrid sensor includes one or more electrodes, one or more illumination elements and one or more light detectors.

Stage **810** is followed by stage **820** of defining, by the health monitoring module, an expected timing of a detection of a QRS complex in the detection signals of the electrode.

Stage **820** may be followed by stage **830** of searching for the QRS complex in detection signals of the electrode that are detected in proximity to the expected timing of detection.

A non-limiting example of an execution of method **800** can be found in FIG. **6**.

There is provided a method for monitoring heart related parameters. The method may include detecting QRS complexes on ECG signal, detecting pulsing activities on PPG signals, phase matching and at least zero optimization stages out of (a) optimal estimation of HR for Bradycardia and Tachycardia detection, and (b) Optimal estimation of HRV for AFIB detection.

The Detection of QRS complexes on ECG signal may include receiving detection signals from one or more elec-

trodes and then differentiating the detection signals in order to get QRS complex slope data.

The following filter can be used to approximate that derivative (X_n , X_{n+1} and X_{n+2} are samples of the detection signal) $y_n = -x_{n-2} - 2x_{n-1} + 2x_{n+1} + x_{n+2}$.

The resultant signal (Y_n) is compared to a set of adaptive thresholds to make the final decision (together with the noise detection results).

The detection of pulsing activity on PPG signal may include preprocessing and peak detection.

The preprocessing may include filtering the PPG signal (for example using a finite impulse response filter with 128 taps between 0.5 and 4 Hz. The outcome of this filtering is a filtered signal. In FIG. **9** the filtered signal is represented by line **902** and the PPG signal is represented by curves **901**. The filtered signal **902** shows a pulsing activity where each pulse corresponds to a single heartbeat.

The peak detection includes detecting peaks which correspond to each heartbeat. These peaks are identified by testing whether within each N samples the maximum value appears on sample $N/2$. N is adjusted so small maxima are not found.

The dots **903** of filtered signal **902** represent some of these peaks. The number of those peaks within a given minute will give the HR in beat per minute (BPM) units.

Two sources of information (PPG pulse timing and QRS pulse timing) both report on the temporal location of the heart contraction and therefore they can be combined and therefore improve the QRS detection. Two problems have to be overcome in order to combine the sources of information: (A) False positive and miss detection of complexes in both the signals and (B) the relative temporal shift between the two sources of information.

FIG. **10** illustrates an ECG signal **1001**. A first ellipse **1002** shows a false detection of a QRS complex. A second ellipse **1003** shows a missed QRS complex.

In FIG. **10** an ECG trace is shown along with beat by beat heart rate (numbers on the bottom of the figure) which are derived by taking the difference in QRS timing. In cases where a QRS is missed and falsely detected the HR which should be around 90 BPM would shift to 144 or 46. The same is true for the PPG signal where complexes might be falsely detected or missed. In order to match between the two sets of detections these false detections and missed complexes should be removed.

False and negative detections may be removed by fitting a polynomial model (for example—of a third order 3) to the RR sequence.

The RR sequence is generated by taking the difference in time between two consecutive QRS complexes. A missed QRS complex within the sequence will create a large entry whereas a false detection will create a rather small entry into the sequence.

FIG. **11** shows a sequence of detection time for QRS complexes. The top graph **1100** shows the timing of each QRS. The circle **1111** marks a false detection and the magenta asterisk **1112** corresponds to a false detection (the complex was not found).

The bottom graph **1120** shows the RR sequence. It is evident that the false detection (**1111**) leads to a momentary decrease in RR value. The miss detected QRS complex (**1112**) led to a large value in the RR sequence.

Once the RR sequence is estimated the method can perform one or more iterations of:

1. Estimating a polynomial model (order 3) to the current RR sequence.

2. Calculating the estimated RR sequence based on the model—call it Err.
 3. Calculating an error term $e=RR-eRR$. In this error term find large entries (LErr) and small entries (sErr). Essentially the LErr terms correspond to missed QRS complexes which result in a high value of RR. The sErr correspond to false detections. And
 4. Searching for out layers (LErr and sErr). Remove sErr. Store the LErr.
- Stages 1-4 can be repeated until no out layers are found. Relative temporal shift between PPG and ECG R location.

FIG. 12 illustrates an example of a RR sequence **1201** and an estimated RR sequence (eRR) **1202**.

The estimated phase and optimal RR interval can be derived for the remaining sequence of R (after removing LErr and sErr—see above). The optimal RR interval can be

$$RR_{opt} = \underset{RR}{\operatorname{argmax}} \left(\operatorname{abs} \left(\sum e^{\left(\frac{j2\pi R(n)}{RR(n)} \right)} \right) \right), RR = \min RR \dots \max RR$$

Once the optimal RR value is found (RR_{opt}) the angle (or phase) of each R entry can be calculated by:

$$\operatorname{Angle}(n)_{RR} = (2\pi R(n) / RR_{opt})$$

The optimal RR and angle is evaluated or both the QRS complexes and the PPG output.

The two outputs are then compared.

Three ways can be used:

1. Calculating a goodness metric for each measurement, ECG and PPG (usually between 0 to 1) and then combining the two by a weighted sum of the two outputs.
2. Statistical comparison—matching the statistics of $\operatorname{Angle}_{QRS}$ and $\operatorname{Angle}_{PPG}$ by using the Kullback-Leibler divergence.
3. Direct matching—testing the agreement of each entry of one sequence ($\operatorname{Angle}_{PPG}$) with the other ($\operatorname{Angle}_{QRS}$). Assuming the angle (both PPG and QRS) has a normal distribution the overall agreement between $\operatorname{Angle}_{QRS}$ and $\operatorname{Angle}_{PPG}$ is evaluated by:

$$L_{\tau} = \prod_i L_{\tau}(\operatorname{Angle}(i)_{PPG}, N(\mu_{QRS}, \sigma_{QRS}))$$

Where L is the likelihood function between a single sample (of $\operatorname{Angle}_{PPG}$) in this case and the distribution of $\operatorname{Angle}_{QRS}$.

$$L(X, N(\mu, \sigma)) = \frac{1}{\sqrt{2\pi\sigma}} e^{-\left(\frac{X-\mu}{\sigma}\right)^2}$$

FIG. 13 illustrates the ECG signal **1301**, the PPG **1302**, as a function of time. It is evident that every ECG QRS complex matches with a peak in the PPG signal. The distance between a peak of the ECG signal **1301** and an adjacent peak of the PPG signal **1302** that follows it represents the pulse transient time (PTT) **1303**.

There can be provided a non-transitory computer readable medium that can store instructions for executing any of the mentioned above methods or any combination of any two or more stages of any of the mentioned above methods.

While certain features of the invention have been illustrated and described herein, many modifications, substitutions, changes, and equivalents will now occur to those of ordinary skill in the art. It is, therefore, to be understood that the appended claims are intended to cover all such modifications and changes as fall within the true spirit of the invention.

We claim:

1. A mobile phone, comprising:
 - a first sensor that is positioned on a first side of the mobile phone;
 - a second sensor that is positioned on the first side of the mobile phone, the first sensor being positioned proximate a first end of the mobile phone and the second sensor being spaced from the first sensor and positioned proximate a second end of the mobile phone;
 - a third sensor that is positioned on a second side of the mobile phone opposite the first side of the mobile phone, each of the first sensor, the second sensor, and the third sensor comprising an electrode and being configured to simultaneously contact a separate finger of a user, wherein at least one of the first sensor, the second sensor, and the third sensor is a hybrid sensor that further comprises an illumination element and a light detector, wherein for at least one hybrid sensor the electrode defines at least one light illumination aperture and multiple light collection apertures; wherein the illumination element is arranged to direct light towards the user through the at least one light illumination aperture; wherein the light detector is arranged to detect light from the user that passes through the multiple light collection apertures; and wherein the at least one illumination aperture is centrally positioned between a pair of light collection apertures;
 - and a health monitoring module located between the first side and the second side of the mobile phone, the health monitoring module comprising a processor arranged to receive and process detection signals from the first sensor, the second sensor, and the third sensor to provide processed signals that are indicative of at least one of a) electrical activity of a heart of the user and b) blood oxygen saturation level of the user.
2. The mobile phone according to claim 1, wherein for the at least one hybrid sensor the electrode defines multiple light illumination apertures, wherein the light illumination apertures and the light collection apertures are arranged in a linear or rectangular array.
3. The mobile phone according to claim 1, wherein at least one hybrid sensor comprises multiple illumination elements and multiple light detectors that are spaced apart from each other.
4. The mobile phone according to claim 1, wherein for at least one hybrid sensor the electrode, the light detector and the illumination element are proximate to each other.
5. The mobile phone according to claim 1, wherein the third sensor is a hybrid sensor that comprises an illumination element and a light detector.
6. The mobile phone according to claim 5, wherein the third sensor is adapted to be positioned in contact by a thumb of one of the hands of the user while the first and second sensors are positioned to be contacted by index fingers of the user.
7. The mobile phone according to claim 5, further comprising a fourth sensor that is positioned to contact a hand of the user that differs from the hand of the user that contacts the third sensor.

8. The mobile phone according to claim 5, wherein the health monitoring module is arranged to perform a common noise rejection algorithm on detection signals received from electrodes of multiple sensors out of the first, second and third sensors.

9. The mobile phone according to claim 2, wherein for each sensor of the first and second sensors the light illumination aperture is positioned at a middle of a longitudinal axis the sensor and at a middle of a traverse axis of the sensor.

10. The mobile phone according to claim 1, wherein the health monitoring module is arranged to process detection signals from the light detector of each hybrid sensor to provide an indication about an electrical activity of a heart of the user.

11. The mobile phone according to claim 1, wherein the first sensor and the second sensor each include a light detector and wherein the health monitoring module is arranged to correlate between the detection signals of the light detector of the first sensor and of the electrode of the first sensor and to correlate between the detection signals from the electrode of the second sensor and from the light detector of the second sensor to provide an indication about an electrical activity of a heart of the user.

12. The mobile phone according to claim 1, wherein the health monitoring module is arranged to process the detection signals of the light detector of each hybrid sensor to define a processing window for processing the detection signals of the electrode of the hybrid sensor.

13. The mobile phone according to claim 1, wherein the health monitoring module is arranged to process the detection signals of one of the light detectors of least one of the first sensor, the second sensor, and the third sensor to detect a QRS complex; define an unexpected timing of a detection of a QRS complex in the detection signals of at least one of the electrodes of the at least one of the first sensor, the second sensor and the third sensor; and search for the QRS complex in detection signals of the at least one electrode that are detected in proximity to the expected timing of detection.

14. The mobile phone according to claim 1 wherein the health monitoring module is arranged to activate an illumination element and a light detector of each hybrid sensor while collecting detection signals from the electrode.

15. The mobile phone according to claim 14, wherein the health monitoring module is arranged to ignore detection signals from an electrode of each hybrid sensor while measuring blood oxygen saturation of the user.

16. The mobile phone according to claim 1 wherein the first sensor and the second sensor each includes an illumination element and a light detector and wherein the electrode of the first sensor, the illumination element of the first sensor and the light detector of the first sensor and the electrode of the second sensor, the illumination element of the second sensor and the light detector of the second sensor are positioned at the first side of the mobile phone.

17. A mobile phone, comprising:

a first sensor that is positioned on a first side of the mobile phone;

a second sensor that is positioned on the first side of the mobile phone, the first sensor being positioned proximate a first end of the mobile phone and the second sensor being spaced from the first sensor and positioned proximate a second end of the mobile phone;

a third sensor that is positioned on a second side of the mobile phone opposite the first side of the mobile phone, each of the first sensor, the second sensor, and the third sensor comprising an electrode and being

configured to simultaneously contact a separate finger of a user, wherein at least one of the first sensor, the second sensor, and the third sensor is a hybrid sensor that further comprises an illumination element and a light detector, wherein for at least one hybrid sensor the electrode defines at least one light illumination aperture and multiple light collection apertures; wherein the illumination element is arranged to direct light towards the user through the at least one light illumination aperture; wherein the light detector is arranged to detect light from the user that passes through the multiple light collection apertures; and wherein the at least one illumination aperture is centrally positioned between a pair of light collection apertures; and

a health monitoring module located between the first side and the second side of the mobile phone, the health monitoring module comprising a processor arranged to receive and process detection signals from the first sensor, the second sensor, and the third sensor to provide processed signals that are indicative of at least one of a) electrical activity of a heart of the user and b) blood oxygen saturation level of the user;

wherein each hybrid sensor of the at least one of the first sensor, the second sensor, and the third sensor comprises a light illumination aperture and multiple light collection apertures;

wherein the illumination element of each hybrid sensor of the at least one of the first sensor, the second sensor, and the third sensor is arranged to direct light towards the user through the light illumination apertures;

wherein the at least one light detector of each hybrid sensor of the at least one of the first sensor, the second sensor, and the third sensor is arranged to detect light from the user that passes through the multiple light collection apertures;

wherein each light detector of each hybrid sensor of the at least one of the first sensor, the second sensor, and the third sensor is shielded by an apertured shield that spans across the entire light detector; wherein the apertured shield is positioned below the electrode of the hybrid sensor.

18. The mobile phone according to claim 17, wherein the third sensor is a hybrid sensor that comprises an electrode, an illumination element and a light detector.

19. The mobile phone according to claim 17 wherein the first sensor and the second sensors each include an illumination element and a light detector; wherein the electrode of the first sensor, the illumination element of the first sensor and the light detector of the first sensor and the electrode of the second sensor, the illumination element of the second sensor and the light detector of the second sensor are positioned at the first side of the mobile phone.

20. A mobile phone, comprising:

a first sensor that is positioned on a first side of the mobile phone;

a second sensor that is positioned on the first side of the mobile phone, the first sensor being positioned proximate a first end of the mobile phone and the second sensor being spaced from the first sensor and positioned proximate a second end of the mobile phone;

a third sensor that is positioned on a second side of the mobile phone opposite the first side of the mobile phone, each of the first sensor, the second sensor, and the third sensor comprising an electrode and being configured to simultaneously contact a separate finger of a user, wherein at least one of the first sensor, the second sensor, and the third sensor is a hybrid sensor

15

that comprises an illumination element and a light detector, wherein for at least one hybrid sensor the electrode defines at least one light illumination aperture and multiple light collection apertures; wherein the illumination element is arranged to direct light towards the user through the at least one light illumination aperture; wherein the light detector is arranged to detect light from the user that passes through the multiple light collection apertures; and wherein the at least one illumination aperture is centrally positioned between a pair of light collection apertures;

a health monitoring module located between the first side and the second side of the mobile phone, the health monitoring module comprising a processor arranged to receive and process detection signals from the first sensor, the second sensor, and the third sensor to provide processed signals that are indicative of at least one of a) electrical activity of a heart of the user and b) blood oxygen saturation level of the user;

wherein the electrode comprises a conductive portion and at least one additional portion; wherein a light illumination aperture and at least one light collection apertures are in the conductive portion and in the at least one additional portion.

21. The mobile phone according to claim 20, wherein the additional portion is nonconductive.

22. The mobile phone according to claim 20, wherein the additional portion is at least three times thicker than the conductive portion.

23. The mobile phone according to claim 1, wherein the health monitoring module is arranged to process detection signals from the at least one light detector to provide an indication about a blood oxygen saturation level of the user.

24. The mobile phone according to claim 23, wherein the health monitoring module is arranged to process detection signals from an electrode of each hybrid sensor to provide an indication about an electrical activity of a heart of the user.

25. The mobile phone according to claim 20 wherein the first sensor and the second sensors each include an illumination element and a light detector; wherein the electrode of the first sensor, the illumination element of the first sensor and the light detector of the first sensor and the electrode of the second sensor, the illumination element of the second

16

sensor and the light detector of the second sensor are positioned at the first side of the mobile phone.

26. A method for monitoring a state of a user, the method comprising:

detect, using multiple sensors of a mobile phone, detection signals indicative of a state of the user; receiving, by a health monitoring module located between the first side and the second side of the mobile phone, detection signals from multiple sensors of the mobile phone;

wherein the multiple sensors comprise: a first sensor that is positioned on a first side of the mobile phone, a second sensor that is positioned on the first side of the mobile phone, the first sensor being positioned proximate a first end of the mobile phone and the second sensor being spaced from the first sensor and positioned proximate a second end of the mobile phone, a third sensor that is positioned on a second side of the mobile phone opposite the first side of the mobile phone, each of the first sensor, the second sensor, and the third sensor comprising an electrode and being configured to simultaneously contact a separate finger of a user; wherein at least one of the first sensor, the second sensor, and the third sensor is a hybrid sensor that further comprises an illumination element and a light detector, wherein for at least one hybrid sensor the electrode defines at least one light illumination aperture and multiple light collection apertures; wherein the illumination element is arranged to direct light towards the user through the at least one light illumination aperture; wherein the light detector is arranged to detect light from the user that passes through the multiple light collection apertures; and wherein the at least one illumination aperture is centrally positioned between a pair of light collection apertures;

and processing, by the health monitoring module, the detection from the first sensor, the second sensor, and the third sensor to provide processed signals that are indicative of at least one of a) electrical activity of a heart of the user and b) blood oxygen saturation level of the user.

* * * * *

专利名称(译)	具有健康监测能力的手持设备		
公开(公告)号	US9693697	公开(公告)日	2017-07-04
申请号	US13/433608	申请日	2012-03-29
[标]申请(专利权)人(译)	TAL BENNY TAL亚伊尔 普雷斯曼阿萨夫		
申请(专利权)人(译)	TAL, BENNY TAL, 亚伊尔 普雷斯曼, 阿萨夫		
当前申请(专利权)人(译)	TAL, BENNY TAL, 亚伊尔 普雷斯曼, 阿萨夫		
[标]发明人	TAL BENNY TAL YAIR PRESSMAN ASSAF		
发明人	TAL, BENNY TAL, YAIR PRESSMAN, ASSAF		
IPC分类号	A61B5/00 A61B5/0245 A61B5/0452 A61B5/1455 A61B5/024 A61B5/0404		
CPC分类号	A61B5/02427 A61B5/0245 A61B5/0404 A61B5/0452 A61B5/14552 A61B2560/0462 A61B2560/0468 A61B2562/0209 A61B2562/0233 A61B2562/046 A61B2562/166		
代理机构(译)	摩根路易斯律师事务所		
其他公开文献	US20130261414A1		
外部链接	Espacenet USPTO		

摘要(译)

一种方法，计算机可读介质和手持设备，所述手持设备可以包括第一传感器，所述第一传感器被定位成当用户握住所述手持设备时被用户的第一只手接触；第二传感器，其定位成当用户握住手持设备时由用户的第二只手接触；其中，第一传感器和第二传感器中的至少一个传感器是混合传感器，其包括电极，照明元件和光检测器；健康监测模块，用于处理来自电极和光检测器的检测信号，以提供指示用户状态的处理信号。

